
ciscoisesdk Documentation

Release 2.1.2

Nov 11, 2023

CONTENTS

1	The User Guide	3
1.1	Installation	3
1.2	Introduction	4
1.3	Quickstart	7
1.4	User API Doc	21
2	The Development Community	2961
2.1	Contributor Covenant Code of Conduct	2961
2.2	Contributing	2962
2.3	Changelog	2964
3	General Information about the Identity Services Engine Service	2977
3.1	What is Identity Services Engine?	2977
3.2	Identity Services Engine for Developers	2977
	Python Module Index	2979
	Index	2981

Simple, lightweight, scalable Python API wrapper for the Identity Services Engine APIs

Welcome to the docs! `ciscoisesdk` is a *community developed* Pythonic wrapping of the Identity Services Engine APIs (for API versions: 3.1.0, 3.1.1, 3.1_Patch_1 and 3.2_beta). The package represents all of the Cisco Identity Services Engine API interactions via native Python tools. Making working with the Cisco Identity Services Engine APIs in Python a *native* and *natural* experience.

ciscoisesdk helps you get things done faster. We take care of the API semantics, and you can focus on writing your code.

With `ciscoisesdk`, you can easily:

- Interact with the Identity Services Engine APIs in an interactive Python session
- Quickly create code that enables you get something done in Identity Services Engine
- Leverage the API wrapper to cleanly add Identity Services Engine functionality to your project without having to write the boilerplate code for working with the Identity Services Engine APIs

To *dive in* and see how `ciscoisesdk` makes your life better, check out the [Quickstart](#)!

Warning: Version 3.1_Patch_1 is the same as 3.1.1. Future releases will remove version 3.1.1 of ISE.

THE USER GUIDE

1.1 Installation

1.1.1 PIP Install

ciscoisesdk is available via PIP and the [Python Package Index \(PyPI\)](#). To install ciscoisesdk, simply run this command from your terminal of choice:

```
$ pip install ciscoisesdk
```

The ciscoisesdk package is distributed as a *source distribution* (no binaries).

1.1.2 PIP Upgrade

To ensure that you have the latest version, check-for and install upgrades via PIP:

```
$ pip install ciscoisesdk --upgrade
```

1.1.3 Get the Source Code

ciscoisesdk is developed on GitHub. If you like and use this package, please take a few seconds to Star the package on the [CiscoISE/ciscoisesdk](#) GitHub page. Your feedback and contributions are always welcome.

Use the following command to download the source code (GIT repository):

```
$ git clone https://github.com/CiscoISE/ciscoisesdk.git
```

You can then install the package to your environment, with the following command:

```
$ python setup.py install
```

Copyright (c) 2023 Cisco and/or its affiliates.

1.2 Introduction

1.2.1 Work with the Identity Services Engine APIs in Native Python!

Sure, working with the Identity Services Engine APIs is easy (see [api_docs](#)). They are RESTful, naturally structured, require only a simple Access Token for authentication, and the data is elegantly represented in intuitive JSON. What could be easier?

```
import requests

URL = 'https://dcloud-dna-ise-rtp.cisco.com/ers/config/networkdevice'
ACCESS_TOKEN = '<your_access_token>'

filter_query = '<filter_query>'
headers = {'authorization': ACCESS_TOKEN,
           'Content-type': 'application/json;charset=utf-8'}
params_data = { 'filter': filter_query }
response = requests.get(URL, params=params_data, headers=headers)
if response.status_code == 200:
    device_response = response.json
    if device_response.get('SearchResult') and device_response['SearchResult'].get(
↳ 'resources'):
        for device in device_response['SearchResult']['resources']:
            print('{:20s}{}'.format(device['id'], device['name']))
else:
    # Oops something went wrong... Better do something about it.
    print(response.status_code, response.text)
```

Like I said, EASY. However, in use, the code can become rather repetitive...

- You have to setup the environment every time
- You have to remember URLs, request parameters and JSON formats (or reference the docs)
- You have to parse the returned JSON and work with multiple layers of list and dictionary indexes

Enter **ciscoisesdk**, a simple API wrapper that wraps all of the Identity Services Engine API calls and returned JSON objects within native Python objects and methods.

With **ciscoisesdk**, the above Python code can be consolidated to the following:

```
from ciscoisesdk import api

api_ = api.IdentityServicesEngineAPI(username='admin',
                                     password='C1sco12345',
                                     uses_api_gateway=True,
                                     base_url='https://dcloud-dna-ise-rtp.cisco.com',
                                     version='3.2_beta',
                                     verify=True,
                                     debug=False,
                                     uses_csrf_token=False)
# Or even just api_ = api.IdentityServicesEngineAPI(username='admin', password='C1sco12345
↳) as others have those values by default.
try:
    device_response = api_.network_device.get_network_device(filter='name.EQ.Test').
```

(continues on next page)

(continued from previous page)

```

↪response
    if device_response.SearchResult and device_response.SearchResult.resources:
        for device in device_response.SearchResult.resources:
            print('{:20s}{}'.format(device.hostname, device.upTime))
except ApiError as e:
    print(e)

```

ciscoisesdk handles all of this for you:

- Reads your Identity Services Engine credentials from environment variables (IDENTITY_SERVICES_ENGINE_ENCODED_AUTH, IDENTITY_SERVICES_ENGINE_USERNAME, IDENTITY_SERVICES_ENGINE_PASSWORD)
- Reads your Identity Services Engine API version from environment variable IDENTITY_SERVICES_ENGINE_VERSION. Supported versions: 3.1.0, 3.1.1, 3.1_Patch_1 and 3.2_beta. Now with version and base_url, you have more control.
- Controls whether to verify the server's TLS certificate or not according to the verify parameter.
- Reads your Identity Services Engine debug from environment variable IDENTITY_SERVICES_ENGINE_DEBUG. Boolean, it controls whether to log information about Identity Services Engine APIs' request and response process.
- Wraps and represents all Identity Services Engine API calls as a simple hierarchical tree of native-Python methods (with default arguments provided everywhere possible!)
- If your Python IDE supports **auto-completion** (like [PyCharm](#)), you can navigate the available methods and object attributes right within your IDE
- Represents all returned JSON objects as native Python objects - you can access all of the object's attributes using native *dot.syntax*
- **Automatic Rate-Limit Handling** Sending a lot of requests to Identity Services Engine? Don't worry; we have you covered. Identity Services Engine will respond with a rate-limit response, which will automatically be caught and "handled" for you. Your requests and script will automatically be "paused" for the amount of time specified by Identity Services Engine, while we wait for the Identity Services Engine rate-limit timer to cool down. After the cool-down, your request will automatically be retried, and your script will continue to run as normal. Handling all of this requires zero (0) changes to your code - you're welcome.

Just know that if you are sending a lot of requests, your script might take longer to run if your requests are getting rate limited.

- **Automatic CSRF token management** Identity Services Engine will send a get request to fetch the X-CSRF-Token for you before performing a POST/PUT/DELETE operation, and it will update the X-CSRF-Token of that operation with the new token. It will try to be smart about it and not perform the fetch operation if one is already present and valid.

All of this, combined, lets you do powerful things simply:

```

from ciscoisesdk import IdentityServicesEngineAPI
from ciscoisesdk.exceptions import ApiError

api_ = IdentityServicesEngineAPI(username='admin', password='C1sco12345')

# Get allowed protocols
search_result = api_.allowed_protocols.get_all().response.SearchResult
if search_result and search_result.resources:
    for resource in search_result.resources:

```

(continues on next page)

(continued from previous page)

```

    resource_detail = api_.allowed_protocols.get_by_id(resource.id).response.
↳ AllowedProtocols
    print("Id {}\\nName {}\\nallowChap {}\\n".format(resource_detail.id, resource_detail.
↳ name, resource_detail.allowChap))

# Filter network device
device_list_response = api_.network_device.get_all(filter='name.EQ.ISE_EST_Local_Host_19
↳ ')
device_responses = device_list_response.response.SearchResult.resources
device_response = device_responses[0]

# Get network device detail
device_response_detail = api_.network_device.get_by_id(device_response.id).response.
↳ NetworkDevice

# Delete network device
delete_device = api_.network_device.delete_by_id(device_response.id)

# Create network device
try:
    network_device_response = api_.network_device.create(name='ISE_EST_Local_Host_19',
↳ network_device_ip_list=[{"ipaddress": "127.35.0.1", "mask": 32}])
    print("Created, new Location {}".format(network_device_response.headers.Location))
except api_Error as e:
    print(e)

```

Head over to the [Quickstart](#) page to begin working with the **Identity Services Engine APIs in native Python!**

1.2.2 MIT License

ciscoisesdk is currently licensed under the [MIT Open Source License](#), and distributed as a source distribution (no binaries) via [PyPI](#), and the complete [source code](#) is available on GitHub.

1.2.3 ciscoisesdk License

MIT License

Copyright (c) 2021 Cisco and/or its affiliates.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Copyright (c) 2023 Cisco and/or its affiliates.

1.3 Quickstart

Dive in! ...to get started using the ciscoisesdk package:

Make sure that you have:

- ciscoisesdk *installed*
- ciscoisesdk *upgraded to the latest version*

1.3.1 Pass your Identity Services Engine Access Token

To interact with the Identity Services Engine APIs, you must have a **Identity Services Engine Access Token**. A Identity Services Engine Access Token is how the Identity Services Engine APIs validate access and identify the requesting user.

As a **best practice**, you can store your Identity Services Engine ‘credentials’ as an environment variables in your development or production environment.

By default, ciscoisesdk will look for the following environment variables to create new connection objects:

- `IDENTITY_SERVICES_ENGINE_DEBUG` - Tells the SDK whether to log request and response information. Useful for debugging and seeing what is going on under the hood. Defaults to False.
- `IDENTITY_SERVICES_ENGINE_VERSION` - Identity Services Engine API version to use. Defaults to ‘3.2_beta’.
- `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - It takes priority. It is the *username:password* encoded in base 64. For example ‘ZGV2bmV0dXNlcjpaXNjbzEyMyEK’ which decoded is ‘devnetuser:Cisco123!’
- `IDENTITY_SERVICES_ENGINE_USERNAME` - HTTP Basic Auth username.
- `IDENTITY_SERVICES_ENGINE_PASSWORD` - HTTP Basic Auth password.
- `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` - Enables or disables the usage of the API Gateway. Defaults to True.
- `IDENTITY_SERVICES_ENGINE_USES_CSRF_TOKEN` - Enables or disables the usage of X-CSRF-Token. Defaults to False.
- `IDENTITY_SERVICES_ENGINE_BASE_URL` - The base URL to be prefixed to the individual API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is True. Defaults to ‘<https://dcloud-dna-ise-rtp.cisco.com>’.
- `IDENTITY_SERVICES_ENGINE_UI_BASE_URL` - The UI base URL to be prefixed to the individual ISE UI API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_ERS_BASE_URL` - The ERS base URL to be prefixed to the individual ISE ERS API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_MNT_BASE_URL` - The MNT base URL to be prefixed to the individual ISE MNT API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_PX_GRID_BASE_URL` - The `PX_GRID` base URL to be prefixed to the individual ISE `PX_GRID` API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_SINGLE_REQUEST_TIMEOUT` - Timeout (in seconds) for RESTful HTTP requests. Defaults to 60.

- `IDENTITY_SERVICES_ENGINE_WAIT_ON_RATE_LIMIT` - Enables or disables automatic rate-limit handling. Defaults to True.
- `IDENTITY_SERVICES_ENGINE_VERIFY` - Controls whether to verify the server's TLS certificate or not. Defaults to True.

However, you choose to set it, if you have `IDENTITY_SERVICES_ENGINE_VERSION`, `IDENTITY_SERVICES_ENGINE_USERNAME` and `IDENTITY_SERVICES_ENGINE_PASSWORD`, or `IDENTITY_SERVICES_ENGINE_VERSION` and `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` environment variables, you are good to go. `ciscoisesdk` will use them to create your access token when creating new *IdentityServicesEngineAPI* objects.

If you don't want to set your credentials as environment variables, you can manually provide them as parameters when creating a *IdentityServicesEngineAPI* object.

Note: The `ciscoisesdk` assumes that the ERS APIs and OpenAPIs are enabled. If `uses_api_gateway` is True, the `ciscoisesdk` assumes that your ISE API Gateway is enabled as well.

1.3.2 Set credentials as environment variables

There are many places and diverse ways that you can set an environment variable, which can include:

- A setting within your development IDE
- A setting in your container / PaaS service
- A statement in a shell script that configures and launches your app

It can be as simple as setting it in your CLI before running your script...

```
$ IDENTITY_SERVICES_ENGINE_USERNAME=your_username_here
$ IDENTITY_SERVICES_ENGINE_PASSWORD=your_password_here
$ python myscript.py
```

...or putting your credentials in a shell script that you source when your shell starts up or before your run a script:

```
$ cat mycredentials.sh
export IDENTITY_SERVICES_ENGINE_ENCODED_AUTH=your_encoded_auth_here
$ source mycredentials.sh
$ python myscript.py
```

1.3.3 Create a *IdentityServicesEngineAPI* “Connection Object”

To make interacting with the Identity Services Engine APIs as simple and intuitive as possible, all of the APIs have ‘wrapped’ underneath a single interface. To get started, import the *IdentityServicesEngineAPI* class and create an API “connection object”.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI()
```

As discussed above (*Pass your Identity Services Engine Access Token*), `ciscoisesdk` defaults to pulling from environment variables to generate your access token. If you do not have those environment variables set and you try to create a new *IdentityServicesEngineAPI* object without providing them, a *AccessTokenError* will be raised (a *ciscoisesdkException* subclass).

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "ciscoisesdk/api/__init__.py", line 356, in __init__
    raise AccessTokenError(error_message)
AccessTokenError: You need an access token to interact with the Identity Services Engine APIs. Identity Services Engine uses HTTP Basic Auth to create an access token. You must provide the username and password or just the encoded_auth, either by setting each parameter or its environment variable counterpart (IDENTITY_SERVICES_ENGINE_USERNAME, IDENTITY_SERVICES_ENGINE_PASSWORD, IDENTITY_SERVICES_ENGINE_ENCODED_AUTH).
```

If you don't provide a known version and try to create a new *IdentityServicesEngineAPI*, a *VersionError* will be raised.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI(username='devnetuser',
                                   password='Cisco123!',
                                   base_url='https://dcloud-dna-ise-rtp.cisco.com',
                                   version='0.1.12')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "ciscoisesdk/api/__init__.py", line 344, in __init__
    raise VersionError(error_message)
VersionError: Unknown API version, known versions are 3.1.0, 3.1.1, 3.1_Patch_1 and 3.2_beta.
```

Use the arguments to manually provide enough information for the HTTP Basic Auth process, when creating a new *IdentityServicesEngineAPI* connection object.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using encoded_auth, with Identity Services Engine API version 3.2_beta
>>> api = IdentityServicesEngineAPI(encoded_auth='YWRtaW46QzFzY28xMjM0NQo=',
                                   base_url="https://dcloud-dna-ise-rtp.cisco.com",
                                   version='3.2_beta',
                                   uses_api_gateway=True,
                                   uses_csrf_token=True)
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using username, and password, with ISE API version 3.2_beta
>>> api = IdentityServicesEngineAPI(username='admin', password='C1sco12345',
                                   uses_api_gateway=True,
                                   base_url="https://dcloud-dna-ise-rtp.cisco.com",
                                   version='3.2_beta',
                                   uses_csrf_token=True)
```

Use the arguments to provide the URLs required depending on the `uses_api_gateway` value.

Note: If `uses_api_gateway` is `True`, the `ciscoisesdk` assumes that your ISE API Gateway is enabled.

Note: If `uses_csrf_token` is `True`, the `ciscoisesdk` assumes that your ISE CSRF Check is enabled. Furthermore, it

assumes you need the `ciscoisdk` to manage the CSRF token automatically for you.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using API Gateway (since it was enabled on ISE)
>>> # Using CSRF Token (since the CSRF Check was enabled on ISE)
>>> api = IdentityServicesEngineAPI(username='admin',
...                                password='Cisco12345',
...                                uses_api_gateway=True,
...                                uses_csrf_token=True,
...                                base_url='https://dcloud-dna-ise-rtp.cisco.com',
...                                version='3.2_beta',
...                                verify=True)
>>> # Not using API Gateway
>>> # Not using CSRF Token
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!',
...                                uses_api_gateway=False,
...                                uses_csrf_token=False,
...                                ers_base_url="https://dcloud-dna-ise-rtp.cisco.
↳ com:9060",
...                                ui_base_url="https://dcloud-dna-ise-rtp.cisco.com:443
↳ ",
...                                mnt_base_url="https://dcloud-dna-ise-rtp.cisco.
↳ com:443",
...                                px_grid_base_url="https://dcloud-dna-ise-rtp.cisco.
↳ com:8910",
...                                version='3.2_beta')
```

Note that this can be very useful if you are reading authentication credentials from a file or database and/or when you want to create more than one connection object.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> kingston_auth = 'ZG5hY2VudGVydXNlcjpdDaXNjbzEyMyEK'
>>> london_auth = ('london', 'rcx0cf43!')
>>> kingston_api = IdentityServicesEngineAPI(encoded_auth=kingston_auth, base_url=
↳ "https://dcloud-dna-ise-rtp.cisco.com", version='3.2_beta')
>>> london_api = IdentityServicesEngineAPI(*london_auth, base_url="https://128.107.71.
↳ 199:443",
...                                     version='3.2_beta', uses_api_gateway=True) #_
↳ * Unpacks tuple
```

1.3.4 CSRF Token Check

If `uses_csrf_token` is `True`, the `ciscoisesdk` assumes that your ISE CSRF Check is enabled. Furthermore, it presumes you need the `ciscoisesdk` to manage the CSRF token **automatically** for you.

If `uses_csrf_token` is False, the `ciscoisesdk` assumes that your ISE CSRF Check is disabled. Additionally, it supposes you do not need the `ciscoisesdk` to send CSRF token for POST/PUT/DELETE operations. In this case, you could still do it manually like in the following code fragment:

```
>>> endpoint_id_to_delete = "be46f4f0-932f-11ec-aa4c-8e0da8a23ad8"
>>> get_request = api.endpoint.get_version(headers={"X-CSRF-Token": "fetch"})
```

(continues on next page)

(continued from previous page)

```
>>> r2 = api.endpoint.delete_by_id(id=endpoint_id_to_delete,
...                               headers={"X-CSRF-Token": get_request.headers["X-CSRF-
↳Token"]})
```

1.3.5 API Gateway

If `uses_api_gateway` is `True`, the `ciscoisesdk` assumes that the API Gateway is enabled.

If `uses_api_gateway` is `True` you only need to set your `base_url`.

If `uses_api_gateway` is `False` you need to set the `ers_base_url`, `ui_base_url`, `mnt_base_url` and `px_grid_base_url`.

Warning:

1. Ensure that you have enabled the ERS APIs and OpenAPIs.
2. Make sure to check the ISE settings for the API Gateway, and set the `uses_api_gateway` accordingly.

If you don't provide the URLs necessary and try to create a new `IdentityServicesEngineAPI`, a `TypeError` will be raised.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # it uses Identity Services Engine username and password, with ISE API version 3.2_
↳beta
>>> # The base_url used by default is `from ciscoisesdk.config import DEFAULT_BASE_URL`
>>> api = IdentityServicesEngineAPI(username='admin',
...                               password='Cisco12345',
...                               uses_api_gateway=True,
...                               base_url=None,
...                               version='3.2_beta',
...                               verify=True)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    api = IdentityServicesEngineAPI(username='admin',
  File "ciscoisesdk/api/__init__.py", line 336, in __init__
  File "ciscoisesdk/utils.py", line 165, in check_type
TypeError: We were expecting to receive an instance of one of the following types:
'basestring'; but instead we received None which is a 'NoneType'.
```

```
>>> # Other way to create IdentityServicesEngineAPI connection object; if it does not_
↳use the API Gateway
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!',
...                               uses_api_gateway=False,
...                               ers_base_url="https://dcloud-dna-ise-rtp.cisco.
↳com:9060",
...                               ui_base_url="https://dcloud-dna-ise-rtp.cisco.com:443
↳",
...                               mnt_base_url="https://dcloud-dna-ise-rtp.cisco.
↳com:443",
...                               # px_grid_base_url="https://dcloud-dna-ise-rtp.cisco.
```

(continues on next page)

(continued from previous page)

```

↪com:8910",
...
version='3.2_beta')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    api = IdentityServicesEngineAPI(username='admin',
  File "ciscoisesdk/api/__init__.py", line 341, in __init__
  File "ciscoisesdk/utils.py", line 165, in check_type
TypeError: We were expecting to receive an instance of one of the following types:
'basestring'; but instead we received None which is a 'NoneType'.

```

1.3.6 Certificates

Besides username, password, encoded_auth, base_url, and version, there are other parameters when creating the *IdentityServicesEngineAPI*, many of them have a default value (check *Package Constants* for more).

When dealing with certificates, the most important one is the `verify` parameter.

To avoid getting errors like the following:

```

>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> own_api = IdentityServicesEngineAPI(encoded_auth='dXN1cm5hbWU6cGFzc3dvcmQK',
... base_url="https://128.107.71.199:443", version='3.2_beta', uses_api_gateway=True)
requests.exceptions.SLError: HTTPConnectionPool(host='128.107.71.199', port=443):
Max retries exceeded with url: /dna/system/api/v1/auth/token (Caused by
SSLError (SSLCertVerificationError(1, '[SSL: CERTIFICATE_VERIFY_FAILED] certificate
verify failed: self signed certificate in certificate chain (_ssl.c:1076)'))))
>>>

```

Include the `verify` parameter and set it to `False`:

```

>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> own_api = IdentityServicesEngineAPI(encoded_auth='dXN1cm5hbWU6cGFzc3dvcmQK',
... base_url="https://128.107.71.199:443", version='1.3.0',
... verify=False)
InsecureRequestWarning: Unverified HTTPS request is being made. Adding certificate
verification is strongly advised. See: https://urllib3.readthedocs.io/en/latest/
↪advanced-usage.html#ssl-warnings
InsecureRequestWarning)
>>>

```

You will see `urllib3` warnings instead. If you want to disable them, the easiest way is with:

```

>>> import urllib3
>>> urllib3.disable_warnings()

```


1.3.7 Package Constants

The following are the default values pulled from `ciscoisesdk.config` and used when creating the connection object.

DEFAULT_DEBUG = 'False'

`debug` default value.

DEFAULT_VERSION = '3.2_beta'

`version` default value.

DEFAULT_BASE_URL = 'https://dcloud-dna-ise-rtp.cisco.com'

`base_url` default value.

DEFAULT_SINGLE_REQUEST_TIMEOUT = 60

`single_request_timeout` default value. Timeout (in seconds) for the RESTful HTTP requests.

DEFAULT_WAIT_ON_RATE_LIMIT = True

`wait_on_rate_limit` default value. Enables or disables automatic rate-limit handling.

DEFAULT_VERIFY = True

`verify` default value. Controls whether to verify the server's TLS certificate or not.

DEFAULT_USES_API_GATEWAY = True

`uses_api_gateway` default value. Controls whether ISE use the gateway or not.

DEFAULT_USES_CSRF_TOKEN = False

`uses_csrf_token` default value. Controls wheter we send the X-CSRF-Token to ISE' ERS APIs.

1.3.8 Making API Calls

Now that you have created a `IdentityServicesEngineAPI` “connection object,” you are ready to start making API calls.

```
>>> api.network_device.get_all(page=1,size=3).response.SearchResult.resources
[{'id': '4969bc30-ad2a-11eb-95af-f263cf05f605',
  'name': 'ISE_EST_Local_Host_19',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/4969bc30-ad2a-11eb-95af-
↪f263cf05f605',
  'type': 'application/json'}},
{'id': 'a56f6360-a9fe-11eb-95af-f263cf05f605',
  'name': 'ISE_EST_Local_Host_92348',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/a56f6360-a9fe-11eb-95af-
↪f263cf05f605',
  'type': 'application/json'}},
{'id': '2ea03580-aa02-11eb-95af-f263cf05f605',
  'name': 'Test_Device_4',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/2ea03580-aa02-11eb-95af-
```

(continues on next page)

(continued from previous page)

```
↪ f263cf05f605',
  'type': 'application/json']}]
```

It really is that easy.

All of the calls have been wrapped and represented as native Python method calls, like `IdentityServicesEngineAPI.network_device.get_all()` which gets the network devices summaries for the Cisco ISE ERS - see the [Network Device - Get All](#) API endpoint documentation.

As you can see, we have represented the API endpoints using simple terms that are aligned with the API docs; for example, representing the `/ers/config/networkdevice` API endpoint as a `network_device.get_network_device()` method available underneath the `IdentityServicesEngineAPI` connection object.

A full list of the available API methods, with their descriptions and parameters, is available in the [User API Doc](#).

A summary of the structure is available for each version supported

- [v3.1.0](#)
- [v3.1.1](#)
- [v3.1_Patch_1](#)
- [v3.2_beta](#)

You can easily access and call any of these methods directly from your `IdentityServicesEngineAPI` connection object:

```
>>> api.network_access_policy_set.get_all().response.response
[{'default': False,
  'id': 'f22b6a01-759b-47e2-99ea-2e062abdb6ed',
  'name': 'Test Policy Set 1',
  'description': 'Test Policy Set',
  'hitCounts': 0,
  'rank': 0,
  'state': 'enabled',
  'condition': {'link': None,
  'conditionType': 'ConditionReference',
  'isNegate': False,
  'name': 'My New Condition',
  'id': '92bba708-1df6-4f03-9d40-d28b4cb2d982',
  'description': 'New optional Description'},
  'serviceName': 'Default Network Access',
  'isProxy': False,
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/api/v1/policy/network-access/policy-set/f22b6a01-759b-
↪ 47e2-99ea-2e062abdb6ed',
  'type': 'application/json'}]}
```

1.3.9 Catching Exceptions

If something should go wrong with the API call, an exception will be raised. `ApiError` exceptions are raised when an error condition is returned from the Identity Services Engine cloud. Details will be provided in the error message.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI, ApiError
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!')
>>> # The uses_api_gateway is True by default and the base_url used by default is `from_
↳ ciscoisesdk.config import DEFAULT_BASE_URL`
>>> network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
-----
ApiError                                Traceback (most recent call last)
<ipython-input-71-afadb5c98c43> in <module>
----> 1 network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
      2
ciscoisesdk/misc.py in check_response_code(response, expected_response_code)
      63         raise RateLimitError(response)
      64     else:
--> 65         raise ApiError(response)
      66
ApiError: [400] - The request was invalid or cannot be otherwise served.
{
  "ERSResponse" : {
    "operation" : "POST-create-networkdevice",
    "messages" : [ {
      "title" : "Network Device Create failed: Device Name Already Exist",
      "type" : "ERROR",
      "code" : "Application resource validation exception"
    } ],
    "link" : {
      "rel" : "related",
      "href" : "https://198.18.133.27/ers/config/networkdevice",
      "type" : "application/xml"
    }
  }
}
```

You can catch any errors returned by the Identity Services Engine cloud by catching `ApiError` exceptions in a try-except block.

```
>>> from ciscoisesdk.exceptions import ApiError
>>> try:
...     network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
... except ApiError as e:
...     print(e)
ApiError: [400] - The request was invalid or cannot be otherwise served.
{
  "ERSResponse" : {
    "operation" : "POST-create-networkdevice",
    "messages" : [ {
```

(continues on next page)

(continued from previous page)

```

        "title" : "Network Device Create failed: Device Name Already Exist",
        "type" : "ERROR",
        "code" : "Application resource validation exception"
    } ],
    "link" : {
        "rel" : "related",
        "href" : "https://198.18.133.27/ers/config/networkdevice",
        "type" : "application/xml"
    }
}
}
>>>

```

ciscoisesdk will also raise a number of other standard errors (`TypeError`, `ValueError`, etc.); however, these errors are usually caused by incorrect use of the package or methods and should be sorted while debugging your app.

1.3.10 Working with Returned Objects

The Identity Services Engine cloud returns data objects in JSON format, like so:

```

[
  {
    "default": false,
    "id": "f22b6a01-759b-47e2-99ea-2e062abdb6ed",
    "name": "Test Policy Set 1",
    "description": "Test Policy Set",
    "hitCounts": 0,
    "rank": 0,
    "state": "enabled",
    "condition": {
      "link": null,
      "conditionType": "ConditionReference",
      "isNegate": false,
      "name": "My New Condition",
      "id": "92bba708-1df6-4f03-9d40-d28b4cb2d982",
      "description": "New optional Description"
    },
    "serviceName": "Default Network Access",
    "isProxy": false,
    "link": {
      "rel": "self",
      "href": "https://198.18.133.27/api/v1/policy/network-access/policy-set/f22b6a01-
↪759b-47e2-99ea-2e062abdb6ed",
      "type": "application/json"
    }
  }
]

```

Sure, JSON data objects can easily be parsed and represented in Python using dictionaries, but when working with an ‘object’ wouldn’t it be nice to be able to work with it like an object - using native object syntax (like accessing attributes using ‘.’ notation)? ciscoisesdk enables you to do just that:

```
>>> policy_set = api.network_access_policy_set.get_all().response.response
>>> policy_set[0].id
'f22b6a01-759b-47e2-99ea-2e062abdb6ed'
>>> policy_set[0].condition.conditionType
'ConditionReference'
>>> policy_set[0].condition.name
'My New Condition'
```

Representing and treating Identity Services Engine data objects as Python data objects, can really help clean up your code and make coding easier:

1. You don't need to create variables to hold all the data attributes, just use the attributes available underneath the data object.

```
>>> # Do this
>>> device_list_response = api.network_device.get_all(filter='name.EQ.ISE_EST_Local_
↳Host_19')
>>> device_response = device_list_response.response.SearchResult.resources[0]
>>> device_response_detail = api.network_device.get_by_id(device_response.id).
↳response.NetworkDevice

>>> # or even this
>>> filter_query = 'name.EQ.ISE_EST_Local_Host_19'
>>> device_response_id = api.network_device.get_all(filter=filter_query).response.
↳SearchResult.resources[0].id
>>> device_response_detail = api.network_device.get_by_id(device_response_id).
↳response.NetworkDevice
```

2. When accessing 'optional' attributes, like `device_list_response.response.SearchResult.resources[0].id` attribute of Identity Services Engine NetworkDevice object, the response object will return None when the attribute is not present and will return the attribute's value when it is present. This avoids some boiler plate code and/or needless exception handling, when working with optional attributes.

```
>>> devices_response = api.network_device.get_all().response
>>> # Instead of doing this
>>> if hasattr(devices_response, 'SearchResult') and hasattr(devices_response.
↳SearchResult, 'resources'):
...     devices = devices_response.SearchResult.resources
...     for d in devices:
...         if hasattr(d, 'id') and hasattr(d, 'description'):
...             # Do something with the configList attribute
...             print(d.id, d.description)
>>> # Or this
... try:
...     devices = devices_response.SearchResult.resources
... except AttributeError as e:
...     pass
... for d in devices:
...     # Do something with the configList attribute
...     print(d.id, d.description)
... except AttributeError as e:
...     pass
>>> # You can do this, which is cleaner
>>> if devices_response.SearchResult and devices_response.SearchResult.resources:
```

(continues on next page)

(continued from previous page)

```

...     for d in devices_response.SearchResult.resources:
...         if d.id and d.description:
...             # Do something with the configList attribute
...             print(d.id, d.description)

```

3. It just feels more *natural*. :-) When iterating through sequences, and working with objects in those sequences (see the next section), working with objects as objects is definitely more Pythonic.

The Zen of Python (PEP 20):

“Beautiful is better than ugly.” “Simple is better than complex.”

The currently modeled *Identity Services Engine Data Object* with its functions, is available [here](#) in the *User API Doc*.

What if Identity Services Engine adds new data attributes?

Attribute access WILL WORK for the newly added attributes (yes, without a package update!). ciscoisesdk is written to automatically take advantage of new attributes and data as they are returned.

1.3.11 Configuring Logging for ciscoisesdk

The main ciscoisesdk logger is ciscoisesdk.

Other loggers are ciscoisesdk.exceptions, ciscoisesdk.restsession and ciscoisesdk.api.custom_caller.

The ciscoisesdk adds only the logging.NullHandler following the [logging recommendations](#) for libraries

So you can add your logging handlers according to your needs.

```

import logging
import warnings
from ciscoisesdk import IdentityServicesEngineAPI

# Another way to disable warnings caused by (verify=False)
warnings.filterwarnings('ignore', message='Unverified HTTPS request')

logger = logging.getLogger('simple_example')
logger.setLevel(logging.DEBUG)
# create console handler and set level to debug
ch = logging.StreamHandler()
# create formatter
formatter = logging.Formatter('%(asctime)s - %(name)s - %(levelname)s - %(message)s')
# add formatter to ch
ch.setFormatter(formatter)
# add ch to logger
logger.addHandler(ch)

ch_ = logging.StreamHandler()
api = IdentityServicesEngineAPI(verify=False, debug=True)
logging.getLogger('ciscoisesdk').addHandler(ch_)

logger.debug('simple message')
api.network_device.get_all().response

```

1.3.12 Adding API call definitions

Custom caller functions help you:

1. Add support for custom API calls.
2. Add support for API calls that are/were not documented when the SDK was released.

```
from ciscoisesdk import api

# Create a IdentityServicesEngineAPI connection object;
# it uses Identity Services Engine sandbox URL, username and password, with Identity_
↳ Services Engine API version 3.2_beta.,
# and requests to verify the server's TLS certificate with verify=True.
api_ = api.IdentityServicesEngineAPI(username="devnetuser",
    password="Cisco123!",
    base_url="https://dcloud-dna-ise-rtp.cisco.com",
    version='3.2_beta',
    verify=True
)

# Add your custom API call to the connection object.
# Define the get_hotspotportal function.
# Call it with:
#     get_hotspotportal(params={'filter': 'name.EQ.Hotspot Guest Portal'})
def get_hotspotportal(params):
    return api_.custom_caller.call_api('GET', '/ers/config/hotspotportal', params)

# Add your custom API call to the connection object.
# Define the delete_hotspotportal_by_id function
# under the custom_caller wrapper.
# Call it with:
#     api_.custom_caller.delete_hotspotportal_by_id('be456g16-14fd-4cac-94b7-ac3b8f9f')
api_.custom_caller.add_api('delete_hotspotportal_by_id',
    lambda _id:
        api_.custom_caller.call_api(
            'DELETE',
            '/ers/config/hotspotportal/{id}',
            path_params={
                'id': _id,
            }
        )
)

# Advance usage example using Custom Caller functions.
def setup_custom():
    """
    Defines the get_hotspotportal_by_id and delete_hotspotportal_by_id functions
    under the custom_caller wrapper, and with help documentation
    in two different ways.

    Check that they have been added with
    'get_hotspotportal_by_id' in dir(api_.custom_caller)
    'delete_hotspotportal_by_id' in dir(api_.custom_caller)
    """
```

(continues on next page)

(continued from previous page)

```

Quickly check that you indeed have them as functions with
type(getattr(api_.custom_caller, 'get_hotspotportal_by_id'))
type(getattr(api_.custom_caller, 'delete_hotspotportal_by_id'))

Check the documentation with
help(api_.custom_caller.get_hotspotportal_by_id)
help(api_.custom_caller.delete_hotspotportal_by_id)

"""

# Alternative 1: Definition with helper function.
def _get_hotspotportal_by_id(_id):
    """Custom hostport portal API call, returns response attribute

    Args:
        _id(str): Hostport portal id.

    Returns:
        RestResponse: REST response with following properties:
            - headers(MyDict): response headers.
            - response(MyDict): response body as a MyDict object. Access the object
→'s properties by using the dot notation
              or the bracket notation.
            - content(bytes): representation of the request's response
            - text(str): representation of the request's response

    """
    return api_.custom_caller.call_api(
        'GET',
        '/ers/config/hotspotportal/{id}',
        path_params={
            'id': _id,
        })

# Finally add the function as an attribute.
api_.custom_caller.add_api('get_hotspotportal_by_id', _get_hotspotportal_by_id)

# Alternative 2: Definition with lambda function.
api_.custom_caller.add_api('delete_hotspotportal_by_id',
    lambda _id:
        api_.custom_caller.call_api(
            'DELETE',
            '/ers/config/hotspotportal/{id}',
            path_params={
                'id': _id,
            })
        )

# Finally add the documentation
api_.custom_caller.delete_hotspotportal_by_id.__doc__ = """
    Custom global credential API call to delete hostport portal

    Args:
        _id(str): Hostport portal id.

```

(continues on next page)

(continued from previous page)

```

Returns:
    RestResponse: REST response with following properties:
        - headers(MyDict): response headers.
        - response(MyDict): response body as a MyDict object. Access the object's
        ↪ properties by using the dot notation
            or the bracket notation.
        - content(bytes): representation of the request's response
        - text(str): representation of the request's response
    """

```

Check out the [Custom Caller](#) documentation to begin using it.

Copyright (c) 2023 Cisco and/or its affiliates.

1.4 User API Doc

1.4.1 IdentityServicesEngineAPI

The *IdentityServicesEngineAPI* class creates “connection objects” for working with the Identity Services Engine APIs and hierarchically organizes the Identity Services Engine APIs and their endpoints underneath these connection objects.

IdentityServicesEngineAPI summary structure

v3.1.0 summary

<i>IdentityServicesEngineAPI</i>	<i>aci_bindings</i>	<i>get_aci_bindings()</i> <i>get_aci</i>
	<i>aci_settings</i>	<i>get_aci_settings()</i> <i>get_ver</i>
	<i>active_directory</i>	<i>create_active_directory()</i>
	<i>admin_user</i>	<i>get_admin_user_by_id()</i> <i>get</i>
	<i>allowed_protocols</i>	<i>create_allowed_protocol()</i>
	<i>anc_endpoint</i>	<i>apply_anc_endpoint()</i> <i>bulk</i>
	<i>anc_policy</i>	<i>bulk_request_for_anc_poli</i>
	<i>authentication</i>	<i>authentication_api()</i>
	<i>authorization_profile</i>	<i>create_authorization_prof</i>
	<i>backup_and_restore</i>	<i>cancel_backup()</i> <i>config_bac</i>
	<i>byod_portal</i>	<i>create_byod_portal()</i> <i>delet</i>
	<i>certificate_profile</i>	<i>create_certificate_profil</i>
	<i>certificate_template</i>	<i>get_certificate_template()</i>
	<i>certificates</i>	<i>bind_csr()</i> <i>delete_csr_by_i</i>
	<i>clear_threats_and_vulnerabilities</i>	<i>clear_threats_and_vulnera</i>
	<i>consumer</i>	<i>access_secret()</i> <i>activate_a</i>
	<i>custom_caller</i>	<i>add_api()</i> <i>call_api()</i>
	<i>device_administration_authentication_rules</i>	<i>create_device_admin_authen</i>
	<i>device_administration_authorization_exception_rules</i>	<i>create_device_admin_local</i>
	<i>device_administration_authorization_global_exception_rules</i>	<i>create_device_admin_polic</i>
	<i>device_administration_authorization_rules</i>	<i>create_device_admin_autho</i>
	<i>device_administration_command_set</i>	<i>get_device_admin_command</i>

	<i>device_administration_conditions</i>	<i>create_device_admin_condi</i>
	<i>device_administration_dictionary_attributes_list</i>	<i>get_device_admin_dictiona</i>
	<i>device_administration_identity_stores</i>	<i>get_device_admin_identity</i>
	<i>device_administration_network_conditions</i>	<i>create_device_admin_netwo</i>
	<i>device_administration_policy_set</i>	<i>create_device_admin_policy</i>
	<i>device_administration_profiles</i>	<i>get_device_admin_profiles</i>
	<i>device_administration_service_names</i>	<i>get_device_admin_service_</i>
	<i>device_administration_time_date_conditions</i>	<i>create_device_admin_time_</i>
	<i>downloadable_acl</i>	<i>create_downloadable_acl()</i>
	<i>egress_matrix_cell</i>	<i>bulk_request_for_egress_m</i>
	<i>endpoint</i>	<i>bulk_request_for_endpoint</i>
	<i>endpoint_certificate</i>	<i>create_endpoint_certificate</i>
	<i>endpoint_identity_group</i>	<i>create_endpoint_group() de</i>
	<i>external_radius_server</i>	<i>create_external_radius_se</i>
	<i>filter_policy</i>	<i>create_filter_policy() del</i>
	<i>guest_location</i>	<i>get_guest_location() get_g</i>
	<i>guest_smtp_notification_configuration</i>	<i>create_guest_smtp_notifica</i>
	<i>guest_ssid</i>	<i>create_guest_ssid() delete</i>
	<i>guest_type</i>	<i>create_guest_type() delete</i>
	<i>guest_user</i>	<i>approve_guest_user_by_id()</i>
	<i>hotspot_portal</i>	<i>create_hotspot_portal() de</i>
	<i>identity_groups</i>	<i>create_identity_group() ge</i>
	<i>identity_sequence</i>	<i>create_identity_sequence()</i>
	<i>internal_user</i>	<i>create_internal_user() del</i>
	<i>ip_to_sgt_mapping</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>ip_to_sgt_mapping_group</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>mdm</i>	<i>get_endpoint_by_mac_addre</i>
	<i>misc</i>	<i>delete_all_sessions() get_</i>
	<i>my_device_portal</i>	<i>create_my_device_portal()</i>
	<i>native_suppliant_profile</i>	<i>delete_native_suppliant_p</i>
	<i>nbar_app</i>	<i>create_nbar_app() delete_n</i>
	<i>network_access_authentication_rules</i>	<i>create_network_access_auth</i>
	<i>network_access_authorization_exception_rules</i>	<i>create_network_access_loc</i>
	<i>network_access_authorization_global_exception_rules</i>	<i>create_network_access_pol</i>
	<i>network_access_authorization_rules</i>	<i>create_network_access_auth</i>
	<i>network_access_conditions</i>	<i>create_network_access_con</i>
	<i>network_access_dictionary</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attribute</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attributes_list</i>	<i>get_network_access_diction</i>
	<i>network_access_identity_stores</i>	<i>get_network_access_identi</i>
	<i>network_access_network_conditions</i>	<i>create_network_access_net</i>
	<i>network_access_policy_set</i>	<i>create_network_access_pol</i>
	<i>network_access_profiles</i>	<i>get_network_access_profil</i>
	<i>network_access_security_groups</i>	<i>get_network_access_securi</i>
	<i>network_access_service_names</i>	<i>get_network_access_servic</i>
	<i>network_access_time_date_conditions</i>	<i>create_network_access_tim</i>
	<i>network_device</i>	<i>bulk_request_for_network_</i>
	<i>network_device_group</i>	<i>create_network_device_gro</i>
	<i>node_deployment</i>	<i>delete_node() get_node_det</i>
	<i>node_details</i>	<i>get_node_detail_by_id() ge</i>

	<i>node_group</i>	<i>create_node_group()</i> <i>delete_node_group()</i>
	<i>pan_ha</i>	<i>disable_pan_ha()</i> <i>enable_pan_ha()</i>
	<i>portal</i>	<i>get_portal_by_id()</i> <i>get_portal_by_name()</i>
	<i>portal_global_setting</i>	<i>get_portal_global_setting()</i>
	<i>portal_theme</i>	<i>create_portal_theme()</i> <i>delete_portal_theme()</i>
	<i>profiler</i>	<i>get_profiles()</i>
	<i>profiler_profile</i>	<i>get_profiler_profile_by_id()</i>
	<i>provider</i>	<i>authorization()</i> <i>register_session_service_node()</i>
	<i>psn_node_details_with_radius_service</i>	<i>get_session_service_node()</i>
	<i>pull_deployment_info</i>	<i>get_deployment_info()</i> <i>get_deployment_status()</i>
	<i>px_grid_node</i>	<i>approve_px_grid_node()</i> <i>delete_px_grid_node()</i>
	<i>px_grid_settings</i>	<i>autoapprove_px_grid_settings()</i>
	<i>radius_failure</i>	<i>get_failures()</i>
	<i>radius_server_sequence</i>	<i>create_radius_server_sequence()</i>
	<i>replication_status</i>	<i>get_node_replication_status()</i>
	<i>repository</i>	<i>create_repository()</i> <i>delete_repository()</i>
	<i>restid_store</i>	<i>create_rest_id_store()</i> <i>delete_rest_id_store()</i>
	<i>security_group_to_virtual_network</i>	<i>bulk_request_for_security_group_to_virtual_network()</i>
	<i>security_groups</i>	<i>bulk_request_for_security_group()</i>
	<i>security_groups_acls</i>	<i>bulk_request_for_security_group_acl()</i>
	<i>self_registered_portal</i>	<i>create_self_registered_portal()</i>
	<i>session_directory</i>	<i>get_session_by_ip_address()</i>
	<i>sg_vn_mapping</i>	<i>bulk_create_sg_vn_mapping()</i>
	<i>sms_provider</i>	<i>get_sms_provider()</i> <i>get_sms_provider_status()</i>
	<i>sponsor_group</i>	<i>create_sponsor_group()</i> <i>delete_sponsor_group()</i>
	<i>sponsor_group_member</i>	<i>get_sponsor_group_member()</i>
	<i>sponsor_portal</i>	<i>create_sponsor_portal()</i> <i>delete_sponsor_portal()</i>
	<i>sponsored_guest_portal</i>	<i>create_sponsored_guest_portal()</i>
	<i>support_bundle_download</i>	<i>download_support_bundle()</i>
	<i>support_bundle_status</i>	<i>get_support_bundle_status()</i>
	<i>support_bundle_trigger_configuration</i>	<i>create_support_bundle_trigger_configuration()</i>
	<i>sxp_connections</i>	<i>bulk_request_for_sxp_connections()</i>
	<i>sxp_local_bindings</i>	<i>bulk_request_for_sxp_local_bindings()</i>
	<i>sxp_vpns</i>	<i>bulk_request_for_sxp_vpns()</i>
	<i>sync_ise_node</i>	<i>sync_node()</i>
	<i>system_certificate</i>	<i>create_system_certificate()</i>
	<i>system_health</i>	<i>get_healths()</i> <i>get_performance()</i>
	<i>tacacs_command_sets</i>	<i>create_tacacs_command_sets()</i>
	<i>tacacs_external_servers</i>	<i>create_tacacs_external_servers()</i>
	<i>tacacs_profile</i>	<i>create_tacacs_profile()</i> <i>delete_tacacs_profile()</i>
	<i>tacacs_server_sequence</i>	<i>create_tacacs_server_sequence()</i>
	<i>tasks</i>	<i>get_task_status()</i> <i>get_task_status_by_id()</i>
	<i>telemetry_information</i>	<i>get_telemetry_info_by_id()</i>
	<i>trust_sec_configuration</i>	<i>get_egress_matrices()</i> <i>get_trust_sec_configuration()</i>
	<i>trust_sec_sxp</i>	<i>get_bindings()</i>
	<i>version_and_patch</i>	<i>get_ise_version_and_patch()</i>
	<i>version_info</i>	<i>get_version_info()</i>
	<i>virtual_network</i>	<i>bulk_create_virtual_network()</i>
	<i>vn_vlan_mapping</i>	<i>bulk_create_vn_vlan_mapping()</i>

v3.1.1 summary

<i>IdentityServicesEngineAPI</i>	<i>aci_bindings</i>	<i>get_aci_bindings()</i> <i>get_aci</i>
	<i>aci_settings</i>	<i>get_aci_settings()</i> <i>get_ver</i>
	<i>active_directory</i>	<i>create_active_directory()</i>
	<i>admin_user</i>	<i>get_admin_user_by_id()</i> <i>get</i>
	<i>allowed_protocols</i>	<i>create_allowed_protocol()</i>
	<i>anc_endpoint</i>	<i>apply_anc_endpoint()</i> <i>bulk</i>
	<i>anc_policy</i>	<i>bulk_request_for_anc_poli</i>
	<i>authentication</i>	<i>authentication_api()</i>
	<i>authorization_profile</i>	<i>create_authorization_prof</i>
	<i>backup_and_restore</i>	<i>cancel_backup()</i> <i>config_bac</i>
	<i>byod_portal</i>	<i>create_byod_portal()</i> <i>delet</i>
	<i>certificate_profile</i>	<i>create_certificate_profil</i>
	<i>certificate_template</i>	<i>get_certificate_template()</i>
	<i>certificates</i>	<i>bind_csr()</i> <i>delete_csr_by_i</i>
	<i>clear_threats_and_vulnerabilities</i>	<i>clear_threats_and_vulnera</i>
	<i>consumer</i>	<i>access_secret()</i> <i>activate_a</i>
	<i>custom_caller</i>	<i>add_api()</i> <i>call_api()</i>
	<i>device_administration_authentication_rules</i>	<i>create_device_admin_authen</i>
	<i>device_administration_authorization_exception_rules</i>	<i>create_device_admin_local</i>
	<i>device_administration_authorization_global_exception_rules</i>	<i>create_device_admin_polic</i>
	<i>device_administration_authorization_rules</i>	<i>create_device_admin_autho</i>
	<i>device_administration_command_set</i>	<i>get_device_admin_command</i>
	<i>device_administration_conditions</i>	<i>create_device_admin_condi</i>
	<i>device_administration_dictionary_attributes_list</i>	<i>get_device_admin_dictiona</i>
	<i>device_administration_identity_stores</i>	<i>get_device_admin_identity</i>
	<i>device_administration_network_conditions</i>	<i>create_device_admin_netwo</i>
	<i>device_administration_policy_set</i>	<i>create_device_admin_polic</i>
	<i>device_administration_profiles</i>	<i>get_device_admin_profiles</i>
	<i>device_administration_service_names</i>	<i>get_device_admin_service_i</i>
	<i>device_administration_time_date_conditions</i>	<i>create_device_admin_time</i>
	<i>downloadable_acl</i>	<i>create_downloadable_acl()</i>
	<i>egress_matrix_cell</i>	<i>bulk_request_for_egress_m</i>
	<i>endpoint</i>	<i>bulk_request_for_endpoint</i>
	<i>endpoint_certificate</i>	<i>create_endpoint_certifica</i>
	<i>endpoint_identity_group</i>	<i>create_endpoint_group()</i> <i>de</i>
	<i>external_radius_server</i>	<i>create_external_radius_se</i>
	<i>filter_policy</i>	<i>create_filter_policy()</i> <i>del</i>
	<i>guest_location</i>	<i>get_guest_location()</i> <i>get_g</i>
	<i>guest_smtp_notification_configuration</i>	<i>create_guest_smtp_notifica</i>
	<i>guest_ssid</i>	<i>create_guest_ssid()</i> <i>delete</i>
	<i>guest_type</i>	<i>create_guest_type()</i> <i>delete</i>
	<i>guest_user</i>	<i>approve_guest_user_by_id()</i>
	<i>hotspot_portal</i>	<i>create_hotspot_portal()</i> <i>de</i>
	<i>identity_groups</i>	<i>create_identity_group()</i> <i>ge</i>
	<i>identity_sequence</i>	<i>create_identity_sequence()</i>
	<i>internal_user</i>	<i>create_internal_user()</i> <i>del</i>
	<i>ip_to_sgt_mapping</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>ip_to_sgt_mapping_group</i>	<i>bulk_request_for_ip_to_sg</i>

	<i>licensing</i>	<i>configure_smart_state()</i> <i>cr</i>
	<i>mdm</i>	<i>get_endpoint_by_mac_address()</i>
	<i>misc</i>	<i>delete_all_sessions()</i> <i>get</i>
	<i>my_device_portal</i>	<i>create_my_device_portal()</i>
	<i>native_suppllicant_profile</i>	<i>delete_native_suppllicant_p</i>
	<i>nbar_app</i>	<i>create_nbar_app()</i> <i>delete_n</i>
	<i>network_access_authentication_rules</i>	<i>create_network_access_auth</i>
	<i>network_access_authorization_exception_rules</i>	<i>create_network_access_loc</i>
	<i>network_access_authorization_global_exception_rules</i>	<i>create_network_access_pol</i>
	<i>network_access_authorization_rules</i>	<i>create_network_access_auth</i>
	<i>network_access_conditions</i>	<i>create_network_access_con</i>
	<i>network_access_dictionary</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attribute</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attributes_list</i>	<i>get_network_access_diction</i>
	<i>network_access_identity_stores</i>	<i>get_network_access_identi</i>
	<i>network_access_network_conditions</i>	<i>create_network_access_net</i>
	<i>network_access_policy_set</i>	<i>create_network_access_pol</i>
	<i>network_access_profiles</i>	<i>get_network_access_profil</i>
	<i>network_access_security_groups</i>	<i>get_network_access_securi</i>
	<i>network_access_service_names</i>	<i>get_network_access_servic</i>
	<i>network_access_time_date_conditions</i>	<i>create_network_access_tim</i>
	<i>network_device</i>	<i>bulk_request_for_network</i>
	<i>network_device_group</i>	<i>create_network_device_gro</i>
	<i>node_deployment</i>	<i>delete_node()</i> <i>get_node_det</i>
	<i>node_details</i>	<i>get_node_detail_by_id()</i> <i>ge</i>
	<i>node_group</i>	<i>add_node()</i> <i>create_node_gro</i>
	<i>node_services</i>	<i>get_interfaces()</i> <i>get_profi</i>
	<i>pan_ha</i>	<i>get_pan_ha_status()</i> <i>update</i>
	<i>patching</i>	<i>install_hotpatch()</i> <i>install</i>
	<i>portal</i>	<i>get_portal_by_id()</i> <i>get_por</i>
	<i>portal_global_setting</i>	<i>get_portal_global_setting</i>
	<i>portal_theme</i>	<i>create_portal_theme()</i> <i>dele</i>
	<i>profiler</i>	<i>get_profiles()</i>
	<i>profiler_profile</i>	<i>get_profiler_profile_by_id</i>
	<i>provider</i>	<i>authorization()</i> <i>register_s</i>
	<i>proxy</i>	<i>get_proxy_connection()</i> <i>upa</i>
	<i>psn_node_details_with_radius_service</i>	<i>get_session_service_node()</i>
	<i>pull_deployment_info</i>	<i>get_deployment_info()</i> <i>get</i>
	<i>px_grid_node</i>	<i>approve_px_grid_node()</i> <i>del</i>
	<i>px_grid_settings</i>	<i>autoapprove_px_grid_settin</i>
	<i>radius_failure</i>	<i>get_failures()</i>
	<i>radius_server_sequence</i>	<i>create_radius_server_sequ</i>
	<i>repository</i>	<i>create_repository()</i> <i>delete</i>
	<i>restid_store</i>	<i>create_rest_id_store()</i> <i>del</i>
	<i>security_group_to_virtual_network</i>	<i>bulk_request_for_security</i>
	<i>security_groups</i>	<i>bulk_request_for_security</i>
	<i>security_groups_acls</i>	<i>bulk_request_for_security</i>
	<i>self_registered_portal</i>	<i>create_self_registered_po</i>
	<i>session_directory</i>	<i>get_session_by_ip_address</i>
	<i>sg_vn_mapping</i>	<i>bulk_create_sg_vn_mapping</i>

	<i>sms_provider</i>	<i>get_sms_provider()</i> <i>get_sms</i>
	<i>sponsor_group</i>	<i>create_sponsor_group()</i> <i>del</i>
	<i>sponsor_group_member</i>	<i>get_sponsor_group_member()</i>
	<i>sponsor_portal</i>	<i>create_sponsor_portal()</i> <i>de</i>
	<i>sponsored_guest_portal</i>	<i>create_sponsored_guest_po</i>
	<i>support_bundle_download</i>	<i>download_support_bundle()</i>
	<i>support_bundle_status</i>	<i>get_support_bundle_status</i>
	<i>support_bundle_trigger_configuration</i>	<i>create_support_bundle()</i> <i>ge</i>
	<i>sxp_connections</i>	<i>bulk_request_for_sxp_conn</i>
	<i>sxp_local_bindings</i>	<i>bulk_request_for_sxp_loca</i>
	<i>sxp_vpns</i>	<i>bulk_request_for_sxp_vpns</i>
	<i>system_certificate</i>	<i>create_system_certificate</i>
	<i>system_health</i>	<i>get_healths()</i> <i>get_performa</i>
	<i>tacacs_command_sets</i>	<i>create_tacacs_command_set</i>
	<i>tacacs_external_servers</i>	<i>create_tacacs_external_se</i>
	<i>tacacs_profile</i>	<i>create_tacacs_profile()</i> <i>de</i>
	<i>tacacs_server_sequence</i>	<i>create_tacacs_server_sequ</i>
	<i>tasks</i>	<i>get_task_status()</i> <i>get_task</i>
	<i>telemetry</i>	<i>get_transport_gateway()</i> <i>up</i>
	<i>telemetry_information</i>	<i>get_telemetry_info_by_id()</i>
	<i>trust_sec_configuration</i>	<i>get_egress_matrices()</i> <i>get</i>
	<i>trust_sec_sxp</i>	<i>get_bindings()</i>
	<i>version_and_patch</i>	<i>get_ise_version_and_patch</i>
	<i>version_info</i>	<i>get_version_info()</i>
	<i>virtual_network</i>	<i>bulk_create_virtual_networ</i>
	<i>vn_vlan_mapping</i>	<i>bulk_create_vn_vlan_mappin</i>

v3.1_Patch_1 summary

<i>IdentityServicesEngineAPI</i>	<i>aci_bindings</i>	<i>get_aci_bindings()</i> <i>get_aci</i>
	<i>aci_settings</i>	<i>get_aci_settings()</i> <i>get_ver</i>
	<i>active_directory</i>	<i>create_active_directory()</i>
	<i>admin_user</i>	<i>get_admin_user_by_id()</i> <i>get</i>
	<i>allowed_protocols</i>	<i>create_allowed_protocol()</i>
	<i>anc_endpoint</i>	<i>apply_anc_endpoint()</i> <i>bulk</i>
	<i>anc_policy</i>	<i>bulk_request_for_anc_poli</i>
	<i>authentication</i>	<i>authentication_api()</i>
	<i>authorization_profile</i>	<i>create_authorization_prof</i>
	<i>backup_and_restore</i>	<i>cancel_backup()</i> <i>config_bac</i>
	<i>byod_portal</i>	<i>create_byod_portal()</i> <i>delet</i>
	<i>certificate_profile</i>	<i>create_certificate_profil</i>
	<i>certificate_template</i>	<i>get_certificate_template()</i>
	<i>certificates</i>	<i>bind_csr()</i> <i>delete_csr_by_i</i>
	<i>clear_threats_and_vulnerabilities</i>	<i>clear_threats_and_vulnera</i>
	<i>consumer</i>	<i>access_secret()</i> <i>activate_a</i>
	<i>custom_caller</i>	<i>add_api()</i> <i>call_api()</i>
	<i>device_administration_authentication_rules</i>	<i>create_device_admin_authen</i>
	<i>device_administration_authorization_exception_rules</i>	<i>create_device_admin_local</i>

	<i>device_administration_authorization_global_exception_rules</i>	<i>create_device_admin_policy</i>
	<i>device_administration_authorization_rules</i>	<i>create_device_admin_autho</i>
	<i>device_administration_command_set</i>	<i>get_device_admin_command_</i>
	<i>device_administration_conditions</i>	<i>create_device_admin_condi</i>
	<i>device_administration_dictionary_attributes_list</i>	<i>get_device_admin_dictiona</i>
	<i>device_administration_identity_stores</i>	<i>get_device_admin_identity</i>
	<i>device_administration_network_conditions</i>	<i>create_device_admin_netwo</i>
	<i>device_administration_policy_set</i>	<i>create_device_admin_polic</i>
	<i>device_administration_profiles</i>	<i>get_device_admin_profiles</i>
	<i>device_administration_service_names</i>	<i>get_device_admin_service_</i>
	<i>device_administration_time_date_conditions</i>	<i>create_device_admin_time_</i>
	<i>downloadable_acl</i>	<i>create_downloadable_acl()</i>
	<i>egress_matrix_cell</i>	<i>bulk_request_for_egress_m</i>
	<i>endpoint</i>	<i>bulk_request_for_endpoint</i>
	<i>endpoint_certificate</i>	<i>create_endpoint_certifica</i>
	<i>endpoint_identity_group</i>	<i>create_endpoint_group() de</i>
	<i>external_radius_server</i>	<i>create_external_radius_se</i>
	<i>filter_policy</i>	<i>create_filter_policy() del</i>
	<i>guest_location</i>	<i>get_guest_location() get_g</i>
	<i>guest_smtp_notification_configuration</i>	<i>create_guest_smtp_notifica</i>
	<i>guest_ssid</i>	<i>create_guest_ssid() delete</i>
	<i>guest_type</i>	<i>create_guest_type() delete</i>
	<i>guest_user</i>	<i>approve_guest_user_by_id()</i>
	<i>hotspot_portal</i>	<i>create_hotspot_portal() de</i>
	<i>identity_groups</i>	<i>create_identity_group() ge</i>
	<i>identity_sequence</i>	<i>create_identity_sequence()</i>
	<i>internal_user</i>	<i>create_internal_user() del</i>
	<i>ip_to_sgt_mapping</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>ip_to_sgt_mapping_group</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>licensing</i>	<i>configure_smart_state() cr</i>
	<i>mdm</i>	<i>get_endpoint_by_mac_addre</i>
	<i>misc</i>	<i>delete_all_sessions() get_</i>
	<i>my_device_portal</i>	<i>create_my_device_portal()</i>
	<i>native_suppliant_profile</i>	<i>delete_native_suppliant_p</i>
	<i>nbar_app</i>	<i>create_nbar_app() delete_n</i>
	<i>network_access_authentication_rules</i>	<i>create_network_access_auti</i>
	<i>network_access_authorization_exception_rules</i>	<i>create_network_access_loc</i>
	<i>network_access_authorization_global_exception_rules</i>	<i>create_network_access_pol</i>
	<i>network_access_authorization_rules</i>	<i>create_network_access_auti</i>
	<i>network_access_conditions</i>	<i>create_network_access_con</i>
	<i>network_access_dictionary</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attribute</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attributes_list</i>	<i>get_network_access_diction</i>
	<i>network_access_identity_stores</i>	<i>get_network_access_identi</i>
	<i>network_access_network_conditions</i>	<i>create_network_access_net</i>
	<i>network_access_policy_set</i>	<i>create_network_access_pol</i>
	<i>network_access_profiles</i>	<i>get_network_access_profil</i>
	<i>network_access_security_groups</i>	<i>get_network_access_securi</i>
	<i>network_access_service_names</i>	<i>get_network_access_servic</i>
	<i>network_access_time_date_conditions</i>	<i>create_network_access_tim</i>

	<i>network_device</i>	<i>bulk_request_for_network_</i>
	<i>network_device_group</i>	<i>create_network_device_gro</i>
	<i>node_deployment</i>	<i>delete_node() get_node_det</i>
	<i>node_details</i>	<i>get_node_detail_by_id() ge</i>
	<i>node_group</i>	<i>add_node() create_node_gro</i>
	<i>node_services</i>	<i>get_interfaces() get_profi</i>
	<i>pan_ha</i>	<i>get_pan_ha_status() update</i>
	<i>patching</i>	<i>install_hotpatch() install</i>
	<i>portal</i>	<i>get_portal_by_id() get_por</i>
	<i>portal_global_setting</i>	<i>get_portal_global_setting</i>
	<i>portal_theme</i>	<i>create_portal_theme() dele</i>
	<i>profiler</i>	<i>get_profiles()</i>
	<i>profiler_profile</i>	<i>get_profiler_profile_by-i</i>
	<i>provider</i>	<i>authorization() register_s</i>
	<i>proxy</i>	<i>get_proxy_connection() upo</i>
	<i>psn_node_details_with_radius_service</i>	<i>get_session_service_node()</i>
	<i>pull_deployment_info</i>	<i>get_deployment_info() get_</i>
	<i>px_grid_node</i>	<i>approve_px_grid_node() del</i>
	<i>px_grid_settings</i>	<i>autoapprove_px_grid_setti</i>
	<i>radius_failure</i>	<i>get_failures()</i>
	<i>radius_server_sequence</i>	<i>create_radius_server_sequ</i>
	<i>repository</i>	<i>create_repository() delete</i>
	<i>restid_store</i>	<i>create_rest_id_store() del</i>
	<i>security_group_to_virtual_network</i>	<i>bulk_request_for_security</i>
	<i>security_groups</i>	<i>bulk_request_for_security</i>
	<i>security_groups_acls</i>	<i>bulk_request_for_security</i>
	<i>self_registered_portal</i>	<i>create_self_registered_por</i>
	<i>session_directory</i>	<i>get_session_by_ip_address</i>
	<i>sg_vn_mapping</i>	<i>bulk_create_sg_vn_mapping</i>
	<i>sms_provider</i>	<i>get_sms_provider() get_sms</i>
	<i>sponsor_group</i>	<i>create_sponsor_group() del</i>
	<i>sponsor_group_member</i>	<i>get_sponsor_group_member()</i>
	<i>sponsor_portal</i>	<i>create_sponsor_portal() de</i>
	<i>sponsored_guest_portal</i>	<i>create_sponsored_guest_por</i>
	<i>support_bundle_download</i>	<i>download_support_bundle()</i>
	<i>support_bundle_status</i>	<i>get_support_bundle_status</i>
	<i>support_bundle_trigger_configuration</i>	<i>create_support_bundle() ge</i>
	<i>sxp_connections</i>	<i>bulk_request_for_sxp_conne</i>
	<i>sxp_local_bindings</i>	<i>bulk_request_for_sxp_loca</i>
	<i>sxp_vpns</i>	<i>bulk_request_for_sxp_vpns</i>
	<i>system_certificate</i>	<i>create_system_certificate</i>
	<i>system_health</i>	<i>get_healths() get_performa</i>
	<i>tacacs_command_sets</i>	<i>create_tacacs_command_set</i>
	<i>tacacs_external_servers</i>	<i>create_tacacs_external_se</i>
	<i>tacacs_profile</i>	<i>create_tacacs_profile() de</i>
	<i>tacacs_server_sequence</i>	<i>create_tacacs_server_sequ</i>
	<i>tasks</i>	<i>get_task_status() get_task</i>
	<i>telemetry</i>	<i>get_transport_gateway() up</i>
	<i>telemetry_information</i>	<i>get_telemetry_info_by_id()</i>
	<i>trust_sec_configuration</i>	<i>get_egress_matrices() get_</i>

	<i>trust_sec_xsp</i>	<i>get_bindings()</i>
	<i>version_and_patch</i>	<i>get_ise_version_and_patch()</i>
	<i>version_info</i>	<i>get_version_info()</i>
	<i>virtual_network</i>	<i>bulk_create_virtual_networks()</i>
	<i>vn_vlan_mapping</i>	<i>bulk_create_vn_vlan_mappings()</i>

v3.2_beta summary

<i>IdentityServicesEngineAPI</i>	<i>aci_bindings</i>	<i>get_aci_bindings()</i> <i>get_aci_bindings_by_id()</i>
	<i>aci_settings</i>	<i>get_aci_settings()</i> <i>get_aci_settings_by_id()</i>
	<i>active_directory</i>	<i>create_active_directory()</i>
	<i>admin_user</i>	<i>get_admin_user_by_id()</i> <i>get_admin_user_by_username()</i>
	<i>allowed_protocols</i>	<i>create_allowed_protocol()</i>
	<i>anc_endpoint</i>	<i>apply_anc_endpoint()</i> <i>bulk_request_for_anc_endpoint()</i>
	<i>anc_policy</i>	<i>bulk_request_for_anc_policy()</i>
	<i>authentication</i>	<i>authentication_api()</i>
	<i>authorization_profile</i>	<i>create_authorization_profile()</i>
	<i>backup_and_restore</i>	<i>cancel_backup()</i> <i>config_backup()</i>
	<i>byod_portal</i>	<i>create_byod_portal()</i> <i>delete_byod_portal()</i>
	<i>certificate_profile</i>	<i>create_certificate_profile()</i>
	<i>certificate_template</i>	<i>get_certificate_template()</i>
	<i>certificates</i>	<i>bind_csr()</i> <i>delete_csr_by_id()</i>
	<i>clear_threats_and_vulnerabilities</i>	<i>clear_threats_and_vulnerabilities()</i>
	<i>configuration</i>	<i>get_configuration()</i> <i>update_configuration()</i>
	<i>consumer</i>	<i>access_secret()</i> <i>activate_consumer()</i>
	<i>custom_caller</i>	<i>add_api()</i> <i>call_api()</i>
	<i>dataconnect_services</i>	<i>get_dataconnect_service()</i>
	<i>device_administration_authentication_rules</i>	<i>create_device_admin_authentication_rules()</i>
	<i>device_administration_authorization_exception_rules</i>	<i>create_device_admin_local_auth_exception_rules()</i>
	<i>device_administration_authorization_global_exception_rules</i>	<i>create_device_admin_policy_exception_rules()</i>
	<i>device_administration_authorization_rules</i>	<i>create_device_admin_authentication_rules()</i>
	<i>device_administration_command_set</i>	<i>get_device_admin_command_set()</i>
	<i>device_administration_conditions</i>	<i>create_device_admin_conditions()</i>
	<i>device_administration_dictionary_attributes_list</i>	<i>get_device_admin_dictionary_attributes_list()</i>
	<i>device_administration_identity_stores</i>	<i>get_device_admin_identity_stores()</i>
	<i>device_administration_network_conditions</i>	<i>create_device_admin_network_conditions()</i>
	<i>device_administration_policy_set</i>	<i>create_device_admin_policy_set()</i>
	<i>device_administration_profiles</i>	<i>get_device_admin_profiles()</i>
	<i>device_administration_service_names</i>	<i>get_device_admin_service_names()</i>
	<i>device_administration_time_date_conditions</i>	<i>create_device_admin_time_date_conditions()</i>
	<i>downloadable_acl</i>	<i>create_downloadable_acl()</i>
	<i>edda</i>	<i>create_connector_config()</i>
	<i>egress_matrix_cell</i>	<i>bulk_request_for_egress_matrix_cell()</i>
	<i>endpoint</i>	<i>bulk_request_for_endpoint()</i>
	<i>endpoint_certificate</i>	<i>create_endpoint_certificate()</i>
	<i>endpoint_identity_group</i>	<i>create_endpoint_group()</i> <i>delete_endpoint_group()</i>
	<i>external_radius_server</i>	<i>create_external_radius_server()</i>
	<i>filter_policy</i>	<i>create_filter_policy()</i> <i>delete_filter_policy()</i>

	<i>guest_location</i>	<i>get_guest_location()</i> <i>get_g</i>
	<i>guest_smtp_notification_configuration</i>	<i>create_guest_smtp_notific</i>
	<i>guest_ssid</i>	<i>create_guest_ssid()</i> <i>delete</i>
	<i>guest_type</i>	<i>create_guest_type()</i> <i>delete</i>
	<i>guest_user</i>	<i>approve_guest_user_by_id()</i>
	<i>hotspot_portal</i>	<i>create_hotspot_portal()</i> <i>de</i>
	<i>identity_groups</i>	<i>create_identity_group()</i> <i>ge</i>
	<i>identity_sequence</i>	<i>create_identity_sequence()</i>
	<i>internal_user</i>	<i>create_internal_user()</i> <i>del</i>
	<i>ip_to_sgt_mapping</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>ip_to_sgt_mapping_group</i>	<i>bulk_request_for_ip_to_sg</i>
	<i>licensing</i>	<i>configure_smart_state()</i> <i>cr</i>
	<i>mdm</i>	<i>get_endpoint_by_mac_addres</i>
	<i>misc</i>	<i>delete_all_sessions()</i> <i>get</i>
	<i>my_device_portal</i>	<i>create_my_device_portal()</i>
	<i>native_suppllicant_profile</i>	<i>delete_native_suppllicant_</i>
	<i>network_access_authentication_rules</i>	<i>create_network_access_auti</i>
	<i>network_access_authorization_exception_rules</i>	<i>create_network_access_loc</i>
	<i>network_access_authorization_global_exception_rules</i>	<i>create_network_access_pol</i>
	<i>network_access_authorization_rules</i>	<i>create_network_access_auti</i>
	<i>network_access_conditions</i>	<i>create_network_access_con</i>
	<i>network_access_dictionary</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attribute</i>	<i>create_network_access_dic</i>
	<i>network_access_dictionary_attributes_list</i>	<i>get_network_access_diction</i>
	<i>network_access_identity_stores</i>	<i>get_network_access_identi</i>
	<i>network_access_network_conditions</i>	<i>create_network_access_net</i>
	<i>network_access_policy_set</i>	<i>create_network_access_pol</i>
	<i>network_access_profiles</i>	<i>get_network_access_profil</i>
	<i>network_access_security_groups</i>	<i>get_network_access_securi</i>
	<i>network_access_service_names</i>	<i>get_network_access_servic</i>
	<i>network_access_time_date_conditions</i>	<i>create_network_access_tim</i>
	<i>network_device</i>	<i>bulk_request_for_network_</i>
	<i>network_device_group</i>	<i>create_network_device_gro</i>
	<i>node_deployment</i>	<i>delete_node()</i> <i>get_node_det</i>
	<i>node_details</i>	<i>get_node_detail_by_id()</i> <i>ge</i>
	<i>node_group</i>	<i>add_node()</i> <i>create_node_gro</i>
	<i>node_services</i>	<i>get_interfaces()</i> <i>get_profi</i>
	<i>pan_ha</i>	<i>get_pan_ha_status()</i> <i>update</i>
	<i>patching</i>	<i>install_hotpatch()</i> <i>install</i>
	<i>portal</i>	<i>get_portal_by_id()</i> <i>get_por</i>
	<i>portal_global_setting</i>	<i>get_portal_global_setting</i>
	<i>portal_theme</i>	<i>create_portal_theme()</i> <i>dele</i>
	<i>profiler</i>	<i>get_profiles()</i>
	<i>profiler_profile</i>	<i>get_profiler_profile_by_i</i>
	<i>provider</i>	<i>authorization()</i> <i>register_s</i>
	<i>proxy</i>	<i>get_proxy_connection()</i> <i>up</i>
	<i>psn_node_details_with_radius_service</i>	<i>get_session_service_node()</i>
	<i>pull_deployment_info</i>	<i>get_deployment_info()</i> <i>get</i>
	<i>px_grid_node</i>	<i>approve_px_grid_node()</i> <i>del</i>
	<i>px_grid_settings</i>	<i>autoapprove_px_grid_settin</i>

	<i>radius_failure</i>	<i>get_failures()</i>
	<i>radius_server_sequence</i>	<i>create_radius_server_sequ</i>
	<i>repository</i>	<i>create_repository()</i> <i>delete</i>
	<i>restid_store</i>	<i>create_rest_id_store()</i> <i>del</i>
	<i>security_group_to_virtual_network</i>	<i>bulk_request_for_security</i>
	<i>security_groups</i>	<i>bulk_request_for_security</i>
	<i>security_groups_acls</i>	<i>bulk_request_for_security</i>
	<i>self_registered_portal</i>	<i>create_self_registered_por</i>
	<i>session_directory</i>	<i>get_session_by_ip_address</i>
	<i>sms_provider</i>	<i>get_sms_provider()</i> <i>get_sms</i>
	<i>sponsor_group</i>	<i>create_sponsor_group()</i> <i>del</i>
	<i>sponsor_group_member</i>	<i>get_sponsor_group_member()</i>
	<i>sponsor_portal</i>	<i>create_sponsor_portal()</i> <i>de</i>
	<i>sponsored_guest_portal</i>	<i>create_sponsored_guest_po</i>
	<i>subscriber</i>	<i>bulk_subscriber_operation</i>
	<i>support_bundle_download</i>	<i>download_support_bundle()</i>
	<i>support_bundle_status</i>	<i>get_support_bundle_status</i>
	<i>support_bundle_trigger_configuration</i>	<i>create_support_bundle()</i> <i>ge</i>
	<i>sxp_connections</i>	<i>bulk_request_for_sxp_conne</i>
	<i>sxp_local_bindings</i>	<i>bulk_request_for_sxp_loca</i>
	<i>sxp_vpns</i>	<i>bulk_request_for_sxp_vpns</i>
	<i>system_certificate</i>	<i>create_system_certificate</i>
	<i>system_health</i>	<i>get_healths()</i> <i>get_performa</i>
	<i>tacacs_command_sets</i>	<i>create_tacacs_command_set</i>
	<i>tacacs_external_servers</i>	<i>create_tacacs_external.se</i>
	<i>tacacs_profile</i>	<i>create_tacacs_profile()</i> <i>de</i>
	<i>tacacs_server_sequence</i>	<i>create_tacacs_server_sequ</i>
	<i>tasks</i>	<i>get_task_status()</i> <i>get_task</i>
	<i>telemetry</i>	<i>get_transport_gateway()</i> <i>up</i>
	<i>telemetry_information</i>	<i>get_telemetry_info_by_id()</i>
	<i>trust_sec_configuration</i>	<i>get_egress_matrices()</i> <i>get</i>
	<i>trust_sec_sxp</i>	<i>get_bindings()</i>
	<i>version_and_patch</i>	<i>get_ise_version_and_patch</i>
	<i>version_info</i>	<i>get_version_info()</i>

IdentityServicesEngineAPI Class

class IdentityServicesEngineAPI

Identity Services Engine API wrapper.

Creates a ‘session’ for all API calls through a created IdentityServicesEngineAPI object. The ‘session’ handles authentication, provides the needed headers, and checks all responses for error conditions.

IdentityServicesEngineAPI wraps all of the individual Identity Services Engine APIs and represents them in a simple hierarchical structure.

```
__init__(username=None, password=None, encoded_auth=None, uses_api_gateway=None,
          base_url=None, ui_base_url=None, ers_base_url=None, mnt_base_url=None,
          px_grid_base_url=None, single_request_timeout=None, wait_on_rate_limit=None, verify=None,
          version=None, debug=None, uses_csrf_token=None, object_factory=<function
          mydict_data_factory>, validator=<class
          'ciscoisesdk.models.schema_validator.SchemaValidator'>, perform_initialize=True)
```

Create a new `IdentityServicesEngineAPI` object. An access token is required to interact with the Identity Services Engine APIs. This package supports two methods for you to pass the authorization token:

1. Provide a `encoded_auth` value (username:password encoded in base 64). *This has priority over the following method*
2. Provide username and password values.

This package supports two methods for you to set those values:

1. Provide the parameter. That is the `encoded_auth` or username and password parameters.
2. If an argument is not supplied, the package checks for its environment variable counterpart. That is the `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH`, `IDENTITY_SERVICES_ENGINE_USERNAME`, `IDENTITY_SERVICES_ENGINE_PASSWORD`.

When not given enough parameters an `AccessTokenError` is raised.

Parameters

- **uses_api_gateway** (*bool*, *basestring*) – Controls whether we use the ISE's API Gateway to make the request. Defaults to the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` (or `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY_STRING`) environment variable or `ciscoisesdk.config.DEFAULT_USES_API_GATEWAY` if the environment variables are not set.
- **base_url** (*basestring*) – The base URL to be prefixed to the individual API endpoint suffixes, used when `uses_api_gateway` is `True`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable or `ciscoisesdk.config.DEFAULT_BASE_URL` if the environment variable is not set.
- **ui_base_url** (*basestring*) – The UI base URL to be prefixed to the individual ISE UI API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **ers_base_url** (*basestring*) – The ERS base URL to be prefixed to the individual ISE ERS API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **mnt_base_url** (*basestring*) – The MNT base URL to be prefixed to the individual ISE MNT API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **px_grid_base_url** (*basestring*) – The PxGrid base URL to be prefixed to the individual ISE PxGrid API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **username** (*basestring*) – HTTP Basic Auth username.
- **password** (*basestring*) – HTTP Basic Auth password.
- **encoded_auth** (*basestring*) – HTTP Basic Auth base64 encoded string.
- **single_request_timeout** (*int*) – Timeout (in seconds) for RESTful HTTP requests. Defaults to the `IDENTITY_SERVICES_ENGINE_SINGLE_REQUEST_TIMEOUT` environment variable or `ciscoisesdk.config.DEFAULT_SINGLE_REQUEST_TIMEOUT` if the environment variable is not set.
- **wait_on_rate_limit** (*bool*) – Enables or disables automatic rate-limit handling. Defaults to the `IDENTITY_SERVICES_ENGINE_WAIT_ON_RATE_LIMIT` environment

variable or `ciscoisesdk.config.DEFAULT_WAIT_ON_RATE_LIMIT` if the environment variable is not set.

- **verify** (*bool*, *basestring*) – Controls whether we verify the server’s TLS certificate, or a string, in which case it must be a path to a CA bundle to use. Defaults to the `IDENTITY_SERVICES_ENGINE_VERIFY` (or `IDENTITY_SERVICES_ENGINE_VERIFY_STRING`) environment variable or `ciscoisesdk.config.DEFAULT_VERIFY` if the environment variables are not set.
- **version** (*basestring*) – Controls which version of `IDENTITY_SERVICES_ENGINE` to use. Defaults to the `IDENTITY_SERVICES_ENGINE_VERSION` environment variable or `ciscoisesdk.config.DEFAULT_VERSION` if the environment variable is not set.
- **debug** (*bool*, *basestring*) – Controls whether to log information about Identity Services Engine APIs’ request and response process. Defaults to the `IDENTITY_SERVICES_ENGINE_DEBUG` environment variable or `False` if the environment variable is not set.
- **uses_csrf_token** (*bool*, *basestring*) – Controls whether we send the CSRF token to ISE’s ERS APIs. Defaults to the `IDENTITY_SERVICES_ENGINE_USES_CSRF_TOKEN` environment variable or `ciscoisesdk.config.DEFAULT_USES_CSRF_TOKEN` if the environment variables are not set.
- **object_factory** (*callable*) – The factory function to use to create Python objects from the returned Identity Services Engine JSON data objects.
- **validator** (*callable*) – The factory class with function `json_schema_validate(model:string)` that returns an object with function `validate(obj:dict)` is used to validate Python objects sent in the request body.
- **perform_initialize** (*bool*) – The flag that, if enabled, initializes now all the related objects to manage information from Identity Services Engine, like the authentication, the sessions (requests library), and the API wrappers (for each ISE API family). Defaults to `True`. You can initialize/reinitialize later with *reinitialize*. The original value will not change.

Returns

A new `IdentityServicesEngineAPI` object.

Return type

IdentityServicesEngineAPI

Raises

- **TypeError** – If the parameter types are incorrect.
- **AccessTokenError** – If an access token is not provided via the `access_token` argument or an environment variable.
- **VersionError** – If the version is not provided via the `version` argument or an environment variable, or it is not a Identity Services Engine API supported version [`‘3.1.0’`, `‘3.1.1’`, `‘3.1_Patch_1’`, `‘3.2_beta’`].

initialize_authentication()

Function used when `perform_initialize` is `True` in class init. Init Authentication wrapper early to use for `basicAuth` requests.

initialize_sessions()

Performs initialization of `“session_ui”`, `“session_ers”`, `“session”`, `“session_mnt”`, `“session_px_grid”` properties. Creating for each one a `RestSession` object that handles the requests.

initialize_api_wrappers()

Initializes the API wrappers according to the defined version.

reinitialize()

Calls all the methods necessary to initialize/reinitialize the IdentityServicesEngineAPI.

property authentication

Utility object that provides authentication method.

property perform_initialize

The flag that, if enabled, initialized in the constructor all the related objects to manage information from Identity Services Engine.

is_password(*password*)

Check if the value of the current password match

is_encoded_auth(*encoded_auth*)

Check if the value of the current encoded_auth match

property session

The Identity Services Engine API session.

property session_ui

The Identity Services Engine UI API session.

property session_ers

The Identity Services Engine ERS API session.

property session_mnt

The Identity Services Engine MNT API session.

property session_px_grid

The Identity Services Engine PxGrid API session.

property username

HTTP Basic Auth username

change_password(*password*)

HTTP Basic Auth password.

It may require to call reinitialize to distribute the changes accross the SDK objects.

change_encoded_auth(*encoded_auth*)

HTTP Basic Auth base64 encoded string.

It may require to call reinitialize to distribute the changes accross the SDK objects.

property uses_api_gateway

If the Identity Services Engine API uses an API Gateway.

property base_url

The base URL prefixed to the individual API endpoint suffixes for ERS and Custom Caller operations.

property ui_base_url

The ui base URL prefixed to the individual API endpoint suffixes for UI operations.

property ers_base_url

The ers base URL prefixed to the individual API endpoint suffixes for ERS operations.

property mnt_base_url

The mnt base URL prefixed to the individual API endpoint suffixes for MNT operations.

property px_grid_base_url

The px_grid base URL prefixed to the individual API endpoint suffixes for PxGrid operations

property single_request_timeout

Timeout (in seconds) for an single HTTP request.

property wait_on_rate_limit

Automatic rate-limit handling enabled / disabled.

property verify

The verify (TLS Certificate) for the API endpoints.

property version

The API version of Identity Services Engine.

property debug

If log information about Identity Services Engine APIs' request and response process is shown.

property uses_csrf_token

If the Identity Services Engine ERS API requires the X-CSRF-Token to be sent.

property object_factory

The factory function to use to create Python objects from the returned Identity Services Engine JSON data objects.

property validator

The function used to validate Python objects sent in the request body.

authentication**class Authentication**

Identity Services Engine Authentication API.

Wraps the Identity Services Engine Authentication API and exposes the API as native Python methods that return native Python objects.

property verify

The verify (TLS Certificate) for the API endpoints.

property base_url

The base URL for the API endpoints.

property single_request_timeout

Timeout in seconds for the API requests.

authentication_api(*username, password, encoded_auth=None*)

Exchange basic auth data for a Authorization Basic encoded value that can be used to invoke the APIs.

Parameters

- **username** (*basestring*) – HTTP Basic Auth username.
- **password** (*basestring*) – HTTP Basic Auth password.
- **encoded_auth** (*basestring*) – HTTP Basic Auth base64 encoded string.

Returns

An AccessToken object with the access token provided by the Identity Services Engine cloud.

Return type

AccessToken

Raises

TypeError – If the parameter types are incorrect.

custom_caller**class CustomCaller**

Identity Services Engine CustomCaller.

Identity Services Engine CustomCaller allows API creation.

add_api(*name, obj*)

Adds an api call to the CustomCaller.

Parameters

- **name** (*str*) – name you want to set to the api client, has to follow python variable naming rule.
- **obj** (*object*) – api call which is actually a calling call_api method.

call_api(*method, resource_path, raise_exception=True, original_response=False, **kwargs*)

Handles the requests and response.

Parameters

- **method** (*basestring*) – type of request.
- **resource_path** (*basestring*) – URL in the request object.
- **raise_exception** (*bool*) – If True, http exceptions will be raised.
- **original_response** (*bool*) – If True, MyDict (JSON response) is returned, else response object.
- **path_params** (*dict*) (*optional*) – Find each path_params' key in the resource_path and replace it with path_params' value.
- **params** (*optional*) – Dictionary or bytes to be sent in the query string for the Request.
- **data** (*optional*) – Dictionary, bytes, or file-like object to send in the body of the Request.
- **json** (*optional*) – json data to send in the body of the Request.
- **headers** (*optional*) – Dictionary of HTTP Headers to send with the Request.
- **cookies** (*optional*) – Dict or CookieJar object to send with the Request.
- **files** (*optional*) – Dictionary of 'name': file-like-objects (or {'name': ('filename', fileobj)}) for multipart encoding upload.
- **auth** (*optional*) – Auth tuple to enable Basic/Digest/Custom HTTP Auth.
- **timeout** (*float, tuple*) (*optional*) – How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **allow_redirects** (*bool*) (*optional*) – bool. Set to True if POST/PUT/DELETE redirect following is allowed.

- **proxies** (*optional*) – Dictionary mapping protocol to the URL of the proxy.
- **verify** (*bool, string*) (*optional*) – if True, the SSL cert will be verified. A CA_BUNDLE path can also be provided as a string.
- **stream** (*optional*) – if False, the response content will be immediately downloaded.
- **cert** (*basestring, tuple*) (*optional*) – if String, path to ssl client cert file (.pem). If Tuple, ('cert', 'key') pair

Returns

If original_response is True returns the original object response, else returns a JSON response with access to the object's properties by using the dot notation or the bracket notation. Defaults to False.

Return type

RestResponse or *object*

Raises

- **TypeError** – If the parameter types are incorrect.
- **HTTPError** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.1.0**aci_bindings****class AciBindings**

Identity Services Engine ACIBindings API (version: 3.1.0).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

The ACI Bindings API allows clients to retrieve bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on the ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip, sgt, vn, psn, learnedFrom, or learnedBy with CONTAINS mode of search.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
ip	String	Yes	Binding IPv4 address. Each binding will be exclusively identified by its IP address and virtual network	10.0.0.1
sgt	String	No	Security Group Tag (SGT) value. The valid range for SGT values is 0-65534	1234
vn	String	Yes	Virtual network. Each binding will be exclusively identified by its IP address and virtual network	vn1234
psn	String	No	Cisco ISE Policy Service node (PSN) IP address	10.86.189.216
learnedFrom	String	Yes	Binding Source	ISE by ACI ACI by ISE
learnedBy	String	Yes	Binding Type	SXP(SXP, 0) STATIC(Static, 1) RADIUS(RADIUS, 2) ACI(ACI, 3)

get_aci_bindings(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.1.0).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

ACI Settings API allows the client to get and update the ACI Settings. In addition, testing the ACI Domain Manager connection is also possible using the TestACIConnection.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		AciSettings
id	String	No	Resource UUID value		29fb45ab-6a8e-4658-8a28-02521c258178
description	String	No			Aci Settings
enableAci	Boolean	Yes	Enable ACI Integration	false	
isAci50	Boolean	Yes	Enable 5.0 ACI Version	false	
ipAddressHost- Name	String	No	ACI Cluster IP Address / Host name		
adminName	String	No	ACI Cluster Admin name		
adminPassword	String	No	ACI Cluster Admin pass- word		
tenantName	String	No	ACI Cluster Tenant name	ISE	
l3RouteNetwork	String	No	ACI Cluster L3 Route net- work name	L3_ROUTE	
suffixToEpg	String	No	Name Conversion - EPG suffix	SGT	
suffixToSgt	String	No	Name Conversion - SGT suffix	EPG	
allSxpDomain	Boolean	No	SXP Propagation to all the SXP domains	false	
specificSxpDo- main	Boolean	No	SXP Propagation to spe- cific SXP domains	true	
specifixSxpDo- mainList	List	No	Specific SXP domains list	[default]	
isAci51	Boolean	Yes	Enable 5.1 ACI Version	false	
aciipaddress	String	No	ACI Domain manager Ip Address		
aciuserName	String	No	ACI Domain manager Username		
acipassword	String	No	ACI Domain manager Password		
enableData- Plane	Boolean	No	Enable data plane	false	
untaggedPack- etIepgName	String	No	Untagged IEPG packets name	untagged	
defaultSgtName	String	No	Default SGT name	Unknown	
enableEle- mentsLimit	Boolean	No	Enable Elements Limit	false	
maxNu- mIepgFromAci	Inte- ger	No	Max number of IEPGs	1000	
maxNumSgt- ToAci	Inte- ger	No	Max number of SGTs	500	

get_aci_settings(headers=None, **query_parameters)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

test_aci_connectivity(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_aci_settings_by_id(id, aci50=None, aci51=None, aciipaddress=None, acipassword=None,
    aciuser_name=None, admin_name=None, admin_password=None,
    all_sxp_domain=None, default_sgt_name=None, enable_aci=None,
    enable_data_plane=None, enable_elements_limit=None,
    ip_address_host_name=None, l3_route_network=None,
    max_num_iepg_from_aci=None, max_num_sgt_to_aci=None,
    specific_sxp_domain=None, specifix_sxp_domain_list=None,
    suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None,
    untagged_packet_iepg_name=None, headers=None, payload=None,
    active_validation=True, **query_parameters)
```

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.
- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint**class AncEndpoint**

Identity Services Engine ANCEndpoint API (version: 3.1.0).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
macAddress	String	Yes	MAC address of the endpoint	00:11:22:33:44:55
policy-Name	String	Yes	Policy name to be applied to the endpoint	policy1

Supported ANC API transactions per second

On a 5 node Cisco ISE deployment with 60k sessions or on a 9 node Cisco ISE deployment with 200k/500k sessions, 250 transactions per second (TPS) is supported for any ANC API.

Supported ANC APIs

* `applyEndpointByMacAddress` * `clearEndpointByMacaddress` * `applyEndpointByIpAddress` * `applyEndpointPolicy` * `clearEndpointPolicy`

Deployment	Number of Sessions	Supported ANC APIs TPS
5 nodes	60k	250
9 nodes	200k	250
5 nodes	500k	250

`get_anc_endpoint_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_anc_endpoint_by_id`

`clear_anc_endpoint(additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to clear the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data (list)** – additionalData, property of the request body (list of objects).
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *apply_anc_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory

class ActiveDirectory

Identity Services Engine ActiveDirectory API (version: 3.1.0).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

The Active Directory API allows the user to carry out add, delete, and search operations on the active directory domains through Cisco ISE's join points. For example, if you want to connect to the domain cisco.com and retrieve the domain groups, you can carry out the following steps which are also available as APIs: Step 1 Create a domain join point in Cisco ISE. In the "domain" parameter use cisco.com.

Step 2 Get all defined join points and copy your join point's ID from the response.

Step 3 Join all Cisco ISE nodes to the domain. Use the ID received in the Step 2 in the URL. From this point onwards, you can perform several actions. In each action you should specify the joint point ID in the URL, as retrieved in step 2 in the previous configuration task. For example, you can:

- Retrieve the user groups using the joint point ID.

- Retrieve the groups of a specific domain using the join point ID. The domain parameter can be cisco.com or any of its trusted domains. You can use the get all trusted domains operation to retrieve the list.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifica- tion	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.4	Support new attributes	advanced- Settings	Added ERSActiveDirectoryAdvancedSettings Attribute 'advancedSettings'
				adAt- tributes	Added ERSActiveDirectoryAt- tributes Attribute 'adAttributes'
				enable- Domain- WhiteList	Added Boolean Attribute 'en- ableDomainWhiteList'
2	1.2	3.1	Support new attributes under ActiveDirectory AdvancedSettings	enable- FailedAuth- Protection	Added Boolean Attribute 'en- ableFailedAuthProtection'
				failedAu- thThresh- old	Added Integer Attribute 'failedAuthThreshold'
				auth Protec- tionType	Added Enum Attribute 'authPro- tectionType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_ characters	...	Company_users
id	String	No	Resource UUID value	...	af1cd190-7d71-11eb-b02e-ead13cf60dcb
description	String	No	No character restriction	...	Group of Active company users
domain	String	Yes	The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed	...	cisco.com
adScopes-Names	String	No	String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed	Default_Scope	...
enableDomain-WhiteList	Boolean	No	...	true	...
adGroups	List	No	Holds list of AD Groups
• groups	List	No	List of Groups

continues on next page

Table 5 – continued from previous page

• name	String	Yes	Required for each group in the group list with no duplication between groups. All characters are allowed except %	...	cisco.com/operators
• sid	String	Yes	Cisco ISE uses security identifiers (SIDs) for optimization of group membership evaluation. SIDs are useful for efficiency (speed) when the groups are evaluated. All characters are allowed except %	...	S-1-5-32-548
• type	String	No	No character restriction	...	GLOBAL
adAttributes	List	No	Holds list of AD Attributes
• attributes	List	No	List of Attributes
• name	String	Yes	Required for each attribute in the attribute list with no duplication between attributes. All characters are allowed except <%”	...	name1
• type	Enum	Yes	Required for each group in the group list. Allowed values: - STRING, - IP, - BOOLEAN, - INT, - OCTET_STRING	STRING	...

continues on next page

Table 5 – continued from previous page

• internal-Name	String	Yes	Required for each attribute in the attribute list. All characters are allowed except <%”	...	internalName1
• default-Value	String	Yes	Required for each attribute in the attribute list. Can contain an empty string. All characters are allowed except <%”	...	defaultString
advancedSettings	List	No
• rewriteRules	List	No	Identity rewrite is an advanced feature that directs Cisco ISE to manipulate the identity before it is passed to the external Active Directory system. You can create rules to change the identity to a desired format that includes or excludes a domain prefix and/or suffix or other additional markup of your choice
• rowId	Integer	Yes	Required for each rule in the list in serial order	...	0
• rewriteMatch	String	Yes	Required for each rule in the list with no duplication between rules. All characters are allowed except %”	...	exampleMatch0

continues on next page

Table 5 – continued from previous page

• rewriteResult	String	Yes	Required for each rule in the list. All characters are allowed except %”	...	exampleResult0
• enableRewrites	Boolean	No	...	false	...
• enablePassChange	Boolean	No	...	true	...
• enableMachineAuth	Boolean	No	...	true	...
• enableMachineAccess	Boolean	No	...	true	...
• enableDialinPermissionCheck	Boolean	No	...	false	...
• plaintextAuth	Boolean	No	...	false	...
• agingTime	Integer	No	Range 1-8760 hours	5	...
• enableCallbackForDialinClient	Boolean	No	...	false	...
• identityNotInAdBehaviour	Enum	No	Allowed values: - REJECT, - SEARCH_JOINED_FOREST, - SEARCH_ALL	SEARCH_JOINED_FOREST	

continues on next page

Table 5 – continued from previous page

• unreachableDomainsBehaviour	Enum	No	Allowed values: - PROCEED, - DROP	PROCEED	...
• schema	Enum	No	Allowed values: - ACTIVE_DIRECTORY, - CUSTOM-Choose ACTIVE_DIRECTORY schema when the AD attributes defined in AD can be copied to relevant attributes in Cisco ISE. If customization is needed, choose CUSTOM schema. All User info attributes are always set to default value if schema is ACTIVE_DIRECTORY. Values can be changed only for CUSTOM schema	ACTIVE_DIRECTORY	...
• firstName	String	No	User info attribute. All characters are allowed except %	givenName	...
• department	String	No	User info attribute. All characters are allowed except %	department	...
• lastName	String	No	User info attribute. All characters are allowed except %	sn	...

continues on next page

Table 5 – continued from previous page

• organiza- tionalU- nit	String	No	User info at- tribute. All characters are allowed except %	company	...
• jobTitle	String	No	User info at- tribute. All characters are allowed except %	title	...
• locality	String	No	User info at- tribute. All characters are allowed except %	l	...
• email	String	No	User info at- tribute. All characters are allowed except %	mail	...
• stateOr- Province	String	No	User info at- tribute. All characters are allowed except %	st	...
• telephone	String	No	User info at- tribute. All characters are allowed except %	telepho- neNumber	...
• country	String	No	User info at- tribute. All characters are allowed except %	co	...
• streetAd- dress	String	No	User info at- tribute. All characters are allowed except %	streetAddress	...
• enable- FailedAu- th Protec- tion	Boolean	No	Enable prevent AD account lockout due to too many bad password attempts	false	...
• failedAu- thThresh- old	Integer	No	Number of bad password attempts	5	...

continues on next page

Table 5 – continued from previous page

• authProtection-Type	Enum	No	Enable prevent AD account lockout. Allowed values:- WIRELESS, - WIRED, - BOTH	WIRELESS	...
-----------------------	------	----	---	----------	-----

get_active_directory_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

load_groups_from_domain(*id*, *ad_attributes=None*, *ad_scopes_names=None*, *adgroups=None*, *advanced_settings=None*, *description=None*, *domain=None*, *enable_domain_white_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_characters, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
is_user_member_of_groups(id, additional_data=None, headers=None, payload=None,  
                          active_validation=True, **query_parameters)
```

This API verifies if the user is a member of the given groups.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_trusted_domains(id, headers=None, **query_parameters)
```

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

join_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetches the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – *additionalData*, property of the request body (list of objects).
- **id** (*basestring*) – *id* path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – *page* query parameter. Page number.
- **size** (*int*) – *size* query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory*

`get_active_directory_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

create_active_directory(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_active_directory*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.1.0).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

The Admin User API allows to retrieve information related to admin users configured on Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	1.1	2.0	Cisco ISE Release 2.3 Admin User

Resource Definition

Attribute	Type	Re- quired	Description	Example Values	De- fault Value
name	String	Yes	Resource Name		
id	String	Yes	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69	
description	String	No			
changePass- word	Boolean	Yes		true	true
email	String	No		email1@domain.com	
includeSys- temAlarm- sInEmail	Boolean	No		false	
inactiveAc- countN- everDisabled	Boolean	No		true	
enabled	Boolean	Yes		false	
external	Boolean	No		true	
customAt- tributes	String	No	Key Value Map	{“MyCustom- Attribute” : “Value1”}	
firstName	String	No			
adminGroups	String	No	Admin Group Names	Super Admin	
lastName	String	No			
password	String	No	The password field doesn’t show the actual password configured. It is hidden with the asterisk (*) symbol		

get_admin_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

allowed_protocols**class AllowedProtocols**

Identity Services Engine AllowedProtocols API (version: 3.1.0).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

Allowed Protocols API allows the client to add, delete, update, search and perform actions on allowed protocols.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.7	Added support for TEAP	preferredEapProtocol	Added value 'TEAP' to enum attribute preferredEapProtocol
				allowTeap	Added boolean attribute allowTeap
				allowTeapEapMsChapV2	Added boolean attribute allowTeapEapMsChapV2
				allowTeapEapMsChapV2PwdChange	Added boolean attribute allowTeap
				allowTeapEapMsChapV2PwdChangeRetries	Added int attribute allowTeapEapMsChapV2PwdChangeRetries
				allowTeapEapTls	Added boolean attribute allowTeapEapTls

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Device Admin
id	String	No	Resource UUID, Mandatory for update	926901b0-8c01-11e6-996c-525400b48521
description	String	No		Default Allowed Protocol Service Device Admin
processHost-Lookup	Boolean	Yes		true
allowPapAscii	Boolean	No		true
allowChap	Boolean	Yes		false
allowMsChapV1	Boolean	Yes		false
allowMsChapV2	Boolean	Yes		false
allowEapMd5	Boolean	Yes		true
allowLeap	Boolean	Yes		false
allowEapTls	Boolean	Yes		true
allowEapTtls	Boolean	Yes		true
allowEapFast	Boolean	Yes		true
allowPeap	Boolean	Yes		true
allowTeap	Boolean	Yes		true
allowPreferredEapProtocol	Boolean	Yes		true

continues on next page

Table 6 – continued from previous page

eapTlsLBit	Boolean	Yes		false
allowWeakCiphersForEap	Boolean	Yes		false
requireMessageAuth	Boolean	Yes		false
preferredEapProtocol	Enum	No	The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored.	PEAP
eapTls	List	No	The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol	
• allowEapTlsAuthOfExpiredCerts	Boolean	Yes		false
• eapTlsEnableStatelessSessionResume	Boolean	Yes		false
• eapTlsSessionTicketTtl	Integer	No	Time to live. The eapTlsSessionTicketTtl is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
• eapTlsSessionTicketTtlUnits	Enum	No	Time to live time units. The eapTlsSessionTicketTtlUnits is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored.	SECONDS

continues on next page

Table 6 – continued from previous page

• eapTlsSessionTicketPrecentage	Integer	No	The eapTlsSessionTicketPrecentage is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
peap	List	No	The peap is required only if allowPeap is true, otherwise it must be ignored. The object peap contains the settings for PEAP protocol	
• allowPeapEapMsChapV2	Boolean	Yes		true
• allow-PeapEapMsChapV2PwdChange	Boolean	No	The allow-PeapEapMsChapV2PwdChange is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored	true
• allow-PeapEapMsChapV2PwdChangeRetries	Integer	No	The allow-PeapEapMsChapV2PwdChangeRetries is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
• allowPeapEapGtc	Boolean	Yes		false
• allowPeapEapGtcPwdChange	Boolean	No	The allowPeapEapGtcPwdChange is required only if allowPeapEapGtc is true, otherwise it must be ignored	false

continues on next page

Table 6 – continued from previous page

• allowPeapEapGtcPwdChangeRetries	Integer	No	The allowPeapEapGtcPwdChangeRetries is required only if allowPeapEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
• allowPeapEapTls	Boolean	Yes		true
• allowPeapEapTlsAuthOfExpiredCerts	Boolean	No	The allowPeapEapTlsAuthOfExpiredCerts is required only if allowPeapEapTls is true, otherwise it must be ignored	false
• requireCryptobinding	Boolean	Yes		false
• allowPeapV0	Boolean	Yes		false
eapTtls	List	No	The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol	
• eapTtlsPapAscii	Boolean	Yes		true
• eapTtlsChap	Boolean	Yes		true
• eapTtlsMsChapV1	Boolean	Yes		true
• eapTtlsMsChapV2	Boolean	Yes		true

continues on next page

Table 6 – continued from previous page

• eapT-tlsEapMd5	Boolean	Yes		true
• eapT-tlsEapM-sChapV2	Boolean	Yes		true
• eapT-tlsEapM-sChapV2PwdChange	Boolean	No	The eapTtlsEapM-sChapV2PwdChange is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored	true
• eapT-tlsEapM-sChapV2PwdChangeRetries	Integer	No	The eapTtlsEapM-sChapV2PwdChangeRetries is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
eapFast	List	No	The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol	
• allowEap-FastEapM-sChapV2	Boolean	Yes		true
• allowEap-FastEapM-sChapV2PwdChange	Boolean	No	The allowEap-FastEapM-sChapV2PwdChange is required only if allowEap-FastEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 6 – continued from previous page

<ul style="list-style-type: none"> • allowEap-FastEapM-sChapV2PwChangeRetries 	Integer	No	The allowEap-FastEapM-sChapV2PwChangeRetries is required only if eapTlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapGtc 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChange 	Boolean	No	The allowEap-FastEapGtcPwChange is required only if allowEap-FastEapGtc is true, otherwise it must be ignored	true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChangeRetries 	Integer	No	The allowEap-FastEapGtcPwChangeRetries is required only if allowEapFastEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapTlsAuthOfExpiredCerts 	Boolean	No	The allowEap-FastEapTlsAuthOfExpiredCerts is required only if allowEap-FastEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastEnableEAPChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • eapFastUsePacs 	Boolean	Yes		true

continues on next page

Table 6 – continued from previous page

• eapFastUsePacsTunnelPacTtl	Integer	No	The eapFastUsePacsTunnelPacTtl is required only if eapFastUsePacs is true, otherwise it must be ignored	7776000
• eapFastUsePacsTunnelPacTtlUnits	Enum	No	The eapFastUsePacsTunnelPacTtlUnits is required only if eapFastUsePacs is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsUseProactivePacUpdatePercentage	Integer	No	The eapFastUsePacsUseProactivePacUpdatePercentage is required only if eapFastUsePacs is true, otherwise it must be ignored	10
• eapFastUsePacsAllowAnonymProvisioning	Boolean	No	The eapFastUsePacsAllowAnonymProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAllowAuthenProvisioning	Boolean	No	The eapFastUsePacsAllowAuthenProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning	Boolean	No	The eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false

continues on next page

Table 6 – continued from previous page

• eapFastUsePacsAcceptClientCert	Boolean	No	The eapFastUsePacsAcceptClientCert is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false
• eapFastUsePacsAllowMachineAuthentication	Boolean	No		false
• eapFastUsePacsMachinePacTtl	Integer	No	The eapFastUsePacsMachinePacTtl is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored	1
• eapFastUsePacsMachinePacTtlUnits	Enum	No	The eapFastUsePacsMachinePacTtlUnits is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsStatelessSessionResume	Boolean	No	The eapFastUsePacsStatelessSessionResume is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAuthorizationPacTtl	Integer	No	The eapFastUsePacsAuthorizationPacTtl is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored	1

continues on next page

Table 6 – continued from previous page

<ul style="list-style-type: none"> • eapFastUsePacsAuthorizationPacTtlUnits 	Enum	No	The eapFastUsePacsAuthorizationPacTtlUnits is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored.	SECONDS
<ul style="list-style-type: none"> • eapFastDontUsePacsAcceptClientCert 	Boolean	No	The eapFastDontUsePacsAcceptClientCert is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastDontUsePacsAllowMachineAuthentication 	Boolean	No	The eapFastDontUsePacsAllowMachineAuthentication is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
teap	List	No	The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol	
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChange 	Boolean	No	The allowTeapEapM-sChapV2PwdChange is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 6 – continued from previous page

<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChangeRetries 	Integer	No	The allowTeapEapM-sChapV2PwdChangeRetries is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	3
<ul style="list-style-type: none"> • allowTeapEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapTlsAuthOfExpiredCerts 	Boolean	No	The allowTeapEapTlsAuthOfExpiredCerts is required only if allowTeapEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • acceptClientCertDuringTunnelEst 	Boolean	Yes		true
<ul style="list-style-type: none"> • enableEapChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • allowDowngradeMsk 	Boolean	Yes		false

get_allowed_protocol_by_name(name, headers=None, **query_parameters)

This API allows the client to get an allowed protocol by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_name`***`get_allowed_protocol_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_id`*


```
update_allowed_protocol_by_id(id, allow_chap=None, allow_eap_fast=None, allow_eap_md5=None,
                             allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None,
                             allow_ms_chap_v1=None, allow_ms_chap_v2=None,
                             allow_pap_ascii=None, allow_peap=None,
                             allow_preferred_eap_protocol=None, allow_teap=None,
                             allow_weak_ciphers_for_eap=None, description=None,
                             eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None,
                             name=None, peap=None, preferred_eap_protocol=None,
                             process_host_lookup=None, require_message_auth=None, teap=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_ttls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols_generator*

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.

- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
create(allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None,
allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None,
allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None,
allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None,
eap_ttls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None,
process_host_lookup=None, require_message_auth=None, teap=None, headers=None,
payload=None, active_validation=True, **query_parameters)
```

Alias for *create_allowed_protocol*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy

class AncPolicy

Identity Services Engine AncPolicy API (version: 3.1.0).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource ID	test
description	String	No		
action	Enum	Yes	<ul style="list-style-type: none"> • QUAR-ANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. • PORT-BOUNCE: Resets the port on the network device to which the endpoint is connected • SHUT-DOWN : Shuts down the port on the network device to which the endpoint is connected • RE_AUTHENTICATE: Re-authenticates the session from the endpoint 	

get_anc_policy_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_anc_policy_by_name*

`get_anc_policy_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_anc_policy_by_id*

```
update_anc_policy_by_id(id, actions=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, actions=None, name=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_anc_policy_by_id*

```
delete_anc_policy_by_id(id, headers=None, **query_parameters)
```

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy_generator*

create_anc_policy(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_anc_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_policy(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.1.0).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

Authorization Profile API allows the client to add, delete, update, search and perform actions on authorization profiles.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revi- sion Mod- ifica- tion	Revision Modification
				At- tribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.3	Support new attributes under common tasks	ac- cessType	Added Attribute 'accessType'. Default value:'ACCESS_ACCEPT', additional values: 'ACCESS_REJECT'
				au- thzPro- file- Type	Added Attribute 'authzProfileType' to differentiate between types of authorization profiles. Default value:'SWITCH' (used for Standard Authorization Profiles) , additional values:'TACACS', 'TRUSTSEC'
				reauth	Added Attribute 'reauth' to determine reauthentication policy
				we- bRedi- rec- tion	Added Attribute 'webRedirection' to support selection of portal redirection
				acl	Added String Attribute 'acl'
				track- Move- ment	Added Boolean Attribute 'trackMovement'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID value		id
description	String	No			description
vlan	List	No			
• nameID	String	Yes			vlanName
• tagID	Integer	Yes	Valid range is 0-31		1
airespaceACL	String	No			ACL
webRedirection	List	No			
• WebRedirectionType	String	Yes	Value MUST be one of the following: CentralizedWebAuth, HotSpot, NativeSupplicantProvisioning, ClientProvisioning. The WebRedirectionType must fit the portalName		Centralized-WebAuth
• acl	String	Yes			acl
• portalName	String	Yes	A portal that exist in the DB and fits the WebRedirectionType		Sponsored Guest Portal (default)
• staticIPHostNameFQDN	String	No			10.56.54.200

continues on next page

Table 7 – continued from previous page

• displayC- ertifi- catesRe- newalMes- sages	Boolean	No	The displayC- ertificatesRe- newalMes- sages is mandatory when ‘We- bRedirection- Type’ value is ‘Central- izedWebAuth’. For all other ‘WebRedi- rectionType’ values the field must be ignored	true	
accessType	Enum	No	Allowed Values: AC- CESS_ACCEPT, AC- CESS_REJECT	AC- CESS_ACCEPT	
authzProfile- Type	Enum	No	Allowed Val- ues: SWITCH, TRUSTSEC, TACACS	SWITCH	
			SWITCH is used for Standard Au- thorization Profiles		
profileName	String	No		Cisco	
acl	String	No			aclfilter
daclName	String	No			PER- MIT_ALL_IPV4_TRAFFIC
autoSmartPort	String	No			autoSmartPort
interfaceTem- plate	String	No			interfaceTem- plate
ipv6ACLFILTER	String	No			ipv6ACLFILTER
avcProfile	String	No			avcProfile
asaVpn	String	No			Cisco:cisco- call-type
trackMove- ment	Boolean	No		false	
serviceTem- plate	Boolean	No		false	
easywiredSes- sionCandidate	Boolean	No		false	
voiceDomain- Permission	Boolean	No		false	
neat	Boolean	No		false	
webAuth	Boolean	No		false	

continues on next page

Table 7 – continued from previous page

macSecPolicy	Enum	No	Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE		MUST_SECURE
reauth	List	No			
• connectivity	Enum	Yes	Allowed Values: DEFAULT, RA-DIUS_REQUEST		RA-DIUS_REQUEST
• timer	Integer	Yes	Valid range is 1-65535		1800
advancedAttributes	List	No			
• leftHand-SideDictionary-Attribute	List	Yes	Left side Dictionary and Attribute		
• dictionary-Name	String	Yes	Dictionary name		
• attribute-Name	String	Yes	Attribute name		
• rightHand-SideAttribute-Value	List	Yes	Attribute value can be of type AttributeValue or Advanced-DictionaryAttribute. For AttributeValue the value is String, For Advanced-Dictionary-Attribute the value is dictionaryName and attributeName properties		
ipv6DaclName	String	No			PER-MIT_ALL_IPV6_TRAFFIC
airespaceIPv6ACL	String	No			ACL6

`get_authorization_profile_by_name(name, headers=None, **query_parameters)`

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_id*

update_authorization_profile_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.

- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_authorization_profile_by_id*

delete_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_authorization_profile_by_id*

get_authorization_profiles(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles***get_authorization_profiles_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles_generator*


```
create_authorization_profile(access_type=None, acl=None, advanced_attributes=None,
                             agentless_posture=None, airespace_acl=None,
                             airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
                             auto_smart_port=None, avc_profile=None, dacl_name=None,
                             description=None, easywired_session_candidate=None, id=None,
                             interface_template=None, ipv6_acl_filter=None,
                             ipv6_dacl_name=None, mac_sec_policy=None, name=None,
                             neat=None, profile_name=None, reauth=None, service_template=None,
                             track_movement=None, vlan=None, voice_domain_permission=None,
                             web_auth=None, web_redirection=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API creates an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.

- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_authorization_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

byod_portal**class ByodPortal**

Identity Services Engine BYODPortal API (version: 3.1.0).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

BYOD Portal API provides the ability to Create, Read, Update, Delete and Search BYOD portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		BYOD Portal (default)
id	String	No	Resource UUID, mandatory for update		9a9b910c-54d3-44a4-a3c3-dd007c171599

continues on next page

Table 8 – continued from previous page

description	String	No			Default portal and user experience used when employees register a personal device on the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?portalId=54d3-44a4-a3c3-dd007c171599
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	BYOD	
settings	List	No	Defines all of the settings groups available for a BYOD		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		["eth0", "bond0"]

continues on next page

Table 8 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• end- pointI- dentity- Group	String	Yes	Unique Id of the endpoint identity group where user's devices will be added. Used only in Hotspot Portal		
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• byodSet- tings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWel- comeSet- tings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enable- BYOD	Boolean	No		true	
• en- ableGues- tAccess	Boolean	No		false	

continues on next page

Table 8 – continued from previous page

• re-requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No		false	
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodRegistrationSettings	List	No	Configuration of BYOD endpoint Registration step configuration		
• showDeviceID	Boolean	No	Display Device ID field during registration	true	
• endpointIdentityGroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521

continues on next page

Table 8 – continued from previous page

• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Au- thentication Success where should device be redirected.	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		Redirect URL
• support- InfoSet- tings	List	No	Configuration of BYOD endpoint wel- come step configuration		
• in- cludeSup- portIn- foPage	Boolean	No		false	
• in- cludeMacAddr	Boolean	No		false	
• in- cludeIpAd- dress	Boolean	No		false	
• include- BrowserUser- Agent	Boolean	No		false	
• include- Policy- Server	Boolean	No		false	
• include- Failure- Code	Boolean	No		false	

continues on next page

Table 8 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available for a BYOD		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 8 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 8 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			BYOD Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 8 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_byod_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_byod_portal_by_id*

update_byod_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a BYOD portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_byod_portal_by_id`

```
delete_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_byod_portal_by_id`

```
get_byod_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                headers=None, **query_parameters)
```

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal*

get_byod_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_byod_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

backup_and_restore**class BackupAndRestore**

Identity Services Engine Backup And Restore API (version: 3.1.0).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_last_status(headers=None, **query_parameters)`Alias for `get_last_config_backup_status`
`restore_config_backup(backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **`backup_encryption_key(string)`** – The encryption key which was provided at the time of taking backup., property of the request body.
- **`repository_name(string)`** – Name of the configured repository where the backup file exists., property of the request body.
- **`restore_file(string)`** – Name of the backup file to be restored on ISE node., property of the request body.
- **`restore_include_adeos(string)`** – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

restore(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *restore_config_backup*

update_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcIiSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node., property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.

- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node., property of the request body. Available values are ‘DAILY’, ‘MONTHLY’, ‘ONCE’ and ‘WEEKLY’.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are ‘DISABLE’ and ‘ENABLE’.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY, property of the request body. Available values are ‘FRI’, ‘MON’, ‘SAT’, ‘SUN’, ‘THU’, ‘TUE’ and ‘WED’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.1.0).

Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

The certificate profile API allows the client to add, search and perform actions on the certificate profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.4	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Certificate_Profile
id	String	No	Resource UUID		f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No			
allowedAsUserName	Boolean	No	To be set true or false	false	
external-identity-store-name	String	No	Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen	[not applicable]	[not applicable]
certificate-attribute-name	ENUM	No	Attribute name of the Certificate Profile - used only when CERTIFICATE is chosen in usernameFrom. Allowed values: - SUBJECT_COMMON_NAME - SUBJECT_ALTERNATIVE_NAME - SUBJECT_SERIAL_NUMBER - SUBJECT - SUBJECT_ALTERNATIVE_NAME_OTHER_NAME - SUBJECT_ALTERNATIVE_NAME_EMAIL - SUBJECT_ALTERNATIVE_NAME_DNS. - Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN	SUBJECT_COMMON_NAME	
match-Mode	ENUM	No	Match mode of the Certificate Profile. Allowed values: NEVER, RESOLVE_IDENTITY_AMBIGUITY, BINARY_COMPARISON	NEVER	
username-From	ENUM	No	The attribute in the certificate where the user name should be taken from.	CERTIFICATE	

get_certificate_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_name*

`get_certificate_profile_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_id*

```
update_certificate_profile_by_id(id, allowed_as_user_name=None,  
                                certificate_attribute_name=None, description=None,  
                                external_identity_store_name=None, match_mode=None,  
                                name=None, username_from=None, headers=None,  
                                payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allowed_as_user_name=None*, *certificate_attribute_name=None*, *description=None*, *external_identity_store_name=None*, *match_mode=None*, *name=None*, *username_from=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_certificate_profile_by_id*

get_certificate_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile*

get_certificate_profile_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.

- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_certificate_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificate_template**class CertificateTemplate**

Identity Services Engine CertificateTemplate API (version: 3.1.0).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

The certificate template API provides the ability to search for certificate templates.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.2	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
raProfile-Name	String	Yes	RA profile for the Certificate template	ISE internal CA
keySize	Integer	No	Key Size of the Certificate Template	2048 1024
validity	Integer	No	Validity period of the Certificate Template: Valid Range 21 - 3652	730

get_certificate_template_by_name(name, headers=None, **query_parameters)

This API allows the client to get a certificate template by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_name*

get_certificate_template_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *`get_certificate_template_generator`***`get_version`**(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.1.0).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csrs_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
generate_csr(allow_wild_card_cert=None, certificate_policies=None, digest_type=None,
             hostnames=None, key_length=None, key_type=None, portal_group_tag=None,
             san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None,
             subject_common_name=None, subject_country=None, subject_org=None,
             subject_org_unit=None, subject_state=None, used_for=None, headers=None,
             payload=None, active_validation=True, **query_parameters)
```

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following Parameters are present in POST request body

PARAMETER DESCRIPTION

EXAMPLE hostnames List of ise node hostnames for which CSRs should be generated [ise-host1, ise-host2]

allowWildCardCert Allow use of WildCards in certificates false

keyLength Length of the Key used for CSR generation (required) 512

keyType Type of key used for CSR generation either RSA or ECDSA(required)

digestType Hash algorithm used for signing CSR(required) SHA-256

usedFor Certificate Usage(required) MULTI-USE

subjectCommonName Certificate common name(CN)(required) \$FQDN\$

subjectOrgUnit Certificate organizational unit(OU) Engineering

subjectOrg Certificate organization (O) Cisco

subjectCity Certificate city or locality (L) San Jose

subjectState Certificate state (ST) California

subjectCountry Certificate country (C) US

sanDNS Array of SAN(Subject Alternative Name) DNS entries(optional) [ise.example.com]

sanIP Array of SAN IP entries(optional) [1.1.1.1]

sanURI Array of SAN URI entries(optional) [<https://1.1.1.1>]

sanDir Array of SAN DIR entries(optional) [CN=AAA,DC=COM,C=IL]

portalGroupTag Portal Group Tag when using certificate for PORTAL service Default Portal Certificate Group

NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames

When Certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – keyType, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.
- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.

- **used_for** (*string*) – usedFor, property of the request body. Available values are ‘ADMIN’, ‘DTLS- AUTH’, ‘EAP-AUTH’, ‘IMS’, ‘MULTI-USE’, ‘PORTAL’, ‘PXGRID’ and ‘SAML’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname, id, dirpath=None, save_file=None, filename=None, headers=None, **query_parameters*)

The response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. The hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. The ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. The ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_csr_by_id`(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **`host_name`** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be deleted.
- **`id`** (*basestring*) – id path parameter. The ID of the Certificate Signing Request to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`regenerate_ise_root_ca`(*remove_existing_ise_intermediate_csr=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API will initiate regeneration of ISE root CA certificate chain. Response contains id which can be used to track the status. Setting "removeExistingISEIntermediateCSR" to true will remove existing ISE Intermediate CSR.

Parameters

- **`remove_existing_ise_intermediate_csr`** (*boolean*) – Setting this attribute to true will remove existing ISE Intermediate CSR, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

renew_certificates(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API will initiate regeneration of certificates. Response contains id which can be used to track the status.

Parameters

- **cert_type** (*string*) – certType, property of the request body. Available values are 'IMS' and 'OCSP'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
portal_group_tag=None, pxgrid=None, radius=None, saml=None,
validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
**query_parameters)
```

Bind CA Signed Certificate. NOTE: This API requires an

existing Certificate Signing Request, and the root certificate must already be trusted. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body **PARAMETER DESCRIPTION EXAMPLE** name Friendly name of the certificate. Signed Certificate data Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

)

(required). awk 'NF {sub(/

/, ""); printf

“%sn”, \$0;}’ <<your .pem file>> allowExtendedValidity Allow the certificates greater than validity of 398 days (required) false allowOutOfDateCert Allow out of date certificates (required) false allowReplacementOfCertificates Allow Replacement of certificates (required) false allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADSec server false pxgrid Use certificate for the pxGrid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group validateCertificateExtensions Validate Certificate Extensions false Following Roles can be used in any combinations **ROLE DEFAULT WARNING** Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the ISE

Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of

certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow

Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

data(string): Signed Certificate data (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

host_name(string): Name of Host whose CSR ID has been provided (required), property of the request body.

id(string): ID of the generated CSR (required), property of the request body.

ims(boolean): Use certificate for the ISE Messaging Service, property of the request body.

name(string): Friendly Name of the certificate, property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

.

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

```
export_system_certificate(export=None, id=None, password=None, dirpath=None, save_file=None,  
filename=None, headers=None, payload=None, active_validation=True,  
**query_parameters)
```

Export System Certificate. Following Parameters are used in POST body
PARAMETER DESCRIPTION
EXAMPLE id ID of a System Certificate(required) < SYSTEM_CERT_ID >
export One of the below option is required “CERTIFICATE” : Export only Certificate without Private Key
 “CERTIFICATE_WITH_PRIVATE_KEY” : Export both Certificate and Private Key(“certificatePassword” is required)
CERTIFICATE_WITH_PRIVATE_KEY password Certificate Password (required if “export” :
CERTIFICATE_WITH_PRIVATE_KEY) Password Constraints: Alphanumeric Minimum of 8 Characters
 Maximum of 100 Characters Passw*** NOTE: The response of this API carries a ZIP file containing
 the certificate and private key if “export” : “CERTIFICATE_WITH_PRIVATE_KEY” in the request. If
 “export” : “CERTIFICATE” in request body, the response carries a ZIP file containing only the certificate.
WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the
 private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are ‘CERTIFICATE’ and ‘CERTIFICATE_WITH_PRIVATE_KEY’.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_system_certificate(admin=None, allow_extended_validity=None,
                          allow_out_of_date_cert=None, allow_replacement_of_certificates=None,
                          allow_replacement_of_portal_group_tag=None,
                          allow_sha1_certificates=None, allow_wild_card_certificates=None,
                          data=None, eap=None, ims=None, name=None, password=None,
                          portal=None, portal_group_tag=None,
                          portal_tag_transfer_for_same_subject=None, private_key_data=None,
                          pxgrid=None, radius=None, role_transfer_for_same_subject=None,
                          saml=None, validate_certificate_extensions=None, headers=None,
                          payload=None, active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE:

The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers.

NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. System Certificate password Password of the certificate to be imported (required). Passw*** data Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). awk 'NF

```
{sub(/
```

```
/, ""); printf "%sn", $0;}' <<your .pem file>>
```

privateKeyData Plain-text contents of the private key file. Every space needs to be replaced with newline escape sequence (

) (required). awk 'NF {sub(/ /,

```
""); printf "%sn", $0;}' <<your .pem file>> allowOutOfDateCert Allow out of date certificates (required) false allowSHA1Certificates Allow SHA1 based certificates (required) false allowExtendedValidity Allow the certificates greater than validity of 398 days (required) false roleTransferForSameSubject Allow the transfer of roles to certificates with same subject false portalTagTransferForSameSubject Acquire the group tag of the matching certificate false admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADIUS server false pxgrid Use certificate for the px-Grid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false allowWildcardCertificates Allow use of WildCards in certificates false validateCertificateExtensions Validate Certificate Extensions false Following Roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .
```

Args:

admin(boolean): Use certificate to authenticate the ISE

Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based certificates (required), property of the request body.

allow_wild_card_certificates(boolean): Allow Wildcard Certificates, property of the request body.

data(string): Certificate Content (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

ims(boolean): Use certificate for the ISE Messaging Service, property of the request body.

name(string): Name of the certificate, property of the request body.

password(string): Certificate Password (required), property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

portal_tag_transfer_for_same_subject(boolean): Allow overwriting the portal tag from matching certificate of same subject, property of the request body.

private_key_data(string): Private Key data (required), property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

role_transfer_for_same_subject(boolean): Allow transfer of roles for certificate with matching subject, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name, filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name, filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name (basestring)** – hostName path parameter. Name of the host of which system certificates should be returned.
- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sort (basestring)** – sort query parameter. sort type asc or desc.
- **sort_by (basestring)** – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter (basestring, list, set, tuple)** – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificate_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API displays details of a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **id** (*basestring*) – id path parameter. The id of the system certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.


```
update_system_certificate(host_name, id, admin=None,
                          allow_replacement_of_portal_group_tag=None, description=None,
                          eap=None, expiration_ttl_period=None, expiration_ttl_units=None,
                          ims=None, name=None, portal=None, portal_group_tag=None,
                          portal_tag_transfer_for_same_subject=None, pxgrid=None, radius=None,
                          renew_self_signed_certificate=None,
                          role_transfer_for_same_subject=None, saml=None, headers=None,
                          payload=None, active_validation=True, **query_parameters)
```

Update a System Certificate. NOTE: Renewing a certificate will cause an application server restart on the selected node. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body

PARAMETER	DESCRIPTION	EXAMPLE
name	Friendly name of the certificate.	System Certificate
description	Description of the Certificate	Default
admin	Use certificate to authenticate the ISE Admin Portal	false
eap	Use certificate for EAP protocols that use SSL/TLS tunneling	false
radius	Use certificate for RADIUS server	false
pxgrid	Use certificate for the pxGrid Controller	false
ims	Use certificate for the ISE Messaging Service	false
saml	Use certificate for SAML Signing	false
portal	Use certificate for portal	false
portal_group_tag	Portal Group Tag for using certificate with portal role	Default
portal_tag_transfer_for_same_subject	Allow Replacement of Portal Group Tag (required)	false
role_transfer_for_same_subject	Allow the transfer of roles to certificates with same subject	false
portal_tag_transfer_for_same_subject	Acquire the group tag of the matching certificate	false
renew_self_signed_certificate	Renew Self Signed Certificate	false
expiration_ttl_period	Expiration Period	365
expiration_ttl_units	Expiration Units in one of the below formats	days / weeks / months / years

Following Roles can be used in any combinations

ROLE	DEFAULT	WARNING
Admin	False	Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates
EAP	False	Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
RADIUS	False	Only one system certificate can be used for RADIUS. Assigning RADIUS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
DTLS	False	Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
SAML	False	SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the ISE Admin Portal, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.
- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are 'days', 'months', 'weeks' and 'years'.
- **ims** (*boolean*) – Use certificate for the ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.

- **portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self Signed Certificate, property of the request body.
- **role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject , property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_system_certificate_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host from which the System Certificate needs to be deleted.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_certificates`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_certificates_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: `friendlyName` `subject` `issuedTo` `issuedBy` `validFrom` `Supported Date Format: yyyy-MM- dd HH:mm:ss` `Supported Operators: EQ, NEQ, GT and LT` `expirationDate` `Supported Date Format: yyyy-MM-dd HH:mm:ss` `Supported Operators: EQ, NEQ, GT and LT` `status` `Allowed values: enabled, disabled` `Supported Operators: EQ, NEQ` .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`export_trusted_certificate`(*id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*,
***query_parameters*)

The response of this API carries a trusted certificate file mapped to the requested id.

Parameters

- **`id`** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be exported.
- **`dirpath`** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **`save_file`** (*bool*) – Enable or disable automatic file creation of raw response.
- **`filename`** (*basestring*) – The filename used to save the download file.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type*DownloadResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.
- **`DownloadFailure`** – If was not able to download the raw
- **`response to a file.`** –

`import_trust_certificate`(*allow_basic_constraint_cafalse=None*, *allow_out_of_date_cert=None*,
allow_shal_certificates=None, *data=None*, *description=None*, *name=None*,
trust_for_certificate_based_admin_auth=None,
trust_for_cisco_services_auth=None, *trust_for_client_auth=None*,
trust_for_ise_auth=None, *validate_certificate_extensions=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

Import an X509 certificate as a trust certificate. NOTE:

Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
PARAMETER DESCRIPTION
EXAMPLE name Friendly name of the certificate
Trust Certificate description Description of the certificate
Passw*** data Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

)

(required). awk 'NF {sub(/

/, ""); printf

“%sn”, \$0; }’ <<your .pem file>> allowOutOfDateCert Allow out of date certificates (required) false
allowSHA1Certificates Allow SHA1 based certificates (required) false trustForIseAuth Trust for authentication within ISE false trustForClientAuth Trust for client authentication and Syslog false trustForCertificateBasedAdminAuth Trust for Certificate based Admin authentication false trustForCiscoServicesAuth Trust for authentication of Cisco Services false validateCertificateExtensions Validate extensions for trust certificate false
NOTE: If name is not set, a default name of the following format will be generated: common-name#issuer#nnnnn where “nnnnn” is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate will be trusted in ISE. The objective here is to distinguish between certificates that are used for trust within an ISE deployment and public certificates that are used to trust Cisco services. Typically, you will not want to use a given certificate for both purposes. Trusted For Usage Authentication within ISE Use “trustForIseAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Args:**allow_basic_constraint_cafalse(boolean): Allow**

Certificates with Basic Constraints CA Field as False (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

data(string): Certificate content (required), property

of the request body.

description(string): Description of the certificate,

property of the request body.

name(string): Name of the certificate, property of the

request body.

trust_for_certificate_based_admin_auth(boolean): Trust

for Certificate based Admin authentication, property of the request body.

trust_for_cisco_services_auth(boolean): Trust for

authentication of Cisco Services, property of the request body.

trust_for_client_auth(boolean): Trust for client
authentication and Syslog, property of the request body.

trust_for_ise_auth(boolean): Trust for authentication
within ISE, property of the request body.

validate_certificate_extensions(boolean): Validate trust
certificate extension, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

payload(dict): A JSON serializable Python object to send in the
body of the Request.

active_validation(bool): Enable/Disable payload validation.
Defaults to True.

****query_parameters: Additional query parameters (provides**
support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. MalformedRequest: If the request body created is invalid. ApiError: If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(id, headers=None, **query_parameters)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id (basestring)** – id path parameter. The id of the trust certificate.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_trusted_certificate(id, authenticate_before_crl_received=None, automatic_crl_update=None,  
                           automatic_crl_update_period=None, automatic_crl_update_units=None,  
                           crl_distribution_url=None, crl_download_failure_retries=None,  
                           crl_download_failure_retries_units=None, description=None,  
                           download_crl=None, enable_ocsp_validation=None,  
                           enable_server_identity_check=None, ignore_crl_expiration=None,  
                           name=None, non_automatic_crl_update_period=None,  
                           non_automatic_crl_update_units=None,  
                           reject_if_no_status_from_ocs_p=None,  
                           reject_if_unreachable_from_ocs_p=None, selected_ocsp_service=None,  
                           status=None, trust_for_certificate_based_admin_auth=None,  
                           trust_for_cisco_services_auth=None, trust_for_client_auth=None,  
                           trust_for_ise_auth=None, headers=None, payload=None,  
                           active_validation=True, **query_parameters)
```

Update a trusted certificate present in ISE trust store. Following Parameters are used in PUT request body

PARAMETER	DESCRIPTION	EXAMPLE	name	Friendly name
certificate	Trust Certificate status	Status of the certificate	name	Friendly name of the certificate(required)
trustForIseAuth	Trust for authentication within ISE	false	trustForClientAuth	Trust for client authentication and Syslog
trustForCertificateBasedAdminAuth	Trust for Certificate based Admin authentication	false	trustForCiscoServicesAuth	Trust for authentication of Cisco Services
enableOCSPValidation	Switch to enable/disable OCSP Validation	false	selectedOCSPService	Name of selected OCSP Service
INTERNAL_OCSP_SERVICE	INTERNAL_OCSP_SERVICE	INTERNAL_OCSP_SERVICE	rejectIfNoStatusFromOCSP	Switch to reject certificate if there is no status from OCSP
rejectIfUnreachableFromOCSP	Switch to reject certificate if unreachable from OCSP	false	downloadCRL	Switch to enable/disable download of CRL
downloadCRL	Switch to enable/disable download of CRL	false	crlDistributionUrl	Certificate Revocation List Distribution URL
crlDistributionUrl	Automatic CRL update	Switch to enable/disable automatic CRL update	automaticCRLUpdatePeriod	Automatic CRL update period
automaticCRLUpdatePeriod	Automatic CRL update period	5	automaticCRLUpdateUnits	Unit of time for automatic CRL update
automaticCRLUpdateUnits	Unit of time for automatic CRL update	Minutes	nonAutomaticCRLUpdatePeriod	Non automatic CRL update period
nonAutomaticCRLUpdatePeriod	Non automatic CRL update period	1	nonAutomaticCRLUpdateUnits	Unit of time of non automatic CRL update
nonAutomaticCRLUpdateUnits	Unit of time of non automatic CRL update	Hours	crlDownloadFailureRetries	If CRL download fails, wait time before retry
crlDownloadFailureRetries	If CRL download fails, wait time before retry	10	crlDownloadFailureRetriesUnits	Unit of time before retry if CRL download fails
crlDownloadFailureRetriesUnits	Unit of time before retry if CRL download fails	Minutes	enableServerIdentityCheck	Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL
enableServerIdentityCheck	Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL	false	authenticateBeforeCRLReceived	Switch to enable/disable CRL Verification if CRL is not Received
authenticateBeforeCRLReceived	Switch to enable/disable CRL Verification if CRL is not Received	false	ignoreCRLExpiration	Switch to enable/disable ignore CRL Expiration
ignoreCRLExpiration	Switch to enable/disable ignore CRL Expiration	false	Trusted For Usage	Authentication within ISE
Trusted For Usage	Authentication within ISE	Use “trustForIseAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes	Client authentication and Syslog	Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “trustForClientAuth” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication
Client authentication and Syslog	Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “trustForClientAuth” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication	Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes	Note: “trustForCertificateBasedAdminAuth”	can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services
Note: “trustForCertificateBasedAdminAuth”	can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services	Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. OCSP Configuration Usage	Validation against OCSP service	Use “enableOCSPValidation”:true to validate the certificate against OCSP service mentioned in the field selectedOCSPService
Validation against OCSP service	Use “enableOCSPValidation”:true to validate the certificate against OCSP service mentioned in the field selectedOCSPService	OCSP Service name	Use “selectedOCSPService”:	“Name of OCSP Service” Name of the OCSP service against which the certificate should be validated
Use “selectedOCSPService”:	“Name of OCSP Service” Name of the OCSP service against which the certificate should be validated	Note: “selectedOCSPService” value will on be used if “enableOCSPValidation” has been set true. Reject the request if OCSP returns UNKNOWN status	Use “rejectIfNoStatusFromOCSP”:	true to reject the cer-

tificate if the OCSP service returns UNKNOWN status Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OCSP Responder is unreachable Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OCSP service is unreachable. Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field `crlDistributionUrl` CRL distribution url Use “`crlDistributionUrl`” to specify the URL from where the CRL should be downloaded Note: “`crlDistributionUrl`” value will only be used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and `automaticCRLUpdatePeriod`, `automaticCRLUpdatePeriod` to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod”, `nonAutomaticCRLUpdateUnits` to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” to set retry time period if CRL download fails Note: “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable/disable CRL Verification if CRL is not Received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable/disable automatic CRL update, property of the request body.
- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable/disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable/disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.

- **ignore_crl_expiration** (*boolean*) – Switch to enable/disable ignore CRL Expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.
- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocs_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘Disabled’ and ‘Enabled’.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within ISE, property of the request body.
- **id** (*basestring*) – id path parameter. The id of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities

class ClearThreatsAndVulnerabilities

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.1.0).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

Clear Threats and Vulnerabilities API allows the user to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.1	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	Yes	Resource UUID value	
macAd-dresses	String	Yes	One or more endpoint MAC ad-dresses	["00:00:00:00:00:F2", "00:00:00:00:00:F3"]

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_threats_and_vulnerabilities*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

consumer**class Consumer**

Identity Services Engine Consumer API (version: 3.1.0).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](https://developer.cisco.com/site/license/cisco-sample-code-license/)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

create_account(*node_name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

AccountCreate.

Parameters

- **`node_name`** (*string*) – nodeName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_account*

activate_account(*description=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

access_secret(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccessSecret.

Parameters

- **peer_node_name** (*string*) – peerNodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules

class DeviceAdministrationAuthenticationRules

Identity Services Engine Device Administration - Authentication Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_authentication_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authentication rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rules`*


```
create_device_admin_authentication_rule(policy_id, identity_source_name=None,
                                         if_auth_fail=None, if_process_fail=None,
                                         if_user_not_found=None, link=None, rule=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

Device Admin Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None,  
        if_user_not_found=None, link=None, rule=None, headers=None, payload=None,  
        active_validation=True, **query_parameters)
```

Alias for *create_device_admin_authentication_rule*

```
reset_hit_counts_device_admin_authentication_rules(policy_id, headers=None,  
                                                    **query_parameters)
```

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)
```

Alias for *reset_hit_counts_device_admin_authentication_rules*

```
get_device_admin_authentication_rule_by_id(id, policy_id, headers=None, **query_parameters)
```

Device Admin Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_device_admin_authentication_rule_by_id*

update_device_admin_authentication_rule_by_id(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update rule.

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_device_admin_authentication_rule_by_id`*

`delete_device_admin_authentication_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete rule.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`id`** (*basestring*) – `id` path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *`delete_device_admin_authentication_rule_by_id`*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_local_exception_rules*

create_device_admin_local_exception_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.

- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_local_exception_rule*

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_device_admin_local_exceptions`***`get_device_admin_local_exception_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Device Admin Get local exception rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_device_admin_local_exception_rule_by_id`***`update_device_admin_local_exception_rule_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Device Admin Update local exception rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_local_exception_rule_by_id*

delete_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_local_exception_rule_by_id*

device_administration_authorization_global_exception_rules**class DeviceAdministrationAuthorizationGlobalExceptionRules**

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_set_global_exception_rules(*headers=None*, ***query_parameters*)

Device Admin Get global execption rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_device_admin_policy_set_global_exception_rules*

create_device_admin_policy_set_global_exception(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Device Admin Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_global_exceptions*

get_device_admin_policy_set_global_exception_by_rule_id(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_by_rule_id*

update_device_admin_policy_set_global_exception_by_rule_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_global_exception_by_rule_id*

device_administration_authorization_rules

class DeviceAdministrationAuthorizationRules

Identity Services Engine Device Administration - Authorization Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for `get_device_admin_authorization_rules`

`create_device_admin_authorization_rule(policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` or dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authorization_rule*

`reset_hit_counts_device_admin_authorization_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

`get_device_admin_authorization_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authorization_rule_by_id*

update_device_admin_authorization_rule_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_device_admin_authorization_rule_by_id*

delete_device_admin_authorization_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Device Admin Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_device_admin_authorization_rule_by_id*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_command_sets(*headers=None, **query_parameters*)

Device Admin Return list of command sets. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_conditions(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_device_admin_conditions`

`create_device_admin_condition(attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to exist-ing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner con-dition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner mem-bers of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggre-gated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

get_device_admin_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authorization_rules*

get_device_admin_condition_by_name(*name, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_condition_by_name*

update_device_admin_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name*=None, *attribute_value*=None, *children*=None, *condition_type*=None, *dates_range*=None, *dates_range_exception*=None, *description*=None, *dictionary_name*=None, *dictionary_value*=None, *hours_range*=None, *hours_range_exception*=None, *id*=None, *is_negate*=None, *link*=None, *operator*=None, *week_days*=None, *week_days_exception*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers*=None, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers*=None, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers*=None, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_for_policy_sets`(*headers=None, **query_parameters*)Alias for *`get_device_admin_conditions_for_policy_sets`***`get_device_admin_condition_by_id`**(*id, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **`id (basestring)`** – id path parameter. Condition id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id, headers=None, **query_parameters*)Alias for *`get_device_admin_condition_by_id`***`update_device_admin_condition_by_id`**(*id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body

(list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_id*

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_device_admin_condition_by_id`

device_administration_dictionary_attributes_list**class DeviceAdministrationDictionaryAttributesList**

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_dictionaries_authentication(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authorization*

get_device_admin_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_policy_set*

device_administration_identity_stores

class DeviceAdministrationIdentityStores

Identity Services Engine Device Administration - Identity Stores API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_device_admin_identity_stores(*headers=None, **query_parameters*)

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_identity_stores*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_network_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_network_conditions*

create_device_admin_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.

- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_network_condition_by_id*

update_device_admin_network_condition_by_id(*id*, *condition_type=None*, *conditions=None*,
description=None, *link=None*, *name=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are ‘DeviceCondition’, ‘DevicePortCondition’ and ‘EndstationCondition’.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type*=None, *conditions*=None, *description*=None, *link*=None, *name*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers*=None, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ***query_parameters*)

Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set

class DeviceAdministrationPolicySet

Identity Services Engine Device Administration - Policy Set API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_sets(*headers*=None, ***query_parameters*)

Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *`get_device_admin_policy_sets`***`create_device_admin_policy_set`**(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` , or, dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **`condition`** (*object*) – condition, property of the request body.
- **`default`** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **`description`** (*string*) – The description for the policy set, property of the request body.
- **`hit_counts`** (*integer*) – The amount of times the policy was matched, property of the request body.
- **`id`** (*string*) – Identifier for the policy set, property of the request body.
- **`is_proxy`** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **`rank`** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **`service_name`** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **`state`** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'disabled', 'enabled' and 'monitor'.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_policy_sets*

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_by_id*

update_device_admin_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.

- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_by_id*

device_administration_profiles

class DeviceAdministrationProfiles

Identity Services Engine Device Administration - Profiles API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

get_device_admin_profiles(*headers=None*, ***query_parameters*)

Device Admin Returns list of shell profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers (*dict*)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_profiles*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_service_names*

device_administration_time_date_conditions

class DeviceAdministrationTimeDateConditions

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_time_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_time_conditions*

create_device_admin_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.

- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
        dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
        dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
        is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_device_admin_time_condition*

```
get_device_admin_time_condition_by_id(id, headers=None, **query_parameters)
```

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_time_condition_by_id*

update_device_admin_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_device_admin_time_condition_by_id](#)

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [delete_device_admin_time_condition_by_id](#)

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.1.0).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

Downloadable ACL API allows the client to add, delete, update, search and perform actions on downloadable ACL.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute IP version in 2.6	daclType	Added Enum Attribute 'daclType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]		multiline_acl
id	String	Yes	Resource UUID		c1e0e9e0-717f-11eb-9fb2-b6cb23d38630
description	String	No	Use the string n for a newline		description
dacl	String	Yes	The DACL Content. Use the string n for a newline		permit ip any any
daclType	Enum	No	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	

get_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a downloadable ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_downloadable_acl_by_id*

update_downloadable_acl_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string *n* for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string *n* for a newline, property of the request body.
- **id** (*basestring*) – *id*, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [*_*.-], property of the request body.
- **id** – *id* path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_downloadable_acl_by_id*](#)

delete_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a downloadable ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_downloadable_acl_by_id*](#)

get_downloadable_acl(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl***get_downloadable_acl_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl_generator***create_downloadable_acl**(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string `\n` for a newline, property of the request body.

- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string `\n` for a newline, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [`_.-`], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell**class EgressMatrixCell**

Identity Services Engine EgressMatrixCell API (version: 3.1.0).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

Egress Policy Matrix Cell API allows the client to add, update, delete and search egress matrix cells among other operations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version
1	1.1	2.3	Introducing bulk operations

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		ANY-ANY
id	String	No	Resource UUID, mandatory for update		f92c1a900-8c01-11e6-996c-525400b48521
description	String	No			Default egress rule
default-Rule	Enum	Yes	Allowed values: NONE, DENY_IP, PERMIT_IP	NONE	PERMIT_IP
destinationSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521
matrix-CellStatus	Enum	Yes	Allowed values: DISABLED, ENABLED, MONITOR	DISABLED	ENABLED
sgACLs	List	Yes			[“92951ac0-8c01-11e6-996c-525400b48521”]
sourceSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*headers=None, **query_parameters*)

Alias for *clear_all_matrix_cells*

set_all_cells_status(*status, headers=None, **query_parameters*)

his API allows the client to set status of all the egress matrix cells.

Parameters

- **status** (*basestring*) – status path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_status(*status*, *headers=None*, ***query_parameters*)

Alias for *set_all_cells_status*

clone_matrix_cell(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

This API allows the client to clone an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **src_sgt_id** (*basestring*) – srcSgtId path parameter.
- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_egress_matrix_cell_by_id`***`update_egress_matrix_cell_by_id(id, default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update an egress matrix cell.

Parameters

- **`default_rule (string)`** – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`destination_sgt_id (string)`** – destinationSgtId, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`matrix_cell_status (string)`** – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`sgacIs (list)`** – sgacIs, property of the request body (list of strings).
- **`source_sgt_id (string)`** – sourceSgtId, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*,
matrix_cell_status=None, *name=None*, *sgacIs=None*, *source_sgt_id=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_egress_matrix_cell_by_id*

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-
Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell_generator*

create_egress_matrix_cell(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacIs** (*list*) – sgacIs, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_egress_matrix_cell*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.1.0).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

Endpoint Certificate API allows the client to create endpoint certificates signed by the Cisco ISE Internal CA. This API can takes in certificate request details, create a RSA key pair, create a certificate and return the resulting key pair and certificate as a ZIP file. ZIP files are returned as an octet stream.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
certTemplateName	String	Yes	Name of an Internal CA template	Certificate_Template_Name
format	Enum	Yes	Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN	PKCS8
password	String	Yes	Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#	Password_123
certificateRequest	Map	Yes	Key value map. Must have CN and SAN entries	
• CN	String	Yes	Matches the requester's User Name, unless the Requester is an ERS Admin. ERS Admins are allowed to create requests for any CN	userName [or] machineName
• SAN	String	Yes	Valid MAC Address, delimited by '-'	11-22-33-44-55-66

```
create_endpoint_certificate(cert_template_name=None, certificate_request=None, format=None,
                             password=None, dirpath=None, save_file=None, filename=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to create an endpoint certificate.

Parameters

- **cert_template_name** (*string*) – Name of an Internal CA template, property of the request body.
- **certificate_request** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.

- **format** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **password** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

create(*cert_template_name=None, certificate_request=None, format=None, password=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_certificate*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group**class EndpointIdentityGroup**

Identity Services Engine EndpointIdentityGroup API (version: 3.1.0).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

Endpoint Identity Groups API allows the client to add, delete, update, and search endpoint groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.4	Added GetByName operation		

Resource Definition

Attribute	Type	Re-quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		Cisco-Meraki-Devicee
id	String	No	Resource UUID, mandatory for update		1e2700a0-8c00-11e6-996c-525400b48521
description	String	No			Identity Group for Profile: Cisco-Meraki-Device
systemDefined	Boolean	Yes		false	true

get_endpoint_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_id*

update_endpoint_group_by_id(*id*, *description=None*, *name=None*, *system_defined=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_endpoint_group_by_id*

delete_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_group_by_id*

get_endpoint_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups*

get_endpoint_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups_generator*

create_endpoint_group(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

external_radius_server**class ExternalRadiusServer**

Identity Services Engine ExternalRADIUSServer API (version: 3.1.0).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

External RADIUS Server API allows the client to add, delete, update, search and perform actions on external RADIUS server.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Allowed characters are alphanumeric and _ (underscore).		externalRadiusServer1
id	String	No	Resource UUID, mandatory for update		da095377-dce8-486e-933a-6ea788bbf51a
description	String	No			example external radius server
hostIP	String	Yes	The IP of the host - must be a valid IPV4 address		1.1.1.1
sharedSecret	String	Yes	Shared secret maximum length is 128 characters		sharedSecret
enableKeyWrap	Boolean	Yes	KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices		true
encryptionKey	String	No	The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		1616161616161616
authenticatorKey	String	No	The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		2020202020202020
keyInputFormat	Enum	Yes	Specifies the format of the input for fields 'encryptionKey' and 'authenticatorKey'. Allowed Values: ASCII, HEXADECIMAL		ASCII
authenticationPort	Integer	Yes	Valid Range 1 to 65535		1812
accountingPort	Integer	Yes	Valid Range 1 to 65535		1813
time-out	Integer	Yes	Valid Range 1 to 120		5
re-tries	Integer	Yes	Valid Range 1 to 9		3
proxy-Time-out	Integer	No	Valid Range 1 to 600	300	

get_external_radius_server_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for `get_external_radius_server_by_id`

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed charactera are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_external_radius_server_by_id*

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_external_radius_server_by_id*

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server*

get_external_radius_server_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

create_external_radius_server(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.

- **key_input_format** (*string*) – Specifies the format of the input for fields ‘encryption-Key’ and ‘authenticatorKey’. Allowed Values: ASCII HEXADECEIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(accounting_port=None, authentication_port=None, authenticator_key=None, description=None,
        enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None,
        name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_external_radius_server*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

filter_policy**class FilterPolicy**

Identity Services Engine FilterPolicy API (version: 3.1.0).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

Filter Policy API allows clients to add, get, update and delete SXP domain filter policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
subnet	String	No	Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined	subnetAddress
sgt	String	No	SGT name or ID. At least one of subnet or sgt or vn should be defined	sgt
vn	String	No	Virtual Network. At least one of subnet or sgt or vn should be defined	virtual-Network
domains	String	Yes	List of SXP Domains, separated with comma	Sxp Vpn Name

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.

- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_filter_policy_by_id`***`get_filter_policy(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_filter_policy`***`get_filter_policy_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_filter_policy_generator*

create_filter_policy(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_filter_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.1.0).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

Guest Location API allows the client to search the locations configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	9f083530-8c01-11e6-996c-525400b48521
descrip-tion	String	No		

get_guest_location_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

Alias for `get_guest_location`

`get_guest_location_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration**class GuestSmtpNotificationConfiguration**

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.1.0).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

Guest SMTP notification configuration API is a global setting for enabling email notifications within guest application. These APIs allow to create, update and retrieve the notification settings. The create API may not be required to be used as of Cisco ISE Release 2.2 because the single SMTP notification configuration is the only one used and it always gets created during the Cisco ISE application initialization period.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for update		9ecb5340-8c01-11e6-996c-525400b48521
description	String	No			
defaultFromAddress	String	No	The default from email address to be used to send emails from	donotreply@example.com	
notificationEnabled	Boolean	No	Indicates if the email notification service is to be enabled	true	
smtpServer	String	No	The SMTP server ip address or fqdn such as outbound.mycompany.com		
useDefaultFromAddress	Boolean	No	If the default from address should be used rather than using a sponsor user email address	false	
smtpPort	String	No	Port at which SMTP Secure Server is listening	25	
connectionTimeout	String	No	Interval in seconds for all the SMTP client connections	60	
useTLSorSSLEncryption	Boolean	No	If configured to true, SMTP server authentication will happen using TLS/SSL	false	
usePasswordAuthentication	Boolean	No	If configured to true, SMTP server authentication will happen using username/password	false	
userName	String	No	Username of Secure SMTP server		
password	String	No	Password of Secure SMTP server		

get_guest_smtp_notification_settings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_guest_smtp_notification_settings_by_id`***`update_guest_smtp_notification_settings_by_id(id, connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a SMTP configuration setting.

Parameters

- **`connection_timeout (string)`** – Interval in seconds for all the SMTP client connections, property of the request body.
- **`default_from_address (string)`** – The default from email address to be used to send emails from, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`notification_enabled (boolean)`** – Indicates if the email notification service is to be enabled, property of the request body.
- **`password (string)`** – Password of Secure SMTP server, property of the request body.
- **`smtp_port (string)`** – Port at which SMTP Secure Server is listening, property of the request body.
- **`smtp_server (string)`** – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **`use_default_from_address (boolean)`** – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **`use_password_authentication (boolean)`** – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **`use_tlsor_ssl_encryption (boolean)`** – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.

- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlscrl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

get_guest_smtp_notification_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings*

get_guest_smtp_notification_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings_generator*

create_guest_smtp_notification_settings(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.

- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlsor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(connection_timeout=None, default_from_address=None, notification_enabled=None,  
        password=None, smtp_port=None, smtp_server=None, use_default_from_address=None,  
        use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None,  
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_guest_smtp_notification_settings*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_ssid

class GuestSsid

Identity Services Engine GuestSSID API (version: 3.1.0).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

Guest SSIDs are global objects that are referenced by Cisco ISE sponsor portals. Guest SSID API allows the client to add, delete, update and search guest SSID among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]	ssid_value
id	String	No	Resource UUID, mandatory for update	9132eedc-7910-4ffe-805e-3d3a366f7fb7
description	String	No		

get_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_ssid_by_id*

update_guest_ssid_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest SSID by ID.

Parameters

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_ssid_by_id*

get_guest_ssid(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_guest_ssid`

```
get_guest_ssid_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                          sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid_generator*

create_guest_ssid(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_ssid*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_type**class GuestType**

Identity Services Engine GuestType API (version: 3.1.0).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

Guest Type API allows the client to add, delete, update and search guest types.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Contractor (default)
id	String	No	Resource UUID, mandatory for update		9f03a151-8c01-11e6-996c-525400b48521
description	String	No			Default settings allow network access for up to a year.
accessTime	List	No			
<ul style="list-style-type: none"> allowAccessOn-Specific-DaysTimes 	Boolean	No	Enable Specific Day Time Limits	false	
<ul style="list-style-type: none"> default-Duration 	Integer	No		90	
<ul style="list-style-type: none"> durationTime-Unit 	Enum	No	Allowed values are: - DAYS, - HOURS, - MINUTES	DAYS	
<ul style="list-style-type: none"> from-FirstLogin 	Boolean	No	When Account Duration starts from first login or specified date	false	
<ul style="list-style-type: none"> maxAccountDuration 	Integer	No	Maximum value of Account Duration	365	
<ul style="list-style-type: none"> dayTime-Limits 	List	No	List of Time Ranges for account access		
<ul style="list-style-type: none"> dayTime-Limit 	List	No	Time Ranges for account access		
<ul style="list-style-type: none"> startTime 	String	No	Start time in HH:mm format	09:00	
<ul style="list-style-type: none"> endTime 	String	No	End time in HH:mm format	17:00	
<ul style="list-style-type: none"> days 	List	No	List of Days		
276				Chapter 1. The User Guide	
	<ul style="list-style-type: none"> day 	Enum	No	Value should be one of Week day. Allowed	

update_guest_type_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_sms(id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *update_guest_type_sms*

`get_guest_type_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest type by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *get_guest_type_by_id*

```
update_guest_type_by_id(id, access_time=None, description=None, expiration_notification=None,
                        is_default_type=None, login_options=None, name=None,
                        sponsor_groups=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, access_time=None, description=None, expiration_notification=None,
             is_default_type=None, login_options=None, name=None, sponsor_groups=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_type_by_id*

get_guest_type(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*

create_guest_type(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_type*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_user

class GuestUser

Identity Services Engine GuestUser API (version: 3.1.0).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

Guest User API allows the client to add, delete, update and search guest users among other operations which are available from the sponsor portal. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only ‘create’ bulk operation. However, all other operation which are bulk supported can be used in the same way.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		guestUser
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			ERS Example user
customFields	Map	No	Key value map		“some key” : “some value”
guestType	String	No			Contractor
status	String	No			
reasonForVisit	String	No			
personBeingVisited	String	No			
sponsorUserName	String	No			Mr Spons
sponsorUserId	String	No			
statusReason	String	No			
portalId	String	No			23423432523

continues on next page

Table 9 – continued from previous page

guestAccess-Info	List	No			
• valid-Days	Integer	Yes	Number of days guest user is valid. To validate validDays property, Cisco ISE considers only date (not time) between fromDate and toDate properties		90
• fromDate	String	No			07/29/2014 14:44
• toDate	String	No			10/29/2014 17:30
• location	String	No			San Jose
• ssid	String	No			
• groupTag	String	No			
GuestInfo	List	Yes			
• emailAddress	String	No			email@some.uri.com
• enabled	Boolean	Yes	This field is only for Get operation not applicable for Create, Update operations	false	
• password	String	Yes			asdlkj324ew
• phoneNum-ber	String	No	Phone number should be E.164 format		+13211239034
• smsService-Provider	String	No			Global Default

continues on next page

Table 9 – continued from previous page

• user-Name	String	No	If account needs be created with mobile number, please provide mobile number here		DS3ewdsa34wWE
• firstName	String	No			
• lastName	String	No			
• company	String	No			
• creation-Time	String	No			
• notificationLanguage	String	No			

approve_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to approve a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

approve_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *approve_guest_user_by_id*

change_sponsor_password(*portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to change the sponsor password.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to suspend a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`suspend_guest_user_by_name`***`reinstate_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`reinstate_guest_user_by_name`***`get_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_guest_user_by_name`*

`update_guest_user_by_name(name, custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, id=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a guest user by name.

Parameters

- **`custom_fields (object)`** – Key value map, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`guest_access_info (object)`** – guestAccessInfo, property of the request body.
- **`guest_info (object)`** – guestInfo, property of the request body.
- **`guest_type (string)`** – guestType, property of the request body.
- **`id (string)`** – id, property of the request body.
- **`name (basestring)`** – name, property of the request body.
- **`portal_id (string)`** – portalId, property of the request body.
- **`reason_for_visit (string)`** – reasonForVisit, property of the request body.
- **`sponsor_user_id (string)`** – sponsorUserId, property of the request body.
- **`sponsor_user_name (string)`** – sponsorUserName, property of the request body.
- **`status (string)`** – status, property of the request body.
- **`status_reason (string)`** – statusReason, property of the request body.
- **`name`** – name path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_name*

delete_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_name*

reset_guest_user_password_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_id(id, headers=None, **query_parameters)`Alias for *`reinstate_guest_user_by_id`***`update_guest_user_email(id, portal_id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a guest user email by ID.

Parameters

- **`additional_data(list)`** – `additionalData`, property of the request body (list of objects).
- **`id(basestring)`** – `id` path parameter.
- **`portal_id(basestring)`** – `portalId` path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_email(id, portal_id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`Alias for *`update_guest_user_email`*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

Alias for *update_guest_user_sms*

deny_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deny a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deny_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deny_guest_user_by_id*

get_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.

- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_id*

delete_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_id*

get_guest_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users*

get_guest_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users_generator*

create_guest_user(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_user*

suspend_guest_user_by_id(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to suspend a guest user by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

suspend_by_id(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *suspend_guest_user_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the guest user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_guest_user(*operation_type=None*, *resource_media_type=None*, *headers=None*,
 payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_guest_user*

monitor_bulk_status_guest_user(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_guest_user*

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.1.0).

Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

Hotspot Guest Portal API provides the ability to create, read, update, delete and search hotspot guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Hotspot Guest Portal (default)	
id	String	No	Resource UUID, mandatory for update	b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	
description	String	No	Guests do not require username and password credentials to access the network, but you can optionally require an access code		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	

continues on next page

Table 10 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	HOTSPOTGUEST	
settings	List	No	Defines all of the settings groups available for a BYOD		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal	aa178bd0-8bff-11e6-996c-525400b48521	

continues on next page

Table 10 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• coaType	Enum	No	Allowed Values: COAREAU-THENTICATE, COATER-MINATE	COAREAU-THENTICATE	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• requireAccessCode	Boolean	No	Require the portal user to enter an access code. Only used in Hotspot portal	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 10 – continued from previous page

• require-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• authSuccessSettings	List	No			
• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUCCESSPAGE, ORIGINATINGURL, URL	AUTHSUCCESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		

continues on next page

Table 10 – continued from previous page

• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		
• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 10 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	
• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		

continues on next page

Table 10 – continued from previous page

• page-Back-ground-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	BYOD Portal		
• contact-Text	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			

continues on next page

Table 10 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_hotspot_portal`

```
get_hotspot_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                              sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the hotspot portals. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

create_hotspot_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_hotspot_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMapping API (version: 3.1.0).

Wraps the Identity Services Engine IPToSGTMapping API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping API allows the client to add, delete, update, search and deploy IP to SGT mapping.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	server1.cisco.com
id	String	No	Resource UUID, mandatory for update	
description	String	No		
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL		network_device_id
deployType	Enum	Yes	Allowed values: ALL, ND, NDG	ND
hostName	String	Mandatory if hostIp is empty		server1.cisco.com
sgt	String	Mandatory unless mappingGroup is set		sgt_id
hostIp	String	Mandatory if hostName is empty – valid IPL		
mappingGroup	String	Mandatory unless sgt and deployTo and deployType are set		

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all(*headers=None, **query_parameters*)

Alias for *deploy_all_ip_to_sgt_mapping*

get_deploy_status_ip_to_sgt_mapping(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status(*headers=None, **query_parameters*)

Alias for *get_deploy_status_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id, deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if hostName is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if hostIp is empty, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless sgt and deployTo and deployType are set, property of the request body.
- **name** (*string*) – name, property of the request body.

- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_by_id*

delete_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_ip_to_sgt_mapping_by_id***get_ip_to_sgt_mapping**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_generator`*

`create_ip_to_sgt_mapping`(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **`deploy_to`** (*string*) – Mandatory unless `mappingGroup` is set or unless `deployType=ALL`, property of the request body.
- **`deploy_type`** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **`host_ip`** (*string*) – Mandatory if `hostName` is empty -valid IP, property of the request body.
- **`host_name`** (*string*) – Mandatory if `hostIp` is empty, property of the request body.
- **`mapping_group`** (*string*) – Mapping Group Id. Mandatory unless `sgt` and `deployTo` and `deployType` are set, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt`** (*string*) – Mandatory unless `mappingGroup` is set, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None,
        name=None, sgt=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_ip_to_sgt_mapping*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_ip_to_sgt_mapping(operation_type=None, resource_media_type=None,
                                    headers=None, payload=None, active_validation=True,
                                    **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping*

monitor_bulk_status_ip_to_sgt_mapping(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group

class IpToSgtMappingGroup

Identity Services Engine IPToSGTMappingGroup API (version: 3.1.0).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping Group API allows the client to add, delete, update, search and deploy IP to SGT mapping groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		groupA
id	String	No	Resource UUID, mandatory for update		
description	String	No			
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL			net-work_device_id
deploy-Type	Enum	Yes	Allowed values: ALL, ND, NDG	ALL	
sgt	String	Mandatory unless mappingGroup is set			sgt_id

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_ip_to_sgt_mapping_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_ip_to_sgt_mapping_group_by_id`*

`update_ip_to_sgt_mapping_group_by_id(id, deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_ip_to_sgt_mapping_group_by_id`*

`get_ip_to_sgt_mapping_group`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_group`*

`get_ip_to_sgt_mapping_group_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_generator*

create_ip_to_sgt_mapping_group(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping_group*

monitor_bulk_status_ip_to_sgt_mapping_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.1.0).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

Identity Groups API allows the client to search identity groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added Create and GetByName operations

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	GuestType_Weekly (default)
id	String	No	Resource UUID, mandatory for update	9efe2310-8c01-11e6-996c-525400b48521
description	String	No		Identity group mirroring the guest type
parent	String	Yes		NAC Group:NAC:IdentityGroups:User Identity Groups

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_name***get_identity_group_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_id***update_identity_group_by_id**(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

get_identity_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups*

get_identity_groups_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

create_identity_group(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to identity group.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.1.0).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

Identity Sequence API allows the client to add, delete, update and search Identity sequences.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	All_User_ID_Stores
id	String	No	Resource UUID, mandatory for update	93246270-8c01-11e6-996c-525400b48521
description	String	No		A built-in Identity Sequence to include all User Identity Stores
breakOn-StoreFail	Boolean	Yes	Do not access other stores in the sequence If a selected identity store cannot be accessed for authentication	false
certificateAuthenticationProfile	String	Yes	Certificate Authentication Profile, empty if doesn't exist	Preloaded_Certificate_Profile
idSeqItem	List	Yes	List of id stores comprised of id store name and order	[{ "idstore": "Internal Users", "order": 1 }, { "idstore": "All_AD_Join_Points", "order": 2 }, { "idstore": "Guest Users", "order": 3 }]

get_identity_sequence_by_name(name, headers=None, **query_parameters)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

get_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

update_identity_sequence_by_id(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

delete_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_identity_sequence_by_id*

get_identity_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence*

get_identity_sequence_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.

- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

internal_user**class InternalUser**

Identity Services Engine InternalUser API (version: 3.1.0).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

Internal User API allows the client to add, delete, update and search internal users.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		b24b09e2-16f8-4e48-ace1-2c262a9449f1
description	String	No			description
changePassword	Boolean	Yes		true	
email	String	No			email@domain.com
enablePassword	String	No	EnablePassword field is added in ISE 2.0 to support T+		enablePassword
enabled	Boolean	Yes	Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled'		true
custom-Attributes	String	No	Key value map		{ "key1" : "value1" }
first-Name	String	No			firstName
identity-Groups	String	No	CSV of identity group IDs		identity-Groups
last-Name	String	No			lastName
password	String	No			password
passwordID-Store	String	Yes	The id store where the internal user's password is kept	Internal Users	
expiry-DateEnabled	Boolean	No		false	
expiry-Date	String	No	To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD'		2021-05-19

get_internal_user_by_name(name, headers=None, **query_parameters)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_name*

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.

- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_name*

delete_internal_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`

Alias for *`delete_internal_user_by_name`*

`get_internal_user_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an internal user by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_internal_user_by_id`*

```
update_internal_user_by_id(id, change_password=None, custom_attributes=None, description=None,
                           email=None, enable_password=None, enabled=None, expiry_date=None,
                           expiry_date_enabled=None, first_name=None, identity_groups=None,
                           last_name=None, name=None, password=None, password_idstore=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be ‘Enabled’ or ‘Disabled’. The values are case sensitive. For example, ‘[ERSObjectURL]?filter=enabled.EQ.Enabled’, property of the request body.
- **expiry_date** (*string*) – To store the internal user’s expiry date information. It’s format is = ‘YYYY-MM-DD’, property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_id*

get_internal_user(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user*

get_internal_user_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(change_password=None, custom_attributes=None, description=None, email=None,
        enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
        first_name=None, identity_groups=None, last_name=None, name=None, password=None,
        password_idstore=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for `create_internal_user`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the internal user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

mdm

class Mdm

Identity Services Engine MDM API (version: 3.1.0).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pwg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access.

Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_endpoints(*headers=None, **query_parameters*)

getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)

getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)

getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)

getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc

class Misc

Identity Services Engine Misc API (version: 3.1.0).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 MNT REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_mnt*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_active_count(*headers=None, **query_parameters*)

ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_active_list(headers=None, **query_parameters)`

ActiveList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_session_auth_list(headers=None, **query_parameters)`

Session/AuthList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_posture_count(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_count(*headers=None, **query_parameters*)

ProfilerCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac*, *headers=None*, ***query_parameters*)

Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_session_id(*session_id*, *headers=None*, ***query_parameters*)

Sessions by SessionID.

Parameters

- **session_id** (*basestring*) – session_id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_all_sessions(*headers=None*, ***query_parameters*)

Delete All Sessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_mnt_version(*headers=None, **query_parameters*)

MNT Version.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_failure_reasons(*headers=None, **query_parameters*)

FailureReasons.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_authentication_status_by_mac(*mac, records, seconds, headers=None, **query_parameters*)

AuthenticationStatus by MAC.

Parameters

- **mac** (*basestring*) – MAC path parameter.
- **seconds** (*basestring*) – SECONDS path parameter.
- **records** (*basestring*) – RECORDS path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_reauthentication_by_mac(*endpoint_mac, psn_name, reauth_type, headers=None, **query_parameters*)

Session Reauthentication by MAC.

Parameters

- **psn_name** (*basestring*) – PSN_NAME path parameter.
- **endpoint_mac** (*basestring*) – ENDPOINT_MAC path parameter.
- **reauth_type** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`session_disconnect`(*disconnect_type, endpoint_ip, mac, nas_ipv4, psn_name, headers=None, **query_parameters*)

Session Disconnect.

Parameters

- **`endpoint_ip`** (*basestring*) – ENDPOINT_IP path parameter.
- **`psn_name`** (*basestring*) – PSN_NAME path parameter.
- **`mac`** (*basestring*) – MAC path parameter.
- **`disconnect_type`** (*basestring*) – DISCONNECT_TYPE path parameter.
- **`nas_ipv4`** (*basestring*) – NAS_IPV4 path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_account_status_by_mac(*duration*, *mac*, *headers=None*, ***query_parameters*)

AccountStatus by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **duration** (*basestring*) – duration path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.1.0).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

My Device Portal API provides the ability to create, read, update, delete and search my device portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		My Devices Portal (default)
id	String	No	Resource UUID, mandatory for update		901f1b37-4a2f-46d9-8653-d925d2dde3aa
description	String	No			Default portal used by employees to register and manage their personal devices
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/mydevicesportal/PortalSetup
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	MYDEVICE	
settings	List	No	Defines all of the settings groups available for a Mydevice portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443

continues on next page

Table 11 – continued from previous page

• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal		aa178bd0-8bff-11e6-996c-525400b48521
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		
• max-FailedAttempts-BeforeRate-Limit	Integer	No	Maximum failed login attempts before rate limiting	5	

continues on next page

Table 11 – continued from previous page

• timeBetweenLoginsDuringRateLimit	Integer	No		2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK - ONPAGE, - ASLINK	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		

continues on next page

Table 11 – continued from previous page

• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• employeeChangePasswordSettings	List	No			
• allowEmployeeToChangePwd	Boolean	No	Allow employees to change their own passwords	false	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	

continues on next page

Table 11 – continued from previous page

• support-InfoSet-tings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		

continues on next page

Table 11 – continued from previous page

customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI

continues on next page

Table 11 – continued from previous page

• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			My Devices Portal
• contact-Text	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			

continues on next page

Table 11 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_my_device_portal_by_id*

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_my_device_portal_by_id*

get_my_device_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_my_device_portal`

```
get_my_device_portal_generator(filter=None, filter_type=None, page=None, size=None,
                                sortasc=None, sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_my_device_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

native_suppliant_profile

class NativeSupplicantProfile

Identity Services Engine NativeSupplicantProfile API (version: 3.1.0).

Wraps the Identity Services Engine NativeSupplicantProfile API and exposes the API as native Python methods that return native Python objects.

Native supplicant profile API provides the ability to update, delete and search native supplicant profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Cisco-ISE-NSP
id	String	No	Resource UUID, mandatory for update	b8ce01e6-b150-4d4e-9698-40e48d5e0197
description	String	No		Pre-configured Native Supplicant Profile. The SSID Will Need To Be Customized For Your Environment
wirelessProfiles	List	Yes	List of Wireless profiles	
• ssid	String	Yes	SSID for the wireless profile	ISE
• allowedProtocol	Enum	Yes	Allowed protocol for the wireless profile.	TLS
• certificateTemplateId	String	No	Certificate template ID	0ca8f1b6-500d-560b-e053-75189a0ab0d1
• actionType	Enum	Yes	Action type for WifiProfile.	UPDATE
• previousSsid	String	Yes	Previous ssid for WifiProfile (required for updating existing WirelessProfile)	ssid1

get_native_supPLICANT_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a native supplicant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_native_suppllicant_profile_by_id`***`update_native_suppllicant_profile_by_id(id, description=None, name=None, wireless_profiles=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a native suppllicant profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`wireless_profiles`** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_native_suppllicant_profile_by_id*

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native supplicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_native_suppllicant_profile_by_id*

get_native_suppllicant_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the native supplicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

`get_native_suppllicant_profile_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type*Generator***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native suppllicant profile.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rules*

create_network_access_authentication_rule(*policy_id*, *identity_source_name=None*,
if_auth_fail=None, *if_process_fail=None*,
if_user_not_found=None, *link=None*, *rule=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`get_network_access_authentication_rule_by_id`*

`update_network_access_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update rule.

Parameters

- **`identity_source_name(string)`** – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail(string)`** – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail(string)`** – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found(string)`** – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link(object)`** – link, property of the request body.
- **`rule(object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id(basestring)`** – policyId path parameter. Policy id.
- **`id(basestring)`** – id path parameter. Rule id.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

`delete_network_access_authentication_rule_by_id`(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete rule.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_authentication_rule_by_id*

network_access_authorization_exception_rules

class NetworkAccessAuthorizationExceptionRules

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_local_exception_rules(*policy_id, headers=None, **query_parameters*)

Network Access Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id, headers=None, **query_parameters*)

Alias for *get_network_access_local_exception_rules*

create_network_access_local_exception_rule(*policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.

- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_local_exception_rule*

reset_hit_counts_network_access_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_network_access_local_exceptions`***`get_network_access_local_exception_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Network Access Get local exception rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_network_access_local_exception_rule_by_id`***`update_network_access_local_exception_rule_by_id(id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_set_global_exception_rules(*headers=None, **query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_network_access_policy_set_global_exception_rules`

`create_network_access_policy_set_global_exception_rule(link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rule_by_id*

update_network_access_policy_set_global_exception_rule_by_id(*id*, *link=None*, *profile=None*,
rule=None,
security_group=None,
headers=None,
payload=None,
active_validation=True,
***query_parameters*)

Network Access Update global exception authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

delete_network_access_policy_set_global_exception_rule_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_global_exception_rule_by_id*

network_access_authorization_rules

class NetworkAccessAuthorizationRules

Identity Services Engine Network Access - Authorization Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rules*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

`reset_hit_counts_network_access_authorization_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authorization_rules*

get_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rule_by_id*

update_network_access_authorization_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

delete_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authorization_rule_by_id*

network_access_conditions

class NetworkAccessConditions

Identity Services Engine Network Access - Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_conditions(*headers=None*, ***query_parameters*)

Network Access Returns all library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions*

create_network_access_condition(*attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model `LibraryConditionAttributes` , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: `LibraryConditionAndBlock` or `LibraryConditionOrBlock` . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: `ConditionAttributes` , `ConditionAndBlock` , `ConditionOrBlock` , that represent dynamically built Conditions which are not stored in the conditions Library, or using `ConditionReference` , which includes an ID to existing stored condition in the library. The `LibraryCondition` models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (`ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock`), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using `ConditionReference` model in inner layers, the condition name is not required. `ConditionReference` objects can also include a reference ID to a condition of type `TimeAndDate`

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘`ConditionAndBlock`’, ‘`ConditionAttributes`’, ‘`ConditionOrBlock`’, ‘`ConditionReference`’, ‘`LibraryConditionAndBlock`’, ‘`LibraryConditionAttributes`’, ‘`LibraryConditionOrBlock`’ and ‘`TimeAndDateCondition`’.
- **dates_range** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.

- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
        dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
        dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
        is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_condition_by_name*

update_network_access_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_name*

delete_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_name*

get_network_access_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions_for_policy_sets*

get_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_network_access_condition_by_id*

update_network_access_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.

- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_id*

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_id*

network_access_dictionary

class NetworkAccessDictionary

Identity Services Engine Network Access - Dictionary API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries(*headers=None*, ***query_parameters*)

Get all Dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries*

create_network_access_dictionaries(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_dictionaries*

get_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

GET a dictionary by name.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_network_access_dictionary_by_name*

update_network_access_dictionary_by_name(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_by_name*

delete_network_access_dictionary_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_access_dictionary_by_name`*

network_access_dictionary_attribute**class NetworkAccessDictionaryAttribute**

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

`get_network_access_dictionary_attributes_by_dictionary_name`(*dictionary_name*,
headers=None,
***query_parameters*)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **`dictionary_name`** (*basestring*) – `dictionaryName` path parameter. the name of the dictionary the dictionary attribute belongs to.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

create_network_access_dictionary_attribute(*dictionary_name*, *allowed_values=None*,
data_type=None, *description=None*,
direction_type=None, *id=None*, *internal_name=None*,
name=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute's name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

```
update_network_access_dictionary_attribute_by_name(dictionary_name, name,
                                                    allowed_values=None, data_type=None,
                                                    description=None, direction_type=None,
                                                    id=None, internal_name=None,
                                                    headers=None, payload=None,
                                                    active_validation=True,
                                                    **query_parameters)
```

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.
- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_attribute_by_name*

network_access_dictionary_attributes_list

class NetworkAccessDictionaryAttributesList

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries_authentication(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authentication*

get_network_access_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_authorization***get_network_access_dictionaries_policy_set**(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_policy_set***network_access_identity_stores****class NetworkAccessIdentityStores**

Identity Services Engine Network Access - Identity Stores API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_network_access_identity_stores(*headers=None, **query_parameters*)

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_identity_stores*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for `get_network_access_network_conditions`

create_network_access_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_network_condition_by_id*

update_network_access_network_condition_by_id(*id, condition_type=None, conditions=None, description=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_network_condition_by_id*

delete_network_access_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_network_access_network_condition_by_id***network_access_policy_set****class NetworkAccessPolicySet**

Identity Services Engine Network Access - Policy Set API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_sets(*headers=None*, ***query_parameters*)

Get all network access policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)Alias for *get_network_access_policy_sets***create_network_access_policy_set**(*condition=None*, *default=None*, *description=None*, *hit_counts=None*, *id=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set*

reset_hit_counts_network_access_policy_sets(*headers=None, **query_parameters*)

Network Access Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_policy_sets*

get_network_access_policy_set_by_id(*id, headers=None, **query_parameters*)

Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_network_access_policy_set_by_id`*
`update_network_access_policy_set_by_id(id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update a policy set.

Parameters

- **`condition`** (*object*) – condition, property of the request body.
- **`default`** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **`description`** (*string*) – The description for the policy set, property of the request body.
- **`hit_counts`** (*integer*) – The amount of times the policy was matched, property of the request body.
- **`id`** (*basestring*) – Identifier for the policy set, property of the request body.
- **`is_proxy`** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **`rank`** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **`service_name`** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **`state`** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'disabled', 'enabled' and 'monitor'.
- **`id`** – id path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_by_id*

delete_network_access_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_by_id*

network_access_profiles

class NetworkAccessProfiles

Identity Services Engine Network Access - Profiles API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

get_network_access_profiles(*headers=None*, ***query_parameters*)

Network Access Returns list of authorization profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_security_groups*

network_access_service_names

class NetworkAccessServiceNames

Identity Services Engine Network Access - Service Names API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

get_network_access_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_network_access_service_names***network_access_time_date_conditions****class NetworkAccessTimeDateConditions**

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_time_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_time_conditions*

create_network_access_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
        dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
        dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
        is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_access_time_condition*

get_network_access_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_time_condition_by_id*

update_network_access_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_time_condition_by_id*

delete_network_access_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_time_condition_by_id*

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.1.0).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

Network Device API allows the client to add, delete, update, and search network devices. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	2.0	Cisco ISE 2.0 model changes for TACACS+ and 3rd-Party support	tacacsSet- tings:sharedSecret	Added Attribute 'shared-Secret' for Tacacs+ sup- port
				tacacsSet- tings:connectModeOptions	Added Attribute 'connect- ModeOptions' for Tacacs+ support
				profileName	Added Attribute 'profile- Name' for 3rd-Party sup- port support
				coaPort	Added Attribute 'coaPort' for 3rd-Party support sup- port
2	1.2	2.4	Cisco ISE 2.4 model changes for Multi shared secret and DTLS Required support	authenticationset- tings:enableMultiSecret	Added Attribute 'enable- MultiSecret' for multiple shared secret
				authenticationset- tings:secondRadiusSharedSecret	Added Attribute 'secon- dings:SharedSecret' for multiple shared secret
				authenticationset- tings:dtlsRequired	Added Attribute 'dtlsRe- quired' for dtls settings

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		ISE_EST_Local_Host
id	String	No	Resource UUID, mandatory for update		79aac430-7cc8-11eb-ad58-005056926583
description	String	No			example nd
authentication-Settings	List	Yes			
• enableKey-Wrap	Boolean	Yes			false
• enabled	Boolean	Yes		false	
• keyEncryption-Key	String	Yes			1234567890123456
• keyInput-Format	Enum	Yes	Allowed values: ASCII, HEXADECIMAL	ASCII	
• messageAuthenticator-CodeKey	String	No			12345678901234567890
• networkProtocol	Enum	No	Allowed values: RADIUS, TACACS_PLUS	RADIUS	
• radiusShared-Secret	String	No			VHEGKOC-CUHYB
• enable-MultiSecret	Boolean	No			false

continues on next page

Table 12 – continued from previous page

• sec- ondRa- diusShared- Secret	String	No			
• dtlsRe- quired	Boolean	No	This value enforces use of dtls	false	
coaPort	Integer	Yes	Since 2.0 (for 3rd party)		0
dtlsDnsName	String	No	This value is used to verify the client identity contained in the X.509 RA-DIUS/DTLS client certificate		ISE213.il.com
NetworkDevi- ceIPList	List	Yes	List of IP Subnets for this node		
• ipaddress	String	Yes	It can be either single IP address or IP range address		127.0.0.1
• getIpad- dressEx- clude	String	Yes	It can be either single IP address or IP range address		
• mask	Integer	Yes			32
NetworkDe- viceGroupList	List	No	List of Net- work Device Group names for this node		[“Loca- tion#All Loca- tions”, “Device Type#All De- vice Types”]
modelName	String	No			
softwareVer- sion	String	No			
profileName	String	Yes	Since 2.0 (for 3rd party)	true	Cisco
snmpsettings	List	Yes			

continues on next page

Table 12 – continued from previous page

• linkTrap-Query	Boolean	Yes	SNMP link Trap Query	true	
• macTrap-Query	Boolean	Yes	SNMP MAC Trap Query	true	
• originat-ingPol-icySer-vicesNode	String	Yes	Originating Policy Services Node	Auto	
• polling-Interval	Integer	Yes	SNMP Polling Interval in seconds (Valid Range 600 to 86400)	3600	
• roCom-munity	String	No	SNMP RO Community		aaa
• version	Enum	No	Allowed values: ONE, TWO_C, THREE		ONE
tacacsSettings	List	Yes	Since 2.0 (for Tacacs+)		
• connect-ModeOp-tions	Enum	No	Allowed values: OFF, ON_LEGACY, ON_DRAFT_COMPLIANT		ON_LEGACY
• sharedSe-cret	String	Yes	Since 2.0		aaa
trustsecsettings	List	Yes			
• de-viceAu-thentica-tionSet-tings	List	Yes			
• sgaDevi-ceId	String	No			networkDe-vice1

continues on next page

Table 12 – continued from previous page

• sgaDevicePassword	String	No			aaa
• device-ConfigurationDeployment	List	Yes			
• enable-Mode-Password	String	No			aaa
• exec-Mode-Password	String	No			aaa
• exec-ModeUsername	String	No			aaa
• include-WhenDeployingSGTUpdates	Boolean	No		false	
• sgaNotificationAndUpdates	List	Yes			
• downloadEnvironmentDataEveryXSeconds	Integer	No		86400	

continues on next page

Table 12 – continued from previous page

• downloadPeer-Autho-rization-PolicyEveryXSec-onds	Integer	No		86400	
• download-SGA-CLList-sEveryXSec-onds	Integer	No		86400	
• otherS-GADe-vices-ToTrust-ThisDe-vice	Boolean	No		false	
• reAu-thentica-tionEveryXSec-onds	Integer	No		86400	
• sendCon-figura-tionToDe-vice	Boolean	No		false	
• sendCon-figura-tionToDe-viceUsing	Enum	No	Allowed values: EN-ABLE_USING_COA, EN-ABLE_USING_CLI, DIS-ABLE_ALL	EN-ABLE_USING_COA	

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.

- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *delete_network_device_by_name***get_network_device_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_network_device_by_id*

update_network_device_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
              model_name=None, name=None, network_device_group_list=None,
              network_device_ip_list=None, profile_name=None, snmpsettings=None,
              software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None,
              payload=None, active_validation=True, **query_parameters)
```

Alias for *update_network_device_by_id*

```
delete_network_device_by_id(id, headers=None, **query_parameters)
```

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_network_device_by_id*

```
get_network_device(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                    headers=None, **query_parameters)
```

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device*

get_network_device_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).

- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
        model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None,
        profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None,
        trustsecsettings=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_device*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group**class NetworkDeviceGroup**

Identity Services Engine NetworkDeviceGroup API (version: 3.1.0).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

Network Device Group API allows the client to search network device groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.3	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Device Type#All Device Types
id	String	No	Resource UUID, mandatory for update	70c79c30-8bff-11e6-996c-525400b48521
description	String	No		All Device Types
other-name	String	No		Device Type

get_network_device_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_name*

get_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_id*

update_network_device_group_by_id(*id*, *description=None*, *name=None*, *othername=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id(id, description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *`update_network_device_group_by_id`*

`delete_network_device_group_by_id(id, headers=None, **query_parameters)`

This API deletes a network device group.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_network_device_group_by_id`*

get_network_device_group(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group*

```
get_network_device_group_generator(filter=None, filter_type=None, page=None, size=None,
                                     sortasc=None, sortdsc=None, headers=None,
                                     **query_parameters)
```

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_deployment**class NodeDeployment**

Identity Services Engine Node Deployment API (version: 3.1.0).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

APIs for the configuration, administration and monitoring of the nodes in an ISE cluster deployment.

`get_nodes`(*headers=None, **query_parameters*)

Discovers all deployment nodes in the cluster. It provides basic information about each of deployed nodes in the cluster like Hostname, personas, status, roles and services. .

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
register_node(administration=None, fdqn=None, general_settings=None, password=None,  
              profile_configuration=None, user_name=None, headers=None, payload=None,  
              active_validation=True, **query_parameters)
```

Register ISE node to form a multi-node deployment .

Parameters

- **administration** (*object*) – administration, property of the request body.
- **fdqn** (*string*) – fdqn, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **general_settings** (*object*) – generalSettings, property of the request body.
- **password** (*string*) – password, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **user_name** (*string*) – userName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
promote_node(promotion_type=None, headers=None, payload=None, active_validation=True,  
              **query_parameters)
```

Changes the cluster setting by promoting a node to primary when executed on standalone or secondary node. It could also be used to convert a deployment node to standalone node. .

Parameters

- **promotion_type** (*string*) – promotionType, property of the request body. Available values are 'SECONDARY_TO_PRIMARY', 'STANDALONE_TO_PRIMARY' and 'TO_STANDALONE'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(*hostname*, *headers=None*, ***query_parameters*)

It provides detailed information of the deployed node in the cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*hostname*, *headers=None*, ***query_parameters*)

Alias for *get_node_details*

```
update_node(hostname, general_settings=None, profile_configuration=None, headers=None,
            payload=None, active_validation=True, **query_parameters)
```

Updates the deployed ISE node with the information provided .

Parameters

- **general_settings** (*object*) – generalSettings, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_node(hostname, headers=None, **query_parameters)
```

The de-register ednode becomes a standalone Cisco ISE node. It retains the last configuration that it received from the PrimaryPAN and assumes the default personas of a standalone node that are Administration, PolicyService, and Monitoring. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. node name of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_group**class NodeGroup**

Identity Services Engine Node Group API (version: 3.1.0).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

APIs for the configuration, administration and monitoring of the nodes in an ISE cluster deployment.

`get_node_groups(headers=None, **query_parameters)`

Get details of all the node groups in the cluster. To detect node failure and to reset all URL-redirceted sessions on the failed node, two or more Policy Service nodes can be placed in the same node group. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all URL-redirceted sessions on the failed node.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

Get details of a node group in the cluster.

Parameters

- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*node_group_name*, *description=None*, *mar_cache=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Developers need to create node group in the system. Node Group is a group of PSNs, mainly used for terminating posture pending sessions when a PSN in local node group fails. Node group members can communicate over TCP/7800.

Parameters

- **description** (*string*) – description, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **mar_cache** (*object*) – mar-cache, property of the request body.
- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_node_group(*node_group_name, description=None, mar_cache=None, headers=None, payload=None, active_validation=True, **query_parameters*)

API updates an existing node group in the system.

Parameters

- **`description`** (*string*) – description, property of the request body. Constraints: `maxLength` set to 256 and `minLength` set to 1.
- **`mar_cache`** (*object*) – mar-cache, property of the request body.
- **`node_group_name`** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

Developers need to delete node group in the system.

Parameters

- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_details

class NodeDetails

Identity Services Engine NodeDetails API (version: 3.1.0).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

Node Details API allows the client to get deployment node details, get all nodes and filter nodes based on NodeServiceTypes.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Ver- sion		
1	1.1	2.4	Support Node Service Types as part of Node Object	NodeSer- viceTypes	Added String Field NodeServiceTypes. String represents services configured on the Node
2	1.2	2.7	Support Node FQDN as part of Node Object	fqdn	Added String Field FQDN. String rep- resents FQDN of the Node
3	1.3	3.0	Support SXP IP Ad- dress as part of Node Details	sxpIpAd- dress	Added String Field sxpIpAddress. String represents SXP IP Address of the Node

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577- 0014737c8fcf
description	String	No		
gateWay	String	No		10.0.10.11
displayName	String	No		TestNode
inDeployment	Boolean	No		false
ipAddresses	String	No		[“10.0.0.1”, “10.0.0.2”]
otherPapFqdn	String	No		OtherTestNode
ipAddress	String	No		10.0.0.3
sxpIpAddress	String	No		10.10.10.1
nodeService- Types	String	No		DEVICE ADMIN
fqdn	String	No		test.ers.cisco.com
primaryPapN- ode	Boolean	No		true
papNode	Boolean	No		true
pxGridNode	Boolean	No		true

get_node_detail_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_name*

`get_node_detail_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the node details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.1.0).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

APIs for the configuration, administration and monitoring of the nodes in an ISE cluster deployment.

get_pan_ha_status(*headers=None, **query_parameters*)

In a high availability configuration, the Primary Administration Node (PAN) is in the active state. The Secondary PAN (backup PAN) is in the standby state, which means it receives all configuration updates from the Primary PAN, but is not active in the ISE network. You can configure ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

enable_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or a combination of these. If the PANs are in different data centers, you must have a health check node for each PAN.

Parameters

- **failed_attempts** (*integer*) – failedAttempts, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **polling_interval** (*integer*) – pollingInterval, property of the request body.
- **primary_health_check_node** (*string*) – primaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **secondary_health_check_node** (*string*) – secondaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

disable_pan_ha(*headers=None, **query_parameters*)

Disable the automatic PAN failover.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting

class PortalGlobalSetting

Identity Services Engine PortalGlobalSetting API (version: 3.1.0).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

The Portal Global Setting API allows the user to customize the text that is displayed in the Cisco ISE portals. This global setting controls whether HTML alone or both HTML and Javascript are permitted to be used in customized text.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
id	String	Yes	Resource UUID value	21013cb2-d030-4fb1-9ba2-35757634d770
cus-tomization	Enum	Yes	Allowed values: HTML, HTMLAND-JAVASCRIPT	HTML

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ****query_parameters**)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

get_portal_global_settings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_theme

class PortalTheme

Identity Services Engine PortalTheme API (version: 3.1.0).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

Portal Theme API allows the client to add, delete, update and search Portal Theme among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Blue theme
id	String	No	Resource UUID, mandatory for update	9eb421c0-8c01-11e6-996c-525400b48521
description	String	No		
theme-Data	String	Yes	Portal Theme for all portals	Base 64 encoded string of CSS file

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_portal_theme_by_id***update_portal_theme_by_id**(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_theme_by_id*

delete_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_portal_theme_by_id*

get_portal_themes(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

get_portal_themes_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes_generator*

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_portal_theme*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler

class Profiler

Identity Services Engine Profiler API (version: 3.1.0).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pwg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_profiles(*headers=None*, ***query_parameters*)

getProfiles.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler_profile

class ProfilerProfile

Identity Services Engine ProfilerProfile API (version: 3.1.0).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

Profiler Profile API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	2Wire-Device
id	String	No	Resource UUID, mandatory for update	fe8c7cc0-8bff-11e6-996c-525400b48521
description	String	No		Policy for 2Wire-Device
parentId	String	Yes		

get_profiler_profile_by_id(id, headers=None, **query_parameters)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_profiler_profile_by_id***get_profiler_profiles**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_profiler_profiles_generator`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.1.0).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

register_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reregister_service(headers=None, **query_parameters)`

ServiceReregister.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`authorization(headers=None, **query_parameters)`

Authorization.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service**class PsnNodeDetailsWithRadiusService**

Identity Services Engine `PsnNodeDetailsWithRadiusService` API (version: 3.1.0).

Wraps the Identity Services Engine `PsnNodeDetailsWithRadiusService` API and exposes the API as native Python methods that return native Python objects.

PSN Node Details with RADIUS Service API allows the client to get deployment node details where 'Session Services' is enabled.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No		PSN with Session Service
ipAddress	String	Yes		10.0.0.1

`get_session_service_node_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_id*

get_session_service_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node*

get_session_service_node_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

pull_deployment_info

class PullDeploymentInfo

Identity Services Engine PullDeploymentInfo API (version: 3.1.0).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

Pull Deployment Info API allows clients to get the complete information about a Cisco ISE deployment. The information includes details about the deployment, network access, NADs, MDMs, licenses, posture and profiler.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.7	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description
name	String	Yes	Resource Name
id	String	No	Resource UUID, mandatory for update
description	String	No	
networkAccessInfo	List	No	networkAccessInfo Details
• deploymentID	String	Yes	Deployment ID
• isCsnEnabled	Boolean	Yes	false
• nodeList	List	Yes	Node list

continues on next page

Table 13 – continued from previous page

• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• sdaVNs	List	No	
• trustSecControl	String	No	ISE
• radius3RdParty	List	No	
profilerInfo	List	No	profilerInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Includes 'profiles' which is an array of dictionaries describing various attributes with the properties:- profile (List), - customProfilesCount (Integer), - endpointTypes (String), - totalProfilesCount (Integer), - uniqueEndpointsCount (Integer), - unknownEndpointsCount (Integer), - totalEndpointsCount (Integer), - unknownEndpointsPercentage (Integer)
deploymentInfo	List	No	deploymentInfo Details
• deploymentID	String	Yes	Deployment ID

continues on next page

Table 13 – continued from previous page

• versionHistoryInfo	List	No	Array of dictionaries describing various attributes with the properties:- opType (String), - mainVersion (String), - epochTime (Integer)
• nodeList	List	Yes	Node list
• nodeAndNode-CountAnd-CountInfo	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• fipsstatus	String	No	Disabled
nadInfo	List	No	nadInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declaredType (String), - scope (String), - value (List), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• nadcountInfo	List	No	
• totalActiveNAD-Count	Integer	No	0
mdmInfo	List	No	mdmInfo Details

continues on next page

Table 13 – continued from previous page

• activeMdmServersCount	Integer	Yes	0
• activeDesktopMdmServersCount	Integer	Yes	0
• activeMobileMdmServersCount	Integer	Yes	0
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
licensesInfo	List	No	licensesInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
postureInfo	List	No	postureInfo Details

continues on next page

Table 13 – continued from previous page

• content	List	Yes	Array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
kongInfo	List	No	kongInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Array of dictionaries describing various attributes with the properties:- sn (String), - service (List)

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **timeout** (*float*, *tuple*) – How long to wait for the server to send data before giving up.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings

class PxGridSettings

Identity Services Engine PxGridSettings API (version: 3.1.0).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

pxGrid Settings API allows the client to change auto-approve settings for pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for up- date		
description	String	No			
autoApproveCert- BasedAccounts	Boolean	Yes	Auto approve certificate based ac- counts when true	false	true
allowPassword- BasedAccounts	Boolean	Yes	Allow password based acoounts when true	false	

autoapprove_px_grid_settings(*allow_password_based_accounts=None*,
auto_approve_cert_based_accounts=None, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

autoapprove(*allow_password_based_accounts=None*, *auto_approve_cert_based_accounts=None*,
headers=None, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *autoapprove_px_grid_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.1.0).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxe*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_failures(*headers=None, **query_parameters*)

getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.1.0).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

RADIUS Server Sequence API allows the client to add, delete, update, search and perform actions on RADIUS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.3	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			description
stripPrefix	Boolean	No		false	
stripSuffix	Boolean	No		false	
prefixSeparator	String	No	The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character		
suffixSeparator	String	No	The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character	@	
remoteAccounting	Boolean	No		true	
localAccounting	Boolean	No		false	
useAttrSetOnRequest	Boolean	No		false	
useAttrSetBeforeAcc	Boolean	No		false	
continueAuthorzPolicy	Boolean	No		false	
radiusServers	List	Yes	List with names of external radius server. The order of the names in the list is the order of servers that will be used during authentication		[“externalRadiusServer1”, “externalRadiusServer2”]
onRequestAttrManipulators	List	No	The onRequestAttrManipulators is required only if useAttrSetOnRequest is true		
<ul style="list-style-type: none"> Attribute-Manipulator 	List	No			
<ul style="list-style-type: none"> action 	Enum	Yes	Allowed Values: ADD,		ADD

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).

- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list*=None, *continue_authorz_policy*=None, *description*=None, *local_accounting*=None, *name*=None, *on_request_attr_manipulator_list*=None, *prefix_separator*=None, *radius_server_list*=None, *remote_accounting*=None, *strip_prefix*=None, *strip_suffix*=None, *suffix_separator*=None, *use_attr_set_before_acc*=None, *use_attr_set_on_request*=None, *headers*=None, *payload*=None, *active_validation*=True, ****query_parameters**)

Alias for [*update_radius_server_sequence_by_id*](#)

delete_radius_server_sequence_by_id(*id*, *headers*=None, ****query_parameters**)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ****query_parameters**)

Alias for [*delete_radius_server_sequence_by_id*](#)

get_radius_server_sequence(*page*=None, *size*=None, *headers*=None, ****query_parameters**)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence***`get_radius_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence_generator*

```
create_radius_server_sequence(before_accept_attr_manipulators_list=None,
                             continue_authorz_policy=None, description=None,
                             local_accounting=None, name=None,
                             on_request_attr_manipulator_list=None, prefix_separator=None,
                             radius_server_list=None, remote_accounting=None,
                             strip_prefix=None, strip_suffix=None, suffix_separator=None,
                             use_attr_set_before_acc=None, use_attr_set_on_request=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API creates a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.1.0).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

REST ID Store API allows clients to add, get, update and delete REST ID stores.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	RestIdStore1
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		Object that represents the restID store
restIdStoreAttributes	List	Yes	Holds the attributes of the restID object	
• username-Suffix	String	Yes	Suffix of the user-name domain	@place.com
• rootUrl	String	Yes	url of the root of the RestIDStore	rootUrl
• predefined	Enum	Yes	The cloud provider connected to of the RestIDStore. Options are: - Azure, - Okta, - None	Azure
• headers	List	Yes	Headers for the RestIDStore	
• key	String	Yes	Key of the header	tenantID
• value	String	Yes	Value of the header	tenantID_value

get_rest_id_store_by_name(name, headers=None, **query_parameters)

This API allows the client to get a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_name*

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_name*

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store*

get_rest_id_store_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

replication_status

class ReplicationStatus

Identity Services Engine Replication Status API (version: 3.1.0).

Wraps the Identity Services Engine Replication Status API and exposes the API as native Python methods that return native Python objects.

APIs for the configuration, administration and monitoring of the nodes in an ISE cluster deployment.

get_node_replication_status(*node*, *headers=None*, ***query_parameters*)

Retrives replication status of a node.

Parameters

- **node** (*basestring*) – node path parameter. ID of the existing node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.1.0).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None*, ***query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_repositories*

`create_repository`(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **`enable_pki`** (*boolean*) – enablePki, property of the request body.
- **`name`** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **`password`** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **`path`** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **`protocol`** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **`server_name`** (*string*) – serverName, property of the request body.
- **`user_name`** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_repository*

`get_repository`(*name, headers=None, **query_parameters*)

Get a specific repository identified by the name passed in the URL. .

Parameters

- **`name`** (*basestring*) – name path parameter. Unique name for a repository.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name, headers=None, **query_parameters*)

Alias for *get_repository*

`update_repository`(*name, enable_pki=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*basestring*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **name** – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *enable_pki=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_repository*

delete_repository(*name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_files(*name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider

class SmsProvider

Identity Services Engine SMSProvider API (version: 3.1.0).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

SMS Provider API allows the client to search the SMS providers configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		

get_sms_provider(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider*

get_sms_provider_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sxp_connections**class SxpConnections**

Identity Services Engine SXPConnections API (version: 3.1.0).

Wraps the Identity Services Engine SXPConnections API and exposes the API as native Python methods that return native Python objects.

SXP Connections API allows clients to add, get, update and delete the Security Group Tag (SGT) Exchange Protocol (SXP) connections.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	sxpVpn	Attribute can include some VPNs separated by comma

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		Brief description about network peer
sxpPeer	String	Yes		Sxp Peer Name
sxpVpn	String	Yes		Sxp VPN Name
sxpNode	String	Yes		Sxp Node Name
ipAddress	String	Yes		Sxp Peer IP address
sxpMode	String	Yes		Sxp Mode
sxpVersion	String	Yes		Sxp Version
enabled	Boolean	Yes		true

get_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_connections_by_id*

delete_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP connection.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_connections_by_id*

get_sxp_connections(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

create_sxp_connections(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None,
        sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_sxp_connections*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_sxp_connections(operation_type=None, resource_media_type=None,
                                  headers=None, payload=None, active_validation=True,
                                  **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_connections*

sxp_local_bindings

class SxpLocalBindings

Identity Services Engine SXPLocalBindings API (version: 3.1.0).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

SXP Local Bindings API allows clients to add, get, update and delete SGT static mappings.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	vns	Added new property for the Virtual Networks

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
binding-Name	String	No	This field is deprecated from Cisco ISE 3.0	
ipAddressOrHost	String	Yes	IP address for static mapping (hostname is not supported)	ipAddressOrHost
sgt	String	Yes	SGT name or ID	sgt_id
sxpVpn	String	Yes	List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined	Sxp Vpn Name
vns	String	Yes	List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined	virtualNetwork

get_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_local_bindings_by_id*

update_sxp_local_bindings_by_id(*id*, *binding_name=None*, *description=None*,
ip_address_or_host=None, *sgt=None*, *sxp_vpn=None*, *vns=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *binding_name=None*, *description=None*, *ip_address_or_host=None*, *sgt=None*, *sxp_vpn=None*, *vns=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_local_bindings_by_id*

delete_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP local binding.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

```
get_sxp_local_bindings_generator(filter=None, filter_type=None, page=None, size=None,
                                   sortasc=None, sortdsc=None, headers=None,
                                   **query_parameters)
```

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

create_sxp_local_bindings(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None,
        sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_sxp_local_bindings*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_sxp_local_bindings(operation_type=None, resource_media_type=None,
                                     headers=None, payload=None, active_validation=True,
                                     **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_local_bindings*

monitor_bulk_status_sxp_local_bindings(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_local_bindings*

sxp_vpns

class SxpVpns

Identity Services Engine SXPVPNs API (version: 3.1.0).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

SXP VPNs API allows clients to add, get and delete SXP VPNs (SXP Domains).

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	ef36ca16-0cf7-4806-b2a9-6f547cfe4805
description	String	No		
sxpVpnName	String	Yes		default

get_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_vpn_by_id*

delete_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP VPN.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_vpn_by_id*

get_sxp_vpns(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – sxpVpnName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create(sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for `create_sxp_vpn`

`get_version(headers=None, **query_parameters)`

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_vpns(operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to submit the bulk request.

Parameters

- **`operation_type(string)`** – operationType, property of the request body.

- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_vpns*

monitor_bulk_status_sxp_vpns(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_xp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

SGT mapping to virtual networks are mapped to referenced vlan. These constructs come from out side of Cisco ISE and are not CRUDable inside Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.3	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No		description
sgtId	String	No		sgt_id
virtual-network-list	List	No	Includes 'vlans' which is an array of dictionaries describing various attributes with the properties: - id (String), - name (String), - description (String), - defaultVlan (Boolean), - max-Value (Integer), - data (Boolean)	<pre> { "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "virtual1", "description": "description", "defaultVirtualNetwork": false, "vlans": [{ "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "vlan1", "description": "description1", "defaultVlan": true, "maxValue": 1882725260, "data": true }] }</pre>

get_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

update_security_groups_to_vn_to_vlan_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_security_groups_to_vn_to_vlan_by_id`*

`delete_security_groups_to_vn_to_vlan_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL to virtual network.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_security_groups_to_vn_to_vlan_by_id`*

get_security_groups_to_vn_to_vlan(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan*

get_security_groups_to_vn_to_vlan_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_generator*

create_security_groups_to_vn_to_vlan(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_to_vn_to_vlan*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_groups_to_vn_to_vlan`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_security_groups_to_vn_to_vlan`*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

SGT API allows the client to search SGTs.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	1.4	Cisco ISE 1.4 model changes	isTagFromRange	Removed Attribute isTagFromRange - deprecated - set to FALSE value by default
2	1.2	2.3	Cisco ISE 2.3 model changes	propagateToApic	Added Boolean Attribute propagateToApic - By default value is false
3	1.3	2.7	Cisco ISE 2.7 model changes	isReadOnly	Added Boolean Attribute isReadOnly - By default value is false
				defaultSGACLs	Added List Attribute defaultSGACLs

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Employees
id	String	No	Resource UUID, mandatory for update		93ad6890-8c01-11e6-996c-525400b48521
description	String	No			Employee Security Group
value	Integer	Yes	Value range: 2 to 65519 or -1 to auto-generate		4
propagateToApic	Boolean	No			true
isReadOnly	Boolean	No		false	
defaultSGACLs	List	No			[]
propagateToApic	Boolean	No			true
generationId	Integer	No			0

get_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for `get_security_group_by_id`
`update_security_group_by_id(id, default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a security group.

Parameters

- **`default_sgacIs`** (*list*) – defaultSGACLs, property of the request body (list of objects).
- **`description`** (*string*) – description, property of the request body.
- **`generation_id`** (*string*) – generationId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`is_read_only`** (*boolean*) – isReadOnly, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`propogate_to_apic`** (*boolean*) – propogateToApic, property of the request body.
- **`value`** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

get_security_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups*

get_security_groups_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*

create_security_group(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 to 65519 or -1 to auto- generate, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None,
        propagate_to_apic=None, value=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_security_group*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_group`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_security_group`*

monitor_bulk_status_security_group(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

Security Groups ACLs API allows the client to search security groups access control lists.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	2.3	Introducing bulk operations		
2	1.2	3.1	Cisco ISE 3.1 model changes	modelledContent	Adding modelled content from Cisco ISE 3.1

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Permit IP
id	String	No	Resource UUID, mandatory for update		92951ac0-8c01-11e6-996c-525400b48521
description	String	No			Permit IP SGACL
ACLContent	String	No			permit ip
ipVersion	Enum	Yes	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	
isRead-Only	Boolean	No		false	
generationId	String	No	GenerationId is a read only attribute and is being generated by the server		0
modelled-Content	List	No	Modelled content of contract		

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for `get_security_groups_acl_by_id`
`update_security_groups_acl_by_id(id, aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a security group ACL.

Parameters

- **`aclcontent`** (*string*) – aclcontent, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`generation_id`** (*string*) – generationId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`ip_version`** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **`is_read_only`** (*boolean*) – isReadOnly, property of the request body.
- **`modelled_content`** (*object*) – Modelled content of contract, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_acl_by_id*

delete_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl*

get_security_groups_acl_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.

- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_groups_acl`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_security_groups_acl`*

monitor_bulk_status_security_groups_acl(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_groups_acl*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.1.0).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

Self Registered Guest Portal API provides the ability to create, read, update, delete and search self registered portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Self-Registered Guest Portal (default)
id	String	No	Resource UUID, mandatory for update		4e8ade36-4048-472a-b345-632cc155acfc
description	String	No			Guests may create their own accounts and be assigned a username and password, or use their social login to access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?portalId=4048-472a-b345-632cc155acfc
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDE-VICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SELF-REGGUEST	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		

continues on next page

Table 14 – continued from previous page

• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on.		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• authentication-Method	String	Yes	Unique Id of the identity source sequence		92e50f80-8c01-11e6-996c-525400b48521
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type		Contractor (default)
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 14 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireAccessCode	Boolean	No	Require the portal user to enter an access code	false	
• accessCode	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		

continues on next page

Table 14 – continued from previous page

• al- lowGuest- ToCre- ateAc- counts	Boolean	No		false	
• al- lowGuest- ToChangePass- word	Boolean	No	Require the portal user to enter an access code	false	
• al- lowAlter- nateGuest- Portal	Boolean	No			false
• alter- nateGuest- Portal	String	No			
• selfReg- PageSet- tings	List	No			
• as- signGuest- sToGuest- Type	String	No	Guests are as- signed to this guest type		
• account- Validity- Duration	Integer	No	Self-registered guest account is valid for this many ac- count_validity_time_units	1	
• account- Validity- TimeU- nits	Enum	No	Time units for ac- count_validity_duration.	DAYS	
• requir- eReg- istra- tionCode	Boolean	No	Self-registered guests are re- quired to enter a registration code	false	

continues on next page

Table 14 – continued from previous page

• registrationCode	String	No	The registration code that the guest user must enter		
• fieldUserName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldFirstName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLastName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldEmailAddr	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldPhoneNo	List	No			
• include	Boolean	No			true

continues on next page

Table 14 – continued from previous page

• require	Boolean	No	Only applicable if include = true		false
• field-Company	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLocation	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectable-Locations	List	No	Guests can choose from these locations to set their time zone		[“San Jose”]
• fieldSmsProvider	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableSmsProviders	List	No	This attribute is an array of SMS provider names		[“Global Default”]
• fieldPersonBeingVisited	List	No			

continues on next page

Table 14 – continued from previous page

• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• field-Reason-ForVisit	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• enableGuestEmailWhitelist	Boolean	No	Allow guests with an email address from selected domains	false	

continues on next page

Table 14 – continued from previous page

• guestEmail-Whitelist-Domains	List	No	Self-registered guests whose e-mail address is in one of these domains will be allowed. Only valid if enableGuestEmail-Whitelist = true		
• enableGuestEmail-Blacklist	Boolean	No	Disallow guests with an e-mail address from selected domains	false	
• guestEmail-Blacklist-Domains	List	No	Self-registered guests whose e-mail address is in one of these domains will be disallowed. Only valid if enableGuestEmail-Blacklist = true		
• requireGuestApproval	Boolean	No	Require self-registered guests to be approved if true	false	
• autoLogin-SelfWait	Boolean	No	Allow guests to login automatically from self-registration after sponsor's approval. No need to provide the credentials by guest to login	false	
• autoLogin-TimePeriod	Integer	No	Waiting period for auto login until sponsor's approval. If time exceeds, guest has to login manually by providing the credentials. Default value is 5 minutes	5	

continues on next page

Table 14 – continued from previous page

• sendApprovalRequestTo	Enum	No	Specifies where approval requests are sent. Only valid if requireGuestApproval = true.	SELECTEDEMAILADDRESSES	
• approvalEmailAddresses	String	No	Only valid if requireGuestApproval = true and sendApprovalRequestTo = SELECTEDEMAILADDRESSES		
• postRegistrationRedirect	Enum	No	After the registration submission direct the guest user to one of the following pages. Only valid if requireGuestApproval = true.	SELFREGISTRATIONSUCCESS	
• postRegistrationRedirectUrl	String	No	URL where guest user is redirected after registration. Only valid if requireGuestApproval = true and postRegistrationRedirect = URL		
• credentialNotificationUsingEmail	Boolean	No	If true, send credential notification upon approval using email. Only valid if requireGuestApproval = true	false	

continues on next page

Table 14 – continued from previous page

<ul style="list-style-type: none"> • credentialNotificationUsingSms 	Boolean	No	If true, send credential notification upon approval using SMS. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • approveDenyLinksValidFor 	Integer	No	This attribute, along with approveDenyLinksTimeUnits, specifies how long the link can be used. Only valid if requireGuestApproval = true	1440	
<ul style="list-style-type: none"> • approveDenyLinksTimeUnits 	Enum	No	This attribute, along with approveDenyLinksValidFor, specifies how long the link can be used. Only valid if requireGuestApproval = true.	DAYS	

continues on next page

Table 14 – continued from previous page

<ul style="list-style-type: none">• re-requireApprovalToAuthenticate	Boolean	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be required to enter their username and password if this attribute is true. Only valid if requireGuestApproval = true	false	
--	---------	----	---	-------	--

continues on next page

Table 14 – continued from previous page

• sponsor-PortalList	List	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be authenticated against the selected sponsor portals in the order specified. Only valid if requireGuestApproval = true. The array should contain the names of the selected portals		
• selfReg-Success-Settings	List	No			
• includeUserName	Boolean	No		true	
• includePassword	Boolean	No		true	
• includeFirst-Name	Boolean	No		true	

continues on next page

Table 14 – continued from previous page

• include-Last-Name	Boolean	No		true	
• includeEmailAddr	Boolean	No		true	
• include-PhoneNo	Boolean	No		true	
• include-Company	Boolean	No		true	
• include-Location	Boolean	No		true	
• includeSm-sProvider	Boolean	No		true	
• include-PersonBeingVisited	Boolean	No		true	
• includeReason-ForVisit	Boolean	No		true	
• allowGuest-SendSelfUsing-Print	Boolean	No		false	
• allowGuest-SendSelfUsingE-mail	Boolean	No		false	

continues on next page

Table 14 – continued from previous page

• allowGuest-SendSelfUsingSms	Boolean	No		false	
• includeAup	Boolean	No		false	
• aupOn-Page	Boolean	No		false	
• requireAupAcceptance	Boolean	No		false	
• requireAupScrolling	Boolean	No		false	
• allowGuest-Login-FromSelfregSuccessPage	Boolean	No		false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 14 – continued from previous page

• requireAup-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	
• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequency-Interval-Days	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAt-FirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegister-GuestDevices	Boolean	No	Automatically register guest devices	true	

continues on next page

Table 14 – continued from previous page

• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No		true	
• enableGuestAccess	Boolean	No		false	
• requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ONPAGE	
• requireAupAcceptance	Boolean	No		false	

continues on next page

Table 14 – continued from previous page

• require-Scrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodReg-istra-tionSet-tings	List	No	Configuration of BYOD endpoint Reg-istration step configuration		
• showDe-viceID	Boolean	No	Display Device ID field during registration	true	
• end-PointId-ntity-GroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521
• byodReg-istra-tionSuc-cessSet-tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	
• redirec-tUrl	String	No	Target URL for redirection, used when suc-cessRedirect = URL		
• authSuc-cessSet-tings	List	No			
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	

continues on next page

Table 14 – continued from previous page

• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL		www.cisco.com
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUserAgent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	

continues on next page

Table 14 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 14 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 14 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 14 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_self_registered_portal_by_id*

delete_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_self_registered_portal_by_id*

get_self_registered_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals_generator*

create_self_registered_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_self_registered_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory**class SessionDirectory**

Identity Services Engine Session Directory API (version: 3.1.0).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](https://developer.cisco.com/site/license/cisco-sample-code-license/)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_sessions(*headers=None*, ***query_parameters*)

getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_for_recovery(*headers=None, **query_parameters*)

getSessionsForRecovery.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_ip_address(*headers=None, **query_parameters*)

getSessionByIpAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_mac_address(*headers=None, **query_parameters*)

getSessionByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_groups(*headers=None, **query_parameters*)

getUserGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)

getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)

Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.1.0).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to add, delete, update and search sponsor groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Em-plALL_ACCOUNTS (default)oyees
id	String	No	Resource UUID, mandatory for update		9f1eca71-8c01-11e6-996c-525400b48521
description	String	No			Sponsors assigned to this group can manage all guest user accounts. By default, users in the ALL_ACCOUNTS user identity group are members of this sponsor group
isEnabled	Boolean	No			true
isDefault-Group	Boolean	No			true
member-Groups	List	No			["ALL_ACCOUNTS (default)"]
guestTypes	List	No			["Contractor (default)", "Daily (default)", "Weekly (default)"]
locations	List	No			["San Jose"]
autoNotification	Boolean	No			false
managePermission	Enum	No	Allowed values:		ALLACCOUNTS, GROUPACCOUNTS, OWNACCOUNTS
createPermissions	List	No			

continues on next page

Table 15 – continued from previous page

• canImportMultipleAccounts	Boolean	No			true
• importBatchSizeLimit	Integer	No		200	
• canCreateRandomAccounts	Boolean	No			true
• randomBatchSizeLimit	Integer	No		200	
• defaultUsernamePrefix	String	No			
• canSpecifyUsernamePrefix	Boolean	No			true
• canSetFutureStartDate	Boolean	No			false
• startDateFutureLimitDays	Integer	No			1
otherPermissions	List	No			

continues on next page

Table 15 – continued from previous page

• canUpdateGuest-Contact-Info	Boolean	No			true
• canViewGuest-Pass-words	Boolean	No			true
• canSendSm-sNotifica-tions	Boolean	No			false
• canResetGuest-Pass-words	Boolean	No			true
• canExtendGues-tAc-counts	Boolean	No			true
• canDeleteGues-tAc-counts	Boolean	No			true
• canSuspendGues-tAc-counts	Boolean	Yes			true
• require-SuspensionReason	Boolean	No			false

continues on next page

Table 15 – continued from previous page

• canRein-stateSuspendedAccounts	Boolean	No			true
• canApproveSelfregGuests	Boolean	No			true
• limitApprovalToSponsorsGuests	Boolean	Yes			false
• canAccessViaRest	Boolean	No			false

get_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_by_id*

update_sponsor_group_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor group by ID.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, auto_notification=None, create_permissions=None, description=None,
             guest_types=None, is_default_group=None, is_enabled=None, locations=None,
             manage_permission=None, member_groups=None, name=None, other_permissions=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `update_sponsor_group_by_id`

```
delete_sponsor_group_by_id(id, headers=None, **query_parameters)
```

This API deletes a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sponsor_group_by_id`

```
get_sponsor_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group*

get_sponsor_group_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_generator*

create_sponsor_group(*auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).

- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sponsor_group_member**class SponsorGroupMember**

Identity Services Engine SponsorGroupMember API (version: 3.1.0).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to search the group members from different identity stores configured in the GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ALL_ACCOUNTS (default)
id	String	No	Resource UUID value	a176c430-8c01-11e6-996c-525400b48521
description	String	No		
dicType	String	Yes		
guid	String	Yes		

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal**class SponsorPortal**

Identity Services Engine SponsorPortal API (version: 3.1.0).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

Sponsor Portal API provides the ability to create, read, update, delete and search sponsor portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Sponsor Portal (default)

continues on next page

Table 16 – continued from previous page

id	String	No	Resource UUID, mandatory for update		04cd708b-feef-4c75-bf3e-2d2a9c302da2
description	String	No			Default portal used by sponsors to create and manage accounts for authorized visitors to securely access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8445/portal/PortalSetup.action?portalId=feef-4c75-bf3e-2d2a9c302da2
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	SPONSOR	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8445
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on.		["eth0", "bond0"]

continues on next page

Table 16 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• fqdn	String	No	The fully-qualified domain name (FQDN) that end-users will use to access this portal. Used only in Sponsor portal		Default Portal Certificate Group
• authen- tication- Method	String	Yes	Unique Id of the identity source sequence		92faba60-8c01-11e6-996c-525400b48521
• idleTime- out	Integer	No		10	
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• availab- leSsids	List	No	Names of the SSIDs available for assignment to guest users by sponsors		
• login- PageSet- tings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 16 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	

continues on next page

Table 16 – continued from previous page

• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• sponsorChangePasswordSettings	List	No			
• allowSponsorToChangePwd	Boolean	No	Allow sponsors to change their own passwords	false	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		

continues on next page

Table 16 – continued from previous page

• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUser-Agent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	
• emptyFieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• defaultEmptyFieldValue	String	No	The default value displayed for an empty field Only valid when emptyFieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 16 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI

continues on next page

Table 16 – continued from previous page

• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contact-Text	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			

continues on next page

Table 16 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_portal_by_id*

update_sponsor_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor portal by ID.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a sponsor portal by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_portal_by_id*

get_sponsor_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_sponsor_portal`

```
get_sponsor_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                              sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.1.0).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

Sponsored Guest Portal API provides the ability to create, read, update, delete and search sponsored guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Sponsored Guest Portal (default))	
id	String	No	Resource UUID, mandatory for update	d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
description	String	No	Sponsors create guest accounts, and guests access the network using their assigned username and password		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	SPONSORED	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	

continues on next page

Table 17 – continued from previous page

• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• authentication-Method	String	Yes	Unique Id of the identity source sequence	92faba60-8c01-11e6-996c-525400b48521	
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type	Contractor (default)	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 17 – continued from previous page

<ul style="list-style-type: none"> • max-FailedAttemptsBeforeRateLimit 	Integer	No	Maximum failed login attempts before rate limiting	5	
<ul style="list-style-type: none"> • timeBetweenLoginsDuringRateLimit 	Integer	No	Time between login attempts when rate limiting	2	
<ul style="list-style-type: none"> • includeAup 	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
<ul style="list-style-type: none"> • aupDisplay 	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ASLINK	
<ul style="list-style-type: none"> • requireAupAcceptance 	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
<ul style="list-style-type: none"> • requireAccessCode 	Boolean	No	Require the portal user to enter an access code	false	
<ul style="list-style-type: none"> • accessCode 	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		

continues on next page

Table 17 – continued from previous page

• al- lowGuest- ToCre- ateAc- counts	Boolean	No	false		
• al- lowGuest- ToChangePass- word	Boolean	No	Require the portal user to enter an access code	false	
• aupSet- tings	List	No	Configuration of the Accept- able Use Policy (AUP) for a portal		
• dis- playFre- quency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Al- lowed Values: FIRSTLOGIN, EVERY- LOGIN, RECURRING	FIRSTLOGIN	
• in- cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• re- quireAup- Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAc- ceptance = true	false	
• useD- iffAup- ForEm- ployees	Boolean	No	Only valid if requireAupAc- ceptance = trueG	false	

continues on next page

Table 17 – continued from previous page

• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequency-Interval-Days	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAt-FirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegister-GuestDevices	Boolean	No	Automatically register guest devices	true	
• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		

continues on next page

Table 17 – continued from previous page

• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No	true		
• enableGuestAccess	Boolean	No	false		
• requireMDM	Boolean	No	false		
• includeAup	Boolean	No	true		
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No	false		
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	

continues on next page

Table 17 – continued from previous page

• byodReg- istra- tionSet- tings	List	No	Configuration of BYOD endpoint Reg- istration step configuration		
• showDe- viceID	Boolean	No	Display Device ID field during registration	true	
• end- PointId- entity- GroupId	String	No	Identity group id for which endpoint belongs	aa13bb40-8bff- 11e6-996c- 525400b48521	
• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Authentica- tion Success where should device be redirected. Al- lowed values: AUTHSUC- CESSPAGE, ORIGINATIN- GURL, URL	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		
• authSuc- cessSet- tings	List	No			

continues on next page

Table 17 – continued from previous page

• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUC-CESSPAGE, ORIGINATINGURL, URL	AUTHSUC-CESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		
• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		

continues on next page

Table 17 – continued from previous page

• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	

continues on next page

Table 17 – continued from previous page

• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		
• page-Background-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		

continues on next page

Table 17 – continued from previous page

• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	Guest Portal		
• contactText	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			

continues on next page

Table 17 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_sponsored_guest_portal_by_id`***`update_sponsored_guest_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **`customizations(object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description(string)`** – description, property of the request body.
- **`id(basestring)`** – id, property of the request body.
- **`name(string)`** – name, property of the request body.
- **`portal_test_url(string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type(string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings(object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsored_guest_portal_by_id*

delete_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsored_guest_portal_by_id*

get_sponsored_guest_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals*


```
get_sponsored_guest_portals_generator(filter=None, filter_type=None, page=None, size=None,
                                         sortasc=None, sortdsc=None, headers=None,
                                         **query_parameters)
```

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals_generator*

create_sponsored_guest_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsored_guest_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download

class SupportBundleDownload

Identity Services Engine SupportBundleDownload API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

Support Bundle Download API allows client to download support bundles provided those are generated and available in the default location.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
fileName	String	Yes	File name along with path from where file needs to be downloaded	filename

download_support_bundle(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *download_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_status

class SupportBundleStatus

Identity Services Engine SupportBundleStatus API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

Support Bundle Status API allows clients to query status of a triggered support bundle.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ciscoise
id	String	No	Resource UUID, mandatory for update	ciscoise
description	String	No		Support Bundle Status api
file-Name	String	No		ise-support-bundle-pk-ciscoise-admin-04-09-2021-15-07.tar.gpg
fileSize	Integer	No		1080924274
host-Name	String	No		ciscoise
message	String	No		Support Bundle generation completed
start-Time	String	No		Fri Apr 09 15:07:55 IST 2021
status	String	No		complete

get_support_bundle_status_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a support bundle status by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status*

get_support_bundle_status_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_support_bundle_status_generator***get_version**(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration**class SupportBundleTriggerConfiguration**

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

Support Bundle Trigger API allows clients to trigger support bundle provided the log settings are given using which the support needs to be generated.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values
name	String	Yes	Resource Name	supportBundle
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No	Support Bundle Generation	
hostName	String	Yes	This parameter is hostName only, xxxx of xxxx.yyy.zz	sampleHost
supportBundleOptions	List	Yes		
<ul style="list-style-type: none"> • includeConfigDB 	Boolean	Yes	Set to include Config DB in Support Bundle	false
<ul style="list-style-type: none"> • includeDebugLogs 	Boolean	Yes	Set to include Debug logs in Support Bundle	false
<ul style="list-style-type: none"> • includeLocalLogs 	Boolean	Yes	Set to include Local logs in Support Bundle	false
<ul style="list-style-type: none"> • includeCoreFiles 	Boolean	Yes	Set to include Core files in Support Bundle	false
<ul style="list-style-type: none"> • includeSystemLogs 	Boolean	Yes	Set to include System logs in Support Bundle	false
<ul style="list-style-type: none"> • mntLogs 	Boolean	Yes	Set to include Monitoring and troubleshooting logs in Support Bundle	false
<ul style="list-style-type: none"> • policyXml 	Boolean	Yes	Set to include Policy XML in Support Bundle	false
<ul style="list-style-type: none"> • fromDate 	Date	No	Date from where support bundle should include the logs	04/21/2019
<ul style="list-style-type: none"> • toDate 	Date	No	Date upto where support bundle should include the logs	04/22/2019

```
create_support_bundle(description=None, host_name=None, name=None,
                      support_bundle_include_options=None, headers=None, payload=None,
                      active_validation=True, **query_parameters)
```

This API allows the client to create a support bundle trigger configuration.

Parameters

- **description** (*string*) – description, property of the request body.
- **host_name** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **support_bundle_include_options** (*object*) – supportBundleIncludeOptions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sync_ise_node**class SyncIseNode**

Identity Services Engine Sync ISE Node API (version: 3.1.0).

Wraps the Identity Services Engine Sync ISE Node API and exposes the API as native Python methods that return native Python objects.

APIs for the configuration, administration and monitoring of the nodes in an ISE cluster deployment.

sync_node(*hostname=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Performing a manual sync will involve a reload of the target node, but not the primary PAN. There might be situations where if the node has been out of sync for a long time, it may not be possible to recover via a manual sync.

Parameters

- **hostname** (*string*) – hostname, property of the request body. Constraints: `maxLength` set to 64 and `minLength` set to 1.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health

class SystemHealth

Identity Services Engine System Health API (version: 3.1.0).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_healths(*headers=None*, ***query_parameters*)

getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)

getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_certificate

class SystemCertificate

Identity Services Engine SystemCertificate API (version: 3.1.0).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

System Certificate API provides the ability to create certificates like SAML, pxGrid.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		Support Bundle Status api
nodeId	String	Yes	NodeId of Cisco ISE application	ISE-01
localCertStub	List	Yes	Inputs for certificate creation	
<ul style="list-style-type: none"> subjectStub 	List	No	Subject data of certificate	
<ul style="list-style-type: none"> common-Name 	String	No	Common Name	\$FQDN\$
<ul style="list-style-type: none"> organizationalUnitName 	String	No	Organizational Unit Name	Cisco-SAMLCert
<ul style="list-style-type: none"> organization-Name 	String	No	Organizational Name	Cisco
<ul style="list-style-type: none"> localityName 	String	No	Locality Name	City
<ul style="list-style-type: none"> stateOr-Province-Name 	String	No	State or Province Name	State
<ul style="list-style-type: none"> countryName 	String	No	Country Name	Country
<ul style="list-style-type: none"> keyType 	String	Yes	Key Type	RSA OR ECDSA
<ul style="list-style-type: none"> keyLength 	String	Yes	Key Length	512 OR 1024 OR 2048 OR 4096
<ul style="list-style-type: none"> digest 	String	Yes	Digest	SHA-256 OR SHA-384 OR SHA-512
<ul style="list-style-type: none"> expirationTTL 	Integer	Yes	Expiration Time to Live (TTL)	2
<ul style="list-style-type: none"> selectedExpirationTTLUnit 	String	Yes	Selected Expiration TTL Unit	days OR weeks OR months OR years
1.4. User API Doc				667
<ul style="list-style-type: none"> groupTagDD 	String	No	Group Tag DD	add-group-tag

```
create_system_certificate(ers_local_cert_stub=None, node_id=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_system_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

tacacs_command_sets**class TacacsCommandSets**

Identity Services Engine TACACSCCommandSets API (version: 3.1.0).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

TACACS Command Sets API allows the client to add, delete, update, search and perform actions on TACACS command sets.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		DenyAllCommands
id	String	No	Resource UUID, mandatory for update		0cef7990-6120-11ea-bffb-7a82c56e81f0
description	String	No			Default Command Set
permitUnmatched	Boolean	No		false	
commands	List	No	Holds list of Commands		
<ul style="list-style-type: none"> commandList 	List	No	Array of dictionaries describing various attributes with the properties: <ul style="list-style-type: none"> - grant (Enum. Allowed values: PERMIT, DENY, DENY_ALWAYS), - command (String), - arguments (String) 		<pre>[{ "grant": "PERMIT", "command": "create", "arguments": "value" }]</pre>

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation .
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)Alias for *get_tacacs_command_sets_generator***create_tacacs_command_sets**(commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers

class TacacsExternalServers

Identity Services Engine TACACSExternalServers API (version: 3.1.0).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

TACACS External Servers API allows the client to add, delete, update, search and perform actions on TACACS external servers.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsExternalServer1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsExternalServer-ForSDK
hostIP	String	Yes	The server IPV4 address		1.1.1.1
connectionPort	Integer	No	The port to connect the server	49	
single-Connect	Boolean	No	Define the use of single connection	true	
sharedSecret	String	Yes	The server shared secret		SharedSecret
timeout	Integer	No	The server timeout	20	

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_id*

update_tacacs_external_servers_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_external_servers_by_id*

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_external_servers_by_id*

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers*

get_tacacs_external_servers_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_tacacs_external_servers_generator***create_tacacs_external_servers**(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_profile**class TacacsProfile**

Identity Services Engine TACACSPROFILE API (version: 3.1.0).

Wraps the Identity Services Engine TACACSPROFILE API and exposes the API as native Python methods that return native Python objects.

TACACS Profile API allows the client to add, delete, update, search and perform actions on TACACS profile.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Shell Profile
id	String	No	Resource UUID, mandatory for update	93d7ee70-92b5-11eb-a39d-96858bc78604
description	String	No		Default Shell Profile
sessionAttributes	List	No	Holds list of session attributes. View type for GUI is Shell by default	
<ul style="list-style-type: none"> sessionAttributeList 	List	No	Array of dictionaries describing various attributes with the properties: - type (Enum. Allowed values: MANDATORY, OPTIONAL), - name (String), - value (String)	[{ "type" : "MANDATORY", "name" : "attr1", "value" : "value" }]

get_tacacs_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile_by_name***get_tacacs_profile_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile_by_id***update_tacacs_profile_by_id**(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_profile_by_id*

delete_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_tacacs_profile_by_id***get_tacacs_profile**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile***get_tacacs_profile_generator**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_tacacs_profile_generator`*

`create_tacacs_profile`(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`session_attributes`** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.1.0).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

TACACS Server Sequence API allows the client to add, delete, update, search and perform actions on TACACS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsServerSequence1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsServerSequenceForSDK
serverList	String	Yes	The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication		TacacsExternalServer1,TacacsExternalServer2
localAccounting	Boolean	No		false	
remoteAccounting	Boolean	No		true	
prefixStrip	Boolean	No	Define if a delimiter will be used for prefix strip	false	
suffixStrip	Boolean	No	Define if a delimiter will be used for suffix strip	false	
prefixDelimiter	String	No	The delimiter that will be used for prefix strip		
suffixDelimiter	String	No	The delimiter that will be used for suffix strip	@	

get_tacacs_server_sequence_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_name`***`get_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_id`*
`update_tacacs_server_sequence_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None,
             prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None,
             suffix_strip=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_tacacs_server_sequence_by_id`

```
delete_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)
```

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_tacacs_server_sequence_by_id`

```
get_tacacs_server_sequence(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *`get_tacacs_server_sequence`***`get_tacacs_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *`get_tacacs_server_sequence_generator`*


```
create_tacacs_server_sequence(description=None, local_accounting=None, name=None,
                             prefix_delimiter=None, prefix_strip=None, remote_accounting=None,
                             server_list=None, suffix_delimiter=None, suffix_strip=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None,
        remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `create_tacacs_server_sequence`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.1.0).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

Telemetry Information API allows clients to get telemetry configuration information.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	ed7176fb-3faf-4060-845e-d5fa5236bd6e
description	String	No		
status	String	No		SCHEnable
deploymentId	String	No		ed7176fb-3faf-4060-845e-d5fa5236bd6e
udiSN	String	No		CH2MKIEGBGO

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information*

get_telemetry_information_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration**class TrustSecConfiguration**

Identity Services Engine TrustSec Configuration API (version: 3.1.0).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxxg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_security_groups(*headers=None, **query_parameters*)

getSecurityGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_security_groups***get_security_group_acls**(*headers=None, **query_parameters*)*getSecurityGroupAcls*.**Parameters**

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_egress_policies(*headers=None, **query_parameters*)*getEgressPolicies*.**Parameters**

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_matrices(headers=None, **query_parameters)``getEgressMatrices.`**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`trust_sec_sxp`**`class TrustSecSxp`**

Identity Services Engine TrustSec SXP API (version: 3.1.0).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_bindings(*headers=None*, ***query_parameters*)

getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.1.0).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_ise_version_and_patch(*headers=None*, ***query_parameters*)

This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info**class VersionInfo**

Identity Services Engine VersionInfo API (version: 3.1.0).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_version_info(*resource, headers=None, **query_parameters*)

Get all VersionInfo.

Parameters

- **resource** (*basestring*) – resource path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint**class Endpoint**

Identity Services Engine endpoint API (version: 3.1.0).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

Endpoint API allows the client to add, delete, update, search, register and de-register endpoints. Please note that each API description shows whether the API is supported in bulk operation. The Bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re- vi- sion #	Re- source Version	Cisco ISE Version	Description	Revision Modifica- tion	
				Attribute	Description
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.1	Cisco ISE 2.1 model changes	custom-Attributes	Added custom attributes for the user to include custom attributes when adding endpoints to Cisco ISE
2	1.2	2.2	Cisco ISE 2.2 model changes	apiAdded	Added custom operation to get list of rejected endpoints: '/getrejectedendpoints'
				apiAdded	Added custom operation to release rejected endpoint: '{id}/releaserejectedendpoint'

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	11:22:33:44:55:66
id	String	No	Resource UUID, mandatory for update	172f8270-8f4f-11eb-b4a8-9eb04987ed29
description	String	No		MyEndpoint
customAttributes	Map	No	Key value map	{"key1": "value1"}
groupId	String	Yes		aa13bb40-8bff-11e6-996c-525400b48521
identityStore	String	No		identityStore
identityStoreId	String	No		identityStoreId
mac	String	Yes		11:22:33:44:55:66
portalUser	String	No		portalUser
profileId	String	No		profileId
staticGroupAssignment	Boolean	Yes		true
staticProfileAssignment	Boolean	Yes		false

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

release_rejected(*id*, *headers=None*, ***query_parameters*)

Alias for *release_rejected_endpoint*

deregister_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to de-register an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deregister(*id*, *headers=None*, ***query_parameters*)

Alias for *deregister_endpoint*

get_rejected_endpoints(*headers=None*, ***query_parameters*)

This API allows the client to get the rejected endpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_rejected(*headers=None, **query_parameters*)

Alias for *get_rejected_endpoints*

get_endpoint_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_endpoint_by_id*

update_endpoint_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_by_id*

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_by_id*


```
register_endpoint(custom_attributes=None, description=None, group_id=None, id=None,  
                 identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None,  
                 name=None, portal_user=None, profile_id=None, static_group_assignment=None,  
                 static_profile_assignment=None, headers=None, payload=None,  
                 active_validation=True, **query_parameters)
```

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for `register_endpoint`

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: `/ers/config/endpoint?filter={filter name}.{operator}.{logical profile name}` Example: `https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple` Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET `/ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18` Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_endpoints_generator`*

`create_endpoint`(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint.

Parameters

- **`custom_attributes`** (*object*) – customAttributes, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`group_id`** (*string*) – groupId, property of the request body.
- **`identity_store`** (*string*) – identityStore, property of the request body.
- **`identity_store_id`** (*string*) – identityStoreId, property of the request body.
- **`mac`** (*string*) – mac, property of the request body.
- **`mdm_attributes`** (*object*) – mdmAttributes, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_user`** (*string*) – portalUser, property of the request body.
- **`profile_id`** (*string*) – profileId, property of the request body.
- **`static_group_assignment`** (*boolean*) – staticGroupAssignment, property of the request body.
- **`static_profile_assignment`** (*boolean*) – staticProfileAssignment, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status`(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_endpoint***nbar_app****class NbarApp**

Identity Services Engine nbarApp API (version: 3.1.0).

Wraps the Identity Services Engine nbarApp API and exposes the API as native Python methods that return native Python objects.

`get_nbar_apps`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all NBAR Applications.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_nbar_apps`*

`get_nbar_apps_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all NBAR Applications.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_nbar_apps_generator`*

`create_nbar_app`(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create NBAR application.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`network_identities`** (*list*) – Array of NIs, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_nbar_app*

get_nbar_app_by_id(*id, headers=None, **query_parameters*)

Get NBAR Application by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_nbar_app_by_id*

update_nbar_app_by_id(*id, description=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update NBAR Application.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **network_identities** (*list*) – Array of NIs, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *network_identities=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_nbar_app_by_id*

delete_nbar_app_by_id(*id*, *headers=None*, ****query_parameters**)

Delete NBAR Application.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_nbar_app_by_id*

portal

class Portal

Identity Services Engine portal API (version: 3.1.0).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

Portal API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ISE Portal (default)
id	String	No	Resource UUID, mandatory for update	bc5524ea-b1e5-47ed-a907-5304821da916
description	String	No		ISE Portal for saml based feature purpose
portal-Type	String	No		GUEST

get_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_portal_by_id`***`get_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`**

This API allows the client to get all the portals. Filter: [name, description]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals*

`get_portals_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.1.0).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

pxGrid Node API allows the client to retrieve pxGrid information, delete an existing pxGrid node, and approve new pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	ers-sample-client
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
descrip-tion	String	No		ERS sample client
status	String	No		Online (XMPP)
auth-Method	String	No		Certificate
groups	String	No		

pxGrid Characterization

Session data Consumption over pxGrid

On a 35 node Cisco ISE deployment with a dedicated primary Policy Administration node (PAN), dedicated secondary PAN, dedicated primary Monitoring and Troubleshooting node (MnT node), dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous Policy Service node (PSN) platforms, there was no delay observed in consuming session data with the following parameters as shown in the table below:

RADIUS Traffic	Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	pxGrid client's delay in consuming session data
Upto 500 transactions per second (TPS)	~2 million	50	No delay

Bulk download time taken

On a 35 node Cisco ISE deployment with a dedicated primary PAN, dedicated secondary PAN, dedicated primary MnT, dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous PSN Platforms, the bulk download time for all the pxGrid clients is shown in the table below:

Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	Time taken for bulk download
2 million	50	~17 minutes

Note: From Cisco ISE Release 3.1, we can use either `pxgridnode` or `pxgridNode` in the URL.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_name*

delete_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_px_grid_node_by_name*

get_px_grid_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_id*

get_px_grid_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_px_grid_node***`get_px_grid_node_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sg_vn_mapping

class SgVnMapping

Identity Services Engine sgVnMapping API (version: 3.1.0).

Wraps the Identity Services Engine sgVnMapping API and exposes the API as native Python methods that return native Python objects.

get_sg_vn_mappings(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not

Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings*

get_sg_vn_mappings_generator (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings_generator*

create_sg_vn_mapping(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Security Group and Virtual Network mapping.

Parameters

- **id** (*string*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sg_vn_mapping*

bulk_create_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *bulk_create_sg_vn_mappings*

bulk_delete_sg_vn_mappings(headers=None, payload=None, active_validation=True, **query_parameters)

Delete SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *bulk_delete_sg_vn_mappings*

bulk_update_sg_vn_mappings(headers=None, payload=None, active_validation=True, **query_parameters)

Update SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_sg_vn_mappings*

get_sg_vn_mapping_by_id(*id, headers=None, **query_parameters*)

Get Security Group and Virtual Network mapping by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_sg_vn_mapping_by_id*

update_sg_vn_mapping_by_id(*id, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update Security Group and Virtual Network mapping.

Parameters

- **id** (*basestring*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sg_vn_mapping_by_id*

delete_sg_vn_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Security Group and Virtual Network mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ****query_parameters**)

Alias for *delete_sg_vn_mapping_by_id*

tasks**class Tasks**

Identity Services Engine tasks API (version: 3.1.0).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

get_task_status(*headers=None*, ****query_parameters**)

get all task status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_task_status_by_id(*task_id*, *headers=None*, ***query_parameters*)

Monitor task status.

Parameters

- **task_id** (*basestring*) – taskId path parameter. The id of the task executed before.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

virtual_network

class VirtualNetwork

Identity Services Engine virtualNetwork API (version: 3.1.0).

Wraps the Identity Services Engine virtualNetwork API and exposes the API as native Python methods that return native Python objects.

get_virtual_networks(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.

- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks*

get_virtual_networks_generator (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator

common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks_generator*

create_virtual_network(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*string*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_virtual_network*

bulk_create_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_virtual_networks*

bulk_delete_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_delete_virtual_networks*

bulk_update_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_update(headers=None, payload=None, active_validation=True, **query_parameters)`Alias for *`bulk_update_virtual_networks`***`get_virtual_network_by_id(id, headers=None, **query_parameters)`**

Get Virtual Network by id.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_virtual_network_by_id`***`update_virtual_network_by_id(id, additional_attributes=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Update Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*basestring*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *additional_attributes=None*, *last_update=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_virtual_network_by_id*

delete_virtual_network_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Virtual Network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_virtual_network_by_id`***`vn_vlan_mapping`****`class VnVlanMapping`**Identity Services Engine `vnVlanMapping` API (version: 3.1.0).Wraps the Identity Services Engine `vnVlanMapping` API and exposes the API as native Python methods that return native Python objects.**`get_vn_vlan_mappings(filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters)`**

Get all VN-Vlan Mappings.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mappings*

get_vn_vlan_mappings_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mappings_generator*

create_vn_vlan_mapping(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mapping.

Parameters

- **id (string)** – Identifier of the VN-Vlan Mapping, property of the request body.
- **is_data (boolean)** – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan (boolean)** – Flag which indicates if the Vlan is default, property of the request body.
- **last_update (string)** – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **max_value (integer)** – Max value, property of the request body.
- **name (string)** – Name of the Vlan, property of the request body.
- **vn_id (string)** – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name (string)** – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_vn_vlan_mapping*

bulk_create_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_vn_vlan_mappings*

bulk_delete_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_delete_vn_vlan_mappings*

bulk_update_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_vn_vlan_mappings*

get_vn_vlan_mapping_by_id(*id, headers=None, **query_parameters*)

Get VN-Vlan Mapping by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mapping_by_id*

update_vn_vlan_mapping_by_id(*id, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – Identifier of the VN-Vlan Mapping, property of the request body.

- **is_data** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **max_value** (*integer*) – Max value, property of the request body.
- **name** (*string*) – Name of the Vlan, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_vn_vlan_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

Delete VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.1.1**aci_bindings****class AciBindings**

Identity Services Engine ACIBindings API (version: 3.1.1).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

The ACI Bindings API allows clients to retrieve bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on the ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip, sgt, vn, psn, learnedFrom, or learnedBy with CONTAINS mode of search.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
ip	String	Yes	Binding IPv4 address. Each binding will be exclusively identified by its IP address and virtual network	10.0.0.1
sgt	String	No	Security Group Tag (SGT) value. The valid range for SGT values is 0-65534	1234
vn	String	Yes	Virtual network. Each binding will be exclusively identified by its IP address and virtual network	vn1234
psn	String	No	Cisco ISE Policy Service node (PSN) IP address	10.86.189.216
learnedFrom	String	Yes	Binding Source	ISE by ACI ACI by ISE
learnedBy	String	Yes	Binding Type	SXP(SXP, 0) STATIC(Static, 1) RADIUS(RADIUS, 2) ACI(ACI, 3)

get_aci_bindings(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.1.1).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

ACI Settings API allows the client to get and update the ACI Settings. In addition, testing the ACI Domain Manager connection is also possible using the TestACIConnection.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		AciSettings
id	String	No	Resource UUID value		29fb45ab-6a8e-4658-8a28-02521c258178
description	String	No			Aci Settings
enableAci	Boolean	Yes	Enable ACI Integration	false	
isAci50	Boolean	Yes	Enable 5.0 ACI Version	false	
ipAddressHost- Name	String	No	ACI Cluster IP Address / Host name		
adminName	String	No	ACI Cluster Admin name		
adminPassword	String	No	ACI Cluster Admin pass- word		
tenantName	String	No	ACI Cluster Tenant name	ISE	
l3RouteNetwork	String	No	ACI Cluster L3 Route net- work name	L3_ROUTE	
suffixToEpg	String	No	Name Conversion - EPG suffix	SGT	
suffixToSgt	String	No	Name Conversion - SGT suffix	EPG	
allSxpDomain	Boolean	No	SXP Propagation to all the SXP domains	false	
specificSxpDo- main	Boolean	No	SXP Propagation to spe- cific SXP domains	true	
specifixSxpDo- mainList	List	No	Specific SXP domains list	[default]	
isAci51	Boolean	Yes	Enable 5.1 ACI Version	false	
aciipaddress	String	No	ACI Domain manager Ip Address		
aciuserName	String	No	ACI Domain manager Username		
acipassword	String	No	ACI Domain manager Password		
enableData- Plane	Boolean	No	Enable data plane	false	
untaggedPack- etIepgName	String	No	Untagged IEPG packets name	untagged	
defaultSgtName	String	No	Default SGT name	Unknown	
enableEle- mentsLimit	Boolean	No	Enable Elements Limit	false	
maxNu- mIepgFromAci	Inte- ger	No	Max number of IEPGs	1000	
maxNumSgt- ToAci	Inte- ger	No	Max number of SGTs	500	

get_aci_settings(*headers=None, **query_parameters*)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

test_aci_connectivity(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.


```
update_aci_settings_by_id(id, aci50=None, aci51=None, aciipaddress=None, acipassword=None,
    aciuser_name=None, admin_name=None, admin_password=None,
    all_sxp_domain=None, default_sgt_name=None, enable_aci=None,
    enable_data_plane=None, enable_elements_limit=None,
    ip_address_host_name=None, l3_route_network=None,
    max_num_iepg_from_aci=None, max_num_sgt_to_aci=None,
    specific_sxp_domain=None, specifix_sxp_domain_list=None,
    suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None,
    untagged_packet_iepg_name=None, headers=None, payload=None,
    active_validation=True, **query_parameters)
```

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.
- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint**class AncEndpoint**

Identity Services Engine ANCEndpoint API (version: 3.1.1).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
macAddress	String	Yes	MAC address of the endpoint	00:11:22:33:44:55
policy-Name	String	Yes	Policy name to be applied to the endpoint	policy1

Supported ANC API transactions per second

On a 5 node Cisco ISE deployment with 60k sessions or on a 9 node Cisco ISE deployment with 200k/500k sessions, 250 transactions per second (TPS) is supported for any ANC API.

Supported ANC APIs

* `applyEndpointByMacAddress` * `clearEndpointByMacaddress` * `applyEndpointByIpAddress` * `applyEndpointPolicy` * `clearEndpointPolicy`

Deployment	Number of Sessions	Supported ANC APIs TPS
5 nodes	60k	250
9 nodes	200k	250
5 nodes	500k	250

`get_anc_endpoint_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC endpoint by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **`headers`**(MyDict): response headers.
- **`response`**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **`content`**(bytes): representation of the request's response
- **`text`**(str): representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`get_anc_endpoint_by_id`*

`clear_anc_endpoint`(*additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to clear the required configuration.

Parameters

- **`additional_data`** (*list*) – additionalData, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data (list)** – additionalData, property of the request body (list of objects).
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *apply_anc_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory

class ActiveDirectory

Identity Services Engine ActiveDirectory API (version: 3.1.1).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

The Active Directory API allows the user to carry out add, delete, and search operations on the active directory domains through Cisco ISE's join points. For example, if you want to connect to the domain cisco.com and retrieve the domain groups, you can carry out the following steps which are also available as APIs: Step 1 Create a domain join point in Cisco ISE. In the "domain" parameter use cisco.com.

Step 2 Get all defined join points and copy your join point's ID from the response.

Step 3 Join all Cisco ISE nodes to the domain. Use the ID received in the Step 2 in the URL. From this point onwards, you can perform several actions. In each action you should specify the joint point ID in the URL, as retrieved in step 2 in the previous configuration task. For example, you can:

- Retrieve the user groups using the joint point ID.

- Retrieve the groups of a specific domain using the join point ID. The domain parameter can be cisco.com or any of its trusted domains. You can use the get all trusted domains operation to retrieve the list.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifica- tion	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.4	Support new attributes	advanced- Settings	Added ERSActiveDirectoryAdvancedSettings Attribute 'advancedSettings'
				adAt- tributes	Added ERSActiveDirectoryAt- tributes Attribute 'adAttributes'
				enable- Domain- WhiteList	Added Boolean Attribute 'en- ableDomainWhiteList'
2	1.2	3.1	Support new attributes under ActiveDirectory AdvancedSettings	enable- FailedAuth- Protection	Added Boolean Attribute 'en- ableFailedAuthProtection'
				failedAu- thThresh- old	Added Integer Attribute 'failedAuthThreshold'
				auth Protec- tionType	Added Enum Attribute 'authPro- tectionType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_ characters	...	Company_users
id	String	No	Resource UUID value	...	af1cd190-7d71-11eb-b02e-ead13cf60dcb
description	String	No	No character restriction	...	Group of Active company users
domain	String	Yes	The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed	...	cisco.com
adScopes-Names	String	No	String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed	Default_Scope	...
enableDomain-WhiteList	Boolean	No	...	true	...
adGroups	List	No	Holds list of AD Groups
• groups	List	No	List of Groups

continues on next page

Table 18 – continued from previous page

• name	String	Yes	Required for each group in the group list with no duplication between groups. All characters are allowed except %	...	cisco.com/operators
• sid	String	Yes	Cisco ISE uses security identifiers (SIDs) for optimization of group membership evaluation. SIDs are useful for efficiency (speed) when the groups are evaluated. All characters are allowed except %	...	S-1-5-32-548
• type	String	No	No character restriction	...	GLOBAL
adAttributes	List	No	Holds list of AD Attributes
• attributes	List	No	List of Attributes
• name	String	Yes	Required for each attribute in the attribute list with no duplication between attributes. All characters are allowed except <%”	...	name1
• type	Enum	Yes	Required for each group in the group list. Allowed values: - STRING, - IP, - BOOLEAN, - INT, - OCTET_STRING	STRING	...

continues on next page

Table 18 – continued from previous page

• internal-Name	String	Yes	Required for each attribute in the attribute list. All characters are allowed except <%”	...	internalName1
• default-Value	String	Yes	Required for each attribute in the attribute list. Can contain an empty string. All characters are allowed except <%”	...	defaultString
advancedSettings	List	No
• rewriteRules	List	No	Identity rewrite is an advanced feature that directs Cisco ISE to manipulate the identity before it is passed to the external Active Directory system. You can create rules to change the identity to a desired format that includes or excludes a domain prefix and/or suffix or other additional markup of your choice
• rowId	Integer	Yes	Required for each rule in the list in serial order	...	0
• rewriteMatch	String	Yes	Required for each rule in the list with no duplication between rules. All characters are allowed except %”	...	exampleMatch0

continues on next page

Table 18 – continued from previous page

• rewriteResult	String	Yes	Required for each rule in the list. All characters are allowed except %”	...	exampleResult0
• enableRewrites	Boolean	No	...	false	...
• enablePassChange	Boolean	No	...	true	...
• enableMachineAuth	Boolean	No	...	true	...
• enableMachineAccess	Boolean	No	...	true	...
• enableDialinPermissionCheck	Boolean	No	...	false	...
• plaintextAuth	Boolean	No	...	false	...
• agingTime	Integer	No	Range 1-8760 hours	5	...
• enableCallbackForDialinClient	Boolean	No	...	false	...
• identityNotInAdBehaviour	Enum	No	Allowed values: - REJECT, - SEARCH_JOINED_FOREST, - SEARCH_ALL	SEARCH_JOINED_FOREST	

continues on next page

Table 18 – continued from previous page

• unreachableDomainsBehaviour	Enum	No	Allowed values: - PROCEED, - DROP	PROCEED	...
• schema	Enum	No	Allowed values: - ACTIVE_DIRECTORY, - CUSTOM-Choose ACTIVE_DIRECTORY schema when the AD attributes defined in AD can be copied to relevant attributes in Cisco ISE. If customization is needed, choose CUSTOM schema. All User info attributes are always set to default value if schema is ACTIVE_DIRECTORY. Values can be changed only for CUSTOM schema	ACTIVE_DIRECTORY	...
• firstName	String	No	User info attribute. All characters are allowed except %	givenName	...
• department	String	No	User info attribute. All characters are allowed except %	department	...
• lastName	String	No	User info attribute. All characters are allowed except %	sn	...

continues on next page

Table 18 – continued from previous page

• organiza- tionalU- nit	String	No	User info at- tribute. All characters are allowed except %	company	...
• jobTitle	String	No	User info at- tribute. All characters are allowed except %	title	...
• locality	String	No	User info at- tribute. All characters are allowed except %	l	...
• email	String	No	User info at- tribute. All characters are allowed except %	mail	...
• stateOr- Province	String	No	User info at- tribute. All characters are allowed except %	st	...
• telephone	String	No	User info at- tribute. All characters are allowed except %	telepho- neNumber	...
• country	String	No	User info at- tribute. All characters are allowed except %	co	...
• streetAd- dress	String	No	User info at- tribute. All characters are allowed except %	streetAddress	...
• enable- FailedAu- th Protec- tion	Boolean	No	Enable prevent AD account lockout due to too many bad password attempts	false	...
• failedAu- thThresh- old	Integer	No	Number of bad password attempts	5	...

continues on next page

Table 18 – continued from previous page

• authProtection-Type	Enum	No	Enable prevent AD account lockout. Allowed values:- WIRELESS, - WIRED, - BOTH	WIRELESS	...
-----------------------	------	----	---	----------	-----

get_active_directory_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

load_groups_from_domain(*id*, *ad_attributes=None*, *ad_scopes_names=None*, *adgroups=None*, *advanced_settings=None*, *description=None*, *domain=None*, *enable_domain_white_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_characters, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
is_user_member_of_groups(id, additional_data=None, headers=None, payload=None,  
                           active_validation=True, **query_parameters)
```

This API verifies if the user is a member of the given groups.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_trusted_domains(id, headers=None, **query_parameters)
```

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

join_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetchs the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory*

`get_active_directory_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

create_active_directory(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_active_directory*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.1.1).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

The Admin User API allows to retrieve information related to admin users configured on Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	1.1	2.0	Cisco ISE Release 2.3 Admin User

Resource Definition

Attribute	Type	Re- quired	Description	Example Values	De- fault Value
name	String	Yes	Resource Name		
id	String	Yes	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69	
description	String	No			
changePass- word	Boolean	Yes		true	true
email	String	No		email1@domain.com	
includeSys- temAlarm- sInEmail	Boolean	No		false	
inactiveAc- countN- everDisabled	Boolean	No		true	
enabled	Boolean	Yes		false	
external	Boolean	No		true	
customAt- tributes	String	No	Key Value Map	{“MyCustom- Attribute” : “Value1”}	
firstName	String	No			
adminGroups	String	No	Admin Group Names	Super Admin	
lastName	String	No			
password	String	No	The password field doesn’t show the actual password configured. It is hidden with the asterisk (*) symbol		

get_admin_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

allowed_protocols**class AllowedProtocols**

Identity Services Engine AllowedProtocols API (version: 3.1.1).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

Allowed Protocols API allows the client to add, delete, update, search and perform actions on allowed protocols.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.7	Added support for TEAP	preferredEapProtocol	Added value 'TEAP' to enum attribute preferredEapProtocol
				allowTeap	Added boolean attribute allowTeap
				allowTeapEapMsChapV2	Added boolean attribute allowTeapEapMsChapV2
				allowTeapEapMsChapV2PwdChange	Added boolean attribute allowTeap
				allowTeapEapMsChapV2PwdChangeRetries	Added int attribute allowTeapEapMsChapV2PwdChangeRetries
				allowTeapEapTls	Added boolean attribute allowTeapEapTls

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Device Admin
id	String	No	Resource UUID, Mandatory for update	926901b0-8c01-11e6-996c-525400b48521
description	String	No		Default Allowed Protocol Service Device Admin
processHost-Lookup	Boolean	Yes		true
allowPapAscii	Boolean	No		true
allowChap	Boolean	Yes		false
allowMsChapV1	Boolean	Yes		false
allowMsChapV2	Boolean	Yes		false
allowEapMd5	Boolean	Yes		true
allowLeap	Boolean	Yes		false
allowEapTls	Boolean	Yes		true
allowEapTtls	Boolean	Yes		true
allowEapFast	Boolean	Yes		true
allowPeap	Boolean	Yes		true
allowTeap	Boolean	Yes		true
allowPreferredEapProtocol	Boolean	Yes		true

continues on next page

Table 19 – continued from previous page

eapTlsLBit	Boolean	Yes		false
allowWeakCiphersForEap	Boolean	Yes		false
requireMessageAuth	Boolean	Yes		false
preferredEapProtocol	Enum	No	The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored.	PEAP
eapTls	List	No	The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol	
• allowEapTlsAuthOfExpiredCerts	Boolean	Yes		false
• eapTlsEnableStatelessSessionResume	Boolean	Yes		false
• eapTlsSessionTicketTtl	Integer	No	Time to live. The eapTlsSessionTicketTtl is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
• eapTlsSessionTicketTtlUnits	Enum	No	Time to live time units. The eapTlsSessionTicketTtlUnits is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored.	SECONDS

continues on next page

Table 19 – continued from previous page

• eapTlsSessionTicketPrecentage	Integer	No	The eapTlsSessionTicketPrecentage is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
peap	List	No	The peap is required only if allowPeap is true, otherwise it must be ignored. The object peap contains the settings for PEAP protocol	
• allowPeapEapMsChapV2	Boolean	Yes		true
• allow-PeapEapMsChapV2PwdChange	Boolean	No	The allow-PeapEapMsChapV2PwdChange is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored	true
• allow-PeapEapMsChapV2PwdChangeRetries	Integer	No	The allow-PeapEapMsChapV2PwdChangeRetries is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
• allowPeapEapGtc	Boolean	Yes		false
• allowPeapEapGtcPwdChange	Boolean	No	The allowPeapEapGtcPwdChange is required only if allowPeapEapGtc is true, otherwise it must be ignored	false

continues on next page

Table 19 – continued from previous page

<ul style="list-style-type: none"> • allowPeapEapGtcPwdChangeRetries 	Integer	No	The allowPeapEapGtcPwdChangeRetries is required only if allowPeapEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowPeapEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowPeapEapTlsAuthOfExpiredCerts 	Boolean	No	The allowPeapEapTlsAuthOfExpiredCerts is required only if allowPeapEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • requireCryptobinding 	Boolean	Yes		false
<ul style="list-style-type: none"> • allowPeapV0 	Boolean	Yes		false
eapTtls	List	No	The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol	
<ul style="list-style-type: none"> • eapTtlsPapAscii 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsChap 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsMsChapV1 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsMsChapV2 	Boolean	Yes		true

continues on next page

Table 19 – continued from previous page

• eapT-tlsEapMd5	Boolean	Yes		true
• eapT-tlsEapM-sChapV2	Boolean	Yes		true
• eapT-tlsEapM-sChapV2PwdChange	Boolean	No	The eapTtlsEapM-sChapV2PwdChange is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored	true
• eapT-tlsEapM-sChapV2PwdChangeRetries	Integer	No	The eapTtlsEapM-sChapV2PwdChangeRetries is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
eapFast	List	No	The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol	
• allowEap-FastEapM-sChapV2	Boolean	Yes		true
• allowEap-FastEapM-sChapV2PwdChange	Boolean	No	The allowEap-FastEapM-sChapV2PwdChange is required only if allowEap-FastEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 19 – continued from previous page

<ul style="list-style-type: none"> • allowEap-FastEapM-sChapV2PwdChangeRetries 	Integer	No	The allowEap-FastEapM-sChapV2PwdChangeRetries is required only if eapTlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapGtc 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwdChange 	Boolean	No	The allowEap-FastEapGtcPwdChange is required only if allowEap-FastEapGtc is true, otherwise it must be ignored	true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwdChangeRetries 	Integer	No	The allowEap-FastEapGtcPwdChangeRetries is required only if allowEapFastEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapTlsAuthOfExpiredCerts 	Boolean	No	The allowEap-FastEapTlsAuthOfExpiredCerts is required only if allowEap-FastEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastEnableEAPChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • eapFastUsePacs 	Boolean	Yes		true

continues on next page

Table 19 – continued from previous page

• eapFastUsePacsTunnelPacTtl	Integer	No	The eapFastUsePacsTunnelPacTtl is required only if eapFastUsePacs is true, otherwise it must be ignored	7776000
• eapFastUsePacsTunnelPacTtlUnits	Enum	No	The eapFastUsePacsTunnelPacTtlUnits is required only if eapFastUsePacs is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsUseProactivePacUpdatePercentage	Integer	No	The eapFastUsePacsUseProactivePacUpdatePercentage is required only if eapFastUsePacs is true, otherwise it must be ignored	10
• eapFastUsePacsAllowAnonymProvisioning	Boolean	No	The eapFastUsePacsAllowAnonymProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAllowAuthenProvisioning	Boolean	No	The eapFastUsePacsAllowAuthenProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning	Boolean	No	The eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false

continues on next page

Table 19 – continued from previous page

• eapFastUsePacsAcceptClientCert	Boolean	No	The eapFastUsePacsAcceptClientCert is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false
• eapFastUsePacsAllowMachineAuthentication	Boolean	No		false
• eapFastUsePacsMachinePacTtl	Integer	No	The eapFastUsePacsMachinePacTtl is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored	1
• eapFastUsePacsMachinePacTtlUnits	Enum	No	The eapFastUsePacsMachinePacTtlUnits is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsStatelessSessionResume	Boolean	No	The eapFastUsePacsStatelessSessionResume is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAuthorizationPacTtl	Integer	No	The eapFastUsePacsAuthorizationPacTtl is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored	1

continues on next page

Table 19 – continued from previous page

<ul style="list-style-type: none"> • eapFastUsePacsAuthorizationPacTtlUnits 	Enum	No	The eapFastUsePacsAuthorizationPacTtlUnits is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored.	SECONDS
<ul style="list-style-type: none"> • eapFastDontUsePacsAcceptClientCert 	Boolean	No	The eapFastDontUsePacsAcceptClientCert is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastDontUsePacsAllowMachineAuthentication 	Boolean	No	The eapFastDontUsePacsAllowMachineAuthentication is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
teap	List	No	The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol	
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChange 	Boolean	No	The allowTeapEapM-sChapV2PwdChange is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 19 – continued from previous page

• allowTeapEapM-sChapV2PwdChangeRetries	Integer	No	The allowTeapEapM-sChapV2PwdChangeRetries is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	3
• allowTeapEapTls	Boolean	Yes		true
• allowTeapEapTlsAuthOfExpiredCerts	Boolean	No	The allowTeapEapTlsAuthOfExpiredCerts is required only if allowTeapEapTls is true, otherwise it must be ignored	false
• acceptClientCertDuringTunnelEst	Boolean	Yes		true
• enableEapChaining	Boolean	Yes		false
• allowDowngradeMsk	Boolean	Yes		false

get_allowed_protocol_by_name(name, headers=None, **query_parameters)

This API allows the client to get an allowed protocol by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_name`***`get_allowed_protocol_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_id`*

```
update_allowed_protocol_by_id(id, allow_chap=None, allow_eap_fast=None, allow_eap_md5=None,
                             allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None,
                             allow_ms_chap_v1=None, allow_ms_chap_v2=None,
                             allow_pap_ascii=None, allow_peap=None,
                             allow_preferred_eap_protocol=None, allow_teap=None,
                             allow_weak_ciphers_for_eap=None, description=None,
                             eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None,
                             name=None, peap=None, preferred_eap_protocol=None,
                             process_host_lookup=None, require_message_auth=None, teap=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_ttls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols_generator*

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.

- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
create(allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None,
allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None,
allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None,
allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None,
eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None,
process_host_lookup=None, require_message_auth=None, teap=None, headers=None,
payload=None, active_validation=True, **query_parameters)
```

Alias for *create_allowed_protocol*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy

class AncPolicy

Identity Services Engine AncPolicy API (version: 3.1.1).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource ID	test
description	String	No		
action	Enum	Yes	<ul style="list-style-type: none"> • QUAR-ANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. • PORT-BOUNCE: Resets the port on the network device to which the endpoint is connected • SHUT-DOWN : Shuts down the port on the network device to which the endpoint is connected • RE_AUTHENTICATE: Re-authenticates the session from the endpoint 	

get_anc_policy_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_name`*

`get_anc_policy_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC policy by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_id`*

```
update_anc_policy_by_id(id, actions=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are ‘QUARANTINE’, ‘PORTBOUNCE’, ‘SHUTDOWN’ and ‘RE_AUTHENTICATE’).
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, actions=None, name=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_anc_policy_by_id*

```
delete_anc_policy_by_id(id, headers=None, **query_parameters)
```

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy_generator*

create_anc_policy(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_anc_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_policy(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.1.1).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

Authorization Profile API allows the client to add, delete, update, search and perform actions on authorization profiles.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revi- sion Mod- ifica- tion	Revision Modification
				At- tribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.3	Support new attributes under common tasks	ac- cessType	Added Attribute 'accessType'. Default value:'ACCESS_ACCEPT', additional values: 'ACCESS_REJECT'
				au- thzPro- file- Type	Added Attribute 'authzProfileType' to differentiate between types of authorization profiles. Default value:'SWITCH' (used for Standard Authorization Profiles) , additional values:'TACACS', 'TRUSTSEC'
				reauth	Added Attribute 'reauth' to determine reauthentication policy
				we- bRedi- rec- tion	Added Attribute 'webRedirection' to support selection of portal redirection
				acl	Added String Attribute 'acl'
				track- Move- ment	Added Boolean Attribute 'trackMovement'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID value		id
description	String	No			description
vlan	List	No			
• nameID	String	Yes			vlanName
• tagID	Integer	Yes	Valid range is 0-31		1
airespaceACL	String	No			ACL
webRedirection	List	No			
• WebRedirectionType	String	Yes	Value MUST be one of the following: CentralizedWebAuth, HotSpot, NativeSupplicantProvisioning, ClientProvisioning. The WebRedirectionType must fit the portalName		Centralized-WebAuth
• acl	String	Yes			acl
• portal-Name	String	Yes	A portal that exist in the DB and fits the WebRedirectionType		Sponsored Guest Portal (default)
• staticIPHost-Name-FQDN	String	No			10.56.54.200

continues on next page

Table 20 – continued from previous page

• displayC- ertifi- catesRe- newalMes- sages	Boolean	No	The displayC- ertificatesRe- newalMes- sages is mandatory when ‘We- bRedirection- Type’ value is ‘Central- izedWebAuth’. For all other ‘WebRedi- rectionType’ values the field must be ignored	true	
accessType	Enum	No	Allowed Values: AC- CESS_ACCEPT, AC- CESS_REJECT	AC- CESS_ACCEPT	
authzProfile- Type	Enum	No	Allowed Val- ues: SWITCH, TRUSTSEC, TACACS	SWITCH	
			SWITCH is used for Standard Au- thorization Profiles		
profileName	String	No		Cisco	
acl	String	No			aclfilter
daclName	String	No			PER- MIT_ALL_IPV4_TRAFFIC
autoSmartPort	String	No			autoSmartPort
interfaceTem- plate	String	No			interfaceTem- plate
ipv6ACLFILTER	String	No			ipv6ACLFILTER
avcProfile	String	No			avcProfile
asaVpn	String	No			Cisco:cisco- call-type
trackMove- ment	Boolean	No		false	
serviceTem- plate	Boolean	No		false	
easywiredSes- sionCandidate	Boolean	No		false	
voiceDomain- Permission	Boolean	No		false	
neat	Boolean	No		false	
webAuth	Boolean	No		false	

continues on next page

Table 20 – continued from previous page

macSecPolicy	Enum	No	Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE		MUST_SECURE
reauth	List	No			
• connectivity	Enum	Yes	Allowed Values: DEFAULT, RA-DIUS_REQUEST		RA-DIUS_REQUEST
• timer	Integer	Yes	Valid range is 1-65535		1800
advancedAttributes	List	No			
• leftHand-SideDictionary-Attribute	List	Yes	Left side Dictionary and Attribute		
• dictionary-Name	String	Yes	Dictionary name		
• attribute-Name	String	Yes	Attribute name		
• rightHand-SideAttribute-Value	List	Yes	Attribute value can be of type AttributeValue or Advanced-DictionaryAttribute. For AttributeValue the value is String, For Advanced-Dictionary-Attribute the value is dictionaryName and attributeName properties		
ipv6DaclName	String	No			PERMIT_ALL_IPV6_TRAFFIC
airespaceIPv6ACL	String	No			ACL6

`get_authorization_profile_by_name(name, headers=None, **query_parameters)`

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_id*

update_authorization_profile_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.

- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_authorization_profile_by_id*

delete_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_authorization_profile_by_id*

get_authorization_profiles(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles***get_authorization_profiles_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles_generator*

```
create_authorization_profile(access_type=None, acl=None, advanced_attributes=None,
                             agentless_posture=None, airespace_acl=None,
                             airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
                             auto_smart_port=None, avc_profile=None, dacl_name=None,
                             description=None, easywired_session_candidate=None, id=None,
                             interface_template=None, ipv6_acl_filter=None,
                             ipv6_dacl_name=None, mac_sec_policy=None, name=None,
                             neat=None, profile_name=None, reauth=None, service_template=None,
                             track_movement=None, vlan=None, voice_domain_permission=None,
                             web_auth=None, web_redirection=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API creates an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.

- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_authorization_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

byod_portal**class ByodPortal**

Identity Services Engine BYODPortal API (version: 3.1.1).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

BYOD Portal API provides the ability to Create, Read, Update, Delete and Search BYOD portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		BYOD Portal (default)
id	String	No	Resource UUID, mandatory for update		9a9b910c-54d3-44a4-a3c3-dd007c171599

continues on next page

Table 21 – continued from previous page

description	String	No			Default portal and user experience used when employees register a personal device on the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?portalId=54d3-44a4-a3c3-dd007c171599
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	BYOD	
settings	List	No	Defines all of the settings groups available for a BYOD		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		["eth0", "bond0"]

continues on next page

Table 21 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• end- pointI- dentity- Group	String	Yes	Unique Id of the endpoint identity group where user's devices will be added. Used only in Hotspot Portal		
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• byodSet- tings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWel- comeSet- tings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enable- BYOD	Boolean	No		true	
• en- ableGues- tAccess	Boolean	No		false	

continues on next page

Table 21 – continued from previous page

• re-requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No		false	
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodRegistrationSettings	List	No	Configuration of BYOD endpoint Registration step configuration		
• showDeviceID	Boolean	No	Display Device ID field during registration	true	
• endpointIdentityGroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521

continues on next page

Table 21 – continued from previous page

• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Au- thentication Success where should device be redirected.	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		Redirect URL
• support- InfoSet- tings	List	No	Configuration of BYOD endpoint wel- come step configuration		
• in- cludeSup- portIn- foPage	Boolean	No		false	
• in- cludeMacAddr	Boolean	No		false	
• in- cludeIpAd- dress	Boolean	No		false	
• include- BrowserUser- Agent	Boolean	No		false	
• include- Policy- Server	Boolean	No		false	
• include- Failure- Code	Boolean	No		false	

continues on next page

Table 21 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available for a BYOD		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 21 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 21 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			BYOD Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 21 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_byod_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_byod_portal_by_id*

update_byod_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a BYOD portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_byod_portal_by_id`

```
delete_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_byod_portal_by_id`

```
get_byod_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                headers=None, **query_parameters)
```

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal*

get_byod_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_byod_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

backup_and_restore**class BackupAndRestore**

Identity Services Engine Backup And Restore API (version: 3.1.1).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_last_status`(*headers=None, **query_parameters*)Alias for `get_last_config_backup_status`**`restore_config_backup`**(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **`backup_encryption_key`** (*string*) – The encryption key which was provided at the time of taking backup., property of the request body.
- **`repository_name`** (*string*) – Name of the configured repository where the backup file exists., property of the request body.
- **`restore_file`** (*string*) – Name of the backup file to be restored on ISE node., property of the request body.
- **`restore_include_adeos`** (*string*) – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

restore(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *restore_config_backup*

update_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description (string)** – Description of the backup., property of the request body.
- **backup_encryption_key (string)** – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name (string)** – The backup file will get saved with this name., property of the request body.
- **end_date (string)** – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency (string)** – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.

- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘DISABLE’ and ‘ENABLE’.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are ‘FRI’, ‘MON’, ‘SAT’, ‘SUN’, ‘THU’, ‘TUE’ and ‘WED’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None,
        frequency=None, month_day=None, repository_name=None, start_date=None, status=None,
        time=None, week_day=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.1.1).

Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

The certificate profile API allows the client to add, search and perform actions on the certificate profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.4	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Certificate_Profile
id	String	No	Resource UUID		f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No			
allowedAsUserName	Boolean	No	To be set true or false	false	
external-identity-store-name	String	No	Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen	[not applicable]	[not applicable]
certificate-attribute-name	ENUM	No	Attribute name of the Certificate Profile - used only when CERTIFICATE is chosen in usernameFrom. Allowed values: - SUBJECT_COMMON_NAME - SUBJECT_ALTERNATIVE_NAME - SUBJECT_SERIAL_NUMBER - SUBJECT - SUBJECT_ALTERNATIVE_NAME_OTHER_NAME - SUBJECT_ALTERNATIVE_NAME_EMAIL - SUBJECT_ALTERNATIVE_NAME_DNS. - Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN	SUBJECT_COMMON_NAME	
match-Mode	ENUM	No	Match mode of the Certificate Profile. Allowed values: NEVER, RESOLVE_IDENTITY_AMBIGUITY, BINARY_COMPARISON	NEVER	
username-From	ENUM	No	The attribute in the certificate where the user name should be taken from.	CERTIFICATE	

get_certificate_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_certificate_profile_by_name`*

`get_certificate_profile_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a certificate profile by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_certificate_profile_by_id`*

```
update_certificate_profile_by_id(id, allowed_as_user_name=None,
                                certificate_attribute_name=None, description=None,
                                external_identity_store_name=None, match_mode=None,
                                name=None, username_from=None, headers=None,
                                payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allowed_as_user_name=None*, *certificate_attribute_name=None*, *description=None*, *external_identity_store_name=None*, *match_mode=None*, *name=None*, *username_from=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_certificate_profile_by_id*

get_certificate_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile*

get_certificate_profile_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.

- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_certificate_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificate_template**class CertificateTemplate**

Identity Services Engine CertificateTemplate API (version: 3.1.1).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

The certificate template API provides the ability to search for certificate templates.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.2	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
raProfile-Name	String	Yes	RA profile for the Certificate template	ISE internal CA
keySize	Integer	No	Key Size of the Certificate Template	2048 1024
validity	Integer	No	Validity period of the Certificate Template: Valid Range 21 - 3652	730

get_certificate_template_by_name(name, headers=None, **query_parameters)

This API allows the client to get a certificate template by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_name*

get_certificate_template_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *`get_certificate_template_generator`***`get_version`**(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.1.1).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csrs_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
generate_csr(allow_wild_card_cert=None, certificate_policies=None, digest_type=None,  
             hostnames=None, key_length=None, key_type=None, portal_group_tag=None,  
             san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None,  
             subject_common_name=None, subject_country=None, subject_org=None,  
             subject_org_unit=None, subject_state=None, used_for=None, headers=None,  
             payload=None, active_validation=True, **query_parameters)
```

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following parameters are present in POST request body

PARAMETER DESCRIPTION

EXAMPLE hostnames List of Cisco ISE node hostnames for which CSRs should be generated

“hostnames”: [“ise-host1”, “ise-host2”] allowWildCardCert Allow use of WildCards in certificates

“allowWildCardCert”: false keyLength * required Length of the key used for CSR generation (required).

“keyLength”: “512” keyType * required Type of key used for CSR generation either RSA or ECDSA (required).

“keyType”: “RSA” digestType * required Hash algorithm used for signing CSR (required).

“digestType”: “SHA-256” usedFor * required Certificate usage (required).

“usedFor”: “MULTI-USE” certificatePolicies Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs.

“certificatePolicies”: “Certificate Policies” subjectCommonName * required Certificate common name (CN) (required).

“subjectCommonName”: “\$FQDN\$” subjectOrgUnit Certificate organizational unit (OU).

“subjectOrgUnit”: “Engineering” subjectOrg Certificate organization (O).

“subjectOrg”: “Cisco” subjectCity Certificate city or locality (L).

“subjectCity”: “San Jose” subjectState Certificate state (ST).

“subjectState”: “California” subjectCountry Certificate country (C).

“subjectCountry”: “US” sanDNS Array of SAN (Subject Alternative Name) DNS entries (optional).

“sanDNS”: [“ise.example.com”] sanIP Array of SAN IP entries (optional).

“sanIP”: [“1.1.1.1”] sanURI Array of SAN URI entries (optional).

“sanURI”: [“https://1.1.1.1”] sanDir Array of SAN DIR entries (optional).

“sanDir”: [“CN=AAA,DC=COM,C=IL”] portalGroupTag Portal Group Tag when using certificate for PORTAL service

“portalGroupTag”: “Default Portal Certificate Group”

NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames

When certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – keyType, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.

- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.
- **used_for** (*string*) – usedFor, property of the request body. Available values are ‘ADMIN’, ‘DTLS- AUTH’, ‘EAP-AUTH’, ‘IMS’, ‘MULTI-USE’, ‘PORTAL’, ‘PXGRID’ and ‘SAML’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname*, *id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*, ***query_parameters*)

Response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type*DownloadResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node for given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_csr_by_id`(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on given HostName and ID.

Parameters

- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host of which CSR's should be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the Certificate Signing Request to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`regenerate_ise_root_ca`(*remove_existing_ise_intermediate_csr=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API initiates regeneration of Cisco ISE root CA certificate chain. Response contains ID which can be used to track the status. Setting “removeExistingISEIntermediateCSR” to true removes existing Cisco ISE Intermediate CSR.

Parameters

- **remove_existing_ise_intermediate_csr** (*boolean*) – Setting this attribute to true removes existing Cisco ISE Intermediate CSR, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

renew_certificates(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API initiates regeneration of certificates. Response contains ID which can be used to track the status.

Parameters

- **cert_type** (*string*) – certType, property of the request body. Available values are 'IMS' and 'OCSP'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
portal_group_tag=None, pxgrid=None, radius=None, saml=None,
validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
**query_parameters)
```

Bind CA Signed Certificate. NOTE: This API requires an

existing Certificate Signing Request, and the root certificate must already be trusted. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body **PARAMETER DESCRIPTION EXAMPLE** name Friendly name of the certificate. “name”: “CA Signed Certificate” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

```
{sub(/
```

```
/, “”); printf “%csn”, $0;}’ <<your .pem file>>
```

to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid binding of expired certificates (not Secure). “allowOutOfDateCert”: true allowReplacementOfCertificates * required Allow Replacement of certificates (required). “allowReplacementOfCertificates”: true allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADIUS server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”: false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal Certificate Group” validateCertificateExtensions Validate Certificate Extensions “validateCertificateExtensions”: false Following roles can be used in any combinations **ROLE DEFAULT WARNING** Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the
Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

data(string): Signed certificate data (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

host_name(string): Name of Host whose CSR ID has been provided (required), property of the request body.

id(string): ID of the generated CSR (required), property of the request body.

ims(boolean): Use certificate for the Cisco ISE Messaging Service, property of the request body.

name(string): Friendly Name of the certificate, property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

*****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Raises:

`TypeError`: If the parameter types are incorrect. `MalformedRequest`: If the request body created is invalid. `ApiError`: If the Identity Services Engine cloud returns an error.

export_system_certificate(*export=None, id=None, password=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Export System Certificate. Following parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE
id * required ID of a System Certificate (required). "id": "CERT-ID" export One of the below option is required "CERTIFICATE" : Export only certificate without private key "CERTIFICATE_WITH_PRIVATE_KEY" : Export both certificate and private key ("certificatePassword" is required). "export": "CERTIFICATE_WITH_PRIVATE_KEY" password * required Certificate password (required if "export" : CERTIFICATE_WITH_PRIVATE_KEY). Password constraints: Alphanumeric Minimum of 8 Characters Maximum of 100 Characters "password": "certificate password" NOTE: The response of this API carries a ZIP file containing the certificate and private key if "export" : "CERTIFICATE_WITH_PRIVATE_KEY" in the request. If "export" : "CERTIFICATE" in request body, the response carries a ZIP file containing only the certificate. WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are 'CERTIFICATE' and 'CERTIFICATE_WITH_PRIVATE_KEY'.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
generate_self_signed_certificate(admin=None, allow_extended_validity=None,
                                allow_portal_tag_transfer_for_same_subject=None,
                                allow_replacement_of_certificates=None,
                                allow_replacement_of_portal_group_tag=None,
                                allow_role_transfer_for_same_subject=None,
                                allow_san_dns_bad_name=None,
                                allow_san_dns_non_resolvable=None,
                                allow_wild_card_certificates=None, certificate_policies=None,
                                digest_type=None, eap=None, expiration_ttl=None,
                                expiration_ttl_unit=None, host_name=None, key_length=None,
                                key_type=None, name=None, portal=None,
                                portal_group_tag=None, pxgrid=None, radius=None, saml=None,
                                san_dns=None, san_ip=None, san_uri=None, subject_city=None,
                                subject_common_name=None, subject_country=None,
                                subject_org=None, subject_org_unit=None, subject_state=None,
                                headers=None, payload=None, active_validation=True,
                                **query_parameters)
```

Generate Self-signed Certificate NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. NOTE: Wildcard certificate and SAML certificate can be generated only on PSPAN or Standalone Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE `hostName` * required Hostname or FQDN of the node in which certificate needs to be created (required). `hostName`: `"ise-node-001"` name Friendly name of the certificate. `name`: `"Self-signed System Certificate"` `subjectCommonName` Certificate common name (CN) NOTE: 1. CN is Mandatory if SAN not configured. 2. Subject can contain a multi- valued CN. For multi-valued RDNs, follow the format `"CN=value1, CN=value2"` `subjectCommonName`: `"$FQDN$" subjectOrgUnit` Certificate organizational unit (OU) NOTE: Subject can contain a multi-valued OU. For multi- valued RDNs, follow the format `"OU=value1, OU=value2"` `subjectOrgUnit`: `"Engineering"` `subjectOrg` Certificate organization (O) NOTE: Subject can contain a multi-valued O fields. For multi-valued RDNs, follow the format `"O=value1, O=value2"` `subjectOrg`: `"Cisco"` `subjectCity` Certificate city or locality (L) `subjectCity`: `"San Jose"` `subjectState` Certificate state (ST) `subjectState`: `"California"` `subjectCountry` Certificate country (C) `subjectCountry`: `"US"` `sanDNS` Array of SAN (Subject Alternative Name) DNS entries `sanDNS`: `["ise.example.com"]` `sanIP` Array of SAN IP entries `sanIP`: `["1.1.1.1"]` `sanURI` Array of SAN URI entries `sanURI`: `["https://1.1.1.1"]` `keyType` * required Algorithm to use for certificate public key creation (required). `keyType`: `"RSA"` `keyLength` * required Bit size of the public key (required). `keyLength`: `"4096"` `digestType` * required Digest to sign with (required). `digestType`: `"SHA-384"` `certificatePolicies` Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs. `certificatePolicies`: `"Certificate Policies"` `expirationTTL` * required Certificate expiration value (required). NOTE: Expiration TTL should be within Unix time limit `expirationTTL`: `2` `expirationTTLUnit` * required Certificate expiration unit (required). `expirationTTLUnit`: `"years"` `admin` Use certificate to authenticate the Cisco ISE Admin Portal `admin`: `false` `eap` Use certificate for EAP protocols that use SSL/TLS tunneling `eap`: `false` `radius` Use certificate for RADSec server `radius`: `false` `pxgrid` Use certificate for the pxGrid Controller `pxgrid`: `false` `saml` Use certificate for SAML Signing `saml`: `false` `portal` Use certificate for portal `portal`: `false` `portalGroupTag` Portal Group Tag for using certificate with portal role `portalGroupTag`: `"Default Portal Certificate Group"` `allowReplacementOfPortalGroupTag` * required Allow Replacement of Portal Group Tag (required). `allowReplacementOfPortalGroupTag`: `true` `allowWildCardCertificates` Allow use of WildCards in certificates `allowWildCardCertificates`: `false` `allowReplacementOfCertificates` * required Allow replacement of certificates (required). `allowReplacementOfCertificates`: `true` `allowExtendedValidity` * required Allow generation of self-signed

certificate with validity greater than 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject * required Allow the transfer of roles to certificates with same subject (required). If the matching certificate on Cisco ISE has either admin or portal role and if request has admin or portal role selected along with allowRoleTransferForSameSubject parameter as true, self- signed certificate would be generated with both admin and portal role enabled “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject * required Acquire the group tag of the matching certificate (required). If the request portal group tag is different from the group tag of matching certificate (If matching certificate in Cisco ISE has portal role enabled), self- signed certificate would be generated by acquiring the group tag of matching certificate if allowPortalTagTransferForSameSubject parameter is true “allowPortalTagTransferForSameSubject”: true allowSanDnsBadName * required Allow generation of self-signed certificate with bad Common Name & SAN Values [like “example.org.”,”invalid.”,”test.”,”localhost” ,etc.] (required). SECURITY ALERT: It is recommended to use “allowSanDnsBadName”: false to avoid generation of certificates with bad Common Name & SAN Values which are not secure “allowSanDnsBadName”: true allowSanDnsNonResolvable * required Allow generation of self-signed certificate with non resolvable Common Name or SAN Values (required). “allowSanDnsNonResolvable”: true ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. SAML False SAML cannot be used with other Usage. .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_extended_validity** (*boolean*) – Allow generation of self-signed certificate with validity greater than 398 days, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_certificates** (*boolean*) – Allow Replacement of certificates, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag, property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **allow_san_dns_bad_name** (*boolean*) – Allow usage of SAN DNS Bad name, property of the request body.
- **allow_san_dns_non_resolvable** (*boolean*) – Allow use of non resolvable Common Name or SAN Values, property of the request body.
- **allow_wild_card_certificates** (*boolean*) – Allow Wildcard Certificates, property of the request body.
- **certificate_policies** (*string*) – Certificate Policies, property of the request body.
- **digest_type** (*string*) – Digest to sign with, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl** (*integer*) – Certificate expiration value, property of the request body.

- **expiration_ttl_unit** (*string*) – Certificate expiration unit, property of the request body. Available values are ‘days’, ‘months’, ‘weeks’ and ‘years’.
- **host_name** (*string*) – Hostname of the Cisco ISE node in which self-signed certificate should be generated., property of the request body.
- **key_length** (*string*) – Bit size of public key, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – Algorithm to use for certificate public key creation, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **name** (*string*) – Friendly name of the certificate., property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **san_dns** (*list*) – Array of SAN (Subject Alternative Name) DNS entries, property of the request body (list of strings).
- **san_ip** (*list*) – Array of SAN IP entries, property of the request body (list of strings).
- **san_uri** (*list*) – Array of SAN URI entries, property of the request body (list of strings).
- **subject_city** (*string*) – Certificate city or locality (L), property of the request body.
- **subject_common_name** (*string*) – Certificate common name (CN), property of the request body.
- **subject_country** (*string*) – Certificate country (C), property of the request body.
- **subject_org** (*string*) – Certificate organization (O), property of the request body.
- **subject_org_unit** (*string*) – Certificate organizational unit (OU), property of the request body.
- **subject_state** (*string*) – Certificate state (ST), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
import_system_certificate(admin=None, allow_extended_validity=None,
                        allow_out_of_date_cert=None,
                        allow_portal_tag_transfer_for_same_subject=None,
                        allow_replacement_of_certificates=None,
                        allow_replacement_of_portal_group_tag=None,
                        allow_role_transfer_for_same_subject=None,
                        allow_sha1_certificates=None, allow_wild_card_certificates=None,
                        data=None, eap=None, ims=None, name=None, password=None,
                        portal=None, portal_group_tag=None, private_key_data=None,
                        pxgrid=None, radius=None, saml=None,
                        validate_certificate_extensions=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE:

The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. “name”: “System certificate” password * required Password of the certificate to be imported (required). “password”: “certificate password” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required).

Use awk ‘NF {sub(/

/, “”); printf “%sn”, \$0;}’ <<your

.pem file>> to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” privateKeyData * required Plain-text contents of the private key file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

{sub(/

/, “”); printf “%sn”, \$0;}’ <<your .pem file>>

to extract privateKeyData from private key file. “data”: “Plain-text contents of the private key file.” allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid import of expired certificates (not Secure). “allowOutOfDateCert”: true allowSHA1certificates * required Allow import of certificate with signature that uses the SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use “allowSHA1certificates”: false to avoid import of SHA1 based certificates (less secure). “allowSHA1certificates”: true allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject Allow the transfer of roles to certificates with same subject “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject Acquire the group tag of the matching certificate “allowPortalTagTransferForSameSubject”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADSec server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”:

false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal certificate Group” allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true allowWildcardcertificates Allow use of WildCards in certificates “allowWildcardcertificates”: false validatecertificateExtensions Validate certificate extensions “validatecertificateExtensions”: false Following roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the

Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of

certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_portal_tag_transfer_for_same_subject(boolean):

Allow overwriting the portal tag from matching certificate of same subject, property of the request body.

allow_replacement_of_certificates(boolean): Allow

Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow

Replacement of Portal Group Tag (required), property of the request body.

allow_role_transfer_for_same_subject(boolean): Allow

transfer of roles for certificate with matching subject , property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

allow_wild_card_certificates(boolean): Allow Wildcard

certificates, property of the request body.

data(string): Certificate Content (required), property

of the request body.

eap(boolean): Use certificate for EAP protocols that use

SSL/TLS tunneling, property of the request body.

ims(boolean): Use certificate for the Cisco ISE

Messaging Service, property of the request body.

name(string): Name of the certificate, property of the

request body.

password(string): Certificate Password (required),,

property of the request body.

portal(boolean): Use for portal, property of the request

body.

portal_group_tag(string): Set Group tag, property of the request body.

private_key_data(string): Private Key data (required), property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate certificate extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificate_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API provides details of a System Certificate of a particular node based on given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **id** (*basestring*) – id path parameter. ID of the system certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
update_system_certificate(host_name, id, admin=None,
                           allow_portal_tag_transfer_for_same_subject=None,
                           allow_replacement_of_portal_group_tag=None,
                           allow_role_transfer_for_same_subject=None, description=None,
                           eap=None, expiration_ttl_period=None, expiration_ttl_units=None,
                           ims=None, name=None, portal=None, portal_group_tag=None,
                           pxgrid=None, radius=None, renew_self_signed_certificate=None,
                           saml=None, headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

Update a System Certificate. NOTE: Renewing a certificate causes an application server restart on the selected node. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body

PARAMETER	DESCRIPTION	EXAMPLE
name	Friendly name of the certificate.	"name": "System Certificate"
description	Description of the certificate	"description": "Description of certificate"
admin	Use certificate to authenticate the Cisco ISE Admin Portal	"admin": false
eap	Use certificate for EAP protocols that use SSL/TLS tunneling	"eap": false
radius	Use certificate for RADIUS server	"radius": false
pxgrid	Use certificate for the pxGrid Controller	"pxgrid": false
ims	Use certificate for the Cisco ISE Messaging Service	"ims": false
saml	Use certificate for SAML Signing	"saml": false
portal	Use certificate for portal	"portal": false
portalGroupTag	Portal Group Tag for using certificate with portal role	"portalGroupTag": "Default Portal Certificate Group"
allowReplacementOfPortalGroupTag	* required Allow Replacement of Portal Group Tag (required).	"allowReplacementOfPortalGroupTag": true
allowRoleTransferForSameSubject	* required Allow transfer of roles to certificates with same subject (required).	"allowRoleTransferForSameSubject": true
allowPortalTagTransferForSameSubject	* required Acquire group tag of the matching certificate (required).	"allowPortalTagTransferForSameSubject": true
renewSelfSignedCertificate	Renew Self- signed Certificate	"renewSelfSignedCertificate": false
expirationTTLPeriod	Expiration Period	"expirationTTLPeriod": 365
expirationTTLUnits	Expiration Units in one of the below formats days / weeks / months / years	"expirationTTLUnits": "days"

Following roles can be used in any combinations

ROLE	DEFAULT	WARNING
Admin	False	Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates
EAP	Authentication	False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
RADIUS	DTLS	False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
SAML	False	SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.
- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are 'days', 'months', 'weeks' and 'years'.
- **ims** (*boolean*) – Use certificate for the Cisco ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self- signed Certificate, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_system_certificate_by_id`(*host_name, id, allow_wildcard_delete=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API deletes a System Certificate of a particular node based on given HostName and ID.

Parameters

- **`allow_wildcard_delete`** (*boolean*) – If the given certificate to be deleted is a wildcard certificate, corresponding certificate gets deleted on rest of the nodes in the deployment as well., property of the request body.
- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host from which System Certificate needs to be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the System Certificate to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_certificates`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM- dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_trusted_certificate(*id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*,
 ***query_parameters*)

The response of this API carries a trusted certificate file mapped to the requested ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be exported.

- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_trust_certificate(allow_basic_constraint_cafalse=None, allow_out_of_date_cert=None,
                        allow_sha1_certificates=None, data=None, description=None, name=None,
                        trust_for_certificate_based_admin_auth=None,
                        trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                        trust_for_ise_auth=None, validate_certificate_extensions=None,
                        headers=None, payload=None, active_validation=True,
                        **query_parameters)
```

Import an X509 certificate as a trust certificate. NOTE:

Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body `PARAMETER DESCRIPTION` EXAMPLE name Friendly name of the certificate “name”: “Trust Certificate” description Description of the certificate “description”: “Imported Trust Certificate” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use `awk 'NF {sub(/ /, "");`

```
printf “%sn”, $0; }’ <<your .pem file>>
```

to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” `allowOutOfDateCert` * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid import of expired certificates (not Secure). “allowOutOfDateCert”: true `allowSHA1Certificates` * required Allow import of certificate with signature that uses SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use “allowSHA1Certificates”: false to avoid import of SHA1 based certificates (less secure). “allowSHA1Certificates”: true `allowBasicConstraintCAFalse` * required Allow certificates with Basic Constraints CA Field as False (required). SECURITY ALERT: It is recommended to use “allowBasicConstraintCAFalse”: false to avoid import of certificates with Basic Constraints CA Field as False (not Secure). “allowBasicConstraintCAFalse”: true `trustForIseAuth` Trust for authentication within Cisco ISE “trustForIseAuth”: false `trustForClientAuth` Trust for client authentication and Syslog “trustForClientAuth”: false `trustForCertificateBasedAdminAuth` Trust for

certificate based Admin authentication “trustForCertificateBasedAdminAuth”: false trustForCiscoServicesAuth Trust for authentication of Cisco Services “trustForCiscoServicesAuth”: false validateCertificateExtensions Validate extensions for trust certificate “validateCertificateExtensions”: false NOTE: If name is not set, a default name with the following format is used: common-name#issuer#nnnnn where “nnnnn” is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate is trusted in Cisco ISE. The objective here is to distinguish between certificates that are used for trust within an Cisco ISE deployment and public certificates that are used to trust Cisco services. Typically, you do not want to use a given certificate for both purposes. Trusted For Usage Authentication within Cisco ISE Use “trustForIseAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact Cisco ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Args:

allow_basic_constraint_cafalse(boolean): Allow

certificates with Basic Constraints CA Field as False (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

data(string): Certificate content (required), property

of the request body.

description(string): Description of the certificate,

property of the request body.

name(string): Name of the certificate, property of the

request body.

trust_for_certificate_based_admin_auth(boolean): Trust

for Certificate based Admin authentication, property of the request body.

trust_for_cisco_services_auth(boolean): Trust for

authentication of Cisco Services, property of the request body.

trust_for_client_auth(boolean): Trust for client

authentication and Syslog, property of the request body.

trust_for_ise_auth(boolean): Trust for authentication

within Cisco ISE, property of the request body.

validate_certificate_extensions(boolean): Validate trust

certificate extension, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

.

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(id, headers=None, **query_parameters)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id (basestring)** – id path parameter. ID of the trust certificate.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_trusted_certificate(id, authenticate_before_crl_received=None, automatic_crl_update=None,
                           automatic_crl_update_period=None, automatic_crl_update_units=None,
                           crl_distribution_url=None, crl_download_failure_retries=None,
                           crl_download_failure_retries_units=None, description=None,
                           download_crl=None, enable_ocsp_validation=None,
                           enable_server_identity_check=None, ignore_crl_expiration=None,
                           name=None, non_automatic_crl_update_period=None,
                           non_automatic_crl_update_units=None,
                           reject_if_no_status_from_ocs_p=None,
                           reject_if_unreachable_from_ocs_p=None, selected_ocsp_service=None,
                           status=None, trust_for_certificate_based_admin_auth=None,
                           trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                           trust_for_ise_auth=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

Update a trusted certificate present in Cisco ISE trust store. Following parameters are used in PUT request body

PARAMETER	DESCRIPTION	EXAMPLE	name	* required	Friendly name of the certificate (required)
"name"	"Trust Certificate"	status	Status of the certificate	"status"	"Enabled"
description	Description of the certificate	"description"	"Certificate for secure connection to cisco.com"	trustForIseAuth	Trust for authentication within Cisco ISE
trustForIseAuth	Trust for authentication within Cisco ISE	false	trustForClientAuth	Trust for client authentication and Syslog	
trustForClientAuth	Trust for client authentication and Syslog	false	trustForCertificateBasedAdminAuth	Trust for certificate based Admin authentication	
trustForCertificateBasedAdminAuth	Trust for certificate based Admin authentication	false	trustForCiscoServicesAuth	Trust for authentication of Cisco Services	
trustForCiscoServicesAuth	Trust for authentication of Cisco Services	false	enableOCSPValidation	Switch to enable or disable OSCP Validation	
enableOCSPValidation	Switch to enable or disable OSCP Validation	false	selectedOCSPService	Name of selected OSCP Service	
selectedOCSPService	Name of selected OSCP Service	"INTERNAL_OCSP_SERVICE"	rejectIfNoStatusFromOCSP	Switch to reject certificate if there is no status from OSCP	
rejectIfNoStatusFromOCSP	Switch to reject certificate if there is no status from OSCP	false	rejectIfUnreachableFromOCSP	Switch to reject certificate if unreachable from OSCP	
rejectIfUnreachableFromOCSP	Switch to reject certificate if unreachable from OSCP	false	downloadCRL	Switch to enable or disable download of CRL	
downloadCRL	Switch to enable or disable download of CRL	false	crlDistributionUrl	Certificate Revocation List Distribution URL	
crlDistributionUrl	Certificate Revocation List Distribution URL	"CRL distribution URL"	automaticCRLUpdate	Switch to enable or disable automatic CRL update	
automaticCRLUpdate	Switch to enable or disable automatic CRL update	false	automaticCRLUpdatePeriod	Automatic CRL update period	
automaticCRLUpdatePeriod	Automatic CRL update period	5	automaticCRLUpdateUnits	Unit of time for automatic CRL update	
automaticCRLUpdateUnits	Unit of time for automatic CRL update	"Minutes"	nonAutomaticCRLUpdatePeriod	Non automatic CRL update period	
nonAutomaticCRLUpdatePeriod	Non automatic CRL update period	1	nonAutomaticCRLUpdateUnits	Unit of time of non automatic CRL update	
nonAutomaticCRLUpdateUnits	Unit of time of non automatic CRL update	"Hours"	crlDownloadFailureRetries	If CRL download fails, wait time before retry	
crlDownloadFailureRetries	If CRL download fails, wait time before retry	10	crlDownloadFailureRetriesUnits	Unit of time before retry if CRL download fails	
crlDownloadFailureRetriesUnits	Unit of time before retry if CRL download fails	"Minutes"	enableServerIdentityCheck	Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL	
enableServerIdentityCheck	Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL	false	authenticateBeforeCRLReceived	Switch to enable or disable CRL Verification if CRL is not Received	
authenticateBeforeCRLReceived	Switch to enable or disable CRL Verification if CRL is not Received	false	ignoreCRLEExpiration	Switch to enable or disable ignore CRL Expiration	
ignoreCRLEExpiration	Switch to enable or disable ignore CRL Expiration	false	trustForIseAuth	Trusted For Usage Authentication within Cisco ISE	
trustForIseAuth	Trusted For Usage Authentication within Cisco ISE	true	trustForClientAuth	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	
trustForClientAuth	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	true	trustForCertificateBasedAdminAuth	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	
trustForCertificateBasedAdminAuth	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	true	trustForCiscoServicesAuth	Use if the certificate is used for trusting external Cisco services, such as Feed Service	
trustForCiscoServicesAuth	Use if the certificate is used for trusting external Cisco services, such as Feed Service	true	enableOCSPValidation	Usage Validation against OSCP service	
enableOCSPValidation	Usage Validation against OSCP service	true	selectedOCSPService	Use OSCP Service name	
selectedOCSPService	Use OSCP Service name	"Name of OSCP Service"	selectedOCSPService	Name of the OSCP service against which the certificate should be validated	
selectedOCSPService	Name of the OSCP service against which the certificate should be validated	"Name of OSCP Service"		Note: "selectedOCSPService" value is used if "enableOCSPValidation" has been set true. Re-	

ject the request if OCSP returns UNKNOWN status Use “rejectIfNoStatusFromOCSP”:true to reject the certificate if the OCSP service returns UNKNOWN status Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OCSP Responder is unreachable Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OCSP service is unreachable. Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field `crlDistributionUrl` CRL distribution url Use “`crlDistributionUrl`” to specify the URL from where the CRL should be downloaded Note: “`crlDistributionUrl`” value is used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and `automaticCRLUpdatePeriod`, `automaticCRLUpdatePeriod` to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod”, `nonAutomaticCRLUpdateUnits` to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” to set retry time period if CRL download fails Note: “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable or disable CRL verification if CRL is not received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable or disable automatic CRL update, property of the request body.
- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable or disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable or disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.

- **ignore_crl_expiration** (*boolean*) – Switch to enable or disable ignore CRL expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.
- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocs_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘Disabled’ and ‘Enabled’.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within Cisco ISE, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities

class ClearThreatsAndVulnerabilities

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.1.1).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

Clear Threats and Vulnerabilities API allows the user to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.1	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	Yes	Resource UUID value	
macAd-dresses	String	Yes	One or more endpoint MAC ad-dresses	["00:00:00:00:00:F2", "00:00:00:00:00:F3"]

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_threats_and_vulnerabilities*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

consumer**class Consumer**

Identity Services Engine Consumer API (version: 3.1.1).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

create_account(*node_name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

AccountCreate.

Parameters

- **node_name** (*string*) – nodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_account*

activate_account(*description=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

access_secret(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccessSecret.

Parameters

- **peer_node_name** (*string*) – peerNodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules**class DeviceAdministrationAuthenticationRules**

Identity Services Engine Device Administration - Authentication Rules API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_authentication_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authentication rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rules`*

```
create_device_admin_authentication_rule(policy_id, identity_source_name=None,
                                         if_auth_fail=None, if_process_fail=None,
                                         if_user_not_found=None, link=None, rule=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

Device Admin Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None,  
        if_user_not_found=None, link=None, rule=None, headers=None, payload=None,  
        active_validation=True, **query_parameters)
```

Alias for *create_device_admin_authentication_rule*

```
reset_hit_counts_device_admin_authentication_rules(policy_id, headers=None,  
                                                    **query_parameters)
```

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)
```

Alias for *reset_hit_counts_device_admin_authentication_rules*

```
get_device_admin_authentication_rule_by_id(id, policy_id, headers=None, **query_parameters)
```

Device Admin Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rule_by_id`*

`update_device_admin_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update rule.

Parameters

- **`identity_source_name (string)`** – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail (string)`** – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail (string)`** – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found (string)`** – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link (object)`** – link, property of the request body.
- **`rule (object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_device_admin_authentication_rule_by_id`*

`delete_device_admin_authentication_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete rule.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`id`** (*basestring*) – `id` path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *`delete_device_admin_authentication_rule_by_id`*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_local_exception_rules*

create_device_admin_local_exception_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.

- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_local_exception_rule*

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_device_admin_local_exceptions`***`get_device_admin_local_exception_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Device Admin Get local exception rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_device_admin_local_exception_rule_by_id`***`update_device_admin_local_exception_rule_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Device Admin Update local exception rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_local_exception_rule_by_id*

delete_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for `delete_device_admin_local_exception_rule_by_id`

device_administration_authorization_global_exception_rules**class DeviceAdministrationAuthorizationGlobalExceptionRules**

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_policy_set_global_exception_rules(headers=None, **query_parameters)`

Device Admin Get global execption rules.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_device_admin_policy_set_global_exception_rules*

create_device_admin_policy_set_global_exception(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Device Admin Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_global_exceptions*

get_device_admin_policy_set_global_exception_by_rule_id(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_by_rule_id*

update_device_admin_policy_set_global_exception_by_rule_id(*id*, *commands=None*, *link=None*,
profile=None, *rule=None*,
headers=None, *payload=None*,
active_validation=True,
***query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_global_exception_by_rule_id*

device_administration_authorization_rules

class DeviceAdministrationAuthorizationRules

Identity Services Engine Device Administration - Authorization Rules API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for `get_device_admin_authorization_rules`

`create_device_admin_authorization_rule(policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` or dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authorization_rule*

reset_hit_counts_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

get_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_device_admin_authorization_rule_by_id*

update_device_admin_authorization_rule_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *`update_device_admin_authorization_rule_by_id`*

`delete_device_admin_authorization_rule_by_id(id, policy_id, headers=None, **query_parameters)`

Device Admin Delete authorization rule.

Parameters

- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`delete_device_admin_authorization_rule_by_id`*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_command_sets(*headers=None, **query_parameters*)

Device Admin Return list of command sets. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_conditions(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_device_admin_conditions`

`create_device_admin_condition(attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model `LibraryConditionAttributes` , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: `LibraryConditionAndBlock` or `LibraryConditionOrBlock` . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: `ConditionAttributes` , `ConditionAndBlock` , `ConditionOrBlock` , that represent dynamically built Conditions which are not stored in the conditions Library, or using `ConditionReference` , which includes an ID to exist-ing stored condition in the library. The `LibraryCondition` models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (`ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock`), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner mem-bers of the root condition. When using `ConditionReference` model in inner layers, the condition name is not required. `ConditionReference` objects can also include a reference ID to a condition of type `TimeAndDate`

..

Parameters

- **`attribute_name (string)`** – Dictionary attribute name, property of the request body.
- **`attribute_value (string)`** – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children (list)`** – In case type is `andBlock` or `orBlock` additional conditions will be aggre-gated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

get_device_admin_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authorization_rules*

get_device_admin_condition_by_name(*name, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_condition_by_name*

update_device_admin_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers=None*, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_for_policy_sets`(*headers=None, **query_parameters*)Alias for *`get_device_admin_conditions_for_policy_sets`***`get_device_admin_condition_by_id`**(*id, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **`id`** (*basestring*) – id path parameter. Condition id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id, headers=None, **query_parameters*)Alias for *`get_device_admin_condition_by_id`***`update_device_admin_condition_by_id`**(*id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body

(list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_id*

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_device_admin_condition_by_id`

device_administration_dictionary_attributes_list**class DeviceAdministrationDictionaryAttributesList**

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_dictionaries_authentication(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authorization*

get_device_admin_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(headers=None, **query_parameters)

Alias for *get_device_admin_dictionaries_policy_set*

device_administration_identity_stores

class DeviceAdministrationIdentityStores

Identity Services Engine Device Administration - Identity Stores API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_device_admin_identity_stores(headers=None, **query_parameters)

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_device_admin_identity_stores*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_network_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_network_conditions*

create_device_admin_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.

- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_network_condition_by_id*

update_device_admin_network_condition_by_id(*id*, *condition_type=None*, *conditions=None*,
description=None, *link=None*, *name=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are ‘DeviceCondition’, ‘DevicePortCondition’ and ‘EndstationCondition’.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set

class DeviceAdministrationPolicySet

Identity Services Engine Device Administration - Policy Set API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_sets(*headers=None*, ***query_parameters*)

Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *get_device_admin_policy_sets***`create_device_admin_policy_set`**(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` , or, dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **`condition`** (*object*) – condition, property of the request body.
- **`default`** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **`description`** (*string*) – The description for the policy set, property of the request body.
- **`hit_counts`** (*integer*) – The amount of times the policy was matched, property of the request body.
- **`id`** (*string*) – Identifier for the policy set, property of the request body.
- **`is_proxy`** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **`rank`** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **`service_name`** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **`state`** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'disabled', 'enabled' and 'monitor'.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_policy_sets*

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_by_id*

update_device_admin_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.

- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_by_id*

device_administration_profiles

class DeviceAdministrationProfiles

Identity Services Engine Device Administration - Profiles API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

get_device_admin_profiles(*headers=None*, ***query_parameters*)

Device Admin Returns list of shell profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers (*dict*)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_profiles*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_service_names*

device_administration_time_date_conditions

class DeviceAdministrationTimeDateConditions

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_time_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_time_conditions*

create_device_admin_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.

- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
      dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
      dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
      is_negate=None, link=None, name=None, operator=None, week_days=None,
      week_days_exception=None, headers=None, payload=None, active_validation=True,
      **query_parameters)
```

Alias for *create_device_admin_time_condition*

```
get_device_admin_time_condition_by_id(id, headers=None, **query_parameters)
```

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_time_condition_by_id*

update_device_admin_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_device_admin_time_condition_by_id](#)

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [delete_device_admin_time_condition_by_id](#)

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.1.1).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

Downloadable ACL API allows the client to add, delete, update, search and perform actions on downloadable ACL.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute IP version in 2.6	daclType	Added Enum Attribute 'daclType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]		multiline_acl
id	String	Yes	Resource UUID		c1e0e9e0-717f-11eb-9fb2-b6cb23d38630
description	String	No	Use the string n for a newline		description
dacl	String	Yes	The DACL Content. Use the string n for a newline		permit ip any any
daclType	Enum	No	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	

get_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a downloadable ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_downloadable_acl_by_id*

update_downloadable_acl_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string *n* for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string *n* for a newline, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [*_*.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_downloadable_acl_by_id*](#)

delete_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a downloadable ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_downloadable_acl_by_id*](#)

get_downloadable_acl(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl***get_downloadable_acl_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl_generator***create_downloadable_acl**(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string `\n` for a newline, property of the request body.

- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string `n` for a newline, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [`_.-`], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell**class EgressMatrixCell**

Identity Services Engine EgressMatrixCell API (version: 3.1.1).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

Egress Policy Matrix Cell API allows the client to add, update, delete and search egress matrix cells among other operations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version
1	1.1	2.3	Introducing bulk operations

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		ANY-ANY
id	String	No	Resource UUID, mandatory for update		f92c1a900-8c01-11e6-996c-525400b48521
description	String	No			Default egress rule
default-Rule	Enum	Yes	Allowed values: NONE, DENY_IP, PERMIT_IP	NONE	PERMIT_IP
destinationSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521
matrix-CellStatus	Enum	Yes	Allowed values: DISABLED, ENABLED, MONITOR	DISABLED	ENABLED
sgACLs	List	Yes			[“92951ac0-8c01-11e6-996c-525400b48521”]
sourceSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*headers=None, **query_parameters*)

Alias for *clear_all_matrix_cells*

set_all_cells_status(*status, headers=None, **query_parameters*)

his API allows the client to set status of all the egress matrix cells.

Parameters

- **status** (*basestring*) – status path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_status(*status*, *headers=None*, ***query_parameters*)

Alias for *set_all_cells_status*

clone_matrix_cell(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

This API allows the client to clone an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **src_sgt_id** (*basestring*) – srcSgtId path parameter.
- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_egress_matrix_cell_by_id`***`update_egress_matrix_cell_by_id(id, default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update an egress matrix cell.

Parameters

- **`default_rule`** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`destination_sgt_id`** (*string*) – destinationSgtId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`matrix_cell_status`** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgacIs`** (*list*) – sgacIs, property of the request body (list of strings).
- **`source_sgt_id`** (*string*) – sourceSgtId, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*,
matrix_cell_status=None, *name=None*, *sgacIs=None*, *source_sgt_id=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_egress_matrix_cell_by_id*

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-
Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell_generator*

create_egress_matrix_cell(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacIs** (*list*) – sgacIs, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_egress_matrix_cell*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.1.1).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

Endpoint Certificate API allows the client to create endpoint certificates signed by the Cisco ISE Internal CA. This API can takes in certificate request details, create a RSA key pair, create a certificate and return the resulting key pair and certificate as a ZIP file. ZIP files are returned as an octet stream.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
certTemplateName	String	Yes	Name of an Internal CA template	Certificate_Template_Name
format	Enum	Yes	Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN	PKCS8
password	String	Yes	Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#	Password_123
certificateRequest	Map	Yes	Key value map. Must have CN and SAN entries	
• CN	String	Yes	Matches the requester's User Name, unless the Requester is an ERS Admin. ERS Admins are allowed to create requests for any CN	userName [or] machineName
• SAN	String	Yes	Valid MAC Address, delimited by '-'	11-22-33-44-55-66

```
create_endpoint_certificate(cert_template_name=None, certificate_request=None, format=None,
                           password=None, dirpath=None, save_file=None, filename=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to create an endpoint certificate.

Parameters

- **cert_template_name** (*string*) – Name of an Internal CA template, property of the request body.
- **certificate_request** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.

- **format** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **password** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
create(cert_template_name=None, certificate_request=None, format=None, password=None,
        dirpath=None, save_file=None, filename=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_endpoint_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group**class EndpointIdentityGroup**

Identity Services Engine EndpointIdentityGroup API (version: 3.1.1).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

Endpoint Identity Groups API allows the client to add, delete, update, and search endpoint groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.4	Added GetByName operation		

Resource Definition

Attribute	Type	Re-quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		Cisco-Meraki-Devicee
id	String	No	Resource UUID, mandatory for update		1e2700a0-8c00-11e6-996c-525400b48521
description	String	No			Identity Group for Profile: Cisco-Meraki-Device
systemDefined	Boolean	Yes		false	true

get_endpoint_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_id*

update_endpoint_group_by_id(*id*, *description=None*, *name=None*, *system_defined=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_endpoint_group_by_id*

delete_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_group_by_id*

get_endpoint_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups*

get_endpoint_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups_generator*

create_endpoint_group(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

external_radius_server**class ExternalRadiusServer**

Identity Services Engine ExternalRADIUSServer API (version: 3.1.1).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

External RADIUS Server API allows the client to add, delete, update, search and perform actions on external RADIUS server.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Allowed characters are alphanumeric and _ (underscore).		externalRadiusServer1
id	String	No	Resource UUID, mandatory for update		da095377-dce8-486e-933a-6ea788bbf51a
description	String	No			example external radius server
hostIP	String	Yes	The IP of the host - must be a valid IPV4 address		1.1.1.1
sharedSecret	String	Yes	Shared secret maximum length is 128 characters		sharedSecret
enableKeyWrap	Boolean	Yes	KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices		true
encryptionKey	String	No	The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		1616161616161616
authenticatorKey	String	No	The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		2020202020202020
keyInputFormat	Enum	Yes	Specifies the format of the input for fields 'encryptionKey' and 'authenticatorKey'. Allowed Values: ASCII, HEXADECIMAL		ASCII
authenticationPort	Integer	Yes	Valid Range 1 to 65535		1812
accountingPort	Integer	Yes	Valid Range 1 to 65535		1813
time-out	Integer	Yes	Valid Range 1 to 120		5
re-tries	Integer	Yes	Valid Range 1 to 9		3
proxy-Time-out	Integer	No	Valid Range 1 to 600	300	

get_external_radius_server_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for `get_external_radius_server_by_id`

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed charactera are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_external_radius_server_by_id*

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_external_radius_server_by_id*

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server*

get_external_radius_server_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

create_external_radius_server(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.

- **key_input_format** (*string*) – Specifies the format of the input for fields ‘encryption-Key’ and ‘authenticatorKey’. Allowed Values: ASCII HEXADECEIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(accounting_port=None, authentication_port=None, authenticator_key=None, description=None,
        enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None,
        name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_external_radius_server*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

filter_policy**class FilterPolicy**

Identity Services Engine FilterPolicy API (version: 3.1.1).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

Filter Policy API allows clients to add, get, update and delete SXP domain filter policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
subnet	String	No	Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined	subnetAddress
sgt	String	No	SGT name or ID. At least one of subnet or sgt or vn should be defined	sgt
vn	String	No	Virtual Network. At least one of subnet or sgt or vn should be defined	virtual-Network
domains	String	Yes	List of SXP Domains, separated with comma	Sxp Vpn Name

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.

- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_filter_policy_by_id`***`get_filter_policy(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_filter_policy`***`get_filter_policy_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_filter_policy_generator*

create_filter_policy(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_filter_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.1.1).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

Guest Location API allows the client to search the locations configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	9f083530-8c01-11e6-996c-525400b48521
descrip-tion	String	No		

get_guest_location_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

Alias for `get_guest_location`

`get_guest_location_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration**class GuestSmtpNotificationConfiguration**

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.1.1).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

Guest SMTP notification configuration API is a global setting for enabling email notifications within guest application. These APIs allow to create, update and retrieve the notification settings. The create API may not be required to be used as of Cisco ISE Release 2.2 because the single SMTP notification configuration is the only one used and it always gets created during the Cisco ISE application initialization period.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for update		9ecb5340-8c01-11e6-996c-525400b48521
description	String	No			
defaultFromAddress	String	No	The default from email address to be used to send emails from	donotreply@example.com	
notificationEnabled	Boolean	No	Indicates if the email notification service is to be enabled	true	
smtpServer	String	No	The SMTP server ip address or fqdn such as outbound.mycompany.com		
useDefaultFromAddress	Boolean	No	If the default from address should be used rather than using a sponsor user email address	false	
smtpPort	String	No	Port at which SMTP Secure Server is listening	25	
connectionTimeout	String	No	Interval in seconds for all the SMTP client connections	60	
useTLSorSSLEncryption	Boolean	No	If configured to true, SMTP server authentication will happen using TLS/SSL	false	
usePasswordAuthentication	Boolean	No	If configured to true, SMTP server authentication will happen using username/password	false	
userName	String	No	Username of Secure SMTP server		
password	String	No	Password of Secure SMTP server		

get_guest_smtp_notification_settings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_guest_smtp_notification_settings_by_id`***`update_guest_smtp_notification_settings_by_id(id, connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a SMTP configuration setting.

Parameters

- **`connection_timeout (string)`** – Interval in seconds for all the SMTP client connections, property of the request body.
- **`default_from_address (string)`** – The default from email address to be used to send emails from, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`notification_enabled (boolean)`** – Indicates if the email notification service is to be enabled, property of the request body.
- **`password (string)`** – Password of Secure SMTP server, property of the request body.
- **`smtp_port (string)`** – Port at which SMTP Secure Server is listening, property of the request body.
- **`smtp_server (string)`** – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **`use_default_from_address (boolean)`** – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **`use_password_authentication (boolean)`** – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **`use_tlsor_ssl_encryption (boolean)`** – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.

- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlsv1_2=None*, *use_ssl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

get_guest_smtp_notification_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings*

get_guest_smtp_notification_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings_generator*

create_guest_smtp_notification_settings(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.

- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlsor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(connection_timeout=None, default_from_address=None, notification_enabled=None,  
        password=None, smtp_port=None, smtp_server=None, use_default_from_address=None,  
        use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None,  
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_guest_smtp_notification_settings*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_ssid

class GuestSsid

Identity Services Engine GuestSSID API (version: 3.1.1).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

Guest SSIDs are global objects that are referenced by Cisco ISE sponsor portals. Guest SSID API allows the client to add, delete, update and search guest SSID among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]	ssid_value
id	String	No	Resource UUID, mandatory for update	9132eedc-7910-4ffe-805e-3d3a366f7fb7
description	String	No		

get_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_ssid_by_id*

update_guest_ssid_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest SSID by ID.

Parameters

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_ssid_by_id*

get_guest_ssid(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid*

get_guest_ssid_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid_generator*

create_guest_ssid(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_ssid*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_type**class GuestType**

Identity Services Engine GuestType API (version: 3.1.1).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

Guest Type API allows the client to add, delete, update and search guest types.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Contractor (default)
id	String	No	Resource UUID, mandatory for update		9f03a151-8c01-11e6-996c-525400b48521
description	String	No			Default settings allow network access for up to a year.
accessTime	List	No			
<ul style="list-style-type: none"> allowAccessOn-Specific-DaysTimes 	Boolean	No	Enable Specific Day Time Limits	false	
<ul style="list-style-type: none"> default-Duration 	Integer	No		90	
<ul style="list-style-type: none"> durationTime-Unit 	Enum	No	Allowed values are: - DAYS, - HOURS, - MINUTES	DAYS	
<ul style="list-style-type: none"> from-FirstLogin 	Boolean	No	When Account Duration starts from first login or specified date	false	
<ul style="list-style-type: none"> maxAccountDuration 	Integer	No	Maximum value of Account Duration	365	
<ul style="list-style-type: none"> dayTime-Limits 	List	No	List of Time Ranges for account access		
<ul style="list-style-type: none"> dayTime-Limit 	List	No	Time Ranges for account access		
<ul style="list-style-type: none"> startTime 	String	No	Start time in HH:mm format	09:00	
<ul style="list-style-type: none"> endTime 	String	No	End time in HH:mm format	17:00	
<ul style="list-style-type: none"> days 	List	No	List of Days		
994				Chapter 1.	The User Guide
	<ul style="list-style-type: none"> day 	Enum	No	Value should be one of Week day. Allowed	

update_guest_type_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`update_sms(id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *update_guest_type_sms*

`get_guest_type_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest type by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *get_guest_type_by_id*


```
update_guest_type_by_id(id, access_time=None, description=None, expiration_notification=None,
                        is_default_type=None, login_options=None, name=None,
                        sponsor_groups=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, access_time=None, description=None, expiration_notification=None,
            is_default_type=None, login_options=None, name=None, sponsor_groups=None,
            headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_type_by_id*

get_guest_type(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*

create_guest_type(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_type*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_user

class GuestUser

Identity Services Engine GuestUser API (version: 3.1.1).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

Guest User API allows the client to add, delete, update and search guest users among other operations which are available from the sponsor portal. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only ‘create’ bulk operation. However, all other operation which are bulk supported can be used in the same way.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		guestUser
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			ERS Example user
customFields	Map	No	Key value map		“some key” : “some value”
guestType	String	No			Contractor
status	String	No			
reasonForVisit	String	No			
personBeingVisited	String	No			
sponsorUserName	String	No			Mr Spons
sponsorUserId	String	No			
statusReason	String	No			
portalId	String	No			23423432523

continues on next page

Table 22 – continued from previous page

guestAccess-Info	List	No			
• valid-Days	Integer	Yes	Number of days guest user is valid. To validate validDays property, Cisco ISE considers only date (not time) between fromDate and toDate properites		90
• fromDate	String	No			07/29/2014 14:44
• toDate	String	No			10/29/2014 17:30
• location	String	No			San Jose
• ssid	String	No			
• groupTag	String	No			
GuestInfo	List	Yes			
• emailAd-dress	String	No			email@some.uri.com
• enabled	Boolean	Yes	This field is only for Get operation not applicable for Create, Update operations	false	
• password	String	Yes			asdlkj324ew
• pho-neNum-ber	String	No	Phone number should be E.164 format		+13211239034
• smsSer-vice-Provider	String	No			Global Default

continues on next page

Table 22 – continued from previous page

• user-Name	String	No	If account needs be created with mobile number, please provide mobile number here		DS3ewdsa34wWE
• firstName	String	No			
• lastName	String	No			
• company	String	No			
• creation-Time	String	No			
• notificationLanguage	String	No			

approve_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to approve a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

approve_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *approve_guest_user_by_id*

change_sponsor_password(*portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to change the sponsor password.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to suspend a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`suspend_guest_user_by_name`***`reinstate_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`reinstate_guest_user_by_name`***`get_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_guest_user_by_name`*

`update_guest_user_by_name(name, custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, id=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a guest user by name.

Parameters

- **`custom_fields (object)`** – Key value map, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`guest_access_info (object)`** – guestAccessInfo, property of the request body.
- **`guest_info (object)`** – guestInfo, property of the request body.
- **`guest_type (string)`** – guestType, property of the request body.
- **`id (string)`** – id, property of the request body.
- **`name (basestring)`** – name, property of the request body.
- **`portal_id (string)`** – portalId, property of the request body.
- **`reason_for_visit (string)`** – reasonForVisit, property of the request body.
- **`sponsor_user_id (string)`** – sponsorUserId, property of the request body.
- **`sponsor_user_name (string)`** – sponsorUserName, property of the request body.
- **`status (string)`** – status, property of the request body.
- **`status_reason (string)`** – statusReason, property of the request body.
- **`name`** – name path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_name*

delete_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_name*

reset_guest_user_password_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_id`(*id*, *headers=None*, ***query_parameters*)Alias for *`reinstate_guest_user_by_id`***`update_guest_user_email`**(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user email by ID.

Parameters

- **`additional_data`** (*list*) – `additionalData`, property of the request body (list of objects).
- **`id`** (*basestring*) – `id` path parameter.
- **`portal_id`** (*basestring*) – `portalId` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_email`(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)Alias for *`update_guest_user_email`*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

Alias for *update_guest_user_sms*

deny_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deny a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deny_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deny_guest_user_by_id*

get_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.

- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_id*

delete_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_id*

get_guest_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users*

get_guest_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users_generator*

create_guest_user(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_user*

suspend_guest_user_by_id(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to suspend a guest user by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

suspend_by_id(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *suspend_guest_user_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the guest user.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_guest_user(*operation_type=None*, *resource_media_type=None*, *headers=None*,
 payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – operationType, property of the request body.
- **`resource_media_type`** (*string*) – resourceMediaType, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_guest_user*

monitor_bulk_status_guest_user(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_guest_user*

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.1.1).

Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

Hotspot Guest Portal API provides the ability to create, read, update, delete and search hotspot guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Hotspot Guest Portal (default)	
id	String	No	Resource UUID, mandatory for update	b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	
description	String	No	Guests do not require username and password credentials to access the network, but you can optionally require an access code		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	

continues on next page

Table 23 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	HOTSPOTGUEST	
settings	List	No	Defines all of the settings groups available for a BYOD		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	
• allowedInterfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificateGroupTag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• endpointIdentityGroup	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal	aa178bd0-8bff-11e6-996c-525400b48521	

continues on next page

Table 23 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• coaType	Enum	No	Allowed Values: COAREAU-THENTICATE, COATER-MINATE	COAREAU-THENTICATE	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• requireAccessCode	Boolean	No	Require the portal user to enter an access code. Only used in Hotspot portal	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 23 – continued from previous page

• require-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• authSuccessSettings	List	No			
• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUCCESSPAGE, ORIGINATINGURL, URL	AUTHSUCCESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		

continues on next page

Table 23 – continued from previous page

• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		
• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 23 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	
• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		

continues on next page

Table 23 – continued from previous page

• page-Back-ground-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	BYOD Portal		
• contact-Text	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			

continues on next page

Table 23 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_hotspot_portal`

```
get_hotspot_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                              sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the hotspot portals. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

create_hotspot_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_hotspot_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMapping API (version: 3.1.1).

Wraps the Identity Services Engine IPToSGTMapping API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping API allows the client to add, delete, update, search and deploy IP to SGT mapping.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	server1.cisco.com
id	String	No	Resource UUID, mandatory for update	
description	String	No		
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL		network_device_id
deployType	Enum	Yes	Allowed values: ALL, ND, NDG	ND
hostName	String	Mandatory if hostIp is empty		server1.cisco.com
sgt	String	Mandatory unless mappingGroup is set		sgt_id
hostIp	String	Mandatory if hostName is empty – valid IPL		
mappingGroup	String	Mandatory unless sgt and deployTo and deployType are set		

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all(*headers=None, **query_parameters*)

Alias for *deploy_all_ip_to_sgt_mapping*

get_deploy_status_ip_to_sgt_mapping(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status(*headers=None, **query_parameters*)

Alias for *get_deploy_status_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id, deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless *mappingGroup* is set or unless *deployType=ALL*, property of the request body.
- **deploy_type** (*string*) – Allowed values: *ALL*, *ND*, *NDG*, property of the request body.
- **host_ip** (*string*) – Mandatory if *hostName* is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if *hostIp* is empty, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless *sgt* and *deployTo* and *deployType* are set, property of the request body.
- **name** (*string*) – name, property of the request body.

- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_by_id*

delete_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_ip_to_sgt_mapping_by_id***get_ip_to_sgt_mapping**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_generator`*

`create_ip_to_sgt_mapping`(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **`deploy_to`** (*string*) – Mandatory unless `mappingGroup` is set or unless `deployType=ALL`, property of the request body.
- **`deploy_type`** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **`host_ip`** (*string*) – Mandatory if `hostName` is empty -valid IP, property of the request body.
- **`host_name`** (*string*) – Mandatory if `hostIp` is empty, property of the request body.
- **`mapping_group`** (*string*) – Mapping Group Id. Mandatory unless `sgt` and `deployTo` and `deployType` are set, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt`** (*string*) – Mandatory unless `mappingGroup` is set, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None,  
name=None, sgt=None, headers=None, payload=None, active_validation=True,  
**query_parameters)
```

Alias for *create_ip_to_sgt_mapping*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_ip_to_sgt_mapping(operation_type=None, resource_media_type=None,  
headers=None, payload=None, active_validation=True,  
**query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping*

monitor_bulk_status_ip_to_sgt_mapping(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group

class IpToSgtMappingGroup

Identity Services Engine IPToSGTMappingGroup API (version: 3.1.1).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping Group API allows the client to add, delete, update, search and deploy IP to SGT mapping groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		groupA
id	String	No	Resource UUID, mandatory for update		
description	String	No			
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL			net-work_device_id
deploy-Type	Enum	Yes	Allowed values: ALL, ND, NDG	ALL	
sgt	String	Mandatory unless mappingGroup is set			sgt_id

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_ip_to_sgt_mapping_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_ip_to_sgt_mapping_group_by_id`*

`update_ip_to_sgt_mapping_group_by_id(id, deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_ip_to_sgt_mapping_group_by_id*

get_ip_to_sgt_mapping_group(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_group`*

`get_ip_to_sgt_mapping_group_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_generator*

create_ip_to_sgt_mapping_group(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping_group*

monitor_bulk_status_ip_to_sgt_mapping_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.1.1).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

Identity Groups API allows the client to search identity groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added Create and GetByName operations

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	GuestType_Weekly (default)
id	String	No	Resource UUID, mandatory for update	9efe2310-8c01-11e6-996c-525400b48521
description	String	No		Identity group mirroring the guest type
parent	String	Yes		NAC Group:NAC:IdentityGroups:User Identity Groups

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_name***get_identity_group_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_id***update_identity_group_by_id**(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

get_identity_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups*

get_identity_groups_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

create_identity_group(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to identity group.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.1.1).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

Identity Sequence API allows the client to add, delete, update and search Identity sequences.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	All_User_ID_Stores
id	String	No	Resource UUID, mandatory for update	93246270-8c01-11e6-996c-525400b48521
description	String	No		A built-in Identity Sequence to include all User Identity Stores
breakOn-StoreFail	Boolean	Yes	Do not access other stores in the sequence If a selected identity store cannot be accessed for authentication	false
certificateAuthenticationProfile	String	Yes	Certificate Authentication Profile, empty if doesn't exist	Preloaded_Certificate_Profile
idSeqItem	List	Yes	List of id stores comprised of id store name and order	[{ "idstore": "Internal Users", "order": 1 }, { "idstore": "All_AD_Join_Points", "order": 2 }, { "idstore": "Guest Users", "order": 3 }]

get_identity_sequence_by_name(name, headers=None, **query_parameters)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

get_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

update_identity_sequence_by_id(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

delete_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_identity_sequence_by_id*

get_identity_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence*

get_identity_sequence_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.

- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

internal_user**class InternalUser**

Identity Services Engine InternalUser API (version: 3.1.1).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

Internal User API allows the client to add, delete, update and search internal users.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		b24b09e2-16f8-4e48-ace1-2c262a9449f1
description	String	No			description
changePassword	Boolean	Yes		true	
email	String	No			email@domain.com
enablePassword	String	No	EnablePassword field is added in ISE 2.0 to support T+		enablePassword
enabled	Boolean	Yes	Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled'		true
custom-Attributes	String	No	Key value map		{ "key1" : "value1" }
firstName	String	No			firstName
identity-Groups	String	No	CSV of identity group IDs		identity-Groups
lastName	String	No			lastName
password	String	No			password
passwordID-Store	String	Yes	The id store where the internal user's password is kept	Internal Users	
expiry-DateEnabled	Boolean	No		false	
expiry-Date	String	No	To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD'		2021-05-19

get_internal_user_by_name(name, headers=None, **query_parameters)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_name*

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.

- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_name*

delete_internal_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_name*

get_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_id*


```
update_internal_user_by_id(id, change_password=None, custom_attributes=None, description=None,
                           email=None, enable_password=None, enabled=None, expiry_date=None,
                           expiry_date_enabled=None, first_name=None, identity_groups=None,
                           last_name=None, name=None, password=None, password_idstore=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_id*

get_internal_user(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user*

get_internal_user_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(change_password=None, custom_attributes=None, description=None, email=None,
        enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
        first_name=None, identity_groups=None, last_name=None, name=None, password=None,
        password_idstore=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for `create_internal_user`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the internal user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

licensing

class Licensing

Identity Services Engine Licensing API (version: 3.1.1).

Wraps the Identity Services Engine Licensing API and exposes the API as native Python methods that return native Python objects.

```
get_connection_type(headers=None, **query_parameters)
```

Get connection type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_eval_license_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_feature_to_tier_mapping(headers=None, **query_parameters)`

Get feature to tier mapping.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_registration_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create_registration_info(connection_type=None, registration_type=None, ssm_on_prem_server=None, tier=None, token=None, headers=None, payload=None, active_validation=True, **query_parameters)`

License Configure registration information.

Parameters

- **`connection_type (string)`** – `connectionType`, property of the request body. Available values are 'HTTP_DIRECT', 'PROXY', 'SSM_ONPREM_SERVER' and 'TRANSPORT_GATEWAY'.
- **`registration_type (string)`** – `registrationType`, property of the request body. Available values are 'DEREGISTER', 'REGISTER', 'RENEW' and 'UPDATE'.

- **ssm_on_prem_server** (*string*) – If connection type is selected as SSM_ONPREM_SERVER, then IP address or the hostname (or FQDN) of the SSM On-Prem server Host., property of the request body.
- **tier** (*list*) – tier, property of the request body (list of strings. Available values are ‘ADVANTAGE’, ‘DEVICEADMIN’, ‘ESSENTIAL’, ‘PREMIER’ and ‘VM’).
- **token** (*string*) – token, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_smart_state(*headers=None, **query_parameters*)

Get smart license information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

configure_smart_state(headers=None, **query_parameters)

License Configure smart state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_tier_state_info(headers=None, **query_parameters)

Get tier state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_tier_state_info(*headers=None, payload=None, active_validation=True, **query_parameters*)

Applicable values for name & status parameters: name: ESSENTIAL, ADVANTAGE, PREMIER, DE-VICEADMIN status: ENABLED, DISABLED .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

mdm**class Mdm**

Identity Services Engine MDM API (version: 3.1.1).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id, name, portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pmg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_endpoints(*headers=None, **query_parameters*)

getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)

getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)

getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)

getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc**class Misc**

Identity Services Engine Misc API (version: 3.1.1).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 MNT REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_mnt*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_active_count (*headers=None*, ***query_parameters*)

ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_list(*headers=None, **query_parameters*)

ActiveList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_auth_list(*headers=None, **query_parameters*)

Session/AuthList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_posture_count(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_count(*headers=None, **query_parameters*)

ProfilerCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac*, *headers=None*, ***query_parameters*)

Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_sessions_by_session_id(session_id, headers=None, **query_parameters)`

Sessions by SessionID.

Parameters

- **`session_id`** (*basestring*) – `session_id` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_all_sessions(headers=None, **query_parameters)`

Delete All Sessions.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_mnt_version(headers=None, **query_parameters)`

MNT Version.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_failure_reasons(headers=None, **query_parameters)`

FailureReasons.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_authentication_status_by_mac`(*mac, records, seconds, headers=None, **query_parameters*)

AuthenticationStatus by MAC.

Parameters

- **`mac`** (*basestring*) – MAC path parameter.
- **`seconds`** (*basestring*) – SECONDS path parameter.
- **`records`** (*basestring*) – RECORDS path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`session_reauthentication_by_mac`(*endpoint_mac, psn_name, reauth_type, headers=None, **query_parameters*)

Session Reauthentication by MAC.

Parameters

- **`psn_name`** (*basestring*) – PSN_NAME path parameter.
- **`endpoint_mac`** (*basestring*) – ENDPOINT_MAC path parameter.

- **reauth_type** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_disconnect (*disconnect_type, endpoint_ip, mac, nas_ipv4, psn_name, headers=None, **query_parameters*)

Session Disconnect.

Parameters

- **endpoint_ip** (*basestring*) – ENDPOINT_IP path parameter.
- **psn_name** (*basestring*) – PSN_NAME path parameter.
- **mac** (*basestring*) – MAC path parameter.
- **disconnect_type** (*basestring*) – DISCONNECT_TYPE path parameter.
- **nas_ipv4** (*basestring*) – NAS_IPV4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_account_status_by_mac(*duration*, *mac*, *headers=None*, ***query_parameters*)

AccountStatus by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **duration** (*basestring*) – duration path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.1.1).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

My Device Portal API provides the ability to create, read, update, delete and search my device portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		My Devices Portal (default)
id	String	No	Resource UUID, mandatory for update		901f1b37-4a2f-46d9-8653-d925d2dde3aa
description	String	No			Default portal used by employees to register and manage their personal devices
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/mydevicesportal/PortalSetup
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	MYDEVICE	
settings	List	No	Defines all of the settings groups available for a Mydevice portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		

continues on next page

Table 24 – continued from previous page

• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal		aa178bd0-8bff-11e6-996c-525400b48521
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 24 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No		2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK - ONPAGE, - ASLINK	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	

continues on next page

Table 24 – continued from previous page

• aupSet- tings	List	No	Configuration of the Accept- able Use Policy (AUP) for a portal		
• dis- playFre- quency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• in- cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• require- Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAc- ceptance = true	false	
• dis- playFre- quency- Interval- Days	Integer	No	Number of days between AUP confir- mations (when displayFre- quency = recurring)	7	
• employ- eeChangePass- wordSet- tings	List	No			
• allowEm- ployee- ToChangePwd	Boolean	No	Allow employ- ees to change their own pass- words	false	
• post- Login- Banner- Settings	List	No			

continues on next page

Table 24 – continued from previous page

• include-PostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• support-InfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE

continues on next page

Table 24 – continued from previous page

• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		

continues on next page

Table 24 – continued from previous page

• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			My Devices Portal
• contact-Text	String	No			Contact Support

continues on next page

Table 24 – continued from previous page

• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		

continues on next page

Table 24 – continued from previous page

• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_my_device_portal_by_id*

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_my_device_portal_by_id`*

`get_my_device_portal`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal*

`get_my_device_portal_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`sortasc (basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc (basestring)`** – sortdsc query parameter. sort desc.
- **`filter (basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type (basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_my_device_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

native_suppliant_profile

class NativeSuppliantProfile

Identity Services Engine NativeSuppliantProfile API (version: 3.1.1).

Wraps the Identity Services Engine NativeSuppliantProfile API and exposes the API as native Python methods that return native Python objects.

Native suppliant profile API provides the ability to update, delete and search native suppliant profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Cisco-ISE-NSP
id	String	No	Resource UUID, mandatory for update	b8ce01e6-b150-4d4e-9698-40e48d5e0197
description	String	No		Pre-configured Native Supplicant Profile. The SSID Will Need To Be Customized For Your Environment
wirelessProfiles	List	Yes	List of Wireless profiles	
• ssid	String	Yes	SSID for the wireless profile	ISE
• allowedProtocol	Enum	Yes	Allowed protocol for the wireless profile.	TLS
• certificateTemplateId	String	No	Certificate template ID	0ca8f1b6-500d-560b-e053-75189a0ab0d1
• actionType	Enum	Yes	Action type for WifiProfile.	UPDATE
• previousSsid	String	Yes	Previous ssid for WifiProfile (required for updating existing WirelessProfile)	ssid1

get_native_suppliant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a native supplicant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_native_suppllicant_profile_by_id`***`update_native_suppllicant_profile_by_id(id, description=None, name=None, wireless_profiles=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a native suppllicant profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`wireless_profiles`** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_native_suppllicant_profile_by_id*

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native supplicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_native_suppllicant_profile_by_id*

get_native_suppllicant_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the native supplicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

`get_native_suppllicant_profile_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type*Generator***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native suppllicant profile.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rules*

create_network_access_authentication_rule(*policy_id*, *identity_source_name=None*,
if_auth_fail=None, *if_process_fail=None*,
if_user_not_found=None, *link=None*, *rule=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`get_network_access_authentication_rule_by_id`*

`update_network_access_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update rule.

Parameters

- **`identity_source_name(string)`** – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail(string)`** – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail(string)`** – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found(string)`** – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link(object)`** – link, property of the request body.
- **`rule(object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id(basestring)`** – policyId path parameter. Policy id.
- **`id(basestring)`** – id path parameter. Rule id.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

delete_network_access_authentication_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete rule.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_authentication_rule_by_id*

network_access_authorization_exception_rules

class NetworkAccessAuthorizationExceptionRules

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_local_exception_rules(*policy_id, headers=None, **query_parameters*)

Network Access Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id, headers=None, **query_parameters*)

Alias for *get_network_access_local_exception_rules*

create_network_access_local_exception_rule(*policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.

- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_local_exception_rule*

reset_hit_counts_network_access_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_network_access_local_exceptions`***`get_network_access_local_exception_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Network Access Get local exception rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_network_access_local_exception_rule_by_id`***`update_network_access_local_exception_rule_by_id(id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_set_global_exception_rules(*headers=None, **query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_network_access_policy_set_global_exception_rules`

`create_network_access_policy_set_global_exception_rule(link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rule_by_id*

update_network_access_policy_set_global_exception_rule_by_id(*id*, *link=None*, *profile=None*,
rule=None,
security_group=None,
headers=None,
payload=None,
active_validation=True,
***query_parameters*)

Network Access Update global exception authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

delete_network_access_policy_set_global_exception_rule_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_global_exception_rule_by_id*

network_access_authorization_rules

class NetworkAccessAuthorizationRules

Identity Services Engine Network Access - Authorization Rules API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rules*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

`reset_hit_counts_network_access_authorization_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authorization_rules*

get_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rule_by_id*

update_network_access_authorization_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

delete_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authorization_rule_by_id*

network_access_conditions

class NetworkAccessConditions

Identity Services Engine Network Access - Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_conditions(*headers=None*, ***query_parameters*)

Network Access Returns all library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions*

create_network_access_condition(*attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model `LibraryConditionAttributes` , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: `LibraryConditionAndBlock` or `LibraryConditionOrBlock` . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: `ConditionAttributes` , `ConditionAndBlock` , `ConditionOrBlock` , that represent dynamically built Conditions which are not stored in the conditions Library, or using `ConditionReference` , which includes an ID to existing stored condition in the library. The `LibraryCondition` models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (`ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock`), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using `ConditionReference` model in inner layers, the condition name is not required. `ConditionReference` objects can also include a reference ID to a condition of type `TimeAndDate`

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(`reference`,`single`) indicates than “`conditionId`” OR “`ConditionAttrs`” fields should contain condition data but not both Logical aggregation(`and`,`or`) enum indicates that additional conditions are present under the `children` field, property of the request body. Available values are ‘`ConditionAndBlock`’, ‘`ConditionAttributes`’, ‘`ConditionOrBlock`’, ‘`ConditionReference`’, ‘`LibraryConditionAndBlock`’, ‘`LibraryConditionAttributes`’, ‘`LibraryConditionOrBlock`’ and ‘`TimeAndDateCondition`’.
- **dates_range** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format `yyyy- mm-dd` (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format `yyyy- mm-dd` (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format `hh:mm` (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format `hh:mm` (h = hour , mm = minutes) Default All Day , property of the request body.

- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
      dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
      dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
      is_negate=None, link=None, name=None, operator=None, week_days=None,
      week_days_exception=None, headers=None, payload=None, active_validation=True,
      **query_parameters)
```

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_condition_by_name*

update_network_access_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_name*

delete_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_name*

get_network_access_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions_for_policy_sets*

get_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for `get_network_access_condition_by_id`

update_network_access_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.

- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_id*

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_id*

network_access_dictionary

class NetworkAccessDictionary

Identity Services Engine Network Access - Dictionary API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries(*headers=None*, ***query_parameters*)

Get all Dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries*

create_network_access_dictionaries(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_dictionaries*

get_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

GET a dictionary by name.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_network_access_dictionary_by_name*

update_network_access_dictionary_by_name(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_by_name*

delete_network_access_dictionary_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_access_dictionary_by_name`*

network_access_dictionary_attribute**class NetworkAccessDictionaryAttribute**

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

`get_network_access_dictionary_attributes_by_dictionary_name`(*dictionary_name*,
headers=None,
***query_parameters*)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **`dictionary_name`** (*basestring*) – `dictionaryName` path parameter. the name of the dictionary the dictionary attribute belongs to.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

create_network_access_dictionary_attribute(*dictionary_name*, *allowed_values=None*,
data_type=None, *description=None*,
direction_type=None, *id=None*, *internal_name=None*,
name=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute's name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

```
update_network_access_dictionary_attribute_by_name(dictionary_name, name,  
                                                  allowed_values=None, data_type=None,  
                                                  description=None, direction_type=None,  
                                                  id=None, internal_name=None,  
                                                  headers=None, payload=None,  
                                                  active_validation=True,  
                                                  **query_parameters)
```

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.
- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_attribute_by_name*

network_access_dictionary_attributes_list

class NetworkAccessDictionaryAttributesList

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries_authentication(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authentication*

get_network_access_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_authorization***get_network_access_dictionaries_policy_set**(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_policy_set***network_access_identity_stores****class NetworkAccessIdentityStores**

Identity Services Engine Network Access - Identity Stores API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_network_access_identity_stores(*headers=None, **query_parameters*)

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_identity_stores*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_network_access_network_conditions*

create_network_access_network_condition(*cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **`cli_dnis_list`** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **`condition_type`** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **`description`** (*string*) – description, property of the request body.
- **`device_group_list`** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **`device_list`** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **`id`** (*string*) – id, property of the request body.
- **`ip_addr_list`** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **`link`** (*object*) – link, property of the request body.
- **`mac_addr_list`** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).

- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(id, headers=None, **query_parameters)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_network_condition_by_id*

update_network_access_network_condition_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_network_access_network_condition_by_id*

delete_network_access_network_condition_by_id(*id*, *headers=None*, ****query_parameters**)

Network Access Delete network condition.

Parameters

- **id (basestring)** – id path parameter. Condition id.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_network_condition_by_id*

network_access_policy_set

class NetworkAccessPolicySet

Identity Services Engine Network Access - Policy Set API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_sets(*headers=None*, ***query_parameters*)

Get all network access policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_sets*

create_network_access_policy_set(*condition=None*, *default=None*, *description=None*, *hit_counts=None*, *id=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.

- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set*

reset_hit_counts_network_access_policy_sets(*headers=None, **query_parameters*)

Network Access Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_policy_sets*

get_network_access_policy_set_by_id(*id, headers=None, **query_parameters*)

Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_by_id*

update_network_access_policy_set_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_by_id*

delete_network_access_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_by_id*

network_access_profiles

class NetworkAccessProfiles

Identity Services Engine Network Access - Profiles API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

get_network_access_profiles(*headers=None, **query_parameters*)

Network Access Returns list of authorization profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_network_access_security_groups*

network_access_service_names**class NetworkAccessServiceNames**

Identity Services Engine Network Access - Service Names API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

`get_network_access_service_names`(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_network_access_service_names*

network_access_time_date_conditions

class NetworkAccessTimeDateConditions

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.1.1).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_time_conditions(headers=None, **query_parameters)

Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_network_access_time_conditions*

create_network_access_time_condition(attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)

Network Access Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body

(list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
      dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
      dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
      is_negate=None, link=None, name=None, operator=None, week_days=None,
      week_days_exception=None, headers=None, payload=None, active_validation=True,
      **query_parameters)
```

Alias for *create_network_access_time_condition*

```
get_network_access_time_condition_by_id(id, headers=None, **query_parameters)
```

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_network_access_time_condition_by_id*

update_network_access_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates

Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_time_condition_by_id*

delete_network_access_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_time_condition_by_id*

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.1.1).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

Network Device API allows the client to add, delete, update, and search network devices. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	2.0	Cisco ISE 2.0 model changes for TACACS+ and 3rd-Party support	tacacsSet- tings:sharedSecret	Added Attribute 'shared-Secret' for Tacacs+ sup- port
				tacacsSet- tings:connectModeOptions	Added Attribute 'connect- ModeOptions' for Tacacs+ support
				profileName	Added Attribute 'profile- Name' for 3rd-Party sup- port support
				coaPort	Added Attribute 'coaPort' for 3rd-Party support sup- port
2	1.2	2.4	Cisco ISE 2.4 model changes for Multi shared secret and DTLS Required support	authenticationset- tings:enableMultiSecret	Added Attribute 'enable- MultiSecret' for multiple shared secret
				authenticationset- tings:secondRadiusSharedSecret	Added Attribute 'secon- dRadiusSharedSecret' for multiple shared secret
				authenticationset- tings:dtlsRequired	Added Attribute 'dtlsRe- quired' for dtls settings

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Val- ues
-----------	------	----------	-------------	----------------	---------------------

continues on next page

Table 25 – continued from previous page

name	String	Yes	Resource Name		ISE_EST_Local_Host
id	String	No	Resource UUID, mandatory for update		79aac430-7cc8-11eb-ad58-005056926583
description	String	No			example nd
authentication-Settings	List	Yes			
• enableKey-Wrap	Boolean	Yes			false
• enabled	Boolean	Yes		false	
• keyEncryption-Key	String	Yes			1234567890123456
• keyInput-Format	Enum	Yes	Allowed values: ASCII, HEXADECI-MAL	ASCII	
• messageAuthenticator-CodeKey	String	No			12345678901234567890
• networkProtocol	Enum	No	Allowed values: RADIUS, TACACS_PLUS	RADIUS	
• radiusShared-Secret	String	No			VHEGKOC-CUHYB
• enable-MultiSecret	Boolean	No			false

continues on next page

Table 25 – continued from previous page

• sec-ondRa-diusShared-Secret	String	No			
• dtlsRe-quired	Boolean	No	This value enforces use of dtls	false	
coaPort	Integer	Yes	Since 2.0 (for 3rd party)		0
dtlsDnsName	String	No	This value is used to verify the client identity contained in the X.509 RA-DIUS/DTLS client certificate		ISE213.il.com
NetworkDeviceIPList	List	Yes	List of IP Subnets for this node		
• ipaddress	String	Yes	It can be either single IP address or IP range address		127.0.0.1
• getIpAddressExclude	String	Yes	It can be either single IP address or IP range address		
• mask	Integer	Yes			32
NetworkDeviceGroupList	List	No	List of Network Device Group names for this node		[“Location#All Locations”, “Device Type#All Device Types”]
modelName	String	No			
softwareVersion	String	No			
profileName	String	Yes	Since 2.0 (for 3rd party)	true	Cisco
snmpsettings	List	Yes			

continues on next page

Table 25 – continued from previous page

• linkTrap-Query	Boolean	Yes	SNMP link Trap Query	true	
• macTrap-Query	Boolean	Yes	SNMP MAC Trap Query	true	
• originat-ingPol-icySer-vicesNode	String	Yes	Originating Policy Services Node	Auto	
• polling-Interval	Integer	Yes	SNMP Polling Interval in seconds (Valid Range 600 to 86400)	3600	
• roCom-munity	String	No	SNMP RO Community		aaa
• version	Enum	No	Allowed values: ONE, TWO_C, THREE		ONE
tacacsSettings	List	Yes	Since 2.0 (for Tacacs+)		
• connect-ModeOp-tions	Enum	No	Allowed values: OFF, ON_LEGACY, ON_DRAFT_COMPLIANT		ON_LEGACY
• sharedSe-cret	String	Yes	Since 2.0		aaa
trustsecsettings	List	Yes			
• de-viceAu-thentica-tionSet-tings	List	Yes			
• sgaDevi-ceId	String	No			networkDe-vice1

continues on next page

Table 25 – continued from previous page

• sgaDevicePassword	String	No			aaa
• deviceConfigurationDeployment	List	Yes			
• enableModePassword	String	No			aaa
• execModePassword	String	No			aaa
• execModeUsername	String	No			aaa
• includeWhenDeployingSGTUpdates	Boolean	No		false	
• sgaNotificationAndUpdates	List	Yes			
• downloadEnvironmentDataEveryXSeconds	Integer	No		86400	

continues on next page

Table 25 – continued from previous page

• downloadPeer-Autho-rization-PolicyEveryXSec-onds	Integer	No		86400	
• download-SGA-CLList-sEveryXSec-onds	Integer	No		86400	
• otherS-GADe-vices-ToTrust-ThisDe-vice	Boolean	No		false	
• reAu-thentica-tionEveryXSec-onds	Integer	No		86400	
• sendCon-figura-tionToDe-vice	Boolean	No		false	
• sendCon-figura-tionToDe-viceUsing	Enum	No	Allowed values: EN-ABLE_USING_COA, EN-ABLE_USING_CLI, DIS-ABLE_ALL	EN-ABLE_USING_COA	

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.

- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`Alias for *`delete_network_device_by_name`***`get_network_device_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a network device by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_network_device_by_id`***`update_network_device_by_id(id, authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_iplist** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
              model_name=None, name=None, network_device_group_list=None,
              network_device_ip_list=None, profile_name=None, snmpsettings=None,
              software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None,
              payload=None, active_validation=True, **query_parameters)
```

Alias for `update_network_device_by_id`

```
delete_network_device_by_id(id, headers=None, **query_parameters)
```

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_network_device_by_id`

```
get_network_device(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                    headers=None, **query_parameters)
```

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device*

get_network_device_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_iplist=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_iplist** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).

- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
        model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None,
        profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None,
        trustsecsettings=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_device*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group**class NetworkDeviceGroup**

Identity Services Engine NetworkDeviceGroup API (version: 3.1.1).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

Network Device Group API allows the client to search network device groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.3	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Device Type#All Device Types
id	String	No	Resource UUID, mandatory for update	70c79c30-8bff-11e6-996c-525400b48521
description	String	No		All Device Types
other-name	String	No		Device Type

get_network_device_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_name*

get_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_id*

update_network_device_group_by_id(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_network_device_group_by_id`*

`delete_network_device_group_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device group.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_device_group_by_id`*

get_network_device_group(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group*

```
get_network_device_group_generator(filter=None, filter_type=None, page=None, size=None,
                                     sortasc=None, sortdsc=None, headers=None,
                                     **query_parameters)
```

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_deployment**class NodeDeployment**

Identity Services Engine Node Deployment API (version: 3.1.1).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

`get_nodes`(*filter=None, filter_type=None, headers=None, **query_parameters*)

The API lists all the nodes that are deployed in the cluster. Returns basic information about each of the deployed nodes in the cluster like hostname, status, roles, and services. Supports filtering on FQDN, host-name, IP address, roles, services and node status. .

Parameters

- **`filter`**(*basestring, list, set, tuple*) – filter query parameter. Simple filtering is available through the filter query string parameter. The structure of a filter is a triplet of field operator and value, separated by dots. More than one filter can be sent. The logical operator common to all filter criteria is AND by default, and can be changed by using the “filter-Type=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`**(*basestring*) – filterType query parameter. The logical operator common to all filter criteria is AND by default, and can be changed by using this parameter.
- **`headers`**(*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

register_node(*allow_cert_import=None, fqdn=None, password=None, roles=None, services=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API registers a Cisco ISE node to form a multi-node deployment. Approximate execution time 300 seconds. .

Parameters

- **`allow_cert_import`** (*boolean*) – Consent to import the self- signed certificate of the registering node. , property of the request body.
- **`fqdn`** (*string*) – fqdn, property of the request body.
- **`password`** (*string*) – password, property of the request body.
- **`roles`** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'PrimaryAdmin', 'PrimaryDedicatedMonitoring', 'PrimaryMonitoring', 'SecondaryAdmin', 'SecondaryDedicatedMonitoring', 'SecondaryMonitoring' and 'Standalone').
- **`services`** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'DeviceAdmin', 'PassiveIdentity', 'Profiler', 'SXP', 'Session', 'TC-NAC', 'pxGrid' and 'pxGridCloud').
- **`user_name`** (*string*) – userName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(hostname, headers=None, **query_parameters)

This API retrieves detailed information of the deployed node. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(hostname, headers=None, **query_parameters)

Alias for *get_node_details*

update_node(hostname, roles=None, services=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API updates the configuration of the Cisco ISE node with the configuration provided. Approximate execution time 300 seconds. .

Parameters

- **roles** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'PrimaryAdmin', 'PrimaryDedicatedMonitoring', 'PrimaryMonitoring', 'SecondaryAdmin', 'SecondaryDedicatedMonitoring', 'SecondaryMonitoring' and 'Standalone').
- **services** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'DeviceAdmin', 'PassiveIdentity', 'Profiler', 'SXP', 'Session', 'TC-NAC', 'pxGrid' and 'pxGridCloud').
- **hostname** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node(hostname, headers=None, **query_parameters)

The deregistered node becomes a standalone Cisco ISE node. It retains the last configuration that it received from the primary PAN and assumes the default roles and services of a standalone node. Approximate execution time 300 seconds. .

Parameters

- **hostname (basestring)** – hostname path parameter. The hostname of the node in the deployment to be deregistered.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

make_primary(*headers=None, **query_parameters*)

This API promotes the standalone node on which the API is invoked to the primary Policy Administration node (PAN). .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

promote_node(*headers=None, **query_parameters*)

Execute this API in the secondary PAN in the cluster to promote the node to primary PAN. Ensure that the API Gateway setting is enabled in the secondary PAN. Approximate execution time 300 seconds. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

make_standalone(*headers=None, **query_parameters*)

This API changes the primary PAN in a single node cluster on which the API is invoked, to a standalone node. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sync_node(*hostname, headers=None, **query_parameters*)

Performing a manual synchronization involves a reload of the target node, but not the primary PAN. Approximate execution time 300 seconds.

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_group

class NodeGroup

Identity Services Engine Node Group API (version: 3.1.1).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

get_node_groups(*headers=None, **query_parameters*)

This API retrieves the details of all the node groups in the cluster. Each node group retrieved consists of name, description and MAR cache details like query-attempts, query-timeout, replication-attempts, replication- timeout. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*description=None, mar_cache=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a node group in the cluster. A node group is a group of PSNs, where the PSNs maintain a heartbeat with each other. It is used primarily to terminate or transfer posture-pending sessions when a PSN in a local node group fails. Node group members can communicate over TCP/7800. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** **name** * required Name of the node group(valid-range: 1-100 characters) {"name": "site1"} **description** Description of the node group (valid-range: 0-256 characters) {"name": "site2", "description": "sample"} **query-attempts** The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1) {"name": "site3", "marCache": {"query-attempts": 1}} **query-timeout** The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2) {"name": "site4", "marCache": {"query-timeout": 2}} **replication-attempts** The number of

times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2) {"name": "site5","marCache": {"replication-attempts": 2}} replication-timeout The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5) second(s) {"name": "site6","marCache": {"replication-timeout": 5}} NOTE 1: : Node group name and description cannot contain any of the following characters: ! % ^ : ; , . ~ @ # & [{ (|) }] ` > < / " ' + = ? NOTE 2: : Parameter marCache stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory- authentication users. We can enable the marCache for a nodegroup by providing key "marCache" in json request. Additionally we may also provide any combination of parameters query-attempts, query-timeout, replication- attempts, replication-timeout in marCache object. If no value is specified for a particular parameter its default value will be recorded.If no marCache object is given, marCache will be considered as disabled. .

Parameters

- **description** (*string*) – description, property of the request body.
- **mar_cache** (*object*) – marCache, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the details of a node group in the cluster using a node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_node_group`(*node_group_name*, *description=None*, *mar_cache=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to update an existing node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** **name** * required Name of the node group existing in ISE(valid-range: 1-100 characters) **NOTE** : name of an existing node group cannot be modified. "name" parameter should be identical to the node group name(`nodeGroupName`) provided in the path {"name": "site1"} **description** Description of the node group (valid-range: 0-256 characters) {"name": "site2", "description": "sample"} **query-attempts** The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1) {"name": "site3", "marCache": {"query-attempts": 1}} **query-timeout** The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2) second(s) {"name": "site4", "marCache": {"query-timeout": 2}} **replication-attempts** The number of times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2) {"name": "site5", "marCache": {"replication-attempts": 2}} **replication-timeout** The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5) second(s) {"name": "site6", "marCache": {"replication-timeout": 5}} **NOTE 1**: Node group name and description cannot contain any of the following characters: ! % ^ ; , . ~ @ # & [{ (|) }] ` > < / " ' + = ? **NOTE 2**: Parameter `marCache` stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory-authentication users. We can enable the `marCache` for a nodegroup by providing key "marCache" in json request. Additionally we may also provide any combination of parameters `query-attempts`, `query-timeout`, `replication-attempts`, `replication-timeout` in `marCache` object. If no value is specified for a particular parameter its default value will be recorded. If no `marCache` object is given, `marCache` will be disabled. .

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`mar_cache`** (*object*) – `marCache`, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`node_group_name`** (*basestring*) – `nodeGroupName` path parameter. Name of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node_group(*force_delete*, *node_group_name*, *headers=None*, ***query_parameters*)

Delete an existing node group in the cluster. Deleting the node group does not delete the nodes, but failover is no longer carried out among the nodes.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **force_delete** (*bool*) – forceDelete query parameter. Force delete the group even if the node group contains one or more nodes.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

add_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API adds a node to the node group in the cluster. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all the URL-redirceted sessions on the failed node. The following parameters are used in the request body of the API: PARAMETER DESCRIPTION EXAMPLE *hostname* * required Name of the host name {"hostname": "isenode"}

Parameters

- **hostname** (*string*) – hostname, property of the request body.
- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_nodes(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the list of nodes associated with a node group in the cluster with a given node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

remove_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to remove a node from a node group in the cluster. Removing node from the node group does not delete the node, but failover is no longer carried out if the node is not part any node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** `hostname` * required Name of the host name {`"hostname": "isnode"`} .

Parameters

- **`hostname`** (*string*) – hostname, property of the request body.
- **`node_group_name`** (*basestring*) – `nodeGroupName` path parameter. Name of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_services

class NodeServices

Identity Services Engine Node Services API (version: 3.1.1).

Wraps the Identity Services Engine Node Services API and exposes the API as native Python methods that return native Python objects.

get_interfaces(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the list of interfaces on a node in a cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sxp_interface(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the SXP interface. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_sxp_interface(*hostname*, *interface=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API configures the SXP interface. .

Parameters

- **interface** (*string*) – interface, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_probe_config(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the profiler probe configuration of a PSN. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`set_profiler_probe_config`(*hostname*, *active_directory=None*, *dhcp=None*, *dhcp_span=None*, *dns=None*, *http=None*, *netflow=None*, *nmap=None*, *pxgrid=None*, *radius=None*, *snmp_query=None*, *snmp_trap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API updates the profiler probe configuration of a PSN. Set probe value as null to disable probe. Ex: Below payload will disable NMAP, PxGrid and SNMPTRAP probes { "activeDirectory": { "daysBeforeRescan": 1 }, "dhcp": { "interfaces": "[{"interface": "GigabitEthernet 0"}]", "port": 0 }, "dhcpSpan": { "interfaces": "[{"interface": "GigabitEthernet 0"}]" }, "dns": { "timeout": 2 }, "http": { "interfaces": "[{"interface": "GigabitEthernet 0"}]" }, "netflow": { "interfaces": "[{"interface": "GigabitEthernet 0"}]", "port": 0 }, "nmap": null , "pxgrid": null , "radius": [], "snmpQuery": { "eventTimeout": 30, "retries": 2, "timeout": 1000 }, "snmpTrap": null } .

Parameters

- **`active_directory`** (*object*) – The Active Directory probe queries the Active Directory for Windows information., property of the request body.
- **`dhcp`** (*object*) – The DHCP probe listens for DHCP packets from IP helpers., property of the request body.
- **`dhcp_span`** (*object*) – The DHCP SPAN probe collects DHCP packets., property of the request body.
- **`dns`** (*object*) – The DNS probe performs a DNS lookup for the FQDN., property of the request body.
- **`http`** (*object*) – The HTTP probe receives and parses HTTP packets., property of the request body.
- **`netflow`** (*object*) – The NetFlow probe collects the NetFlow packets that are sent to it from routers., property of the request body.
- **`nmap`** (*list*) – The NMAP probe scans endpoints for open ports and OS., property of the request body (list of objects).
- **`pxgrid`** (*list*) – The pxGrid probe fetches attributes of MAC address or IP address as a subscriber from the pxGrid queue., property of the request body (list of objects).

- **radius** (*list*) – The RADIUS probe collects RADIUS session attributes as well as CDP, LLDP, DHCP, HTTP, and MDM attributes from IOS Sensors., property of the request body (list of objects).
- **snmp_query** (*object*) – The SNMP query probe collects details from network devices such as interface, CDP, LLDP, and ARP., property of the request body.
- **snmp_trap** (*object*) – The SNMP trap probe receives linkup, linkdown, and MAC notification traps from network devices., property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_details

class NodeDetails

Identity Services Engine NodeDetails API (version: 3.1.1).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

Node Details API allows the client to get deployment node details, get all nodes and filter nodes based on NodeServiceTypes.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Ver- sion		
1	1.1	2.4	Support Node Service Types as part of Node Object	NodeSer- viceTypes	Added String Field NodeServiceTypes. String represents services configured on the Node
2	1.2	2.7	Support Node FQDN as part of Node Object	fqdn	Added String Field FQDN. String rep- resents FQDN of the Node
3	1.3	3.0	Support SXP IP Ad- dress as part of Node Details	sxpIpAd- dress	Added String Field sxpIpAddress. String represents SXP IP Address of the Node

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577- 0014737c8fcf
description	String	No		
gateWay	String	No		10.0.10.11
displayName	String	No		TestNode
inDeployment	Boolean	No		false
ipAddresses	String	No		[“10.0.0.1”, “10.0.0.2”]
otherPapFqdn	String	No		OtherTestNode
ipAddress	String	No		10.0.0.3
sxpIpAddress	String	No		10.10.10.1
nodeService- Types	String	No		DEVICE ADMIN
fqdn	String	No		test.ers.cisco.com
primaryPapN- ode	Boolean	No		true
papNode	Boolean	No		true
pxGridNode	Boolean	No		true

get_node_detail_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_name*

`get_node_detail_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the node details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.1.1).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

get_pan_ha_status(*headers=None, **query_parameters*)

In a high availability configuration, the primary PAN is in active state. The secondary PAN (backup PAN) is in standby state, which means that it receives all the configuration updates from the primary PAN, but is not active in the Cisco ISE cluster. You can configure Cisco ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or any combination of these. If the PANs are in different data centers, you must have a health check node for each PAN. All the fields are mandatory to enable PanHA. Values of failedAttempts, pollingInterval, primaryHealthCheckNode, and secondaryHealthCheckNode are not considered when the isEnabled value is “false” in the request body.

Parameters

- **failed_attempts** (*integer*) – Failover occurs if the primary PAN is down for the specified number of failure polls. Count (2 60). The default value is 5. , property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **polling_interval** (*integer*) – Administration nodes are checked after each interval. Seconds (30 300) The default value is 120. , property of the request body.
- **primary_health_check_node** (*object*) – primaryHealthCheckNode, property of the request body.
- **secondary_health_check_node** (*object*) – secondaryHealthCheckNode, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

patching

class Patching

Identity Services Engine Patching API (version: 3.1.1).

Wraps the Identity Services Engine Patching API and exposes the API as native Python methods that return native Python objects.

list_installed_hotpatches(*headers=None, **query_parameters*)

List all the installed hot patches in the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

install_hotpatch(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch installation process. As hot patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **hotpatch_name** (*string*) – hotpatchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`rollback_hotpatch`(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch rollback process. As hot patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **`hotpatch_name`** (*string*) – hotpatchName, property of the request body.
- **`repository_name`** (*string*) – repositoryName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

list_installed_patches(*headers=None, **query_parameters*)

List all the installed patches in the system, with the patch number for rollback. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

install_patch(*patch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch installation process. As the patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_name** (*string*) – patchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

rollback_patch(*patch_number=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch rollback process. As the patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_number** (*integer*) – patchNumber, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting**class PortalGlobalSetting**

Identity Services Engine PortalGlobalSetting API (version: 3.1.1).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

The Portal Global Setting API allows the user to customize the text that is displayed in the Cisco ISE portals. This global setting controls whether HTML alone or both HTML and Javascript are permitted to be used in customized text.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
id	String	Yes	Resource UUID value	21013cb2-d030-4fb1-9ba2-35757634d770
cus-tomization	Enum	Yes	Allowed values: HTML, HTMLAND-JAVASCRIPT	HTML

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdesc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

get_portal_global_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

portal_theme**class PortalTheme**

Identity Services Engine PortalTheme API (version: 3.1.1).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

Portal Theme API allows the client to add, delete, update and search Portal Theme among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Default Blue theme
id	String	No	Resource UUID, mandatory for update	9eb421c0-8c01-11e6-996c-525400b48521
descrip-tion	String	No		
theme-Data	String	Yes	Portal Theme for all portals	Base 64 encoded string of CSS file

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_theme_by_id*

update_portal_theme_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_portal_theme_by_id`*

`delete_portal_theme_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_portal_theme_by_id`*

get_portal_themes(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

```
get_portal_themes_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for [*get_portal_themes_generator*](#)

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [*create_portal_theme*](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler**class Profiler**

Identity Services Engine Profiler API (version: 3.1.1).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxxg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_profiles(*headers=None, **query_parameters*)

getProfiles.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler_profile**class ProfilerProfile**

Identity Services Engine ProfilerProfile API (version: 3.1.1).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

Profiler Profile API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	2Wire-Device
id	String	No	Resource UUID, mandatory for update	fe8c7cc0-8bff-11e6-996c-525400b48521
description	String	No		Policy for 2Wire-Device
parentId	String	Yes		

get_profiler_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profile_by_id*

get_profiler_profiles(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.1.1).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

register_service(*name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reregister_service(*headers=None, **query_parameters*)

ServiceReregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

authorization(*headers=None, **query_parameters*)

Authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service

class PsnNodeDetailsWithRadiusService

Identity Services Engine PsnNodeDetailsWithRadiusService API (version: 3.1.1).

Wraps the Identity Services Engine PsnNodeDetailsWithRadiusService API and exposes the API as native Python methods that return native Python objects.

PSN Node Details with RADIUS Service API allows the client to get deployment node details where 'Session Services' is enabled.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for up-date	ab6deded-fcc2-47ff-8577-0014737c8fcf
descrip-tion	String	No		PSN with Session Service
ipAddress	String	Yes		10.0.0.1

get_session_service_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_session_service_node_by_id`***`get_session_service_node(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the PSN node details.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_session_service_node`*

get_session_service_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(*MyDict*): response headers.
 - **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(*bytes*): representation of the request's response
 - **text**(*str*): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pull_deployment_info**class PullDeploymentInfo**

Identity Services Engine PullDeploymentInfo API (version: 3.1.1).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

Pull Deployment Info API allows clients to get the complete information about a Cisco ISE deployment. The information includes details about the deployment, network access, NADs, MDMs, licenses, posture and profiler.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.7	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description
name	String	Yes	Resource Name
id	String	No	Resource UUID, mandatory for update
description	String	No	
networkAccessInfo	List	No	networkAccessInfo Details
• deploymentID	String	Yes	Deployment ID
• isCsnEnabled	Boolean	Yes	false
• nodeList	List	Yes	Node list

continues on next page

Table 26 – continued from previous page

• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• sdaVNs	List	No	
• trustSecControl	String	No	ISE
• radius3RdParty	List	No	
profilerInfo	List	No	profilerInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Includes 'profiles' which is an array of dictionaries describing various attributes with the properties:- profile (List), - customProfilesCount (Integer), - endpointTypes (String), - totalProfilesCount (Integer), - uniqueEndpointsCount (Integer), - unknownEndpointsCount (Integer), - totalEndpointsCount (Integer), - unknownEndpointsPercentage (Integer)
deploymentInfo	List	No	deploymentInfo Details
• deploymentID	String	Yes	Deployment ID

continues on next page

Table 26 – continued from previous page

• versionHistoryInfo	List	No	Array of dictionaries describing various attributes with the properties:- opType (String), - mainVersion (String), - epochTime (Integer)
• nodeList	List	Yes	Node list
• nodeAndNode-CountAnd-CountInfo	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• fipsstatus	String	No	Disabled
nadInfo	List	No	nadInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declaredType (String), - scope (String), - value (List), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• nadcountInfo	List	No	
• totalActiveNAD-Count	Integer	No	0
mdmInfo	List	No	mdmInfo Details

continues on next page

Table 26 – continued from previous page

• activeMdmServersCount	Integer	Yes	0
• activeDesktopMdmServersCount	Integer	Yes	0
• activeMobileMdmServersCount	Integer	Yes	0
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes ‘content’ which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
licensesInfo	List	No	licensesInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes ‘content’ which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
postureInfo	List	No	postureInfo Details

continues on next page

Table 26 – continued from previous page

• content	List	Yes	Array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
kongInfo	List	No	kongInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Array of dictionaries describing various attributes with the properties:- sn (String), - service (List)

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **timeout** (*float*, *tuple*) – How long to wait for the server to send data before giving up.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings

class PxGridSettings

Identity Services Engine PxGridSettings API (version: 3.1.1).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

pxGrid Settings API allows the client to change auto-approve settings for pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for up- date		
description	String	No			
autoApproveCert- BasedAccounts	Boolean	Yes	Auto approve certificate based ac- counts when true	false	true
allowPassword- BasedAccounts	Boolean	Yes	Allow password based acoounts when true	false	

```
autoapprove_px_grid_settings(allow_password_based_accounts=None,
                             auto_approve_cert_based_accounts=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
autoapprove(allow_password_based_accounts=None, auto_approve_cert_based_accounts=None,
            headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *autoapprove_px_grid_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.1.1).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxe*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_failures(*headers=None, **query_parameters*)

getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.1.1).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

RADIUS Server Sequence API allows the client to add, delete, update, search and perform actions on RADIUS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.3	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		ab6dedd-fcc2-47ff-8577-0014737c8fcf
description	String	No			description
stripPrefix	Boolean	No		false	
stripSuffix	Boolean	No		false	
prefixSeparator	String	No	The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character		
suffixSeparator	String	No	The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character	@	
remoteAccounting	Boolean	No		true	
localAccounting	Boolean	No		false	
useAttrSetOnRequest	Boolean	No		false	
useAttrSetBeforeAcc	Boolean	No		false	
continueAuthorzPolicy	Boolean	No		false	
radiusServers	List	Yes	List with names of external radius server. The order of the names in the list is the order of servers that will be used during authentication		[“externalRadiusServer1”, “externalRadiusServer2”]
onRequestAttrManipulators	List	No	The onRequestAttrManipulators is required only if useAttrSetOnRequest is true		
<ul style="list-style-type: none"> Attribute-Manipulator 	List	No			
1246				Chapter 1.	The User Guide
<ul style="list-style-type: none"> action 	Enum	Yes	Allowed Values: ADD,		ADD

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).

- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list*=None, *continue_authorz_policy*=None, *description*=None, *local_accounting*=None, *name*=None, *on_request_attr_manipulator_list*=None, *prefix_separator*=None, *radius_server_list*=None, *remote_accounting*=None, *strip_prefix*=None, *strip_suffix*=None, *suffix_separator*=None, *use_attr_set_before_acc*=None, *use_attr_set_on_request*=None, *headers*=None, *payload*=None, *active_validation*=True, ****query_parameters**)

Alias for *update_radius_server_sequence_by_id*

delete_radius_server_sequence_by_id(*id*, *headers*=None, ****query_parameters**)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ****query_parameters**)

Alias for *delete_radius_server_sequence_by_id*

get_radius_server_sequence(*page*=None, *size*=None, *headers*=None, ****query_parameters**)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence***`get_radius_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence_generator*

```
create_radius_server_sequence(before_accept_attr_manipulators_list=None,
                              continue_authorz_policy=None, description=None,
                              local_accounting=None, name=None,
                              on_request_attr_manipulator_list=None, prefix_separator=None,
                              radius_server_list=None, remote_accounting=None,
                              strip_prefix=None, strip_suffix=None, suffix_separator=None,
                              use_attr_set_before_acc=None, use_attr_set_on_request=None,
                              headers=None, payload=None, active_validation=True,
                              **query_parameters)
```

This API creates a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.1.1).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

REST ID Store API allows clients to add, get, update and delete REST ID stores.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	RestIdStore1
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		Object that represents the restID store
restIDStoreAttributes	List	Yes	Holds the attributes of the restID object	
• username-Suffix	String	Yes	Suffix of the user-name domain	@place.com
• rootUrl	String	Yes	url of the root of the RestIDStore	rootUrl
• predefined	Enum	Yes	The cloud provider connected to of the RestIDStore. Options are: - Azure, - Okta, - None	Azure
• headers	List	Yes	Headers for the RestIDStore	
• key	String	Yes	Key of the header	tenantID
• value	String	Yes	Value of the header	tenantID_value

get_rest_id_store_by_name(name, headers=None, **query_parameters)

This API allows the client to get a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_rest_id_store_by_name*](#)

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for [*delete_rest_id_store_by_name*](#)

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store*

get_rest_id_store_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.1.1).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None, **query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_repositories*

create_repository(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.

- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and `_./@$` characters., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_repository*

get_repository(*repository_name, headers=None, **query_parameters*)

Get a specific repository identified by the name passed in the URL. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*repository_name*, *headers=None*, ***query_parameters*)Alias for *get_repository***update_repository**(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_repository*

delete_repository(*repository_name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*repository_name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_files(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider**class SmsProvider**

Identity Services Engine SMSProvider API (version: 3.1.1).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

SMS Provider API allows the client to search the SMS providers configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		

get_sms_provider(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider*

get_sms_provider_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sxp_connections**class SxpConnections**

Identity Services Engine SXPCConnections API (version: 3.1.1).

Wraps the Identity Services Engine SXPCConnections API and exposes the API as native Python methods that return native Python objects.

SXP Connections API allows clients to add, get, update and delete the Security Group Tag (SGT) Exchange Protocol (SXP) connections.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	sxpVpn	Attribute can include some VPNs separated by comma

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		Brief description about network peer
sxpPeer	String	Yes		Sxp Peer Name
sxpVpn	String	Yes		Sxp VPN Name
sxpNode	String	Yes		Sxp Node Name
ipAddress	String	Yes		Sxp Peer IP address
sxpMode	String	Yes		Sxp Mode
sxpVersion	String	Yes		Sxp Version
enabled	Boolean	Yes		true

get_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*,
sxp_mode=None, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*,
sxp_vpn=None, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None,
             sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None,
             active_validation=True, **query_parameters)
```

Alias for `update_sxp_connections_by_id`

```
delete_sxp_connections_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP connection.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sxp_connections_by_id`

```
get_sxp_connections(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                    sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

create_sxp_connections(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.

- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_connections*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_connections(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status(bulkid, headers=None, **query_parameters)`

Alias for *`monitor_bulk_status_sxp_connections`*

sxp_local_bindings**class SxpLocalBindings**

Identity Services Engine SXPLocalBindings API (version: 3.1.1).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

SXP Local Bindings API allows clients to add, get, update and delete SGT static mappings.

Revision History

Revi- sion #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	vns	Added new property for the Virtual Networks

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
binding-Name	String	No	This field is deprecated from Cisco ISE 3.0	
ipAddressOrHost	String	Yes	IP address for static mapping (hostname is not supported)	ipAddressOrHost
sgt	String	Yes	SGT name or ID	sgt_id
sxpVpn	String	Yes	List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined	Sxp Vpn Name
vns	String	Yes	List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined	virtualNetwork

get_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_local_bindings_by_id*

update_sxp_local_bindings_by_id(*id*, *binding_name=None*, *description=None*,
ip_address_or_host=None, *sgt=None*, *sxp_vpn=None*, *vns=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, binding_name=None, description=None, ip_address_or_host=None, sgt=None,
             sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_sxp_local_bindings_by_id`

```
delete_sxp_local_bindings_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP local binding.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

get_sxp_local_bindings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

create_sxp_local_bindings(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_local_bindings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_sxp_local_bindings(operation_type=None, resource_media_type=None,  
                                     headers=None, payload=None, active_validation=True,  
                                     **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request(operation_type=None, resource_media_type=None, headers=None, payload=None,  
              active_validation=True, **query_parameters)
```

Alias for *bulk_request_for_sxp_local_bindings*

```
monitor_bulk_status_sxp_local_bindings(bulkid, headers=None, **query_parameters)
```

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_sxp_local_bindings***sxp_vpns****class SxpVpns**

Identity Services Engine SXPVPNs API (version: 3.1.1).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

SXP VPNs API allows clients to add, get and delete SXP VPNs (SXP Domains).

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	ef36ca16-0cf7-4806-b2a9-6f547cfe4805
description	String	No		
sxpVpnName	String	Yes		default

get_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_vpn_by_id*

delete_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP VPN.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_vpn_by_id*

get_sxp_vpns(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – sxpVpnName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_vpn*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_vpns`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_sxp_vpns`*

monitor_bulk_status_sxp_vpns(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.1.1).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

SGT mapping to virtual networks are mapped to referenced vlan. These constructs come from out side of Cisco ISE and are not CRUDable inside Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.3	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No		description
sgtId	String	No		sgt_id
virtualnetworklist	List	No	Includes 'vlangs' which is an array of dictionaries describing various attributes with the properties: - id (String), - name (String), - description (String), - defaultVlan (Boolean), - max-Value (Integer), - data (Boolean)	<pre> { "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "virtual1", "description": "description", "defaultVirtualNetwork": false, "vlangs": [{ "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "vlan1", "description": "description1", "defaultVlan": true, "maxValue": 1882725260, "data": true }] }</pre>

get_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

update_security_groups_to_vn_to_vlan_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_to_vn_to_vlan_by_id*

delete_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL to virtual network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_security_groups_to_vn_to_vlan_by_id`

`get_security_groups_to_vn_to_vlan(filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan*

get_security_groups_to_vn_to_vlan_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_security_groups_to_vn_to_vlan_generator`*

`create_security_groups_to_vn_to_vlan`(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group to virtual network.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt_id`** (*string*) – sgtId, property of the request body.
- **`virtualnetworklist`** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_to_vn_to_vlan*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_groups_to_vn_to_vlan(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_to_vn_to_vlan*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.1.1).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

SGT API allows the client to search SGTs.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	1.4	Cisco ISE 1.4 model changes	isTagFromRange	Removed Attribute isTagFromRange - deprecated - set to FALSE value by default
2	1.2	2.3	Cisco ISE 2.3 model changes	propagateToApic	Added Boolean Attribute propagateToApic - By default value is false
3	1.3	2.7	Cisco ISE 2.7 model changes	isReadOnly	Added Boolean Attribute isReadOnly - By default value is false
				defaultSGACLs	Added List Attribute defaultSGACLs

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Employees
id	String	No	Resource UUID, mandatory for update		93ad6890-8c01-11e6-996c-525400b48521
description	String	No			Employee Security Group
value	Integer	Yes	Value range: 2 to 65519 or -1 to auto-generate		4
propagateToApic	Boolean	No			true
isReadOnly	Boolean	No		false	
defaultSGACLs	List	No			[]
propagateToApic	Boolean	No			true
generationId	Integer	No			0

get_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_group_by_id*

update_security_group_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 or 65519 or -1 to auto- generate, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

get_security_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups*

get_security_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*

create_security_group(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propogate_to_apic** (*boolean*) – propogateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_group*

monitor_bulk_status_security_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.1.1).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

Security Groups ACLs API allows the client to search security groups access control lists.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	2.3	Introducing bulk operations		
2	1.2	3.1	Cisco ISE 3.1 model changes	modelledContent	Adding modelled content from Cisco ISE 3.1

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Permit IP
id	String	No	Resource UUID, mandatory for update		92951ac0-8c01-11e6-996c-525400b48521
description	String	No			Permit IP SGACL
ACLContent	String	No			permit ip
ipVersion	Enum	Yes	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	
isRead-Only	Boolean	No		false	
generationId	String	No	GenerationId is a read only attribute and is being generated by the server		0
modelled-Content	List	No	Modelled content of contract		

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_acl_by_id*

update_security_groups_acl_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_security_groups_acl_by_id*

delete_security_groups_acl_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a security group ACL.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_security_groups_acl`

```
get_security_groups_acl_generator(filter=None, filter_type=None, page=None, size=None,
                                   sortasc=None, sortdsc=None, headers=None,
                                   **query_parameters)
```

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None,
        modelled_content=None, name=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_security_groups_acl*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_security_groups_acl(operation_type=None, resource_media_type=None,
                                     headers=None, payload=None, active_validation=True,
                                     **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_acl*

monitor_bulk_status_security_groups_acl(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_acl*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.1.1).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

Self Registered Guest Portal API provides the ability to create, read, update, delete and search self registered portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Self-Registered Guest Portal (default)
id	String	No	Resource UUID, mandatory for update		4e8ade36-4048-472a-b345-632cc155acfc
description	String	No			Guests may create their own accounts and be assigned a username and password, or use their social login to access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?po4048-472a-b345-632cc155acfc

continues on next page

Table 27 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SELF-REGGUEST	
settings	List	No	Defines all of the settings groups available for a portal		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on.		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• authentication-Method	String	Yes	Unique Id of the identity source sequence		92e50f80-8c01-11e6-996c-525400b48521
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type		Contractor (default)

continues on next page

Table 27 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		
• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 27 – continued from previous page

• re-requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• re-requireAccessCode	Boolean	No	Require the portal user to enter an access code	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• allowGuest-ToCreateAccounts	Boolean	No		false	
• allowGuest-ToChangePassword	Boolean	No	Require the portal user to enter an access code	false	
• allowAlternateGuest-Portal	Boolean	No			false
• alternateGuest-Portal	String	No			
• selfReg-PageSettings	List	No			

continues on next page

Table 27 – continued from previous page

• as-signGuestsToGuest-Type	String	No	Guests are assigned to this guest type		
• account-Validity-Duration	Integer	No	Self-registered guest account is valid for this many account_validity_time_units	1	
• account-Validity-TimeUnits	Enum	No	Time units for account_validity_duration.	DAYS	
• requireRegistrationCode	Boolean	No	Self-registered guests are required to enter a registration code	false	
• registrationCode	String	No	The registration code that the guest user must enter		
• fieldUserName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldFirstName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLastName	List	No			

continues on next page

Table 27 – continued from previous page

• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldE-mailAddr	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldPhoneNo	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldCompany	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLocation	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableLocations	List	No	Guests can choose from these locations to set their time zone		[“San Jose”]

continues on next page

Table 27 – continued from previous page

• fieldSm-sProvider	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableSm-sProviders	List	No	This attribute is an array of SMS provider names		["Global Default"]
• fieldPersonBeingVisited	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• field-Reason-ForVisit	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 27 – continued from previous page

• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• enableGuestEmailWhitelist	Boolean	No	Allow guests with an e-mail address from selected domains	false	
• guestEmailWhitelistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be allowed. Only valid if enableGuestEmailWhitelist = true		
• enableGuestEmailBlacklist	Boolean	No	Disallow guests with an e-mail address from selected domains	false	
• guestEmailBlacklistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be disallowed. Only valid if enableGuestEmailBlacklist = true		
• requireGuestApproval	Boolean	No	Require self-registered guests to be approved if true	false	

continues on next page

Table 27 – continued from previous page

<ul style="list-style-type: none"> • autoLogin-SelfWait 	Boolean	No	Allow guests to login automatically from self-registration after sponsor's approval. No need to provide the credentials by guest to login	false	
<ul style="list-style-type: none"> • autoLogin-TimePeriod 	Integer	No	Waiting period for auto login until sponsor's approval. If time exceeds, guest has to login manually by providing the credentials. Default value is 5 minutes	5	
<ul style="list-style-type: none"> • sendApprovalRequestTo 	Enum	No	Specifies where approval requests are sent. Only valid if requireGuestApproval = true.	SELECTEDEMAILADDRESSES	
<ul style="list-style-type: none"> • approvalEmailAddresses 	String	No	Only valid if requireGuestApproval = true and sendApprovalRequestTo = SELECTEDEMAILADDRESSES		
<ul style="list-style-type: none"> • postRegistrationRedirect 	Enum	No	After the registration submission direct the guest user to one of the following pages. Only valid if requireGuestApproval = true.	SELFREGISTRATIONSUCCESS	

continues on next page

Table 27 – continued from previous page

<ul style="list-style-type: none"> • postReg- istra- tionRedi- rectUrl 	String	No	URL where guest user is redirected after registration. Only valid if requireGuestApproval = true and postRegistrationRedirect = URL		
<ul style="list-style-type: none"> • creden- tial- Notifica- tionUsingE- mail 	Boolean	No	If true, send credential notification upon approval using email. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • creden- tialNotifi- cationUs- ingSms 	Boolean	No	If true, send credential notification upon approval using SMS. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • approve- DenyLinksValid- For 	Integer	No	This attribute, along with approveDenyLinksTimeUnits, specifies how long the link can be used. Only valid if requireGuestApproval = true	1440	
<ul style="list-style-type: none"> • approve- DenyLinksTime- Units 	Enum	No	This attribute, along with approveDenyLinksValidFor, specifies how long the link can be used. Only valid if requireGuestApproval = true.	DAYS	

continues on next page

Table 27 – continued from previous page

<ul style="list-style-type: none">• re-requireApprovalToAuthenticate	Boolean	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be required to enter their username and password if this attribute is true. Only valid if requireGuestApproval = true	false	
--	---------	----	---	-------	--

continues on next page

Table 27 – continued from previous page

• sponsor-PortalList	List	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be authenticated against the selected sponsor portals in the order specified. Only valid if requireGuestApproval = true. The array should contain the names of the selected portals		
• selfReg-Success-Settings	List	No			
• includeUserName	Boolean	No		true	
• includePassword	Boolean	No		true	
• includeFirst-Name	Boolean	No		true	

continues on next page

Table 27 – continued from previous page

• include-Last-Name	Boolean	No		true	
• includeEmailAddr	Boolean	No		true	
• include-PhoneNo	Boolean	No		true	
• include-Company	Boolean	No		true	
• include-Location	Boolean	No		true	
• includeSm-sProvider	Boolean	No		true	
• include-PersonBeingVisited	Boolean	No		true	
• includeReason-ForVisit	Boolean	No		true	
• allowGuest-SendSelfUsing-Print	Boolean	No		false	
• allowGuest-SendSelfUsingE-mail	Boolean	No		false	

continues on next page

Table 27 – continued from previous page

• allowGuest-SendSelfUsingSms	Boolean	No		false	
• includeAup	Boolean	No		false	
• aupOn-Page	Boolean	No		false	
• requireAupAcceptance	Boolean	No		false	
• requireAupScrolling	Boolean	No		false	
• allowGuest-Login-FromSelfregSuccessPage	Boolean	No		false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 27 – continued from previous page

• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	
• skipAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAtFirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegisterGuestDevices	Boolean	No	Automatically register guest devices	true	

continues on next page

Table 27 – continued from previous page

• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No		true	
• enableGuestAccess	Boolean	No		false	
• requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ONPAGE	
• requireAupAcceptance	Boolean	No		false	

continues on next page

Table 27 – continued from previous page

• require-Scrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodReg-istra-tionSet-tings	List	No	Configuration of BYOD endpoint Reg-istration step configuration		
• showDe-viceID	Boolean	No	Display Device ID field during registration	true	
• end-PointI-identity-GroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521
• byodReg-istra-tionSuc-cessSet-tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	
• redirec-tUrl	String	No	Target URL for redirection, used when suc-cessRedirect = URL		
• authSuc-cessSet-tings	List	No			
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	

continues on next page

Table 27 – continued from previous page

• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL		www.cisco.com
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUserAgent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	

continues on next page

Table 27 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 27 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 27 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 27 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_self_registered_portal_by_id*

```
delete_self_registered_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_self_registered_portal_by_id*

```
get_self_registered_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                           sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals_generator*

create_self_registered_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_self_registered_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory**class SessionDirectory**

Identity Services Engine Session Directory API (version: 3.1.1).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_sessions(*headers=None, **query_parameters*)

getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_for_recovery(*headers=None, **query_parameters*)

getSessionsForRecovery.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_ip_address(*headers=None, **query_parameters*)

getSessionByIpAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_mac_address(*headers=None, **query_parameters*)

getSessionByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_groups(*headers=None, **query_parameters*)

getUserGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)

getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)

Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.1.1).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to add, delete, update and search sponsor groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Em-plALL_ACCOUNTS (default)oyees
id	String	No	Resource UUID, mandatory for update		9f1eca71-8c01-11e6-996c-525400b48521
description	String	No			Sponsors assigned to this group can manage all guest user accounts. By default, users in the ALL_ACCOUNTS user identity group are members of this sponsor group
isEnabled	Boolean	No			true
isDefault-Group	Boolean	No			true
member-Groups	List	No			["ALL_ACCOUNTS (default)"]
guestTypes	List	No			["Contractor (default)", "Daily (default)", "Weekly (default)"]
locations	List	No			["San Jose"]
autoNotification	Boolean	No			false
managePermission	Enum	No	Allowed values:		ALLACCOUNTS, GROUPACCOUNTS, OWNACCOUNTS
createPermissions	List	No			

continues on next page

Table 28 – continued from previous page

• canImportMultipleAccounts	Boolean	No			true
• importBatchSizeLimit	Integer	No		200	
• canCreateRandomAccounts	Boolean	No			true
• randomBatchSizeLimit	Integer	No		200	
• defaultUsernamePrefix	String	No			
• canSpecifyUsernamePrefix	Boolean	No			true
• canSetFutureStartDate	Boolean	No			false
• startDateFutureLimitDays	Integer	No			1
otherPermissions	List	No			

continues on next page

Table 28 – continued from previous page

• canUpdateGuest-Contact-Info	Boolean	No			true
• canViewGuest-Pass-words	Boolean	No			true
• canSendSm-sNotifica-tions	Boolean	No			false
• canResetGuest-Pass-words	Boolean	No			true
• canExtendGues-tAc-counts	Boolean	No			true
• canDeleteGues-tAc-counts	Boolean	No			true
• canSuspendGues-tAc-counts	Boolean	Yes			true
• require-SuspensionReason	Boolean	No			false

continues on next page

Table 28 – continued from previous page

• canReinstateSuspendedAccounts	Boolean	No			true
• canApproveSelfregGuests	Boolean	No			true
• limitApprovalToSponsorsGuests	Boolean	Yes			false
• canAccessViaRest	Boolean	No			false

get_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_by_id*

update_sponsor_group_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor group by ID.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, auto_notification=None, create_permissions=None, description=None,
             guest_types=None, is_default_group=None, is_enabled=None, locations=None,
             manage_permission=None, member_groups=None, name=None, other_permissions=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `update_sponsor_group_by_id`

```
delete_sponsor_group_by_id(id, headers=None, **query_parameters)
```

This API deletes a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sponsor_group_by_id`

```
get_sponsor_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

This API allows the client to get all the sponsor groups. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group*

get_sponsor_group_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_generator*

create_sponsor_group(*auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).

- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sponsor_group_member**class SponsorGroupMember**

Identity Services Engine SponsorGroupMember API (version: 3.1.1).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to search the group members from different identity stores configured in the GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ALL_ACCOUNTS (default)
id	String	No	Resource UUID value	a176c430-8c01-11e6-996c-525400b48521
description	String	No		
dicType	String	Yes		
guid	String	Yes		

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal**class SponsorPortal**

Identity Services Engine SponsorPortal API (version: 3.1.1).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

Sponsor Portal API provides the ability to create, read, update, delete and search sponsor portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Sponsor Portal (default)

continues on next page

Table 29 – continued from previous page

id	String	No	Resource UUID, mandatory for update		04cd708b-feef-4c75-bf3e-2d2a9c302da2
description	String	No			Default portal used by sponsors to create and manage accounts for authorized visitors to securely access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8445/portal/PortalSetup.action?portalId=feef-4c75-bf3e-2d2a9c302da2
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SPONSOR	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8445
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on.		["eth0", "bond0"]

continues on next page

Table 29 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• fqdn	String	No	The fully-qualified domain name (FQDN) that end-users will use to access this portal. Used only in Sponsor portal		Default Portal Certificate Group
• authen- tication- Method	String	Yes	Unique Id of the identity source sequence		92faba60-8c01-11e6-996c-525400b48521
• idleTime- out	Integer	No		10	
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• availab- leSsids	List	No	Names of the SSIDs available for assignment to guest users by sponsors		
• login- PageSet- tings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 29 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	

continues on next page

Table 29 – continued from previous page

• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• sponsorChangePasswordSettings	List	No			
• allowSponsorToChangePwd	Boolean	No	Allow sponsors to change their own passwords	false	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		

continues on next page

Table 29 – continued from previous page

• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUserAgent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	
• emptyFieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• defaultEmptyFieldValue	String	No	The default value displayed for an empty field Only valid when emptyFieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 29 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI

continues on next page

Table 29 – continued from previous page

• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contact-Text	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			

continues on next page

Table 29 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_portal_by_id*

update_sponsor_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor portal by ID.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_portal_by_id*

get_sponsor_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_sponsor_portal`

```
get_sponsor_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.1.1).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

Sponsored Guest Portal API provides the ability to create, read, update, delete and search sponsored guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Sponsored Guest Portal (default))	
id	String	No	Resource UUID, mandatory for update	d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
description	String	No	Sponsors create guest accounts, and guests access the network using their assigned username and password		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	SPONSORED	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	

continues on next page

Table 30 – continued from previous page

• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• authentication-Method	String	Yes	Unique Id of the identity source sequence	92faba60-8c01-11e6-996c-525400b48521	
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type	Contractor (default)	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 30 – continued from previous page

<ul style="list-style-type: none"> • max-FailedAttemptsBeforeRateLimit 	Integer	No	Maximum failed login attempts before rate limiting	5	
<ul style="list-style-type: none"> • timeBetweenLoginsDuringRateLimit 	Integer	No	Time between login attempts when rate limiting	2	
<ul style="list-style-type: none"> • includeAup 	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
<ul style="list-style-type: none"> • aupDisplay 	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ASLINK	
<ul style="list-style-type: none"> • requireAupAcceptance 	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
<ul style="list-style-type: none"> • requireAccessCode 	Boolean	No	Require the portal user to enter an access code	false	
<ul style="list-style-type: none"> • accessCode 	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		

continues on next page

Table 30 – continued from previous page

• al-lowGuest-ToCreateAccounts	Boolean	No	false		
• al-lowGuest-ToChangePassword	Boolean	No	Require the portal user to enter an access code	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed Values: FIRSTLOGIN, EVERYLOGIN, RECURRING	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	

continues on next page

Table 30 – continued from previous page

• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAtFirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegisterGuestDevices	Boolean	No	Automatically register guest devices	true	
• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		

continues on next page

Table 30 – continued from previous page

• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No	true		
• enableGuestAccess	Boolean	No	false		
• requireMDM	Boolean	No	false		
• includeAup	Boolean	No	true		
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No	false		
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	

continues on next page

Table 30 – continued from previous page

• byodReg- istra- tionSet- tings	List	No	Configuration of BYOD endpoint Reg- istration step configuration		
• showDe- viceID	Boolean	No	Display Device ID field during registration	true	
• end- PointId- entity- GroupId	String	No	Identity group id for which endpoint belongs	aa13bb40-8bff- 11e6-996c- 525400b48521	
• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Authentica- tion Success where should device be redirected. Al- lowed values: AUTHSUC- CESSPAGE, ORIGINATIN- GURL, URL	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		
• authSuc- cessSet- tings	List	No			

continues on next page

Table 30 – continued from previous page

• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUC-CESSPAGE, ORIGINATINGURL, URL	AUTHSUC-CESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		
• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		

continues on next page

Table 30 – continued from previous page

• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	

continues on next page

Table 30 – continued from previous page

• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		
• page-Background-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		

continues on next page

Table 30 – continued from previous page

• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	Guest Portal		
• contactText	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			

continues on next page

Table 30 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_sponsored_guest_portal_by_id`*
`update_sponsored_guest_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **`customizations (object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`portal_test_url (string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type (string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **`settings (object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_sponsored_guest_portal_by_id`*

`delete_sponsored_guest_portal_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_sponsored_guest_portal_by_id`*

`get_sponsored_guest_portals`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals*

```
get_sponsored_guest_portals_generator(filter=None, filter_type=None, page=None, size=None,
                                       sortasc=None, sortdsc=None, headers=None,
                                       **query_parameters)
```

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals_generator*

create_sponsored_guest_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsored_guest_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download

class SupportBundleDownload

Identity Services Engine SupportBundleDownload API (version: 3.1.1).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

Support Bundle Download API allows client to download support bundles provided those are generated and available in the default location.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
fileName	String	Yes	File name along with path from where file needs to be downloaded	filename

download_support_bundle(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *download_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_status**class SupportBundleStatus**

Identity Services Engine SupportBundleStatus API (version: 3.1.1).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

Support Bundle Status API allows clients to query status of a triggered support bundle.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ciscoise
id	String	No	Resource UUID, mandatory for update	ciscoise
description	String	No		Support Bundle Status api
file-Name	String	No		ise-support-bundle-pk-ciscoise-admin-04-09-2021-15-07.tar.gpg
fileSize	Integer	No		1080924274
host-Name	String	No		ciscoise
message	String	No		Support Bundle generation completed
start-Time	String	No		Fri Apr 09 15:07:55 IST 2021
status	String	No		complete

get_support_bundle_status_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a support bundle status by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status*

get_support_bundle_status_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration**class SupportBundleTriggerConfiguration**

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.1.1).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

Support Bundle Trigger API allows clients to trigger support bundle provided the log settings are given using which the support needs to be generated.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values
name	String	Yes	Resource Name	supportBundle
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No	Support Bundle Generation	
hostName	String	Yes	This parameter is hostName only, xxxx of xxxx.yyy.zz	sampleHost
supportBundleOptions	List	Yes		
<ul style="list-style-type: none"> • includeConfigDB 	Boolean	Yes	Set to include Config DB in Support Bundle	false
<ul style="list-style-type: none"> • includeDebugLogs 	Boolean	Yes	Set to include Debug logs in Support Bundle	false
<ul style="list-style-type: none"> • includeLocalLogs 	Boolean	Yes	Set to include Local logs in Support Bundle	false
<ul style="list-style-type: none"> • includeCoreFiles 	Boolean	Yes	Set to include Core files in Support Bundle	false
<ul style="list-style-type: none"> • includeSystemLogs 	Boolean	Yes	Set to include System logs in Support Bundle	false
<ul style="list-style-type: none"> • mntLogs 	Boolean	Yes	Set to include Monitoring and troubleshooting logs in Support Bundle	false
<ul style="list-style-type: none"> • policyXml 	Boolean	Yes	Set to include Policy XML in Support Bundle	false
<ul style="list-style-type: none"> • fromDate 	Date	No	Date from where support bundle should include the logs	04/21/2019
<ul style="list-style-type: none"> • toDate 	Date	No	Date upto where support bundle should include the logs	04/22/2019

```
create_support_bundle(description=None, host_name=None, name=None,
                      support_bundle_include_options=None, headers=None, payload=None,
                      active_validation=True, **query_parameters)
```

This API allows the client to create a support bundle trigger configuration.

Parameters

- **description** (*string*) – description, property of the request body.
- **host_name** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **support_bundle_include_options** (*object*) – supportBundleIncludeOptions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health**class SystemHealth**

Identity Services Engine System Health API (version: 3.1.1).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_healths(*headers=None*, ***query_parameters*)

getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)

getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

system_certificate**class SystemCertificate**

Identity Services Engine SystemCertificate API (version: 3.1.1).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

System Certificate API provides the ability to create certificates like SAML, pxGrid.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		Support Bundle Status api
nodeId	String	Yes	NodeId of Cisco ISE application	ISE-01
localCertStub	List	Yes	Inputs for certificate creation	
<ul style="list-style-type: none">subjectStub	List	No	Subject data of certificate	
<ul style="list-style-type: none">common-Name	String	No	Common Name	\$FQDN\$
<ul style="list-style-type: none">organizationalUnitName	String	No	Organizational Unit Name	Cisco-SAMLCert
<ul style="list-style-type: none">organization-Name	String	No	Organizational Name	Cisco
<ul style="list-style-type: none">localityName	String	No	Locality Name	City
<ul style="list-style-type: none">stateOr-Province-Name	String	No	State or Province Name	State
<ul style="list-style-type: none">countryName	String	No	Country Name	Country
<ul style="list-style-type: none">keyType	String	Yes	Key Type	RSA OR ECDSA
<ul style="list-style-type: none">keyLength	String	Yes	Key Length	512 OR 1024 OR 2048 OR 4096
<ul style="list-style-type: none">digest	String	Yes	Digest	SHA-256 OR SHA-384 OR SHA-512
<ul style="list-style-type: none">expirationTTL	Integer	Yes	Expiration Time to Live (TTL)	2
<ul style="list-style-type: none">selectedExpirationTTLU-nit	String	Yes	Selected Expiration TTL Unit	days OR weeks OR months OR years
			Chapter 1. The User Guide	
<ul style="list-style-type: none">groupTagDD	String	No	Group Tag DD	add-group-tag

create_system_certificate(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_system_certificate*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

tacacs_command_sets**class TacacsCommandSets**

Identity Services Engine TACACSCCommandSets API (version: 3.1.1).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

TACACS Command Sets API allows the client to add, delete, update, search and perform actions on TACACS command sets.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		DenyAllCommands
id	String	No	Resource UUID, mandatory for update		0cef7990-6120-11ea-bffb-7a82c56e81f0
description	String	No			Default Command Set
permitUnmatched	Boolean	No		false	
commands	List	No	Holds list of Commands		
• commandList	List	No	Array of dictionaries describing various attributes with the properties: <ul style="list-style-type: none"> - grant (Enum. Allowed values: PERMIT, DENY, DENY_ALWAYS), - command (String), - arguments (String) 		[{ "grant" : "PERMIT", "command" : "create", "arguments" : "value" }]

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*,
permit_unmatched=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation .
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)

Alias for *get_tacacs_command_sets_generator*

create_tacacs_command_sets(commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers

class TacacsExternalServers

Identity Services Engine TACACSExternalServers API (version: 3.1.1).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

TACACS External Servers API allows the client to add, delete, update, search and perform actions on TACACS external servers.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsExternalServer1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsExternalServer-ForSDK
hostIP	String	Yes	The server IPV4 address		1.1.1.1
connectionPort	Integer	No	The port to connect the server	49	
single-Connect	Boolean	No	Define the use of single connection	true	
sharedSecret	String	Yes	The server shared secret		SharedSecret
timeout	Integer	No	The server timeout	20	

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_id*

update_tacacs_external_servers_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_external_servers_by_id*

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_external_servers_by_id*

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers*

get_tacacs_external_servers_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)

Alias for *get_tacacs_external_servers_generator*

create_tacacs_external_servers(connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_profile

class TacacsProfile

Identity Services Engine TACACSPROFILE API (version: 3.1.1).

Wraps the Identity Services Engine TACACSPROFILE API and exposes the API as native Python methods that return native Python objects.

TACACS Profile API allows the client to add, delete, update, search and perform actions on TACACS profile.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Shell Profile
id	String	No	Resource UUID, mandatory for update	93d7ee70-92b5-11eb-a39d-96858bc78604
description	String	No		Default Shell Profile
sessionAttributes	List	No	Holds list of session attributes. View type for GUI is Shell by default	
<ul style="list-style-type: none"> sessionAttributeList 	List	No	Array of dictionaries describing various attributes with the properties: - type (Enum. Allowed values: MANDATORY, OPTIONAL), - name (String), - value (String)	[{ "type" : "MANDATORY", "name" : "attr1", "value" : "value" }]

get_tacacs_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`get_tacacs_profile_by_name`***`get_tacacs_profile_by_id`**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)Alias for *`get_tacacs_profile_by_id`***`update_tacacs_profile_by_id`**(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a TACACS profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.

- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_profile_by_id*

delete_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_tacacs_profile_by_id***get_tacacs_profile**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile***get_tacacs_profile_generator**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile_generator*

create_tacacs_profile(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.1.1).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

TACACS Server Sequence API allows the client to add, delete, update, search and perform actions on TACACS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsServerSequence1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsServerSequenceForSDK
serverList	String	Yes	The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication		TacacsExternalServer1,TacacsExternalServer2
localAccounting	Boolean	No		false	
remoteAccounting	Boolean	No		true	
prefixStrip	Boolean	No	Define if a delimiter will be used for prefix strip	false	
suffixStrip	Boolean	No	Define if a delimiter will be used for suffix strip	false	
prefixDelimiter	String	No	The delimiter that will be used for prefix strip		
suffixDelimiter	String	No	The delimiter that will be used for suffix strip	@	

get_tacacs_server_sequence_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_name`***`get_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_id`***`update_tacacs_server_sequence_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None,
              prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None,
              suffix_strip=None, headers=None, payload=None, active_validation=True,
              **query_parameters)
```

Alias for `update_tacacs_server_sequence_by_id`

```
delete_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)
```

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_tacacs_server_sequence_by_id`

```
get_tacacs_server_sequence(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_server_sequence*

`get_tacacs_server_sequence_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_server_sequence_generator*

```
create_tacacs_server_sequence(description=None, local_accounting=None, name=None,  
                               prefix_delimiter=None, prefix_strip=None, remote_accounting=None,  
                               server_list=None, suffix_delimiter=None, suffix_strip=None,  
                               headers=None, payload=None, active_validation=True,  
                               **query_parameters)
```

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.


```
create(description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None,
        remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_tacacs_server_sequence*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.1.1).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

Telemetry Information API allows clients to get telemetry configuration information.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	ed7176fb-3faf-4060-845e-d5fa5236bd6e
description	String	No		
status	String	No		SCHEnable
deploymentId	String	No		ed7176fb-3faf-4060-845e-d5fa5236bd6e
udiSN	String	No		CH2MKIEGBGO

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information*

get_telemetry_information_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*,
 ***query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration**class TrustSecConfiguration**

Identity Services Engine TrustSec Configuration API (version: 3.1.1).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_security_groups(*headers=None*, ***query_parameters*)

getSecurityGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *get_security_groups***`get_security_group_acls`**(*headers=None, **query_parameters*)*getSecurityGroupAcls*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_policies`(*headers=None, **query_parameters*)*getEgressPolicies*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_matrices(headers=None, **query_parameters)``getEgressMatrices.`**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`trust_sec_sxp`**`class TrustSecSxp`**

Identity Services Engine TrustSec SXP API (version: 3.1.1).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_bindings(*headers=None*, ***query_parameters*)

getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.1.1).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_ise_version_and_patch(*headers=None*, ***query_parameters*)

This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info

class VersionInfo

Identity Services Engine VersionInfo API (version: 3.1.1).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_version_info(*resource, headers=None, **query_parameters*)

Get all VersionInfo.

Parameters

- **resource (basestring)** – resource path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint**class Endpoint**

Identity Services Engine endpoint API (version: 3.1.1).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

Endpoint API allows the client to add, delete, update, search, register and de-register endpoints. Please note that each API description shows whether the API is supported in bulk operation. The Bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re-vi-sion #	Re-source Version	Cisco ISE Version	Description	Revision Modification	
				Attribute	Description
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.1	Cisco ISE 2.1 model changes	custom-Attributes	Added custom attributes for the user to include custom attributes when adding endpoints to Cisco ISE
2	1.2	2.2	Cisco ISE 2.2 model changes	apiAdded	Added custom operation to get list of rejected endpoints: '/getrejectedendpoints'
				apiAdded	Added custom operation to release rejected endpoint: '{id}/releaserejectedendpoint'

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	11:22:33:44:55:66
id	String	No	Resource UUID, mandatory for update	172f8270-8f4f-11eb-b4a8-9eb04987ed29
description	String	No		MyEndpoint
customAttributes	Map	No	Key value map	{"key1": "value1"}
groupId	String	Yes		aa13bb40-8bff-11e6-996c-525400b48521
identityStore	String	No		identityStore
identityStoreId	String	No		identityStoreId
mac	String	Yes		11:22:33:44:55:66
portalUser	String	No		portalUser
profileId	String	No		profileId
staticGroupAssignment	Boolean	Yes		true
staticProfileAssignment	Boolean	Yes		false

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

release_rejected(*id*, *headers=None*, ***query_parameters*)

Alias for *release_rejected_endpoint*

deregister_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to de-register an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deregister(*id*, *headers=None*, ***query_parameters*)

Alias for *deregister_endpoint*

get_rejected_endpoints(*headers=None*, ***query_parameters*)

This API allows the client to get the rejected endpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_rejected(*headers=None, **query_parameters*)

Alias for *get_rejected_endpoints*

get_endpoint_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_endpoint_by_id***update_endpoint_by_id**(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_by_id*

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_by_id*

```
register_endpoint(custom_attributes=None, description=None, group_id=None, id=None,  
                  identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None,  
                  name=None, portal_user=None, profile_id=None, static_group_assignment=None,  
                  static_profile_assignment=None, headers=None, payload=None,  
                  active_validation=True, **query_parameters)
```

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *register_endpoint*

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Enpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_endpoints_generator`*

`create_endpoint`(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint.

Parameters

- **`custom_attributes`** (*object*) – customAttributes, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`group_id`** (*string*) – groupId, property of the request body.
- **`identity_store`** (*string*) – identityStore, property of the request body.
- **`identity_store_id`** (*string*) – identityStoreId, property of the request body.
- **`mac`** (*string*) – mac, property of the request body.
- **`mdm_attributes`** (*object*) – mdmAttributes, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_user`** (*string*) – portalUser, property of the request body.
- **`profile_id`** (*string*) – profileId, property of the request body.
- **`static_group_assignment`** (*boolean*) – staticGroupAssignment, property of the request body.
- **`static_profile_assignment`** (*boolean*) – staticProfileAssignment, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status`(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_endpoint***nbar_app****class NbarApp**

Identity Services Engine nbarApp API (version: 3.1.1).

Wraps the Identity Services Engine nbarApp API and exposes the API as native Python methods that return native Python objects.

`get_nbar_apps`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all NBAR Applications.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_nbar_apps`*

`get_nbar_apps_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all NBAR Applications.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_nbar_apps_generator`*

`create_nbar_app`(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create NBAR application.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`network_identities`** (*list*) – Array of NIs, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_nbar_app*

get_nbar_app_by_id(*id, headers=None, **query_parameters*)

Get NBAR Application by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_nbar_app_by_id*

update_nbar_app_by_id(*id, description=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update NBAR Application.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **network_identities** (*list*) – Array of NIs, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *network_identities=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_nbar_app_by_id*

delete_nbar_app_by_id(*id*, *headers=None*, ****query_parameters**)

Delete NBAR Application.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_nbar_app_by_id*

portal

class Portal

Identity Services Engine portal API (version: 3.1.1).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

Portal API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ISE Portal (default)
id	String	No	Resource UUID, mandatory for update	bc5524ea-b1e5-47ed-a907-5304821da916
description	String	No		ISE Portal for saml based feature purpose
portal-Type	String	No		GUEST

get_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_portal_by_id***get_portals**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals*

`get_portals_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

proxy

class Proxy

Identity Services Engine proxy API (version: 3.1.1).

Wraps the Identity Services Engine proxy API and exposes the API as native Python methods that return native Python objects.

get_proxy_connection(*headers=None, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_proxy_connection(*bypass_hosts=None, fqdn=None, password=None, password_required=None, port=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **bypass_hosts** (*string*) – Bypass hosts for the proxy connection, property of the request body.
- **fqdn** (*string*) – proxy IP address or DNS-resolvable host name, property of the request body.
- **password** (*string*) – Password for the proxy connection, property of the request body.

- **password_required** (*boolean*) – Indicates whether password configuration is required for Proxy., property of the request body.
- **port** (*integer*) – Port for proxy connection. should be between 1 and 65535, property of the request body.
- **user_name** (*string*) – User name for the proxy connection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.1.1).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

pxGrid Node API allows the client to retrieve pxGrid information, delete an existing pxGrid node, and approve new pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	ers-sample-client
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No		ERS sample client
status	String	No		Online (XMPP)
auth-Method	String	No		Certificate
groups	String	No		

pxGrid Characterization

Session data Consumption over pxGrid

On a 35 node Cisco ISE deployment with a dedicated primary Policy Administration node (PAN), dedicated secondary PAN, dedicated primary Monitoring and Troubleshooting node (MnT node), dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous Policy Service node (PSN) platforms, there was no delay observed in consuming session data with the following parameters as shown in the table below:

RADIUS Traffic	Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	pxGrid client's delay in consuming session data
Upto 500 transactions per second (TPS)	~2 million	50	No delay

Bulk download time taken

On a 35 node Cisco ISE deployment with a dedicated primary PAN, dedicated secondary PAN, dedicated primary MnT, dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous PSN Platforms, the bulk download time for all the pxGrid clients is shown in the table below:

Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	Time taken for bulk download
2 million	50	~17 minutes

Note: From Cisco ISE Release 3.1, we can use either pxgridnode or pxgridNode in the URL.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_name*

delete_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_px_grid_node_by_name*

get_px_grid_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_px_grid_node_by_id`***`get_px_grid_node(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_px_grid_node`***`get_px_grid_node_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sg_vn_mapping

class SgVnMapping

Identity Services Engine sgVnMapping API (version: 3.1.1).

Wraps the Identity Services Engine sgVnMapping API and exposes the API as native Python methods that return native Python objects.

get_sg_vn_mappings(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings*

get_sg_vn_mappings_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings_generator*

create_sg_vn_mapping(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Security Group and Virtual Network mapping.

Parameters

- **id** (*string*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sg_vn_mapping*

bulk_create_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_sg_vn_mappings*

bulk_delete_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)Alias for *bulk_delete_sg_vn_mappings***bulk_update_sg_vn_mappings**(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)Alias for *bulk_update_sg_vn_mappings***get_sg_vn_mapping_by_id**(*id, headers=None, **query_parameters*)

Get Security Group and Virtual Network mapping by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sg_vn_mapping_by_id*

update_sg_vn_mapping_by_id(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update Security Group and Virtual Network mapping.

Parameters

- **id** (*basestring*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sg_vn_mapping_by_id*

`delete_sg_vn_mapping_by_id`(*id*, *headers=None*, ***query_parameters*)

Delete Security Group and Virtual Network mapping.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sg_vn_mapping_by_id*

tasks

class Tasks

Identity Services Engine tasks API (version: 3.1.1).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

get_task_status(*headers=None, **query_parameters*)

get all task status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_task_status_by_id(*task_id, headers=None, **query_parameters*)

Monitor task status.

Parameters

- **task_id** (*basestring*) – taskId path parameter. The id of the task executed before.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry**class Telemetry**

Identity Services Engine telemetry API (version: 3.1.1).

Wraps the Identity Services Engine telemetry API and exposes the API as native Python methods that return native Python objects.

get_transport_gateway(*headers=None, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_transport_gateway(*enable_transport_gateway=None, url=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **enable_transport_gateway** (*boolean*) – Indicates whether transport gateway is enabled or not., property of the request body.

- **url** (*string*) – URL of transport gateway, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

virtual_network

class VirtualNetwork

Identity Services Engine virtualNetwork API (version: 3.1.1).

Wraps the Identity Services Engine virtualNetwork API and exposes the API as native Python methods that return native Python objects.

get_virtual_networks(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals

NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks*

get_virtual_networks_generator (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks_generator*

create_virtual_network(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*string*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`create_virtual_network`*

`bulk_create_virtual_networks`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network in bulk.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_create`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_create_virtual_networks`*

bulk_delete_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_delete_virtual_networks*

bulk_update_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_virtual_networks*

get_virtual_network_by_id(*id, headers=None, **query_parameters*)

Get Virtual Network by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_virtual_network_by_id*

update_virtual_network_by_id(*id, additional_attributes=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*basestring*) – Identifier of the Virtual Network, property of the request body.

- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *additional_attributes=None*, *last_update=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_virtual_network_by_id*

delete_virtual_network_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Virtual Network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_virtual_network_by_id***vn_vlan_mapping****class VnVlanMapping**

Identity Services Engine vnVlanMapping API (version: 3.1.1).

Wraps the Identity Services Engine vnVlanMapping API and exposes the API as native Python methods that return native Python objects.

get_vn_vlan_mappings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mappings*

`get_vn_vlan_mappings_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_vn_vlan_mappings_generator`*

`create_vn_vlan_mapping`(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mapping.

Parameters

- **`id`** (*string*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **`is_data`** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **`is_default_vlan`** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **`last_update`** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **`max_value`** (*integer*) – Max value, property of the request body.
- **`name`** (*string*) – Name of the Vlan, property of the request body.
- **`vn_id`** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **`vn_name`** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_vn_vlan_mapping*

bulk_create_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_vn_vlan_mappings*

bulk_delete_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *bulk_delete_vn_vlan_mappings*

bulk_update_vn_vlan_mappings(headers=None, payload=None, active_validation=True, **query_parameters)

Update VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_vn_vlan_mappings*

get_vn_vlan_mapping_by_id(*id, headers=None, **query_parameters*)

Get VN-Vlan Mapping by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mapping_by_id*

update_vn_vlan_mapping_by_id(*id, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **is_data** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.

- **max_value** (*integer*) – Max value, property of the request body.
- **name** (*string*) – Name of the Vlan, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_vn_vlan_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

Delete VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.1_Patch_1**aci_bindings****class AciBindings**

Identity Services Engine ACIBindings API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

The ACI Bindings API allows clients to retrieve bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on the ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip, sgt, vn, psn, learnedFrom, or learnedBy with CONTAINS mode of search.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
ip	String	Yes	Binding IPv4 address. Each binding will be exclusively identified by its IP address and virtual network	10.0.0.1
sgt	String	No	Security Group Tag (SGT) value. The valid range for SGT values is 0-65534	1234
vn	String	Yes	Virtual network. Each binding will be exclusively identified by its IP address and virtual network	vn1234
psn	String	No	Cisco ISE Policy Service node (PSN) IP address	10.86.189.216
learnedFrom	String	Yes	Binding Source	ISE by ACI ACI by ISE
learnedBy	String	Yes	Binding Type	SXP(SXP, 0) STATIC(Static, 1) RADIUS(RADIUS, 2) ACI(ACI, 3)

get_aci_bindings(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

ACI Settings API allows the client to get and update the ACI Settings. In addition, testing the ACI Domain Manager connection is also possible using the TestACIConnection.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		AciSettings
id	String	No	Resource UUID value		29fb45ab-6a8e-4658-8a28-02521c258178
description	String	No			Aci Settings
enableAci	Boolean	Yes	Enable ACI Integration	false	
isAci50	Boolean	Yes	Enable 5.0 ACI Version	false	
ipAddressHost- Name	String	No	ACI Cluster IP Address / Host name		
adminName	String	No	ACI Cluster Admin name		
adminPassword	String	No	ACI Cluster Admin pass- word		
tenantName	String	No	ACI Cluster Tenant name	ISE	
l3RouteNetwork	String	No	ACI Cluster L3 Route net- work name	L3_ROUTE	
suffixToEpg	String	No	Name Conversion - EPG suffix	SGT	
suffixToSgt	String	No	Name Conversion - SGT suffix	EPG	
allSxpDomain	Boolean	No	SXP Propagation to all the SXP domains	false	
specificSxpDo- main	Boolean	No	SXP Propagation to spe- cific SXP domains	true	
specifixSxpDo- mainList	List	No	Specific SXP domains list	[default]	
isAci51	Boolean	Yes	Enable 5.1 ACI Version	false	
aciipaddress	String	No	ACI Domain manager Ip Address		
aciuserName	String	No	ACI Domain manager Username		
acipassword	String	No	ACI Domain manager Password		
enableData- Plane	Boolean	No	Enable data plane	false	
untaggedPack- etIepgName	String	No	Untagged IEPG packets name	untagged	
defaultSgtName	String	No	Default SGT name	Unknown	
enableEle- mentsLimit	Boolean	No	Enable Elements Limit	false	
maxNu- mIepgFromAci	Inte- ger	No	Max number of IEPGs	1000	
maxNumSgt- ToAci	Inte- ger	No	Max number of SGTs	500	

get_aci_settings(headers=None, **query_parameters)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

test_aci_connectivity(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_aci_settings_by_id(id, aci50=None, aci51=None, aciipaddress=None, acipassword=None,
    aciuser_name=None, admin_name=None, admin_password=None,
    all_sxp_domain=None, default_sgt_name=None, enable_aci=None,
    enable_data_plane=None, enable_elements_limit=None,
    ip_address_host_name=None, l3_route_network=None,
    max_num_iepg_from_aci=None, max_num_sgt_to_aci=None,
    specific_sxp_domain=None, specifix_sxp_domain_list=None,
    suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None,
    untagged_packet_iepg_name=None, headers=None, payload=None,
    active_validation=True, **query_parameters)
```

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.
- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint**class AncEndpoint**

Identity Services Engine ANCEndpoint API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
macAddress	String	Yes	MAC address of the endpoint	00:11:22:33:44:55
policy-Name	String	Yes	Policy name to be applied to the endpoint	policy1

Supported ANC API transactions per second

On a 5 node Cisco ISE deployment with 60k sessions or on a 9 node Cisco ISE deployment with 200k/500k sessions, 250 transactions per second (TPS) is supported for any ANC API.

Supported ANC APIs

* `applyEndpointByMacAddress` * `clearEndpointByMacaddress` * `applyEndpointByIpAddress` * `applyEndpointPolicy` * `clearEndpointPolicy`

Deployment	Number of Sessions	Supported ANC APIs TPS
5 nodes	60k	250
9 nodes	200k	250
5 nodes	500k	250

`get_anc_endpoint_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_anc_endpoint_by_id`

`clear_anc_endpoint(additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to clear the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data (list)** – additionalData, property of the request body (list of objects).
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *apply_anc_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory

class ActiveDirectory

Identity Services Engine ActiveDirectory API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

The Active Directory API allows the user to carry out add, delete, and search operations on the active directory domains through Cisco ISE's join points. For example, if you want to connect to the domain cisco.com and retrieve the domain groups, you can carry out the following steps which are also available as APIs: Step 1 Create a domain join point in Cisco ISE. In the "domain" parameter use cisco.com.

Step 2 Get all defined join points and copy your join point's ID from the response.

Step 3 Join all Cisco ISE nodes to the domain. Use the ID received in the Step 2 in the URL. From this point onwards, you can perform several actions. In each action you should specify the joint point ID in the URL, as retrieved in step 2 in the previous configuration task. For example, you can:

- Retrieve the user groups using the joint point ID.

- Retrieve the groups of a specific domain using the join point ID. The domain parameter can be cisco.com or any of its trusted domains. You can use the get all trusted domains operation to retrieve the list.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifica- tion	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.4	Support new attributes	advanced- Settings	Added ERSActiveDirectoryAdvancedSettings Attribute 'advancedSettings'
				adAt- tributes	Added ERSActiveDirectoryAttributes Attribute 'adAttributes'
				enable- Domain- WhiteList	Added Boolean Attribute 'enableDomainWhiteList'
2	1.2	3.1	Support new attributes under ActiveDirectory AdvancedSettings	enable- FailedAuth- Protection	Added Boolean Attribute 'enableFailedAuthProtection'
				failedAu- thThresh- old	Added Integer Attribute 'failedAuthThreshold'
				auth Protec- tionType	Added Enum Attribute 'authProtectionType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_ characters	...	Company_users
id	String	No	Resource UUID value	...	af1cd190-7d71-11eb-b02e-ead13cf60dcb
description	String	No	No character restriction	...	Group of Active company users
domain	String	Yes	The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed	...	cisco.com
adScopes-Names	String	No	String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed	Default_Scope	...
enableDomain-WhiteList	Boolean	No	...	true	...
adGroups	List	No	Holds list of AD Groups
• groups	List	No	List of Groups

continues on next page

Table 31 – continued from previous page

• name	String	Yes	Required for each group in the group list with no duplication between groups. All characters are allowed except %	...	cisco.com/operators
• sid	String	Yes	Cisco ISE uses security identifiers (SIDs) for optimization of group membership evaluation. SIDs are useful for efficiency (speed) when the groups are evaluated. All characters are allowed except %	...	S-1-5-32-548
• type	String	No	No character restriction	...	GLOBAL
adAttributes	List	No	Holds list of AD Attributes
• attributes	List	No	List of Attributes
• name	String	Yes	Required for each attribute in the attribute list with no duplication between attributes. All characters are allowed except <%”	...	name1
• type	Enum	Yes	Required for each group in the group list. Allowed values: - STRING, - IP, - BOOLEAN, - INT, - OCTET_STRING	STRING	...

continues on next page

Table 31 – continued from previous page

• internal-Name	String	Yes	Required for each attribute in the attribute list. All characters are allowed except <%"	...	internalName1
• default-Value	String	Yes	Required for each attribute in the attribute list. Can contain an empty string. All characters are allowed except <%"	...	defaultString
advancedSettings	List	No
• rewriteRules	List	No	Identity rewrite is an advanced feature that directs Cisco ISE to manipulate the identity before it is passed to the external Active Directory system. You can create rules to change the identity to a desired format that includes or excludes a domain prefix and/or suffix or other additional markup of your choice
• rowId	Integer	Yes	Required for each rule in the list in serial order	...	0
• rewriteMatch	String	Yes	Required for each rule in the list with no duplication between rules. All characters are allowed except %"	...	exampleMatch0

continues on next page

Table 31 – continued from previous page

• rewriteResult	String	Yes	Required for each rule in the list. All characters are allowed except %”	...	exampleResult0
• enableRewrites	Boolean	No	...	false	...
• enablePassChange	Boolean	No	...	true	...
• enableMachineAuth	Boolean	No	...	true	...
• enableMachineAccess	Boolean	No	...	true	...
• enableDialinPermissionCheck	Boolean	No	...	false	...
• plaintextAuth	Boolean	No	...	false	...
• agingTime	Integer	No	Range 1-8760 hours	5	...
• enableCallbackForDialinClient	Boolean	No	...	false	...
• identityNotInAdBehaviour	Enum	No	Allowed values: - REJECT, - SEARCH_JOINED_FOREST, - SEARCH_ALL	SEARCH_JOINED_FOREST	

continues on next page

Table 31 – continued from previous page

• unreachableDomainsBehaviour	Enum	No	Allowed values: - PROCEED, - DROP	PROCEED	...
• schema	Enum	No	Allowed values: - ACTIVE_DIRECTORY, - CUSTOM-Choose ACTIVE_DIRECTORY schema when the AD attributes defined in AD can be copied to relevant attributes in Cisco ISE. If customization is needed, choose CUSTOM schema. All User info attributes are always set to default value if schema is ACTIVE_DIRECTORY. Values can be changed only for CUSTOM schema	ACTIVE_DIRECTORY	...
• firstName	String	No	User info attribute. All characters are allowed except %	givenName	...
• department	String	No	User info attribute. All characters are allowed except %	department	...
• lastName	String	No	User info attribute. All characters are allowed except %	sn	...

continues on next page

Table 31 – continued from previous page

• organiza- tionalU- nit	String	No	User info at- tribute. All characters are allowed except %	company	...
• jobTitle	String	No	User info at- tribute. All characters are allowed except %	title	...
• locality	String	No	User info at- tribute. All characters are allowed except %	l	...
• email	String	No	User info at- tribute. All characters are allowed except %	mail	...
• stateOr- Province	String	No	User info at- tribute. All characters are allowed except %	st	...
• telephone	String	No	User info at- tribute. All characters are allowed except %	telepho- neNumber	...
• country	String	No	User info at- tribute. All characters are allowed except %	co	...
• streetAd- dress	String	No	User info at- tribute. All characters are allowed except %	streetAddress	...
• enable- FailedAu- th Protec- tion	Boolean	No	Enable prevent AD account lockout due to too many bad password attempts	false	...
• failedAu- thThresh- old	Integer	No	Number of bad password attempts	5	...

continues on next page

Table 31 – continued from previous page

• authProtection-Type	Enum	No	Enable prevent AD account lockout. Allowed values:- WIRELESS, - WIRED, - BOTH	WIRELESS	...
-----------------------	------	----	---	----------	-----

get_active_directory_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
load_groups_from_domain(id, ad_attributes=None, ad_scopes_names=None, adgroups=None,
                        advanced_settings=None, description=None, domain=None,
                        enable_domain_white_list=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes (object)** – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names (string)** – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups (object)** – Holds list of AD Groups, property of the request body.
- **advanced_settings (object)** – advancedSettings, property of the request body.
- **description (string)** – No character restriction, property of the request body.
- **domain (string)** – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list (boolean)** – enableDomainWhiteList, property of the request body.
- **id (basestring)** – Resource UUID value, property of the request body.
- **name (string)** – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **id** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
is_user_member_of_groups(id, additional_data=None, headers=None, payload=None,  
                           active_validation=True, **query_parameters)
```

This API verifies if the user is a member of the given groups.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_trusted_domains(id, headers=None, **query_parameters)
```

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

join_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetchs the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory*

`get_active_directory_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

create_active_directory(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None,  
description=None, domain=None, enable_domain_white_list=None, id=None, name=None,  
headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_active_directory*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.1_Patch_1).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

The Admin User API allows to retrieve information related to admin users configured on Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	1.1	2.0	Cisco ISE Release 2.3 Admin User

Resource Definition

Attribute	Type	Re- quired	Description	Example Values	De- fault Value
name	String	Yes	Resource Name		
id	String	Yes	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69	
description	String	No			
changePass- word	Boolean	Yes		true	true
email	String	No		email1@domain.com	
includeSys- temAlarm- sInEmail	Boolean	No		false	
inactiveAc- countN- everDisabled	Boolean	No		true	
enabled	Boolean	Yes		false	
external	Boolean	No		true	
customAt- tributes	String	No	Key Value Map	{“MyCustom- Attribute” : “Value1”}	
firstName	String	No			
adminGroups	String	No	Admin Group Names	Super Admin	
lastName	String	No			
password	String	No	The password field doesn’t show the actual password configured. It is hidden with the asterisk (*) symbol		

get_admin_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

allowed_protocols**class AllowedProtocols**

Identity Services Engine AllowedProtocols API (version: 3.1_Patch_1).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

Allowed Protocols API allows the client to add, delete, update, search and perform actions on allowed protocols.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.7	Added support for TEAP	preferredEapProtocol	Added value 'TEAP' to enum attribute preferredEapProtocol
				allowTeap	Added boolean attribute allowTeap
				allowTeapEapMsChapV2	Added boolean attribute allowTeapEapMsChapV2
				allowTeapEapMsChapV2PwdChange	Added boolean attribute allowTeap
				allowTeapEapMsChapV2PwdChangeRetries	Added int attribute allowTeapEapMsChapV2PwdChangeRetries
				allowTeapEapTls	Added boolean attribute allowTeapEapTls

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Device Admin
id	String	No	Resource UUID, Mandatory for update	926901b0-8c01-11e6-996c-525400b48521
description	String	No		Default Allowed Protocol Service Device Admin
processHost-Lookup	Boolean	Yes		true
allowPapAscii	Boolean	No		true
allowChap	Boolean	Yes		false
allowMsChapV1	Boolean	Yes		false
allowMsChapV2	Boolean	Yes		false
allowEapMd5	Boolean	Yes		true
allowLeap	Boolean	Yes		false
allowEapTls	Boolean	Yes		true
allowEapTtls	Boolean	Yes		true
allowEapFast	Boolean	Yes		true
allowPeap	Boolean	Yes		true
allowTeap	Boolean	Yes		true
allowPreferredEapProtocol	Boolean	Yes		true

continues on next page

Table 32 – continued from previous page

eapTlsLBit	Boolean	Yes		false
allowWeakCiphersForEap	Boolean	Yes		false
requireMessageAuth	Boolean	Yes		false
preferredEapProtocol	Enum	No	The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored.	PEAP
eapTls	List	No	The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol	
• allowEapTlsAuthOfExpiredCerts	Boolean	Yes		false
• eapTlsEnableStatelessSessionResume	Boolean	Yes		false
• eapTlsSessionTicketTtl	Integer	No	Time to live. The eapTlsSessionTicketTtl is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
• eapTlsSessionTicketTtlUnits	Enum	No	Time to live time units. The eapTlsSessionTicketTtlUnits is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored.	SECONDS

continues on next page

Table 32 – continued from previous page

<ul style="list-style-type: none"> • eapTlsSessionTicketPrecentage 	Integer	No	The eapTlsSessionTicketPrecentage is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
peap	List	No	The peap is required only if allowPeap is true, otherwise it must be ignored. The object peap contains the settings for PEAP protocol	
<ul style="list-style-type: none"> • allowPeapEapMsChapV2 	Boolean	Yes		true
<ul style="list-style-type: none"> • allow-PeapEapMsChapV2PwdChange 	Boolean	No	The allow-PeapEapMsChapV2PwdChange is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored	true
<ul style="list-style-type: none"> • allow-PeapEapMsChapV2PwdChangeRetries 	Integer	No	The allow-PeapEapMsChapV2PwdChangeRetries is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowPeapEapGtc 	Boolean	Yes		false
<ul style="list-style-type: none"> • allowPeapEapGtcPwdChange 	Boolean	No	The allowPeapEapGtcPwdChange is required only if allowPeapEapGtc is true, otherwise it must be ignored	false

continues on next page

Table 32 – continued from previous page

• allowPeapEapGtcPwdChangeRetries	Integer	No	The allowPeapEapGtcPwdChangeRetries is required only if allowPeapEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
• allowPeapEapTls	Boolean	Yes		true
• allowPeapEapTlsAuthOfExpiredCerts	Boolean	No	The allowPeapEapTlsAuthOfExpiredCerts is required only if allowPeapEapTls is true, otherwise it must be ignored	false
• requireCryptobinding	Boolean	Yes		false
• allowPeapV0	Boolean	Yes		false
eapTtls	List	No	The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol	
• eapTtlsPapAscii	Boolean	Yes		true
• eapTtlsChap	Boolean	Yes		true
• eapTtlsMsChapV1	Boolean	Yes		true
• eapTtlsMsChapV2	Boolean	Yes		true

continues on next page

Table 32 – continued from previous page

• eapT-tlsEapMd5	Boolean	Yes		true
• eapT-tlsEapM-sChapV2	Boolean	Yes		true
• eapT-tlsEapM-sChapV2PwdChange	Boolean	No	The eapTtlsEapM-sChapV2PwdChange is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored	true
• eapT-tlsEapM-sChapV2PwdChangeRetries	Integer	No	The eapTtlsEapM-sChapV2PwdChangeRetries is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
eapFast	List	No	The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol	
• allowEap-FastEapM-sChapV2	Boolean	Yes		true
• allowEap-FastEapM-sChapV2PwdChange	Boolean	No	The allowEap-FastEapM-sChapV2PwdChange is required only if allowEap-FastEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 32 – continued from previous page

<ul style="list-style-type: none"> • allowEap-FastEapM-sChapV2PwChangeRetries 	Integer	No	The allowEap-FastEapM-sChapV2PwChangeRetries is required only if eapTlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapGtc 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChange 	Boolean	No	The allowEap-FastEapGtcPwChange is required only if allowEap-FastEapGtc is true, otherwise it must be ignored	true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChangeRetries 	Integer	No	The allowEap-FastEapGtcPwChangeRetries is required only if allowEapFastEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapTlsAuthOfExpiredCerts 	Boolean	No	The allowEap-FastEapTlsAuthOfExpiredCerts is required only if allowEap-FastEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastEnableEAPChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • eapFastUsePacs 	Boolean	Yes		true

continues on next page

Table 32 – continued from previous page

• eapFastUsePacsTunnelPacTtl	Integer	No	The eapFastUsePacsTunnelPacTtl is required only if eapFastUsePacs is true, otherwise it must be ignored	7776000
• eapFastUsePacsTunnelPacTtlUnits	Enum	No	The eapFastUsePacsTunnelPacTtlUnits is required only if eapFastUsePacs is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsUseProactivePacUpdatePercentage	Integer	No	The eapFastUsePacsUseProactivePacUpdatePercentage is required only if eapFastUsePacs is true, otherwise it must be ignored	10
• eapFastUsePacsAllowAnonymProvisioning	Boolean	No	The eapFastUsePacsAllowAnonymProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAllowAuthenProvisioning	Boolean	No	The eapFastUsePacsAllowAuthenProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning	Boolean	No	The eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false

continues on next page

Table 32 – continued from previous page

• eapFastUsePacsAcceptClientCert	Boolean	No	The eapFastUsePacsAcceptClientCert is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false
• eapFastUsePacsAllowMachineAuthentication	Boolean	No		false
• eapFastUsePacsMachinePacTtl	Integer	No	The eapFastUsePacsMachinePacTtl is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored	1
• eapFastUsePacsMachinePacTtlUnits	Enum	No	The eapFastUsePacsMachinePacTtlUnits is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsStatelessSessionResume	Boolean	No	The eapFastUsePacsStatelessSessionResume is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAuthorizationPacTtl	Integer	No	The eapFastUsePacsAuthorizationPacTtl is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored	1

continues on next page

Table 32 – continued from previous page

<ul style="list-style-type: none"> • eapFastUsePacsAuthorizationPacTtlUnits 	Enum	No	The eapFastUsePacsAuthorizationPacTtlUnits is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored.	SECONDS
<ul style="list-style-type: none"> • eapFastDontUsePacsAcceptClientCert 	Boolean	No	The eapFastDontUsePacsAcceptClientCert is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastDontUsePacsAllowMachineAuthentication 	Boolean	No	The eapFastDontUsePacsAllowMachineAuthentication is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
teap	List	No	The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol	
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChange 	Boolean	No	The allowTeapEapM-sChapV2PwdChange is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 32 – continued from previous page

• allowTeapEapM-sChapV2PwdChangeRetries	Integer	No	The allowTeapEapM-sChapV2PwdChangeRetries is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	3
• allowTeapEapTls	Boolean	Yes		true
• allowTeapEapTlsAuthOfExpiredCerts	Boolean	No	The allowTeapEapTlsAuthOfExpiredCerts is required only if allowTeapEapTls is true, otherwise it must be ignored	false
• acceptClientCertDuringTunnelEst	Boolean	Yes		true
• enableEapChaining	Boolean	Yes		false
• allowDowngradeMsk	Boolean	Yes		false

get_allowed_protocol_by_name(name, headers=None, **query_parameters)

This API allows the client to get an allowed protocol by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_name`***`get_allowed_protocol_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_id`*

```
update_allowed_protocol_by_id(id, allow_chap=None, allow_eap_fast=None, allow_eap_md5=None,
                             allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None,
                             allow_ms_chap_v1=None, allow_ms_chap_v2=None,
                             allow_pap_ascii=None, allow_peap=None,
                             allow_preferred_eap_protocol=None, allow_teap=None,
                             allow_weak_ciphers_for_eap=None, description=None,
                             eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None,
                             name=None, peap=None, preferred_eap_protocol=None,
                             process_host_lookup=None, require_message_auth=None, teap=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_ttls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols_generator*

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.

- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
create(allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None,
        allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None,
        allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None,
        allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None,
        eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None,
        process_host_lookup=None, require_message_auth=None, teap=None, headers=None,
        payload=None, active_validation=True, **query_parameters)
```

Alias for *create_allowed_protocol*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy

class AncPolicy

Identity Services Engine AncPolicy API (version: 3.1_Patch_1).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource ID	test
description	String	No		
action	Enum	Yes	<ul style="list-style-type: none"> • QUAR-ANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. • PORT-BOUNCE: Resets the port on the network device to which the endpoint is connected • SHUT-DOWN : Shuts down the port on the network device to which the endpoint is connected • RE_AUTHENTICATE: Re-authenticates the session from the endpoint 	

get_anc_policy_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_name`*

`get_anc_policy_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC policy by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_id`*

```
update_anc_policy_by_id(id, actions=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are ‘QUARANTINE’, ‘PORTBOUNCE’, ‘SHUTDOWN’ and ‘RE_AUTHENTICATE’).
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, actions=None, name=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_anc_policy_by_id*

```
delete_anc_policy_by_id(id, headers=None, **query_parameters)
```

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy_generator*

create_anc_policy(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_anc_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_policy(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.1_Patch_1).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

Authorization Profile API allows the client to add, delete, update, search and perform actions on authorization profiles.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revi- sion Mod- ifica- tion	Revision Modification
				At- tribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.3	Support new attributes under common tasks	ac- cessType	Added Attribute 'accessType'. Default value:'ACCESS_ACCEPT', additional values: 'ACCESS_REJECT'
				au- thzPro- file- Type	Added Attribute 'authzProfileType' to differentiate between types of authorization profiles. Default value:'SWITCH' (used for Standard Authorization Profiles) , additional values:'TACACS', 'TRUSTSEC'
				reauth	Added Attribute 'reauth' to determine reauthentication policy
				we- bRedi- rec- tion	Added Attribute 'webRedirection' to support selection of portal redirection
				acl	Added String Attribute 'acl'
				track- Move- ment	Added Boolean Attribute 'trackMovement'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID value		id
description	String	No			description
vlan	List	No			
• nameID	String	Yes			vlanName
• tagID	Integer	Yes	Valid range is 0-31		1
airespaceACL	String	No			ACL
webRedirection	List	No			
• WebRedirectionType	String	Yes	Value MUST be one of the following: CentralizedWebAuth, HotSpot, NativeSupplicantProvisioning, ClientProvisioning. The WebRedirectionType must fit the portalName		Centralized-WebAuth
• acl	String	Yes			acl
• portal-Name	String	Yes	A portal that exist in the DB and fits the WebRedirectionType		Sponsored Guest Portal (default)
• staticIPHost-Name-FQDN	String	No			10.56.54.200

continues on next page

Table 33 – continued from previous page

• displayC- ertifi- catesRe- newalMes- sages	Boolean	No	The displayC- ertificatesRe- newalMes- sages is mandatory when ‘We- bRedirection- Type’ value is ‘Central- izedWebAuth’. For all other ‘WebRedi- rectionType’ values the field must be ignored	true	
accessType	Enum	No	Allowed Values: AC- CESS_ACCEPT, AC- CESS_REJECT	AC- CESS_ACCEPT	
authzProfile- Type	Enum	No	Allowed Val- ues: SWITCH, TRUSTSEC, TACACS	SWITCH	
			SWITCH is used for Standard Au- thorization Profiles		
profileName	String	No		Cisco	
acl	String	No			aclfilter
daclName	String	No			PER- MIT_ALL_IPV4_TRAFFIC
autoSmartPort	String	No			autoSmartPort
interfaceTem- plate	String	No			interfaceTem- plate
ipv6ACLFILTER	String	No			ipv6ACLFILTER
avcProfile	String	No			avcProfile
asaVpn	String	No			Cisco:cisco- call-type
trackMove- ment	Boolean	No		false	
serviceTem- plate	Boolean	No		false	
easywiredSes- sionCandidate	Boolean	No		false	
voiceDomain- Permission	Boolean	No		false	
neat	Boolean	No		false	
webAuth	Boolean	No		false	

continues on next page

Table 33 – continued from previous page

macSecPolicy	Enum	No	Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE		MUST_SECURE
reauth	List	No			
• connectivity	Enum	Yes	Allowed Values: DEFAULT, RADIUS_REQUEST		RADIUS_REQUEST
• timer	Integer	Yes	Valid range is 1-65535		1800
advancedAttributes	List	No			
• leftHandSideDictionaryAttribute	List	Yes	Left side Dictionary and Attribute		
• dictionaryName	String	Yes	Dictionary name		
• attributeName	String	Yes	Attribute name		
• rightHandSideAttributeValue	List	Yes	Attribute value can be of type AttributeValue or AdvancedDictionaryAttribute. For AttributeValue the value is String, For AdvancedDictionaryAttribute the value is dictionaryName and attributeName properties		
ipv6DaclName	String	No			PERMIT_ALL_IPV6_TRAFFIC
airespaceIPv6ACL	String	No			ACL6

`get_authorization_profile_by_name(name, headers=None, **query_parameters)`

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_id*

update_authorization_profile_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.

- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_authorization_profile_by_id*

delete_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_authorization_profile_by_id*

get_authorization_profiles(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles***get_authorization_profiles_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles_generator*

```
create_authorization_profile(access_type=None, acl=None, advanced_attributes=None,
                             agentless_posture=None, airespace_acl=None,
                             airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
                             auto_smart_port=None, avc_profile=None, dacl_name=None,
                             description=None, easywired_session_candidate=None, id=None,
                             interface_template=None, ipv6_acl_filter=None,
                             ipv6_dacl_name=None, mac_sec_policy=None, name=None,
                             neat=None, profile_name=None, reauth=None, service_template=None,
                             track_movement=None, vlan=None, voice_domain_permission=None,
                             web_auth=None, web_redirection=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API creates an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.

- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(access_type=None, acl=None, advanced_attributes=None, agentless_posture=None,
        airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
        auto_smart_port=None, avc_profile=None, dacl_name=None, description=None,
        easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None,
        ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None,
        reauth=None, service_template=None, track_movement=None, vlan=None,
        voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None,
        payload=None, active_validation=True, **query_parameters)
```

Alias for *create_authorization_profile*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

byod_portal**class ByodPortal**

Identity Services Engine BYODPortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

BYOD Portal API provides the ability to Create, Read, Update, Delete and Search BYOD portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		BYOD Portal (default)
id	String	No	Resource UUID, mandatory for update		9a9b910c-54d3-44a4-a3c3-dd007c171599

continues on next page

Table 34 – continued from previous page

description	String	No			Default portal and user experience used when employees register a personal device on the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?portalId=54d3-44a4-a3c3-dd007c171599
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	BYOD	
settings	List	No	Defines all of the settings groups available for a BYOD		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		["eth0", "bond0"]

continues on next page

Table 34 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• end- pointI- dentity- Group	String	Yes	Unique Id of the endpoint identity group where user's devices will be added. Used only in Hotspot Portal		
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• byodSet- tings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWel- comeSet- tings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enable- BYOD	Boolean	No		true	
• en- ableGues- tAccess	Boolean	No		false	

continues on next page

Table 34 – continued from previous page

• re-requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No		false	
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodRegistrationSettings	List	No	Configuration of BYOD endpoint Registration step configuration		
• showDeviceID	Boolean	No	Display Device ID field during registration	true	
• endpointIdentityGroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521

continues on next page

Table 34 – continued from previous page

• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Au- thentication Success where should device be redirected.	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		Redirect URL
• support- InfoSet- tings	List	No	Configuration of BYOD endpoint wel- come step configuration		
• in- cludeSup- portIn- foPage	Boolean	No		false	
• in- cludeMacAddr	Boolean	No		false	
• in- cludeIpAd- dress	Boolean	No		false	
• include- BrowserUser- Agent	Boolean	No		false	
• include- Policy- Server	Boolean	No		false	
• include- Failure- Code	Boolean	No		false	

continues on next page

Table 34 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available for a BYOD		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 34 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 34 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			BYOD Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 34 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_byod_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_byod_portal_by_id*

update_byod_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a BYOD portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.


```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_byod_portal_by_id`

```
delete_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_byod_portal_by_id`

```
get_byod_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                headers=None, **query_parameters)
```

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal*

get_byod_portal_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_byod_portal*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

backup_and_restore**class BackupAndRestore**

Identity Services Engine Backup And Restore API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_last_status(*headers=None, **query_parameters*)Alias for *get_last_config_backup_status*
restore_config_backup(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **`backup_encryption_key`** (*string*) – The encryption key which was provided at the time of taking backup., property of the request body.
- **`repository_name`** (*string*) – Name of the configured repository where the backup file exists., property of the request body.
- **`restore_file`** (*string*) – Name of the backup file to be restored on ISE node., property of the request body.
- **`restore_include_adeos`** (*string*) – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

restore(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *restore_config_backup*

update_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description (string)** – Description of the backup., property of the request body.
- **backup_encryption_key (string)** – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name (string)** – The backup file will get saved with this name., property of the request body.
- **end_date (string)** – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency (string)** – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.

- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘DISABLE’ and ‘ENABLE’.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are ‘FRI’, ‘MON’, ‘SAT’, ‘SUN’, ‘THU’, ‘TUE’ and ‘WED’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.1_Patch_1).
Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

The certificate profile API allows the client to add, search and perform actions on the certificate profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.4	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Certificate_Profile
id	String	No	Resource UUID		f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No			
allowedAsUserName	Boolean	No	To be set true or false	false	
external-identity-store-name	String	No	Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen	[not applicable]	[not applicable]
certificate-attribute-name	ENUM	No	Attribute name of the Certificate Profile - used only when CERTIFICATE is chosen in usernameFrom. Allowed values: - SUBJECT_COMMON_NAME - SUBJECT_ALTERNATIVE_NAME - SUBJECT_SERIAL_NUMBER - SUBJECT - SUBJECT_ALTERNATIVE_NAME_OTHER_NAME - SUBJECT_ALTERNATIVE_NAME_EMAIL - SUBJECT_ALTERNATIVE_NAME_DNS. - Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN	SUBJECT_COMMON_NAME	
match-Mode	ENUM	No	Match mode of the Certificate Profile. Allowed values: NEVER, RESOLVE_IDENTITY_AMBIGUITY, BINARY_COMPARISON	NEVER	
username-From	ENUM	No	The attribute in the certificate where the user name should be taken from.	CERTIFICATE	

get_certificate_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_name*

`get_certificate_profile_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_id*

```
update_certificate_profile_by_id(id, allowed_as_user_name=None,
                                certificate_attribute_name=None, description=None,
                                external_identity_store_name=None, match_mode=None,
                                name=None, username_from=None, headers=None,
                                payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allowed_as_user_name=None*, *certificate_attribute_name=None*, *description=None*, *external_identity_store_name=None*, *match_mode=None*, *name=None*, *username_from=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_certificate_profile_by_id*

get_certificate_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile*

get_certificate_profile_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.

- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_certificate_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificate_template**class CertificateTemplate**

Identity Services Engine CertificateTemplate API (version: 3.1_Patch_1).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

The certificate template API provides the ability to search for certificate templates.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.2	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
raProfile-Name	String	Yes	RA profile for the Certificate template	ISE internal CA
keySize	Integer	No	Key Size of the Certificate Template	2048 1024
validity	Integer	No	Validity period of the Certificate Template: Valid Range 21 - 3652	730

get_certificate_template_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_name*

get_certificate_template_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_certificate_template_generator`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csrs_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
generate_csr(allow_wild_card_cert=None, certificate_policies=None, digest_type=None,
             hostnames=None, key_length=None, key_type=None, portal_group_tag=None,
             san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None,
             subject_common_name=None, subject_country=None, subject_org=None,
             subject_org_unit=None, subject_state=None, used_for=None, headers=None,
             payload=None, active_validation=True, **query_parameters)
```

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following parameters are present in POST request body

PARAMETER DESCRIPTION

EXAMPLE hostnames List of Cisco ISE node hostnames for which CSRs should be generated

“hostnames”: [“ise-host1”, “ise-host2”] allowWildCardCert Allow use of WildCards in certificates

“allowWildCardCert”: false keyLength * required Length of the key used for CSR generation (required).

“keyLength”: “512” keyType * required Type of key used for CSR generation either RSA or ECDSA (required).

“keyType”: “RSA” digestType * required Hash algorithm used for signing CSR (required).

“digestType”: “SHA-256” usedFor * required Certificate usage (required).

“usedFor”: “MULTI-USE” certificatePolicies Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs.

“certificatePolicies”: “Certificate Policies” subjectCommonName * required Certificate common name (CN) (required).

“subjectCommonName”: “\$FQDN\$” subjectOrgUnit Certificate organizational unit (OU).

“subjectOrgUnit”: “Engineering” subjectOrg Certificate organization (O).

“subjectOrg”: “Cisco” subjectCity Certificate city or locality (L).

“subjectCity”: “San Jose” subjectState Certificate state (ST).

“subjectState”: “California” subjectCountry Certificate country (C).

“subjectCountry”: “US” sanDNS Array of SAN (Subject Alternative Name) DNS entries (optional).

“sanDNS”: [“ise.example.com”] sanIP Array of SAN IP entries (optional).

“sanIP”: [“1.1.1.1”] sanURI Array of SAN URI entries (optional).

“sanURI”: [“https://1.1.1.1”] sanDir Array of SAN DIR entries (optional).

“sanDir”: [“CN=AAA,DC=COM,C=IL”] portalGroupTag Portal Group Tag when using certificate for PORTAL service

“portalGroupTag”: “Default Portal Certificate Group” NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames When certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – keyType, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.

- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.
- **used_for** (*string*) – usedFor, property of the request body. Available values are ‘ADMIN’, ‘DTLS- AUTH’, ‘EAP-AUTH’, ‘IMS’, ‘MULTI-USE’, ‘PORTAL’, ‘PXGRID’ and ‘SAML’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname, id, dirpath=None, save_file=None, filename=None, headers=None, **query_parameters*)

Response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type*DownloadResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node for given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_csr_by_id`(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on given HostName and ID.

Parameters

- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host of which CSR's should be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the Certificate Signing Request to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`regenerate_ise_root_ca`(*remove_existing_ise_intermediate_csr=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API initiates regeneration of Cisco ISE root CA certificate chain. Response contains ID which can be used to track the status. Setting “removeExistingISEIntermediateCSR” to true removes existing Cisco ISE Intermediate CSR.

Parameters

- **remove_existing_ise_intermediate_csr** (*boolean*) – Setting this attribute to true removes existing Cisco ISE Intermediate CSR, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

renew_certificates(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API initiates regeneration of certificates. Response contains ID which can be used to track the status.

Parameters

- **cert_type** (*string*) – certType, property of the request body. Available values are 'IMS' and 'OCSP'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
portal_group_tag=None, pxgrid=None, radius=None, saml=None,
validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
**query_parameters)
```

Bind CA Signed Certificate. NOTE: This API requires an

existing Certificate Signing Request, and the root certificate must already be trusted. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body **PARAMETER DESCRIPTION EXAMPLE** name Friendly name of the certificate. “name”: “CA Signed Certificate” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

```
{sub(/
```

```
/, “”); printf “%sn”, $0;}’ <<your .pem file>>
```

to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowOutOfDateCert * required Allow out of date certificates (required). **SECURITY ALERT:** It is recommended to use “allowOutOfDateCert”: false to avoid binding of expired certificates (not Secure). “allowOutOfDateCert”: true allowReplacementOfCertificates * required Allow Replacement of certificates (required). “allowReplacementOfCertificates”: true allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADIUS server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”: false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal Certificate Group” validateCertificateExtensions Validate Certificate Extensions “validateCertificateExtensions”: false Following roles can be used in any combinations **ROLE DEFAULT WARNING** Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the
Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

data(string): Signed certificate data (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

host_name(string): Name of Host whose CSR ID has been provided (required), property of the request body.

id(string): ID of the generated CSR (required), property of the request body.

ims(boolean): Use certificate for the Cisco ISE Messaging Service, property of the request body.

name(string): Friendly Name of the certificate, property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

*****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Raises:

`TypeError`: If the parameter types are incorrect. `MalformedRequest`: If the request body created is invalid. `ApiError`: If the Identity Services Engine cloud returns an error.

export_system_certificate(*export=None, id=None, password=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Export System Certificate. Following parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE
id * required ID of a System Certificate (required). "id": "CERT-ID" export One of the below option is required "CERTIFICATE" : Export only certificate without private key "CERTIFICATE_WITH_PRIVATE_KEY" : Export both certificate and private key ("certificatePassword" is required). "export": "CERTIFICATE_WITH_PRIVATE_KEY" password * required Certificate password (required if "export" : CERTIFICATE_WITH_PRIVATE_KEY). Password constraints: Alphanumeric Minimum of 8 Characters Maximum of 100 Characters "password": "certificate password" NOTE: The response of this API carries a ZIP file containing the certificate and private key if "export" : "CERTIFICATE_WITH_PRIVATE_KEY" in the request. If "export" : "CERTIFICATE" in request body, the response carries a ZIP file containing only the certificate. WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are 'CERTIFICATE' and 'CERTIFICATE_WITH_PRIVATE_KEY'.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
generate_self_signed_certificate(admin=None, allow_extended_validity=None,
                                allow_portal_tag_transfer_for_same_subject=None,
                                allow_replacement_of_certificates=None,
                                allow_replacement_of_portal_group_tag=None,
                                allow_role_transfer_for_same_subject=None,
                                allow_san_dns_bad_name=None,
                                allow_san_dns_non_resolvable=None,
                                allow_wild_card_certificates=None, certificate_policies=None,
                                digest_type=None, eap=None, expiration_ttl=None,
                                expiration_ttl_unit=None, host_name=None, key_length=None,
                                key_type=None, name=None, portal=None,
                                portal_group_tag=None, pxgrid=None, radius=None, saml=None,
                                san_dns=None, san_ip=None, san_uri=None, subject_city=None,
                                subject_common_name=None, subject_country=None,
                                subject_org=None, subject_org_unit=None, subject_state=None,
                                headers=None, payload=None, active_validation=True,
                                **query_parameters)
```

Generate Self-signed Certificate NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. NOTE: Wildcard certificate and SAML certificate can be generated only on PSPAN or Standalone Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE hostName * required Hostname or FQDN of the node in which certificate needs to be created (required). “hostName”: “ise-node-001” name Friendly name of the certificate. “name”: “Self-signed System Certificate” subjectCommonName Certificate common name (CN) NOTE: 1. CN is Mandatory if SAN not configured. 2. Subject can contain a multi- valued CN. For multi-valued RDNs, follow the format “CN=value1, CN=value2” “subjectCommonName”: “\$FQDN\$” subjectOrgUnit Certificate organizational unit (OU) NOTE: Subject can contain a multi-valued OU. For multi- valued RDNs, follow the format “OU=value1, OU=value2” “subjectOrgUnit”: “Engineering” subjectOrg Certificate organization (O) NOTE: Subject can contain a multi-valued O fields. For multi-valued RDNs, follow the format “O=value1, O=value2” “subjectOrg”: “Cisco” subjectCity Certificate city or locality (L) “subjectCity”: “San Jose” subjectState Certificate state (ST) “subjectState”: “California” subjectCountry Certificate country (C) “subjectCountry”: “US” sanDNS Array of SAN (Subject Alternative Name) DNS entries “sanDNS”: [“ise.example.com”] sanIP Array of SAN IP entries “sanIP”: [“1.1.1.1”] sanURI Array of SAN URI entries “sanURI”: [“https://1.1.1.1”] keyType * required Algorithm to use for certificate public key creation (required). “keyType”: “RSA” keyLength * required Bit size of the public key (required). “keyLength”: “4096” digestType * required Digest to sign with (required). “digestType”: “SHA-384” certificatePolicies Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs. “certificatePolicies”: “Certificate Policies” expirationTTL * required Certificate expiration value (required). NOTE: Expiration TTL should be within Unix time limit “expirationTTL”: 2 expirationTTLUnit * required Certificate expiration unit (required). “expirationTTLUnit”: “years” admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADSec server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”: false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal Certificate Group” allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true allowWildCardCertificates Allow use of WildCards in certificates “allowWildCardCertificates”: false allowReplacementOfCertificates * required Allow replacement of certificates (required). “allowReplacementOfCertificates”: true allowExtendedValidity * required Allow generation of self-signed

certificate with validity greater than 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject * required Allow the transfer of roles to certificates with same subject (required). If the matching certificate on Cisco ISE has either admin or portal role and if request has admin or portal role selected along with allowRoleTransferForSameSubject parameter as true, self- signed certificate would be generated with both admin and portal role enabled “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject * required Acquire the group tag of the matching certificate (required). If the request portal group tag is different from the group tag of matching certificate (If matching certificate in Cisco ISE has portal role enabled), self- signed certificate would be generated by acquiring the group tag of matching certificate if allowPortalTagTransferForSameSubject parameter is true “allowPortalTagTransferForSameSubject”: true allowSanDnsBadName * required Allow generation of self-signed certificate with bad Common Name & SAN Values [like “example.org.”,”invalid.”,”test.”,”localhost” ,etc.] (required). SECURITY ALERT: It is recommended to use “allowSanDnsBadName”: false to avoid generation of certificates with bad Common Name & SAN Values which are not secure “allowSanDnsBadName”: true allowSanDnsNonResolvable * required Allow generation of self-signed certificate with non resolvable Common Name or SAN Values (required). “allowSanDnsNonResolvable”: true ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. SAML False SAML cannot be used with other Usage. .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_extended_validity** (*boolean*) – Allow generation of self-signed certificate with validity greater than 398 days, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_certificates** (*boolean*) – Allow Replacement of certificates, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag, property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **allow_san_dns_bad_name** (*boolean*) – Allow usage of SAN DNS Bad name, property of the request body.
- **allow_san_dns_non_resolvable** (*boolean*) – Allow use of non resolvable Common Name or SAN Values, property of the request body.
- **allow_wild_card_certificates** (*boolean*) – Allow Wildcard Certificates, property of the request body.
- **certificate_policies** (*string*) – Certificate Policies, property of the request body.
- **digest_type** (*string*) – Digest to sign with, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl** (*integer*) – Certificate expiration value, property of the request body.

- **expiration_ttl_unit** (*string*) – Certificate expiration unit, property of the request body. Available values are ‘days’, ‘months’, ‘weeks’ and ‘years’.
- **host_name** (*string*) – Hostname of the Cisco ISE node in which self-signed certificate should be generated., property of the request body.
- **key_length** (*string*) – Bit size of public key, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – Algorithm to use for certificate public key creation, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **name** (*string*) – Friendly name of the certificate., property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **san_dns** (*list*) – Array of SAN (Subject Alternative Name) DNS entries, property of the request body (list of strings).
- **san_ip** (*list*) – Array of SAN IP entries, property of the request body (list of strings).
- **san_uri** (*list*) – Array of SAN URI entries, property of the request body (list of strings).
- **subject_city** (*string*) – Certificate city or locality (L), property of the request body.
- **subject_common_name** (*string*) – Certificate common name (CN), property of the request body.
- **subject_country** (*string*) – Certificate country (C), property of the request body.
- **subject_org** (*string*) – Certificate organization (O), property of the request body.
- **subject_org_unit** (*string*) – Certificate organizational unit (OU), property of the request body.
- **subject_state** (*string*) – Certificate state (ST), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
import_system_certificate(admin=None, allow_extended_validity=None,
                          allow_out_of_date_cert=None,
                          allow_portal_tag_transfer_for_same_subject=None,
                          allow_replacement_of_certificates=None,
                          allow_replacement_of_portal_group_tag=None,
                          allow_role_transfer_for_same_subject=None,
                          allow_sha1_certificates=None, allow_wild_card_certificates=None,
                          data=None, eap=None, ims=None, name=None, password=None,
                          portal=None, portal_group_tag=None, private_key_data=None,
                          pxgrid=None, radius=None, saml=None,
                          validate_certificate_extensions=None, headers=None, payload=None,
                          active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE:

The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. “name”: “System certificate” password * required Password of the certificate to be imported (required). “password”: “certificate password” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required).

Use awk ‘NF {sub(/

/, “”); printf “%sn”, \$0;}’ <<your

.pem file>> to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” privateKeyData * required Plain-text contents of the private key file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

{sub(/

/, “”); printf “%sn”, \$0;}’ <<your .pem file>>

to extract privateKeyData from private key file. “data”: “Plain-text contents of the private key file.” allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid import of expired certificates (not Secure). “allowOutOfDateCert”: true allowSHA1certificates * required Allow import of certificate with signature that uses the SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use “allowSHA1certificates”: false to avoid import of SHA1 based certificates (less secure). “allowSHA1certificates”: true allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject Allow the transfer of roles to certificates with same subject “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject Acquire the group tag of the matching certificate “allowPortalTagTransferForSameSubject”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADSec server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”:

false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal certificate Group” allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true allowWildcardcertificates Allow use of WildCards in certificates “allowWildcardcertificates”: false validatecertificateExtensions Validate certificate extensions “validatecertificateExtensions”: false Following roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the

Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of

certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_portal_tag_transfer_for_same_subject(boolean):

Allow overwriting the portal tag from matching certificate of same subject, property of the request body.

allow_replacement_of_certificates(boolean): Allow

Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow

Replacement of Portal Group Tag (required), property of the request body.

allow_role_transfer_for_same_subject(boolean): Allow

transfer of roles for certificate with matching subject , property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

allow_wild_card_certificates(boolean): Allow Wildcard

certificates, property of the request body.

data(string): Certificate Content (required), property

of the request body.

eap(boolean): Use certificate for EAP protocols that use

SSL/TLS tunneling, property of the request body.

ims(boolean): Use certificate for the Cisco ISE

Messaging Service, property of the request body.

name(string): Name of the certificate, property of the

request body.

password(string): Certificate Password (required),,

property of the request body.

portal(boolean): Use for portal, property of the request

body.

portal_group_tag(string): Set Group tag, property of the request body.

private_key_data(string): Private Key data (required), property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate certificate extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name, filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificate_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API provides details of a System Certificate of a particular node based on given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **id** (*basestring*) – id path parameter. ID of the system certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_system_certificate(*host_name, id, admin=None, allow_portal_tag_transfer_for_same_subject=None, allow_replacement_of_portal_group_tag=None, allow_role_transfer_for_same_subject=None, description=None, eap=None, expiration_ttl_period=None, expiration_ttl_units=None, ims=None, name=None, portal=None, portal_group_tag=None, pxgrid=None, radius=None, renew_self_signed_certificate=None, saml=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update a System Certificate. NOTE: Renewing a certificate causes an application server restart on the selected node. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body

PARAMETER	DESCRIPTION	EXAMPLE
name	Friendly name of the certificate.	"name": "System Certificate"
description	Description of the certificate	"description": "Description of certificate"
admin	Use certificate to authenticate the Cisco ISE Admin Portal	"admin": false
eap	Use certificate for EAP protocols that use SSL/TLS tunneling	"eap": false
radius	Use certificate for RADIUS server	"radius": false
pxgrid	Use certificate for the pxGrid Controller	"pxgrid": false
ims	Use certificate for the Cisco ISE Messaging Service	"ims": false
saml	Use certificate for SAML Signing	"saml": false
portal	Use certificate for portal	"portal": false
portalGroupTag	Portal Group Tag for using certificate with portal role	"portalGroupTag": "Default Portal Certificate Group"
allowReplacementOfPortalGroupTag	* required Allow Replacement of Portal Group Tag (required).	"allowReplacementOfPortalGroupTag": true
allowRoleTransferForSameSubject	* required Allow transfer of roles to certificates with same subject (required).	"allowRoleTransferForSameSubject": true
allowPortalTagTransferForSameSubject	* required Acquire group tag of the matching certificate (required).	"allowPortalTagTransferForSameSubject": true
renewSelfSignedCertificate	Renew Self- signed Certificate	"renewSelfSignedCertificate": false
expirationTTLPeriod	Expiration Period	"expirationTTLPeriod": 365
expirationTTLUnits	Expiration Units in one of the below formats days / weeks / months / years	"expirationTTLUnits": "days"

Following roles can be used in any combinations

ROLE	DEFAULT	WARNING
Admin	False	Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates
EAP	Authentication	False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
RADIUS	DTLS	False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
SAML	False	SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.
- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are 'days', 'months', 'weeks' and 'years'.
- **ims** (*boolean*) – Use certificate for the Cisco ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self- signed Certificate, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_system_certificate_by_id`(*host_name, id, allow_wildcard_delete=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API deletes a System Certificate of a particular node based on given HostName and ID.

Parameters

- **`allow_wildcard_delete`** (*boolean*) – If the given certificate to be deleted is a wildcard certificate, corresponding certificate gets deleted on rest of the nodes in the deployment as well., property of the request body.
- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host from which System Certificate needs to be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the System Certificate to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_certificates`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM- dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_trusted_certificates_generator(filter=None, filter_type=None, page=None, size=None,
                                   sort=None, sort_by=None, headers=None,
                                   **query_parameters)
```

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_trusted_certificate(*id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*,
 ***query_parameters*)

The response of this API carries a trusted certificate file mapped to the requested ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be exported.

- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_trust_certificate(allow_basic_constraint_cafalse=None, allow_out_of_date_cert=None,
                        allow_sha1_certificates=None, data=None, description=None, name=None,
                        trust_for_certificate_based_admin_auth=None,
                        trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                        trust_for_ise_auth=None, validate_certificate_extensions=None,
                        headers=None, payload=None, active_validation=True,
                        **query_parameters)
```

Import an X509 certificate as a trust certificate. NOTE:

Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body `PARAMETER DESCRIPTION` EXAMPLE name Friendly name of the certificate “name”: “Trust Certificate” description Description of the certificate “description”: “Imported Trust Certificate” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use `awk 'NF {sub(/ /, "");`

```
printf ("%sn", $0; }' <<your .pem file>>
```

to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” `allowOutOfDateCert` * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid import of expired certificates (not Secure). “allowOutOfDateCert”: true `allowSHA1Certificates` * required Allow import of certificate with signature that uses SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use “allowSHA1Certificates”: false to avoid import of SHA1 based certificates (less secure). “allowSHA1Certificates”: true `allowBasicConstraintCAFalse` * required Allow certificates with Basic Constraints CA Field as False (required). SECURITY ALERT: It is recommended to use “allowBasicConstraintCAFalse”: false to avoid import of certificates with Basic Constraints CA Field as False (not Secure). “allowBasicConstraintCAFalse”: true `trustForIseAuth` Trust for authentication within Cisco ISE “trustForIseAuth”: false `trustForClientAuth` Trust for client authentication and Syslog “trustForClientAuth”: false `trustForCertificateBasedAdminAuth` Trust for

certificate based Admin authentication “trustForCertificateBasedAdminAuth”: false trustForCiscoServicesAuth Trust for authentication of Cisco Services “trustForCiscoServicesAuth”: false validateCertificateExtensions Validate extensions for trust certificate “validateCertificateExtensions”: false NOTE: If name is not set, a default name with the following format is used: common-name#issuer#nnnnn where “nnnnn” is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate is trusted in Cisco ISE. The objective here is to distinguish between certificates that are used for trust within an Cisco ISE deployment and public certificates that are used to trust Cisco services. Typically, you do not want to use a given certificate for both purposes. Trusted For Usage Authentication within Cisco ISE Use “trustForIseAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact Cisco ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Args:

allow_basic_constraint_cafalse(boolean): Allow

certificates with Basic Constraints CA Field as False (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

data(string): Certificate content (required), property

of the request body.

description(string): Description of the certificate,

property of the request body.

name(string): Name of the certificate, property of the

request body.

trust_for_certificate_based_admin_auth(boolean): Trust

for Certificate based Admin authentication, property of the request body.

trust_for_cisco_services_auth(boolean): Trust for

authentication of Cisco Services, property of the request body.

trust_for_client_auth(boolean): Trust for client

authentication and Syslog, property of the request body.

trust_for_ise_auth(boolean): Trust for authentication

within Cisco ISE, property of the request body.

validate_certificate_extensions(boolean): Validate trust

certificate extension, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

.

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(id, headers=None, **query_parameters)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id (basestring)** – id path parameter. ID of the trust certificate.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```

update_trusted_certificate(id, authenticate_before_crl_received=None, automatic_crl_update=None,
    automatic_crl_update_period=None, automatic_crl_update_units=None,
    crl_distribution_url=None, crl_download_failure_retries=None,
    crl_download_failure_retries_units=None, description=None,
    download_crl=None, enable_ocsp_validation=None,
    enable_server_identity_check=None, ignore_crl_expiration=None,
    name=None, non_automatic_crl_update_period=None,
    non_automatic_crl_update_units=None,
    reject_if_no_status_from_ocs_p=None,
    reject_if_unreachable_from_ocs_p=None, selected_ocsp_service=None,
    status=None, trust_for_certificate_based_admin_auth=None,
    trust_for_cisco_services_auth=None, trust_for_client_auth=None,
    trust_for_ise_auth=None, headers=None, payload=None,
    active_validation=True, **query_parameters)

```

Update a trusted certificate present in Cisco ISE trust store. Following parameters are used in PUT request body

PARAMETER	DESCRIPTION	EXAMPLE	name *	required	Friendly name of the certificate (required)
"name"	"Trust Certificate"	status	Status of the certificate	"Enabled"	description
"description"	"Certificate for secure connection to cisco.com"	trustForIseAuth	Trust for authentication within Cisco ISE	false	trustForClientAuth
"trustForClientAuth"	Trust for authentication and Syslog	trustForCertificateBasedAdminAuth	Trust for certificate based Admin authentication	false	trustForCiscoServicesAuth
"trustForCiscoServicesAuth"	Trust for authentication of Cisco Services	enableOCSPValidation	Switch to enable or disable OSCP Validation	false	selectedOCSPService
"selectedOCSPService"	Name of selected OSCP Service	rejectIfNoStatusFromOCSP	Switch to reject certificate if there is no status from OSCP	false	rejectIfUnreachableFromOCSP
"rejectIfUnreachableFromOCSP"	Switch to reject certificate if unreachable from OSCP	downloadCRL	Switch to enable or disable download of CRL	false	crlDistributionUrl
"crlDistributionUrl"	Certificate Revocation List Distribution URL	automaticCRLUpdate	Switch to enable or disable automatic CRL update	false	automaticCRLUpdatePeriod
"automaticCRLUpdatePeriod"	Automatic CRL update period	automaticCRLUpdateUnits	Unit of time for automatic CRL update	"Minutes"	nonAutomaticCRLUpdatePeriod
"nonAutomaticCRLUpdatePeriod"	Non automatic CRL update period	nonAutomaticCRLUpdateUnits	Unit of time of non automatic CRL update	"Hours"	crlDownloadFailureRetries
"crlDownloadFailureRetries"	If CRL download fails, wait time before retry	crlDownloadFailureRetriesUnits	Unit of time before retry if CRL download fails	"Minutes"	enableServerIdentityCheck
"enableServerIdentityCheck"	Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL	authenticateBeforeCRLReceived	Switch to enable or disable CRL Verification if CRL is not Received	false	ignoreCRLEExpiration
"ignoreCRLEExpiration"	Switch to enable or disable ignore CRL Expiration	trustForIseAuth	Use "trustForIseAuth":true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	Client authentication and Syslog	trustForClientAuth
"trustForClientAuth"	true if the certificate is to be used for authentication of endpoints that contact Cisco ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: "trustForClientAuth" can be set true only if the "trustForIseAuth" has been set true.	trustForCertificateBasedAdminAuth	Use "trustForCertificateBasedAdminAuth":true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	Note: "trustForCertificateBasedAdminAuth" can be set true only if "trustForIseAuth" and "trustForClientAuth" are true.	trustForCiscoServicesAuth
"trustForCiscoServicesAuth"	true if the certificate is to be used for trusting external Cisco services, such as Feed Service.	enableOCSPValidation	Usage Validation against OSCP service	Use "enableOCSPValidation":true to validate the certificate against OSCP service mentioned in the field selectedOCSPService	selectedOCSPService
"selectedOCSPService"	Name of OSCP Service		Name of the OSCP service against which the certificate should be validated	Note: "selectedOCSPService" value is used if "enableOCSPValidation" has been set true.	

ject the request if OCSP returns UNKNOWN status Use “rejectIfNoStatusFromOCSP”:true to reject the certificate if the OCSP service returns UNKNOWN status Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OCSP Responder is unreachable Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OCSP service is unreachable. Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field `crlDistributionUrl` CRL distribution url Use “`crlDistributionUrl`” to specify the URL from where the CRL should be downloaded Note: “`crlDistributionUrl`” value is used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and `automaticCRLUpdatePeriod`, `automaticCRLUpdatePeriod` to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod”, `nonAutomaticCRLUpdateUnits` to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” to set retry time period if CRL download fails Note: “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable or disable CRL verification if CRL is not received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable or disable automatic CRL update, property of the request body.
- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable or disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable or disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.

- **ignore_crl_expiration** (*boolean*) – Switch to enable or disable ignore CRL expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.
- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocs_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘Disabled’ and ‘Enabled’.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within Cisco ISE, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities

class ClearThreatsAndVulnerabilities

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

Clear Threats and Vulnerabilities API allows the user to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.1	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	Yes	Resource UUID value	
macAd-dresses	String	Yes	One or more endpoint MAC addresses	["00:00:00:00:00:F2", "00:00:00:00:00:F3"]

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_threats_and_vulnerabilities*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

consumer**class Consumer**

Identity Services Engine Consumer API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](https://developer.cisco.com/site/license/cisco-sample-code-license/)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

create_account(*node_name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

AccountCreate.

Parameters

- **`node_name`** (*string*) – nodeName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_account*

activate_account(*description=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

access_secret(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccessSecret.

Parameters

- **peer_node_name** (*string*) – peerNodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules

class DeviceAdministrationAuthenticationRules

Identity Services Engine Device Administration - Authentication Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_authentication_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authentication rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rules`*


```
create_device_admin_authentication_rule(policy_id, identity_source_name=None,
                                         if_auth_fail=None, if_process_fail=None,
                                         if_user_not_found=None, link=None, rule=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

Device Admin Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None,  
        if_user_not_found=None, link=None, rule=None, headers=None, payload=None,  
        active_validation=True, **query_parameters)
```

Alias for *create_device_admin_authentication_rule*

```
reset_hit_counts_device_admin_authentication_rules(policy_id, headers=None,  
                                                    **query_parameters)
```

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)
```

Alias for *reset_hit_counts_device_admin_authentication_rules*

```
get_device_admin_authentication_rule_by_id(id, policy_id, headers=None, **query_parameters)
```

Device Admin Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for `get_device_admin_authentication_rule_by_id`

`update_device_admin_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update rule.

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_device_admin_authentication_rule_by_id`*

`delete_device_admin_authentication_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete rule.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`id`** (*basestring*) – `id` path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *`delete_device_admin_authentication_rule_by_id`*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_local_exception_rules*

create_device_admin_local_exception_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.

- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_local_exception_rule*

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_local_exceptions*

get_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_local_exception_rule_by_id*

update_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update local exception rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_local_exception_rule_by_id*

delete_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for `delete_device_admin_local_exception_rule_by_id`

device_administration_authorization_global_exception_rules**class DeviceAdministrationAuthorizationGlobalExceptionRules**

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_policy_set_global_exception_rules(headers=None, **query_parameters)`

Device Admin Get global execption rules.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_device_admin_policy_set_global_exception_rules*

create_device_admin_policy_set_global_exception(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Device Admin Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_global_exceptions*

get_device_admin_policy_set_global_exception_by_rule_id(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_by_rule_id*

update_device_admin_policy_set_global_exception_by_rule_id(*id*, *commands=None*, *link=None*,
profile=None, *rule=None*,
headers=None, *payload=None*,
active_validation=True,
***query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_global_exception_by_rule_id*

device_administration_authorization_rules

class DeviceAdministrationAuthorizationRules

Identity Services Engine Device Administration - Authorization Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for `get_device_admin_authorization_rules`

`create_device_admin_authorization_rule(policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` or dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authorization_rule*

reset_hit_counts_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

get_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authorization_rule_by_id*

update_device_admin_authorization_rule_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *`update_device_admin_authorization_rule_by_id`*

`delete_device_admin_authorization_rule_by_id(id, policy_id, headers=None, **query_parameters)`

Device Admin Delete authorization rule.

Parameters

- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`delete_device_admin_authorization_rule_by_id`*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_command_sets(*headers=None, **query_parameters*)

Device Admin Return list of command sets. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_conditions(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_device_admin_conditions`

`create_device_admin_condition(attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to exist-ing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner mem-bers of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

get_device_admin_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authorization_rules*

get_device_admin_condition_by_name(*name, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_condition_by_name*

update_device_admin_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers=None*, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_for_policy_sets`(*headers=None, **query_parameters*)Alias for *`get_device_admin_conditions_for_policy_sets`***`get_device_admin_condition_by_id`**(*id, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **`id (basestring)`** – id path parameter. Condition id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id, headers=None, **query_parameters*)Alias for *`get_device_admin_condition_by_id`***`update_device_admin_condition_by_id`**(*id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body

(list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_id*

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_device_admin_condition_by_id`

device_administration_dictionary_attributes_list**class DeviceAdministrationDictionaryAttributesList**

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_dictionaries_authentication(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authorization*

get_device_admin_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_policy_set*

device_administration_identity_stores

class DeviceAdministrationIdentityStores

Identity Services Engine Device Administration - Identity Stores API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_device_admin_identity_stores(*headers=None, **query_parameters*)

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_identity_stores*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_network_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_network_conditions*

create_device_admin_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.

- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_network_condition_by_id*

update_device_admin_network_condition_by_id(*id*, *condition_type=None*, *conditions=None*,
description=None, *link=None*, *name=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are ‘DeviceCondition’, ‘DevicePortCondition’ and ‘EndstationCondition’.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set

class DeviceAdministrationPolicySet

Identity Services Engine Device Administration - Policy Set API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_sets(*headers=None*, ***query_parameters*)

Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_device_admin_policy_sets***create_device_admin_policy_set**(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` , or, dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'disabled', 'enabled' and 'monitor'.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_policy_sets*

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_by_id*

update_device_admin_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.

- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_by_id*

device_administration_profiles

class DeviceAdministrationProfiles

Identity Services Engine Device Administration - Profiles API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

get_device_admin_profiles(*headers=None*, ***query_parameters*)

Device Admin Returns list of shell profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers (*dict*)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_profiles*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_service_names*

device_administration_time_date_conditions

class DeviceAdministrationTimeDateConditions

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_time_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_time_conditions*

create_device_admin_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.

- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
        dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
        dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
        is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_device_admin_time_condition*

```
get_device_admin_time_condition_by_id(id, headers=None, **query_parameters)
```

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_time_condition_by_id*

update_device_admin_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_device_admin_time_condition_by_id](#)

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [delete_device_admin_time_condition_by_id](#)

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.1_Patch_1).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

Downloadable ACL API allows the client to add, delete, update, search and perform actions on downloadable ACL.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute IP version in 2.6	daclType	Added Enum Attribute 'daclType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]		multiline_acl
id	String	Yes	Resource UUID		c1e0e9e0-717f-11eb-9fb2-b6cb23d38630
description	String	No	Use the string n for a newline		description
dacl	String	Yes	The DACL Content. Use the string n for a newline		permit ip any any
daclType	Enum	No	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	

get_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a downloadable ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_downloadable_acl_by_id*

update_downloadable_acl_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string *n* for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string *n* for a newline, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [*_*.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_downloadable_acl_by_id*](#)

delete_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a downloadable ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_downloadable_acl_by_id*](#)

get_downloadable_acl(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl***get_downloadable_acl_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_downloadable_acl_generator***create_downloadable_acl**(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string `\n` for a newline, property of the request body.

- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string `n` for a newline, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [`_.-`], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell**class EgressMatrixCell**

Identity Services Engine EgressMatrixCell API (version: 3.1_Patch_1).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

Egress Policy Matrix Cell API allows the client to add, update, delete and search egress matrix cells among other operations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version
1	1.1	2.3	Introducing bulk operations

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		ANY-ANY
id	String	No	Resource UUID, mandatory for update		f92c1a900-8c01-11e6-996c-525400b48521
description	String	No			Default egress rule
default-Rule	Enum	Yes	Allowed values: NONE, DENY_IP, PERMIT_IP	NONE	PERMIT_IP
destinationSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521
matrix-CellStatus	Enum	Yes	Allowed values: DISABLED, ENABLED, MONITOR	DISABLED	ENABLED
sgACLs	List	Yes			[“92951ac0-8c01-11e6-996c-525400b48521”]
sourceSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*headers=None, **query_parameters*)

Alias for *clear_all_matrix_cells*

set_all_cells_status(*status, headers=None, **query_parameters*)

This API allows the client to set status of all the egress matrix cells.

Parameters

- **status** (*basestring*) – status path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_status(*status*, *headers=None*, ***query_parameters*)

Alias for *set_all_cells_status*

clone_matrix_cell(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

This API allows the client to clone an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **src_sgt_id** (*basestring*) – srcSgtId path parameter.
- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_egress_matrix_cell_by_id`***`update_egress_matrix_cell_by_id(id, default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update an egress matrix cell.

Parameters

- **`default_rule`** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`destination_sgt_id`** (*string*) – destinationSgtId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`matrix_cell_status`** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgacIs`** (*list*) – sgacIs, property of the request body (list of strings).
- **`source_sgt_id`** (*string*) – sourceSgtId, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*,
matrix_cell_status=None, *name=None*, *sgacIs=None*, *source_sgt_id=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_egress_matrix_cell_by_id*

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-
Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell_generator*

create_egress_matrix_cell(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacIs** (*list*) – sgacIs, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_egress_matrix_cell*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.1_Patch_1).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

Endpoint Certificate API allows the client to create endpoint certificates signed by the Cisco ISE Internal CA. This API can takes in certificate request details, create a RSA key pair, create a certificate and return the resulting key pair and certificate as a ZIP file. ZIP files are returned as an octet stream.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
certTemplateName	String	Yes	Name of an Internal CA template	Certificate_Template_Name
format	Enum	Yes	Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN	PKCS8
password	String	Yes	Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#	Password_123
certificateRequest	Map	Yes	Key value map. Must have CN and SAN entries	
• CN	String	Yes	Matches the requester's User Name, unless the Requester is an ERS Admin. ERS Admins are allowed to create requests for any CN	userName [or] machineName
• SAN	String	Yes	Valid MAC Address, delimited by '-'	11-22-33-44-55-66

```
create_endpoint_certificate(cert_template_name=None, certificate_request=None, format=None,
                           password=None, dirpath=None, save_file=None, filename=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to create an endpoint certificate.

Parameters

- **cert_template_name** (*string*) – Name of an Internal CA template, property of the request body.
- **certificate_request** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.

- **format** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **password** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
create(cert_template_name=None, certificate_request=None, format=None, password=None,
        dirpath=None, save_file=None, filename=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_endpoint_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group**class EndpointIdentityGroup**

Identity Services Engine EndpointIdentityGroup API (version: 3.1_Patch_1).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

Endpoint Identity Groups API allows the client to add, delete, update, and search endpoint groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.4	Added GetByName operation		

Resource Definition

Attribute	Type	Re-quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		Cisco-Meraki-Devicee
id	String	No	Resource UUID, mandatory for update		1e2700a0-8c00-11e6-996c-525400b48521
description	String	No			Identity Group for Profile: Cisco-Meraki-Device
systemDefined	Boolean	Yes		false	true

get_endpoint_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_id*

update_endpoint_group_by_id(*id*, *description=None*, *name=None*, *system_defined=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_endpoint_group_by_id*

delete_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_group_by_id*

get_endpoint_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups*

get_endpoint_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups_generator*

create_endpoint_group(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

external_radius_server**class ExternalRadiusServer**

Identity Services Engine ExternalRADIUSServer API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

External RADIUS Server API allows the client to add, delete, update, search and perform actions on external RADIUS server.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Allowed characters are alphanumeric and _ (underscore).		externalRadiusServer1
id	String	No	Resource UUID, mandatory for update		da095377-dce8-486e-933a-6ea788bbf51a
description	String	No			example external radius server
hostIP	String	Yes	The IP of the host - must be a valid IPV4 address		1.1.1.1
sharedSecret	String	Yes	Shared secret maximum length is 128 characters		sharedSecret
enableKeyWrap	Boolean	Yes	KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices		true
encryptionKey	String	No	The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		1616161616161616
authenticatorKey	String	No	The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		2020202020202020
keyInputFormat	Enum	Yes	Specifies the format of the input for fields 'encryptionKey' and 'authenticatorKey'. Allowed Values: ASCII, HEXADECIMAL		ASCII
authenticationPort	Integer	Yes	Valid Range 1 to 65535		1812
accountingPort	Integer	Yes	Valid Range 1 to 65535		1813
time-out	Integer	Yes	Valid Range 1 to 120		5
re-tries	Integer	Yes	Valid Range 1 to 9		3
proxy-Time-out	Integer	No	Valid Range 1 to 600	300	

get_external_radius_server_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for `get_external_radius_server_by_id`

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed charactera are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_external_radius_server_by_id*

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_external_radius_server_by_id*

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server*

get_external_radius_server_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

create_external_radius_server(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECEIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECEIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.

- **key_input_format** (*string*) – Specifies the format of the input for fields ‘encryption-Key’ and ‘authenticatorKey’. Allowed Values: ASCII HEXADECEIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(accounting_port=None, authentication_port=None, authenticator_key=None, description=None,
enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None,
name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None,
headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_external_radius_server*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

filter_policy**class FilterPolicy**

Identity Services Engine FilterPolicy API (version: 3.1_Patch_1).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

Filter Policy API allows clients to add, get, update and delete SXP domain filter policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
subnet	String	No	Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined	subnetAddress
sgt	String	No	SGT name or ID. At least one of subnet or sgt or vn should be defined	sgt
vn	String	No	Virtual Network. At least one of subnet or sgt or vn should be defined	virtual-Network
domains	String	Yes	List of SXP Domains, separated with comma	Sxp Vpn Name

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.

- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_filter_policy_by_id`***`get_filter_policy(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_filter_policy`***`get_filter_policy_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_filter_policy_generator*

create_filter_policy(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_filter_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.1_Patch_1).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

Guest Location API allows the client to search the locations configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	9f083530-8c01-11e6-996c-525400b48521
descrip-tion	String	No		

get_guest_location_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location*

get_guest_location_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration**class GuestSmtpNotificationConfiguration**

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.1_Patch_1).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

Guest SMTP notification configuration API is a global setting for enabling email notifications within guest application. These APIs allow to create, update and retrieve the notification settings. The create API may not be required to be used as of Cisco ISE Release 2.2 because the single SMTP notification configuration is the only one used and it always gets created during the Cisco ISE application initialization period.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for update		9ecb5340-8c01-11e6-996c-525400b48521
description	String	No			
defaultFromAddress	String	No	The default from email address to be used to send emails from	donotreply@example.com	
notificationEnabled	Boolean	No	Indicates if the email notification service is to be enabled	true	
smtpServer	String	No	The SMTP server ip address or fqdn such as outbound.mycompany.com		
useDefaultFromAddress	Boolean	No	If the default from address should be used rather than using a sponsor user email address	false	
smtpPort	String	No	Port at which SMTP Secure Server is listening	25	
connectionTimeout	String	No	Interval in seconds for all the SMTP client connections	60	
useTLSorSSLEncryption	Boolean	No	If configured to true, SMTP server authentication will happen using TLS/SSL	false	
usePasswordAuthentication	Boolean	No	If configured to true, SMTP server authentication will happen using username/password	false	
userName	String	No	Username of Secure SMTP server		
password	String	No	Password of Secure SMTP server		

get_guest_smtp_notification_settings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_guest_smtp_notification_settings_by_id`***`update_guest_smtp_notification_settings_by_id(id, connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a SMTP configuration setting.

Parameters

- **`connection_timeout (string)`** – Interval in seconds for all the SMTP client connections, property of the request body.
- **`default_from_address (string)`** – The default from email address to be used to send emails from, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`notification_enabled (boolean)`** – Indicates if the email notification service is to be enabled, property of the request body.
- **`password (string)`** – Password of Secure SMTP server, property of the request body.
- **`smtp_port (string)`** – Port at which SMTP Secure Server is listening, property of the request body.
- **`smtp_server (string)`** – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **`use_default_from_address (boolean)`** – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **`use_password_authentication (boolean)`** – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **`use_tlsor_ssl_encryption (boolean)`** – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.

- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlscrl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

get_guest_smtp_notification_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings*

get_guest_smtp_notification_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings_generator*

create_guest_smtp_notification_settings(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.

- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlsor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(connection_timeout=None, default_from_address=None, notification_enabled=None,  
        password=None, smtp_port=None, smtp_server=None, use_default_from_address=None,  
        use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None,  
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_guest_smtp_notification_settings*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_ssid

class GuestSsid

Identity Services Engine GuestSSID API (version: 3.1_Patch_1).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

Guest SSIDs are global objects that are referenced by Cisco ISE sponsor portals. Guest SSID API allows the client to add, delete, update and search guest SSID among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]	ssid_value
id	String	No	Resource UUID, mandatory for update	9132eedc-7910-4ffe-805e-3d3a366f7fb7
description	String	No		

get_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_ssid_by_id*

update_guest_ssid_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest SSID by ID.

Parameters

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_ssid_by_id*

get_guest_ssid(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid*

get_guest_ssid_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid_generator*

create_guest_ssid(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_ssid*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_type**class GuestType**

Identity Services Engine GuestType API (version: 3.1_Patch_1).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

Guest Type API allows the client to add, delete, update and search guest types.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Contractor (default)
id	String	No	Resource UUID, mandatory for update		9f03a151-8c01-11e6-996c-525400b48521
description	String	No			Default settings allow network access for up to a year.
accessTime	List	No			
<ul style="list-style-type: none"> allowAccessOn-Specific-DaysTimes 	Boolean	No	Enable Specific Day Time Limits	false	
<ul style="list-style-type: none"> default-Duration 	Integer	No		90	
<ul style="list-style-type: none"> durationTime-Unit 	Enum	No	Allowed values are: - DAYS, - HOURS, - MINUTES	DAYS	
<ul style="list-style-type: none"> from-FirstLogin 	Boolean	No	When Account Duration starts from first login or specified date	false	
<ul style="list-style-type: none"> maxAccountDuration 	Integer	No	Maximum value of Account Duration	365	
<ul style="list-style-type: none"> dayTime-Limits 	List	No	List of Time Ranges for account access		
<ul style="list-style-type: none"> dayTime-Limit 	List	No	Time Ranges for account access		
<ul style="list-style-type: none"> startTime 	String	No	Start time in HH:mm format	09:00	
<ul style="list-style-type: none"> endTime 	String	No	End time in HH:mm format	17:00	
<ul style="list-style-type: none"> days 	List	No	List of Days		
1732				Chapter 1.	The User Guide
	<ul style="list-style-type: none"> day 	Enum	No	Value should be one of Week day. Allowed	

update_guest_type_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`update_sms(id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *update_guest_type_sms*

`get_guest_type_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest type by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *get_guest_type_by_id*

```
update_guest_type_by_id(id, access_time=None, description=None, expiration_notification=None,
                        is_default_type=None, login_options=None, name=None,
                        sponsor_groups=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, access_time=None, description=None, expiration_notification=None,
             is_default_type=None, login_options=None, name=None, sponsor_groups=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_type_by_id*

get_guest_type(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*

create_guest_type(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_type*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_user

class GuestUser

Identity Services Engine GuestUser API (version: 3.1_Patch_1).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

Guest User API allows the client to add, delete, update and search guest users among other operations which are available from the sponsor portal. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only ‘create’ bulk operation. However, all other operation which are bulk supported can be used in the same way.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		guestUser
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			ERS Example user
customFields	Map	No	Key value map		“some key” : “some value”
guestType	String	No			Contractor
status	String	No			
reasonForVisit	String	No			
personBeingVisited	String	No			
sponsorUserName	String	No			Mr Spons
sponsorUserId	String	No			
statusReason	String	No			
portalId	String	No			23423432523

continues on next page

Table 35 – continued from previous page

guestAccess-Info	List	No			
• valid-Days	Integer	Yes	Number of days guest user is valid. To validate validDays property, Cisco ISE considers only date (not time) between fromDate and toDate properties		90
• fromDate	String	No			07/29/2014 14:44
• toDate	String	No			10/29/2014 17:30
• location	String	No			San Jose
• ssid	String	No			
• groupTag	String	No			
GuestInfo	List	Yes			
• emailAddress	String	No			email@some.uri.com
• enabled	Boolean	Yes	This field is only for Get operation not applicable for Create, Update operations	false	
• password	String	Yes			asdlkj324ew
• phoneNum-ber	String	No	Phone number should be E.164 format		+13211239034
• smsService-Provider	String	No			Global Default

continues on next page

Table 35 – continued from previous page

• user-Name	String	No	If account needs be created with mobile number, please provide mobile number here		DS3ewdsa34wWE
• firstName	String	No			
• lastName	String	No			
• company	String	No			
• creation-Time	String	No			
• notificationLanguage	String	No			

approve_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to approve a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

approve_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *approve_guest_user_by_id*

change_sponsor_password(*portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to change the sponsor password.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to suspend a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`suspend_guest_user_by_name`***`reinstate_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`reinstate_guest_user_by_name`***`get_guest_user_by_name`**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_name*

`update_guest_user_by_name`(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by name.

Parameters

- **`custom_fields`** (*object*) – Key value map, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`guest_access_info`** (*object*) – guestAccessInfo, property of the request body.
- **`guest_info`** (*object*) – guestInfo, property of the request body.
- **`guest_type`** (*string*) – guestType, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*basestring*) – name, property of the request body.
- **`portal_id`** (*string*) – portalId, property of the request body.
- **`reason_for_visit`** (*string*) – reasonForVisit, property of the request body.
- **`sponsor_user_id`** (*string*) – sponsorUserId, property of the request body.
- **`sponsor_user_name`** (*string*) – sponsorUserName, property of the request body.
- **`status`** (*string*) – status, property of the request body.
- **`status_reason`** (*string*) – statusReason, property of the request body.
- **`name`** – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_name*

delete_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_name*

reset_guest_user_password_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reinstate_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *reinstate_guest_user_by_id***update_guest_user_email**(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user email by ID.

Parameters

- **additional_data** (*list*) – *additionalData*, property of the request body (list of objects).
- **id** (*basestring*) – *id* path parameter.
- **portal_id** (*basestring*) – *portalId* path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)Alias for *update_guest_user_email*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

Alias for *update_guest_user_sms*

deny_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deny a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deny_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deny_guest_user_by_id*

get_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.

- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_id*

delete_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_id*

get_guest_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users*

get_guest_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users_generator*

create_guest_user(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_user*

suspend_guest_user_by_id(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to suspend a guest user by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_by_id`(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

Alias for *suspend_guest_user_by_id*

`get_version`(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the guest user.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_guest_user`(*operation_type=None*, *resource_media_type=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – operationType, property of the request body.
- **`resource_media_type`** (*string*) – resourceMediaType, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_guest_user*

monitor_bulk_status_guest_user(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_guest_user*

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

Hotspot Guest Portal API provides the ability to create, read, update, delete and search hotspot guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Hotspot Guest Portal (default)	
id	String	No	Resource UUID, mandatory for update	b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	
description	String	No	Guests do not require username and password credentials to access the network, but you can optionally require an access code		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	

continues on next page

Table 36 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	HOTSPOTGUEST	
settings	List	No	Defines all of the settings groups available for a BYOD		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal	aa178bd0-8bff-11e6-996c-525400b48521	

continues on next page

Table 36 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• coaType	Enum	No	Allowed Values: COAREAU-THENTICATE, COATER-MINATE	COAREAU-THENTICATE	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• requireAccessCode	Boolean	No	Require the portal user to enter an access code. Only used in Hotspot portal	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 36 – continued from previous page

• require-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• authSuccessSettings	List	No			
• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUCCESSPAGE, ORIGINATINGURL, URL	AUTHSUCCESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		

continues on next page

Table 36 – continued from previous page

• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		
• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 36 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	
• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		

continues on next page

Table 36 – continued from previous page

• page-Back-ground-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	BYOD Portal		
• contact-Text	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			

continues on next page

Table 36 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_hotspot_portal`

```
get_hotspot_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                              sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the hotspot portals. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

create_hotspot_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_hotspot_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMapping API (version: 3.1_Patch_1).

Wraps the Identity Services Engine IPToSGTMapping API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping API allows the client to add, delete, update, search and deploy IP to SGT mapping.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	server1.cisco.com
id	String	No	Resource UUID, mandatory for update	
description	String	No		
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL		network_device_id
deployType	Enum	Yes	Allowed values: ALL, ND, NDG	ND
hostName	String	Mandatory if hostIp is empty		server1.cisco.com
sgt	String	Mandatory unless mappingGroup is set		sgt_id
hostIp	String	Mandatory if hostName is empty – valid IPL		
mappingGroup	String	Mandatory unless sgt and deployTo and deployType are set		

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all(*headers=None, **query_parameters*)

Alias for *deploy_all_ip_to_sgt_mapping*

get_deploy_status_ip_to_sgt_mapping(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status(*headers=None, **query_parameters*)

Alias for *get_deploy_status_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id, deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless *mappingGroup* is set or unless *deployType=ALL*, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if *hostName* is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if *hostIp* is empty, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless *sgt* and *deployTo* and *deployType* are set, property of the request body.
- **name** (*string*) – name, property of the request body.

- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_by_id*

delete_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_ip_to_sgt_mapping_by_id***get_ip_to_sgt_mapping**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_generator`*

`create_ip_to_sgt_mapping`(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **`deploy_to`** (*string*) – Mandatory unless `mappingGroup` is set or unless `deployType=ALL`, property of the request body.
- **`deploy_type`** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **`host_ip`** (*string*) – Mandatory if `hostName` is empty -valid IP, property of the request body.
- **`host_name`** (*string*) – Mandatory if `hostIp` is empty, property of the request body.
- **`mapping_group`** (*string*) – Mapping Group Id. Mandatory unless `sgt` and `deployTo` and `deployType` are set, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt`** (*string*) – Mandatory unless `mappingGroup` is set, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping*

monitor_bulk_status_ip_to_sgt_mapping(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group

class IpToSgtMappingGroup

Identity Services Engine IPToSGTMappingGroup API (version: 3.1_Patch_1).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping Group API allows the client to add, delete, update, search and deploy IP to SGT mapping groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		groupA
id	String	No	Resource UUID, mandatory for update		
description	String	No			
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL			net-work_device_id
deploy-Type	Enum	Yes	Allowed values: ALL, ND, NDG	ALL	
sgt	String	Mandatory unless mappingGroup is set			sgt_id

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_ip_to_sgt_mapping_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_ip_to_sgt_mapping_group_by_id`*

`update_ip_to_sgt_mapping_group_by_id(id, deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_ip_to_sgt_mapping_group_by_id`*

`get_ip_to_sgt_mapping_group`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_group`*

`get_ip_to_sgt_mapping_group_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_generator*

create_ip_to_sgt_mapping_group(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping_group*

monitor_bulk_status_ip_to_sgt_mapping_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **`bulkid`** (*basestring*) – bulkid path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.1_Patch_1).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

Identity Groups API allows the client to search identity groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added Create and GetByName operations

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	GuestType_Weekly (default)
id	String	No	Resource UUID, mandatory for update	9efe2310-8c01-11e6-996c-525400b48521
descrip-tion	String	No		Identity group mirroring the guest type
parent	String	Yes		NAC Group:NAC:IdentityGroups:User Identity Groups

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_name***get_identity_group_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_identity_group_by_id***update_identity_group_by_id**(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

get_identity_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups*

get_identity_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

create_identity_group(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to identity group.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.1_Patch_1).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

Identity Sequence API allows the client to add, delete, update and search Identity sequences.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	All_User_ID_Stores
id	String	No	Resource UUID, mandatory for update	93246270-8c01-11e6-996c-525400b48521
description	String	No		A built-in Identity Sequence to include all User Identity Stores
breakOn-StoreFail	Boolean	Yes	Do not access other stores in the sequence If a selected identity store cannot be accessed for authentication	false
certificateAuthenticationProfile	String	Yes	Certificate Authentication Profile, empty if doesn't exist	Preloaded_Certificate_Profile
idSeqItem	List	Yes	List of id stores comprised of id store name and order	[{ "idstore": "Internal Users", "order": 1 }, { "idstore": "All_AD_Join_Points", "order": 2 }, { "idstore": "Guest Users", "order": 3 }]

get_identity_sequence_by_name(name, headers=None, **query_parameters)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

get_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

update_identity_sequence_by_id(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

delete_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_identity_sequence_by_id*

get_identity_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence*

get_identity_sequence_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.

- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

internal_user**class InternalUser**

Identity Services Engine InternalUser API (version: 3.1_Patch_1).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

Internal User API allows the client to add, delete, update and search internal users.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		b24b09e2-16f8-4e48-ace1-2c262a9449f1
description	String	No			description
changePassword	Boolean	Yes		true	
email	String	No			email@domain.com
enablePassword	String	No	EnablePassword field is added in ISE 2.0 to support T+		enablePassword
enabled	Boolean	Yes	Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled'		true
custom-Attributes	String	No	Key value map		{ "key1" : "value1" }
firstName	String	No			firstName
identity-Groups	String	No	CSV of identity group IDs		identity-Groups
lastName	String	No			lastName
password	String	No			password
passwordID-Store	String	Yes	The id store where the internal user's password is kept	Internal Users	
expiry-DateEnabled	Boolean	No		false	
expiry-Date	String	No	To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD'		2021-05-19

get_internal_user_by_name(name, headers=None, **query_parameters)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_name*

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.

- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_name*

delete_internal_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_name*

get_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_id*

```
update_internal_user_by_id(id, change_password=None, custom_attributes=None, description=None,
                           email=None, enable_password=None, enabled=None, expiry_date=None,
                           expiry_date_enabled=None, first_name=None, identity_groups=None,
                           last_name=None, name=None, password=None, password_idstore=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be ‘Enabled’ or ‘Disabled’. The values are case sensitive. For example, ‘[ERSObjectURL]?filter=enabled.EQ.Enabled’, property of the request body.
- **expiry_date** (*string*) – To store the internal user’s expiry date information. It’s format is = ‘YYYY-MM-DD’, property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_id*

get_internal_user(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user*

get_internal_user_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(change_password=None, custom_attributes=None, description=None, email=None,
        enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
        first_name=None, identity_groups=None, last_name=None, name=None, password=None,
        password_idstore=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for `create_internal_user`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the internal user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

licensing

class Licensing

Identity Services Engine Licensing API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Licensing API and exposes the API as native Python methods that return native Python objects.

```
get_connection_type(headers=None, **query_parameters)
```

Get connection type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_eval_license_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_feature_to_tier_mapping(headers=None, **query_parameters)`

Get feature to tier mapping.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_registration_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create_registration_info(connection_type=None, registration_type=None, ssm_on_prem_server=None, tier=None, token=None, headers=None, payload=None, active_validation=True, **query_parameters)`

License Configure registration information.

Parameters

- **`connection_type (string)`** – `connectionType`, property of the request body. Available values are 'HTTP_DIRECT', 'PROXY', 'SSM_ONPREM_SERVER' and 'TRANSPORT_GATEWAY'.
- **`registration_type (string)`** – `registrationType`, property of the request body. Available values are 'DEREGISTER', 'REGISTER', 'RENEW' and 'UPDATE'.

- **ssm_on_prem_server** (*string*) – If connection type is selected as SSM_ONPREM_SERVER, then IP address or the hostname (or FQDN) of the SSM On-Prem server Host., property of the request body.
- **tier** (*list*) – tier, property of the request body (list of strings. Available values are ‘ADVANTAGE’, ‘DEVICEADMIN’, ‘ESSENTIAL’, ‘PREMIER’ and ‘VM’).
- **token** (*string*) – token, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_smart_state(*headers=None, **query_parameters*)

Get smart license information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

configure_smart_state(headers=None, **query_parameters)

License Configure smart state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_tier_state_info(headers=None, **query_parameters)

Get tier state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_tier_state_info(*headers=None, payload=None, active_validation=True, **query_parameters*)

Applicable values for name & status parameters: name: ESSENTIAL, ADVANTAGE, PREMIER, DE-VICEADMIN status: ENABLED, DISABLED .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

mdm**class Mdm**

Identity Services Engine MDM API (version: 3.1_Patch_1).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id, name, portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pmg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_endpoints(*headers=None, **query_parameters*)

getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)

getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)

getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)

getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc**class Misc**

Identity Services Engine Misc API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 MNT REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_mnt*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_active_count (*headers=None*, ***query_parameters*)

ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_list(*headers=None, **query_parameters*)

ActiveList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_auth_list(*headers=None, **query_parameters*)

Session/AuthList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_posture_count(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_count(*headers=None, **query_parameters*)

ProfilerCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac*, *headers=None*, ***query_parameters*)

Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_sessions_by_session_id(session_id, headers=None, **query_parameters)`

Sessions by SessionID.

Parameters

- **`session_id`** (*basestring*) – `session_id` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_all_sessions(headers=None, **query_parameters)`

Delete All Sessions.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_mnt_version(headers=None, **query_parameters)`

MNT Version.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_failure_reasons(headers=None, **query_parameters)`

FailureReasons.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_authentication_status_by_mac`(*mac, records, seconds, headers=None, **query_parameters*)

AuthenticationStatus by MAC.

Parameters

- **`mac`** (*basestring*) – MAC path parameter.
- **`seconds`** (*basestring*) – SECONDS path parameter.
- **`records`** (*basestring*) – RECORDS path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`session_reauthentication_by_mac`(*endpoint_mac, psn_name, reauth_type, headers=None, **query_parameters*)

Session Reauthentication by MAC.

Parameters

- **`psn_name`** (*basestring*) – PSN_NAME path parameter.
- **`endpoint_mac`** (*basestring*) – ENDPOINT_MAC path parameter.

- **reauth_type** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_disconnect (*disconnect_type, endpoint_ip, mac, nas_ipv4, psn_name, headers=None, **query_parameters*)

Session Disconnect.

Parameters

- **endpoint_ip** (*basestring*) – ENDPOINT_IP path parameter.
- **psn_name** (*basestring*) – PSN_NAME path parameter.
- **mac** (*basestring*) – MAC path parameter.
- **disconnect_type** (*basestring*) – DISCONNECT_TYPE path parameter.
- **nas_ipv4** (*basestring*) – NAS_IPV4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_account_status_by_mac(*duration*, *mac*, *headers=None*, ***query_parameters*)

AccountStatus by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **duration** (*basestring*) – duration path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

My Device Portal API provides the ability to create, read, update, delete and search my device portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		My Devices Portal (default)
id	String	No	Resource UUID, mandatory for update		901f1b37-4a2f-46d9-8653-d925d2dde3aa
description	String	No			Default portal used by employees to register and manage their personal devices
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/mydevicesportal/PortalSetup
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	MYDEVICE	
settings	List	No	Defines all of the settings groups available for a Mydevice portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		

continues on next page

Table 37 – continued from previous page

• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal		aa178bd0-8bff-11e6-996c-525400b48521
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 37 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No		2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK - ONPAGE, - ASLINK	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	

continues on next page

Table 37 – continued from previous page

• aupSet- tings	List	No	Configuration of the Accept- able Use Policy (AUP) for a portal		
• dis- playFre- quency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• in- cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• require- Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAc- ceptance = true	false	
• dis- playFre- quency- Interval- Days	Integer	No	Number of days between AUP confir- mations (when displayFre- quency = recurring)	7	
• employ- eeChangePass- wordSet- tings	List	No			
• allowEm- ployee- ToChangePwd	Boolean	No	Allow employ- ees to change their own pass- words	false	
• post- Login- Banner- Settings	List	No			

continues on next page

Table 37 – continued from previous page

• include-PostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• support-InfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE

continues on next page

Table 37 – continued from previous page

• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		

continues on next page

Table 37 – continued from previous page

• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			My Devices Portal
• contact-Text	String	No			Contact Support

continues on next page

Table 37 – continued from previous page

• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		

continues on next page

Table 37 – continued from previous page

• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_my_device_portal_by_id*

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_my_device_portal_by_id`*

`get_my_device_portal`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal*

`get_my_device_portal_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_my_device_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

native_suppliant_profile

class NativeSuppliantProfile

Identity Services Engine NativeSuppliantProfile API (version: 3.1_Patch_1).

Wraps the Identity Services Engine NativeSuppliantProfile API and exposes the API as native Python methods that return native Python objects.

Native suppliant profile API provides the ability to update, delete and search native suppliant profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Cisco-ISE-NSP
id	String	No	Resource UUID, mandatory for update	b8ce01e6-b150-4d4e-9698-40e48d5e0197
description	String	No		Pre-configured Native Supplicant Profile. The SSID Will Need To Be Customized For Your Environment
wirelessProfiles	List	Yes	List of Wireless profiles	
• ssid	String	Yes	SSID for the wireless profile	ISE
• allowedProtocol	Enum	Yes	Allowed protocol for the wireless profile.	TLS
• certificateTemplateId	String	No	Certificate template ID	0ca8f1b6-500d-560b-e053-75189a0ab0d1
• actionType	Enum	Yes	Action type for WifiProfile.	UPDATE
• previousSsid	String	Yes	Previous ssid for WifiProfile (required for updating existing WirelessProfile)	ssid1

get_native_supplicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a native supplicant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_native_suppllicant_profile_by_id`***`update_native_suppllicant_profile_by_id(id, description=None, name=None, wireless_profiles=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a native suppllicant profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`wireless_profiles`** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_native_suppllicant_profile_by_id*

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native supplicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_native_suppllicant_profile_by_id*

get_native_suppllicant_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the native supplicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

`get_native_suppllicant_profile_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type*Generator***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native suppllicant profile.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rules*

create_network_access_authentication_rule(*policy_id*, *identity_source_name=None*,
if_auth_fail=None, *if_process_fail=None*,
if_user_not_found=None, *link=None*, *rule=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`get_network_access_authentication_rule_by_id`*

`update_network_access_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update rule.

Parameters

- **`identity_source_name(string)`** – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail(string)`** – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail(string)`** – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found(string)`** – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link(object)`** – link, property of the request body.
- **`rule(object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id(basestring)`** – policyId path parameter. Policy id.
- **`id(basestring)`** – id path parameter. Rule id.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

`delete_network_access_authentication_rule_by_id`(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete rule.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_authentication_rule_by_id*

network_access_authorization_exception_rules

class NetworkAccessAuthorizationExceptionRules

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_local_exception_rules(*policy_id, headers=None, **query_parameters*)

Network Access Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id, headers=None, **query_parameters*)

Alias for *get_network_access_local_exception_rules*

create_network_access_local_exception_rule(*policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.

- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_local_exception_rule*

reset_hit_counts_network_access_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_network_access_local_exceptions`***`get_network_access_local_exception_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Network Access Get local exception rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_network_access_local_exception_rule_by_id`***`update_network_access_local_exception_rule_by_id(id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_set_global_exception_rules(*headers=None, **query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for `get_network_access_policy_set_global_exception_rules`

`create_network_access_policy_set_global_exception_rule(link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rule_by_id*

update_network_access_policy_set_global_exception_rule_by_id(*id*, *link=None*, *profile=None*,
rule=None,
security_group=None,
headers=None,
payload=None,
active_validation=True,
***query_parameters*)

Network Access Update global exception authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

delete_network_access_policy_set_global_exception_rule_by_id(*id*, *headers=None*,
***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_global_exception_rule_by_id*

network_access_authorization_rules

class NetworkAccessAuthorizationRules

Identity Services Engine Network Access - Authorization Rules API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rules*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

`reset_hit_counts_network_access_authorization_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – `policyId` path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authorization_rules*

get_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rule_by_id*

update_network_access_authorization_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

delete_network_access_authorization_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authorization_rule_by_id*

network_access_conditions

class NetworkAccessConditions

Identity Services Engine Network Access - Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_conditions(*headers=None*, ***query_parameters*)

Network Access Returns all library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions*

create_network_access_condition(*attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model `LibraryConditionAttributes` , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: `LibraryConditionAndBlock` or `LibraryConditionOrBlock` . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: `ConditionAttributes` , `ConditionAndBlock` , `ConditionOrBlock` , that represent dynamically built Conditions which are not stored in the conditions Library, or using `ConditionReference` , which includes an ID to existing stored condition in the library. The `LibraryCondition` models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (`ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock`), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using `ConditionReference` model in inner layers, the condition name is not required. `ConditionReference` objects can also include a reference ID to a condition of type `TimeAndDate`

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘`ConditionAndBlock`’, ‘`ConditionAttributes`’, ‘`ConditionOrBlock`’, ‘`ConditionReference`’, ‘`LibraryConditionAndBlock`’, ‘`LibraryConditionAttributes`’, ‘`LibraryConditionOrBlock`’ and ‘`TimeAndDateCondition`’.
- **dates_range** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a `TimeAndDate` condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.

- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
      dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
      dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
      is_negate=None, link=None, name=None, operator=None, week_days=None,
      week_days_exception=None, headers=None, payload=None, active_validation=True,
      **query_parameters)
```

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_condition_by_name*

update_network_access_condition_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_name*

delete_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_name*

get_network_access_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None*, ***query_parameters*)

Alias for *get_network_access_conditions_for_policy_sets*

get_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_network_access_condition_by_id*

update_network_access_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.

- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_id*

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_id*

network_access_dictionary

class NetworkAccessDictionary

Identity Services Engine Network Access - Dictionary API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries(*headers=None*, ***query_parameters*)

Get all Dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries*

create_network_access_dictionaries(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_dictionaries*

get_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

GET a dictionary by name.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_network_access_dictionary_by_name*

update_network_access_dictionary_by_name(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_by_name*

delete_network_access_dictionary_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_access_dictionary_by_name`*

network_access_dictionary_attribute**class NetworkAccessDictionaryAttribute**

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

`get_network_access_dictionary_attributes_by_dictionary_name`(*dictionary_name*,
headers=None,
***query_parameters*)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **`dictionary_name`** (*basestring*) – `dictionaryName` path parameter. the name of the dictionary the dictionary attribute belongs to.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

create_network_access_dictionary_attribute(*dictionary_name*, *allowed_values=None*,
data_type=None, *description=None*,
direction_type=None, *id=None*, *internal_name=None*,
name=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute's name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

```
update_network_access_dictionary_attribute_by_name(dictionary_name, name,
                                                    allowed_values=None, data_type=None,
                                                    description=None, direction_type=None,
                                                    id=None, internal_name=None,
                                                    headers=None, payload=None,
                                                    active_validation=True,
                                                    **query_parameters)
```

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.
- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_attribute_by_name*

network_access_dictionary_attributes_list

class NetworkAccessDictionaryAttributesList

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries_authentication(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authentication*

get_network_access_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_authorization***get_network_access_dictionaries_policy_set**(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_policy_set***network_access_identity_stores****class NetworkAccessIdentityStores**

Identity Services Engine Network Access - Identity Stores API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_network_access_identity_stores(*headers=None, **query_parameters*)

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_identity_stores*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *get_network_access_network_conditions*

`create_network_access_network_condition`(*cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **`cli_dnis_list`** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **`condition_type`** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **`description`** (*string*) – description, property of the request body.
- **`device_group_list`** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **`device_list`** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **`id`** (*string*) – id, property of the request body.
- **`ip_addr_list`** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **`link`** (*object*) – link, property of the request body.
- **`mac_addr_list`** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).

- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(id, headers=None, **query_parameters)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_network_condition_by_id*

update_network_access_network_condition_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are ‘DeviceCondition’, ‘DevicePortCondition’ and ‘EndstationCondition’.
- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_network_condition_by_id*

delete_network_access_network_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Delete network condition.

Parameters

- **id (basestring)** – id path parameter. Condition id.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_network_condition_by_id*

network_access_policy_set

class NetworkAccessPolicySet

Identity Services Engine Network Access - Policy Set API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_sets(*headers=None*, ***query_parameters*)

Get all network access policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_sets*

create_network_access_policy_set(*condition=None*, *default=None*, *description=None*, *hit_counts=None*, *id=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.

- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set*

reset_hit_counts_network_access_policy_sets(*headers=None, **query_parameters*)

Network Access Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_policy_sets*

get_network_access_policy_set_by_id(*id, headers=None, **query_parameters*)

Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_by_id*

update_network_access_policy_set_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_by_id*

delete_network_access_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_by_id*

network_access_profiles

class NetworkAccessProfiles

Identity Services Engine Network Access - Profiles API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

get_network_access_profiles(*headers=None, **query_parameters*)

Network Access Returns list of authorization profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_network_access_security_groups*

network_access_service_names**class NetworkAccessServiceNames**

Identity Services Engine Network Access - Service Names API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

`get_network_access_service_names`(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_service_names*

network_access_time_date_conditions

class NetworkAccessTimeDateConditions

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_time_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_time_conditions*

create_network_access_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body

(list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
        dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
        dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
        is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_access_time_condition*

```
get_network_access_time_condition_by_id(id, headers=None, **query_parameters)
```

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_network_access_time_condition_by_id*

update_network_access_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates

Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_time_condition_by_id*

delete_network_access_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_time_condition_by_id*

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.1_Patch_1).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

Network Device API allows the client to add, delete, update, and search network devices. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	2.0	Cisco ISE 2.0 model changes for TACACS+ and 3rd-Party support	tacacsSet- tings:sharedSecret	Added Attribute 'shared-Secret' for Tacacs+ sup- port
				tacacsSet- tings:connectModeOptions	Added Attribute 'connect- ModeOptions' for Tacacs+ support
				profileName	Added Attribute 'profile- Name' for 3rd-Party sup- port support
				coaPort	Added Attribute 'coaPort' for 3rd-Party support sup- port
2	1.2	2.4	Cisco ISE 2.4 model changes for Multi shared secret and DTLS Required support	authenticationset- tings:enableMultiSecret	Added Attribute 'enable- MultiSecret' for multiple shared secret
				authenticationset- tings:secondRadiusSharedSecret	Added Attribute 'secon- dRadiusSharedSecret' for multiple shared secret
				authenticationset- tings:dtlsRequired	Added Attribute 'dtlsRe- quired' for dtls settings

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Val- ues
-----------	------	----------	-------------	----------------	---------------------

continues on next page

Table 38 – continued from previous page

name	String	Yes	Resource Name		ISE_EST_Local_Host
id	String	No	Resource UUID, mandatory for update		79aac430-7cc8-11eb-ad58-005056926583
description	String	No			example nd
authentication-Settings	List	Yes			
• enableKey-Wrap	Boolean	Yes			false
• enabled	Boolean	Yes		false	
• keyEncryption-Key	String	Yes			1234567890123456
• keyInput-Format	Enum	Yes	Allowed values: ASCII, HEXADECI-MAL	ASCII	
• messageAuthenticator-CodeKey	String	No			12345678901234567890
• networkProtocol	Enum	No	Allowed values: RADIUS, TACACS_PLUS	RADIUS	
• radiusShared-Secret	String	No			VHEGKOC-CUHYB
• enable-MultiSecret	Boolean	No			false

continues on next page

Table 38 – continued from previous page

• sec-ondRa-diusShared-Secret	String	No			
• dtlsRe-quired	Boolean	No	This value enforces use of dtls	false	
coaPort	Integer	Yes	Since 2.0 (for 3rd party)		0
dtlsDnsName	String	No	This value is used to verify the client identity contained in the X.509 RA-DIUS/DTLS client certificate		ISE213.il.com
NetworkDeviceIPList	List	Yes	List of IP Subnets for this node		
• ipaddress	String	Yes	It can be either single IP address or IP range address		127.0.0.1
• getIpAddressExclude	String	Yes	It can be either single IP address or IP range address		
• mask	Integer	Yes			32
NetworkDeviceGroupList	List	No	List of Network Device Group names for this node		[“Location#All Locations”, “Device Type#All Device Types”]
modelName	String	No			
softwareVersion	String	No			
profileName	String	Yes	Since 2.0 (for 3rd party)	true	Cisco
snmpsettings	List	Yes			

continues on next page

Table 38 – continued from previous page

• linkTrap-Query	Boolean	Yes	SNMP link Trap Query	true	
• macTrap-Query	Boolean	Yes	SNMP MAC Trap Query	true	
• originat-ingPol-icySer-vicesNode	String	Yes	Originating Policy Services Node	Auto	
• polling-Interval	Integer	Yes	SNMP Polling Interval in seconds (Valid Range 600 to 86400)	3600	
• roCom-munity	String	No	SNMP RO Community		aaa
• version	Enum	No	Allowed values: ONE, TWO_C, THREE		ONE
tacacsSettings	List	Yes	Since 2.0 (for Tacacs+)		
• connect-ModeOp-tions	Enum	No	Allowed values: OFF, ON_LEGACY, ON_DRAFT_COMPLIANT		ON_LEGACY
• sharedSe-cret	String	Yes	Since 2.0		aaa
trustsecsettings	List	Yes			
• de-viceAu-thentica-tionSet-tings	List	Yes			
• sgaDevi-ceId	String	No			networkDe-vice1

continues on next page

Table 38 – continued from previous page

• sgaDevicePassword	String	No			aaa
• deviceConfigurationDeployment	List	Yes			
• enableModePassword	String	No			aaa
• execModePassword	String	No			aaa
• execModeUsername	String	No			aaa
• includeWhenDeployingSGTUpdates	Boolean	No		false	
• sgaNotificationAndUpdates	List	Yes			
• downloadEnvironmentDataEveryXSeconds	Integer	No		86400	

continues on next page

Table 38 – continued from previous page

• downloadPeer-Autho-rization-PolicyEveryXSec-onds	Integer	No		86400	
• download-SGA-CLList-sEveryXSec-onds	Integer	No		86400	
• otherS-GADe-vices-ToTrust-ThisDe-vice	Boolean	No		false	
• reAu-thentica-tionEveryXSec-onds	Integer	No		86400	
• sendCon-figura-tionToDe-vice	Boolean	No		false	
• sendCon-figura-tionToDe-viceUsing	Enum	No	Allowed values: EN-ABLE_USING_COA, EN-ABLE_USING_CLI, DIS-ABLE_ALL	EN-ABLE_USING_COA	

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.

- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`Alias for *`delete_network_device_by_name`***`get_network_device_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a network device by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_network_device_by_id`***`update_network_device_by_id(id, authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_iplist** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
              model_name=None, name=None, network_device_group_list=None,
              network_device_ip_list=None, profile_name=None, snmpsettings=None,
              software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None,
              payload=None, active_validation=True, **query_parameters)
```

Alias for *update_network_device_by_id*

```
delete_network_device_by_id(id, headers=None, **query_parameters)
```

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_network_device_by_id*

```
get_network_device(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                    headers=None, **query_parameters)
```

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device*

get_network_device_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).

- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,
        model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None,
        profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None,
        trustsecsettings=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_device*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group**class NetworkDeviceGroup**

Identity Services Engine NetworkDeviceGroup API (version: 3.1_Patch_1).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

Network Device Group API allows the client to search network device groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.3	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Device Type#All Device Types
id	String	No	Resource UUID, mandatory for update	70c79c30-8bff-11e6-996c-525400b48521
description	String	No		All Device Types
other-name	String	No		Device Type

get_network_device_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_name*

get_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_id*

update_network_device_group_by_id(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_network_device_group_by_id`*

`delete_network_device_group_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device group.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_device_group_by_id`*

get_network_device_group(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group*

```
get_network_device_group_generator(filter=None, filter_type=None, page=None, size=None,
                                     sortasc=None, sortdsc=None, headers=None,
                                     **query_parameters)
```

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_deployment**class NodeDeployment**

Identity Services Engine Node Deployment API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

`get_nodes`(*filter=None, filter_type=None, headers=None, **query_parameters*)

The API lists all the nodes that are deployed in the cluster. Returns basic information about each of the deployed nodes in the cluster like hostname, status, roles, and services. Supports filtering on FQDN, host-name, IP address, roles, services and node status. .

Parameters

- **`filter`**(*basestring, list, set, tuple*) – filter query parameter. Simple filtering is available through the filter query string parameter. The structure of a filter is a triplet of field operator and value, separated by dots. More than one filter can be sent. The logical operator common to all filter criteria is AND by default, and can be changed by using the “filter-Type=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`**(*basestring*) – filterType query parameter. The logical operator common to all filter criteria is AND by default, and can be changed by using this parameter.
- **`headers`**(*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

register_node(*allow_cert_import=None, fqdn=None, password=None, roles=None, services=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API registers a Cisco ISE node to form a multi-node deployment. Approximate execution time 300 seconds. .

Parameters

- **`allow_cert_import`** (*boolean*) – Consent to import the self- signed certificate of the registering node. , property of the request body.
- **`fqdn`** (*string*) – fqdn, property of the request body.
- **`password`** (*string*) – password, property of the request body.
- **`roles`** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'PrimaryAdmin', 'PrimaryDedicatedMonitoring', 'PrimaryMonitoring', 'SecondaryAdmin', 'SecondaryDedicatedMonitoring', 'SecondaryMonitoring' and 'Standalone').
- **`services`** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'DeviceAdmin', 'PassiveIdentity', 'Profiler', 'SXP', 'Session', 'TC-NAC', 'pxGrid' and 'pxGridCloud').
- **`user_name`** (*string*) – userName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(hostname, headers=None, **query_parameters)

This API retrieves detailed information of the deployed node. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(hostname, headers=None, **query_parameters)

Alias for *get_node_details*

update_node(hostname, roles=None, services=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API updates the configuration of the Cisco ISE node with the configuration provided. Approximate execution time 300 seconds. .

Parameters

- **roles** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'PrimaryAdmin', 'PrimaryDedicatedMonitoring', 'PrimaryMonitoring', 'SecondaryAdmin', 'SecondaryDedicatedMonitoring', 'SecondaryMonitoring' and 'Standalone').
- **services** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'DeviceAdmin', 'PassiveIdentity', 'Profiler', 'SXP', 'Session', 'TC-NAC', 'pxGrid' and 'pxGridCloud').
- **hostname** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node(hostname, headers=None, **query_parameters)

The deregistered node becomes a standalone Cisco ISE node. It retains the last configuration that it received from the primary PAN and assumes the default roles and services of a standalone node. Approximate execution time 300 seconds. .

Parameters

- **hostname (basestring)** – hostname path parameter. The hostname of the node in the deployment to be deregistered.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

make_primary(*headers=None, **query_parameters*)

This API promotes the standalone node on which the API is invoked to the primary Policy Administration node (PAN). .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

promote_node(*headers=None, **query_parameters*)

Execute this API in the secondary PAN in the cluster to promote the node to primary PAN. Ensure that the API Gateway setting is enabled in the secondary PAN. Approximate execution time 300 seconds. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

make_standalone(*headers=None, **query_parameters*)

This API changes the primary PAN in a single node cluster on which the API is invoked, to a standalone node. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sync_node(*hostname, headers=None, **query_parameters*)

Performing a manual synchronization involves a reload of the target node, but not the primary PAN. Approximate execution time 300 seconds.

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_group

class NodeGroup

Identity Services Engine Node Group API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

get_node_groups(*headers=None, **query_parameters*)

This API retrieves the details of all the node groups in the cluster. Each node group retrieved consists of name, description and MAR cache details like query-attempts, query-timeout, replication-attempts, replication- timeout. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*description=None, mar_cache=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a node group in the cluster. A node group is a group of PSNs, where the PSNs maintain a heartbeat with each other. It is used primarily to terminate or transfer posture-pending sessions when a PSN in a local node group fails. Node group members can communicate over TCP/7800. The following parameters are used in the request body of the API:

PARAMETER	DESCRIPTION	EXAMPLE
name	* required Name of the node group(valid-range: 1-100 characters)	{“name”: “site1”}
description	Description of the node group (valid-range: 0-256 characters)	{“name”: “site2”, “description”: “sample”}
query-attempts	The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1)	{“name”: “site3”, “marCache”: {“query-attempts”: 1}}
query-timeout	The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2)	{“name”: “site4”, “marCache”: {“query-timeout”: 2}}
replication-attempts	The number of	

times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2) {"name": "site5","marCache": {"replication-attempts": 2}} replication-timeout The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5) second(s) {"name": "site6","marCache": {"replication-timeout": 5}} NOTE 1: : Node group name and description cannot contain any of the following characters: ! % ^ : ; , . ~ @ # & [{ (|) }] ` > < / " ' + = ? NOTE 2: : Parameter marCache stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory- authentication users. We can enable the marCache for a nodegroup by providing key "marCache" in json request. Additionally we may also provide any combination of parameters query-attempts, query-timeout, replication- attempts, replication-timeout in marCache object. If no value is specified for a particular parameter its default value will be recorded.If no marCache object is given, marCache will be considered as disabled. .

Parameters

- **description** (*string*) – description, property of the request body.
- **mar_cache** (*object*) – marCache, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the details of a node group in the cluster using a node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_node_group`(*node_group_name*, *description=None*, *mar_cache=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to update an existing node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** **name** * required Name of the node group existing in ISE(valid-range: 1-100 characters) **NOTE** : name of an existing node group cannot be modified. "name" parameter should be identical to the node group name(`nodeGroupName`) provided in the path {"name": "site1"} **description** Description of the node group (valid-range: 0-256 characters) {"name": "site2", "description": "sample"} **query-attempts** The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1) {"name": "site3", "marCache": {"query-attempts": 1}} **query-timeout** The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2) second(s) {"name": "site4", "marCache": {"query-timeout": 2}} **replication-attempts** The number of times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2) {"name": "site5", "marCache": {"replication-attempts": 2}} **replication-timeout** The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5) second(s) {"name": "site6", "marCache": {"replication-timeout": 5}} **NOTE 1**: Node group name and description cannot contain any of the following characters: ! % ^ ; , . ~ @ # & [{ (|) }] ` > < / " ' + = ? **NOTE 2**: Parameter `marCache` stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory-authentication users. We can enable the `marCache` for a nodegroup by providing key "marCache" in json request. Additionally we may also provide any combination of parameters `query-attempts`, `query-timeout`, `replication-attempts`, `replication-timeout` in `marCache` object. If no value is specified for a particular parameter its default value will be recorded. If no `marCache` object is given, `marCache` will be disabled. .

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`mar_cache`** (*object*) – `marCache`, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`node_group_name`** (*basestring*) – `nodeGroupName` path parameter. Name of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node_group(*force_delete*, *node_group_name*, *headers=None*, ***query_parameters*)

Delete an existing node group in the cluster. Deleting the node group does not delete the nodes, but failover is no longer carried out among the nodes.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **force_delete** (*bool*) – forceDelete query parameter. Force delete the group even if the node group contains one or more nodes.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

add_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API adds a node to the node group in the cluster. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all the URL-redirceted sessions on the failed node. The following parameters are used in the request body of the API: PARAMETER DESCRIPTION EXAMPLE *hostname* * required Name of the host name {"hostname": "isenode"}

Parameters

- **hostname** (*string*) – hostname, property of the request body.
- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_nodes(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the list of nodes associated with a node group in the cluster with a given node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

remove_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to remove a node from a node group in the cluster. Removing node from the node group does not delete the node, but failover is no longer carried out if the node is not part any node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** `hostname` * required Name of the host name {`"hostname": "isnode"`} .

Parameters

- **`hostname`** (*string*) – hostname, property of the request body.
- **`node_group_name`** (*basestring*) – `nodeGroupName` path parameter. Name of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_services

class NodeServices

Identity Services Engine Node Services API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Node Services API and exposes the API as native Python methods that return native Python objects.

get_interfaces(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the list of interfaces on a node in a cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sxp_interface(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the SXP interface. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_sxp_interface(*hostname*, *interface=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API configures the SXP interface. .

Parameters

- **interface** (*string*) – interface, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_probe_config(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the profiler probe configuration of a PSN. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`set_profiler_probe_config`(*hostname*, *active_directory=None*, *dhcp=None*, *dhcp_span=None*, *dns=None*, *http=None*, *netflow=None*, *nmap=None*, *pxgrid=None*, *radius=None*, *snmp_query=None*, *snmp_trap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API updates the profiler probe configuration of a PSN. Set probe value as null to disable probe. Ex: Below payload will disable NMAP, PxGrid and SNMPTRAP probes { "activeDirectory": { "daysBeforeRescan": 1 }, "dhcp": { "interfaces": "[{"interface": "GigabitEthernet 0"}]", "port": 0 }, "dhcpSpan": { "interfaces": "[{"interface": "GigabitEthernet 0"}]" }, "dns": { "timeout": 2 }, "http": { "interfaces": "[{"interface": "GigabitEthernet 0"}]" }, "netflow": { "interfaces": "[{"interface": "GigabitEthernet 0"}]", "port": 0 }, "nmap": null , "pxgrid": null , "radius": [], "snmpQuery": { "eventTimeout": 30, "retries": 2, "timeout": 1000 }, "snmpTrap": null } .

Parameters

- **`active_directory`** (*object*) – The Active Directory probe queries the Active Directory for Windows information., property of the request body.
- **`dhcp`** (*object*) – The DHCP probe listens for DHCP packets from IP helpers., property of the request body.
- **`dhcp_span`** (*object*) – The DHCP SPAN probe collects DHCP packets., property of the request body.
- **`dns`** (*object*) – The DNS probe performs a DNS lookup for the FQDN., property of the request body.
- **`http`** (*object*) – The HTTP probe receives and parses HTTP packets., property of the request body.
- **`netflow`** (*object*) – The NetFlow probe collects the NetFlow packets that are sent to it from routers., property of the request body.
- **`nmap`** (*list*) – The NMAP probe scans endpoints for open ports and OS., property of the request body (list of objects).
- **`pxgrid`** (*list*) – The pxGrid probe fetches attributes of MAC address or IP address as a subscriber from the pxGrid queue., property of the request body (list of objects).

- **radius** (*list*) – The RADIUS probe collects RADIUS session attributes as well as CDP, LLDP, DHCP, HTTP, and MDM attributes from IOS Sensors., property of the request body (list of objects).
- **snmp_query** (*object*) – The SNMP query probe collects details from network devices such as interface, CDP, LLDP, and ARP., property of the request body.
- **snmp_trap** (*object*) – The SNMP trap probe receives linkup, linkdown, and MAC notification traps from network devices., property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_details

class NodeDetails

Identity Services Engine NodeDetails API (version: 3.1_Patch_1).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

Node Details API allows the client to get deployment node details, get all nodes and filter nodes based on NodeServiceTypes.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifi- cation	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Ver- sion		
1	1.1	2.4	Support Node Service Types as part of Node Object	NodeSer- viceTypes	Added String Field NodeServiceTypes. String represents services configured on the Node
2	1.2	2.7	Support Node FQDN as part of Node Object	fqdn	Added String Field FQDN. String rep- resents FQDN of the Node
3	1.3	3.0	Support SXP IP Ad- dress as part of Node Details	sxpIpAd- dress	Added String Field sxpIpAddress. String represents SXP IP Address of the Node

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577- 0014737c8fcf
description	String	No		
gateWay	String	No		10.0.10.11
displayName	String	No		TestNode
inDeployment	Boolean	No		false
ipAddresses	String	No		[“10.0.0.1”, “10.0.0.2”]
otherPapFqdn	String	No		OtherTestNode
ipAddress	String	No		10.0.0.3
sxpIpAddress	String	No		10.10.10.1
nodeService- Types	String	No		DEVICE ADMIN
fqdn	String	No		test.ers.cisco.com
primaryPapN- ode	Boolean	No		true
papNode	Boolean	No		true
pxGridNode	Boolean	No		true

get_node_detail_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_name*

`get_node_detail_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the node details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

get_pan_ha_status(headers=None, **query_parameters)

In a high availability configuration, the primary PAN is in active state. The secondary PAN (backup PAN) is in standby state, which means that it receives all the configuration updates from the primary PAN, but is not active in the Cisco ISE cluster. You can configure Cisco ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or any combination of these. If the PANs are in different data centers, you must have a health check node for each PAN. All the fields are mandatory to enable PanHA. Values of failedAttempts, pollingInterval, primaryHealthCheckNode, and secondaryHealthCheckNode are not considered when the isEnabled value is “false” in the request body.

Parameters

- **failed_attempts** (*integer*) – Failover occurs if the primary PAN is down for the specified number of failure polls. Count (2 60). The default value is 5. , property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **polling_interval** (*integer*) – Administration nodes are checked after each interval. Seconds (30 300) The default value is 120. , property of the request body.
- **primary_health_check_node** (*object*) – primaryHealthCheckNode, property of the request body.
- **secondary_health_check_node** (*object*) – secondaryHealthCheckNode, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

patching

class Patching

Identity Services Engine Patching API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Patching API and exposes the API as native Python methods that return native Python objects.

list_installed_hotpatches(*headers=None, **query_parameters*)

List all the installed hot patches in the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

install_hotpatch(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch installation process. As hot patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **hotpatch_name** (*string*) – hotpatchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`rollback_hotpatch`(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch rollback process. As hot patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **`hotpatch_name`** (*string*) – hotpatchName, property of the request body.
- **`repository_name`** (*string*) – repositoryName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

list_installed_patches(*headers=None, **query_parameters*)

List all the installed patches in the system, with the patch number for rollback. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

install_patch(*patch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch installation process. As the patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_name** (*string*) – patchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

rollback_patch(*patch_number=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch rollback process. As the patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_number** (*integer*) – patchNumber, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting**class PortalGlobalSetting**

Identity Services Engine PortalGlobalSetting API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

The Portal Global Setting API allows the user to customize the text that is displayed in the Cisco ISE portals. This global setting controls whether HTML alone or both HTML and Javascript are permitted to be used in customized text.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
id	String	Yes	Resource UUID value	21013cb2-d030-4fb1-9ba2-35757634d770
cus-tomization	Enum	Yes	Allowed values: HTML, HTMLAND-JAVASCRIPT	HTML

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdesc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

get_portal_global_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

portal_theme**class PortalTheme**

Identity Services Engine PortalTheme API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

Portal Theme API allows the client to add, delete, update and search Portal Theme among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Default Blue theme
id	String	No	Resource UUID, mandatory for update	9eb421c0-8c01-11e6-996c-525400b48521
descrip-tion	String	No		
theme-Data	String	Yes	Portal Theme for all portals	Base 64 encoded string of CSS file

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_theme_by_id*

update_portal_theme_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_portal_theme_by_id`*

`delete_portal_theme_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_portal_theme_by_id`*

get_portal_themes(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

get_portal_themes_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for [*get_portal_themes_generator*](#)

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [*create_portal_theme*](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler**class Profiler**

Identity Services Engine Profiler API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxe*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_profiles(*headers=None, **query_parameters*)

getProfiles.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler_profile**class ProfilerProfile**

Identity Services Engine ProfilerProfile API (version: 3.1_Patch_1).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

Profiler Profile API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	2Wire-Device
id	String	No	Resource UUID, mandatory for update	fe8c7cc0-8bff-11e6-996c-525400b48521
description	String	No		Policy for 2Wire-Device
parentId	String	Yes		

get_profiler_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profile_by_id*

get_profiler_profiles(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](https://developer.cisco.com/site/license/cisco-sample-code-license/)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

register_service(*name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reregister_service(*headers=None, **query_parameters*)

ServiceReregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

authorization(*headers=None, **query_parameters*)

Authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service

class PsnNodeDetailsWithRadiusService

Identity Services Engine PsnNodeDetailsWithRadiusService API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PsnNodeDetailsWithRadiusService API and exposes the API as native Python methods that return native Python objects.

PSN Node Details with RADIUS Service API allows the client to get deployment node details where 'Session Services' is enabled.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for up-date	ab6deded-fcc2-47ff-8577-0014737c8fcf
descrip-tion	String	No		PSN with Session Service
ipAddress	String	Yes		10.0.0.1

get_session_service_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_session_service_node_by_id`***`get_session_service_node(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the PSN node details.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_session_service_node`*

get_session_service_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pull_deployment_info**class PullDeploymentInfo**

Identity Services Engine PullDeploymentInfo API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

Pull Deployment Info API allows clients to get the complete information about a Cisco ISE deployment. The information includes details about the deployment, network access, NADs, MDMs, licenses, posture and profiler.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.7	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description
name	String	Yes	Resource Name
id	String	No	Resource UUID, mandatory for update
description	String	No	
networkAccessInfo	List	No	networkAccessInfo Details
• deploymentID	String	Yes	Deployment ID
• isCsnEnabled	Boolean	Yes	false
• nodeList	List	Yes	Node list

continues on next page

Table 39 – continued from previous page

• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• sdaVNs	List	No	
• trustSecControl	String	No	ISE
• radius3RdParty	List	No	
profilerInfo	List	No	profilerInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Includes 'profiles' which is an array of dictionaries describing various attributes with the properties:- profile (List), - customProfilesCount (Integer), - endpointTypes (String), - totalProfilesCount (Integer), - uniqueEndpointsCount (Integer), - unknownEndpointsCount (Integer), - totalEndpointsCount (Integer), - unknownEndpointsPercentage (Integer)
deploymentInfo	List	No	deploymentInfo Details
• deploymentID	String	Yes	Deployment ID

continues on next page

Table 39 – continued from previous page

• versionHistoryInfo	List	No	Array of dictionaries describing various attributes with the properties:- opType (String), - mainVersion (String), - epochTime (Integer)
• nodeList	List	Yes	Node list
• nodeAndNode-CountAnd-CountInfo	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• fipsstatus	String	No	Disabled
nadInfo	List	No	nadInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declaredType (String), - scope (String), - value (List), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• nadcountInfo	List	No	
• totalActiveNAD-Count	Integer	No	0
mdmInfo	List	No	mdmInfo Details

continues on next page

Table 39 – continued from previous page

• activeMdmServersCount	Integer	Yes	0
• activeDesktopMdmServersCount	Integer	Yes	0
• activeMobileMdmServersCount	Integer	Yes	0
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
licensesInfo	List	No	licensesInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
postureInfo	List	No	postureInfo Details

continues on next page

Table 39 – continued from previous page

• content	List	Yes	Array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
kongInfo	List	No	kongInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Array of dictionaries describing various attributes with the properties:- sn (String), - service (List)

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **timeout** (*float*, *tuple*) – How long to wait for the server to send data before giving up.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings

class PxGridSettings

Identity Services Engine PxGridSettings API (version: 3.1_Patch_1).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

pxGrid Settings API allows the client to change auto-approve settings for pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for up- date		
description	String	No			
autoApproveCert- BasedAccounts	Boolean	Yes	Auto approve certificate based ac- counts when true	false	true
allowPassword- BasedAccounts	Boolean	Yes	Allow password based acoounts when true	false	

```
autoapprove_px_grid_settings(allow_password_based_accounts=None,
                             auto_approve_cert_based_accounts=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
autoapprove(allow_password_based_accounts=None, auto_approve_cert_based_accounts=None,
            headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *autoapprove_px_grid_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.1_Patch_1).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_failures(*headers=None, **query_parameters*)

getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.1_Patch_1).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

RADIUS Server Sequence API allows the client to add, delete, update, search and perform actions on RADIUS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.3	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			description
stripPrefix	Boolean	No		false	
stripSuffix	Boolean	No		false	
prefixSeparator	String	No	The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character		
suffixSeparator	String	No	The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character	@	
remoteAccounting	Boolean	No		true	
localAccounting	Boolean	No		false	
useAttrSetOnRequest	Boolean	No		false	
useAttrSetBeforeAcc	Boolean	No		false	
continueAuthorzPolicy	Boolean	No		false	
radiusServers	List	Yes	List with names of external radius server. The order of the names in the list is the order of servers that will be used during authentication		[“externalRadiusServer1”, “externalRadiusServer2”]
onRequestAttrManipulators	List	No	The onRequestAttrManipulators is required only if useAttrSetOnRequest is true		
<ul style="list-style-type: none"> Attribute-Manipulator 	List	No			
1984				Chapter 1.	The User Guide
<ul style="list-style-type: none"> action 	Enum	Yes	Allowed Values: ADD,		ADD

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).

- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list*=None, *continue_authorz_policy*=None, *description*=None, *local_accounting*=None, *name*=None, *on_request_attr_manipulator_list*=None, *prefix_separator*=None, *radius_server_list*=None, *remote_accounting*=None, *strip_prefix*=None, *strip_suffix*=None, *suffix_separator*=None, *use_attr_set_before_acc*=None, *use_attr_set_on_request*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_radius_server_sequence_by_id*

delete_radius_server_sequence_by_id(*id*, *headers*=None, ***query_parameters*)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ***query_parameters*)

Alias for *delete_radius_server_sequence_by_id*

get_radius_server_sequence(*page*=None, *size*=None, *headers*=None, ***query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence***`get_radius_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence_generator*


```
create_radius_server_sequence(before_accept_attr_manipulators_list=None,
                             continue_authorz_policy=None, description=None,
                             local_accounting=None, name=None,
                             on_request_attr_manipulator_list=None, prefix_separator=None,
                             radius_server_list=None, remote_accounting=None,
                             strip_prefix=None, strip_suffix=None, suffix_separator=None,
                             use_attr_set_before_acc=None, use_attr_set_on_request=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API creates a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.1_Patch_1).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

REST ID Store API allows clients to add, get, update and delete REST ID stores.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	RestIdStore1
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		Object that represents the restID store
restIdStoreAttributes	List	Yes	Holds the attributes of the restID object	
• username-Suffix	String	Yes	Suffix of the user-name domain	@place.com
• rootUrl	String	Yes	url of the root of the RestIDStore	rootUrl
• predefined	Enum	Yes	The cloud provider connected to of the RestIDStore. Options are: - Azure, - Okta, - None	Azure
• headers	List	Yes	Headers for the RestIDStore	
• key	String	Yes	Key of the header	tenantID
• value	String	Yes	Value of the header	tenantID_value

get_rest_id_store_by_name(name, headers=None, **query_parameters)

This API allows the client to get a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_rest_id_store_by_name*](#)

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for [*delete_rest_id_store_by_name*](#)

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store*

get_rest_id_store_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, ers_rest_idstore_user_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **ers_rest_idstore_user_attributes** (*object*) – ersRestIDStoreUserAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, ers_rest_idstore_user_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None, **query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_repositories*

create_repository(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.

- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and `_./@$` characters., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_repository*

get_repository(*repository_name, headers=None, **query_parameters*)

Get a specific repository identified by the name passed in the URL. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*repository_name*, *headers=None*, ***query_parameters*)Alias for *get_repository***update_repository**(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_repository*

delete_repository(*repository_name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*repository_name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_files(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider**class SmsProvider**

Identity Services Engine SMSProvider API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

SMS Provider API allows the client to search the SMS providers configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		

get_sms_provider(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider*

get_sms_provider_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sxp_connections**class SxpConnections**

Identity Services Engine SXPCConnections API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SXPCConnections API and exposes the API as native Python methods that return native Python objects.

SXP Connections API allows clients to add, get, update and delete the Security Group Tag (SGT) Exchange Protocol (SXP) connections.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	sxpVpn	Attribute can include some VPNs separated by comma

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		Brief description about network peer
sxpPeer	String	Yes		Sxp Peer Name
sxpVpn	String	Yes		Sxp VPN Name
sxpNode	String	Yes		Sxp Node Name
ipAddress	String	Yes		Sxp Peer IP address
sxpMode	String	Yes		Sxp Mode
sxpVersion	String	Yes		Sxp Version
enabled	Boolean	Yes		true

get_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*,
sxp_mode=None, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*,
sxp_vpn=None, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None,
             sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None,
             active_validation=True, **query_parameters)
```

Alias for `update_sxp_connections_by_id`

```
delete_sxp_connections_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP connection.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sxp_connections_by_id`

```
get_sxp_connections(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                   sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

create_sxp_connections(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.

- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_connections*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_connections(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

- REST response with following properties:
- headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_connections*

sxp_local_bindings

class SxpLocalBindings

Identity Services Engine SXPLocalBindings API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

SXP Local Bindings API allows clients to add, get, update and delete SGT static mappings.

Revision History

Revi- sion #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	vns	Added new property for the Virtual Networks

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
binding-Name	String	No	This field is deprecated from Cisco ISE 3.0	
ipAddressOrHost	String	Yes	IP address for static mapping (hostname is not supported)	ipAddressOrHost
sgt	String	Yes	SGT name or ID	sgt_id
sxpVpn	String	Yes	List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined	Sxp Vpn Name
vns	String	Yes	List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined	virtualNetwork

get_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_local_bindings_by_id*

update_sxp_local_bindings_by_id(*id*, *binding_name=None*, *description=None*,
ip_address_or_host=None, *sgt=None*, *sxp_vpn=None*, *vns=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, binding_name=None, description=None, ip_address_or_host=None, sgt=None,
             sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_sxp_local_bindings_by_id`

```
delete_sxp_local_bindings_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP local binding.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

get_sxp_local_bindings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

create_sxp_local_bindings(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_local_bindings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_local_bindings(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_local_bindings*

monitor_bulk_status_sxp_local_bindings(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_sxp_local_bindings***sxp_vpns****class SxpVpns**

Identity Services Engine SXPVPNs API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

SXP VPNs API allows clients to add, get and delete SXP VPNs (SXP Domains).

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	ef36ca16-0cf7-4806-b2a9-6f547cfe4805
description	String	No		
sxpVpnName	String	Yes		default

get_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_vpn_by_id*

delete_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP VPN.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_vpn_by_id*

get_sxp_vpns(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – sxpVpnName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_vpn*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_vpns`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_sxp_vpns`*

monitor_bulk_status_sxp_vpns(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

SGT mapping to virtual networks are mapped to referenced vlan. These constructs come from out side of Cisco ISE and are not CRUDable inside Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.3	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No		description
sgtId	String	No		sgt_id
virtualnetworklist	List	No	Includes 'vlangs' which is an array of dictionaries describing various attributes with the properties: - id (String), - name (String), - description (String), - defaultVlan (Boolean), - max-Value (Integer), - data (Boolean)	<pre> { "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "virtual1", "description": "description", "defaultVirtualNetwork": false, "vlangs": [{ "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "vlan1", "description": "description1", "defaultVlan": true, "maxValue": 1882725260, "data": true }] }</pre>

get_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

update_security_groups_to_vn_to_vlan_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_to_vn_to_vlan_by_id*

delete_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL to virtual network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_to_vn_to_vlan_by_id*

get_security_groups_to_vn_to_vlan(*filter=None*, *filter_type=None*, *page=None*, *size=None*,
headers=None, ***query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan*

`get_security_groups_to_vn_to_vlan_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_security_groups_to_vn_to_vlan_generator`*

`create_security_groups_to_vn_to_vlan`(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group to virtual network.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt_id`** (*string*) – sgtId, property of the request body.
- **`virtualnetworklist`** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_to_vn_to_vlan*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_groups_to_vn_to_vlan(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_to_vn_to_vlan*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

SGT API allows the client to search SGTs.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	1.4	Cisco ISE 1.4 model changes	isTagFromRange	Removed Attribute isTagFromRange - deprecated - set to FALSE value by default
2	1.2	2.3	Cisco ISE 2.3 model changes	propagateToApic	Added Boolean Attribute propagateToApic - By default value is false
3	1.3	2.7	Cisco ISE 2.7 model changes	isReadOnly	Added Boolean Attribute isReadOnly - By default value is false
				defaultSGACLs	Added List Attribute defaultSGACLs

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Employees
id	String	No	Resource UUID, mandatory for update		93ad6890-8c01-11e6-996c-525400b48521
description	String	No			Employee Security Group
value	Integer	Yes	Value range: 2 to 65519 or -1 to auto-generate		4
propagateToApic	Boolean	No			true
isReadOnly	Boolean	No		false	
defaultSGACLs	List	No			[]
propagateToApic	Boolean	No			true
generationId	Integer	No			0

get_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_group_by_id*

update_security_group_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACLs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 or 65519 or -1 to auto- generate, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

get_security_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups*

get_security_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*

create_security_group(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propogate_to_apic** (*boolean*) – propogateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_group*

monitor_bulk_status_security_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

Security Groups ACLs API allows the client to search security groups access control lists.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	2.3	Introducing bulk operations		
2	1.2	3.1	Cisco ISE 3.1 model changes	modelledContent	Adding modelled content from Cisco ISE 3.1

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Permit IP
id	String	No	Resource UUID, mandatory for update		92951ac0-8c01-11e6-996c-525400b48521
description	String	No			Permit IP SGACL
ACLContent	String	No			permit ip
ipVersion	Enum	Yes	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	
isRead-Only	Boolean	No		false	
generationId	String	No	GenerationId is a read only attribute and is being generated by the server		0
modelled-Content	List	No	Modelled content of contract		

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_acl_by_id*

update_security_groups_acl_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_security_groups_acl_by_id*

delete_security_groups_acl_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a security group ACL.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_security_groups_acl`

```
get_security_groups_acl_generator(filter=None, filter_type=None, page=None, size=None,
                                   sortasc=None, sortdsc=None, headers=None,
                                   **query_parameters)
```

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None,
        modelled_content=None, name=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_security_groups_acl*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_security_groups_acl(operation_type=None, resource_media_type=None,
                                     headers=None, payload=None, active_validation=True,
                                     **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_acl*

monitor_bulk_status_security_groups_acl(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_acl*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

Self Registered Guest Portal API provides the ability to create, read, update, delete and search self registered portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Val- ues
name	String	Yes	Resource Name		Self-Registered Guest Portal (default)
id	String	No	Resource UUID, mandatory for update		4e8ade36-4048-472a-b345-632cc155acfc
description	String	No			Guests may create their own accounts and be assigned a username and password, or use their social login to access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?po4048-472a-b345-632cc155acfc

continues on next page

Table 40 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SELF-REGGUEST	
settings	List	No	Defines all of the settings groups available for a portal		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on.		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• authentication-Method	String	Yes	Unique Id of the identity source sequence		92e50f80-8c01-11e6-996c-525400b48521
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type		Contractor (default)

continues on next page

Table 40 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		
• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 40 – continued from previous page

• re-requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• re-requireAccessCode	Boolean	No	Require the portal user to enter an access code	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• allowGuest-ToCreateAccounts	Boolean	No		false	
• allowGuest-ToChangePassword	Boolean	No	Require the portal user to enter an access code	false	
• allowAlternateGuest-Portal	Boolean	No			false
• alternateGuest-Portal	String	No			
• selfReg-PageSettings	List	No			

continues on next page

Table 40 – continued from previous page

• as-signGuestsToGuest-Type	String	No	Guests are assigned to this guest type		
• account-Validity-Duration	Integer	No	Self-registered guest account is valid for this many account_validity_time_units	1	
• account-Validity-TimeUnits	Enum	No	Time units for account_validity_duration.	DAYS	
• requireRegistrationCode	Boolean	No	Self-registered guests are required to enter a registration code	false	
• registrationCode	String	No	The registration code that the guest user must enter		
• fieldUserName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldFirstName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLastName	List	No			

continues on next page

Table 40 – continued from previous page

• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldE-mailAddr	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldPhoneNo	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldCompany	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLocation	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableLocations	List	No	Guests can choose from these locations to set their time zone		[“San Jose”]

continues on next page

Table 40 – continued from previous page

• fieldSm-sProvider	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableSm-sProviders	List	No	This attribute is an array of SMS provider names		["Global Default"]
• fieldPersonBeingVisited	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• field-Reason-ForVisit	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 40 – continued from previous page

• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• enableGuestEmailWhitelist	Boolean	No	Allow guests with an e-mail address from selected domains	false	
• guestEmailWhitelistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be allowed. Only valid if enableGuestEmailWhitelist = true		
• enableGuestEmailBlacklist	Boolean	No	Disallow guests with an e-mail address from selected domains	false	
• guestEmailBlacklistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be disallowed. Only valid if enableGuestEmailBlacklist = true		
• requireGuestApproval	Boolean	No	Require self-registered guests to be approved if true	false	

continues on next page

Table 40 – continued from previous page

<ul style="list-style-type: none"> • autoLogin-SelfWait 	Boolean	No	Allow guests to login automatically from self-registration after sponsor's approval. No need to provide the credentials by guest to login	false	
<ul style="list-style-type: none"> • autoLogin-TimePeriod 	Integer	No	Waiting period for auto login until sponsor's approval. If time exceeds, guest has to login manually by providing the credentials. Default value is 5 minutes	5	
<ul style="list-style-type: none"> • sendApprovalRequestTo 	Enum	No	Specifies where approval requests are sent. Only valid if requireGuestApproval = true.	SELECTEDEMAILADDRESSES	
<ul style="list-style-type: none"> • approvalEmailAddresses 	String	No	Only valid if requireGuestApproval = true and sendApprovalRequestTo = SELECTEDEMAILADDRESSES		
<ul style="list-style-type: none"> • postRegistrationRedirect 	Enum	No	After the registration submission direct the guest user to one of the following pages. Only valid if requireGuestApproval = true.	SELFREGISTRATIONSUCCESS	

continues on next page

Table 40 – continued from previous page

<ul style="list-style-type: none"> • postRegistrationRedirectUrl 	String	No	URL where guest user is redirected after registration. Only valid if requireGuestApproval = true and postRegistrationRedirect = URL		
<ul style="list-style-type: none"> • credentialNotificationUsingEmail 	Boolean	No	If true, send credential notification upon approval using email. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • credentialNotificationUsingSms 	Boolean	No	If true, send credential notification upon approval using SMS. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • approveDenyLinksValidFor 	Integer	No	This attribute, along with approveDenyLinksTimeUnits, specifies how long the link can be used. Only valid if requireGuestApproval = true	1440	
<ul style="list-style-type: none"> • approveDenyLinksTimeUnits 	Enum	No	This attribute, along with approveDenyLinksValidFor, specifies how long the link can be used. Only valid if requireGuestApproval = true.	DAYS	

continues on next page

Table 40 – continued from previous page

<ul style="list-style-type: none">• re-requireApprovalToAuthenticate	Boolean	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be required to enter their username and password if this attribute is true. Only valid if requireGuestApproval = true	false	
--	---------	----	---	-------	--

continues on next page

Table 40 – continued from previous page

• sponsor-PortalList	List	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be authenticated against the selected sponsor portals in the order specified. Only valid if requireGuestApproval = true. The array should contain the names of the selected portals		
• selfReg-Success-Settings	List	No			
• includeUserName	Boolean	No		true	
• includePassword	Boolean	No		true	
• includeFirst-Name	Boolean	No		true	

continues on next page

Table 40 – continued from previous page

• include-Last-Name	Boolean	No		true	
• includeEmailAddr	Boolean	No		true	
• include-PhoneNo	Boolean	No		true	
• include-Company	Boolean	No		true	
• include-Location	Boolean	No		true	
• includeSm-sProvider	Boolean	No		true	
• include-PersonBeingVisited	Boolean	No		true	
• includeReason-ForVisit	Boolean	No		true	
• allowGuest-SendSelfUsing-Print	Boolean	No		false	
• allowGuest-SendSelfUsingE-mail	Boolean	No		false	

continues on next page

Table 40 – continued from previous page

• allowGuest-SendSelfUsingSms	Boolean	No		false	
• includeAup	Boolean	No		false	
• aupOn-Page	Boolean	No		false	
• requireAupAcceptance	Boolean	No		false	
• requireAupScrolling	Boolean	No		false	
• allowGuest-Login-FromSelfregSuccessPage	Boolean	No		false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 40 – continued from previous page

• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	
• skipAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAtFirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegisterGuestDevices	Boolean	No	Automatically register guest devices	true	

continues on next page

Table 40 – continued from previous page

• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No		true	
• enableGuestAccess	Boolean	No		false	
• requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ONPAGE	
• requireAupAcceptance	Boolean	No		false	

continues on next page

Table 40 – continued from previous page

• require-Scrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodReg-istra-tionSet-tings	List	No	Configuration of BYOD endpoint Reg-istration step configuration		
• showDe-viceID	Boolean	No	Display Device ID field during registration	true	
• end-PointI-identity-GroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521
• byodReg-istra-tionSuc-cessSet-tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	
• redirec-tUrl	String	No	Target URL for redirection, used when suc-cessRedirect = URL		
• authSuc-cessSet-tings	List	No			
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	

continues on next page

Table 40 – continued from previous page

• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL		www.cisco.com
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUserAgent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	

continues on next page

Table 40 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 40 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 40 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 40 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_self_registered_portal_by_id*

```
delete_self_registered_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_self_registered_portal_by_id*

```
get_self_registered_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                           sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals_generator*

create_self_registered_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_self_registered_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory**class SessionDirectory**

Identity Services Engine Session Directory API (version: 3.1_Patch_1).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_sessions(*headers=None*, ***query_parameters*)

getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_for_recovery(*headers=None, **query_parameters*)

getSessionsForRecovery.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_ip_address(*headers=None, **query_parameters*)

getSessionByIpAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_mac_address(*headers=None, **query_parameters*)

getSessionByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_groups(*headers=None, **query_parameters*)

getUserGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)

getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)

Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to add, delete, update and search sponsor groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Em-plALL_ACCOUNTS (default)oyees
id	String	No	Resource UUID, mandatory for update		9f1eca71-8c01-11e6-996c-525400b48521
description	String	No			Sponsors assigned to this group can manage all guest user accounts. By default, users in the ALL_ACCOUNTS user identity group are members of this sponsor group
isEnabled	Boolean	No			true
isDefault-Group	Boolean	No			true
member-Groups	List	No			["ALL_ACCOUNTS (default)"]
guestTypes	List	No			["Contractor (default)", "Daily (default)", "Weekly (default)"]
locations	List	No			["San Jose"]
autoNotification	Boolean	No			false
managePermission	Enum	No	Allowed values:		ALLACCOUNTS, GROUPACCOUNTS, OWNACCOUNTS
createPermissions	List	No			

continues on next page

Table 41 – continued from previous page

• canImportMultipleAccounts	Boolean	No			true
• importBatchSizeLimit	Integer	No		200	
• canCreateRandomAccounts	Boolean	No			true
• randomBatchSizeLimit	Integer	No		200	
• defaultUsernamePrefix	String	No			
• canSpecifyUsernamePrefix	Boolean	No			true
• canSetFutureStartDate	Boolean	No			false
• startDateFutureLimitDays	Integer	No			1
otherPermissions	List	No			

continues on next page

Table 41 – continued from previous page

• canUpdateGuestContactInfo	Boolean	No			true
• canViewGuestPasswords	Boolean	No			true
• canSendSMSNotifications	Boolean	No			false
• canResetGuestPasswords	Boolean	No			true
• canExtendGuestAccounts	Boolean	No			true
• canDeleteGuestAccounts	Boolean	No			true
• canSuspendGuestAccounts	Boolean	Yes			true
• requireSuspensionReason	Boolean	No			false

continues on next page

Table 41 – continued from previous page

• canRein-stateSuspendedAccounts	Boolean	No			true
• canApproveSelfregGuests	Boolean	No			true
• limitApprovalToSponsorsGuests	Boolean	Yes			false
• canAccessViaRest	Boolean	No			false

get_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_by_id*

update_sponsor_group_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor group by ID.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, auto_notification=None, create_permissions=None, description=None,
             guest_types=None, is_default_group=None, is_enabled=None, locations=None,
             manage_permission=None, member_groups=None, name=None, other_permissions=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `update_sponsor_group_by_id`

```
delete_sponsor_group_by_id(id, headers=None, **query_parameters)
```

This API deletes a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sponsor_group_by_id`

```
get_sponsor_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

This API allows the client to get all the sponsor groups. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group*

get_sponsor_group_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_generator*

create_sponsor_group(*auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).

- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sponsor_group_member**class SponsorGroupMember**

Identity Services Engine SponsorGroupMember API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to search the group members from different identity stores configured in the GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ALL_ACCOUNTS (default)
id	String	No	Resource UUID value	a176c430-8c01-11e6-996c-525400b48521
description	String	No		
dicType	String	Yes		
guid	String	Yes		

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal**class SponsorPortal**

Identity Services Engine SponsorPortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

Sponsor Portal API provides the ability to create, read, update, delete and search sponsor portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Sponsor Portal (default)

continues on next page

Table 42 – continued from previous page

id	String	No	Resource UUID, mandatory for update		04cd708b-feef-4c75-bf3e-2d2a9c302da2
description	String	No			Default portal used by sponsors to create and manage accounts for authorized visitors to securely access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8445/portal/PortalSetup.action?portalId=feef-4c75-bf3e-2d2a9c302da2
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SPONSOR	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8445
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on.		["eth0", "bond0"]

continues on next page

Table 42 – continued from previous page

• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• fqdn	String	No	The fully-qualified domain name (FQDN) that end-users will use to access this portal. Used only in Sponsor portal		Default Portal Certificate Group
• authentication-Method	String	Yes	Unique Id of the identity source sequence		92faba60-8c01-11e6-996c-525400b48521
• idleTime-out	Integer	No		10	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• availableSsids	List	No	Names of the SSIDs available for assignment to guest users by sponsors		
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 42 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	

continues on next page

Table 42 – continued from previous page

• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• sponsorChangePasswordSettings	List	No			
• allowSponsorToChangePwd	Boolean	No	Allow sponsors to change their own passwords	false	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		

continues on next page

Table 42 – continued from previous page

• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 42 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI

continues on next page

Table 42 – continued from previous page

• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contact-Text	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			

continues on next page

Table 42 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_portal_by_id*

update_sponsor_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor portal by ID.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a sponsor portal by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_portal_by_id*

get_sponsor_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_sponsor_portal`

```
get_sponsor_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

Sponsored Guest Portal API provides the ability to create, read, update, delete and search sponsored guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Sponsored Guest Portal (default))	
id	String	No	Resource UUID, mandatory for update	d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
description	String	No	Sponsors create guest accounts, and guests access the network using their assigned username and password		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	SPONSORED	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	

continues on next page

Table 43 – continued from previous page

• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• authentication-Method	String	Yes	Unique Id of the identity source sequence	92faba60-8c01-11e6-996c-525400b48521	
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type	Contractor (default)	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 43 – continued from previous page

<ul style="list-style-type: none"> • max-FailedAttemptsBeforeRateLimit 	Integer	No	Maximum failed login attempts before rate limiting	5	
<ul style="list-style-type: none"> • timeBetweenLoginsDuringRateLimit 	Integer	No	Time between login attempts when rate limiting	2	
<ul style="list-style-type: none"> • includeAup 	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
<ul style="list-style-type: none"> • aupDisplay 	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ASLINK	
<ul style="list-style-type: none"> • requireAupAcceptance 	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
<ul style="list-style-type: none"> • requireAccessCode 	Boolean	No	Require the portal user to enter an access code	false	
<ul style="list-style-type: none"> • accessCode 	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		

continues on next page

Table 43 – continued from previous page

• al-lowGuest-ToCreateAccounts	Boolean	No	false		
• al-lowGuest-ToChangePassword	Boolean	No	Require the portal user to enter an access code	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed Values: FIRSTLOGIN, EVERYLOGIN, RECURRING	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAupForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	

continues on next page

Table 43 – continued from previous page

• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequency-Interval-Days	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAt-FirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegister-GuestDevices	Boolean	No	Automatically register guest devices	true	
• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		

continues on next page

Table 43 – continued from previous page

• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No	true		
• enableGuestAccess	Boolean	No	false		
• requireMDM	Boolean	No	false		
• includeAup	Boolean	No	true		
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No	false		
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	

continues on next page

Table 43 – continued from previous page

• byodReg- istra- tionSet- tings	List	No	Configuration of BYOD endpoint Reg- istration step configuration		
• showDe- viceID	Boolean	No	Display Device ID field during registration	true	
• end- PointId- entity- GroupId	String	No	Identity group id for which endpoint belongs	aa13bb40-8bff- 11e6-996c- 525400b48521	
• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Authentica- tion Success where should device be redirected. Al- lowed values: AUTHSUC- CESSPAGE, ORIGINATIN- GURL, URL	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		
• authSuc- cessSet- tings	List	No			

continues on next page

Table 43 – continued from previous page

• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUC-CESSPAGE, ORIGINATINGURL, URL	AUTHSUC-CESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		
• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		

continues on next page

Table 43 – continued from previous page

• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	

continues on next page

Table 43 – continued from previous page

• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		
• page-Background-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		

continues on next page

Table 43 – continued from previous page

• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	Guest Portal		
• contactText	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			

continues on next page

Table 43 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_sponsored_guest_portal_by_id`*
`update_sponsored_guest_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **`customizations(object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description(string)`** – description, property of the request body.
- **`id(basestring)`** – id, property of the request body.
- **`name(string)`** – name, property of the request body.
- **`portal_test_url(string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type(string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings(object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_sponsored_guest_portal_by_id`*

`delete_sponsored_guest_portal_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_sponsored_guest_portal_by_id`*

`get_sponsored_guest_portals`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsored_guest_portals*

```
get_sponsored_guest_portals_generator(filter=None, filter_type=None, page=None, size=None,
                                         sortasc=None, sortdsc=None, headers=None,
                                         **query_parameters)
```

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals_generator*

create_sponsored_guest_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsored_guest_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download

class SupportBundleDownload

Identity Services Engine SupportBundleDownload API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

Support Bundle Download API allows client to download support bundles provided those are generated and available in the default location.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
fileName	String	Yes	File name along with path from where file needs to be downloaded	filename

download_support_bundle(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *download_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_status**class SupportBundleStatus**

Identity Services Engine SupportBundleStatus API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

Support Bundle Status API allows clients to query status of a triggered support bundle.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ciscoise
id	String	No	Resource UUID, mandatory for update	ciscoise
description	String	No		Support Bundle Status api
file-Name	String	No		ise-support-bundle-pk-ciscoise-admin-04-09-2021-15-07.tar.gpg
fileSize	Integer	No		1080924274
host-Name	String	No		ciscoise
message	String	No		Support Bundle generation completed
start-Time	String	No		Fri Apr 09 15:07:55 IST 2021
status	String	No		complete

get_support_bundle_status_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a support bundle status by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status*

get_support_bundle_status_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration**class SupportBundleTriggerConfiguration**

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

Support Bundle Trigger API allows clients to trigger support bundle provided the log settings are given using which the support needs to be generated.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values
name	String	Yes	Resource Name	supportBundle
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No	Support Bundle Generation	
hostName	String	Yes	This parameter is hostName only, xxxx of xxxx.yyy.zz	sampleHost
supportBundleOptions	List	Yes		
• includeConfigDB	Boolean	Yes	Set to include Config DB in Support Bundle	false
• includeDebugLogs	Boolean	Yes	Set to include Debug logs in Support Bundle	false
• includeLocalLogs	Boolean	Yes	Set to include Local logs in Support Bundle	false
• includeCoreFiles	Boolean	Yes	Set to include Core files in Support Bundle	false
• includeSystemLogs	Boolean	Yes	Set to include System logs in Support Bundle	false
• mntLogs	Boolean	Yes	Set to include Monitoring and troubleshooting logs in Support Bundle	false
• policyXml	Boolean	Yes	Set to include Policy XML in Support Bundle	false
• fromDate	Date	No	Date from where support bundle should include the logs	04/21/2019
• toDate	Date	No	Date upto where support bundle should include the logs	04/22/2019

```
create_support_bundle(description=None, host_name=None, name=None,
                      support_bundle_include_options=None, headers=None, payload=None,
                      active_validation=True, **query_parameters)
```

This API allows the client to create a support bundle trigger configuration.

Parameters

- **description** (*string*) – description, property of the request body.
- **host_name** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **support_bundle_include_options** (*object*) – supportBundleIncludeOptions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health**class SystemHealth**

Identity Services Engine System Health API (version: 3.1_Patch_1).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_healths(*headers=None*, ***query_parameters*)

getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)

getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

system_certificate**class SystemCertificate**

Identity Services Engine SystemCertificate API (version: 3.1_Patch_1).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

System Certificate API provides the ability to create certificates like SAML, pxGrid.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		Support Bundle Status api
nodeId	String	Yes	NodeId of Cisco ISE application	ISE-01
localCertStub	List	Yes	Inputs for certificate creation	
<ul style="list-style-type: none">subjectStub	List	No	Subject data of certificate	
<ul style="list-style-type: none">common-Name	String	No	Common Name	\$FQDN\$
<ul style="list-style-type: none">organizationalUnitName	String	No	Organizational Unit Name	Cisco-SAMLCert
<ul style="list-style-type: none">organization-Name	String	No	Organizational Name	Cisco
<ul style="list-style-type: none">localityName	String	No	Locality Name	City
<ul style="list-style-type: none">stateOr-Province-Name	String	No	State or Province Name	State
<ul style="list-style-type: none">countryName	String	No	Country Name	Country
<ul style="list-style-type: none">keyType	String	Yes	Key Type	RSA OR ECDSA
<ul style="list-style-type: none">keyLength	String	Yes	Key Length	512 OR 1024 OR 2048 OR 4096
<ul style="list-style-type: none">digest	String	Yes	Digest	SHA-256 OR SHA-384 OR SHA-512
<ul style="list-style-type: none">expirationTTL	Integer	Yes	Expiration Time to Live (TTL)	2
<ul style="list-style-type: none">selectedExpirationTTLU-nit	String	Yes	Selected Expiration TTL Unit	days OR weeks OR months OR years
			Chapter 1. The User Guide	
<ul style="list-style-type: none">groupTagDD	String	No	Group Tag DD	add-group-tag


```
create_system_certificate(ers_local_cert_stub=None, node_id=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_system_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`tacacs_command_sets`**`class TacacsCommandSets`**

Identity Services Engine TACACSCCommandSets API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

TACACS Command Sets API allows the client to add, delete, update, search and perform actions on TACACS command sets.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		DenyAllCommands
id	String	No	Resource UUID, mandatory for update		0cef7990-6120-11ea-bffb-7a82c56e81f0
description	String	No			Default Command Set
permitUnmatched	Boolean	No		false	
commands	List	No	Holds list of Commands		
<ul style="list-style-type: none"> commandList 	List	No	Array of dictionaries describing various attributes with the properties: <ul style="list-style-type: none"> - grant (Enum. Allowed values: PERMIT, DENY, DENY_ALWAYS), - command (String), - arguments (String) 		[{ "grant": "PERMIT", "command": "create", "arguments": "value" }]

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*,
permit_unmatched=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation .
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)

Alias for *get_tacacs_command_sets_generator*

create_tacacs_command_sets(commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers

class TacacsExternalServers

Identity Services Engine TACACSExternalServers API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

TACACS External Servers API allows the client to add, delete, update, search and perform actions on TACACS external servers.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsExternalServer1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f- 6827768335ab
descrip- tion	String	No			TacacsExternalServer- ForSDK
hostIP	String	Yes	The server IPV4 address		1.1.1.1
connec- tionPort	Inte- ger	No	The port to connect the server	49	
single- Connect	Boolean	No	Define the use of single con- nection	true	
sharedSe- cret	String	Yes	The server shared secret		SharedSecret
timeout	Inte- ger	No	The server timeout	20	

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_id*

update_tacacs_external_servers_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_external_servers_by_id*

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_external_servers_by_id*

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers*

get_tacacs_external_servers_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_external_servers_generator*

create_tacacs_external_servers(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_profile

class TacacsProfile

Identity Services Engine TACACSPROFILE API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TACACSPROFILE API and exposes the API as native Python methods that return native Python objects.

TACACS Profile API allows the client to add, delete, update, search and perform actions on TACACS profile.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Shell Profile
id	String	No	Resource UUID, mandatory for update	93d7ee70-92b5-11eb-a39d-96858bc78604
description	String	No		Default Shell Profile
sessionAttributes	List	No	Holds list of session attributes. View type for GUI is Shell by default	
<ul style="list-style-type: none"> sessionAttributeList 	List	No	Array of dictionaries describing various attributes with the properties: - type (Enum. Allowed values: MANDATORY, OPTIONAL), - name (String), - value (String)	[{ "type" : "MANDATORY", "name" : "attr1", "value" : "value" }]

get_tacacs_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)Alias for *`get_tacacs_profile_by_name`***`get_tacacs_profile_by_id`**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)Alias for *`get_tacacs_profile_by_id`***`update_tacacs_profile_by_id`**(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a TACACS profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.

- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_profile_by_id*

delete_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_tacacs_profile_by_id***get_tacacs_profile**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile***get_tacacs_profile_generator**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile_generator*

create_tacacs_profile(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

TACACS Server Sequence API allows the client to add, delete, update, search and perform actions on TACACS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsServerSequence1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsServerSequenceForSDK
serverList	String	Yes	The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication		TacacsExternalServer1,TacacsExternalServer2
localAccounting	Boolean	No		false	
remoteAccounting	Boolean	No		true	
prefixStrip	Boolean	No	Define if a delimiter will be used for prefix strip	false	
suffixStrip	Boolean	No	Define if a delimiter will be used for suffix strip	false	
prefixDelimiter	String	No	The delimiter that will be used for prefix strip		
suffixDelimiter	String	No	The delimiter that will be used for suffix strip	@	

get_tacacs_server_sequence_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_name`***`get_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_id`***`update_tacacs_server_sequence_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None,
              prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None,
              suffix_strip=None, headers=None, payload=None, active_validation=True,
              **query_parameters)
```

Alias for *update_tacacs_server_sequence_by_id*

```
delete_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)
```

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_tacacs_server_sequence_by_id*

```
get_tacacs_server_sequence(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_tacacs_server_sequence`*

`get_tacacs_server_sequence_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_tacacs_server_sequence_generator`*

```
create_tacacs_server_sequence(description=None, local_accounting=None, name=None,  
                               prefix_delimiter=None, prefix_strip=None, remote_accounting=None,  
                               server_list=None, suffix_delimiter=None, suffix_strip=None,  
                               headers=None, payload=None, active_validation=True,  
                               **query_parameters)
```

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None,
        remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_tacacs_server_sequence*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

Telemetry Information API allows clients to get telemetry configuration information.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	ed7176fb-3faf-4060-845e-d5fa5236bd6e
description	String	No		
status	String	No		SCHEnable
deploymentId	String	No		ed7176fb-3faf-4060-845e-d5fa5236bd6e
udiSN	String	No		CH2MKIEGBGO

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information*

get_telemetry_information_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*,
***query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration**class TrustSecConfiguration**

Identity Services Engine TrustSec Configuration API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxxg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_security_groups(*headers=None*, ***query_parameters*)

getSecurityGroups.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *get_security_groups***`get_security_group_acls`**(*headers=None, **query_parameters*)*getSecurityGroupAcls*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_policies`(*headers=None, **query_parameters*)*getEgressPolicies*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_matrices(headers=None, **query_parameters)``getEgressMatrices.`**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`trust_sec_sxp`**`class TrustSecSxp`**

Identity Services Engine TrustSec SXP API (version: 3.1_Patch_1).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_bindings(*headers=None, **query_parameters*)

getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.1_Patch_1).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_ise_version_and_patch(*headers=None, **query_parameters*)

This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info

class VersionInfo

Identity Services Engine VersionInfo API (version: 3.1_Patch_1).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_version_info(*resource, headers=None, **query_parameters*)

Get all VersionInfo.

Parameters

- **resource (basestring)** – resource path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint**class Endpoint**

Identity Services Engine endpoint API (version: 3.1_Patch_1).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

Endpoint API allows the client to add, delete, update, search, register and de-register endpoints. Please note that each API description shows whether the API is supported in bulk operation. The Bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re-vi-sion #	Re-source Version	Cisco ISE Version	Description	Revision Modification	
				Attribute	Description
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.1	Cisco ISE 2.1 model changes	custom-Attributes	Added custom attributes for the user to include custom attributes when adding endpoints to Cisco ISE
2	1.2	2.2	Cisco ISE 2.2 model changes	apiAdded	Added custom operation to get list of rejected endpoints: '/getrejectedendpoints'
				apiAdded	Added custom operation to release rejected endpoint: '{id}/releaserejectedendpoint'

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	11:22:33:44:55:66
id	String	No	Resource UUID, mandatory for update	172f8270-8f4f-11eb-b4a8-9eb04987ed29
description	String	No		MyEndpoint
customAttributes	Map	No	Key value map	{"key1": "value1"}
groupId	String	Yes		aa13bb40-8bff-11e6-996c-525400b48521
identityStore	String	No		identityStore
identityStoreId	String	No		identityStoreId
mac	String	Yes		11:22:33:44:55:66
portalUser	String	No		portalUser
profileId	String	No		profileId
staticGroupAssignment	Boolean	Yes		true
staticProfileAssignment	Boolean	Yes		false

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

release_rejected(*id*, *headers=None*, ***query_parameters*)

Alias for *release_rejected_endpoint*

deregister_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to de-register an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deregister(*id*, *headers=None*, ***query_parameters*)

Alias for *deregister_endpoint*

get_rejected_endpoints(*headers=None*, ***query_parameters*)

This API allows the client to get the rejected endpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_rejected(*headers=None, **query_parameters*)

Alias for *get_rejected_endpoints*

get_endpoint_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_endpoint_by_id`***`update_endpoint_by_id(id, custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update an endpoint.

Parameters

- **`custom_attributes`** (*object*) – customAttributes, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`group_id`** (*string*) – groupId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`identity_store`** (*string*) – identityStore, property of the request body.
- **`identity_store_id`** (*string*) – identityStoreId, property of the request body.
- **`mac`** (*string*) – mac, property of the request body.
- **`mdm_attributes`** (*object*) – mdmAttributes, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_user`** (*string*) – portalUser, property of the request body.
- **`profile_id`** (*string*) – profileId, property of the request body.
- **`static_group_assignment`** (*boolean*) – staticGroupAssignment, property of the request body.
- **`static_profile_assignment`** (*boolean*) – staticProfileAssignment, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_by_id*

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_by_id*

```
register_endpoint(custom_attributes=None, description=None, group_id=None, id=None,  
                  identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None,  
                  name=None, portal_user=None, profile_id=None, static_group_assignment=None,  
                  static_profile_assignment=None, headers=None, payload=None,  
                  active_validation=True, **query_parameters)
```

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *register_endpoint*

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_endpoints_generator`*

`create_endpoint`(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint.

Parameters

- **`custom_attributes`** (*object*) – customAttributes, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`group_id`** (*string*) – groupId, property of the request body.
- **`identity_store`** (*string*) – identityStore, property of the request body.
- **`identity_store_id`** (*string*) – identityStoreId, property of the request body.
- **`mac`** (*string*) – mac, property of the request body.
- **`mdm_attributes`** (*object*) – mdmAttributes, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_user`** (*string*) – portalUser, property of the request body.
- **`profile_id`** (*string*) – profileId, property of the request body.
- **`static_group_assignment`** (*boolean*) – staticGroupAssignment, property of the request body.
- **`static_profile_assignment`** (*boolean*) – staticProfileAssignment, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status(bulkid, headers=None, **query_parameters)`Alias for *`monitor_bulk_status_endpoint`***nbar_app****class NbarApp**

Identity Services Engine nbarApp API (version: 3.1_Patch_1).

Wraps the Identity Services Engine nbarApp API and exposes the API as native Python methods that return native Python objects.

`get_nbar_apps(filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters)`

Get all NBAR Applications.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`sort (basestring)`** – sort query parameter. sort type asc or desc.
- **`sort_by (basestring)`** – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter (basestring, list, set, tuple)`** – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type (basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_nbar_apps*

get_nbar_apps_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all NBAR Applications.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_nbar_apps_generator`*

`create_nbar_app`(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create NBAR application.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`network_identities`** (*list*) – Array of NIs, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_nbar_app*

get_nbar_app_by_id(*id, headers=None, **query_parameters*)

Get NBAR Application by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_nbar_app_by_id*

update_nbar_app_by_id(*id, description=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update NBAR Application.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **network_identities** (*list*) – Array of NIs, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *network_identities=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_nbar_app_by_id*

delete_nbar_app_by_id(*id*, *headers=None*, ****query_parameters**)

Delete NBAR Application.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_nbar_app_by_id*

portal

class Portal

Identity Services Engine portal API (version: 3.1_Patch_1).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

Portal API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ISE Portal (default)
id	String	No	Resource UUID, mandatory for update	bc5524ea-b1e5-47ed-a907-5304821da916
description	String	No		ISE Portal for saml based feature purpose
portal-Type	String	No		GUEST

get_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_portal_by_id`***`get_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`**

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals*

`get_portals_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)

Alias for *get_portals_generator*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

proxy

class Proxy

Identity Services Engine proxy API (version: 3.1_Patch_1).

Wraps the Identity Services Engine proxy API and exposes the API as native Python methods that return native Python objects.

get_proxy_connection(*headers=None, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_proxy_connection(*bypass_hosts=None, fqdn=None, password=None, password_required=None, port=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **bypass_hosts** (*string*) – Bypass hosts for the proxy connection, property of the request body.
- **fqdn** (*string*) – proxy IP address or DNS-resolvable host name, property of the request body.
- **password** (*string*) – Password for the proxy connection, property of the request body.

- **password_required** (*boolean*) – Indicates whether password configuration is required for Proxy., property of the request body.
- **port** (*integer*) – Port for proxy connection. should be between 1 and 65535, property of the request body.
- **user_name** (*string*) – User name for the proxy connection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.1_Patch_1).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

pxGrid Node API allows the client to retrieve pxGrid information, delete an existing pxGrid node, and approve new pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	ers-sample-client
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No		ERS sample client
status	String	No		Online (XMPP)
auth-Method	String	No		Certificate
groups	String	No		

pxGrid Characterization

Session data Consumption over pxGrid

On a 35 node Cisco ISE deployment with a dedicated primary Policy Administration node (PAN), dedicated secondary PAN, dedicated primary Monitoring and Troubleshooting node (MnT node), dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous Policy Service node (PSN) platforms, there was no delay observed in consuming session data with the following parameters as shown in the table below:

RADIUS Traffic	Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	pxGrid client's delay in consuming session data
Upto 500 transactions per second (TPS)	~2 million	50	No delay

Bulk download time taken

On a 35 node Cisco ISE deployment with a dedicated primary PAN, dedicated secondary PAN, dedicated primary MnT, dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous PSN Platforms, the bulk download time for all the pxGrid clients is shown in the table below:

Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	Time taken for bulk download
2 million	50	~17 minutes

Note: From Cisco ISE Release 3.1, we can use either pxgridnode or pxgridNode in the URL.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_name*

delete_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_px_grid_node_by_name*

get_px_grid_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_px_grid_node_by_id`***`get_px_grid_node(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page`** (*`int`*) – page query parameter. Page number.
- **`size`** (*`int`*) – size query parameter. Number of objects returned per page.
- **`headers`** (*`dict`*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_px_grid_node`***`get_px_grid_node_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page`** (*`int`*) – page query parameter. Page number.
- **`size`** (*`int`*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sg_vn_mapping

class SgVnMapping

Identity Services Engine sgVnMapping API (version: 3.1_Patch_1).

Wraps the Identity Services Engine sgVnMapping API and exposes the API as native Python methods that return native Python objects.

get_sg_vn_mappings(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings*

get_sg_vn_mappings_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings_generator*

create_sg_vn_mapping(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Security Group and Virtual Network mapping.

Parameters

- **id** (*string*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sg_vn_mapping*

bulk_create_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_sg_vn_mappings*

bulk_delete_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_delete`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_delete_sg_vn_mappings`*

`bulk_update_sg_vn_mappings`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update SG-VN Mappings in bulk.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_update`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_update_sg_vn_mappings`*

`get_sg_vn_mapping_by_id`(*id, headers=None, **query_parameters*)

Get Security Group and Virtual Network mapping by id.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sg_vn_mapping_by_id*

update_sg_vn_mapping_by_id(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update Security Group and Virtual Network mapping.

Parameters

- **id** (*basestring*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sg_vn_mapping_by_id*

`delete_sg_vn_mapping_by_id`(*id*, *headers=None*, ***query_parameters*)

Delete Security Group and Virtual Network mapping.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sg_vn_mapping_by_id*

tasks

class Tasks

Identity Services Engine tasks API (version: 3.1_Patch_1).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

get_task_status(*headers=None, **query_parameters*)

get all task status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_task_status_by_id(*task_id, headers=None, **query_parameters*)

Monitor task status.

Parameters

- **task_id** (*basestring*) – taskId path parameter. The id of the task executed before.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry**class Telemetry**

Identity Services Engine telemetry API (version: 3.1_Patch_1).

Wraps the Identity Services Engine telemetry API and exposes the API as native Python methods that return native Python objects.

get_transport_gateway(*headers=None, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_transport_gateway(*enable_transport_gateway=None, url=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **enable_transport_gateway** (*boolean*) – Indicates whether transport gateway is enabled or not., property of the request body.

- **url** (*string*) – URL of transport gateway, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

virtual_network

class VirtualNetwork

Identity Services Engine virtualNetwork API (version: 3.1_Patch_1).

Wraps the Identity Services Engine virtualNetwork API and exposes the API as native Python methods that return native Python objects.

get_virtual_networks(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals

NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks*

get_virtual_networks_generator (*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks_generator*

create_virtual_network(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*string*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`create_virtual_network`*

`bulk_create_virtual_networks`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network in bulk.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_create`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_create_virtual_networks`*

bulk_delete_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_delete_virtual_networks*

bulk_update_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_virtual_networks*

get_virtual_network_by_id(*id, headers=None, **query_parameters*)

Get Virtual Network by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_virtual_network_by_id*

update_virtual_network_by_id(*id, additional_attributes=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*basestring*) – Identifier of the Virtual Network, property of the request body.

- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *additional_attributes=None*, *last_update=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_virtual_network_by_id*

delete_virtual_network_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Virtual Network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_virtual_network_by_id***vn_vlan_mapping****class VnVlanMapping**

Identity Services Engine vnVlanMapping API (version: 3.1_Patch_1).

Wraps the Identity Services Engine vnVlanMapping API and exposes the API as native Python methods that return native Python objects.

get_vn_vlan_mappings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_vn_vlan_mappings`*

`get_vn_vlan_mappings_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *`get_vn_vlan_mappings_generator`*

`create_vn_vlan_mapping`(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mapping.

Parameters

- **`id`** (*string*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **`is_data`** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **`is_default_vlan`** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **`last_update`** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **`max_value`** (*integer*) – Max value, property of the request body.
- **`name`** (*string*) – Name of the Vlan, property of the request body.
- **`vn_id`** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **`vn_name`** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_vn_vlan_mapping*

bulk_create_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_vn_vlan_mappings*

bulk_delete_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_delete_vn_vlan_mappings*

bulk_update_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_vn_vlan_mappings*

get_vn_vlan_mapping_by_id(*id, headers=None, **query_parameters*)

Get VN-Vlan Mapping by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mapping_by_id*

update_vn_vlan_mapping_by_id(*id, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **is_data** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.

- **max_value** (*integer*) – Max value, property of the request body.
- **name** (*string*) – Name of the Vlan, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_vn_vlan_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

Delete VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.2_beta**aci_bindings****class AciBindings**

Identity Services Engine ACIBindings API (version: 3.2_beta).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

The ACI Bindings API allows clients to retrieve bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on the ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip, sgt, vn, psn, learnedFrom, or learnedBy with CONTAINS mode of search.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdc2d9fd69
description	String	No		
ip	String	Yes	Binding IPv4 address. Each binding will be exclusively identified by its IP address and virtual network	10.0.0.1
sgt	String	No	Security Group Tag (SGT) value. The valid range for SGT values is 0-65534	1234
vn	String	Yes	Virtual network. Each binding will be exclusively identified by its IP address and virtual network	vn1234
psn	String	No	Cisco ISE Policy Service node (PSN) IP address	10.86.189.216
learnedFrom	String	Yes	Binding Source	ISE by ACI ACI by ISE
learnedBy	String	Yes	Binding Type	SXP(SXP, 0) STATIC(Static, 1) RADIUS(RADIUS, 2) ACI(ACI, 3)

get_aci_bindings(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.2_beta).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

ACI Settings API allows the client to get and update the ACI Settings. In addition, testing the ACI Domain Manager connection is also possible using the TestACIConnection.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		AciSettings
id	String	No	Resource UUID value		29fb45ab-6a8e-4658-8a28-02521c258178
description	String	No			Aci Settings
enableAci	Boolean	Yes	Enable ACI Integration	false	
isAci50	Boolean	Yes	Enable 5.0 ACI Version	false	
ipAddressHost- Name	String	No	ACI Cluster IP Address / Host name		
adminName	String	No	ACI Cluster Admin name		
adminPassword	String	No	ACI Cluster Admin pass- word		
tenantName	String	No	ACI Cluster Tenant name	ISE	
l3RouteNetwork	String	No	ACI Cluster L3 Route net- work name	L3_ROUTE	
suffixToEpg	String	No	Name Conversion - EPG suffix	SGT	
suffixToSgt	String	No	Name Conversion - SGT suffix	EPG	
allSxpDomain	Boolean	No	SXP Propagation to all the SXP domains	false	
specificSxpDo- main	Boolean	No	SXP Propagation to spe- cific SXP domains	true	
specifixSxpDo- mainList	List	No	Specific SXP domains list	[default]	
isAci51	Boolean	Yes	Enable 5.1 ACI Version	false	
aciipaddress	String	No	ACI Domain manager Ip Address		
aciuserName	String	No	ACI Domain manager Username		
acipassword	String	No	ACI Domain manager Password		
enableData- Plane	Boolean	No	Enable data plane	false	
untaggedPack- etIepgName	String	No	Untagged IEPG packets name	untagged	
defaultSgtName	String	No	Default SGT name	Unknown	
enableEle- mentsLimit	Boolean	No	Enable Elements Limit	false	
maxNu- mIepgFromAci	Inte- ger	No	Max number of IEPGs	1000	
maxNumSgt- ToAci	Inte- ger	No	Max number of SGTs	500	

get_aci_settings(headers=None, **query_parameters)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

test_aci_connectivity(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_aci_settings_by_id(id, aci50=None, aci51=None, aciipaddress=None, acipassword=None,
    aciuser_name=None, admin_name=None, admin_password=None,
    all_sxp_domain=None, default_sgt_name=None, enable_aci=None,
    enable_data_plane=None, enable_elements_limit=None,
    ip_address_host_name=None, l3_route_network=None,
    max_num_iepg_from_aci=None, max_num_sgt_to_aci=None,
    specific_sxp_domain=None, specifix_sxp_domain_list=None,
    suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None,
    untagged_packet_iepg_name=None, headers=None, payload=None,
    active_validation=True, **query_parameters)
```

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.
- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint**class AncEndpoint**

Identity Services Engine ANCEndpoint API (version: 3.2_beta).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
macAddress	String	Yes	MAC address of the endpoint	00:11:22:33:44:55
policy-Name	String	Yes	Policy name to be applied to the endpoint	policy1

Supported ANC API transactions per second

On a 5 node Cisco ISE deployment with 60k sessions or on a 9 node Cisco ISE deployment with 200k/500k sessions, 250 transactions per second (TPS) is supported for any ANC API.

Supported ANC APIs

* `applyEndpointByMacAddress` * `clearEndpointByMacaddress` * `applyEndpointByIpAddress` * `applyEndpointPolicy` * `clearEndpointPolicy`

Deployment	Number of Sessions	Supported ANC APIs TPS
5 nodes	60k	250
9 nodes	200k	250
5 nodes	500k	250

`get_anc_endpoint_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_anc_endpoint_by_id`

`clear_anc_endpoint(additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to clear the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data (list)** – additionalData, property of the request body (list of objects).
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *apply_anc_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **`bulkid`** (*basestring*) – bulkid path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory

class ActiveDirectory

Identity Services Engine ActiveDirectory API (version: 3.2_beta).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

The Active Directory API allows the user to carry out add, delete, and search operations on the active directory domains through Cisco ISE's join points. For example, if you want to connect to the domain cisco.com and retrieve the domain groups, you can carry out the following steps which are also available as APIs: Step 1 Create a domain join point in Cisco ISE. In the "domain" parameter use cisco.com.

Step 2 Get all defined join points and copy your join point's ID from the response.

Step 3 Join all Cisco ISE nodes to the domain. Use the ID received in the Step 2 in the URL. From this point onwards, you can perform several actions. In each action you should specify the joint point ID in the URL, as retrieved in step 2 in the previous configuration task. For example, you can:

- Retrieve the user groups using the joint point ID.

- Retrieve the groups of a specific domain using the join point ID. The domain parameter can be cisco.com or any of its trusted domains. You can use the get all trusted domains operation to retrieve the list.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Version	Description	Revision Modifica- tion	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.4	Support new attributes	advanced- Settings	Added ERSActiveDirectoryAdvancedSettings Attribute 'advancedSettings'
				adAt- tributes	Added ERSActiveDirectoryAt- tributes Attribute 'adAttributes'
				enable- Domain- WhiteList	Added Boolean Attribute 'en- ableDomainWhiteList'
2	1.2	3.1	Support new attributes under ActiveDirectory AdvancedSettings	enable- FailedAuth- Protection	Added Boolean Attribute 'en- ableFailedAuthProtection'
				failedAu- thThresh- old	Added Integer Attribute 'failedAuthThreshold'
				auth Protec- tionType	Added Enum Attribute 'authPro- tectionType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/_ characters	...	Company_users
id	String	No	Resource UUID value	...	af1cd190-7d71-11eb-b02e-ead13cf60dcb
description	String	No	No character restriction	...	Group of Active company users
domain	String	Yes	The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed	...	cisco.com
adScopes-Names	String	No	String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed	Default_Scope	...
enableDomain-WhiteList	Boolean	No	...	true	...
adGroups	List	No	Holds list of AD Groups
• groups	List	No	List of Groups

continues on next page

Table 44 – continued from previous page

• name	String	Yes	Required for each group in the group list with no duplication between groups. All characters are allowed except %	...	cisco.com/operators
• sid	String	Yes	Cisco ISE uses security identifiers (SIDs) for optimization of group membership evaluation. SIDs are useful for efficiency (speed) when the groups are evaluated. All characters are allowed except %	...	S-1-5-32-548
• type	String	No	No character restriction	...	GLOBAL
adAttributes	List	No	Holds list of AD Attributes
• attributes	List	No	List of Attributes
• name	String	Yes	Required for each attribute in the attribute list with no duplication between attributes. All characters are allowed except <%”	...	name1
• type	Enum	Yes	Required for each group in the group list. Allowed values: - STRING, - IP, - BOOLEAN, - INT, - OCTET_STRING	STRING	...

continues on next page

Table 44 – continued from previous page

• internal-Name	String	Yes	Required for each attribute in the attribute list. All characters are allowed except <%”	...	internalName1
• default-Value	String	Yes	Required for each attribute in the attribute list. Can contain an empty string. All characters are allowed except <%”	...	defaultString
advancedSettings	List	No
• rewriteRules	List	No	Identity rewrite is an advanced feature that directs Cisco ISE to manipulate the identity before it is passed to the external Active Directory system. You can create rules to change the identity to a desired format that includes or excludes a domain prefix and/or suffix or other additional markup of your choice
• rowId	Integer	Yes	Required for each rule in the list in serial order	...	0
• rewriteMatch	String	Yes	Required for each rule in the list with no duplication between rules. All characters are allowed except %”	...	exampleMatch0

continues on next page

Table 44 – continued from previous page

• rewriteResult	String	Yes	Required for each rule in the list. All characters are allowed except %”	...	exampleResult0
• enableRewrites	Boolean	No	...	false	...
• enablePassChange	Boolean	No	...	true	...
• enableMachineAuth	Boolean	No	...	true	...
• enableMachineAccess	Boolean	No	...	true	...
• enableDialinPermissionCheck	Boolean	No	...	false	...
• plaintextAuth	Boolean	No	...	false	...
• agingTime	Integer	No	Range 1-8760 hours	5	...
• enableCallbackForDialinClient	Boolean	No	...	false	...
• identityNotInAdBehaviour	Enum	No	Allowed values: - REJECT, - SEARCH_JOINED_FOREST, - SEARCH_ALL	SEARCH_JOINED_FOREST	

continues on next page

Table 44 – continued from previous page

• unreachableDomainsBehaviour	Enum	No	Allowed values: - PROCEED, - DROP	PROCEED	...
• schema	Enum	No	Allowed values: - ACTIVE_DIRECTORY, - CUSTOM-Choose ACTIVE_DIRECTORY schema when the AD attributes defined in AD can be copied to relevant attributes in Cisco ISE. If customization is needed, choose CUSTOM schema. All User info attributes are always set to default value if schema is ACTIVE_DIRECTORY. Values can be changed only for CUSTOM schema	ACTIVE_DIRECTORY	...
• firstName	String	No	User info attribute. All characters are allowed except %	givenName	...
• department	String	No	User info attribute. All characters are allowed except %	department	...
• lastName	String	No	User info attribute. All characters are allowed except %	sn	...

continues on next page

Table 44 – continued from previous page

• organiza- tionalU- nit	String	No	User info at- tribute. All characters are allowed except %	company	...
• jobTitle	String	No	User info at- tribute. All characters are allowed except %	title	...
• locality	String	No	User info at- tribute. All characters are allowed except %	l	...
• email	String	No	User info at- tribute. All characters are allowed except %	mail	...
• stateOr- Province	String	No	User info at- tribute. All characters are allowed except %	st	...
• telephone	String	No	User info at- tribute. All characters are allowed except %	telepho- neNumber	...
• country	String	No	User info at- tribute. All characters are allowed except %	co	...
• streetAd- dress	String	No	User info at- tribute. All characters are allowed except %	streetAddress	...
• enable- FailedAu- th Protec- tion	Boolean	No	Enable prevent AD account lockout due to too many bad password attempts	false	...
• failedAu- thThresh- old	Integer	No	Number of bad password attempts	5	...

continues on next page

Table 44 – continued from previous page

• authProtection-Type	Enum	No	Enable prevent AD account lockout. Allowed values:- WIRELESS, - WIRED, - BOTH	WIRELESS	...
-----------------------	------	----	---	----------	-----

get_active_directory_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

load_groups_from_domain(*id*, *ad_attributes=None*, *ad_scopes_names=None*, *adgroups=None*, *advanced_settings=None*, *description=None*, *domain=None*, *enable_domain_white_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
is_user_member_of_groups(id, additional_data=None, headers=None, payload=None,  
                           active_validation=True, **query_parameters)
```

This API verifies if the user is a member of the given groups.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_trusted_domains(id, headers=None, **query_parameters)
```

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

join_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetches the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory*

`get_active_directory_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

create_active_directory(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_active_directory*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.2_beta).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

The Admin User API allows to retrieve information related to admin users configured on Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	1.1	2.0	Cisco ISE Release 2.3 Admin User

Resource Definition

Attribute	Type	Re- quired	Description	Example Values	De- fault Value
name	String	Yes	Resource Name		
id	String	Yes	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69	
description	String	No			
changePass- word	Boolean	Yes		true	true
email	String	No		email1@domain.com	
includeSys- temAlarm- sInEmail	Boolean	No		false	
inactiveAc- countN- everDisabled	Boolean	No		true	
enabled	Boolean	Yes		false	
external	Boolean	No		true	
customAt- tributes	String	No	Key Value Map	{“MyCustom- Attribute” : “Value1”}	
firstName	String	No			
adminGroups	String	No	Admin Group Names	Super Admin	
lastName	String	No			
password	String	No	The password field doesn’t show the actual password configured. It is hidden with the asterisk (*) symbol		

get_admin_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

allowed_protocols**class AllowedProtocols**

Identity Services Engine AllowedProtocols API (version: 3.2_beta).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

Allowed Protocols API allows the client to add, delete, update, search and perform actions on allowed protocols.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.7	Added support for TEAP	preferredEapProtocol	Added value 'TEAP' to enum attribute preferredEapProtocol
				allowTeap	Added boolean attribute allowTeap
				allowTeapEapMsChapV2	Added boolean attribute allowTeapEapMsChapV2
				allowTeapEapMsChapV2PwdChange	Added boolean attribute allowTeap
				allowTeapEapMsChapV2PwdChangeRetries	Added int attribute allowTeapEapMsChapV2PwdChangeRetries
				allowTeapEapTls	Added boolean attribute allowTeapEapTls

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Device Admin
id	String	No	Resource UUID, Mandatory for update	926901b0-8c01-11e6-996c-525400b48521
description	String	No		Default Allowed Protocol Service Device Admin
processHost-Lookup	Boolean	Yes		true
allowPapAscii	Boolean	No		true
allowChap	Boolean	Yes		false
allowMsChapV1	Boolean	Yes		false
allowMsChapV2	Boolean	Yes		false
allowEapMd5	Boolean	Yes		true
allowLeap	Boolean	Yes		false
allowEapTls	Boolean	Yes		true
allowEapTtls	Boolean	Yes		true
allowEapFast	Boolean	Yes		true
allowPeap	Boolean	Yes		true
allowTeap	Boolean	Yes		true
allowPreferredEapProtocol	Boolean	Yes		true

continues on next page

Table 45 – continued from previous page

eapTlsLBit	Boolean	Yes		false
allowWeakCiphersForEap	Boolean	Yes		false
requireMessageAuth	Boolean	Yes		false
preferredEapProtocol	Enum	No	The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored.	PEAP
eapTls	List	No	The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol	
• allowEapTlsAuthOfExpiredCerts	Boolean	Yes		false
• eapTlsEnableStatelessSessionResume	Boolean	Yes		false
• eapTlsSessionTicketTtl	Integer	No	Time to live. The eapTlsSessionTicketTtl is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
• eapTlsSessionTicketTtlUnits	Enum	No	Time to live time units. The eapTlsSessionTicketTtlUnits is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored.	SECONDS

continues on next page

Table 45 – continued from previous page

• eapTlsSessionTicketPrecentage	Integer	No	The eapTlsSessionTicketPrecentage is required only if eapTlsEnableStatelessSessionResume is true, otherwise it must be ignored	1
peap	List	No	The peap is required only if allowPeap is true, otherwise it must be ignored. The object peap contains the settings for PEAP protocol	
• allowPeapEapMsChapV2	Boolean	Yes		true
• allow-PeapEapMsChapV2PwdChange	Boolean	No	The allow-PeapEapMsChapV2PwdChange is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored	true
• allow-PeapEapMsChapV2PwdChangeRetries	Integer	No	The allow-PeapEapMsChapV2PwdChangeRetries is required only if allowPeapEapMsChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
• allowPeapEapGtc	Boolean	Yes		false
• allowPeapEapGtcPwdChange	Boolean	No	The allowPeapEapGtcPwdChange is required only if allowPeapEapGtc is true, otherwise it must be ignored	false

continues on next page

Table 45 – continued from previous page

<ul style="list-style-type: none"> • allowPeapEapGtcPwdChangeRetries 	Integer	No	The allowPeapEapGtcPwdChangeRetries is required only if allowPeapEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowPeapEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowPeapEapTlsAuthOfExpiredCerts 	Boolean	No	The allowPeapEapTlsAuthOfExpiredCerts is required only if allowPeapEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • requireCryptobinding 	Boolean	Yes		false
<ul style="list-style-type: none"> • allowPeapV0 	Boolean	Yes		false
eapTtls	List	No	The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol	
<ul style="list-style-type: none"> • eapTtlsPapAscii 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsChap 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsMsChapV1 	Boolean	Yes		true
<ul style="list-style-type: none"> • eapTtlsMsChapV2 	Boolean	Yes		true

continues on next page

Table 45 – continued from previous page

• eapT-tlsEapMd5	Boolean	Yes		true
• eapT-tlsEapM-sChapV2	Boolean	Yes		true
• eapT-tlsEapM-sChapV2PwdChange	Boolean	No	The eapTtlsEapM-sChapV2PwdChange is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored	true
• eapT-tlsEapM-sChapV2PwdChangeRetries	Integer	No	The eapTtlsEapM-sChapV2PwdChangeRetries is required only if eapTtlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
eapFast	List	No	The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol	
• allowEap-FastEapM-sChapV2	Boolean	Yes		true
• allowEap-FastEapM-sChapV2PwdChange	Boolean	No	The allowEap-FastEapM-sChapV2PwdChange is required only if allowEap-FastEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 45 – continued from previous page

<ul style="list-style-type: none"> • allowEap-FastEapM-sChapV2PwChangeRetries 	Integer	No	The allowEap-FastEapM-sChapV2PwChangeRetries is required only if eapTlsEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapGtc 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChange 	Boolean	No	The allowEap-FastEapGtcPwChange is required only if allowEap-FastEapGtc is true, otherwise it must be ignored	true
<ul style="list-style-type: none"> • allowEap-FastEapGtcPwChangeRetries 	Integer	No	The allowEap-FastEapGtcPwChangeRetries is required only if allowEapFastEapGtc is true, otherwise it must be ignored. Valid range is 0-3	1
<ul style="list-style-type: none"> • allowEap-FastEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowEap-FastEapTlsAuthOfExpiredCerts 	Boolean	No	The allowEap-FastEapTlsAuthOfExpiredCerts is required only if allowEap-FastEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastEnableEAPChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • eapFastUsePacs 	Boolean	Yes		true

continues on next page

Table 45 – continued from previous page

• eapFastUsePacsTunnelPacTtl	Integer	No	The eapFastUsePacsTunnelPacTtl is required only if eapFastUsePacs is true, otherwise it must be ignored	7776000
• eapFastUsePacsTunnelPacTtlUnits	Enum	No	The eapFastUsePacsTunnelPacTtlUnits is required only if eapFastUsePacs is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsUseProactivePacUpdatePercentage	Integer	No	The eapFastUsePacsUseProactivePacUpdatePercentage is required only if eapFastUsePacs is true, otherwise it must be ignored	10
• eapFastUsePacsAllowAnonymProvisioning	Boolean	No	The eapFastUsePacsAllowAnonymProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAllowAuthenProvisioning	Boolean	No	The eapFastUsePacsAllowAuthenProvisioning is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning	Boolean	No	The eapFastUsePacsReturnAccessAcceptAfterAuthenticatedProvisioning is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false

continues on next page

Table 45 – continued from previous page

• eapFastUsePacsAcceptClientCert	Boolean	No	The eapFastUsePacsAcceptClientCert is required only if eapFastUsePacsAllowAuthenProvisioning is true, otherwise it must be ignored	false
• eapFastUsePacsAllowMachineAuthentication	Boolean	No		false
• eapFastUsePacsMachinePacTtl	Integer	No	The eapFastUsePacsMachinePacTtl is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored	1
• eapFastUsePacsMachinePacTtlUnits	Enum	No	The eapFastUsePacsMachinePacTtlUnits is required only if eapFastUsePacsAllowMachineAuthentication is true, otherwise it must be ignored.	SECONDS
• eapFastUsePacsStatelessSessionResume	Boolean	No	The eapFastUsePacsStatelessSessionResume is required only if eapFastUsePacs is true, otherwise it must be ignored	false
• eapFastUsePacsAuthorizationPacTtl	Integer	No	The eapFastUsePacsAuthorizationPacTtl is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored	1

continues on next page

Table 45 – continued from previous page

<ul style="list-style-type: none"> • eapFastUsePacsAuthorizationPacTtlUnits 	Enum	No	The eapFastUsePacsAuthorizationPacTtlUnits is required only if eapFastUsePacsStatelessSessionResume is true, otherwise it must be ignored.	SECONDS
<ul style="list-style-type: none"> • eapFastDontUsePacsAcceptClientCert 	Boolean	No	The eapFastDontUsePacsAcceptClientCert is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
<ul style="list-style-type: none"> • eapFastDontUsePacsAllowMachineAuthentication 	Boolean	No	The eapFastDontUsePacsAllowMachineAuthentication is required only if eapFastUsePacs is FALSE, otherwise it must be ignored	false
teap	List	No	The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol	
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChange 	Boolean	No	The allowTeapEapM-sChapV2PwdChange is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored	true

continues on next page

Table 45 – continued from previous page

<ul style="list-style-type: none"> • allowTeapEapM-sChapV2PwdChangeRetries 	Integer	No	The allowTeapEapM-sChapV2PwdChangeRetries is required only if allowTeapEapM-sChapV2 is true, otherwise it must be ignored. Valid range is 0-3	3
<ul style="list-style-type: none"> • allowTeapEapTls 	Boolean	Yes		true
<ul style="list-style-type: none"> • allowTeapEapTlsAuthOfExpiredCerts 	Boolean	No	The allowTeapEapTlsAuthOfExpiredCerts is required only if allowTeapEapTls is true, otherwise it must be ignored	false
<ul style="list-style-type: none"> • acceptClientCertDuringTunnelEst 	Boolean	Yes		true
<ul style="list-style-type: none"> • enableEapChaining 	Boolean	Yes		false
<ul style="list-style-type: none"> • allowDowngradeMsk 	Boolean	Yes		false

get_allowed_protocol_by_name(name, headers=None, **query_parameters)

This API allows the client to get an allowed protocol by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_name`***`get_allowed_protocol_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_allowed_protocol_by_id`*

```
update_allowed_protocol_by_id(id, allow_chap=None, allow_eap_fast=None, allow_eap_md5=None,
                             allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None,
                             allow_ms_chap_v1=None, allow_ms_chap_v2=None,
                             allow_pap_ascii=None, allow_peap=None,
                             allow_preferred_eap_protocol=None, allow_teap=None,
                             allow_weak_ciphers_for_eap=None, description=None,
                             eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None,
                             name=None, peap=None, preferred_eap_protocol=None,
                             process_host_lookup=None, require_message_auth=None, teap=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_ttls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols_generator*

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.

- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
create(allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None,
allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None,
allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None,
allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None,
eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None,
process_host_lookup=None, require_message_auth=None, teap=None, headers=None,
payload=None, active_validation=True, **query_parameters)
```

Alias for *create_allowed_protocol*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy

class AncPolicy

Identity Services Engine AncPolicy API (version: 3.2_beta).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

Adaptive Network Control (ANC) provides the ability to create network endpoint authorization controls based on ANC policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.1	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource ID	test
description	String	No		
action	Enum	Yes	<ul style="list-style-type: none"> • QUAR-ANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. • PORT-BOUNCE: Resets the port on the network device to which the endpoint is connected • SHUT-DOWN : Shuts down the port on the network device to which the endpoint is connected • RE_AUTHENTICATE: Re-authenticates the session from the endpoint 	

get_anc_policy_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_name`*

`get_anc_policy_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an ANC policy by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_anc_policy_by_id`*

```
update_anc_policy_by_id(id, actions=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are ‘QUARANTINE’, ‘PORTBOUNCE’, ‘SHUTDOWN’ and ‘RE_AUTHENTICATE’).
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, actions=None, name=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for *update_anc_policy_by_id*

```
delete_anc_policy_by_id(id, headers=None, **query_parameters)
```

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy_generator*

create_anc_policy(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_anc_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_policy(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.2_beta).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

Authorization Profile API allows the client to add, delete, update, search and perform actions on authorization profiles.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revi- sion Mod- ifica- tion	Revision Modification
				At- tribute	Description
0	1.0	2.2	Initial Cisco ISE Version		
1	1.1	2.3	Support new attributes under common tasks	ac- cessType	Added Attribute 'accessType'. Default value:'ACCESS_ACCEPT', additional values: 'ACCESS_REJECT'
				au- thzPro- file- Type	Added Attribute 'authzProfileType' to differentiate between types of authorization profiles. Default value:'SWITCH' (used for Standard Authorization Profiles) , additional values:'TACACS', 'TRUSTSEC'
				reauth	Added Attribute 'reauth' to determine reauthentication policy
				we- bRedi- rec- tion	Added Attribute 'webRedirection' to support selection of portal redirection
				acl	Added String Attribute 'acl'
				track- Move- ment	Added Boolean Attribute 'trackMovement'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID value		id
description	String	No			description
vlan	List	No			
• nameID	String	Yes			vlanName
• tagID	Integer	Yes	Valid range is 0-31		1
airespaceACL	String	No			ACL
webRedirection	List	No			
• WebRedirectionType	String	Yes	Value MUST be one of the following: CentralizedWebAuth, HotSpot, NativeSupplicantProvisioning, ClientProvisioning. The WebRedirectionType must fit the portalName		Centralized-WebAuth
• acl	String	Yes			acl
• portal-Name	String	Yes	A portal that exist in the DB and fits the WebRedirectionType		Sponsored Guest Portal (default)
• staticIPHost-Name-FQDN	String	No			10.56.54.200

continues on next page

Table 46 – continued from previous page

• displayC- ertifi- catesRe- newalMes- sages	Boolean	No	The displayC- ertificatesRe- newalMes- sages is mandatory when ‘We- bRedirection- Type’ value is ‘Central- izedWebAuth’. For all other ‘WebRedi- rectionType’ values the field must be ignored	true	
accessType	Enum	No	Allowed Values: AC- CESS_ACCEPT, AC- CESS_REJECT	AC- CESS_ACCEPT	
authzProfile- Type	Enum	No	Allowed Val- ues: SWITCH, TRUSTSEC, TACACS	SWITCH	
			SWITCH is used for Standard Au- thorization Profiles		
profileName	String	No		Cisco	
acl	String	No			aclfilter
daclName	String	No			PER- MIT_ALL_IPV4_TRAFFIC
autoSmartPort	String	No			autoSmartPort
interfaceTem- plate	String	No			interfaceTem- plate
ipv6ACLFILTER	String	No			ipv6ACLFILTER
avcProfile	String	No			avcProfile
asaVpn	String	No			Cisco:cisco- call-type
trackMove- ment	Boolean	No		false	
serviceTem- plate	Boolean	No		false	
easywiredSes- sionCandidate	Boolean	No		false	
voiceDomain- Permission	Boolean	No		false	
neat	Boolean	No		false	
webAuth	Boolean	No		false	

continues on next page

Table 46 – continued from previous page

macSecPolicy	Enum	No	Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE		MUST_SECURE
reauth	List	No			
• connectivity	Enum	Yes	Allowed Values: DEFAULT, RA-DIUS_REQUEST		RA-DIUS_REQUEST
• timer	Integer	Yes	Valid range is 1-65535		1800
advancedAttributes	List	No			
• leftHand-SideDictionary-Attribute	List	Yes	Left side Dictionary and Attribute		
• dictionary-Name	String	Yes	Dictionary name		
• attribute-Name	String	Yes	Attribute name		
• rightHand-SideAttribute-Value	List	Yes	Attribute value can be of type AttributeValue or Advanced-DictionaryAttribute. For AttributeValue the value is String, For Advanced-Dictionary-Attribute the value is dictionaryName and attributeName properties		
ipv6DaclName	String	No			PERMIT_ALL_IPV6_TRAFFIC
airespaceIPv6ACL	String	No			ACL6

`get_authorization_profile_by_name(name, headers=None, **query_parameters)`

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_id*

update_authorization_profile_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.

- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_authorization_profile_by_id*

delete_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_authorization_profile_by_id*

get_authorization_profiles(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles***get_authorization_profiles_generator**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_authorization_profiles_generator*

```
create_authorization_profile(access_type=None, acl=None, advanced_attributes=None,
                             agentless_posture=None, airespace_acl=None,
                             airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
                             auto_smart_port=None, avc_profile=None, dacl_name=None,
                             description=None, easywired_session_candidate=None, id=None,
                             interface_template=None, ipv6_acl_filter=None,
                             ipv6_dacl_name=None, mac_sec_policy=None, name=None,
                             neat=None, profile_name=None, reauth=None, service_template=None,
                             track_movement=None, vlan=None, voice_domain_permission=None,
                             web_auth=None, web_redirection=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API creates an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.

- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_authorization_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

byod_portal**class ByodPortal**

Identity Services Engine BYODPortal API (version: 3.2_beta).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

BYOD Portal API provides the ability to Create, Read, Update, Delete and Search BYOD portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		BYOD Portal (default)
id	String	No	Resource UUID, mandatory for update		9a9b910c-54d3-44a4-a3c3-dd007c171599

continues on next page

Table 47 – continued from previous page

description	String	No			Default portal and user experience used when employees register a personal device on the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?po54d3-44a4-a3c3-dd007c171599
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	BYOD	
settings	List	No	Defines all of the settings groups available for a BYOD		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		["eth0", "bond0"]

continues on next page

Table 47 – continued from previous page

• certifi- cate- Group- Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• end- pointI- dentity- Group	String	Yes	Unique Id of the endpoint identity group where user's devices will be added. Used only in Hotspot Portal		
• display- Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback- Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alway- sUsed- Language	String	No	Used when displayLang = ALWAYSUSE		English
• byodSet- tings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		
• byodWel- comeSet- tings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enable- BYOD	Boolean	No		true	
• en- ableGues- tAccess	Boolean	No		false	

continues on next page

Table 47 – continued from previous page

• re-requireMDM	Boolean	No		false	
• includeAup	Boolean	No		true	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No		false	
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodRegistrationSettings	List	No	Configuration of BYOD endpoint Registration step configuration		
• showDeviceID	Boolean	No	Display Device ID field during registration	true	
• endpointIdentityGroupId	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521

continues on next page

Table 47 – continued from previous page

• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Au- thentication Success where should device be redirected.	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		Redirect URL
• support- InfoSet- tings	List	No	Configuration of BYOD endpoint wel- come step configuration		
• in- cludeSup- portIn- foPage	Boolean	No		false	
• in- cludeMacAddr	Boolean	No		false	
• in- cludeIpAd- dress	Boolean	No		false	
• include- BrowserUser- Agent	Boolean	No		false	
• include- Policy- Server	Boolean	No		false	
• include- Failure- Code	Boolean	No		false	

continues on next page

Table 47 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available for a BYOD		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 47 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 47 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			BYOD Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 47 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_byod_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_byod_portal_by_id*

update_byod_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a BYOD portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
              portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
              **query_parameters)
```

Alias for `update_byod_portal_by_id`

```
delete_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_byod_portal_by_id`

```
get_byod_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                 headers=None, **query_parameters)
```

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal*

get_byod_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_byod_portal*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

backup_and_restore**class BackupAndRestore**

Identity Services Engine Backup And Restore API (version: 3.2_beta).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_last_status`(*headers=None, **query_parameters*)Alias for `get_last_config_backup_status`**`restore_config_backup`**(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **`backup_encryption_key`** (*string*) – The encryption key which was provided at the time of taking backup., property of the request body.
- **`repository_name`** (*string*) – Name of the configured repository where the backup file exists., property of the request body.
- **`restore_file`** (*string*) – Name of the backup file to be restored on ISE node., property of the request body.
- **`restore_include_adeos`** (*string*) – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

restore(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *restore_config_backup*

update_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description (string)** – Description of the backup., property of the request body.
- **backup_encryption_key (string)** – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name (string)** – The backup file will get saved with this name., property of the request body.
- **end_date (string)** – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency (string)** – frequency, property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.

- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘DISABLE’ and ‘ENABLE’.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – weekDay, property of the request body. Available values are ‘FRI’, ‘MON’, ‘SAT’, ‘SUN’, ‘THU’, ‘TUE’ and ‘WED’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None,
        frequency=None, month_day=None, repository_name=None, start_date=None, status=None,
        time=None, week_day=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.2_beta).

Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

The certificate profile API allows the client to add, search and perform actions on the certificate profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.4	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Certificate_Profile
id	String	No	Resource UUID		f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No			
allowedAsUserName	Boolean	No	To be set true or false	false	
external-identity-store-name	String	No	Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen	[not applicable]	[not applicable]
certificate-attribute-name	ENUM	No	Attribute name of the Certificate Profile - used only when CERTIFICATE is chosen in usernameFrom. Allowed values: - SUBJECT_COMMON_NAME - SUBJECT_ALTERNATIVE_NAME - SUBJECT_SERIAL_NUMBER - SUBJECT - SUBJECT_ALTERNATIVE_NAME_OTHER_NAME - SUBJECT_ALTERNATIVE_NAME_EMAIL - SUBJECT_ALTERNATIVE_NAME_DNS. - Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN	SUBJECT_COMMON_NAME	
match-Mode	ENUM	No	Match mode of the Certificate Profile. Allowed values: NEVER, RESOLVE_IDENTITY_AMBIGUITY, BINARY_COMPARISON	NEVER	
username-From	ENUM	No	The attribute in the certificate where the user name should be taken from.	CERTIFICATE	

get_certificate_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_name*

`get_certificate_profile_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_id*

```
update_certificate_profile_by_id(id, allowed_as_user_name=None,
                                certificate_attribute_name=None, description=None,
                                external_identity_store_name=None, match_mode=None,
                                name=None, username_from=None, headers=None,
                                payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allowed_as_user_name=None*, *certificate_attribute_name=None*, *description=None*, *external_identity_store_name=None*, *match_mode=None*, *name=None*, *username_from=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_certificate_profile_by_id*

get_certificate_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile*

get_certificate_profile_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.

- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_certificate_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificate_template**class CertificateTemplate**

Identity Services Engine CertificateTemplate API (version: 3.2_beta).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

The certificate template API provides the ability to search for certificate templates.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.2	Initial Cisco ISE Version	

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
raProfile-Name	String	Yes	RA profile for the Certificate template	ISE internal CA
keySize	Integer	No	Key Size of the Certificate Template	2048 1024
validity	Integer	No	Validity period of the Certificate Template: Valid Range 21 - 3652	730

get_certificate_template_by_name(name, headers=None, **query_parameters)

This API allows the client to get a certificate template by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_name*

get_certificate_template_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *`get_certificate_template_generator`***`get_version`**(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.2_beta).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csrs_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
generate_csr(allow_wild_card_cert=None, certificate_policies=None, digest_type=None,
             hostnames=None, key_length=None, key_type=None, portal_group_tag=None,
             san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None,
             subject_common_name=None, subject_country=None, subject_org=None,
             subject_org_unit=None, subject_state=None, used_for=None, headers=None,
             payload=None, active_validation=True, **query_parameters)
```

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following parameters are present in POST request body

PARAMETER DESCRIPTION

EXAMPLE hostnames List of Cisco ISE node hostnames for which CSRs should be generated

“hostnames”: [“ise-host1”, “ise-host2”] allowWildCardCert Allow use of WildCards in certificates

“allowWildCardCert”: false keyLength * required Length of the key used for CSR generation (required).

“keyLength”: “512” keyType * required Type of key used for CSR generation either RSA or ECDSA (required).

“keyType”: “RSA” digestType * required Hash algorithm used for signing CSR (required).

“digestType”: “SHA-256” usedFor * required Certificate usage (required).

“usedFor”: “MULTI-USE” certificatePolicies Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs.

“certificatePolicies”: “Certificate Policies” subjectCommonName * required Certificate common name (CN) (required).

“subjectCommonName”: “\$FQDN\$” subjectOrgUnit Certificate organizational unit (OU).

“subjectOrgUnit”: “Engineering” subjectOrg Certificate organization (O).

“subjectOrg”: “Cisco” subjectCity Certificate city or locality (L).

“subjectCity”: “San Jose” subjectState Certificate state (ST).

“subjectState”: “California” subjectCountry Certificate country (C).

“subjectCountry”: “US” sanDNS Array of SAN (Subject Alternative Name) DNS entries (optional).

“sanDNS”: [“ise.example.com”] sanIP Array of SAN IP entries (optional).

“sanIP”: [“1.1.1.1”] sanURI Array of SAN URI entries (optional).

“sanURI”: [“https://1.1.1.1”] sanDir Array of SAN DIR entries (optional).

“sanDir”: [“CN=AAA,DC=COM,C=IL”] portalGroupTag Portal Group Tag when using certificate for PORTAL service

“portalGroupTag”: “Default Portal Certificate Group”

NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames

When certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – keyType, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.

- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.
- **used_for** (*string*) – usedFor, property of the request body. Available values are ‘ADMIN’, ‘DTLS- AUTH’, ‘EAP-AUTH’, ‘IMS’, ‘MULTI-USE’, ‘PORTAL’, ‘PXGRID’ and ‘SAML’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname*, *id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*, ***query_parameters*)

Response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type*DownloadResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node for given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_csr_by_id`(*host_name, id, headers=None, **query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on given HostName and ID.

Parameters

- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host of which CSR's should be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the Certificate Signing Request to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`regenerate_ise_root_ca`(*remove_existing_ise_intermediate_csr=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API initiates regeneration of Cisco ISE root CA certificate chain. Response contains ID which can be used to track the status. Setting “removeExistingISEIntermediateCSR” to true removes existing Cisco ISE Intermediate CSR.

Parameters

- **remove_existing_ise_intermediate_csr** (*boolean*) – Setting this attribute to true removes existing Cisco ISE Intermediate CSR, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

renew_certificates(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API initiates regeneration of certificates. Response contains ID which can be used to track the status.

Parameters

- **cert_type** (*string*) – certType, property of the request body. Available values are 'IMS' and 'OCSP'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
portal_group_tag=None, pxgrid=None, radius=None, saml=None,
validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
**query_parameters)
```

Bind CA Signed Certificate. NOTE: This API requires an

existing Certificate Signing Request, and the root certificate must already be trusted. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body **PARAMETER DESCRIPTION EXAMPLE** name Friendly name of the certificate. “name”: “CA Signed Certificate” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

```
{sub(/
```

/, “”); printf “%sn”, \$0;}’ <<your .pem file>>

to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid binding of expired certificates (not Secure). “allowOutOfDateCert”: true allowReplacementOfCertificates * required Allow Replacement of certificates (required). “allowReplacementOfCertificates”: true allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADIUS server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”: false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal Certificate Group” validateCertificateExtensions Validate Certificate Extensions “validateCertificateExtensions”: false Following roles can be used in any combinations **ROLE DEFAULT WARNING** Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the
Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

data(string): Signed certificate data (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

host_name(string): Name of Host whose CSR ID has been provided (required), property of the request body.

id(string): ID of the generated CSR (required), property of the request body.

ims(boolean): Use certificate for the Cisco ISE Messaging Service, property of the request body.

name(string): Friendly Name of the certificate, property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

*****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Raises:

`TypeError`: If the parameter types are incorrect. `MalformedRequest`: If the request body created is invalid. `ApiError`: If the Identity Services Engine cloud returns an error.

export_system_certificate(*export=None, id=None, password=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Export System Certificate. Following parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE
id * required ID of a System Certificate (required). "id": "CERT-ID" export One of the below option is required "CERTIFICATE" : Export only certificate without private key "CERTIFICATE_WITH_PRIVATE_KEY" : Export both certificate and private key ("certificatePassword" is required). "export": "CERTIFICATE_WITH_PRIVATE_KEY" password * required Certificate password (required if "export" : CERTIFICATE_WITH_PRIVATE_KEY). Password constraints: Alphanumeric Minimum of 8 Characters Maximum of 100 Characters "password": "certificate password" NOTE: The response of this API carries a ZIP file containing the certificate and private key if "export" : "CERTIFICATE_WITH_PRIVATE_KEY" in the request. If "export" : "CERTIFICATE" in request body, the response carries a ZIP file containing only the certificate. WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are 'CERTIFICATE' and 'CERTIFICATE_WITH_PRIVATE_KEY'.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
generate_self_signed_certificate(admin=None, allow_extended_validity=None,
                                allow_portal_tag_transfer_for_same_subject=None,
                                allow_replacement_of_certificates=None,
                                allow_replacement_of_portal_group_tag=None,
                                allow_role_transfer_for_same_subject=None,
                                allow_san_dns_bad_name=None,
                                allow_san_dns_non_resolvable=None,
                                allow_wild_card_certificates=None, certificate_policies=None,
                                digest_type=None, eap=None, expiration_ttl=None,
                                expiration_ttl_unit=None, host_name=None, key_length=None,
                                key_type=None, name=None, portal=None,
                                portal_group_tag=None, pxgrid=None, radius=None, saml=None,
                                san_dns=None, san_ip=None, san_uri=None, subject_city=None,
                                subject_common_name=None, subject_country=None,
                                subject_org=None, subject_org_unit=None, subject_state=None,
                                headers=None, payload=None, active_validation=True,
                                **query_parameters)
```

Generate Self-signed Certificate NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. NOTE: Wildcard certificate and SAML certificate can be generated only on PSPAN or Standalone Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE `hostName` * required Hostname or FQDN of the node in which certificate needs to be created (required). `hostName`: "ise-node-001" name Friendly name of the certificate. `name`: "Self-signed System Certificate" `subjectCommonName` Certificate common name (CN) NOTE: 1. CN is Mandatory if SAN not configured. 2. Subject can contain a multi- valued CN. For multi-valued RDNs, follow the format "CN=value1, CN=value2" `subjectCommonName`: "\$FQDN\$" `subjectOrgUnit` Certificate organizational unit (OU) NOTE: Subject can contain a multi-valued OU. For multi- valued RDNs, follow the format "OU=value1, OU=value2" `subjectOrgUnit`: "Engineering" `subjectOrg` Certificate organization (O) NOTE: Subject can contain a multi-valued O fields. For multi-valued RDNs, follow the format "O=value1, O=value2" `subjectOrg`: "Cisco" `subjectCity` Certificate city or locality (L) `subjectCity`: "San Jose" `subjectState` Certificate state (ST) `subjectState`: "California" `subjectCountry` Certificate country (C) `subjectCountry`: "US" `sanDNS` Array of SAN (Subject Alternative Name) DNS entries `sanDNS`: ["ise.example.com"] `sanIP` Array of SAN IP entries `sanIP`: ["1.1.1.1"] `sanURI` Array of SAN URI entries `sanURI`: ["https://1.1.1.1"] `keyType` * required Algorithm to use for certificate public key creation (required). `keyType`: "RSA" `keyLength` * required Bit size of the public key (required). `keyLength`: "4096" `digestType` * required Digest to sign with (required). `digestType`: "SHA-384" `certificatePolicies` Certificate policy OID or list of OIDs that the certificate should conform to. Use comma or space to separate the OIDs. `certificatePolicies`: "Certificate Policies" `expirationTTL` * required Certificate expiration value (required). NOTE: Expiration TTL should be within Unix time limit `expirationTTL`: 2 `expirationTTLUnit` * required Certificate expiration unit (required). `expirationTTLUnit`: "years" `admin` Use certificate to authenticate the Cisco ISE Admin Portal `admin`: false `eap` Use certificate for EAP protocols that use SSL/TLS tunneling `eap`: false `radius` Use certificate for RADSec server `radius`: false `pxgrid` Use certificate for the pxGrid Controller `pxgrid`: false `saml` Use certificate for SAML Signing `saml`: false `portal` Use certificate for portal `portal`: false `portalGroupTag` Portal Group Tag for using certificate with portal role `portalGroupTag`: "Default Portal Certificate Group" `allowReplacementOfPortalGroupTag` * required Allow Replacement of Portal Group Tag (required). `allowReplacementOfPortalGroupTag`: true `allowWildCardCertificates` Allow use of WildCards in certificates `allowWildCardCertificates`: false `allowReplacementOfCertificates` * required Allow replacement of certificates (required). `allowReplacementOfCertificates`: true `allowExtendedValidity` * required Allow generation of self-signed

certificate with validity greater than 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject * required Allow the transfer of roles to certificates with same subject (required). If the matching certificate on Cisco ISE has either admin or portal role and if request has admin or portal role selected along with allowRoleTransferForSameSubject parameter as true, self- signed certificate would be generated with both admin and portal role enabled “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject * required Acquire the group tag of the matching certificate (required). If the request portal group tag is different from the group tag of matching certificate (If matching certificate in Cisco ISE has portal role enabled), self- signed certificate would be generated by acquiring the group tag of matching certificate if allowPortalTagTransferForSameSubject parameter is true “allowPortalTagTransferForSameSubject”: true allowSanDnsBadName * required Allow generation of self-signed certificate with bad Common Name & SAN Values [like “example.org.”,”invalid.”,”test.”,”localhost” ,etc.] (required). SECURITY ALERT: It is recommended to use “allowSanDnsBadName”: false to avoid generation of certificates with bad Common Name & SAN Values which are not secure “allowSanDnsBadName”: true allowSanDnsNonResolvable * required Allow generation of self-signed certificate with non resolvable Common Name or SAN Values (required). “allowSanDnsNonResolvable”: true ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. SAML False SAML cannot be used with other Usage. .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_extended_validity** (*boolean*) – Allow generation of self-signed certificate with validity greater than 398 days, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_certificates** (*boolean*) – Allow Replacement of certificates, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag, property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **allow_san_dns_bad_name** (*boolean*) – Allow usage of SAN DNS Bad name, property of the request body.
- **allow_san_dns_non_resolvable** (*boolean*) – Allow use of non resolvable Common Name or SAN Values, property of the request body.
- **allow_wild_card_certificates** (*boolean*) – Allow Wildcard Certificates, property of the request body.
- **certificate_policies** (*string*) – Certificate Policies, property of the request body.
- **digest_type** (*string*) – Digest to sign with, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl** (*integer*) – Certificate expiration value, property of the request body.

- **expiration_ttl_unit** (*string*) – Certificate expiration unit, property of the request body. Available values are ‘days’, ‘months’, ‘weeks’ and ‘years’.
- **host_name** (*string*) – Hostname of the Cisco ISE node in which self-signed certificate should be generated., property of the request body.
- **key_length** (*string*) – Bit size of public key, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – Algorithm to use for certificate public key creation, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **name** (*string*) – Friendly name of the certificate., property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **san_dns** (*list*) – Array of SAN (Subject Alternative Name) DNS entries, property of the request body (list of strings).
- **san_ip** (*list*) – Array of SAN IP entries, property of the request body (list of strings).
- **san_uri** (*list*) – Array of SAN URI entries, property of the request body (list of strings).
- **subject_city** (*string*) – Certificate city or locality (L), property of the request body.
- **subject_common_name** (*string*) – Certificate common name (CN), property of the request body.
- **subject_country** (*string*) – Certificate country (C), property of the request body.
- **subject_org** (*string*) – Certificate organization (O), property of the request body.
- **subject_org_unit** (*string*) – Certificate organizational unit (OU), property of the request body.
- **subject_state** (*string*) – Certificate state (ST), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
import_system_certificate(admin=None, allow_extended_validity=None,
                        allow_out_of_date_cert=None,
                        allow_portal_tag_transfer_for_same_subject=None,
                        allow_replacement_of_certificates=None,
                        allow_replacement_of_portal_group_tag=None,
                        allow_role_transfer_for_same_subject=None,
                        allow_sha1_certificates=None, allow_wild_card_certificates=None,
                        data=None, eap=None, ims=None, name=None, password=None,
                        portal=None, portal_group_tag=None, private_key_data=None,
                        pxgrid=None, radius=None, saml=None,
                        validate_certificate_extensions=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE:

The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. “name”: “System certificate” password * required Password of the certificate to be imported (required). “password”: “certificate password” data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required).

Use awk ‘NF {sub(/

/, “”); printf “%sn”, \$0;}’ <<your

.pem file>> to extract data from certificate file. “data”: “Plain-text contents of the certificate file.” privateKeyData * required Plain-text contents of the private key file. Every space needs to be replaced with newline escape sequence (

) (required). Use awk ‘NF

{sub(/

/, “”); printf “%sn”, \$0;}’ <<your .pem file>>

to extract privateKeyData from private key file. “data”: “Plain-text contents of the private key file.” allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use “allowOutOfDateCert”: false to avoid import of expired certificates (not Secure). “allowOutOfDateCert”: true allowSHA1certificates * required Allow import of certificate with signature that uses the SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use “allowSHA1certificates”: false to avoid import of SHA1 based certificates (less secure). “allowSHA1certificates”: true allowExtendedValidity * required Allow the certificates greater than validity of 398 days (required). “allowExtendedValidity”: true allowRoleTransferForSameSubject Allow the transfer of roles to certificates with same subject “allowRoleTransferForSameSubject”: true allowPortalTagTransferForSameSubject Acquire the group tag of the matching certificate “allowPortalTagTransferForSameSubject”: true admin Use certificate to authenticate the Cisco ISE Admin Portal “admin”: false eap Use certificate for EAP protocols that use SSL/TLS tunneling “eap”: false radius Use certificate for RADSec server “radius”: false pxgrid Use certificate for the pxGrid Controller “pxgrid”: false ims Use certificate for the Cisco ISE Messaging Service “ims”: false saml Use certificate for SAML Signing “saml”: false portal Use certificate for portal “portal”:

false portalGroupTag Portal Group Tag for using certificate with portal role “portalGroupTag”: “Default Portal certificate Group” allowReplacementOfPortalGroupTag * required Allow Replacement of Portal Group Tag (required). “allowReplacementOfPortalGroupTag”: true allowWildcardcertificates Allow use of WildCards in certificates “allowWildcardcertificates”: false validatecertificateExtensions Validate certificate extensions “validatecertificateExtensions”: false Following roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the

Cisco ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of

certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_portal_tag_transfer_for_same_subject(boolean):

Allow overwriting the portal tag from matching certificate of same subject, property of the request body.

allow_replacement_of_certificates(boolean): Allow

Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow

Replacement of Portal Group Tag (required), property of the request body.

allow_role_transfer_for_same_subject(boolean): Allow

transfer of roles for certificate with matching subject , property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

allow_wild_card_certificates(boolean): Allow Wildcard

certificates, property of the request body.

data(string): Certificate Content (required), property

of the request body.

eap(boolean): Use certificate for EAP protocols that use

SSL/TLS tunneling, property of the request body.

ims(boolean): Use certificate for the Cisco ISE

Messaging Service, property of the request body.

name(string): Name of the certificate, property of the

request body.

password(string): Certificate Password (required),,

property of the request body.

portal(boolean): Use for portal, property of the request

body.

portal_group_tag(string): Set Group tag, property of the request body.

private_key_data(string): Private Key data (required), property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate certificate extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.

- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificate_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API provides details of a System Certificate of a particular node based on given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **id** (*basestring*) – id path parameter. ID of the system certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_system_certificate(*host_name, id, admin=None, allow_portal_tag_transfer_for_same_subject=None, allow_replacement_of_portal_group_tag=None, allow_role_transfer_for_same_subject=None, description=None, eap=None, expiration_ttl_period=None, expiration_ttl_units=None, ims=None, name=None, portal=None, portal_group_tag=None, pxgrid=None, radius=None, renew_self_signed_certificate=None, saml=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update a System Certificate. NOTE: Renewing a certificate causes an application server restart on the selected node. NOTE: Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body

PARAMETER	DESCRIPTION	EXAMPLE
name	Friendly name of the certificate.	"name": "System Certificate"
description	Description of the certificate	"description": "Description of certificate"
admin	Use certificate to authenticate the Cisco ISE Admin Portal	"admin": false
eap	Use certificate for EAP protocols that use SSL/TLS tunneling	"eap": false
radius	Use certificate for RADIUS server	"radius": false
pxgrid	Use certificate for the pxGrid Controller	"pxgrid": false
ims	Use certificate for the Cisco ISE Messaging Service	"ims": false
saml	Use certificate for SAML Signing	"saml": false
portal	Use certificate for portal	"portal": false
portalGroupTag	Portal Group Tag for using certificate with portal role	"portalGroupTag": "Default Portal Certificate Group"
allowReplacementOfPortalGroupTag	* required Allow Replacement of Portal Group Tag (required).	"allowReplacementOfPortalGroupTag": true
allowRoleTransferForSameSubject	* required t Allow transfer of roles to certificates with same subject (required).	"allowRoleTransferForSameSubject": true
allowPortalTagTransferForSameSubject	* required Acquire group tag of the matching certificate (required).	"allowPortalTagTransferForSameSubject": true
renewSelfSignedCertificate	Renew Self- signed Certificate	"renewSelfSignedCertificate": false
expirationTTLPeriod	Expiration Period	"expirationTTLPeriod": 365
expirationTTLUnits	Expiration Units in one of the below formats days / weeks / months / years	"expirationTTLUnits": "days"

Following roles can be used in any combinations

ROLE	DEFAULT	WARNING
Admin	False	Enabling Admin role for this certificate causes an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates
EAP	Authentication	False Only one system certificate can be used for EAP. Assigning EAP to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
RADIUS	DTLS	False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate removes the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates
SAML	False	SAML cannot be used with other Usage. Enabling SAML unchecks all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the Cisco ISE Admin Portal, property of the request body.
- **allow_portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **allow_role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject, property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.
- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are 'days', 'months', 'weeks' and 'years'.
- **ims** (*boolean*) – Use certificate for the Cisco ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self- signed Certificate, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_system_certificate_by_id`(*host_name, id, allow_wildcard_delete=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API deletes a System Certificate of a particular node based on given HostName and ID.

Parameters

- **`allow_wildcard_delete`** (*boolean*) – If the given certificate to be deleted is a wildcard certificate, corresponding certificate gets deleted on rest of the nodes in the deployment as well., property of the request body.
- **`host_name`** (*basestring*) – `hostName` path parameter. Name of the host from which System Certificate needs to be deleted.
- **`id`** (*basestring*) – `id` path parameter. ID of the System Certificate to be deleted.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_certificates`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM- dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd

HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_trusted_certificate(*id*, *dirpath=None*, *save_file=None*, *filename=None*, *headers=None*,
 ***query_parameters*)

The response of this API carries a trusted certificate file mapped to the requested ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be exported.

- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The `DownloadResponse` wrapper. Wraps the `urllib3.response.HTTPResponse`. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_trust_certificate(allow_basic_constraint_cafalse=None, allow_out_of_date_cert=None,
                        allow_sha1_certificates=None, data=None, description=None, name=None,
                        trust_for_certificate_based_admin_auth=None,
                        trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                        trust_for_ise_auth=None, validate_certificate_extensions=None,
                        headers=None, payload=None, active_validation=True,
                        **query_parameters)
```

Import an X509 certificate as a trust certificate. NOTE:

Request parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following parameters are used in POST body `PARAMETER DESCRIPTION` EXAMPLE name Friendly name of the certificate "name": "Trust Certificate" description Description of the certificate "description": "Imported Trust Certificate" data * required Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). Use `awk 'NF {sub(/ /, "");`

```
printf "%sn", $0;}' <<your .pem file>>
```

to extract data from certificate file. "data": "Plain-text contents of the certificate file." allowOutOfDateCert * required Allow out of date certificates (required). SECURITY ALERT: It is recommended to use "allowOutOfDateCert": false to avoid import of expired certificates (not Secure). "allowOutOfDateCert": true allowSHA1Certificates * required Allow import of certificate with signature that uses SHA-1 hashing algorithm and is considered less secure (required). SECURITY ALERT: It is recommended to use "allowSHA1Certificates": false to avoid import of SHA1 based certificates (less secure). "allowSHA1Certificates": true allowBasicConstraintCAFalse * required Allow certificates with Basic Constraints CA Field as False (required). SECURITY ALERT: It is recommended to use "allowBasicConstraintCAFalse": false to avoid import of certificates with Basic Constraints CA Field as False (not Secure). "allowBasicConstraintCAFalse": true trustForIseAuth Trust for authentication within Cisco ISE "trustForIseAuth": false trustForClientAuth Trust for client authentication and Syslog "trustForClientAuth": false trustForCertificateBasedAdminAuth Trust for

certificate based Admin authentication “trustForCertificateBasedAdminAuth”: false trustForCiscoServicesAuth Trust for authentication of Cisco Services “trustForCiscoServicesAuth”: false validateCertificateExtensions Validate extensions for trust certificate “validateCertificateExtensions”: false NOTE: If name is not set, a default name with the following format is used: common-name#issuer#nnnnn where “nnnnn” is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate is trusted in Cisco ISE. The objective here is to distinguish between certificates that are used for trust within an Cisco ISE deployment and public certificates that are used to trust Cisco services. Typically, you do not want to use a given certificate for both purposes. Trusted For Usage Authentication within Cisco ISE Use “trustForIseAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact Cisco ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Args:

allow_basic_constraint_cafalse(boolean): Allow

certificates with Basic Constraints CA Field as False (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date

certificates (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based

certificates (required), property of the request body.

data(string): Certificate content (required), property

of the request body.

description(string): Description of the certificate,

property of the request body.

name(string): Name of the certificate, property of the

request body.

trust_for_certificate_based_admin_auth(boolean): Trust

for Certificate based Admin authentication, property of the request body.

trust_for_cisco_services_auth(boolean): Trust for

authentication of Cisco Services, property of the request body.

trust_for_client_auth(boolean): Trust for client

authentication and Syslog, property of the request body.

trust_for_ise_auth(boolean): Trust for authentication

within Cisco ISE, property of the request body.

validate_certificate_extensions(boolean): Validate trust

certificate extension, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request

.

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises:

TypeError: If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(id, headers=None, **query_parameters)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id (basestring)** – id path parameter. ID of the trust certificate.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```

update_trusted_certificate(id, authenticate_before_crl_received=None, automatic_crl_update=None,
    automatic_crl_update_period=None, automatic_crl_update_units=None,
    crl_distribution_url=None, crl_download_failure_retries=None,
    crl_download_failure_retries_units=None, description=None,
    download_crl=None, enable_ocsp_validation=None,
    enable_server_identity_check=None, ignore_crl_expiration=None,
    name=None, non_automatic_crl_update_period=None,
    non_automatic_crl_update_units=None,
    reject_if_no_status_from_ocs_p=None,
    reject_if_unreachable_from_ocs_p=None, selected_ocsp_service=None,
    status=None, trust_for_certificate_based_admin_auth=None,
    trust_for_cisco_services_auth=None, trust_for_client_auth=None,
    trust_for_ise_auth=None, headers=None, payload=None,
    active_validation=True, **query_parameters)

```

Update a trusted certificate present in Cisco ISE trust store. Following parameters are used in PUT request body

PARAMETER	DESCRIPTION	EXAMPLE
<code>name</code>	name * required Friendly name of the certificate (required).	"Trust Certificate"
<code>status</code>	Status of the certificate	"Enabled"
<code>description</code>	Description of the certificate	"Certificate for secure connection to cisco.com"
<code>trustForIseAuth</code>	Trust for authentication within Cisco ISE	false
<code>trustForClientAuth</code>	Trust for client authentication and Syslog	false
<code>trustForCertificateBasedAdminAuth</code>	Trust for certificate based Admin authentication	false
<code>trustForCiscoServicesAuth</code>	Trust for authentication of Cisco Services	false
<code>enableOCSPValidation</code>	Switch to enable or disable OCSP Validation	false
<code>selectedOCSPService</code>	Name of selected OCSP Service	"INTERNAL_OCSP_SERVICE"
<code>rejectIfNoStatusFromOCSP</code>	Switch to reject certificate if there is no status from OCSP	false
<code>rejectIfUnreachableFromOCSP</code>	Switch to reject certificate if unreachable from OCSP	false
<code>crlDistributionUrl</code>	Certificate Revocation List Distribution URL	"CRL distribution URL"
<code>automaticCRLUpdate</code>	Switch to enable or disable automatic CRL update	false
<code>automaticCRLUpdatePeriod</code>	Automatic CRL update period	5
<code>automaticCRLUpdateUnits</code>	Unit of time for automatic CRL update	"Minutes"
<code>nonAutomaticCRLUpdatePeriod</code>	Non automatic CRL update period	1
<code>nonAutomaticCRLUpdateUnits</code>	Unit of time of non automatic CRL update	"Hours"
<code>crlDownloadFailureRetries</code>	If CRL download fails, wait time before retry	10
<code>crlDownloadFailureRetriesUnits</code>	Unit of time before retry if CRL download fails	"Minutes"
<code>enableServerIdentityCheck</code>	Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL	false
<code>authenticateBeforeCRLReceived</code>	Switch to enable or disable CRL Verification if CRL is not Received	false
<code>ignoreCRLEExpiration</code>	Switch to enable or disable ignore CRL Expiration	false
<code>trustForIseAuth</code>	Trusted For Usage Authentication within Cisco ISE	true
<code>trustForClientAuth</code>	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	true
<code>trustForCertificateBasedAdminAuth</code>	Client authentication and Syslog Use	true
<code>trustForCiscoServicesAuth</code>	Use if the certificate is to be used for authentication of endpoints that contact Cisco ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: "trustForClientAuth" can be set true only if the "trustForIseAuth" has been set true.	true
<code>enableOCSPValidation</code>	Certificate based admin authentication Use	true
<code>selectedOCSPService</code>	Use if the certificate is used for trust within Cisco ISE, such as for secure communication between Cisco ISE nodes	"INTERNAL_OCSP_SERVICE"
<code>active_validation</code>	Note: "trustForCertificateBasedAdminAuth" can be set true only if "trustForIseAuth" and "trustForClientAuth" are true.	true
<code>headers</code>	Authentication of Cisco Services Use	
<code>payload</code>	Use "trustForCiscoServicesAuth":true if the certificate is to be used for trusting external Cisco services, such as Feed Service.	
<code>query_parameters</code>	OCSP Configuration Usage Validation against OCSP service Use	
	Use "enableOCSPValidation":true to validate the certificate against OCSP service mentioned in the field selectedOCSPService	
	OCSP Service name Use "selectedOCSPService": "Name of OCSP Service"	
	Name of the OCSP service against which the certificate should be validated	
	Note: "selectedOCSPService" value is used if "enableOCSPValidation" has been set true.	

ject the request if OCSP returns UNKNOWN status Use “rejectIfNoStatusFromOCSP”:true to reject the certificate if the OCSP service returns UNKNOWN status Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OCSP Responder is unreachable Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OCSP service is unreachable. Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field `crlDistributionUrl` CRL distribution url Use “`crlDistributionUrl`” to specify the URL from where the CRL should be downloaded Note: “`crlDistributionUrl`” value is used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and `automaticCRLUpdatePeriod`, `automaticCRLUpdatePeriod` to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod”, `nonAutomaticCRLUpdateUnits` to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” to set retry time period if CRL download fails Note: “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable or disable CRL verification if CRL is not received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable or disable automatic CRL update, property of the request body.
- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable or disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable or disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable or disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.

- **ignore_crl_expiration** (*boolean*) – Switch to enable or disable ignore CRL expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.
- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocs_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘Disabled’ and ‘Enabled’.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within Cisco ISE, property of the request body.
- **id** (*basestring*) – id path parameter. ID of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- *MalformedRequest* – If the request body created is invalid.
- *ApiError* – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- *TypeError* – If the parameter types are incorrect.
- *MalformedRequest* – If the request body created is invalid.
- *ApiError* – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities

class ClearThreatsAndVulnerabilities

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.2_beta).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

Clear Threats and Vulnerabilities API allows the user to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.1	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	Yes	Resource UUID value	
macAd-dresses	String	Yes	One or more endpoint MAC ad-dresses	["00:00:00:00:00:F2", "00:00:00:00:00:F3"]

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_threats_and_vulnerabilities*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

configuration**class Configuration**

Identity Services Engine Configuration API (version: 3.2_beta).

Wraps the Identity Services Engine Configuration API and exposes the API as native Python methods that return native Python objects.

`get_configuration(headers=None, **query_parameters)`

Retrieve configuration information for LSD settings page.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
update_configuration(enable_epo=None, enable_rcm=None, headers=None, payload=None,
                    active_validation=True, **query_parameters)
```

API to enable/disable LSD settings .

Parameters

- **enable_epo** (*boolean*) – To enable/disable LSD ownership settings, property of the request body.
- **enable_rcm** (*boolean*) – To enable/disable random mac(RCM) settings. Please note that this flag will be set to false if enableEPO flag is false, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

consumer

class Consumer

Identity Services Engine Consumer API (version: 3.2_beta).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

```
create_account(node_name=None, headers=None, payload=None, active_validation=True,
                **query_parameters)
```

AccountCreate.

Parameters

- **node_name** (*string*) – nodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(node_name=None, headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_account*

```
activate_account(description=None, headers=None, payload=None, active_validation=True,
                  **query_parameters)
```

AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **`name`** (*string*) – name, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

access_secret(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccessSecret.

Parameters

- **peer_node_name** (*string*) – peerNodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

dataconnect_services

class DataconnectServices

Identity Services Engine Dataconnect Services API (version: 3.2_beta).

Wraps the Identity Services Engine Dataconnect Services API and exposes the API as native Python methods that return native Python objects.

get_odbc_detail(*headers=None, **query_parameters*)

This API retrieves the Dataconnect ODBC details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_dataconnect_service`(*headers=None, **query_parameters*)

This API retrieves the status of the Dataconnect feature.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_dataconnect_password`(*password=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API updates the Dataconnect user password.

Parameters

- **`password`** (*string*) – Password for dataconnect user. Password must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contains at least one special character #\$_%&*+,-.::=?^_~, Has at least 12 characters, Has not more than 30 characters, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_dataconnect_password_expiry(*password_expires_in_days=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API updates the number of days of Dataconnect password expiry.

Parameters

- **password_expires_in_days** (*integer*) – passwordExpiresInDays, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

set_data_connect_service(*is_enabled=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API updates the DataConnect feature status.

Parameters

- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules

class DeviceAdministrationAuthenticationRules

Identity Services Engine Device Administration - Authentication Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_authentication_rules(*policy_id, headers=None, **query_parameters*)

Device Admin Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for `get_device_admin_authentication_rules`

`create_device_admin_authentication_rule`(*policy_id*, *identity_source_id=None*,
identity_source_name=None, *if_auth_fail=None*,
if_process_fail=None, *if_user_not_found=None*,
link=None, *rule=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Device Admin Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **`identity_source_id`** (*string*) – Identity source id from the identity stores, property of the request body.
- **`identity_source_name`** (*string*) – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail`** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail`** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found`** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`rule`** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authentication_rule*

reset_hit_counts_device_admin_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authentication_rules*

get_device_admin_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authentication_rule_by_id*

update_device_admin_authentication_rule_by_id(*id*, *policy_id*, *identity_source_id=None*,
identity_source_name=None, *if_auth_fail=None*,
if_process_fail=None, *if_user_not_found=None*,
link=None, *rule=None*, *headers=None*,
payload=None, *active_validation=True*,
***query_parameters*)

Device Admin Update rule.

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.

- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_authentication_rule_by_id*

delete_device_admin_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_device_admin_authentication_rule_by_id*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_local_exception_rules(*policy_id, headers=None, **query_parameters*)

Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)Alias for *get_device_admin_local_exception_rules***create_device_admin_local_exception_rule**(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_local_exception_rule*

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_local_exceptions*

get_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_device_admin_local_exception_rule_by_id`***`update_device_admin_local_exception_rule_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Device Admin Update local exception rule.

Parameters

- **`commands (list)`** – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **`link (object)`** – link, property of the request body.
- **`profile (string)`** – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **`rule (object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_device_admin_local_exception_rule_by_id*

delete_device_admin_local_exception_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_device_admin_local_exception_rule_by_id*

device_administration_authorization_global_exception_rules

class DeviceAdministrationAuthorizationGlobalExceptionRules

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_policy_set_global_exception_rules(*headers=None, **query_parameters*)

Device Admin Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_rules*

create_device_admin_policy_set_global_exception(*commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.

- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)Alias for *reset_hit_counts_device_admin_global_exceptions***get_device_admin_policy_set_global_exception_by_rule_id**(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)Alias for *get_device_admin_policy_set_global_exception_by_rule_id***update_device_admin_policy_set_global_exception_by_rule_id**(*id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).

- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_device_admin_policy_set_global_exception_by_rule_id`***device_administration_authorization_rules****class DeviceAdministrationAuthorizationRules**

Identity Services Engine Device Administration - Authorization Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_device_admin_authorization_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authorization rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authorization_rules*

create_device_admin_authorization_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authorization_rule*

reset_hit_counts_device_admin_authorization_rules(*policy_id*, *headers=None*,
***query_parameters*)

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

get_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authorization_rule_by_id*

update_device_admin_authorization_rule_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_authorization_rule_by_id*

delete_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_authorization_rule_by_id*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_command_sets(*headers=None*, ***query_parameters*)

Device Admin Return list of command sets. (Other CRUD APIs available throught ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_conditions(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions*

create_device_admin_condition(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to existing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate ..

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘ConditionAttributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAndBlock’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range,

for specific date, the same date should be used for start/end date Default no specific dates
In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

`get_device_admin_conditions_for_authentication_rules`(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_authentication_rules`(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authorization_rules*

get_device_admin_condition_by_name(*name, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_condition_by_name*

update_device_admin_condition_by_name(*name*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update library condition using condition name.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_id*=None, *attribute_name*=None, *attribute_value*=None, *children*=None, *condition_type*=None, *dates_range*=None, *dates_range_exception*=None, *description*=None, *dictionary_name*=None, *dictionary_value*=None, *hours_range*=None, *hours_range_exception*=None, *id*=None, *is_negate*=None, *link*=None, *operator*=None, *week_days*=None, *week_days_exception*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers*=None, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers*=None, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers*=None, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None, **query_parameters*)Alias for *get_device_admin_conditions_for_policy_sets***get_device_admin_condition_by_id**(*id, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)Alias for *get_device_admin_condition_by_id*

update_device_admin_condition_by_id(*id, attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’,

'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.

- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_id*

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_id*

device_administration_dictionary_attributes_list

class DeviceAdministrationDictionaryAttributesList

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_dictionaries_authentication(*headers=None*, ***query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authorization*

get_device_admin_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_policy_set(headers=None, **query_parameters)`Alias for *`get_device_admin_dictionaries_policy_set`***device_administration_identity_stores****class DeviceAdministrationIdentityStores**

Identity Services Engine Device Administration - Identity Stores API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_device_admin_identity_stores(headers=None, **query_parameters)`

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`Alias for *`get_device_admin_identity_stores`*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_network_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_network_conditions*

create_device_admin_network_condition(*cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.

- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*string*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_network_condition_by_id*

update_device_admin_network_condition_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).

- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set

class DeviceAdministrationPolicySet

Identity Services Engine Device Administration - Policy Set API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_policy_sets(*headers=None*, ***query_parameters*)

Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_device_admin_policy_sets***create_device_admin_policy_set**(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'enabled', 'disabled' and 'monitor'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_policy_sets*

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_by_id*

update_device_admin_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.

- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_device_admin_policy_set_by_id`

device_administration_profiles**class DeviceAdministrationProfiles**

Identity Services Engine Device Administration - Profiles API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_device_admin_profiles(headers=None, **query_parameters)`

Device Admin Returns list of profiles. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_profiles*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_service_names*

device_administration_time_date_conditions

class DeviceAdministrationTimeDateConditions

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_device_admin_time_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_time_conditions*

create_device_admin_time_condition(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates time/date condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.

- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_time_condition*

get_device_admin_time_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for `get_device_admin_time_condition_by_id`

update_device_admin_time_condition_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date

range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_time_condition_by_id*

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_time_condition_by_id*

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.2_beta).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

Downloadable ACL API allows the client to add, delete, update, search and perform actions on downloadable ACL.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute IP version in 2.6	daclType	Added Enum Attribute 'daclType'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]		multiline_acl
id	String	Yes	Resource UUID		c1e0e9e0-717f-11eb-9fb2-b6cb23d38630
description	String	No	Use the string n for a newline		description
dacl	String	Yes	The DACL Content. Use the string n for a newline		permit ip any any
daclType	Enum	No	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	

get_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a downloadable ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_downloadable_acl_by_id`

`update_downloadable_acl_by_id(id, dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a downloadable ACL.

Parameters

- **`dacl(string)`** – The DACL Content. Use the string `n` for a newline, property of the request body.
- **`dacl_type(string)`** – Allowed values: `IPV4`, `IPV6`, `IP_AGNOSTIC`, property of the request body.
- **`description(string)`** – Use the string `n` for a newline, property of the request body.
- **`id(basestring)`** – `id`, property of the request body.
- **`name(string)`** – Resource Name. Name may contain alphanumeric or any of the following characters `[_.-]`, property of the request body.
- **`id`** – `id` path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_downloadable_acl_by_id`*

`delete_downloadable_acl_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a downloadable ACL.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_downloadable_acl_by_id`*

`get_downloadable_acl`(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_downloadable_acl*

get_downloadable_acl_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request's response
 - text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_downloadable_acl_generator*

create_downloadable_acl(*dac1=None, dac1_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **dac1** (*string*) – The DACL Content. Use the string `\n` for a newline, property of the request body.
- **dac1_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string `\n` for a newline, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters `[_.-]`, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dac1=None, dac1_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

edda**class Edda**

Identity Services Engine Edda API (version: 3.2_beta).

Wraps the Identity Services Engine Edda API and exposes the API as native Python methods that return native Python objects.

get_connector_config(*headers=None, **query_parameters*)

EDDA Get ALL connectorConfig information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create_connector_config(additional_properties=None, attributes=None, connector_name=None,  
connector_type=None, deltasync_schedule=None, description=None,  
enabled=None, fullsync_schedule=None, protocol=None,  
skip_certificate_validations=None, url=None, headers=None, payload=None,  
active_validation=True, **query_parameters)
```

EDDA Configure connectorconfig information.

Parameters

- **additional_properties** (*object*) – additionalProperties, property of the request body.
- **attributes** (*object*) – connectorName, property of the request body.
- **connector_name** (*string*) – connectorName, property of the request body.
- **connector_type** (*string*) – connector Type list, property of the request body. Available values are 'urlfetcher' and 'vmware'.
- **deltasync_schedule** (*object*) – deltasyncSchedule, property of the request body.
- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **fullsync_schedule** (*object*) – fullsyncSchedule, property of the request body.
- **protocol** (*string*) – protocol, property of the request body.
- **skip_certificate_validations** (*boolean*) – skipCertificateValidations, property of the request body.
- **url** (*object*) – url, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_connector_config_by_connector_name(*connector_name*, *headers=None*, ***query_parameters*)

EDDA Get connectorConfig information based on ConnectorName.

Parameters

- **connector_name** (*basestring*) – connectorName path parameter. update or delete or retrieve the connector config.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_connector_config_by_connector_name(*connector_name*, *additional_properties=None*, *attributes=None*, *connector_type=None*, *deltasync_schedule=None*, *description=None*, *enabled=None*, *fullsync_schedule=None*, *protocol=None*, *skip_certificate_validations=None*, *url=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

EDDA update Configure connectorConfig information based on ConnectorName.

Parameters

- **additional_properties** (*object*) – additionalProperties, property of the request body.
- **attributes** (*object*) – connectorName, property of the request body.
- **connector_name** (*basestring*) – connectorName, property of the request body.
- **connector_type** (*string*) – connector Type list, property of the request body. Available values are 'urlfetcher' and 'vmware'.
- **deltasync_schedule** (*object*) – deltasyncSchedule, property of the request body.
- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.

- **fullsync_schedule** (*object*) – fullsyncSchedule, property of the request body.
- **protocol** (*string*) – protocol, property of the request body.
- **skip_certificate_validations** (*boolean*) – skipCertificateValidations, property of the request body.
- **url** (*object*) – url, property of the request body.
- **connector_name** – connectorName path parameter. update or delete or retrieve the connector config.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_connector_config_by_connector_name(*connector_name*, *headers=None*, ***query_parameters*)

EDDA Delete Configure connectorConfig information based on ConnectorName.

Parameters

- **connector_name** (*basestring*) – connectorName path parameter. update or delete or retrieve the connector config.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_edda_dictionary_references(*headers=None, **query_parameters*)

EDDA Get a map of references to EDDA dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

test_connector(*auth_type=None, auth_values=None, connector_name=None, response_parsing=None, unique_id=None, url=None, headers=None, payload=None, active_validation=True, **query_parameters*)

EDDA test the Connector.

Parameters

- **auth_type** (*string*) – authentication Type list, property of the request body. Available values are 'apikey' and 'basic'.
- **auth_values** (*object*) – Request to test Connector, property of the request body.
- **connector_name** (*string*) – connectorName, property of the request body.
- **response_parsing** (*string*) – uniqueness to identify, property of the request body.
- **unique_id** (*string*) – uniqueness to identify, property of the request body.
- **url** (*string*) – bulkUrl, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell

class EgressMatrixCell

Identity Services Engine EgressMatrixCell API (version: 3.2_beta).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

Egress Policy Matrix Cell API allows the client to add, update, delete and search egress matrix cells among other operations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	
0	1.0	2.0	Initial Cisco ISE Version	
1	1.1	2.3	Introducing bulk operations	

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		ANY-ANY
id	String	No	Resource UUID, mandatory for update		f92c1a900-8c01-11e6-996c-525400b48521
description	String	No			Default egress rule
default-Rule	Enum	Yes	Allowed values: NONE, DENY_IP, PERMIT_IP	NONE	PERMIT_IP
destinationSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521
matrix-CellStatus	Enum	Yes	Allowed values: DISABLED, ENABLED, MONITOR	DISABLED	ENABLED
sgACLs	List	Yes			[“92951ac0-8c01-11e6-996c-525400b48521”]
sourceSgtId	String	Yes			92bb1950-8c01-11e6-996c-525400b48521

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*headers=None, **query_parameters*)

Alias for *clear_all_matrix_cells*

set_all_cells_status(*status, headers=None, **query_parameters*)

This API allows the client to set status of all the egress matrix cells.

Parameters

- **status** (*basestring*) – status path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_status(*status*, *headers=None*, ***query_parameters*)

Alias for *set_all_cells_status*

clone_matrix_cell(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

This API allows the client to clone an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **src_sgt_id** (*basestring*) – srcSgtId path parameter.
- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_egress_matrix_cell_by_id*

update_egress_matrix_cell_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*, *matrix_cell_status=None*, *name=None*, *sgacls=None*, *source_sgt_id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.

- **name** (*string*) – name, property of the request body.
- **sgacIs** (*list*) – sgacIs, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*,
matrix_cell_status=None, *name=None*, *sgacIs=None*, *source_sgt_id=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_egress_matrix_cell_by_id*

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_egress_matrix_cell_generator`*

`create_egress_matrix_cell`(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an egress matrix cell.

Parameters

- **`default_rule`** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`destination_sgt_id`** (*string*) – destinationSgtId, property of the request body.
- **`matrix_cell_status`** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgacIs`** (*list*) – sgacIs, property of the request body (list of strings).
- **`source_sgt_id`** (*string*) – sourceSgtId, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgcls=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_egress_matrix_cell*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.2_beta).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

Endpoint Certificate API allows the client to create endpoint certificates signed by the Cisco ISE Internal CA. This API can takes in certificate request details, create a RSA key pair, create a certificate and return the resulting key pair and certificate as a ZIP file. ZIP files are returned as an octet stream.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
certTemplateName	String	Yes	Name of an Internal CA template	Certificate_Template_Name
format	Enum	Yes	Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN	PKCS8
password	String	Yes	Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#	Password_123
certificateRequest	Map	Yes	Key value map. Must have CN and SAN entries	
• CN	String	Yes	Matches the requester's User Name, unless the Requester is an ERS Admin. ERS Admins are allowed to create requests for any CN	userName [or] machineName
• SAN	String	Yes	Valid MAC Address, delimited by '-'	11-22-33-44-55-66

```
create_endpoint_certificate(cert_template_name=None, certificate_request=None, format=None,
                           password=None, dirpath=None, save_file=None, filename=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to create an endpoint certificate.

Parameters

- **cert_template_name** (*string*) – Name of an Internal CA template, property of the request body.
- **certificate_request** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.

- **format** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **password** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
create(cert_template_name=None, certificate_request=None, format=None, password=None,
        dirpath=None, save_file=None, filename=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_endpoint_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group**class EndpointIdentityGroup**

Identity Services Engine EndpointIdentityGroup API (version: 3.2_beta).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

Endpoint Identity Groups API allows the client to add, delete, update, and search endpoint groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.4	Added GetByName operation		

Resource Definition

Attribute	Type	Re-quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		Cisco-Meraki-Devicee
id	String	No	Resource UUID, mandatory for update		1e2700a0-8c00-11e6-996c-525400b48521
description	String	No			Identity Group for Profile: Cisco-Meraki-Device
systemDefined	Boolean	Yes		false	true

get_endpoint_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_id*

update_endpoint_group_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_group_by_id*

delete_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_group_by_id*

get_endpoint_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups*

get_endpoint_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups_generator*

create_endpoint_group(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

external_radius_server**class ExternalRadiusServer**

Identity Services Engine ExternalRADIUSServer API (version: 3.2_beta).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

External RADIUS Server API allows the client to add, delete, update, search and perform actions on external RADIUS server.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name. Allowed characters are alphanumeric and _ (underscore).		externalRadiusServer1
id	String	No	Resource UUID, mandatory for update		da095377-dce8-486e-933a-6ea788bbf51a
description	String	No			example external radius server
hostIP	String	Yes	The IP of the host - must be a valid IPV4 address		1.1.1.1
sharedSecret	String	Yes	Shared secret maximum length is 128 characters		sharedSecret
enableKeyWrap	Boolean	Yes	KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices		true
encryptionKey	String	No	The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		1616161616161616
authenticatorKey	String	No	The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat')		2020202020202020
keyInputFormat	Enum	Yes	Specifies the format of the input for fields 'encryptionKey' and 'authenticatorKey'. Allowed Values: ASCII, HEXADECIMAL		ASCII
authenticationPort	Integer	Yes	Valid Range 1 to 65535		1812
accountingPort	Integer	Yes	Valid Range 1 to 65535		1813
time-out	Integer	Yes	Valid Range 1 to 120		5
re-tries	Integer	Yes	Valid Range 1 to 9		3
proxy-Time-out	Integer	No	Valid Range 1 to 600	300	

get_external_radius_server_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for `get_external_radius_server_by_id`

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed charactera are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_external_radius_server_by_id*

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_external_radius_server_by_id*

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server*

get_external_radius_server_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

create_external_radius_server(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.

- **key_input_format** (*string*) – Specifies the format of the input for fields ‘encryption-Key’ and ‘authenticatorKey’. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_external_radius_server*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

filter_policy**class FilterPolicy**

Identity Services Engine FilterPolicy API (version: 3.2_beta).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

Filter Policy API allows clients to add, get, update and delete SXP domain filter policies.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
subnet	String	No	Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined	subnetAddress
sgt	String	No	SGT name or ID. At least one of subnet or sgt or vn should be defined	sgt
vn	String	No	Virtual Network. At least one of subnet or sgt or vn should be defined	virtual-Network
domains	String	Yes	List of SXP Domains, separated with comma	Sxp Vpn Name

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.

- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_filter_policy_by_id`***`get_filter_policy(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`Alias for *`get_filter_policy`***`get_filter_policy_generator(page=None, size=None, headers=None, **query_parameters)`**

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_filter_policy_generator*

create_filter_policy(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_filter_policy*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.2_beta).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

Guest Location API allows the client to search the locations configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	9f083530-8c01-11e6-996c-525400b48521
descrip-tion	String	No		

get_guest_location_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

Alias for `get_guest_location`

`get_guest_location_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration**class GuestSmtpNotificationConfiguration**

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.2_beta).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

Guest SMTP notification configuration API is a global setting for enabling email notifications within guest application. These APIs allow to create, update and retrieve the notification settings. The create API may not be required to be used as of Cisco ISE Release 2.2 because the single SMTP notification configuration is the only one used and it always gets created during the Cisco ISE application initialization period.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for update		9ecb5340-8c01-11e6-996c-525400b48521
description	String	No			
defaultFromAddress	String	No	The default from email address to be used to send emails from	donotreply@example.com	
notificationEnabled	Boolean	No	Indicates if the email notification service is to be enabled	true	
smtpServer	String	No	The SMTP server ip address or fqdn such as outbound.mycompany.com		
useDefaultFromAddress	Boolean	No	If the default from address should be used rather than using a sponsor user email address	false	
smtpPort	String	No	Port at which SMTP Secure Server is listening	25	
connectionTimeout	String	No	Interval in seconds for all the SMTP client connections	60	
useTLSorSSLEncryption	Boolean	No	If configured to true, SMTP server authentication will happen using TLS/SSL	false	
usePasswordAuthentication	Boolean	No	If configured to true, SMTP server authentication will happen using username/password	false	
userName	String	No	Username of Secure SMTP server		
password	String	No	Password of Secure SMTP server		

get_guest_smtp_notification_settings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_guest_smtp_notification_settings_by_id`*

`update_guest_smtp_notification_settings_by_id(id, connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a SMTP configuration setting.

Parameters

- **`connection_timeout (string)`** – Interval in seconds for all the SMTP client connections, property of the request body.
- **`default_from_address (string)`** – The default from email address to be used to send emails from, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`notification_enabled (boolean)`** – Indicates if the email notification service is to be enabled, property of the request body.
- **`password (string)`** – Password of Secure SMTP server, property of the request body.
- **`smtp_port (string)`** – Port at which SMTP Secure Server is listening, property of the request body.
- **`smtp_server (string)`** – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **`use_default_from_address (boolean)`** – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **`use_password_authentication (boolean)`** – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **`use_tlsor_ssl_encryption (boolean)`** – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.

- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlsor_ssl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

get_guest_smtp_notification_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings*

get_guest_smtp_notification_settings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings_generator*

create_guest_smtp_notification_settings(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.

- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlsor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_smtp_notification_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_ssid**class GuestSsid**

Identity Services Engine GuestSSID API (version: 3.2_beta).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

Guest SSIDs are global objects that are referenced by Cisco ISE sponsor portals. Guest SSID API allows the client to add, delete, update and search guest SSID among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name. Name may contain alphanumeric or any of the following characters [_.-]	ssid_value
id	String	No	Resource UUID, mandatory for update	9132eedc-7910-4ffe-805e-3d3a366f7fb7
description	String	No		

get_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_ssid_by_id*

update_guest_ssid_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest SSID by ID.

Parameters

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_ssid_by_id*

get_guest_ssid(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid*

get_guest_ssid_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid_generator*

create_guest_ssid(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_ssid*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_type**class GuestType**

Identity Services Engine GuestType API (version: 3.2_beta).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

Guest Type API allows the client to add, delete, update and search guest types.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Contractor (default)
id	String	No	Resource UUID, mandatory for update		9f03a151-8c01-11e6-996c-525400b48521
description	String	No			Default settings allow network access for up to a year.
accessTime	List	No			
<ul style="list-style-type: none"> allowAccessOn-Specific-DaysTimes 	Boolean	No	Enable Specific Day Time Limits	false	
<ul style="list-style-type: none"> default-Duration 	Integer	No		90	
<ul style="list-style-type: none"> durationTime-Unit 	Enum	No	Allowed values are: - DAYS, - HOURS, - MINUTES	DAYS	
<ul style="list-style-type: none"> from-FirstLogin 	Boolean	No	When Account Duration starts from first login or specified date	false	
<ul style="list-style-type: none"> maxAccountDuration 	Integer	No	Maximum value of Account Duration	365	
<ul style="list-style-type: none"> dayTime-Limits 	List	No	List of Time Ranges for account access		
<ul style="list-style-type: none"> dayTime-Limit 	List	No	Time Ranges for account access		
<ul style="list-style-type: none"> startTime 	String	No	Start time in HH:mm format	09:00	
<ul style="list-style-type: none"> endTime 	String	No	End time in HH:mm format	17:00	
<ul style="list-style-type: none"> days 	List	No	List of Days		
1.4. User API Doc					2481
<ul style="list-style-type: none"> day 	Enum	No	Value should be one of Week day. Allowed		

update_guest_type_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_sms(id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *`update_guest_type_sms`*

`get_guest_type_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest type by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_guest_type_by_id`*

```
update_guest_type_by_id(id, access_time=None, description=None, expiration_notification=None,
                        is_default_type=None, login_options=None, name=None,
                        sponsor_groups=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, access_time=None, description=None, expiration_notification=None,
             is_default_type=None, login_options=None, name=None, sponsor_groups=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_type_by_id*

get_guest_type(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*

create_guest_type(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_type*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_user

class GuestUser

Identity Services Engine GuestUser API (version: 3.2_beta).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

Guest User API allows the client to add, delete, update and search guest users among other operations which are available from the sponsor portal. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only 'create' bulk operation. However, all other operation which are bulk supported can be used in the same way.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		guestUser
id	String	No	Resource UUID, mandatory for update		ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No			ERS Example user
customFields	Map	No	Key value map		"some key" : "some value"
guestType	String	No			Contractor
status	String	No			
reasonForVisit	String	No			
personBeingVisited	String	No			
sponsorUserName	String	No			Mr Spons
sponsorUserId	String	No			
statusReason	String	No			
portalId	String	No			23423432523

continues on next page

Table 48 – continued from previous page

guestAccess-Info	List	No			
• valid-Days	Integer	Yes	Number of days guest user is valid. To validate validDays property, Cisco ISE considers only date (not time) between fromDate and toDate properites		90
• fromDate	String	No			07/29/2014 14:44
• toDate	String	No			10/29/2014 17:30
• location	String	No			San Jose
• ssid	String	No			
• groupTag	String	No			
GuestInfo	List	Yes			
• emailAd-dress	String	No			email@some.uri.com
• enabled	Boolean	Yes	This field is only for Get operation not applicable for Create, Update operations	false	
• password	String	Yes			asdlkj324ew
• pho-neNum-ber	String	No	Phone number should be E.164 format		+13211239034
• smsSer-vice-Provider	String	No			Global Default

continues on next page

Table 48 – continued from previous page

• user-Name	String	No	If account needs be created with mobile number, please provide mobile number here		DS3ewdsa34wWE
• firstName	String	No			
• lastName	String	No			
• company	String	No			
• creation-Time	String	No			
• notificationLanguage	String	No			

approve_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to approve a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

approve_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *approve_guest_user_by_id*

change_sponsor_password(*portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to change the sponsor password.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to suspend a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *suspend_guest_user_by_name***reinstate_guest_user_by_name**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reinstate_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *reinstate_guest_user_by_name***get_guest_user_by_name**(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_name*

`update_guest_user_by_name`(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by name.

Parameters

- **`custom_fields`** (*object*) – Key value map, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`guest_access_info`** (*object*) – `guestAccessInfo`, property of the request body.
- **`guest_info`** (*object*) – `guestInfo`, property of the request body.
- **`guest_type`** (*string*) – `guestType`, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*basestring*) – name, property of the request body.
- **`portal_id`** (*string*) – `portalId`, property of the request body.
- **`reason_for_visit`** (*string*) – `reasonForVisit`, property of the request body.
- **`sponsor_user_id`** (*string*) – `sponsorUserId`, property of the request body.
- **`sponsor_user_name`** (*string*) – `sponsorUserName`, property of the request body.
- **`status`** (*string*) – status, property of the request body.
- **`status_reason`** (*string*) – `statusReason`, property of the request body.
- **`name`** – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_name*

delete_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_name*

reset_guest_user_password_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_id`(*id*, *headers=None*, ***query_parameters*)Alias for *reinstate_guest_user_by_id***`update_guest_user_email`**(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user email by ID.

Parameters

- **`additional_data`** (*list*) – `additionalData`, property of the request body (list of objects).
- **`id`** (*basestring*) – `id` path parameter.
- **`portal_id`** (*basestring*) – `portalId` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_email`(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)Alias for *update_guest_user_email*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

Alias for *update_guest_user_sms*

deny_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deny a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deny_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deny_guest_user_by_id*

get_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.

- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, custom_fields=None, description=None, guest_access_info=None, guest_info=None,
             guest_type=None, name=None, portal_id=None, reason_for_visit=None,
             sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *update_guest_user_by_id*

```
delete_guest_user_by_id(id, headers=None, **query_parameters)
```

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_id*

get_guest_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users*

get_guest_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users_generator*

create_guest_user(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_user*

suspend_guest_user_by_id(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to suspend a guest user by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_by_id`(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`suspend_guest_user_by_id`*

`get_version`(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the guest user.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_guest_user`(*operation_type=None*, *resource_media_type=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – operationType, property of the request body.
- **`resource_media_type`** (*string*) – resourceMediaType, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_guest_user*

monitor_bulk_status_guest_user(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status(bulkid, headers=None, **query_parameters)`
Alias for `monitor_bulk_status_guest_user`

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.2_beta).
Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

Hotspot Guest Portal API provides the ability to create, read, update, delete and search hotspot guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Hotspot Guest Portal (default)	
id	String	No	Resource UUID, mandatory for update	b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	
description	String	No	Guests do not require username and password credentials to access the network, but you can optionally require an access code		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=b132a9ef-1491-4e01-9ad4-b48a9c72e1c7	

continues on next page

Table 49 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	HOTSPOTGUEST	
settings	List	No	Defines all of the settings groups available for a BYOD		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal	aa178bd0-8bff-11e6-996c-525400b48521	

continues on next page

Table 49 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• coaType	Enum	No	Allowed Values: COAREAU-THENTI-CATE, COATER-MINATE	COAREAU-THENTICATE	
• aupSet-tings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• re-quireAc-cessCode	Boolean	No	Require the portal user to enter an access code. Only used in Hotspot portal	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAc-cessCode = true)		
• in-cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 49 – continued from previous page

• require-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• authSuccessSettings	List	No			
• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUCCESSPAGE, ORIGINATINGURL, URL	AUTHSUCCESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		

continues on next page

Table 49 – continued from previous page

• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		
• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDEFAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 49 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	
• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		

continues on next page

Table 49 – continued from previous page

• page-Back-ground-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	BYOD Portal		
• contact-Text	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			

continues on next page

Table 49 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_hotspot_portal`

```
get_hotspot_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

create_hotspot_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_hotspot_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMapping API (version: 3.2_beta).

Wraps the Identity Services Engine IPToSGTMapping API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping API allows the client to add, delete, update, search and deploy IP to SGT mapping.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	server1.cisco.com
id	String	No	Resource UUID, mandatory for update	
description	String	No		
deployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL		network_device_id
deployType	Enum	Yes	Allowed values: ALL, ND, NDG	ND
hostName	String	Mandatory if hostIp is empty		server1.cisco.com
sgt	String	Mandatory unless mappingGroup is set		sgt_id
hostIp	String	Mandatory if hostName is empty – valid IPL		
mappingGroup	String	Mandatory unless sgt and deployTo and deployType are set		

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all(*headers=None, **query_parameters*)

Alias for *deploy_all_ip_to_sgt_mapping*

get_deploy_status_ip_to_sgt_mapping(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status(*headers=None, **query_parameters*)

Alias for *get_deploy_status_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id, deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless *mappingGroup* is set or unless *deployType=ALL*, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if *hostName* is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if *hostIp* is empty, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless *sgt* and *deployTo* and *deployType* are set, property of the request body.
- **name** (*string*) – name, property of the request body.

- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_by_id*

delete_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_ip_to_sgt_mapping_by_id*

get_ip_to_sgt_mapping(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_generator`*

`create_ip_to_sgt_mapping`(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **`deploy_to`** (*string*) – Mandatory unless `mappingGroup` is set or unless `deployType=ALL`, property of the request body.
- **`deploy_type`** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **`host_ip`** (*string*) – Mandatory if `hostName` is empty -valid IP, property of the request body.
- **`host_name`** (*string*) – Mandatory if `hostIp` is empty, property of the request body.
- **`mapping_group`** (*string*) – Mapping Group Id. Mandatory unless `sgt` and `deployTo` and `deployType` are set, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt`** (*string*) – Mandatory unless `mappingGroup` is set, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*`RestResponse`***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping*

monitor_bulk_status_ip_to_sgt_mapping(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group

class IpToSgtMappingGroup

Identity Services Engine IPToSGTMappingGroup API (version: 3.2_beta).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

IP To SGT Mapping Group API allows the client to add, delete, update, search and deploy IP to SGT mapping groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.0	Initial Cisco ISE Version

Resource Definition

At-tribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		groupA
id	String	No	Resource UUID, mandatory for update		
de-scrip-tion	String	No			
de-ployTo	String	Mandatory unless mappingGroup is set or unless deployType=ALL			net-work_device_id
de-ploy-Type	Enum	Yes	Allowed values: ALL, ND, NDG	ALL	
sgt	String	Mandatory unless mappingGroup is set			sgt_id

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status_ip_to_sgt_mapping_group(headers=None, **query_parameters)`

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_ip_to_sgt_mapping_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_ip_to_sgt_mapping_group_by_id`*

`update_ip_to_sgt_mapping_group_by_id(id, deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`Alias for *`delete_ip_to_sgt_mapping_group_by_id`***`get_ip_to_sgt_mapping_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`**

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_ip_to_sgt_mapping_group`*

`get_ip_to_sgt_mapping_group_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_generator*

create_ip_to_sgt_mapping_group(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping_group*

monitor_bulk_status_ip_to_sgt_mapping_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.2_beta).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

Identity Groups API allows the client to search identity groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added Create and GetByName operations

Resource Definition

At-tribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	GuestType_Weekly (default)
id	String	No	Resource UUID, mandatory for update	9efe2310-8c01-11e6-996c-525400b48521
description	String	No		Identity group mirroring the guest type
parent	String	Yes		NAC Group:NAC:IdentityGroups:User Identity Groups

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_identity_group_by_name`***`get_identity_group_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get an identity group by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_identity_group_by_id`***`update_identity_group_by_id(id, description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update an identity group.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.

- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

get_identity_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups*

get_identity_groups_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

create_identity_group(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to identity group.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.2_beta).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

Identity Sequence API allows the client to add, delete, update and search Identity sequences.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	All_User_ID_Stores
id	String	No	Resource UUID, mandatory for update	93246270-8c01-11e6-996c-525400b48521
description	String	No		A built-in Identity Sequence to include all User Identity Stores
breakOn-StoreFail	Boolean	Yes	Do not access other stores in the sequence If a selected identity store cannot be accessed for authentication	false
certificateAuthenticationProfile	String	Yes	Certificate Authentication Profile, empty if doesn't exist	Preloaded_Certificate_Profile
idSeqItem	List	Yes	List of id stores comprised of id store name and order	[{ "idstore": "Internal Users", "order": 1 }, { "idstore": "All_AD_Join_Points", "order": 2 }, { "idstore": "Guest Users", "order": 3 }]

get_identity_sequence_by_name(name, headers=None, **query_parameters)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

get_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

update_identity_sequence_by_id(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

delete_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_identity_sequence_by_id*

get_identity_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence*

get_identity_sequence_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.

- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

internal_user**class InternalUser**

Identity Services Engine InternalUser API (version: 3.2_beta).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

Internal User API allows the client to add, delete, update and search internal users.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.3	Initial Cisco ISE Version		
1	1.1	2.6	Support new attribute Proxy Dead Timeout	proxyTime-out	Added int Attribute 'proxyTimeout'

Resource Definition

At-tribute	Type	Re-quired	Description	De-fault Val-ues	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		b24b09e2-16f8-4e48-ace1-2c262a9449f1
de-scrip-tion	String	No			description
changePassword	Boolean	Yes		true	
email	String	No			email@domain.com
enablePassword	String	No	EnablePassword field is added in ISE 2.0 to support T+		enablePass-word
en-abled	Boolean	Yes	Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled'		true
cus-tom-At-tributes	String	No	Key value map		{“key1” : “value1”}
first-Name	String	No			firstName
iden-tity-Groups	String	No	CSV of identity group IDs		identity-Groups
last-Name	String	No			lastName
pass-word	String	No			password
pass-wordID-Store	String	Yes	The id store where the internal user's password is kept	Internal Users	
ex-piry-DateEnabled	Boolean	No		false	
ex-piry-Date	String	No	To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD'		2021-05-19

get_internal_user_by_name(name, headers=None, **query_parameters)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_name*

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSOb jectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.

- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_name*

delete_internal_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`

Alias for *`delete_internal_user_by_name`*

`get_internal_user_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an internal user by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_internal_user_by_id`*

```
update_internal_user_by_id(id, change_password=None, custom_attributes=None, description=None,
                           email=None, enable_password=None, enabled=None, expiry_date=None,
                           expiry_date_enabled=None, first_name=None, identity_groups=None,
                           last_name=None, name=None, password=None, password_idstore=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be ‘Enabled’ or ‘Disabled’. The values are case sensitive. For example, ‘[ERSObjectURL]?filter=enabled.EQ.Enabled’, property of the request body.
- **expiry_date** (*string*) – To store the internal user’s expiry date information. It’s format is = ‘YYYY-MM-DD’, property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_id*

get_internal_user(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-MON-YY Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user*

get_internal_user_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(change_password=None, custom_attributes=None, description=None, email=None,
        enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
        first_name=None, identity_groups=None, last_name=None, name=None, password=None,
        password_idstore=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for [create_internal_user](#)

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the internal user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

licensing

class Licensing

Identity Services Engine Licensing API (version: 3.2_beta).

Wraps the Identity Services Engine Licensing API and exposes the API as native Python methods that return native Python objects.

```
get_connection_type(headers=None, **query_parameters)
```

Get connection type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_eval_license_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_feature_to_tier_mapping(headers=None, **query_parameters)`

Get feature to tier mapping.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_registration_info(headers=None, **query_parameters)`

Get registration information.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create_registration_info(connection_type=None, registration_type=None, ssm_on_prem_server=None, tier=None, token=None, headers=None, payload=None, active_validation=True, **query_parameters)`

License Configure registration information.

Parameters

- **`connection_type (string)`** – `connectionType`, property of the request body. Available values are 'HTTP_DIRECT', 'PROXY', 'SSM_ONPREM_SERVER' and 'TRANSPORT_GATEWAY'.
- **`registration_type (string)`** – `registrationType`, property of the request body. Available values are 'DEREGISTER', 'REGISTER', 'RENEW' and 'UPDATE'.

- **ssm_on_prem_server** (*string*) – If connection type is selected as SSM_ONPREM_SERVER, then IP address or the hostname (or FQDN) of the SSM On-Prem server Host., property of the request body.
- **tier** (*list*) – tier, property of the request body (list of strings. Available values are ‘ADVANTAGE’, ‘DEVICEADMIN’, ‘ESSENTIAL’, ‘PREMIER’ and ‘VM’).
- **token** (*string*) – token, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_smart_state(*headers=None, **query_parameters*)

Get smart license information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

configure_smart_state(headers=None, **query_parameters)

License Configure smart state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_tier_state_info(headers=None, **query_parameters)

Get tier state information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_tier_state_info(*headers=None, payload=None, active_validation=True, **query_parameters*)

Applicable values for name & status parameters: name: ESSENTIAL, ADVANTAGE, PREMIER, DE-VICEADMIN status: ENABLED, DISABLED .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

mdm**class Mdm**

Identity Services Engine MDM API (version: 3.2_beta).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id, name, portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pmg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_endpoints(*headers=None, **query_parameters*)

getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)

getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)

getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)

getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc**class Misc**

Identity Services Engine Misc API (version: 3.2_beta).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 MNT REST APIs

License [Cisco Sample Code License](https://developer.cisco.com/site/license/cisco-sample-code-license/)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_mnt*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_active_count(*headers=None*, ***query_parameters*)

ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_list(*headers=None, **query_parameters*)

ActiveList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_auth_list(*headers=None, **query_parameters*)

Session/AuthList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_posture_count(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_count(*headers=None, **query_parameters*)

ProfilerCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac*, *headers=None*, ***query_parameters*)

Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_sessions_by_session_id(session_id, headers=None, **query_parameters)`

Sessions by SessionID.

Parameters

- **`session_id`** (*basestring*) – `session_id` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_all_sessions(headers=None, **query_parameters)`

Delete All Sessions.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_mnt_version(headers=None, **query_parameters)`

MNT Version.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_failure_reasons(headers=None, **query_parameters)`

FailureReasons.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_authentication_status_by_mac`(*mac, records, seconds, headers=None, **query_parameters*)

AuthenticationStatus by MAC.

Parameters

- **`mac`** (*basestring*) – MAC path parameter.
- **`seconds`** (*basestring*) – SECONDS path parameter.
- **`records`** (*basestring*) – RECORDS path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`session_reauthentication_by_mac`(*endpoint_mac, psn_name, reauth_type, headers=None, **query_parameters*)

Session Reauthentication by MAC.

Parameters

- **`psn_name`** (*basestring*) – PSN_NAME path parameter.
- **`endpoint_mac`** (*basestring*) – ENDPOINT_MAC path parameter.

- **reauth_type** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_disconnect (*disconnect_type*, *endpoint_ip*, *mac*, *nas_ipv4*, *psn_name*, *headers=None*, ***query_parameters*)

Session Disconnect.

Parameters

- **endpoint_ip** (*basestring*) – ENDPOINT_IP path parameter.
- **psn_name** (*basestring*) – PSN_NAME path parameter.
- **mac** (*basestring*) – MAC path parameter.
- **disconnect_type** (*basestring*) – DISCONNECT_TYPE path parameter.
- **nas_ipv4** (*basestring*) – NAS_IPV4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_account_status_by_mac(*duration*, *mac*, *headers=None*, ***query_parameters*)

AccountStatus by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **duration** (*basestring*) – duration path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.2_beta).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

My Device Portal API provides the ability to create, read, update, delete and search my device portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		My Devices Portal (default)
id	String	No	Resource UUID, mandatory for update		901f1b37-4a2f-46d9-8653-d925d2dde3aa
description	String	No			Default portal used by employees to register and manage their personal devices
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/mydevicesportal/PortalSetup
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	MYDEVICE	
settings	List	No	Defines all of the settings groups available for a Mydevice portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		

continues on next page

Table 50 – continued from previous page

• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2		[“eth0”, “bond0”]
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• endpoint-identity-Group	String	Yes	Unique Id of the endpoint identity group where user’s devices will be added. Used only in Hotspot Portal		aa178bd0-8bff-11e6-996c-525400b48521
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 50 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No		2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK - ONPAGE, - ASLINK	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	

continues on next page

Table 50 – continued from previous page

• aupSet- tings	List	No	Configuration of the Accept- able Use Policy (AUP) for a portal		
• dis- playFre- quency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• in- cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• require- Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAc- ceptance = true	false	
• dis- playFre- quency- Interval- Days	Integer	No	Number of days between AUP confir- mations (when displayFre- quency = recurring)	7	
• employ- eeChangePass- wordSet- tings	List	No			
• allowEm- ployee- ToChangePwd	Boolean	No	Allow employ- ees to change their own pass- words	false	
• post- Login- Banner- Settings	List	No			

continues on next page

Table 50 – continued from previous page

• include-PostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• support-InfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE

continues on next page

Table 50 – continued from previous page

• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		

continues on next page

Table 50 – continued from previous page

• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			My Devices Portal
• contact-Text	String	No			Contact Support

continues on next page

Table 50 – continued from previous page

• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		

continues on next page

Table 50 – continued from previous page

• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_my_device_portal_by_id*

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_my_device_portal_by_id`*

`get_my_device_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal*

`get_my_device_portal_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations (object)** – Defines all of the Portal Customizations available, property of the request body.
- **description (string)** – description, property of the request body.
- **name (string)** – name, property of the request body.
- **portal_test_url (string)** – URL to bring up a test page for this portal, property of the request body.
- **portal_type (string)** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings (object)** – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_my_device_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

native_suppliant_profile

class NativeSuppliantProfile

Identity Services Engine NativeSuppliantProfile API (version: 3.2_beta).

Wraps the Identity Services Engine NativeSuppliantProfile API and exposes the API as native Python methods that return native Python objects.

Native suppliant profile API provides the ability to update, delete and search native suppliant profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Cisco-ISE-NSP
id	String	No	Resource UUID, mandatory for update	b8ce01e6-b150-4d4e-9698-40e48d5e0197
description	String	No		Pre-configured Native Supplicant Profile. The SSID Will Need To Be Customized For Your Environment
wirelessProfiles	List	Yes	List of Wireless profiles	
• ssid	String	Yes	SSID for the wireless profile	ISE
• allowedProtocol	Enum	Yes	Allowed protocol for the wireless profile.	TLS
• certificateTemplateId	String	No	Certificate template ID	0ca8f1b6-500d-560b-e053-75189a0ab0d1
• actionType	Enum	Yes	Action type for WifiProfile.	UPDATE
• previousSsid	String	Yes	Previous ssid for WifiProfile (required for updating existing WirelessProfile)	ssid1

get_native_suppliant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a native supplicant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_native_suppllicant_profile_by_id***update_native_suppllicant_profile_by_id**(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a native suppllicant profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **wireless_profiles** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_native_suppllicant_profile_by_id*

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native suppllicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_native_suppllicant_profile_by_id*

get_native_suppllicant_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

get_native_suppllicant_profile_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native suppllicant profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rules*

create_network_access_authentication_rule(*policy_id*, *identity_source_id=None*,
identity_source_name=None, *if_auth_fail=None*,
if_process_fail=None, *if_user_not_found=None*,
link=None, *rule=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_network_access_authentication_rule_by_id*

update_network_access_authentication_rule_by_id(*id, policy_id, identity_source_id=None, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update rule.

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, identity_source_id=None, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

delete_network_access_authentication_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authentication_rule_by_id*

network_access_authorization_exception_rules**class NetworkAccessAuthorizationExceptionRules**

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_local_exception_rules*

```
create_network_access_local_exception_rule(policy_id, link=None, profile=None, rule=None,  
                                             security_group=None, headers=None, payload=None,  
                                             active_validation=True, **query_parameters)
```

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(policy_id, link=None, profile=None, rule=None, security_group=None, headers=None,  
        payload=None, active_validation=True, **query_parameters)
```

Alias for *create_network_access_local_exception_rule*

```
reset_hit_counts_network_access_local_exceptions(policy_id, headers=None,  
                                                  **query_parameters)
```

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_local_exceptions*

get_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_local_exception_rule_by_id*

update_network_access_local_exception_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*,
rule=None, *security_group=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*,
***query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_policy_set_global_exception_rules(*headers=None*, ***query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *`get_network_access_policy_set_global_exception_rules`***`create_network_access_policy_set_global_exception_rule`**(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` or dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **`link`** (*object*) – link, property of the request body.
- **`profile`** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **`rule`** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **`security_group`** (*string*) – Security group used in authorization policies, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_network_access_policy_set_global_exception_rule_by_id`

`update_network_access_policy_set_global_exception_rule_by_id(id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update global exception authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

`delete_network_access_policy_set_global_exception_rule_by_id`(*id*, *headers=None*, ***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_global_exception_rule_by_id*

network_access_authorization_rules

class NetworkAccessAuthorizationRules

Identity Services Engine Network Access - Authorization Rules API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rules*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).

- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

reset_hit_counts_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`Alias for *`reset_hit_counts_network_access_authorization_rules`***`get_network_access_authorization_rule_by_id(id, policy_id, headers=None, **query_parameters)`**

Network Access Get authorization rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`Alias for *`get_network_access_authorization_rule_by_id`***`update_network_access_authorization_rule_by_id(id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

delete_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`delete_network_access_authorization_rule_by_id`*

network_access_conditions**class NetworkAccessConditions**

Identity Services Engine Network Access - Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_network_access_conditions(headers=None, **query_parameters)`

Network Access Returns all library conditions.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_conditions*

create_network_access_condition(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to exist-ing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner mem-bers of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verifi-cation, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggre-gated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “condi-tonId” OR “ConditionAttrs” fields should contain condition data but not both Logical ag-gregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates

In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_network_access_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_network_access_condition_by_name`(*name*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **`name`** (*basestring*) – name path parameter. Condition name.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`get_network_access_condition_by_name`*


```
update_network_access_condition_by_name(name, attribute_id=None, attribute_name=None,
                                         attribute_value=None, children=None,
                                         condition_type=None, dates_range=None,
                                         dates_range_exception=None, description=None,
                                         dictionary_name=None, dictionary_value=None,
                                         hours_range=None, hours_range_exception=None,
                                         id=None, is_negate=None, link=None, operator=None,
                                         week_days=None, week_days_exception=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

Network Access Update library condition using condition name.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates property Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_name(name, attribute_id=None, attribute_name=None, attribute_value=None, children=None,
               condition_type=None, dates_range=None, dates_range_exception=None,
               description=None, dictionary_name=None, dictionary_value=None, hours_range=None,
               hours_range_exception=None, id=None, is_negate=None, link=None, operator=None,
               week_days=None, week_days_exception=None, headers=None, payload=None,
               active_validation=True, **query_parameters)
```

Alias for *update_network_access_condition_by_name*

delete_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_name*

get_network_access_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None, **query_parameters*)

Alias for *get_network_access_conditions_for_policy_sets*

get_network_access_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_condition_by_id*

update_network_access_condition_by_id(*id, attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update library condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.

- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_id*

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_network_access_condition_by_id`*

network_access_dictionary**class NetworkAccessDictionary**

Identity Services Engine Network Access - Dictionary API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_network_access_dictionaries(headers=None, **query_parameters)`

Get all Dictionaries.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries*

create_network_access_dictionaries(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_dictionaries*

get_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

GET a dictionary by name.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_by_name*

update_network_access_dictionary_by_name(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update a Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_name`(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_by_name*

`delete_network_access_dictionary_by_name`(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **`name`** (*basestring*) – name path parameter. the dictionary name.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_dictionary_by_name*

network_access_dictionary_attribute

class NetworkAccessDictionaryAttribute

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_dictionary_attributes_by_dictionary_name(*dictionary_name*,
headers=None,
**query_parameters)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, headers=None, **query_parameters)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

create_network_access_dictionary_attribute(*dictionary_name*, allowed_values=None,
data_type=None, description=None,
direction_type=None, id=None, internal_name=None,
name=None, headers=None, payload=None,
active_validation=True, **query_parameters)

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).

- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are ‘BOOLEAN’, ‘DATE’, ‘FLOAT’, ‘INT’, ‘IP’, ‘IPV4’, ‘IPV6’, ‘IPV6INTERFACE’, ‘IPV6PREFIX’, ‘LONG’, ‘OCTET_STRING’, ‘STRING’, ‘UNIT32’ and ‘UINT64’.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are ‘IN’, ‘OUT’, ‘NONE’ and ‘BOTH’.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute’s name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

update_network_access_dictionary_attribute_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UNIT32' and 'UINT64'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.

- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'IN', 'OUT', 'NONE' and 'BOTH'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.
- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name*, *name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_attribute_by_name*

network_access_dictionary_attributes_list

class NetworkAccessDictionaryAttributesList

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_dictionaries_authentication(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authentication*

get_network_access_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authorization*

get_network_access_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policysset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)Alias for *get_network_access_dictionaries_policy_set***network_access_identity_stores****class NetworkAccessIdentityStores**

Identity Services Engine Network Access - Identity Stores API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_identity_stores(*headers=None, **query_parameters*)

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)Alias for *get_network_access_identity_stores*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_network_conditions*

create_network_access_network_condition(*cli_dnis_list=None, condition_type=None, description=None, device_group_list=None, device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.

- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).
- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*string*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(cli_dnis_list=None, condition_type=None, description=None, device_group_list=None,
       device_list=None, id=None, ip_addr_list=None, link=None, mac_addr_list=None, name=None,
       headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_network_condition_by_id*

update_network_access_network_condition_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **cli_dnis_list** (*list*) – This field should contain a Caller ID (CLI), comma, and Called ID (DNIS). Line format Caller ID (CLI), Called ID (DNIS), property of the request body (list of strings).
- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **description** (*string*) – description, property of the request body.
- **device_group_list** (*list*) – This field should contain a tuple with NDG Root, comma, and an NDG (that it under the root). Line format NDG Root Name, NDG, Port, property of the request body (list of strings).

- **device_list** (*list*) – This field should contain Device Name. The device name must be the same as the name field in a Network Device object. Line format Device Name, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **ip_addr_list** (*list*) – This field should contain IP address or subnet. IP address can be IPV4 format (n.n.n.n) or IPV6 format (n:n:n:n:n:n:n). IP subnet can be IPV4 format (n.n.n.n/m) or IPV6 format (n:n:n:n:n:n:n/m). Line format IP Address or subnet, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **mac_addr_list** (*list*) – This field should contain Endstation MAC address, comma, and Destination MAC addresses. Each Max address must include twelve hexadecimal digits using formats nn:nn:nn:nn:nn:nn or nn-nn-nn-nn-nn-nn or nnnn.nnnn.nnnn or nnnnnnnnnnnn. Line format Endstation MAC, Destination MAC , property of the request body (list of strings).
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *cli_dnis_list=None*, *condition_type=None*, *description=None*, *device_group_list=None*, *device_list=None*, *ip_addr_list=None*, *link=None*, *mac_addr_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_network_condition_by_id*

delete_network_access_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_network_condition_by_id*

network_access_policy_set**class NetworkAccessPolicySet**

Identity Services Engine Network Access - Policy Set API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_policy_sets(*headers=None*, ***query_parameters*)

Get all network access policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_policy_sets*

create_network_access_policy_set(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'enabled', 'disabled' and 'monitor'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set*

reset_hit_counts_network_access_policy_sets(*headers=None, **query_parameters*)

Network Access Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_policy_sets*

get_network_access_policy_set_by_id(*id, headers=None, **query_parameters*)

Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_policy_set_by_id*

update_network_access_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.

- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_by_id*

delete_network_access_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_network_access_policy_set_by_id`*

network_access_profiles**class NetworkAccessProfiles**

Identity Services Engine Network Access - Profiles API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

`get_network_access_profiles(headers=None, **query_parameters)`

Network Access Returns list of profiles. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_security_groups*

network_access_service_names

class NetworkAccessServiceNames

Identity Services Engine Network Access - Service Names API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_service_names(headers=None, **query_parameters)

Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(list)**: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_network_access_service_names*

network_access_time_date_conditions

class NetworkAccessTimeDateConditions

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.2_beta).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

Policy APIs for manage Policy Sets, authorization policies, authentication policies, and policy elements.

get_network_access_time_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_time_conditions*

create_network_access_time_condition(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates time/date condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_id=None, attribute_name=None, attribute_value=None, children=None,
        condition_type=None, dates_range=None, dates_range_exception=None, description=None,
        dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None,
        id=None, is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_access_time_condition*

```
get_network_access_time_condition_by_id(id, headers=None, **query_parameters)
```

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_time_condition_by_id*

update_network_access_time_condition_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id*=None, *attribute_name*=None, *attribute_value*=None, *children*=None, *condition_type*=None, *dates_range*=None, *dates_range_exception*=None, *description*=None, *dictionary_name*=None, *dictionary_value*=None, *hours_range*=None, *hours_range_exception*=None, *is_negate*=None, *link*=None, *name*=None, *operator*=None, *week_days*=None, *week_days_exception*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for [update_network_access_time_condition_by_id](#)

delete_network_access_time_condition_by_id(*id*, *headers*=None, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

[RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ***query_parameters*)

Alias for [delete_network_access_time_condition_by_id](#)

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.2_beta).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

Network Device API allows the client to add, delete, update, and search network devices. Please note that each API description shows whether the API is supported in bulk operation. The bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re- vi- sion #	Re- source Ver- sion	Cisco ISE Ver- sion	Description	Revision Modifi- cation	Revision Modification Description
0	1.0	1.2	Initial Cisco ISE Version	Attribute	Description
1	1.1	2.0	Cisco ISE 2.0 model changes for TACACS+ and 3rd-Party support	tacacsSet- tings:sharedSecret	Added Attribute 'shared-Secret' for Tacacs+ sup- port
				tacacsSet- tings:connectModeOptions	Added Attribute 'connect- ModeOptions' for Tacacs+ support
				profileName	Added Attribute 'profile- Name' for 3rd-Party sup- port support
				coaPort	Added Attribute 'coaPort' for 3rd-Party support sup- port
2	1.2	2.4	Cisco ISE 2.4 model changes for Multi shared secret and DTLS Required support	authenticationset- tings:enableMultiSecret	Added Attribute 'enable- MultiSecret' for multiple shared secret
				authenticationset- tings:secondRadiusSharedSecret	Added Attribute 'secon- dRadiusSharedSecret' for multiple shared secret
				authenticationset- tings:dtlsRequired	Added Attribute 'dtlsRe- quired' for dtls settings

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Val- ues
name	String	Yes	Resource Name		ISE_EST_Local_Host
id	String	No	Resource UUID, manda- tory for update		79aac430- 7cc8- 11eb-ad58- 005056926583
description	String	No			example nd
authentication- Settings	List	Yes			
<ul style="list-style-type: none"> en- ableKey- Wrap 	Boolean	Yes			false

continues on next page

Table 51 – continued from previous page

• enabled	Boolean	Yes		false	
• keyEn- ryption- Key	String	Yes			1234567890123456
• keyInput- Format	Enum	Yes	Allowed val- ues: ASCII, HEXADECI- MAL	ASCII	
• mes- sageAu- thenti- cator- CodeKey	String	No			12345678901234567890
• net- workPro- tocol	Enum	No	Allowed val- ues: RADIUS, TACACS_PLUS	RADIUS	
• ra- diusShared- Secret	String	No			VHEGKOC- CUHYB
• enable- MultiSe- cret	Boolean	No			false
• sec- ondRa- diusShared- Secret	String	No			
• dtlsRe- quired	Boolean	No	This value enforces use of dtls	false	
coaPort	Integer	Yes	Since 2.0 (for 3rd party)		0

continues on next page

Table 51 – continued from previous page

dtlsDnsName	String	No	This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate		ISE213.il.com
NetworkDeviceIPList	List	Yes	List of IP Subnets for this node		
• ipAddress	String	Yes	It can be either single IP address or IP range address		127.0.0.1
• getIpAddressExclude	String	Yes	It can be either single IP address or IP range address		
• mask	Integer	Yes			32
NetworkDeviceGroupList	List	No	List of Network Device Group names for this node		[“Location#All Locations”, “Device Type#All Device Types”]
modelName	String	No			
softwareVersion	String	No			
profileName	String	Yes	Since 2.0 (for 3rd party)	true	Cisco
snmpsettings	List	Yes			
• linkTrapQuery	Boolean	Yes	SNMP link Trap Query	true	
• macTrapQuery	Boolean	Yes	SNMP MAC Trap Query	true	
• originatingPolicyServicesNode	String	Yes	Originating Policy Services Node	Auto	

continues on next page

Table 51 – continued from previous page

• polling-Interval	Integer	Yes	SNMP Polling Interval in seconds (Valid Range 600 to 86400)	3600	
• roCommunity	String	No	SNMP RO Community		aaa
• version	Enum	No	Allowed values: ONE, TWO_C, THREE		ONE
tacacsSettings	List	Yes	Since 2.0 (for Tacacs+)		
• connect-ModeOptions	Enum	No	Allowed values: OFF, ON_LEGACY, ON_DRAFT_COMPLIANT		ON_LEGACY
• sharedSecret	String	Yes	Since 2.0		aaa
trustsecsettings	List	Yes			
• deviceAuthenticationSettings	List	Yes			
• sgaDeviceId	String	No			networkDevice1
• sgaDevicePassword	String	No			aaa
• device-ConfigurationDeployment	List	Yes			
• enable-Mode-Password	String	No			aaa

continues on next page

Table 51 – continued from previous page

• exec-Mode-Password	String	No			aaa
• exec-ModeUser-name	String	No			aaa
• include-WhenDeployingSGTUpdates	Boolean	No		false	
• sgaNotificationAndUpdates	List	Yes			
• downloadEnvironmentDataEveryXSeconds	Integer	No		86400	
• downloadPeerAuthorizationPolicyEveryXSeconds	Integer	No		86400	
• downloadSGACLListsEveryXSeconds	Integer	No		86400	

continues on next page

Table 51 – continued from previous page

• otherS-GADe-vices-ToTrust-ThisDe-vice	Boolean	No		false	
• reAu-thentica-tionEv-eryXSec-onds	Integer	No		86400	
• sendCon-figura-tionToDe-vice	Boolean	No		false	
• sendCon-figura-tionToDe-viceUsing	Enum	No	Allowed values: EN-ABLE_USING_COA, EN-ABLE_USING_CLI, DIS-ABLE_ALL	EN-ABLE_USING_COA	

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*,
description=None, *dtls_dns_name=None*, *id=None*,
model_name=None, *network_device_group_list=None*,
network_device_ip_list=None, *profile_name=None*, *snmpsettings=None*,
software_version=None, *tacacs_settings=None*, *trustsecsettings=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_by_name*

get_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_id*

update_network_device_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_id*

delete_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_device_by_id`*

`get_network_device`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device*

`get_network_device_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`sortasc (basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc (basestring)`** – sortdsc query parameter. sort desc.
- **`filter (basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type (basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.

- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group

class NetworkDeviceGroup

Identity Services Engine NetworkDeviceGroup API (version: 3.2_beta).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

Network Device Group API allows the client to search network device groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.3	Initial Cisco ISE Version
1	1.1	2.4	Added GetByName operation

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	Device Type#All Device Types
id	String	No	Resource UUID, mandatory for update	70c79c30-8bff-11e6-996c-525400b48521
descrip-tion	String	No		All Device Types
other-name	String	No		Device Type

get_network_device_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group_by_name*

get_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_network_device_group_by_id`*

`update_network_device_group_by_id(id, description=None, name=None, ndgtype=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a network device group.

Parameters

- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`ndgtype (string)`** – ndgtype, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *ndgtype=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_group_by_id*

delete_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_group_by_id*

get_network_device_group(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdesc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.

- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_group*

get_network_device_group_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.

- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, ndgtype=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **ndgtype** (*string*) – ndgtype, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, ndgtype=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_deployment

class NodeDeployment

Identity Services Engine Node Deployment API (version: 3.2_beta).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

get_nodes(*filter=None, filter_type=None, headers=None, **query_parameters*)

The API lists all the nodes that are deployed in the cluster. Returns basic information about each of the deployed nodes in the cluster like hostname, status, roles, and services. Supports filtering on FQDN, host-name, IP address, roles, services and node status. .

Parameters

- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering is available through the filter query string parameter. The structure of a filter is a triplet of field operator and value, separated by dots. More than one filter can be sent. The logical operator common to all filter criteria is AND by default, and can be changed by using the “filter-Type=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to all filter criteria is AND by default, and can be changed by using this parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

register_node(*allow_cert_import=None, fqdn=None, password=None, roles=None, services=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API registers a Cisco ISE node to form a multi-node deployment. Approximate execution time 300 seconds. .

Parameters

- **allow_cert_import** (*boolean*) – Consent to import the self- signed certificate of the registering node. , property of the request body.
- **fqdn** (*string*) – fqdn, property of the request body.
- **password** (*string*) – password, property of the request body.
- **roles** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are ‘PrimaryAdmin’, ‘PrimaryDedicatedMonitoring’, ‘PrimaryMonitoring’, ‘SecondaryAdmin’, ‘SecondaryDedicatedMonitoring’, ‘SecondaryMonitoring’ and ‘Standalone’).
- **services** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are ‘DeviceAdmin’, ‘PassiveIdentity’, ‘Profiler’, ‘SXP’, ‘Session’, ‘TC-NAC’, ‘pxGrid’ and ‘pxGridCloud’).
- **user_name** (*string*) – userName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves detailed information of the deployed node. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*hostname*, *headers=None*, ***query_parameters*)Alias for *get_node_details***`update_node`**(*hostname*, *roles=None*, *services=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API updates the configuration of the Cisco ISE node with the configuration provided. Approximate execution time 300 seconds. .

Parameters

- **`roles`** (*list*) – Roles can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'PrimaryAdmin', 'PrimaryDedicatedMonitoring', 'PrimaryMonitoring', 'SecondaryAdmin', 'SecondaryDedicatedMonitoring', 'SecondaryMonitoring' and 'Standalone').
- **`services`** (*list*) – Services can be empty or have many values for a node. , property of the request body (list of strings. Available values are 'DeviceAdmin', 'PassiveIdentity', 'Profiler', 'SXP', 'Session', 'TC-NAC', 'pxGrid' and 'pxGridCloud').
- **`hostname`** (*basestring*) – hostname path parameter. Hostname of the deployed node.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node(hostname, headers=None, **query_parameters)

The deregistered node becomes a standalone Cisco ISE node. It retains the last configuration that it received from the primary PAN and assumes the default roles and services of a standalone node. Approximate execution time 300 seconds. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. The hostname of the node in the deployment to be deregistered.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

make_primary(headers=None, **query_parameters)

This API promotes the standalone node on which the API is invoked to the primary Policy Administration node (PAN). .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

promote_node(*headers=None, **query_parameters*)

Execute this API in the secondary PAN in the cluster to promote the node to primary PAN. Ensure that the API Gateway setting is enabled in the secondary PAN. Approximate execution time 300 seconds. .

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

make_standalone(*headers=None, **query_parameters*)

This API changes the primary PAN in a single node cluster on which the API is invoked, to a standalone node. .

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`sync_node`(*hostname*, *headers=None*, ***query_parameters*)

Performing a manual synchronization involves a reload of the target node, but not the primary PAN. Approximate execution time 300 seconds.

Parameters

- **`hostname`** (*basestring*) – hostname path parameter. Hostname of the node.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_group**class NodeGroup**

Identity Services Engine Node Group API (version: 3.2_beta).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

`get_node_groups`(*headers=None*, ***query_parameters*)

This API retrieves the details of all the node groups in the cluster. Each node group retrieved consists of name, description and MAR cache details like query-attempts, query-timeout, replication-attempts, replication- timeout. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*description=None, mar_cache=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a node group in the cluster. A node group is a group of PSNs, where the PSNs maintain a heartbeat with each other. It is used primarily to terminate or transfer posture-pending sessions when a PSN in a local node group fails. Node group members can communicate over TCP/7800. The following parameters are used in the request body of the API:

PARAMETER	DESCRIPTION	EXAMPLE
name	* required Name of the node group (valid-range: 1-100 characters)	{“name”: “site1”}
description	Description of the node group (valid-range: 0-256 characters)	{“name”: “site2”, “description”: “sample”}
query-attempts	The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1)	{“name”: “site3”, “marCache”: {“query-attempts”: 1}}
query-timeout	The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2)	{“name”: “site4”, “marCache”: {“query-timeout”: 2}}
replication-attempts	The number of times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2)	{“name”: “site5”, “marCache”: {“replication-attempts”: 2}}
replication-timeout	The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5)	{“name”: “site6”, “marCache”: {“replication-timeout”: 5}}

 NOTE 1: : Node group name and description cannot contain any of the following characters: ! % ^ : ; , . ~ @ # & [{ (|) }] ` > < / " ' + = ? NOTE 2: : Parameter marCache stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory- authentication users. We can enable the marCache for a nodegroup by providing key “marCache” in json request. Additionally we may also provide any combination of parameters query-attempts, query-timeout, replication- attempts, replication-timeout in marCache object. If no value is specified for a particular parameter its default value will be recorded.If no marCache object is given, marCache will be considered as disabled. .

Parameters

- **description** (*string*) – description, property of the request body.
- **mar_cache** (*object*) – marCache, property of the request body.
- **name** (*string*) – name, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the details of a node group in the cluster using a node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_node_group(*node_group_name*, *description=None*, *mar_cache=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to update an existing node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** *name* * required Name of the node group existing in ISE(valid-range: 1-100 characters) **NOTE** : name of an existing node group cannot be modified. “name” parameter should be identical to the node group name(*nodeGroupName*) provided in the path {“name”: “site1”} *description* Description of the node group (valid-range: 0-256 characters) {“name”: “site2”, “description”: “sample”} *query-attempts* The number of times Cisco ISE attempts to perform the cache entry query. (valid-range: 0 5, default-value: 1) {“name”: “site3”, “marCache”: {“query-attempts”: 1}} *query-timeout* The time, in seconds, after which a cache entry query times out. (valid-range: 1 10, default-value: 2) second(s) {“name”: “site4”, “marCache”: {“query-timeout”: 2}} *replication-attempts* The number of times Cisco ISE attempts to perform MAR cache entry replication. (valid-range: 0 5, default-value: 2) {“name”: “site5”, “marCache”: {“replication-attempts”: 2}} *replication-timeout* The time, in seconds, after which the cache entry replication times out. (valid-range: 1 10, default-value: 5) second(s) {“name”: “site6”, “marCache”: {“replication-timeout”: 5}} **NOTE 1:** Node group name and description cannot contain any of the following characters: ! % ^ : ; , . ~ @ # & [{ (|) }] ` > < / ” + = ? **NOTE 2:** Parameter *marCache* stands for Machine Access Restriction (MAR) cache that provides an additional means of controlling authorization for Active Directory-authentication users. We can enable the *marCache* for a nodegroup by providing key “marCache” in json request. Additionally we may also provide any combination of parameters *query-attempts*, *query-timeout*, *replication-attempts*, *replication-timeout* in *marCache* object. If no value is specified for a particular parameter its default value will be recorded. If no *marCache* object is given, *marCache* will be disabled. .

Parameters

- **description** (*string*) – description, property of the request body.
- **mar_cache** (*object*) – *marCache*, property of the request body.
- **name** (*string*) – name, property of the request body.
- **node_group_name** (*basestring*) – *nodeGroupName* path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- *headers(MyDict)*: response headers.
- *response(MyDict)*: response body as a *MyDict* object. Access the object’s properties by using the dot notation or the bracket notation.
- *content(bytes)*: representation of the request’s response
- *text(str)*: representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node_group(*force_delete*, *node_group_name*, *headers=None*, ***query_parameters*)

Delete an existing node group in the cluster. Deleting the node group does not delete the nodes, but failover is no longer carried out among the nodes.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **force_delete** (*bool*) – forceDelete query parameter. Force delete the group even if the node group contains one or more nodes.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

add_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API adds a node to the node group in the cluster. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all the URL-redirceted sessions on the failed node. The following parameters are used in the request body of the API: PARAMETER DESCRIPTION EXAMPLE hostname * required Name of the host name {"hostname": "isnode"}

Parameters

- **hostname** (*string*) – hostname, property of the request body.
- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_nodes(*node_group_name*, *headers=None*, ***query_parameters*)

This API retrieves the list of nodes associated with a node group in the cluster with a given node group name.

Parameters

- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

remove_node(*node_group_name*, *hostname=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to remove a node from a node group in the cluster. Removing node from the node group does not delete the node, but failover is no longer carried out if the node is not part any node group. The following parameters are used in the request body of the API: **PARAMETER DESCRIPTION EXAMPLE** **hostname** * required Name of the host name {“hostname”: “isencode”} .

Parameters

- **hostname** (*string*) – hostname, property of the request body.
- **node_group_name** (*basestring*) – nodeGroupName path parameter. Name of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_services

class NodeServices

Identity Services Engine Node Services API (version: 3.2_beta).

Wraps the Identity Services Engine Node Services API and exposes the API as native Python methods that return native Python objects.

get_interfaces(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the list of interfaces on a node in a cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sxp_interface(hostname, headers=None, **query_parameters)

This API retrieves the SXP interface. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_sxp_interface(hostname, interface=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API configures the SXP interface. .

Parameters

- **interface** (*string*) – interface, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_probe_config(*hostname*, *headers=None*, ***query_parameters*)

This API retrieves the profiler probe configuration of a PSN. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
set_profiler_probe_config(hostname, active_directory=None, dhcp=None, dhcp_span=None,  
                           dns=None, http=None, netflow=None, nmap=None, pxgrid=None,  
                           radius=None, snmp_query=None, snmp_trap=None, headers=None,  
                           payload=None, active_validation=True, **query_parameters)
```

This API updates the profiler probe configuration of a PSN. Set probe value as null to disable probe. Ex: Below payload will disable NMAP, PxGrid and SNMPTRAP probes { "activeDirectory": { "daysBeforeRescan": 1 }, "dhcp": { "interfaces": "[{"interface":"GigabitEthernet 0"}]", "port": 0 }, "dhcpSpan": { "interfaces": "[{"interface":"GigabitEthernet 0"}]" }, "dns": { "timeout": 2 }, "http": { "interfaces": "[{"interface":"GigabitEthernet 0"}]" }, "netflow": { "interfaces": "[{"interface":"GigabitEthernet 0"}]" }, "port": 0 }, "nmap": null , "pxgrid": null , "radius": [], "snmpQuery": { "eventTimeout": 30, "retries": 2, "timeout": 1000 }, "snmpTrap": null } .

Parameters

- **active_directory** (*object*) – The Active Directory probe queries the Active Directory for Windows information., property of the request body.
- **dhcp** (*object*) – The DHCP probe listens for DHCP packets from IP helpers., property of the request body.
- **dhcp_span** (*object*) – The DHCP SPAN probe collects DHCP packets., property of the request body.
- **dns** (*object*) – The DNS probe performs a DNS lookup for the FQDN., property of the request body.
- **http** (*object*) – The HTTP probe receives and parses HTTP packets., property of the request body.
- **netflow** (*object*) – The NetFlow probe collects the NetFlow packets that are sent to it from routers., property of the request body.
- **nmap** (*list*) – The NMAP probe scans endpoints for open ports and OS., property of the request body (list of objects).
- **pxgrid** (*list*) – The pxGrid probe fetches attributes of MAC address or IP address as a subscriber from the pxGrid queue., property of the request body (list of objects).
- **radius** (*list*) – The RADIUS probe collects RADIUS session attributes as well as CDP, LLDP, DHCP, HTTP, and MDM attributes from IOS Sensors., property of the request body (list of objects).
- **snmp_query** (*object*) – The SNMP query probe collects details from network devices such as interface, CDP, LLDP, and ARP., property of the request body.
- **snmp_trap** (*object*) – The SNMP trap probe receives linkup, linkdown, and MAC notification traps from network devices., property of the request body.
- **hostname** (*basestring*) – hostname path parameter. Hostname of the node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_details**class NodeDetails**

Identity Services Engine NodeDetails API (version: 3.2_beta).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

Node Details API allows the client to get deployment node details, get all nodes and filter nodes based on `NodeServiceTypes`.

Revision History

Re-vi-sion #	Re-source Ver-sion	Cisco ISE Version	Description	Revision Modifi-cation	Revision Modification
				Attribute	Description
0	1.0	2.2	Initial Cisco ISE Ver-sion		
1	1.1	2.4	Support Node Service Types as part of Node Object	NodeSer-viceTypes	Added String Field <code>NodeServiceTypes</code> . String represents services configured on the Node
2	1.2	2.7	Support Node FQDN as part of Node Object	fqdn	Added String Field FQDN. String represents FQDN of the Node
3	1.3	3.0	Support SXP IP Ad-dress as part of Node Details	sxpIpAd-dress	Added String Field <code>sxpIpAddress</code> . String represents SXP IP Address of the Node

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No		
gateWay	String	No		10.0.10.11
displayName	String	No		TestNode
inDeployment	Boolean	No		false
ipAddresses	String	No		["10.0.0.1", "10.0.0.2"]
otherPapFqdn	String	No		OtherTestNode
ipAddress	String	No		10.0.0.3
sxpIpAddress	String	No		10.10.10.1
nodeService-Types	String	No		DEVICE ADMIN
fqdn	String	No		test.ers.cisco.com
primaryPapNode	Boolean	No		true
papNode	Boolean	No		true
pxGridNode	Boolean	No		true

get_node_detail_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_name*

get_node_detail_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the node details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.2_beta).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

get_pan_ha_status(*headers=None, **query_parameters*)

In a high availability configuration, the primary PAN is in active state. The secondary PAN (backup PAN) is in standby state, which means that it receives all the configuration updates from the primary PAN, but is not active in the Cisco ISE cluster. You can configure Cisco ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or any combination of these. If the PANs are in different data centers, you must have a health check node for each PAN. All the fields are mandatory to enable PanHA. Values of failedAttempts, pollingInterval, primaryHealthCheckNode, and secondaryHealthCheckNode are not considered when the isEnabled value is “false” in the request body.

Parameters

- **failed_attempts** (*integer*) – Failover occurs if the primary PAN is down for the specified number of failure polls. Count (2 60). The default value is 5. , property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.

- **polling_interval** (*integer*) – Administration nodes are checked after each interval. Seconds (30 300) The default value is 120. , property of the request body.
- **primary_health_check_node** (*object*) – primaryHealthCheckNode, property of the request body.
- **secondary_health_check_node** (*object*) – secondaryHealthCheckNode, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

patching

class Patching

Identity Services Engine Patching API (version: 3.2_beta).

Wraps the Identity Services Engine Patching API and exposes the API as native Python methods that return native Python objects.

list_installed_hotpatches(*headers=None, **query_parameters*)

List all the installed hot patches in the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`install_hotpatch`(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch installation process. As hot patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **`hotpatch_name`** (*string*) – hotpatchName, property of the request body.
- **`repository_name`** (*string*) – repositoryName, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`rollback_hotpatch`(*hotpatch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers hot patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the hot patch rollback process. As hot patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **hotpatch_name** (*string*) – hotpatchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

list_installed_patches(*headers=None, **query_parameters*)

List all the installed patches in the system, with the patch number for rollback. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

install_patch(*patch_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch installation on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch installation process. As the patch installation triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_name** (*string*) – patchName, property of the request body.
- **repository_name** (*string*) – repositoryName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

rollback_patch(*patch_number=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers patch rollback on the Cisco ISE node. A task ID is returned which can be used to monitor the progress of the patch rollback process. As the patch rollback triggers the Cisco ISE to restart, the task API becomes unavailable for a certain period of time. .

Parameters

- **patch_number** (*integer*) – patchNumber, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting

class PortalGlobalSetting

Identity Services Engine PortalGlobalSetting API (version: 3.2_beta).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

The Portal Global Setting API allows the user to customize the text that is displayed in the Cisco ISE portals. This global setting controls whether HTML alone or both HTML and Javascript are permitted to be used in customized text.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
id	String	Yes	Resource UUID value	21013cb2-d030-4fb1-9ba2-35757634d770
cus- tomization	Enum	Yes	Allowed values: HTML, HTMLAND-JAVASCRIPT	HTML

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ****query_parameters**)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

get_portal_global_settings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_theme

class PortalTheme

Identity Services Engine PortalTheme API (version: 3.2_beta).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

Portal Theme API allows the client to add, delete, update and search Portal Theme among other operations which are available from all the portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Blue theme
id	String	No	Resource UUID, mandatory for update	9eb421c0-8c01-11e6-996c-525400b48521
description	String	No		
theme-Data	String	Yes	Portal Theme for all portals	Base 64 encoded string of CSS file

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_portal_theme_by_id***update_portal_theme_by_id**(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_theme_by_id*

delete_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_portal_theme_by_id*

get_portal_themes(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

get_portal_themes_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes_generator*

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_portal_theme*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler

class Profiler

Identity Services Engine Profiler API (version: 3.2_beta).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_profiles(*headers=None*, ***query_parameters*)

getProfiles.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

profiler_profile

class ProfilerProfile

Identity Services Engine ProfilerProfile API (version: 3.2_beta).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

Profiler Profile API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	2Wire-Device
id	String	No	Resource UUID, mandatory for update	fe8c7cc0-8bff-11e6-996c-525400b48521
description	String	No		Policy for 2Wire-Device
parentId	String	Yes		

get_profiler_profile_by_id(id, headers=None, **query_parameters)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_profiler_profile_by_id***get_profiler_profiles**(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_profiler_profiles_generator`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.2_beta).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

register_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reregister_service(headers=None, **query_parameters)`

ServiceReregister.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`authorization(headers=None, **query_parameters)`

Authorization.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service**class PsnNodeDetailsWithRadiusService**

Identity Services Engine `PsnNodeDetailsWithRadiusService` API (version: 3.2_beta).

Wraps the Identity Services Engine `PsnNodeDetailsWithRadiusService` API and exposes the API as native Python methods that return native Python objects.

PSN Node Details with RADIUS Service API allows the client to get deployment node details where 'Session Services' is enabled.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	TestNode
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
description	String	No		PSN with Session Service
ipAddress	String	Yes		10.0.0.1

`get_session_service_node_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_id*

get_session_service_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node*

get_session_service_node_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

pull_deployment_info

class PullDeploymentInfo

Identity Services Engine PullDeploymentInfo API (version: 3.2_beta).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

Pull Deployment Info API allows clients to get the complete information about a Cisco ISE deployment. The information includes details about the deployment, network access, NADs, MDMs, licenses, posture and profiler.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.7	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description
name	String	Yes	Resource Name
id	String	No	Resource UUID, mandatory for update
description	String	No	
networkAccessInfo	List	No	networkAccessInfo Details
• deploymentID	String	Yes	Deployment ID
• isCsnEnabled	Boolean	Yes	false
• nodeList	List	Yes	Node list

continues on next page

Table 52 – continued from previous page

• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• sdaVNs	List	No	
• trustSecControl	String	No	ISE
• radius3RdParty	List	No	
profilerInfo	List	No	profilerInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Includes 'profiles' which is an array of dictionaries describing various attributes with the properties:- profile (List), - customProfilesCount (Integer), - endpointTypes (String), - totalProfilesCount (Integer), - uniqueEndpointsCount (Integer), - unknownEndpointsCount (Integer), - totalEndpointsCount (Integer), - unknownEndpointsPercentage (Integer)
deploymentInfo	List	No	deploymentInfo Details
• deploymentID	String	Yes	Deployment ID

continues on next page

Table 52 – continued from previous page

• versionHistoryInfo	List	No	Array of dictionaries describing various attributes with the properties:- opType (String), - mainVersion (String), - epochTime (Integer)
• nodeList	List	Yes	Node list
• nodeAndNode-CountAnd-CountInfo	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• fipsstatus	String	No	Disabled
nadInfo	List	No	nadInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes 'content' which is an array of dictionaries describing various attributes with the properties:- name (String), - declaredType (String), - scope (String), - value (List), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
• nadcountInfo	List	No	
• totalActiveNAD-Count	Integer	No	0
mdmInfo	List	No	mdmInfo Details

continues on next page

Table 52 – continued from previous page

• activeMdmServersCount	Integer	Yes	0
• activeDesktopMdmServersCount	Integer	Yes	0
• activeMobileMdmServersCount	Integer	Yes	0
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes ‘content’ which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
licensesInfo	List	No	licensesInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• nodeAndScope	List	No	Includes ‘content’ which is an array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
postureInfo	List	No	postureInfo Details

continues on next page

Table 52 – continued from previous page

• content	List	Yes	Array of dictionaries describing various attributes with the properties:- name (String), - declared-Type (String), - scope (String), - value (Varies), - nil (Boolean), - globalScope (Boolean), - typeSubstituted (Boolean)
kongInfo	List	No	kongInfo Details
• deploymentID	String	Yes	Deployment ID
• nodeList	List	Yes	Node list
• node	List	No	Array of dictionaries describing various attributes with the properties:- sn (String), - service (List)

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **timeout** (*float*, *tuple*) – How long to wait for the server to send data before giving up.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings

class PxGridSettings

Identity Services Engine PxGridSettings API (version: 3.2_beta).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

pxGrid Settings API allows the client to change auto-approve settings for pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		
id	String	No	Resource UUID, mandatory for up- date		
description	String	No			
autoApproveCert- BasedAccounts	Boolean	Yes	Auto approve certificate based ac- counts when true	false	true
allowPassword- BasedAccounts	Boolean	Yes	Allow password based acoounts when true	false	

```
autoapprove_px_grid_settings(allow_password_based_accounts=None,
                             auto_approve_cert_based_accounts=None, headers=None,
                             payload=None, active_validation=True, **query_parameters)
```

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
autoapprove(allow_password_based_accounts=None, auto_approve_cert_based_accounts=None,
            headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *autoapprove_px_grid_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.2_beta).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxe*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_failures(*headers=None, **query_parameters*)

getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.2_beta).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

RADIUS Server Sequence API allows the client to add, delete, update, search and perform actions on RADIUS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.3	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		name
id	String	No	Resource UUID, mandatory for update		ab6dedd-fcc2-47ff-8577-0014737c8fcf
description	String	No			description
stripPrefix	Boolean	No		false	
stripSuffix	Boolean	No		false	
prefixSeparator	String	No	The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character		
suffixSeparator	String	No	The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character	@	
remoteAccounting	Boolean	No		true	
localAccounting	Boolean	No		false	
useAttrSetOnRequest	Boolean	No		false	
useAttrSetBeforeAcc	Boolean	No		false	
continueAuthorzPolicy	Boolean	No		false	
radiusServers	List	Yes	List with names of external radius server. The order of the names in the list is the order of servers that will be used during authentication		[“externalRadiusServer1”, “externalRadiusServer2”]
onRequestAttrManipulators	List	No	The onRequestAttrManipulators is required only if useAttrSetOnRequest is true		
<ul style="list-style-type: none"> Attribute-Manipulator 	List	No			
2734				Chapter 1.	The User Guide
<ul style="list-style-type: none"> action 	Enum	Yes	Allowed Values: ADD,		ADD

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).

- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list*=None, *continue_authorz_policy*=None, *description*=None, *local_accounting*=None, *name*=None, *on_request_attr_manipulator_list*=None, *prefix_separator*=None, *radius_server_list*=None, *remote_accounting*=None, *strip_prefix*=None, *strip_suffix*=None, *suffix_separator*=None, *use_attr_set_before_acc*=None, *use_attr_set_on_request*=None, *headers*=None, *payload*=None, *active_validation*=True, ****query_parameters**)

Alias for *update_radius_server_sequence_by_id*

delete_radius_server_sequence_by_id(*id*, *headers*=None, ****query_parameters**)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ****query_parameters**)

Alias for *delete_radius_server_sequence_by_id*

get_radius_server_sequence(*page*=None, *size*=None, *headers*=None, ****query_parameters**)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence***`get_radius_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_radius_server_sequence_generator*

```
create_radius_server_sequence(before_accept_attr_manipulators_list=None,
                             continue_authorz_policy=None, description=None,
                             local_accounting=None, name=None,
                             on_request_attr_manipulator_list=None, prefix_separator=None,
                             radius_server_list=None, remote_accounting=None,
                             strip_prefix=None, strip_suffix=None, suffix_separator=None,
                             use_attr_set_before_acc=None, use_attr_set_on_request=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API creates a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.2_beta).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

REST ID Store API allows clients to add, get, update and delete REST ID stores.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	3.0	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	RestIdStore1
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		Object that represents the restID store
ersRestIDStoreAttributes	List	Yes	Holds the attributes of the restID object	
• username-Suffix	String	Yes	Suffix of the user-name domain	@place.com
• rootUrl	String	Yes	url of the root of the RestIDStore	rootUrl
• predefined	Enum	Yes	The cloud provider connected to of the RestIDStore. Options are: - Azure, - Okta, - None	Azure
• headers	List	Yes	Headers for the RestIDStore	
• key	String	Yes	Key of the header	tenantID
• value	String	Yes	Value of the header	tenantID_value

get_rest_id_store_by_name(name, headers=None, **query_parameters)

This API allows the client to get a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_name*

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_name*

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store*

get_rest_id_store_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, ers_rest_idstore_user_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **ers_rest_idstore_user_attributes** (*object*) – ersRestIDStoreUserAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, ers_rest_idstore_user_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.2_beta).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None, **query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_repositories*

create_repository(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.

- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and `_./@$` characters., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_repository*

get_repository(*repository_name, headers=None, **query_parameters*)

Get a specific repository identified by the name passed in the URL. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*repository_name*, *headers=None*, ***query_parameters*)Alias for *get_repository***update_repository**(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*repository_name*, *enable_pki=None*, *name=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_repository*

delete_repository(*repository_name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*repository_name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **repository_name** (*basestring*) – repositoryName path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_files(*repository_name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider**class SmsProvider**

Identity Services Engine SMSProvider API (version: 3.2_beta).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

SMS Provider API allows the client to search the SMS providers configured from Cisco ISE GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	b1155994-b736-46af-9add-04bed3058e3a
description	String	No		

get_sms_provider(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

`get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

Alias for `get_sms_provider`

`get_sms_provider_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sxp_connections**class SxpConnections**

Identity Services Engine SXPCConnections API (version: 3.2_beta).

Wraps the Identity Services Engine SXPCConnections API and exposes the API as native Python methods that return native Python objects.

SXP Connections API allows clients to add, get, update and delete the Security Group Tag (SGT) Exchange Protocol (SXP) connections.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	sxpVpn	Attribute can include some VPNs separated by comma

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		Brief description about network peer
sxpPeer	String	Yes		Sxp Peer Name
sxpVpn	String	Yes		Sxp VPN Name
sxpNode	String	Yes		Sxp Node Name
ipAddress	String	Yes		Sxp Peer IP address
sxpMode	String	Yes		Sxp Mode
sxpVersion	String	Yes		Sxp Version
enabled	Boolean	Yes		true

get_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*,
sxp_mode=None, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*,
sxp_vpn=None, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None,
             sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None,
             active_validation=True, **query_parameters)
```

Alias for `update_sxp_connections_by_id`

```
delete_sxp_connections_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP connection.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sxp_connections_by_id`

```
get_sxp_connections(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                   sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

create_sxp_connections(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.

- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_connections*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_connections(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_connections*

sxp_local_bindings

class SxpLocalBindings

Identity Services Engine SXPLocalBindings API (version: 3.2_beta).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

SXP Local Bindings API allows clients to add, get, update and delete SGT static mappings.

Revision History

Revi- sion #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	3.0	Cisco ISE 3.0 model changes	vns	Added new property for the Virtual Networks

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	f9269682-dcaf-11e3-ad0a-5bdcd2d9fd69
description	String	No		
binding-Name	String	No	This field is deprecated from Cisco ISE 3.0	
ipAddressOrHost	String	Yes	IP address for static mapping (hostname is not supported)	ipAddressOrHost
sgt	String	Yes	SGT name or ID	sgt_id
sxpVpn	String	Yes	List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined	Sxp Vpn Name
vns	String	Yes	List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined	virtualNetwork

get_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_local_bindings_by_id*

update_sxp_local_bindings_by_id(*id*, *binding_name=None*, *description=None*,
ip_address_or_host=None, *sgt=None*, *sxp_vpn=None*, *vns=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, binding_name=None, description=None, ip_address_or_host=None, sgt=None,
             sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_sxp_local_bindings_by_id`

```
delete_sxp_local_bindings_by_id(id, headers=None, **query_parameters)
```

This API deletes a SXP local binding.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

get_sxp_local_bindings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

create_sxp_local_bindings(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_local_bindings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_local_bindings(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_local_bindings*

monitor_bulk_status_sxp_local_bindings(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_sxp_local_bindings***sxp_vpns****class SxpVpns**

Identity Services Engine SXPVPNs API (version: 3.2_beta).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

SXP VPNs API allows clients to add, get and delete SXP VPNs (SXP Domains).

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID value	ef36ca16-0cf7-4806-b2a9-6f547cfe4805
description	String	No		
sxpVpnName	String	Yes		default

get_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_vpn_by_id*

delete_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP VPN.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_vpn_by_id*

get_sxp_vpns(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – sxpVpnName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_vpn*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_vpns`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_sxp_vpns`*

monitor_bulk_status_sxp_vpns(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.2_beta).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

SGT mapping to virtual networks are mapped to referenced vlan. These constructs come from out side of Cisco ISE and are not CRUDable inside Cisco ISE.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.3	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	name
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No		description
sgtId	String	No		sgt_id
virtualnetworklist	List	No	Includes 'vlangs' which is an array of dictionaries describing various attributes with the properties: - id (String), - name (String), - description (String), - defaultVlan (Boolean), - max-Value (Integer), - data (Boolean)	<pre> { "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "virtual1", "description": "description", "defaultVirtualNetwork": false, "vlangs": [{ "id": "1af3d6e2-cc3b-4603-b80f-6827768335ab", "name": "vlan1", "description": "description1", "defaultVlan": true, "maxValue": 1882725260, "data": true }] }</pre>

get_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

update_security_groups_to_vn_to_vlan_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_to_vn_to_vlan_by_id*

delete_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL to virtual network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_to_vn_to_vlan_by_id*

get_security_groups_to_vn_to_vlan(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan*

`get_security_groups_to_vn_to_vlan_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_security_groups_to_vn_to_vlan_generator`*

`create_security_groups_to_vn_to_vlan`(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group to virtual network.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt_id`** (*string*) – sgtId, property of the request body.
- **`virtualnetworklist`** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

`RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_to_vn_to_vlan*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_groups_to_vn_to_vlan(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_to_vn_to_vlan*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.2_beta).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

SGT API allows the client to search SGTs.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	1.2	Initial Cisco ISE Version		
1	1.1	1.4	Cisco ISE 1.4 model changes	isTagFromRange	Removed Attribute isTagFromRange - deprecated - set to FALSE value by default
2	1.2	2.3	Cisco ISE 2.3 model changes	propagateToApic	Added Boolean Attribute propagateToApic - By default value is false
3	1.3	2.7	Cisco ISE 2.7 model changes	isReadOnly	Added Boolean Attribute isReadOnly - By default value is false
				defaultSGACLs	Added List Attribute defaultSGACLs

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Employees
id	String	No	Resource UUID, mandatory for update		93ad6890-8c01-11e6-996c-525400b48521
description	String	No			Employee Security Group
value	Integer	Yes	Value range: 2 to 65519 or -1 to auto-generate		4
propagateToApic	Boolean	No			true
isReadOnly	Boolean	No		false	
defaultSGACLs	List	No			[]
propagateToApic	Boolean	No			true
generationId	Integer	No			0

get_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_group_by_id*

update_security_group_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 or 65519 or -1 to auto- generate, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

get_security_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups*

get_security_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*

create_security_group(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propogate_to_apic** (*boolean*) – propogateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_group*

monitor_bulk_status_security_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.2_beta).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

Security Groups ACLs API allows the client to search security groups access control lists.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description	Revision Modification	Revision Modification
				Attribute	Description
0	1.0	2.0	Initial Cisco ISE Version		
1	1.1	2.3	Introducing bulk operations		
2	1.2	3.1	Cisco ISE 3.1 model changes	modelledContent	Adding modelled content from Cisco ISE 3.1

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Permit IP
id	String	No	Resource UUID, mandatory for update		92951ac0-8c01-11e6-996c-525400b48521
description	String	No			Permit IP SGACL
ACLContent	String	No			permit ip
ipVersion	Enum	Yes	Allowed values: IPV4, IPV6, IP_AGNOSTIC	IPV4	
isRead-Only	Boolean	No		false	
generationId	String	No	GenerationId is a read only attribute and is being generated by the server		0
modelled-Content	List	No	Modelled content of contract		

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_acl_by_id*

update_security_groups_acl_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_security_groups_acl_by_id*

delete_security_groups_acl_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a security group ACL.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_security_groups_acl`

```
get_security_groups_acl_generator(filter=None, filter_type=None, page=None, size=None,
                                   sortasc=None, sortdsc=None, headers=None,
                                   **query_parameters)
```

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None,
        modelled_content=None, name=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for `create_security_groups_acl`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_security_groups_acl(operation_type=None, resource_media_type=None,
        headers=None, payload=None, active_validation=True,
        **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_acl*

monitor_bulk_status_security_groups_acl(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_acl*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.2_beta).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

Self Registered Guest Portal API provides the ability to create, read, update, delete and search self registered portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Self-Registered Guest Portal (default)
id	String	No	Resource UUID, mandatory for update		4e8ade36-4048-472a-b345-632cc155acfc
description	String	No			Guests may create their own accounts and be assigned a username and password, or use their social login to access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8443/portal/PortalSetup.action?po4048-472a-b345-632cc155acfc

continues on next page

Table 53 – continued from previous page

portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SELF-REGGUEST	
settings	List	No	Defines all of the settings groups available for a portal		
• portalSettings	List	No	The port, interface, certificate, and other basic settings of a portal		
• httpsPort	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8443
• allowedInterfaces	Enum	Yes	Interfaces that the portal will be reachable on.		[“eth0”, “bond0”]
• certificateGroupTag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• authenticationMethod	String	Yes	Unique Id of the identity source sequence		92e50f80-8c01-11e6-996c-525400b48521
• assignedGuestTypeForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type		Contractor (default)

continues on next page

Table 53 – continued from previous page

• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• login-PageSettings	List	No	Portal Login Page settings groups follow		
• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 53 – continued from previous page

• re-requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• re-requireAccessCode	Boolean	No	Require the portal user to enter an access code	false	
• access-Code	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		
• allowGuest-ToCreateAccounts	Boolean	No		false	
• allowGuest-ToChangePassword	Boolean	No	Require the portal user to enter an access code	false	
• allowAlternateGuest-Portal	Boolean	No			false
• alternateGuest-Portal	String	No			
• selfReg-PageSettings	List	No			

continues on next page

Table 53 – continued from previous page

• as-signGuestsToGuest-Type	String	No	Guests are assigned to this guest type		
• account-Validity-Duration	Integer	No	Self-registered guest account is valid for this many account_validity_time_units	1	
• account-Validity-TimeUnits	Enum	No	Time units for account_validity_duration.	DAYS	
• requireRegistrationCode	Boolean	No	Self-registered guests are required to enter a registration code	false	
• registrationCode	String	No	The registration code that the guest user must enter		
• fieldUserName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldFirstName	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLastName	List	No			

continues on next page

Table 53 – continued from previous page

• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldE-mailAddr	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldPhoneNo	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldCompany	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• fieldLocation	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableLocations	List	No	Guests can choose from these locations to set their time zone		[“San Jose”]

continues on next page

Table 53 – continued from previous page

• fieldSm-sProvider	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• selectableSm-sProviders	List	No	This attribute is an array of SMS provider names		["Global Default"]
• fieldPersonBeingVisited	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• field-Reason-ForVisit	List	No			
• include	Boolean	No			true
• require	Boolean	No	Only applicable if include = true		false
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	

continues on next page

Table 53 – continued from previous page

• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• enableGuestEmailWhitelist	Boolean	No	Allow guests with an e-mail address from selected domains	false	
• guestEmailWhitelistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be allowed. Only valid if enableGuestEmailWhitelist = true		
• enableGuestEmailBlacklist	Boolean	No	Disallow guests with an e-mail address from selected domains	false	
• guestEmailBlacklistDomains	List	No	Self-registered guests whose e-mail address is in one of these domains will be disallowed. Only valid if enableGuestEmailBlacklist = true		
• requireGuestApproval	Boolean	No	Require self-registered guests to be approved if true	false	

continues on next page

Table 53 – continued from previous page

<ul style="list-style-type: none"> • autoLogin-SelfWait 	Boolean	No	Allow guests to login automatically from self-registration after sponsor's approval. No need to provide the credentials by guest to login	false	
<ul style="list-style-type: none"> • autoLogin-TimePeriod 	Integer	No	Waiting period for auto login until sponsor's approval. If time exceeds, guest has to login manually by providing the credentials. Default value is 5 minutes	5	
<ul style="list-style-type: none"> • sendApprovalRequestTo 	Enum	No	Specifies where approval requests are sent. Only valid if requireGuestApproval = true.	SELECTEDEMAILADDRESSES	
<ul style="list-style-type: none"> • approvalEmailAddresses 	String	No	Only valid if requireGuestApproval = true and sendApprovalRequestTo = SELECTEDEMAILADDRESSES		
<ul style="list-style-type: none"> • postRegistrationRedirect 	Enum	No	After the registration submission direct the guest user to one of the following pages. Only valid if requireGuestApproval = true.	SELFREGISTRATIONSUCCESS	

continues on next page

Table 53 – continued from previous page

<ul style="list-style-type: none"> • postReg- istra- tionRedi- rectUrl 	String	No	URL where guest user is redirected after registration. Only valid if requireGuestApproval = true and postRegistrationRedirect = URL		
<ul style="list-style-type: none"> • creden- tial- Notifica- tionUsingE- mail 	Boolean	No	If true, send credential notification upon approval using email. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • creden- tialNotifi- cationUs- ingSms 	Boolean	No	If true, send credential notification upon approval using SMS. Only valid if requireGuestApproval = true	false	
<ul style="list-style-type: none"> • approve- DenyLinksValid- For 	Integer	No	This attribute, along with approveDenyLinksTimeUnits, specifies how long the link can be used. Only valid if requireGuestApproval = true	1440	
<ul style="list-style-type: none"> • approve- DenyLinksTime- Units 	Enum	No	This attribute, along with approveDenyLinksValidFor, specifies how long the link can be used. Only valid if requireGuestApproval = true.	DAYS	

continues on next page

Table 53 – continued from previous page

<ul style="list-style-type: none">• re-requireApprovalToAuthenticate	Boolean	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be required to enter their username and password if this attribute is true. Only valid if requireGuestApproval = true	false	
--	---------	----	---	-------	--

continues on next page

Table 53 – continued from previous page

• sponsor-PortalList	List	No	When self-registered guests require approval, an approval request is e-mailed to one or more sponsor users. If the Cisco ISE Administrator chooses to include an approval link in the e-mail, a sponsor user who clicks the link will be authenticated against the selected sponsor portals in the order specified. Only valid if requireGuestApproval = true. The array should contain the names of the selected portals		
• selfReg-Success-Settings	List	No			
• includeUserName	Boolean	No		true	
• includePassword	Boolean	No		true	
• includeFirst-Name	Boolean	No		true	

continues on next page

Table 53 – continued from previous page

• include-Last-Name	Boolean	No		true	
• includeEmailAddr	Boolean	No		true	
• include-PhoneNo	Boolean	No		true	
• include-Company	Boolean	No		true	
• include-Location	Boolean	No		true	
• includeSm-sProvider	Boolean	No		true	
• include-PersonBeingVisited	Boolean	No		true	
• includeReason-ForVisit	Boolean	No		true	
• allowGuest-SendSelfUsing-Print	Boolean	No		false	
• allowGuest-SendSelfUsingE-mail	Boolean	No		false	

continues on next page

Table 53 – continued from previous page

• allowGuest-SendSelfUsingSms	Boolean	No		false	
• includeAup	Boolean	No		false	
• aupOn-Page	Boolean	No		false	
• requireAupAcceptance	Boolean	No		false	
• requireAupScrolling	Boolean	No		false	
• allowGuest-Login-FromSelfregSuccessPage	Boolean	No		false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	
• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	

continues on next page

Table 53 – continued from previous page

• requireAup-Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• useDiffAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = trueG	false	
• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequency-Interval-Days	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAt-FirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegister-GuestDevices	Boolean	No	Automatically register guest devices	true	

continues on next page

Table 53 – continued from previous page

• al- lowGuest- sToReg- isterDe- vices	Boolean	No	Allow guests to register devices	false	
• byodSet- tings	List	No	Configuration of BYOD De- vice Welcome, Registration and Success steps		
• byodWel- comeSet- tings	List	No	Configuration of BYOD endpoint wel- come step configuration		
• enable- BYOD	Boolean	No		true	
• en- ableGues- tAccess	Boolean	No		false	
• re- quireMDM	Boolean	No		false	
• in- cludeAup	Boolean	No		true	
• aupDis- play	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ONPAGE	
• re- quireAupAccep- tance	Boolean	No		false	

continues on next page

Table 53 – continued from previous page

• require-Scrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	
• byodReg-istra-tionSet-tings	List	No	Configuration of BYOD endpoint Reg-istration step configuration		
• showDe-viceID	Boolean	No	Display Device ID field during registration	true	
• end-PointId-ntity-GroupID	String	No	Identity group id for which endpoint belongs		aa13bb40-8bff-11e6-996c-525400b48521
• byodReg-istra-tionSuc-cessSet-tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	
• redirec-tUrl	String	No	Target URL for redirection, used when suc-cessRedirect = URL		
• authSuc-cessSet-tings	List	No			
• suc-cessRedi-rect	Enum	No	After an Au-thentication Success where should device be redirected.	AUTHSUC-CESSPAGE	

continues on next page

Table 53 – continued from previous page

• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL		www.cisco.com
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• includeBrowserUserAgent	Boolean	No		false	
• includePolicyServer	Boolean	No		false	
• includeFailureCode	Boolean	No		false	

continues on next page

Table 53 – continued from previous page

• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file

continues on next page

Table 53 – continued from previous page

• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI
• page-Background-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		

continues on next page

Table 53 – continued from previous page

• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contactText	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• bannerImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image

continues on next page

Table 53 – continued from previous page

• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
             portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
             **query_parameters)
```

Alias for `update_self_registered_portal_by_id`

```
delete_self_registered_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_self_registered_portal_by_id`

```
get_self_registered_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                           sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be

sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals_generator*

create_self_registered_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_self_registered_portal*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory**class SessionDirectory**

Identity Services Engine Session Directory API (version: 3.2_beta).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_sessions(*headers=None*, ***query_parameters*)

getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_for_recovery(*headers=None, **query_parameters*)

getSessionsForRecovery.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_ip_address(*headers=None, **query_parameters*)

getSessionByIpAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_mac_address(*headers=None, **query_parameters*)

getSessionByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_groups(*headers=None, **query_parameters*)

getUserGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)

getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)

Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.2_beta).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to add, delete, update and search sponsor groups.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Em-plALL_ACCOUNTS (default)oyees
id	String	No	Resource UUID, mandatory for update		9f1eca71-8c01-11e6-996c-525400b48521
description	String	No			Sponsors assigned to this group can manage all guest user accounts. By default, users in the ALL_ACCOUNTS user identity group are members of this sponsor group
isEnabled	Boolean	No			true
isDefault-Group	Boolean	No			true
member-Groups	List	No			["ALL_ACCOUNTS (default)"]
guestTypes	List	No			["Contractor (default)", "Daily (default)", "Weekly (default)"]
locations	List	No			["San Jose"]
autoNotification	Boolean	No			false
managePermission	Enum	No	Allowed values:		ALLACCOUNTS, GROUPACCOUNTS, OWNACCOUNTS
createPermissions	List	No			

continues on next page

Table 54 – continued from previous page

• canImportMultipleAccounts	Boolean	No			true
• importBatchSizeLimit	Integer	No		200	
• canCreateRandomAccounts	Boolean	No			true
• randomBatchSizeLimit	Integer	No		200	
• defaultUsernamePrefix	String	No			
• canSpecifyUsernamePrefix	Boolean	No			true
• canSetFutureStartDate	Boolean	No			false
• startDateFutureLimitDays	Integer	No			1
otherPermissions	List	No			

continues on next page

Table 54 – continued from previous page

• canUpdateGuest-Contact-Info	Boolean	No			true
• canViewGuest-Pass-words	Boolean	No			true
• canSendSm-sNotifica-tions	Boolean	No			false
• canResetGuest-Pass-words	Boolean	No			true
• canExtendGues-tAc-counts	Boolean	No			true
• canDeleteGues-tAc-counts	Boolean	No			true
• canSuspendGues-tAc-counts	Boolean	Yes			true
• require-SuspensionReason	Boolean	No			false

continues on next page

Table 54 – continued from previous page

• canReinstateSuspendedAccounts	Boolean	No			true
• canApproveSelfregGuests	Boolean	No			true
• limitApprovalToSponsorsGuests	Boolean	Yes			false
• canAccessViaRest	Boolean	No			false

get_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_by_id*

update_sponsor_group_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor group by ID.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **id** (*basestring*) – id, property of the request body.
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, auto_notification=None, create_permissions=None, description=None,
             guest_types=None, is_default_group=None, is_enabled=None, locations=None,
             manage_permission=None, member_groups=None, name=None, other_permissions=None,
             headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `update_sponsor_group_by_id`

```
delete_sponsor_group_by_id(id, headers=None, **query_parameters)
```

This API deletes a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_sponsor_group_by_id`

```
get_sponsor_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

This API allows the client to get all the sponsor groups. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group*

get_sponsor_group_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_group_generator*

create_sponsor_group(*auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).

- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sponsor_group_member**class SponsorGroupMember**

Identity Services Engine SponsorGroupMember API (version: 3.2_beta).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

Sponsor Group API allows the client to search the group members from different identity stores configured in the GUI.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.2	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ALL_ACCOUNTS (default)
id	String	No	Resource UUID value	a176c430-8c01-11e6-996c-525400b48521
description	String	No		
dicType	String	Yes		
guid	String	Yes		

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal**class SponsorPortal**

Identity Services Engine SponsorPortal API (version: 3.2_beta).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

Sponsor Portal API provides the ability to create, read, update, delete and search sponsor portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		Sponsor Portal (default)

continues on next page

Table 55 – continued from previous page

id	String	No	Resource UUID, mandatory for update		04cd708b-feef-4c75-bf3e-2d2a9c302da2
description	String	No			Default portal used by sponsors to create and manage accounts for authorized visitors to securely access the network
portalTestUrl	String	No	URL to bring up a test page for this portal		https://{ise-ip}:8445/portal/PortalSetup.action?portalId=feef-4c75-bf3e-2d2a9c302da2
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSORED, GUEST	SPONSOR	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999		8445
<ul style="list-style-type: none"> allowedInterfaces 	Enum	Yes	Interfaces that the portal will be reachable on.		["eth0", "bond0"]

continues on next page

Table 55 – continued from previous page

• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal		Default Portal Certificate Group
• fqdn	String	No	The fully-qualified domain name (FQDN) that end-users will use to access this portal. Used only in Sponsor portal		Default Portal Certificate Group
• authentication-Method	String	Yes	Unique Id of the identity source sequence		92faba60-8c01-11e6-996c-525400b48521
• idleTime-out	Integer	No		10	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE		USE-BROWSER-LOCALE
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE		English
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE		English
• availableSsids	List	No	Names of the SSIDs available for assignment to guest users by sponsors		
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 55 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• aupSettings	List	No	Configuration of the Acceptable Use Policy (AUP) for a portal		
• displayFrequency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true.	FIRSTLOGIN	

continues on next page

Table 55 – continued from previous page

• includeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• requireAupScrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAcceptance = true	false	
• displayFrequencyIntervalDays	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• sponsorChangePasswordSettings	List	No			
• allowSponsorToChangePwd	Boolean	No	Allow sponsors to change their own passwords	false	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		

continues on next page

Table 55 – continued from previous page

• includeSupportInfoPage	Boolean	No		false	
• includeMacAddr	Boolean	No		false	
• includeIpAddress	Boolean	No		false	
• include-BrowserUser-Agent	Boolean	No		false	
• include-Policy-Server	Boolean	No		false	
• include-Failure-Code	Boolean	No		false	
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page.		HIDE
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		

continues on next page

Table 55 – continued from previous page

• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme		9eb421c0-8c01-11e6-996c-525400b48521
• name	String	Yes	The system- or user-assigned name of the portal theme		Default Blue theme
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array		Base 64 encoded string of Theme CSS file
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color		#0000FF
• banner-Text-Color	String	No			Banner Text color code from GUI

continues on next page

Table 55 – continued from previous page

• page-Back-ground-Color	String	No			Color code from GUI
• pageLabelAnd-Text-Color	String	No			Label and Text color from GUI
• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No			English
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No			Guest Portal
• contact-Text	String	No			Contact Support
• footerElement	String	No			Footer Element
• mobileLogoImage	Image	No			

continues on next page

Table 55 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• desktopLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• backgroundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array		base 64 encoded value of image
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes			ui_contact_ip_address_label
• value	String	Yes			SVAgY-WRkcmVzczo=

get_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_portal_by_id*

update_sponsor_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor portal by ID.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a sponsor portal by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_portal_by_id*

get_sponsor_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_sponsor_portal`

```
get_sponsor_portal_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.2_beta).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

Sponsored Guest Portal API provides the ability to create, read, update, delete and search sponsored guest portals.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.2	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name	Sponsored Guest Portal (default))	
id	String	No	Resource UUID, mandatory for update	d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
description	String	No	Sponsors create guest accounts, and guests access the network using their assigned username and password		
portalTestUrl	String	No	URL to bring up a test page for this portal	https://{ise-ip}:8443/portal/PortalSetup.action?portal=d135de9f-cd87-4ce7-b1a4-1d9c7cf35f33	
portalType	Enum	Yes	Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELF-REGGUEST, SPONSOR, SPONSORED, GUEST	SPONSORED	
settings	List	No	Defines all of the settings groups available for a portal		
<ul style="list-style-type: none"> portalSettings 	List	No	The port, interface, certificate, and other basic settings of a portal		
<ul style="list-style-type: none"> httpsPort 	Integer	Yes	The port number that the allowed interfaces will listen on. Range from 8000 to 8999	8443	

continues on next page

Table 56 – continued from previous page

• allowed-Interfaces	Enum	Yes	Interfaces that the portal will be reachable on. Allowed values: eth0, eth1, eth2, eth3, eth4, eth5, bond0, bond1, bond2	[“eth0”, “bond0”]	
• certificate-Group-Tag	String	Yes	Logical name of the x.509 server certificate that will be used for the portal	Default Portal Certificate Group	
• authentication-Method	String	Yes	Unique Id of the identity source sequence	92faba60-8c01-11e6-996c-525400b48521	
• assignedGuest-Type-ForEmployee	String	Yes	Unique Id of a guest type. Employees using this portal as a guest inherit login options from the guest type	Contractor (default)	
• display-Lang	Enum	No	Allowed values: USE-BROWSER-LOCALE, ALWAYSUSE	USE-BROWSER-LOCALE	
• fallback-Language	String	No	Used when display-Lang = USE-BROWSER-LOCALE	English	
• alwaysUsed-Language	String	No	Used when displayLang = ALWAYSUSE	English	
• login-PageSettings	List	No	Portal Login Page settings groups follow		

continues on next page

Table 56 – continued from previous page

• max-FailedAttemptsBeforeRateLimit	Integer	No	Maximum failed login attempts before rate limiting	5	
• timeBetweenLoginsDuringRateLimit	Integer	No	Time between login attempts when rate limiting	2	
• includeAup	Boolean	No	Include an Acceptable Use Policy (AUP) that should be displayed during login	false	
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ASLINK	
• requireAupAcceptance	Boolean	No	Require the portal user to accept the AUP. Only valid if includeAup = true	false	
• requireAccessCode	Boolean	No	Require the portal user to enter an access code	false	
• accessCode	String	No	Access code that must be entered by the portal user (only valid if requireAccessCode = true)		

continues on next page

Table 56 – continued from previous page

• al- lowGuest- ToCre- ateAc- counts	Boolean	No	false		
• al- lowGuest- ToChangePass- word	Boolean	No	Require the portal user to enter an access code	false	
• aupSet- tings	List	No	Configuration of the Accept- able Use Policy (AUP) for a portal		
• dis- playFre- quency	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Al- lowed Values: FIRSTLOGIN, EVERY- LOGIN, RECURRING	FIRSTLOGIN	
• in- cludeAup	Boolean	No	Require the portal user to read and accept an AUP	true	
• re- quireAup- Scrolling	Boolean	No	Require the portal user to scroll to the end of the AUP. Only valid if requireAupAc- ceptance = true	false	
• useD- iffAup- ForEm- ployees	Boolean	No	Only valid if requireAupAc- ceptance = trueG	false	

continues on next page

Table 56 – continued from previous page

• skipAup-ForEmployees	Boolean	No	Only valid if requireAupAcceptance = true	false	
• displayFrequency-Interval-Days	Integer	No	Number of days between AUP confirmations (when displayFrequency = recurring)	7	
• GuestChangePasswordSettings	List	No			
• allowChangePasswordAt-FirstLogin	Boolean	No	Allow guest to change their own passwords	false	
• guestDeviceRegistrationSettings	List	No			
• autoRegister-GuestDevices	Boolean	No	Automatically register guest devices	true	
• allowGuestsToRegisterDevices	Boolean	No	Allow guests to register devices	false	
• byodSettings	List	No	Configuration of BYOD Device Welcome, Registration and Success steps		

continues on next page

Table 56 – continued from previous page

• byodWelcomeSettings	List	No	Configuration of BYOD endpoint welcome step configuration		
• enableBYOD	Boolean	No	true		
• enableGuestAccess	Boolean	No	false		
• requireMDM	Boolean	No	false		
• includeAup	Boolean	No	true		
• aupDisplay	Enum	No	How the AUP should be displayed, either on page or as a link. Only valid if includeAup = true. Allowed values: ONPAGE, ASLINK	ONPAGE	
• requireAupAcceptance	Boolean	No	false		
• requireScrolling	Boolean	No	Require BYOD devices to scroll down to the bottom of the AUP, Only valid if includeAup = true	false	

continues on next page

Table 56 – continued from previous page

• byodReg- istra- tionSet- tings	List	No	Configuration of BYOD endpoint Reg- istration step configuration		
• showDe- viceID	Boolean	No	Display Device ID field during registration	true	
• end- PointId- entity- GroupId	String	No	Identity group id for which endpoint belongs	aa13bb40-8bff- 11e6-996c- 525400b48521	
• byodReg- istra- tionSuc- cessSet- tings	List	No	Configuration of BYOD endpoint Registration Success step configuration		
• suc- cessRedi- rect	Enum	No	After an Authentica- tion Success where should device be redirected. Al- lowed values: AUTHSUC- CESSPAGE, ORIGINATIN- GURL, URL	AUTHSUC- CESSPAGE	
• redirec- tUrl	String	No	Target URL for redirection, used when suc- cessRedirect = URL		
• authSuc- cessSet- tings	List	No			

continues on next page

Table 56 – continued from previous page

• successRedirect	Enum	No	After an Authentication Success where device should be redirected. Allowed values: AUTHSUC-CESSPAGE, ORIGINATINGURL, URL	AUTHSUC-CESSPAGE	
• redirectUrl	String	No	Target URL for redirection, used when successRedirect = URL	www.cisco.com	
• postLoginBannerSettings	List	No			
• includePostAccessBanner	Boolean	No	Include a Post-Login Banner page	false	
• supportInfoSettings	List	No	Portal Support Information Settings		
• includeSupportInfoPage	Boolean	No	false		
• includeMacAddr	Boolean	No	false		
• includeIpAddress	Boolean	No	false		

continues on next page

Table 56 – continued from previous page

• include-BrowserUser-Agent	Boolean	No	false		
• include-Policy-Server	Boolean	No	false		
• include-Failure-Code	Boolean	No	false		
• empty-FieldDisplay	Enum	No	Specifies how empty fields are handled on the Support Information Page. Allowed values: HIDE, DISPLAY-WITHNO-VALUE, DISPLAYWITH-DEFAULT-VALUE	HIDE	
• default-Empty-Field-Value	String	No	The default value displayed for an empty field Only valid when empty-FieldDisplay = DISPLAY-WITHDE-FAULT-VALUE		
customizations	List	No	Defines all of the Portal Customizations available		
• portalTheme	List	No	Defines the configuration for portal theme		
• id	String	No	The unique internal identifier of the portal theme	9eb421c0-8c01-11e6-996c-525400b48521	

continues on next page

Table 56 – continued from previous page

• name	String	Yes	The system- or user-assigned name of the portal theme	Default Blue theme	
• theme-Data	String	No	A CSS file, represented as a Base64-encoded byte array	Base 64 encoded string of Theme CSS file	
• portalTweak-Settings	List	No	The Tweak Settings are a customization of the Portal Theme that has been selected for the portal. When the Portal Theme selection is changed, the Tweak Settings are overwritten to match the values in the theme. The Tweak Settings can subsequently be changed by the user		
• banner-Color	String	No	Hex value of color	#0000FF	
• banner-Text-Color	String	No	Banner Text color code from GUI		
• page-Background-Color	String	No	Color code from GUI		
• pageLabelAnd-Text-Color	String	No	Label and Text color from GUI		

continues on next page

Table 56 – continued from previous page

• language	List	No	This property is supported only for Read operation and it allows to show the customizations in English. Other languages are not supported		
• viewLanguage	String	No	English		
• globalCustomizations	List	No	Represent the portal Global customizations		
• bannerTitle	String	No	Guest Portal		
• contactText	String	No	Contact Support		
• footerElement	String	No	Footer Element		
• mobileLogoImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• desktopLogoImage	Image	No			

continues on next page

Table 56 – continued from previous page

• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• banner-Image	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• back-groundImage	Image	No			
• data	String	No	Represented as base 64 encoded string of the image byte array	base 64 encoded value of image	
• pageCustomizations	List	No	Represent the entire page customization as a giant dictionary		
• data	List	No	The Dictionary will be exposed here as key value pair		
• key	String	Yes	ui_contact_ip_address_label		
• value	String	Yes	SVAgY-WRkcmVzczo=		

get_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_sponsored_guest_portal_by_id`*
`update_sponsored_guest_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **`customizations(object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description(string)`** – description, property of the request body.
- **`id(basestring)`** – id, property of the request body.
- **`name(string)`** – name, property of the request body.
- **`portal_test_url(string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type(string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings(object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_sponsored_guest_portal_by_id`*

`delete_sponsored_guest_portal_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_sponsored_guest_portal_by_id`*

`get_sponsored_guest_portals`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsored_guest_portals*

```
get_sponsored_guest_portals_generator(filter=None, filter_type=None, page=None, size=None,
                                         sortasc=None, sortdsc=None, headers=None,
                                         **query_parameters)
```

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals_generator*

create_sponsored_guest_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsored_guest_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

subscriber

class Subscriber

Identity Services Engine Subscriber API (version: 3.2_beta).

Wraps the Identity Services Engine Subscriber API and exposes the API as native Python methods that return native Python objects.

get_all_subscribers(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Purpose of this API is to get all Subscribers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_subscribers_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Purpose of this API is to get all Subscribers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_subscriber(*enabled=None, friendly_name=None, identity_groups=None, imeis=None, imsi=None, ki=None, opc=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Purpose of this API is to create Subscriber holding the IMSI.

Parameters

- **enabled** (*boolean*) – Subscriber is enabled or not, property of the request body.
- **friendly_name** (*string*) – Friendly name for the subscriber, property of the request body.
- **identity_groups** (*string*) – Identity Group(s). With more than one idGroups it needs to be comma seperated, property of the request body.
- **imeis** (*string*) – IMEI to be attached to the subscriber, property of the request body.
- **imsi** (*string*) – IMSI for Subscriber, property of the request body.
- **ki** (*string*) – KI, property of the request body.
- **opc** (*string*) – OPC, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_subscriber_operation(*item_list=None, operation=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create/update/delete Subscribers in bulk.

Parameters

- **`item_list`** (*list*) – ItemList, property of the request body (list of objects).
- **`operation`** (*string*) – operation, property of the request body. Available values are 'Create', 'Delete' and 'Update'.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_subscriber_by_imsi(*imsi, headers=None, **query_parameters*)

Purpose of this API is to get Subscriber by IMSI.

Parameters

- **`imsi`** (*basestring*) – imsi path parameter. IMSI parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_subscriber_by_id(*subscriber_id*, *headers=None*, ***query_parameters*)

Purpose of this API is to get Subscriber by ID.

Parameters

- **subscriber_id** (*basestring*) – subscriberId path parameter. Unique id for a subscriber object.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_subscriber(*subscriber_id*, *enabled=None*, *friendly_name=None*, *identity_groups=None*, *imeis=None*, *ki=None*, *opc=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Purpose of this API is to update Subscriber given the Subscriber's Id and the request payload.

Parameters

- **enabled** (*boolean*) – Subscriber is enabled or not, property of the request body.
- **friendly_name** (*string*) – Friendly name for the subscriber, property of the request body.
- **identity_groups** (*string*) – Identity Group(s). With more than one idGroups it needs to be comma seperated, property of the request body.
- **imeis** (*string*) – IMEI to be attached to the subscriber, property of the request body.
- **ki** (*string*) – KI, property of the request body.
- **opc** (*string*) – OPC, property of the request body.
- **subscriber_id** (*basestring*) – subscriberId path parameter. Unique id for a subscriber object.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_subscriber(*subscriber_id*, *headers=None*, ***query_parameters*)

Purpose of this API is to delete the Subscriber given the Subscriber's Id.

Parameters

- **subscriber_id** (*basestring*) – subscriberId path parameter. Unique id for a subscriber object.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download**class SupportBundleDownload**

Identity Services Engine SupportBundleDownload API (version: 3.2_beta).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

Support Bundle Download API allows client to download support bundles provided those are generated and available in the default location.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		
fileName	String	Yes	File name along with path from where file needs to be downloaded	filename

download_support_bundle(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **filename** (*basestring*) – The filename used to save the download file.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

The DownloadResponse wrapper. Wraps the urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

Return type

DownloadResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, filename=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *download_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_status**class SupportBundleStatus**

Identity Services Engine SupportBundleStatus API (version: 3.2_beta).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

Support Bundle Status API allows clients to query status of a triggered support bundle.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ciscoise
id	String	No	Resource UUID, mandatory for update	ciscoise
description	String	No		Support Bundle Status api
file-Name	String	No		ise-support-bundle-pk-ciscoise-admin-04-09-2021-15-07.tar.gpg
fileSize	Integer	No		1080924274
host-Name	String	No		ciscoise
message	String	No		Support Bundle generation completed
start-Time	String	No		Fri Apr 09 15:07:55 IST 2021
status	String	No		complete

get_support_bundle_status_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a support bundle status by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status*

get_support_bundle_status_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration**class SupportBundleTriggerConfiguration**

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.2_beta).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

Support Bundle Trigger API allows clients to trigger support bundle provided the log settings are given using which the support needs to be generated.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	2.7	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Default Values
name	String	Yes	Resource Name	supportBundle
id	String	No	Resource UUID, mandatory for update	1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No	Support Bundle Generation	
hostName	String	Yes	This parameter is hostName only, xxxx of xxxx.yyy.zz	sampleHost
supportBundleOptions	List	Yes		
<ul style="list-style-type: none"> includeConfigDB 	Boolean	Yes	Set to include Config DB in Support Bundle	false
<ul style="list-style-type: none"> includeDebugLogs 	Boolean	Yes	Set to include Debug logs in Support Bundle	false
<ul style="list-style-type: none"> includeLocalLogs 	Boolean	Yes	Set to include Local logs in Support Bundle	false
<ul style="list-style-type: none"> includeCoreFiles 	Boolean	Yes	Set to include Core files in Support Bundle	false
<ul style="list-style-type: none"> includeSystemLogs 	Boolean	Yes	Set to include System logs in Support Bundle	false
<ul style="list-style-type: none"> mntLogs 	Boolean	Yes	Set to include Monitoring and troubleshooting logs in Support Bundle	false
<ul style="list-style-type: none"> policyXml 	Boolean	Yes	Set to include Policy XML in Support Bundle	false
<ul style="list-style-type: none"> fromDate 	Date	No	Date from where support bundle should include the logs	04/21/2019
<ul style="list-style-type: none"> toDate 	Date	No	Date upto where support bundle should include the logs	04/22/2019

```
create_support_bundle(description=None, host_name=None, name=None,
                      support_bundle_include_options=None, headers=None, payload=None,
                      active_validation=True, **query_parameters)
```

This API allows the client to create a support bundle trigger configuration.

Parameters

- **description** (*string*) – description, property of the request body.
- **host_name** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **support_bundle_include_options** (*object*) – supportBundleIncludeOptions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health**class SystemHealth**

Identity Services Engine System Health API (version: 3.2_beta).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxxg*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_healths(*headers=None*, ***query_parameters*)

getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)

getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

system_certificate**class SystemCertificate**

Identity Services Engine SystemCertificate API (version: 3.2_beta).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

System Certificate API provides the ability to create certificates like SAML, pxGrid.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	
description	String	No		Support Bundle Status api
nodeId	String	Yes	NodeId of Cisco ISE application	ISE-01
localCertStub	List	Yes	Inputs for certificate creation	
<ul style="list-style-type: none">• subjectStub	List	No	Subject data of certificate	
<ul style="list-style-type: none">• common-Name	String	No	Common Name	\$FQDN\$
<ul style="list-style-type: none">• organizationalUnitName	String	No	Organizational Unit Name	Cisco-SAMLCert
<ul style="list-style-type: none">• organization-Name	String	No	Organizational Name	Cisco
<ul style="list-style-type: none">• localityName	String	No	Locality Name	City
<ul style="list-style-type: none">• stateOr-Province-Name	String	No	State or Province Name	State
<ul style="list-style-type: none">• countryName	String	No	Country Name	Country
<ul style="list-style-type: none">• keyType	String	Yes	Key Type	RSA OR ECDSA
<ul style="list-style-type: none">• keyLength	String	Yes	Key Length	512 OR 1024 OR 2048 OR 4096
<ul style="list-style-type: none">• digest	String	Yes	Digest	SHA-256 OR SHA-384 OR SHA-512
<ul style="list-style-type: none">• expirationTTL	Integer	Yes	Expiration Time to Live (TTL)	2
<ul style="list-style-type: none">• selectedExpirationTTLU-nit	String	Yes	Selected Expiration TTL Unit	days OR weeks OR months OR years
			Chapter 1. The User Guide	
<ul style="list-style-type: none">• groupTagDD	String	No	Group Tag DD	add-group-tag

```
create_system_certificate(ers_local_cert_stub=None, node_id=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_system_certificate*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`tacacs_command_sets`**class TacacsCommandSets**

Identity Services Engine TACACSCCommandSets API (version: 3.2_beta).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

TACACS Command Sets API allows the client to add, delete, update, search and perform actions on TACACS command sets.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		DenyAllCommands
id	String	No	Resource UUID, mandatory for update		0cef7990-6120-11ea-bffb-7a82c56e81f0
description	String	No			Default Command Set
permitUnmatched	Boolean	No		false	
commands	List	No	Holds list of Commands		
<ul style="list-style-type: none"> commandList 	List	No	Array of dictionaries describing various attributes with the properties: <ul style="list-style-type: none"> - grant (Enum. Allowed values: PERMIT, DENY, DENY_ALWAYS), - command (String), - arguments (String) 		[{ "grant" : "PERMIT", "command" : "create", "arguments" : "value" }]

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*,
permit_unmatched=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation .
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)

Alias for *get_tacacs_command_sets_generator*

create_tacacs_command_sets(commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers

class TacacsExternalServers

Identity Services Engine TACACSExternalServers API (version: 3.2_beta).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

TACACS External Servers API allows the client to add, delete, update, search and perform actions on TACACS external servers.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re- quired	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsExternalServer1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f- 6827768335ab
descrip- tion	String	No			TacacsExternalServer- ForSDK
hostIP	String	Yes	The server IPV4 address		1.1.1.1
connec- tionPort	Inte- ger	No	The port to connect the server	49	
single- Connect	Boolean	No	Define the use of single con- nection	true	
sharedSe- cret	String	Yes	The server shared secret		SharedSecret
timeout	Inte- ger	No	The server timeout	20	

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_id*

update_tacacs_external_servers_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_external_servers_by_id*

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_external_servers_by_id*

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers*

get_tacacs_external_servers_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(page=None, size=None, headers=None, **query_parameters)

Alias for *get_tacacs_external_servers_generator*

create_tacacs_external_servers(connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_profile

class TacacsProfile

Identity Services Engine TACACSPROFILE API (version: 3.2_beta).

Wraps the Identity Services Engine TACACSPROFILE API and exposes the API as native Python methods that return native Python objects.

TACACS Profile API allows the client to add, delete, update, search and perform actions on TACACS profile.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	Default Shell Profile
id	String	No	Resource UUID, mandatory for update	93d7ee70-92b5-11eb-a39d-96858bc78604
description	String	No		Default Shell Profile
sessionAttributes	List	No	Holds list of session attributes. View type for GUI is Shell by default	
<ul style="list-style-type: none"> sessionAttributeList 	List	No	Array of dictionaries describing various attributes with the properties: - type (Enum. Allowed values: MANDATORY, OPTIONAL), - name (String), - value (String)	[{ "type" : "MANDATORY", "name" : "attr1", "value" : "value" }]

get_tacacs_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile_by_name***get_tacacs_profile_by_id**(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile_by_id***update_tacacs_profile_by_id**(*id*, *description=None*, *name=None*, *session_attributes=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_profile_by_id*

delete_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *delete_tacacs_profile_by_id***get_tacacs_profile**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)Alias for *get_tacacs_profile***get_tacacs_profile_generator**(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile_generator*

create_tacacs_profile(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.2_beta).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

TACACS Server Sequence API allows the client to add, delete, update, search and perform actions on TACACS server sequence.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Required	Description	Default Values	Example Values
name	String	Yes	Resource Name		TacacsServerSequence1
id	String	No	Resource UUID, mandatory for update		1af3d6e2-cc3b-4603-b80f-6827768335ab
description	String	No			TacacsServerSequenceForSDK
serverList	String	Yes	The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication		TacacsExternalServer1,TacacsExternalServer2
localAccounting	Boolean	No		false	
remoteAccounting	Boolean	No		true	
prefixStrip	Boolean	No	Define if a delimiter will be used for prefix strip	false	
suffixStrip	Boolean	No	Define if a delimiter will be used for suffix strip	false	
prefixDelimiter	String	No	The delimiter that will be used for prefix strip		
suffixDelimiter	String	No	The delimiter that will be used for suffix strip	@	

get_tacacs_server_sequence_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_name`***`get_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`Alias for *`get_tacacs_server_sequence_by_id`***`update_tacacs_server_sequence_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters)`**

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, local_accounting=None, name=None, prefix_delimiter=None,
              prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None,
              suffix_strip=None, headers=None, payload=None, active_validation=True,
              **query_parameters)
```

Alias for `update_tacacs_server_sequence_by_id`

```
delete_tacacs_server_sequence_by_id(id, headers=None, **query_parameters)
```

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for `delete_tacacs_server_sequence_by_id`

```
get_tacacs_server_sequence(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_tacacs_server_sequence***`get_tacacs_server_sequence_generator`**(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)Alias for *get_tacacs_server_sequence_generator*

```
create_tacacs_server_sequence(description=None, local_accounting=None, name=None,  
                               prefix_delimiter=None, prefix_strip=None, remote_accounting=None,  
                               server_list=None, suffix_delimiter=None, suffix_strip=None,  
                               headers=None, payload=None, active_validation=True,  
                               **query_parameters)
```

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None,
        remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None,
        headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for `create_tacacs_server_sequence`

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.2_beta).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

Telemetry Information API allows clients to get telemetry configuration information.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description		
0	1.0	3.0	Initial Cisco ISE Version		

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	
id	String	No	Resource UUID, mandatory for update	ed7176fb-3faf-4060-845e-d5fa5236bd6e
description	String	No		
status	String	No		SCHEnable
deploymentId	String	No		ed7176fb-3faf-4060-845e-d5fa5236bd6e
udiSN	String	No		CH2MKIEGBGO

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information*

get_telemetry_information_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*,
 ***query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration**class TrustSecConfiguration**

Identity Services Engine TrustSec Configuration API (version: 3.2_beta).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pxe*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *Cisco12345*

get_security_groups(*headers=None*, ***query_parameters*)

getSecurityGroups.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)Alias for *get_security_groups***`get_security_group_acls`**(*headers=None, **query_parameters*)*getSecurityGroupAcls*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_policies`(*headers=None, **query_parameters*)*getEgressPolicies*.**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_egress_matrices(headers=None, **query_parameters)``getEgressMatrices.`**Parameters**

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`trust_sec_sxp`**`class TrustSecSxp`**

Identity Services Engine TrustSec SXP API (version: 3.2_beta).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

Cisco ISE 3.0 pxGrid REST APIs

License [Cisco Sample Code License](<https://developer.cisco.com/site/license/cisco-sample-code-license/>)

Status These are the status icons for the requests so far. - : must create resources to test - : incomplete | untested - : unsupported | bug

Environment Variables This collection uses environment variables in scripts in the **Tests** tab to store data (*id*, *name*, *portalId*, etc.) between requests. This allows you to *GET* or *POST* then immediately *GET {id}* on a resource. Using **No Environment** will cause this convenience functionality to fail so be sure to choose one.

Collection Variables This collection includes some default variables that you will want to update or override with environment variables for your ISE deployment. Specifically, you will want to set: - *ise_pgx*: the ISE PAN node name or IP address. Default: *ise.securitydemo.net* - *rest_username*: the username for ERS API access. Must be a member of **SuperAdmin**, **ERSAdmin** or **ERSOperator** groups. Default: *admin* which is the ISE SuperAdmin - *rest_password*: Default: *C1sco12345*

get_bindings(*headers=None, **query_parameters*)

getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.2_beta).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_ise_version_and_patch(*headers=None, **query_parameters*)

This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info

class VersionInfo

Identity Services Engine VersionInfo API (version: 3.2_beta).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

Version and Patch API is used to provide the Cisco ISE version on which the Cisco ISE cluster is running, and a comma-separated list of the patches that are installed. The highest numbered patch is the patch that the cluster is running on.

get_version_info(*resource, headers=None, **query_parameters*)

Get all VersionInfo.

Parameters

- **resource (basestring)** – resource path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint**class Endpoint**

Identity Services Engine endpoint API (version: 3.2_beta).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

Endpoint API allows the client to add, delete, update, search, register and de-register endpoints. Please note that each API description shows whether the API is supported in bulk operation. The Bulk section is showing only 'create' bulk operation however, all other operation which are bulk supported can be used in same way.

Revision History

Re-vi-sion #	Re-source Version	Cisco ISE Version	Description	Revision Modification	
				Attribute	Description
0	1.0	1.3	Initial Cisco ISE Version		
1	1.1	2.1	Cisco ISE 2.1 model changes	custom-Attributes	Added custom attributes for the user to include custom attributes when adding endpoints to Cisco ISE
2	1.2	2.2	Cisco ISE 2.2 model changes	apiAdded	Added custom operation to get list of rejected endpoints: '/getrejectedendpoints'
				apiAdded	Added custom operation to release rejected endpoint: '{id}/releaserejectedendpoint'

Resource Definition

Attribute	Type	Re- quired	Description	Example Values
name	String	Yes	Resource Name	11:22:33:44:55:66
id	String	No	Resource UUID, mandatory for update	172f8270-8f4f-11eb-b4a8-9eb04987ed29
description	String	No		MyEndpoint
customAttributes	Map	No	Key value map	{"key1": "value1"}
groupId	String	Yes		aa13bb40-8bff-11e6-996c-525400b48521
identityStore	String	No		identityStore
identityStoreId	String	No		identityStoreId
mac	String	Yes		11:22:33:44:55:66
portalUser	String	No		portalUser
profileId	String	No		profileId
staticGroupAssignment	Boolean	Yes		true
staticProfileAssignment	Boolean	Yes		false

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

release_rejected(*id*, *headers=None*, ***query_parameters*)

Alias for *release_rejected_endpoint*

deregister_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to de-register an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deregister(*id*, *headers=None*, ***query_parameters*)

Alias for *deregister_endpoint*

get_rejected_endpoints(*headers=None*, ***query_parameters*)

This API allows the client to get the rejected endpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_rejected(*headers=None, **query_parameters*)

Alias for *get_rejected_endpoints*

get_endpoint_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)Alias for *get_endpoint_by_id***update_endpoint_by_id**(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_by_id*

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_by_id*

```
register_endpoint(custom_attributes=None, description=None, group_id=None, id=None,  
                  identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None,  
                  name=None, portal_user=None, profile_id=None, static_group_assignment=None,  
                  static_profile_assignment=None, headers=None, payload=None,  
                  active_validation=True, **query_parameters)
```

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *register_endpoint*

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_endpoints_generator`*

`create_endpoint`(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint.

Parameters

- **`custom_attributes`** (*object*) – customAttributes, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`group_id`** (*string*) – groupId, property of the request body.
- **`identity_store`** (*string*) – identityStore, property of the request body.
- **`identity_store_id`** (*string*) – identityStoreId, property of the request body.
- **`mac`** (*string*) – mac, property of the request body.
- **`mdm_attributes`** (*object*) – mdmAttributes, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_user`** (*string*) – portalUser, property of the request body.
- **`profile_id`** (*string*) – profileId, property of the request body.
- **`static_group_assignment`** (*boolean*) – staticGroupAssignment, property of the request body.
- **`static_profile_assignment`** (*boolean*) – staticProfileAssignment, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)Alias for *monitor_bulk_status_endpoint***portal****class Portal**

Identity Services Engine portal API (version: 3.2_beta).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

Portal API allows the client to search profiles.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	1.2	Initial Cisco ISE Version
1	2.0	1.3	Introducing new schema - not supporting 1.0 anymore

Resource Definition

Attribute	Type	Required	Description	Example Values
name	String	Yes	Resource Name	ISE Portal (default)
id	String	No	Resource UUID, mandatory for update	bc5524ea-b1e5-47ed-a907-5304821da916
description	String	No		ISE Portal for saml based feature purpose
portal-Type	String	No		GUEST

get_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_by_id*

get_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals*

get_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request's response
 - text(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

proxy**class Proxy**

Identity Services Engine proxy API (version: 3.2_beta).

Wraps the Identity Services Engine proxy API and exposes the API as native Python methods that return native Python objects.

get_proxy_connection(*headers=None, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_proxy_connection(*bypass_hosts=None, fqdn=None, password=None, password_required=None, port=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

The following functionalities are impacted by the proxy settings: Partner Mobile Management Endpoint Profiler Feed Service Update Endpoint Posture Update Endpoint Posture Agent Resources Download CRL (Certificate Revocation List) Download SMS Message Transmission Social Login Rest Auth Service Azure AD pxGrid Cloud .

Parameters

- **bypass_hosts** (*string*) – Bypass hosts for the proxy connection, property of the request body.
- **fqdn** (*string*) – proxy IP address or DNS-resolvable host name, property of the request body.
- **password** (*string*) – Password for the proxy connection, property of the request body.
- **password_required** (*boolean*) – Indicates whether password configuration is required for Proxy., property of the request body.
- **port** (*integer*) – Port for proxy connection. should be between 1 and 65535, property of the request body.
- **user_name** (*string*) – User name for the proxy connection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.2_beta).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

pxGrid Node API allows the client to retrieve pxGrid information, delete an existing pxGrid node, and approve new pxGrid nodes. **Note:** From Cisco ISE Release 3.1, all pxGrid connections must be based on pxGrid 2.0. pxGrid 1.0-based (XMPP-based) integrations will cease to work on Cisco ISE from Release 3.1 onwards. pxGrid Version 2.0, which is based on WebSockets, was introduced in Cisco ISE Release 2.4. We recommend

that you plan and upgrade your other systems to pxGrid 2.0-compliant versions in order to prevent potential disruptions, if any, to integrations.

Revision History

Revision #	Resource Version	Cisco ISE Version	Description
0	1.0	2.4	Initial Cisco ISE Version

Resource Definition

Attribute	Type	Re-quired	Description	Example Values
name	String	Yes	Resource Name	ers-sample-client
id	String	No	Resource UUID, mandatory for update	ab6deded-fcc2-47ff-8577-0014737c8fcf
descrip-tion	String	No		ERS sample client
status	String	No		Online (XMPP)
auth-Method	String	No		Certificate
groups	String	No		

pxGrid Characterization

Session data Consumption over pxGrid

On a 35 node Cisco ISE deployment with a dedicated primary Policy Administration node (PAN), dedicated secondary PAN, dedicated primary Monitoring and Troubleshooting node (MnT node), dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous Policy Service node (PSN) platforms, there was no delay observed in consuming session data with the following parameters as shown in the table below:

RADIUS Traffic	Total number of ses-sions in the deploy-ment	Number of pxGrid clients (subscribers to the session topic)	pxGrid client's delay in consuming session data
Upto 500 transac-tions per second (TPS)	~2 million	50	No delay

Bulk download time taken

On a 35 node Cisco ISE deployment with a dedicated primary PAN, dedicated secondary PAN, dedicated primary MnT, dedicated secondary MnT, dedicated pxGrid node and 30 heterogeneous PSN Platforms, the bulk download time for all the pxGrid clients is shown in the table below:

Total number of sessions in the deployment	Number of pxGrid clients (subscribers to the session topic)	Time taken for bulk download
2 million	50	~17 minutes

Note: From Cisco ISE Release 3.1, we can use either pxgridnode or pxgridNode in the URL.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`Alias for *`get_px_grid_node_by_name`***`delete_px_grid_node_by_name(name, headers=None, **query_parameters)`**

This API deletes a pxGrid node by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`Alias for *`delete_px_grid_node_by_name`***`get_px_grid_node_by_id(id, headers=None, **query_parameters)`**

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_id*

get_px_grid_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node*

get_px_grid_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type

Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

tasks**class Tasks**

Identity Services Engine tasks API (version: 3.2_beta).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

`get_task_status`(*headers=None, **query_parameters*)

get all task status.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type*RestResponse***Raises**

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_task_status_by_id`(*task_id, headers=None, **query_parameters*)

Monitor task status.

Parameters

- **`task_id`** (*basestring*) – taskId path parameter. The id of the task executed before.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry

class Telemetry

Identity Services Engine telemetry API (version: 3.2_beta).

Wraps the Identity Services Engine telemetry API and exposes the API as native Python methods that return native Python objects.

get_transport_gateway(*headers=None, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_transport_gateway(*enable_transport_gateway=None, url=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Transport Gateway acts a proxy for the communication between the ISE servers in your network and the Telemetry servers in case of air-gapped network.

Parameters

- **enable_transport_gateway** (*boolean*) – Indicates whether transport gateway is enabled or not., property of the request body.
- **url** (*string*) – URL of transport gateway, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type

RestResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

Identity Services Engine Data Object

MyDict

class MyDict

A **Python** `_dict_` subclass which tries to act like **JavaScript** objects, so you can use the **dot notation** (`.`) to access members of the object. If the member doesn't exist yet then it's created when you assign something to it. Brackets notation (`d['foo']`) is also possible.

has_path(*key*)

Check existence of "path" in the tree.

```
d = MyDict({'foo': {'bar': 'baz'}})
d.has_path('foo.bar') == True
```

It only supports “dot-notation” (d.foo.bar)

get(key, default=None)

Return the value for key if key is in the dictionary, else default.

to_json()

Returns a JSON-like string representing this instance

DownloadResponse

class DownloadResponse

Download Response wrapper.

Bases: urllib3.response.HTTPResponse. For more information check the [urllib3 documentation](#)

HTTP Response container.

property data

The HTTPResponse’s data

property filename

The downloaded filename

property dirpath

The downloaded directory path

property path

The download file path

RestResponse

class RestResponse

RestResponse to represent the response of the calls to the Identity Services Engine APIs.

property content

The content (bytes) of the RestResponse.

property text

The text (str) of the RestResponse.

property status_code

The HTTP status code from the RestResponse.

property response

The response (MyDict) of the RestResponse.

property headers

The headers (MyDict) of the RestResponse.

Exceptions

exception ciscoisesdkException

Bases: [Exception](#)

Base class for all ciscoisesdk package exceptions.

exception AccessTokenError

Bases: [ciscoisesdkException](#)

Raised when an incorrect Identity Services Engine Access Token has been provided.

exception VersionError

Bases: [ciscoisesdkException](#)

Raised when an incorrect Identity Services Engine version has been provided.

exception ApiError

Bases: [ciscoisesdkException](#)

Errors returned in response to requests sent to the Identity Services Engine APIs.

Several data attributes are available for inspection.

response

The `requests.Response` object returned from the API call.

request

The `requests.PreparedRequest` of the API call.

status_code

The HTTP status code from the API response.

status

The HTTP status from the API response.

details_str

The text from the API response.

details

The parsed JSON details from the API response.

message

The error message from the parsed API response.

description

A description of the HTTP Response Code from the API docs.

additional_data

Additional data describing the issue

exception RateLimitError

Bases: [ApiError](#)

Identity Services Engine Rate-Limit exceeded Error.

Raised when a rate-limit exceeded message is received and the request **will not** be retried.

retry_after

The *Retry-After* time period (in seconds) provided by Identity Services Engine.

Defaults to 15 seconds if the response *Retry-After* header isn't present in the response headers, and defaults to a minimum wait time of 1 second if Identity Services Engine returns a *Retry-After* header of 0 seconds.

exception RateLimitWarning

Bases: [UserWarning](#)

Identity Services Engine rate-limit exceeded warning.

Raised when a rate-limit exceeded message is received and the request will be retried.

retry_after

The *Retry-After* time period (in seconds) provided by Identity Services Engine.

Defaults to 15 seconds if the response *Retry-After* header isn't present in the response headers, and defaults to a minimum wait time of 1 second if Identity Services Engine returns a *Retry-After* header of 0 seconds.

exception MalformedRequest

Bases: [ciscoisesdkException](#)

Raised when a malformed request is received from Identity Services Engine user.

exception DownloadFailure

Bases: [ciscoisesdkException](#)

Errors returned in response to requests sent to the Identity Services Engine APIs with stream=True.

Several data attributes are available for inspection.

response

The `requests.Response` object returned from the API call.

request

The `requests.PreparedRequest` of the API call.

status_code

The HTTP status code from the API response.

status

The HTTP status from the API response.

original_error

The original exception

raw

The raw value of the API response

Copyright (c) 2023 Cisco and/or its affiliates.

THE DEVELOPMENT COMMUNITY

Interested in contributing to the project? Please review our community's Code of Conduct and then check out the Contributing page for info to help you get started.

2.1 Contributor Covenant Code of Conduct

2.1.1 Our Pledge

In the interest of fostering an open and welcoming environment, we as contributors and maintainers pledge to making participation in our project and our community a harassment-free experience for everyone, regardless of age, body size, disability, ethnicity, gender identity and expression, level of experience, nationality, personal appearance, race, religion, or sexual identity and orientation.

2.1.2 Our Standards

Examples of behavior that contributes to creating a positive environment include:

- Using welcoming and inclusive language
- Being respectful of differing viewpoints and experiences
- Gracefully accepting constructive criticism
- Focusing on what is best for the community
- Showing empathy towards other community members

Examples of unacceptable behavior by participants include:

- The use of sexualized language or imagery and unwelcome sexual attention or advances
- Trolling, insulting/derogatory comments, and personal or political attacks
- Public or private harassment
- Publishing others' private information, such as a physical or electronic address, without explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

2.1.3 Our Responsibilities

Project maintainers are responsible for clarifying the standards of acceptable behavior and are expected to take appropriate and fair corrective action in response to any instances of unacceptable behavior.

Project maintainers have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, or to ban temporarily or permanently any contributor for other behaviors that they deem inappropriate, threatening, offensive, or harmful.

2.1.4 Scope

This Code of Conduct applies both within project spaces and in public spaces when an individual is representing the project or its community. Examples of representing a project or community include using an official project e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event. Representation of a project may be further defined and clarified by project maintainers.

2.1.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported by contacting the project team. The project team will review and investigate all complaints, and will respond in a way that it deems appropriate to the circumstances. The project team is obligated to maintain confidentiality with regard to the reporter of an incident. Further details of specific enforcement policies may be posted separately.

Project maintainers who do not follow or enforce the Code of Conduct in good faith may face temporary or permanent repercussions as determined by other members of the project's leadership.

2.1.6 Attribution

This Code of Conduct is adapted from the [Contributor Covenant](#), version 1.4.

2.2 Contributing

ciscoisesdk is a community development project. Feedback, thoughts, ideas, and code contributions are most welcome!

2.2.1 How to contribute Feedback, Issues, Thoughts and Ideas

Please use the [issues](#) page to report issues or post ideas for enhancement.

2.2.2 Interested in Contributing Code?

Developer Scripts

We have created some scripts to automate everyday actions needed when working on the project. Please see the [script](#) directory, and it's README for more information.

Notes on the Test Suite

The test suite is grouped by Identity Services Engine versions supported in the Cisco Identity Services Engine SDK.

The test suite uses a mockup server, instead of calling to a Identity Services Engine server directly.

The mockup server is not perfect, that is why it is sometimes necessary to rerun a failed test, we do this by using *pytest-rerunfailures*. On the *script/test* file, you can find the *pytest-rerunfailures* settings, adjust them locally if strictly necessary.

Contributing Code - Using the CI Automated Testing

1. Check for open [issues](#) or create a new *issue* for the item you want to work on and make sure to comment and let us know that you are working on it.
2. Fork a copy of the [repository](#) and clone your forked repository to your development environment.
3. Run `script/setup` to install the development dependencies and setup your environment.
4. Configure the following environment variables in your development environment:
 - `TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - Your test account's Identity Services Engine encoded_auth (username:password encoded in base 64). This variable has priority over username and password.
 - `TEST_IDENTITY_SERVICES_ENGINE_USERNAME` - Your test account's Identity Services Engine username.
 - `TEST_IDENTITY_SERVICES_ENGINE_PASSWORD` - Your test account's Identity Services Engine password.
 - `DEBUG_ENVIRONMENT_VARIABLE` - Your test's debug variable, which controls whether to log information about Identity Services Engine APIs' request and response process.
 - `VERSION_ENVIRONMENT_VARIABLE` - The Identity Services Engine API's version used to test the SDK.
5. Add your code to your forked repository.

If you are creating some new feature or functionality (excellent!), please also write a [test](#) to verify that your code works as expected.

6. We follow [PEP8](#) reasonably strictly for this project. Please make sure your code passes the linter.
Run `script/test lint` or simply run `flake8` from the project root.
7. Commit your changes.
8. Submit a [pull request](#). The GitHub/Travis CI system runs the test suite against your pull request code. If any tests fail, please review your changes. If everything looks good, we will gladly merge your request!

Contributing Code - Running the Test Suite Locally

1. Check for open [issues](#) or create a new 'issue' for the item you want to work on and make sure to comment and let us know that you are working on it.
2. Fork a copy of the [repository](#) and clone your forked repository to your development environment.
Run `script/setup` to install the development dependencies and setup your environment.
3. Configure the following environment variables in your development environment:
 - `TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - Your test account's Identity Services Engine encoded_auth (username:password encoded in base 64). This variable has priority over username and password.

- `TEST_IDENTITY_SERVICES_ENGINE_USERNAME` - Your test account's Identity Services Engine username.
- `TEST_IDENTITY_SERVICES_ENGINE_PASSWORD` - Your test account's Identity Services Engine password.
- `DEBUG_ENVIRONMENT_VARIABLE` - Your test's debug variable, which controls whether to log information about Identity Services Engine APIs' request and response process.
- `VERSION_ENVIRONMENT_VARIABLE` - The Identity Services Engine API's version used to test the SDK.

Example:

```
#!/usr/bin/env bash
export TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH="<test account's_
↪username:password encoded in base 64>"
```

4. Add your code to your forked repository.

If you are creating some new feature or functionality (excellent!), please also write a `test` to verify that your code works as expected.

5. We follow [PEP8](#) reasonably strictly for this project. Please make sure your code passes the linter.

Run `script/test lint` from the project root.

6. Commit your changes.

7. Ensure your code passes all of the default tests for all the involved Identity Services Engine versions.

Run `script/test` and ensure all tests execute successfully.

8. Submit a [pull request](#). If everything looks good, we will gladly merge your request!

2.3 Changelog

All notable changes to this project will be documented in this file.

The format is based on [Keep a Changelog](#), and this project adheres to [Semantic Versioning](#).

2.3.1 Unreleased

2.3.2 2.1.2 - 2023-11-10

Fixed

- Fix configuration import

2.3.3 2.1.1 - 2023-11-09

Fixed

- some imports that caused problems were removed

2.3.4 2.1.0 - 2023-11-07

Added

- ciscoisesdk now supports ISE 3.2-Beta API services included: configuration, edda, dataconnect_services, subscriber

2.3.5 2.0.12 - 2023-08-25

- Update requirements and readthedocs settings

2.3.6 2.0.11 - 2023-08-24

Changed

- Update requirements

2.3.7 2.0.10 - 2023-07-25

Added

- Adding new param `ersRestIDStoreUserAttributes` on `restid_store` create function.

2.3.8 2.0.9 - 2023-04-19

Changed

- Updating request-toolbelt from 0.9.1 to 0.10.1

2.3.9 2.0.8 - 2022-11-07

Fixed

- Added a missing parameter `allow_wildcard_delete`
 - `ciscoisesdk.api.v3_1_1.certificates.delete_system_certificate_by_id`
 - `ciscoisesdk.api.v3_1_patch_1.certificates.delete_system_certificate_by_id`

2.3.10 2.0.7 - 2022-11-01

Fixed

- The following url have been repaired in `v3_1_0.mics.session_disconnect`, `v3_1_1.mics.session_disconnect` and `v3_1_patch_1.mics.session_disconnect`
 - From `/admin/API/mnt/CoA/Disconnect/{PSN_NAME}/{MAC}/{DISCONNECT_TYPE}/{NAS_IPV4}/{ENDPOINT_IP}` to `/admin/API/mnt/CoA/Disconnect/{PSN_NAME}/{MAC}/{DISCONNECT_TYPE}/{NAS_IPV4}/{ENDPOINT_IP}`

2.3.11 2.0.6 - 2022-10-27

Fixed

- The following variable names have been repaired in v3_1_0.mics, v3_1_1.mics and v3_1_patch_1.mics
 - The following variable was renamed from rec_ord_s to records
 - The following variable was renamed from sec_ond_s to seconds
 - The following variable was renamed from end_poi_ntm_ac to endpoint_mac
 - The following variable was renamed from psn_nam_e to psn_name
 - The following variable was renamed from rea_uth_tty_e to reauth_type
 - The following variable was renamed from dis_con_nec_tty_pe to disconnect_type
 - The following variable was renamed from end_poi_nti_p to endpoint_ip
- The following url have been repaired in v3_1_0.mics.session_disconnect, v3_1_1.mics.session_disconnect and v3_1_patch_1.mics.session_disconnect
 - From /admin/API/mnt/CoA/Disconnect>/{PSN_NAME}/{MAC}/{DISCONNECT_TYPE}/{NAS_IPV4}/{ENDPOINT_IP} to /admin/API/mnt/CoA/Disconnect/{PSN_NAME}/{MAC}/{DISCONNECT_TYPE}/{NAS_IPV4}/{ENDPOINT_IP}

2.3.12 2.0.5 - 2022-10-13

Fixed

- Repaired the request body of the network_access_network_conditions.create_network_access_network_condition request 3.1_patch_1 and 3.1.1
- Repaired the request body of the network_access_network_conditions.update_network_access_network_condition_by_id request 3.1_patch_1 and 3.1.1

2.3.13 2.0.4 - 2022-07-11

Fixed

- Update check_type to pass an instance of a list.

2.3.14 2.0.3 - 2022-06-07

Changed

- Default ISE DEFAULT_VERSION to 3.1_Patch_1
- Update documentation to use ISE v3.1_Patch_1

2.3.15 2.0.2 - 2022-05-02

Fixed

- Update pagination to capture and ignore 500 Internal server error when they attempt to get_next_page. Previous version only captured and ignored 404 Not Found and 400 Bad Request.

2.3.16 2.0.1 - 2022-03-24

Added

- Add DownloadResponse class that wraps the urllib3.response.HTTPResponse.
- Add filename optional parameter to the following functions:
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_csr
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_system_certificate
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_trusted_certificate
 - ciscoisesdk.api.v3_1_0.endpoint_certificate.EndpointCertificate.create_endpoint_certificate
 - ciscoisesdk.api.v3_1_0.endpoint_certificate.EndpointCertificate.create
 - ciscoisesdk.api.v3_1_0.support_bundle_download.SupportBundleDownload.download_support_bundle
 - ciscoisesdk.api.v3_1_0.support_bundle_download.SupportBundleDownload.download
 - ciscoisesdk.api.v3_1_1.certificates.Certificates.export_csr
 - ciscoisesdk.api.v3_1_1.certificates.Certificates.export_system_certificate
 - ciscoisesdk.api.v3_1_1.certificates.Certificates.export_trusted_certificate
 - ciscoisesdk.api.v3_1_1.endpoint_certificate.EndpointCertificate.create_endpoint_certificate
 - ciscoisesdk.api.v3_1_1.endpoint_certificate.EndpointCertificate.create
 - ciscoisesdk.api.v3_1_1.support_bundle_download.SupportBundleDownload.download_support_bundle
 - ciscoisesdk.api.v3_1_1.support_bundle_download.SupportBundleDownload.download

Changed

- Change the response of the following funtions from urllib3.response.HTTPResponse to a wrapper DownloadResponse.
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_csr
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_system_certificate
 - ciscoisesdk.api.v3_1_0.certificates.Certificates.export_trusted_certificate
 - ciscoisesdk.api.v3_1_0.endpoint_certificate.EndpointCertificate.create_endpoint_certificate
 - ciscoisesdk.api.v3_1_0.endpoint_certificate.EndpointCertificate.create
 - ciscoisesdk.api.v3_1_0.support_bundle_download.SupportBundleDownload.download_support_bundle
 - ciscoisesdk.api.v3_1_0.support_bundle_download.SupportBundleDownload.download
 - ciscoisesdk.api.v3_1_1.certificates.Certificates.export_csr

- `ciscoisesdk.api.v3_1_1.certificates.Certificates.export_system_certificate`
- `ciscoisesdk.api.v3_1_1.certificates.Certificates.export_trusted_certificate`
- `ciscoisesdk.api.v3_1_1.endpoint_certificate.EndpointCertificate.create_endpoint_certificate`
- `ciscoisesdk.api.v3_1_1.endpoint_certificate.EndpointCertificate.create`
- `ciscoisesdk.api.v3_1_1.support_bundle_download.SupportBundleDownload.download_support_bundle`
- `ciscoisesdk.api.v3_1_1.support_bundle_download.SupportBundleDownload.download`

2.3.17 2.0.0 - 2022-03-24

Removed

- Removed `access_token` property of `IdentityServicesEngineAPI` and `RestSession`.
- Drop ISE version 3.0.0 support.

2.3.18 1.5.1 - 2022-02-25

2.3.19 Changed

- Update docstring documentation of modules and functions.

2.3.20 1.5.0 - 2022-02-23

Changed

- Marked `access_token` property to be removed in `IdentityServicesEngineAPI` and `RestSession`.
- Changed the way of notifying Deprecation of version 3.0.0 of ISE from print to warning.
- Incremented `IdentityServicesEngineAPI` and `RestSession` constructor parameter count.
- Changed access method and imports used for environment variables and default values in `api/init.py`.
- Changed `IdentityServicesEngineAPI`'s inner properties, getters, and setters to handle only the class itself.
- `RestSession` to request for a refreshed CSRF token if `uses_csrf_token` is enabled.
- Replaced the name of headers checked for ERS methods from “X-CSRF-TOKEN” to “X-CSRF-Token”.
- Changed `ApiError` message when `status_code` is 401 or 403 to include reference to `additional_data` property.

Added

- Support for “CSRF Check for Enhanced Security” for the ISE ERS API (#20).
- Added `status_code` to `RestResponse` (#22).
- Support to have `additional_data` for `ApiError` when HTTP status code are 401 or 403 (#21). The `additional_data` returns a string with:
 - Authorization header used.
 - X-CSRF-Token header used if it was found.

- Username used.
 - Password used.
- Support for managing changes of the IdentityServicesEngineAPI's properties (#21):
 - initialize_authentication function.
 - initialize_sessions function.
 - initialize_api_wrappers function.
 - reinitialize function.
 - authentication getter function.
 - perform_initialize getter function.
 - username getter and setter functions.
 - is_password utility function.
 - is_encoded_auth utility function.
 - uses_api_gateway getter and setter functions.
 - base_url getter and setter functions.
 - ui_base_url getter and setter functions.
 - ers_base_url getter and setter functions.
 - mnt_base_url getter and setter functions.
 - px_grid_base_url getter and setter functions.
 - single_request_timeout getter and setter functions.
 - wait_on_rate_limit getter and setter functions.
 - verify getter and setter functions.
 - version getter and setter functions.
 - debug getter and setter functions.
 - uses_csrf_token getter and setter functions.
 - object_factory getter and setter functions.
 - validator getter and setter functions.
 - session getter function.
 - session_ui getter function.
 - session_ers getter function.
 - session_mnt getter function.
 - session_px_grid getter function.
 - username getter function.
 - change_password utility setter function.
 - change_encoded_auth utility setter function.
- Added warnings for changes of the IdentityServicesEngineAPI's properties.
- Added a test importsdk to verify the behavior between environment variables and module import order.

- New `perform_initialize` parameter for `IdentityServicesEngineAPI` constructor.
- New `uses_csrf_token` parameter for `IdentityServicesEngineAPI` constructor.
- New `get_csrf_token` function for `IdentityServicesEngineAPI`.
- New `uses_csrf_token` and `get_csrf_token` parameters for `RestSession` constructor.
- New `DEFAULT_USES_CSRF_TOKEN` value in `config.py`.
- New `IDENTITY_SERVICES_ENGINE_USES_CSRF_TOKEN` environment variable in `environment.py`.
- New `initialize_authentication` function for `IdentityServicesEngineAPI`.
- New `initialize_sessions` function for `IdentityServicesEngineAPI`.
- New `initialize_api_wrappers` function for `IdentityServicesEngineAPI`.
- New `reinitialize` function for `IdentityServicesEngineAPI`.
- New `is_password` function for `IdentityServicesEngineAPI`.
- New `is_encoded_auth` function for `IdentityServicesEngineAPI`.
- New `change_password` function for `IdentityServicesEngineAPI`.
- New `change_encoded_auth` function for `IdentityServicesEngineAPI`.
- New `debug` setter function for `RestSession`.
- New `uses_csrf_token` getter and setter functions for `RestSession`.
- New `additional_data` property in `ApiError`.

Fixed

- The process that gets the environment variables now can access the variables set after the module is imported, and not only before it.
- Fixed the docstring tables of the API modules.

2.3.21 1.4.2 - 2022-02-18

Fixed

- Update pagination to capture and ignore 400 Bad Request in generators when they attempt to `get_next_page`. Previous version only captured and ignored 404 Not Found.

2.3.22 1.4.1 - 2022-01-20

Changed

- Update module inner documentation.
- Downgrade requirements file to use poetry versions.

2.3.23 1.4.0 - 2022-01-19

Changed

- Update requirements

Fixed

- Update pagination, get_next_page inner logic and location from utils to pagination.

2.3.24 1.3.1 - 2021-12-13

Changed

- Fixes utils.get_next_page generator starting default page

2.3.25 1.3.0 - 2021-12-13

Added

- Adds licensing module
- Adds node_services module
- Adds patching module
- Adds proxy module
- Adds telemetry module
- Adds certificates.generate_self_signed_certificate function
- Adds node_deployment.make_primary function
- Adds node_deployment.make_standalone function
- Adds node_deployment.sync_node function
- Adds node_group.add_node function
- Adds node_group.get_nodes function
- Adds node_group.remove_node function
- Adds pan_ha.update_pan_ha function

Removed

- Removes pan_ha.disable_pan_ha function
- Removes pan_ha.enable_pan_ha function
- Removes replication_status module
- Removes sync_ise_node module

2.3.26 1.2.0 - 2021-11-24

Added

- Adds notice for 3.0.0 (soon to be deprecated)
- Adds Trust Sec endpoints to ISE version 3.1.0

Changed

- Fixes paths for Policy endpoints (get_device_admin_profiles, get_network_access_profiles)
- Updates ISE version 3.1.0 as separate version

Removed

- Removes link of 3.1.0 modules to 3.0.0 version

2.3.27 1.1.0 - 2021-10-22

Added

- Link of 3.1.0 modules to 3.0.0 version

Changed

- Default ISE DEFAULT_VERSION to 3.1.0
- Update documentation to use ISE v3.1.0

2.3.28 1.0.1 - 2021-09-14

Changed

- Disabled warnings of urllib3 if verify is False

2.3.29 1.0.0 - 2021-07-21

Added

- Missing parameters for functions
- get_version functions for ERS wrapper classes.
- Missing functions:
 - AncPolicy.get_anc_policy_generator
 - BackupAndRestore.update_scheduled_config_backup
 - CertificateTemplate.get_certificate_template_generator
 - DeviceAdministrationAuthenticationRules.reset_hit_counts_device_admin_authentication_rules

- DeviceAdministrationAuthorizationExceptionRules.reset_hit_counts_device_admin_local_exceptions
- DeviceAdministrationAuthorizationGlobalExceptionRules.reset_hit_counts_device_admin_global_exceptions
- DeviceAdministrationAuthorizationRules.reset_hit_counts_device_admin_authorization_rules
- DeviceAdministrationPolicySet.reset_hit_counts_device_admin_policy_sets
- MyDevicePortal.delete_my_device_portal_by_id
- NetworkAccessAuthenticationRules.reset_hit_counts_network_access_authentication_rules
- NetworkAccessAuthorizationExceptionRules.reset_hit_counts_network_access_local_exceptions
- NetworkAccessAuthorizationRules.reset_hit_counts_network_access_authorization_rules
- NetworkAccessPolicySet.reset_hit_counts_network_access_policy_sets
- SessionServiceNode.get_session_service_node_generator
- SupportBundleStatus.get_support_bundle_status_generator
- TacacsCommandSets.get_tacacs_command_sets_generator
- Aliases for functions (eg. `get_all`, `get_by_id`, `get_by_name`, `update_by_id`, `delete_by_id`, `create`, and others)

Changed

- Rename module names
 - `deployment` to `pull_deployment_info`
 - `threat` to `clear_threats_and_vulnerabilities`
 - `endpoint_group` to `endpoint_identity_group`
 - `identity_group` to `identity_groups`
 - `identity_store_sequence` to `identity_sequence`
 - `node` to `node_details`
 - `endpoint_cert` to `endpoint_certificate`
 - `guest_smtp_notifications` to `guest_smtp_notification_configuration`
 - `session_service_node` to `psn_node_details_with_radius_service`
 - `sg_acl` to `security_groups_acls`
 - `sg_mapping_group` to `ip_to_sgt_mapping_group`
 - `sg_mapping` to `ip_to_sgt_mapping`
 - `sgt_vn_vlan` to `security_group_to_virtual_network`
 - `sgt` to `security_groups`
 - `support_bundle` to `support_bundle_download`, `support_bundle_status` & `support_bundle_trigger_configuration`
 - `version_` to `version_and_patch`
- Rename function names
 - (BackupAndRestore) `schedule_config_backup` to `create_scheduled_config_backup`
 - (Certificates) `get_csr` to `get_csrs`

- (Certificates) `get_csr_generator` to `get_csrs_generator`
- (Certificates) `renew_certificate` to `renew_certificates`
- (Certificates) `export_system_cert` to `export_system_certificate`
- (Certificates) `export_trusted_cert` to `export_trusted_certificate`
- (DeviceAdministrationAuthenticationRules) `create_device_admin_authentication_rules` to `create_device_admin_authentication_rule`
- (DeviceAdministrationAuthorizationExceptionRules) `delete_device_admin_policyset_global_exception_by_id` to `delete_device_admin_policy_set_global_exception_by_rule_id`
- (DeviceAdministrationAuthorizationExceptionRules) `get_device_admin_policy_set_global_exception` to `get_device_admin_policy_set_global_exception_rules`
- (DeviceAdministrationAuthorizationExceptionRules) `get_device_admin_policy_set_global_exception_by_id` to `get_device_admin_policy_set_global_exception_by_rule_id`
- (DeviceAdministrationAuthorizationExceptionRules) `update_device_admin_policyset_global_exception_by_id` to `update_device_admin_policy_set_global_exception_by_rule_id`
- (DeviceAdministrationDictionaryAttributesList) `get_device_admin_dictionaries_policyset` to `get_device_admin_dictionaries_policy_set`
- (GuestType) `update_guesttype_by_id` to `update_guest_type_by_id`
- (IdentityStoreSequence) `create_identity_store_sequence` to `create_identity_sequence`
- (IdentityStoreSequence) `delete_identity_store_sequence_by_id` to `delete_identity_sequence_by_id`
- (IdentityStoreSequence) `get_identity_store_sequence` to `get_identity_sequence`
- (IdentityStoreSequence) `get_identity_store_sequence_by_id` to `get_identity_sequence_by_id`
- (IdentityStoreSequence) `get_identity_store_sequence_by_name` to `get_identity_sequence_by_name`
- (IdentityStoreSequence) `get_identity_store_sequence_generator` to `get_identity_sequence_generator`
- (IdentityStoreSequence) `update_identity_store_sequence_by_id` to `update_identity_sequence_by_id`
- (InternalUser) `internaluser_by_id` to `get_internal_user_by_id`
- (NetworkAccessAuthorizationGlobalExceptionRules) `create_network_access_global_exception_rule` to `create_network_access_policy_set_global_exception_rule`
- (NetworkAccessAuthorizationGlobalExceptionRules) `delete_network_access_global_exception_rule_by_id` to `delete_network_access_policy_set_global_exception_rule_by_id`
- (NetworkAccessAuthorizationGlobalExceptionRules) `get_network_access_global_exception_rule_by_id` to `get_network_access_policy_set_global_exception_rule_by_id`
- (NetworkAccessAuthorizationGlobalExceptionRules) `get_network_access_global_exception_rules` to `get_network_access_policy_set_global_exception_rules`
- (NetworkAccessAuthorizationGlobalExceptionRules) `update_network_access_global_exception_rule_by_id` to `update_network_access_policy_set_global_exception_rule_by_id`
- (DeviceAdministrationConditions) `get_device_admin_conditions_for_authentication_rule` to `get_device_admin_conditions_for_authentication_rules`

- (DeviceAdministrationConditions) `get_device_admin_conditions_for_authorization_rule` to `get_device_admin_conditions_for_authorization_rules`
- (DeviceAdministrationConditions) `get_device_admin_conditions_for_policy_set` to `get_device_admin_conditions_for_policy_sets`
- (NetworkAccessConditions) `get_network_access_conditions_for_authorization_rule` to `get_network_access_conditions_for_authorization_rules`
- (NetworkAccessConditions) `get_network_access_conditions_for_policy_set` to `get_network_access_conditions_for_policy_sets`
- (NetworkAccessDictionary) `delete_network_access_dictionaries_by_name` to `delete_network_access_dictionary_by_name`
- (NetworkAccessDictionary) `update_network_access_dictionaries_by_name` to `update_network_access_dictionary_by_name`
- (NetworkAccessDictionary) `create_network_access_dictionary_attribute_for_dictionary` to `create_network_access_dictionary_attribute`
- (NetworkAccessDictionaryAttributesList) `get_network_access_dictionaries_policyset` to `get_network_access_dictionaries_policy_set`
- (Node) `get_node_by_id` to `get_node_detail_by_id`
- (Node) `get_node_by_name` to `get_node_detail_by_name`
- (Node) `get_nodes` to `get_node_details`
- (PxGridSettings) `autoapprove_px_grid_node` to `autoapprove_px_grid_settings`
- (Repository) `delete_repository_by_name` to `delete_repository`
- (Repository) `get_repository_by_name` to `get_repository`
- (Repository) `update_repository_by_name` to `update_repository`

Removed

- Removed module
 - `service`
- Removed unknown functions for the API
 - `identity_group.delete_identity_group_by_id`

GENERAL INFORMATION ABOUT THE IDENTITY SERVICES ENGINE SERVICE

3.1 What is Identity Services Engine?

“A better way to control your network. Cisco Identity Services Engine is the network management and command center for Cisco Identity Services Engine, your intent-based network for the enterprise.”

Visit the official [Identity Services Engine](#) website for more information and to create a [free account](#)!

3.2 Identity Services Engine for Developers

Leveraging the Identity Services Engine APIs and developing on top of the Identity Services Engine cloud is easy. Signup for a [free account](#) and then head over to the [Identity Services Engine for Developers](#) website to learn more.

Copyright (c) 2023 Cisco and/or its affiliates.

PYTHON MODULE INDEX

C

`ciscoisesdk.config`, [13](#)

Symbols

`__init__()` (*IdentityServicesEngineAPI* method), 31

A

`access_secret()` (*Consumer* method), 171, 889, 1627, 2366

`AccessTokenError`, 2959

`AciBindings` (class in *ciscois-esdk.api.v3_1_0.aci_bindings*), 37

`AciBindings` (class in *ciscois-esdk.api.v3_1_1.aci_bindings*), 751

`AciBindings` (class in *ciscois-esdk.api.v3_1_patch_1.aci_bindings*), 1489

`AciBindings` (class in *ciscois-esdk.api.v3_2_beta.aci_bindings*), 2227

`AciSettings` (class in *ciscois-esdk.api.v3_1_0.aci_settings*), 40

`AciSettings` (class in *ciscois-esdk.api.v3_1_1.aci_settings*), 754

`AciSettings` (class in *ciscois-esdk.api.v3_1_patch_1.aci_settings*), 1492

`AciSettings` (class in *ciscois-esdk.api.v3_2_beta.aci_settings*), 2230

`activate_account()` (*Consumer* method), 170, 888, 1626, 2365

`ActiveDirectory` (class in *ciscois-esdk.api.v3_1_0.active_directory*), 52

`ActiveDirectory` (class in *ciscois-esdk.api.v3_1_1.active_directory*), 766

`ActiveDirectory` (class in *ciscois-esdk.api.v3_1_patch_1.active_directory*), 1504

`ActiveDirectory` (class in *ciscois-esdk.api.v3_2_beta.active_directory*), 2242

`add_api()` (*CustomCaller* method), 36

`add_node()` (*NodeGroup* method), 1199, 1937, 2687

`additional_data` (*ApiError* attribute), 2959

`AdminUser` (class in *ciscois-esdk.api.v3_1_0.admin_user*), 69

`AdminUser` (class in *ciscois-esdk.api.v3_1_1.admin_user*), 783

`AdminUser` (class in *ciscois-esdk.api.v3_1_patch_1.admin_user*), 1521

`AdminUser` (class in *ciscois-esdk.api.v3_2_beta.admin_user*), 2259

`AllowedProtocols` (class in *ciscois-esdk.api.v3_1_0.allowed_protocols*), 73

`AllowedProtocols` (class in *ciscois-esdk.api.v3_1_1.allowed_protocols*), 787

`AllowedProtocols` (class in *ciscois-esdk.api.v3_1_patch_1.allowed_protocols*), 1525

`AllowedProtocols` (class in *ciscois-esdk.api.v3_2_beta.allowed_protocols*), 2263

`AncEndpoint` (class in *ciscois-esdk.api.v3_1_0.anc_endpoint*), 45

`AncEndpoint` (class in *ciscois-esdk.api.v3_1_1.anc_endpoint*), 759

`AncEndpoint` (class in *ciscois-esdk.api.v3_1_patch_1.anc_endpoint*), 1497

`AncEndpoint` (class in *ciscois-esdk.api.v3_2_beta.anc_endpoint*), 2235

`AncPolicy` (class in *ciscois-esdk.api.v3_1_0.anc_policy*), 91

`AncPolicy` (class in *ciscois-esdk.api.v3_1_1.anc_policy*), 805

`AncPolicy` (class in *ciscois-esdk.api.v3_1_patch_1.anc_policy*), 1543

`AncPolicy` (class in *ciscois-esdk.api.v3_2_beta.anc_policy*), 2281

`ApiError`, 2959

`apply()` (*AncEndpoint* method), 50, 764, 1502, 2240

`apply_anc_endpoint()` (*AncEndpoint* method), 49, 763, 1501, 2239

`approve()` (*PxGridNode* method), 725, 1462, 2200, 2951

`approve_by_id()` (*GuestUser* method), 287, 1005, 1743, 2492

`approve_guest_user_by_id()` (*GuestUser* method), 286, 1004, 1742, 2491

`approve_px_grid_node()` (*PxGridNode* method), 725, 1461, 2199, 2951

`Authentication` (class in *ciscois-esdk.api.authentication*), 35

authentication (*IdentityServicesEngineAPI* property), 34

authentication_api() (*Authentication* method), 35

authorization() (*Provider* method), 496, 1232, 1970, 2720

AuthorizationProfile (class in *ciscoisesdk.api.v3_1_0.authorization_profile*), 100

AuthorizationProfile (class in *ciscoisesdk.api.v3_1_1.authorization_profile*), 814

AuthorizationProfile (class in *ciscoisesdk.api.v3_1_patch_1.authorization_profile*), 1552

AuthorizationProfile (class in *ciscoisesdk.api.v3_2_beta.authorization_profile*), 2290

autoapprove() (*PxGridSettings* method), 507, 1243, 1981, 2731

autoapprove_px_grid_settings() (*PxGridSettings* method), 507, 1243, 1981, 2731

B

BackupAndRestore (class in *ciscoisesdk.api.v3_1_0.backup_and_restore*), 125

BackupAndRestore (class in *ciscoisesdk.api.v3_1_1.backup_and_restore*), 839

BackupAndRestore (class in *ciscoisesdk.api.v3_1_patch_1.backup_and_restore*), 1577

BackupAndRestore (class in *ciscoisesdk.api.v3_2_beta.backup_and_restore*), 2315

base_url (*Authentication* property), 35

base_url (*IdentityServicesEngineAPI* property), 34

bind_csr() (*Certificates* method), 149, 863, 1601, 2339

bulk_create_sg_vn_mappings() (*SgVnMapping* method), 732, 1468, 2206

bulk_create_virtual_networks() (*VirtualNetwork* method), 740, 1478, 2216

bulk_create_vn_vlan_mappings() (*VnVlanMapping* method), 747, 1485, 2223

bulk_delete_sg_vn_mappings() (*SgVnMapping* method), 733, 1469, 2207

bulk_delete_virtual_networks() (*VirtualNetwork* method), 741, 1478, 2216

bulk_delete_vn_vlan_mappings() (*VnVlanMapping* method), 747, 1485, 2223

bulk_request() (*AncEndpoint* method), 51, 765, 1503, 2241

bulk_request() (*AncPolicy* method), 99, 813, 1551, 2289

bulk_request() (*EgressMatrixCell* method), 234, 952, 1690, 2439

bulk_request() (*Endpoint* method), 714, 1449, 2187, 2943

bulk_request() (*GuestUser* method), 301, 1019, 1757, 2506

bulk_request() (*IpToSgtMapping* method), 324, 1042, 1780, 2529

bulk_request() (*IpToSgtMappingGroup* method), 333, 1051, 1789, 2538

bulk_request() (*NetworkDevice* method), 458, 1183, 1921, 2670

bulk_request() (*SecurityGroups* method), 570, 1306, 2044, 2794

bulk_request() (*SecurityGroupsAcls* method), 578, 1314, 2052, 2802

bulk_request() (*SecurityGroupToVirtualNetwork* method), 562, 1298, 2036, 2786

bulk_request() (*SxpConnections* method), 541, 1276, 2014, 2764

bulk_request() (*SxpLocalBindings* method), 549, 1284, 2022, 2772

bulk_request() (*SxpVpns* method), 555, 1290, 2028, 2778

bulk_request_create() (*SgVnMapping* method), 733, 1469, 2207

bulk_request_create() (*VirtualNetwork* method), 741, 1478, 2216

bulk_request_create() (*VnVlanMapping* method), 747, 1485, 2223

bulk_request_delete() (*SgVnMapping* method), 733, 1470, 2208

bulk_request_delete() (*VirtualNetwork* method), 741, 1479, 2217

bulk_request_delete() (*VnVlanMapping* method), 748, 1486, 2224

bulk_request_for_anc_endpoint() (*AncEndpoint* method), 50, 764, 1502, 2240

bulk_request_for_anc_policy() (*AncPolicy* method), 98, 812, 1550, 2288

bulk_request_for_egress_matrix_cell() (*EgressMatrixCell* method), 233, 951, 1689, 2438

bulk_request_for_endpoint() (*Endpoint* method), 713, 1448, 2186, 2942

bulk_request_for_guest_user() (*GuestUser* method), 300, 1018, 1756, 2505

bulk_request_for_ip_to_sgt_mapping() (*IpToSgtMapping* method), 323, 1041, 1779, 2528

bulk_request_for_ip_to_sgt_mapping_group() (*IpToSgtMappingGroup* method), 332, 1050, 1788, 2537

bulk_request_for_network_device() (*NetworkDevice* method), 457, 1182, 1920, 2670

bulk_request_for_security_group() (*SecurityGroups* method), 570, 1305, 2043, 2793

bulk_request_for_security_groups_acl() (*SecurityGroupsAcls* method), 578, 1313, 2051, 2801

- bulk_request_for_security_groups_to_vn_to_vlan_mappings() (*SecurityGroupToVirtualNetwork* method), 562, 1297, 2035, 2785
- bulk_request_for_sxp_connections() (*SxpConnections* method), 540, 1276, 2014, 2764
- bulk_request_for_sxp_local_bindings() (*SxpLocalBindings* method), 548, 1283, 2021, 2771
- bulk_request_for_sxp_vpns() (*SxpVpns* method), 554, 1290, 2028, 2778
- bulk_request_update() (*SgVnMapping* method), 734, 1470, 2208
- bulk_request_update() (*VirtualNetwork* method), 742, 1480, 2218
- bulk_request_update() (*VnVlanMapping* method), 749, 1487, 2225
- bulk_subscriber_operation() (*Subscriber* method), 2881
- bulk_update_sg_vn_mappings() (*SgVnMapping* method), 733, 1470, 2208
- bulk_update_virtual_networks() (*VirtualNetwork* method), 741, 1479, 2217
- bulk_update_vn_vlan_mappings() (*VnVlanMapping* method), 748, 1486, 2224
- ByodPortal (class in *ciscoisesdk.api.v3_1_0.byod_portal*), 111
- ByodPortal (class in *ciscoisesdk.api.v3_1_1.byod_portal*), 825
- ByodPortal (class in *ciscoisesdk.api.v3_1_patch_1.byod_portal*), 1563
- ByodPortal (class in *ciscoisesdk.api.v3_2_beta.byod_portal*), 2301
- ## C
- call_api() (*CustomCaller* method), 36
- cancel() (*BackupAndRestore* method), 126, 840, 1578, 2316
- cancel_backup() (*BackupAndRestore* method), 126, 840, 1578, 2316
- CertificateProfile (class in *ciscoisesdk.api.v3_1_0.certificate_profile*), 131
- CertificateProfile (class in *ciscoisesdk.api.v3_1_1.certificate_profile*), 845
- CertificateProfile (class in *ciscoisesdk.api.v3_1_patch_1.certificate_profile*), 1583
- CertificateProfile (class in *ciscoisesdk.api.v3_2_beta.certificate_profile*), 2321
- Certificates (class in *ciscoisesdk.api.v3_1_0.certificates*), 142
- Certificates (class in *ciscoisesdk.api.v3_1_1.certificates*), 856
- Certificates (class in *ciscoisesdk.api.v3_1_patch_1.certificates*), 1594
- Certificates (class in *ciscoisesdk.api.v3_2_beta.certificates*), 2332
- CertificateTemplate (class in *ciscoisesdk.api.v3_1_0.certificate_template*), 138
- CertificateTemplate (class in *ciscoisesdk.api.v3_1_1.certificate_template*), 852
- CertificateTemplate (class in *ciscoisesdk.api.v3_1_patch_1.certificate_template*), 1590
- CertificateTemplate (class in *ciscoisesdk.api.v3_2_beta.certificate_template*), 2328
- change_encoded_auth() (*IdentityServicesEngineAPI* method), 34
- change_password() (*IdentityServicesEngineAPI* method), 34
- change_sponsor_password() (*GuestUser* method), 287, 1005, 1743, 2492
- ciscoisesdk.config module, 13
- ciscoisesdkException, 2959
- clear() (*AncEndpoint* method), 47, 761, 1499, 2237
- clear() (*ClearThreatsAndVulnerabilities* method), 168, 886, 1624, 2362
- clear() (*EgressMatrixCell* method), 226, 944, 1682, 2431
- clear_all_matrix_cells() (*EgressMatrixCell* method), 225, 943, 1681, 2431
- clear_anc_endpoint() (*AncEndpoint* method), 46, 760, 1498, 2236
- clear_threats_and_vulnerabilities() (*ClearThreatsAndVulnerabilities* method), 168, 886, 1624, 2362
- ClearThreatsAndVulnerabilities (class in *ciscoisesdk.api.v3_1_0.clear_threats_and_vulnerabilities*), 167
- ClearThreatsAndVulnerabilities (class in *ciscoisesdk.api.v3_1_1.clear_threats_and_vulnerabilities*), 885
- ClearThreatsAndVulnerabilities (class in *ciscoisesdk.api.v3_1_patch_1.clear_threats_and_vulnerabilities*), 1623
- ClearThreatsAndVulnerabilities (class in *ciscoisesdk.api.v3_2_beta.clear_threats_and_vulnerabilities*), 2361
- clone() (*EgressMatrixCell* method), 227, 945, 1683, 2433
- clone_matrix_cell() (*EgressMatrixCell* method), 227, 945, 1683, 2432
- config() (*BackupAndRestore* method), 126, 840, 1578, 2316
- config_backup() (*BackupAndRestore* method), 125, 839, 1577, 2315
- Configuration (class in *ciscoisesdk*), 13

esdk.api.v3_2_beta.configuration), 2363
 configure_smart_state() (*Licensing method*), 1078, 1816, 2565
 Consumer (*class in ciscoisesdk.api.v3_1_0.consumer*), 169
 Consumer (*class in ciscoisesdk.api.v3_1_1.consumer*), 887
 Consumer (*class in ciscoisesdk.api.v3_1_patch_1.consumer*), 1625
 Consumer (*class in ciscoisesdk.api.v3_2_beta.consumer*), 2364
 content (*RestResponse property*), 2958
 create() (*ActiveDirectory method*), 68, 782, 1520, 2258
 create() (*AllowedProtocols method*), 90, 804, 1542, 2280
 create() (*AncPolicy method*), 98, 812, 1550, 2288
 create() (*AuthorizationProfile method*), 110, 824, 1562, 2300
 create() (*BackupAndRestore method*), 130, 844, 1582, 2320
 create() (*ByodPortal method*), 124, 838, 1576, 2314
 create() (*CertificateProfile method*), 137, 851, 1589, 2327
 create() (*Consumer method*), 170, 888, 1626, 2365
 create() (*DeviceAdministrationAuthenticationRules method*), 173, 891, 1629, 2372
 create() (*DeviceAdministrationAuthorizationExceptionRules method*), 178, 896, 1634, 2377
 create() (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 182, 900, 1638, 2381
 create() (*DeviceAdministrationAuthorizationRules method*), 187, 905, 1643, 2385
 create() (*DeviceAdministrationConditions method*), 193, 911, 1649, 2392
 create() (*DeviceAdministrationNetworkConditions method*), 205, 923, 1661, 2404
 create() (*DeviceAdministrationPolicySet method*), 209, 927, 1665, 2409
 create() (*DeviceAdministrationTimeDateConditions method*), 216, 934, 1672, 2416
 create() (*DownloadableAcl method*), 224, 942, 1680, 2424
 create() (*EgressMatrixCell method*), 232, 950, 1688, 2438
 create() (*Endpoint method*), 713, 1448, 2186, 2942
 create() (*EndpointCertificate method*), 237, 955, 1693, 2442
 create() (*EndpointIdentityGroup method*), 244, 962, 1700, 2449
 create() (*ExternalRadiusServer method*), 252, 970, 1708, 2457
 create() (*FilterPolicy method*), 258, 976, 1714, 2463
 create() (*GuestSntpNotificationConfiguration method*), 268, 986, 1724, 2473
 create() (*GuestSsid method*), 274, 992, 1730, 2479
 create() (*GuestType method*), 283, 1001, 1739, 2488
 create() (*GuestUser method*), 299, 1017, 1755, 2504
 create() (*HotspotPortal method*), 314, 1032, 1770, 2519
 create() (*IdentityGroups method*), 339, 1057, 1795, 2544
 create() (*IdentitySequence method*), 345, 1063, 1801, 2550
 create() (*InternalUser method*), 355, 1073, 1811, 2560
 create() (*IpToSgtMapping method*), 323, 1041, 1779, 2528
 create() (*IpToSgtMappingGroup method*), 332, 1050, 1788, 2537
 create() (*MyDevicePortal method*), 381, 1105, 1843, 2592
 create() (*NbarApp method*), 718, 1453, 2191
 create() (*NetworkAccessAuthenticationRules method*), 389, 1113, 1851, 2600
 create() (*NetworkAccessAuthorizationExceptionRules method*), 393, 1117, 1855, 2604
 create() (*NetworkAccessAuthorizationGlobalExceptionRules method*), 397, 1121, 1859, 2609
 create() (*NetworkAccessAuthorizationRules method*), 402, 1126, 1864, 2613
 create() (*NetworkAccessConditions method*), 407, 1131, 1869, 2619
 create() (*NetworkAccessDictionary method*), 417, 1141, 1879, 2628
 create() (*NetworkAccessDictionaryAttribute method*), 421, 1145, 1883, 2632
 create() (*NetworkAccessNetworkConditions method*), 428, 1152, 1890, 2639
 create() (*NetworkAccessPolicySet method*), 432, 1156, 1894, 2644
 create() (*NetworkAccessTimeDateConditions method*), 439, 1164, 1902, 2652
 create() (*NetworkDevice method*), 456, 1181, 1919, 2669
 create() (*NetworkDeviceGroup method*), 464, 1189, 1927, 2677
 create() (*PortalTheme method*), 489, 1225, 1963, 2713
 create() (*RadiusServerSequence method*), 516, 1252, 1990, 2740
 create() (*Repository method*), 528, 1263, 2001, 2751
 create() (*RestidStore method*), 525, 1261, 1999, 2749
 create() (*SecurityGroups method*), 569, 1304, 2042, 2792
 create() (*SecurityGroupsAcls method*), 577, 1312, 2050, 2800
 create() (*SecurityGroupToVirtualNetwork method*), 561, 1297, 2035, 2785
 create() (*SelfRegisteredPortal method*), 606, 1341,

- 2079, 2829
- `create()` (*SgVnMapping method*), 732, 1468, 2206
- `create()` (*SponsoredGuestPortal method*), 654, 1389, 2127, 2877
- `create()` (*SponsorGroup method*), 619, 1354, 2092, 2842
- `create()` (*SponsorPortal method*), 636, 1371, 2109, 2859
- `create()` (*SupportBundleTriggerConfiguration method*), 663, 1398, 2136, 2892
- `create()` (*SxpConnections method*), 539, 1275, 2013, 2763
- `create()` (*SxpLocalBindings method*), 547, 1283, 2021, 2771
- `create()` (*SxpVpns method*), 554, 1289, 2027, 2777
- `create()` (*SystemCertificate method*), 668, 1403, 2141, 2897
- `create()` (*TacacsCommandSets method*), 675, 1410, 2148, 2904
- `create()` (*TacacsExternalServers method*), 681, 1416, 2154, 2910
- `create()` (*TacacsProfile method*), 687, 1422, 2160, 2916
- `create()` (*TacacsServerSequence method*), 693, 1428, 2166, 2922
- `create()` (*VirtualNetwork method*), 740, 1478, 2216
- `create()` (*VnVlanMapping method*), 747, 1485, 2223
- `create_account()` (*Consumer method*), 169, 887, 1625, 2365
- `create_active_directory()` (*ActiveDirectory method*), 68, 782, 1520, 2258
- `create_allowed_protocol()` (*AllowedProtocols method*), 88, 802, 1540, 2278
- `create_anc_policy()` (*AncPolicy method*), 97, 811, 1549, 2287
- `create_authorization_profile()` (*Authorization-Profile method*), 108, 822, 1560, 2298
- `create_byod_portal()` (*ByodPortal method*), 123, 837, 1575, 2313
- `create_certificate_profile()` (*CertificateProfile method*), 136, 850, 1588, 2326
- `create_connector_config()` (*Edda method*), 2426
- `create_device_admin_authentication_rule()` (*DeviceAdministrationAuthenticationRules method*), 172, 890, 1628, 2371
- `create_device_admin_authorization_rule()` (*DeviceAdministrationAuthorizationRules method*), 186, 904, 1642, 2385
- `create_device_admin_condition()` (*DeviceAdministrationConditions method*), 191, 909, 1647, 2390
- `create_device_admin_local_exception_rule()` (*DeviceAdministrationAuthorizationException-Rules method*), 177, 895, 1633, 2376
- `create_device_admin_network_condition()` (*DeviceAdministrationNetworkConditions method*), 204, 922, 1660, 2403
- `create_device_admin_policy_set()` (*DeviceAdministrationPolicySet method*), 208, 926, 1664, 2408
- `create_device_admin_policy_set_global_exception()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 182, 900, 1638, 2380
- `create_device_admin_time_condition()` (*DeviceAdministrationTimeDateConditions method*), 214, 932, 1670, 2414
- `create_downloadable_acl()` (*DownloadableAcl method*), 223, 941, 1679, 2424
- `create_egress_matrix_cell()` (*EgressMatrixCell method*), 232, 950, 1688, 2437
- `create_endpoint()` (*Endpoint method*), 712, 1447, 2185, 2941
- `create_endpoint_certificate()` (*EndpointCertificate method*), 236, 954, 1692, 2441
- `create_endpoint_group()` (*EndpointIdentityGroup method*), 243, 961, 1699, 2448
- `create_external_radius_server()` (*ExternalRadiusServer method*), 251, 969, 1707, 2456
- `create_filter_policy()` (*FilterPolicy method*), 257, 975, 1713, 2462
- `create_guest_smtp_notification_settings()` (*GuestSmtNotificationConfiguration method*), 267, 985, 1723, 2472
- `create_guest_ssid()` (*GuestSsid method*), 274, 992, 1730, 2479
- `create_guest_type()` (*GuestType method*), 282, 1000, 1738, 2487
- `create_guest_user()` (*GuestUser method*), 298, 1016, 1754, 2503
- `create_hotspot_portal()` (*HotspotPortal method*), 314, 1032, 1770, 2519
- `create_identity_group()` (*IdentityGroups method*), 338, 1056, 1794, 2543
- `create_identity_sequence()` (*IdentitySequence method*), 344, 1062, 1800, 2549
- `create_internal_user()` (*InternalUser method*), 354, 1072, 1810, 2559
- `create_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 322, 1040, 1778, 2527
- `create_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup method*), 331, 1049, 1787, 2536
- `create_my_device_portal()` (*MyDevicePortal method*), 381, 1104, 1842, 2591
- `create_nbar_app()` (*NbarApp method*), 717, 1452, 2190
- `create_network_access_authentication_rule()` (*NetworkAccessAuthenticationRules method*), 388, 1112, 1850, 2599
- `create_network_access_authorization_rule()`

- (*NetworkAccessAuthorizationRules* method), 401, 1125, 1863, 2612
- `create_network_access_condition()` (*NetworkAccessConditions* method), 405, 1129, 1867, 2617
- `create_network_access_dictionaries()` (*NetworkAccessDictionary* method), 416, 1140, 1878, 2628
- `create_network_access_dictionary_attribute()` (*NetworkAccessDictionaryAttribute* method), 420, 1144, 1882, 2631
- `create_network_access_local_exception_rule()` (*NetworkAccessAuthorizationExceptionRules* method), 392, 1116, 1854, 2603
- `create_network_access_network_condition()` (*NetworkAccessNetworkConditions* method), 427, 1151, 1889, 2638
- `create_network_access_policy_set()` (*NetworkAccessPolicySet* method), 430, 1155, 1893, 2643
- `create_network_access_policy_set_global_exception_rule()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 397, 1121, 1859, 2608
- `create_network_access_time_condition()` (*NetworkAccessTimeDateConditions* method), 438, 1162, 1900, 2650
- `create_network_device()` (*NetworkDevice* method), 455, 1180, 1918, 2668
- `create_network_device_group()` (*NetworkDeviceGroup* method), 464, 1189, 1927, 2676
- `create_node_group()` (*NodeGroup* method), 470, 1196, 1934, 2684
- `create_portal_theme()` (*PortalTheme* method), 488, 1225, 1963, 2712
- `create_radius_server_sequence()` (*RadiusServerSequence* method), 514, 1250, 1988, 2738
- `create_registration_info()` (*Licensing* method), 1076, 1814, 2563
- `create_repository()` (*Repository* method), 527, 1262, 2000, 2750
- `create_rest_id_store()` (*RestidStore* method), 524, 1260, 1998, 2748
- `create_scheduled_config_backup()` (*BackupAndRestore* method), 129, 843, 1581, 2319
- `create_security_group()` (*SecurityGroups* method), 568, 1304, 2042, 2792
- `create_security_groups_acl()` (*SecurityGroupAcls* method), 576, 1312, 2050, 2800
- `create_security_groups_to_vn_to_vlan()` (*SecurityGroupToVirtualNetwork* method), 560, 1296, 2034, 2784
- `create_self_registered_portal()` (*SelfRegisteredPortal* method), 605, 1340, 2078, 2828
- `create_sg_vn_mapping()` (*SgVnMapping* method), 731, 1468, 2206
- `create_sponsor_group()` (*SponsorGroup* method), 618, 1353, 2091, 2841
- `create_sponsor_portal()` (*SponsorPortal* method), 636, 1371, 2109, 2859
- `create_sponsored_guest_portal()` (*SponsoredGuestPortal* method), 654, 1389, 2127, 2877
- `create_subscriber()` (*Subscriber* method), 2880
- `create_support_bundle()` (*SupportBundleTriggerConfiguration* method), 662, 1397, 2135, 2891
- `create_sxp_connections()` (*SxpConnections* method), 539, 1274, 2012, 2762
- `create_sxp_local_bindings()` (*SxpLocalBindings* method), 547, 1282, 2020, 2770
- `create_sxp_vpn()` (*SxpVpns* method), 553, 1289, 2027, 2777
- `create_system_certificate()` (*SystemCertificate* method), 668, 1403, 2141, 2897
- `create_tacacs_command_sets()` (*TacacsCommandSets* method), 674, 1409, 2147, 2903
- `create_tacacs_external_servers()` (*TacacsExternalServers* method), 680, 1415, 2153, 2909
- `create_tacacs_profile()` (*TacacsProfile* method), 686, 1421, 2159, 2915
- `create_tacacs_server_sequence()` (*TacacsServerSequence* method), 692, 1427, 2165, 2921
- `create_virtual_network()` (*VirtualNetwork* method), 739, 1477, 2215
- `create_vn_vlan_mapping()` (*VnVlanMapping* method), 746, 1484, 2222
- `CustomCaller` (class in *ciscoisesdk.api.custom_caller*), 36
- ## D
- `data` (*DownloadResponse* property), 2958
- `DataconnectServices` (class in *ciscoisesdk.api.v3_2_beta.dataconnect_services*), 2367
- `debug` (*IdentityServicesEngineAPI* property), 35
- `DEFAULT_BASE_URL` (in module *ciscoisesdk.config*), 13
- `DEFAULT_DEBUG` (in module *ciscoisesdk.config*), 13
- `DEFAULT_SINGLE_REQUEST_TIMEOUT` (in module *ciscoisesdk.config*), 13
- `DEFAULT_USES_API_GATEWAY` (in module *ciscoisesdk.config*), 13
- `DEFAULT_USES_CSRF_TOKEN` (in module *ciscoisesdk.config*), 13
- `DEFAULT_VERIFY` (in module *ciscoisesdk.config*), 13
- `DEFAULT_VERSION` (in module *ciscoisesdk.config*), 13
- `DEFAULT_WAIT_ON_RATE_LIMIT` (in module *ciscoisesdk.config*), 13
- `delete_active_directory_by_id()` (*ActiveDirectory* method), 65, 779, 1517, 2255

- `delete_all_sessions()` (*Misc method*), 364, 1087, 1825, 2574
- `delete_allowed_protocol_by_id()` (*AllowedProtocols method*), 86, 800, 1538, 2276
- `delete_anc_policy_by_id()` (*AncPolicy method*), 94, 808, 1546, 2284
- `delete_authorization_profile_by_id()` (*AuthorizationProfile method*), 107, 821, 1559, 2297
- `delete_by_id()` (*ActiveDirectory method*), 66, 780, 1518, 2256
- `delete_by_id()` (*AllowedProtocols method*), 87, 801, 1539, 2277
- `delete_by_id()` (*AncPolicy method*), 95, 809, 1547, 2285
- `delete_by_id()` (*AuthorizationProfile method*), 107, 821, 1559, 2297
- `delete_by_id()` (*ByodPortal method*), 121, 835, 1573, 2311
- `delete_by_id()` (*DeviceAdministrationAuthenticationRules method*), 176, 894, 1632, 2375
- `delete_by_id()` (*DeviceAdministrationAuthorizationExceptionRules method*), 181, 899, 1637, 2379
- `delete_by_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 185, 903, 1641, 2384
- `delete_by_id()` (*DeviceAdministrationAuthorizationRules method*), 189, 907, 1645, 2388
- `delete_by_id()` (*DeviceAdministrationConditions method*), 201, 919, 1657, 2400
- `delete_by_id()` (*DeviceAdministrationNetworkConditions method*), 207, 925, 1663, 2407
- `delete_by_id()` (*DeviceAdministrationPolicySet method*), 212, 930, 1668, 2412
- `delete_by_id()` (*DeviceAdministrationTimeDateConditions method*), 219, 937, 1675, 2419
- `delete_by_id()` (*DownloadableAcl method*), 222, 940, 1678, 2422
- `delete_by_id()` (*EgressMatrixCell method*), 229, 947, 1685, 2435
- `delete_by_id()` (*Endpoint method*), 708, 1443, 2181, 2937
- `delete_by_id()` (*EndpointIdentityGroup method*), 241, 959, 1697, 2446
- `delete_by_id()` (*ExternalRadiusServer method*), 250, 968, 1706, 2455
- `delete_by_id()` (*FilterPolicy method*), 256, 974, 1712, 2461
- `delete_by_id()` (*GuestSsid method*), 272, 990, 1728, 2477
- `delete_by_id()` (*GuestType method*), 280, 998, 1736, 2485
- `delete_by_id()` (*GuestUser method*), 296, 1014, 1752, 2501
- `delete_by_id()` (*HotspotPortal method*), 312, 1030, 1768, 2517
- `delete_by_id()` (*IdentitySequence method*), 343, 1061, 1799, 2548
- `delete_by_id()` (*InternalUser method*), 352, 1070, 1808, 2557
- `delete_by_id()` (*IpToSgtMapping method*), 320, 1038, 1776, 2525
- `delete_by_id()` (*IpToSgtMappingGroup method*), 329, 1047, 1785, 2534
- `delete_by_id()` (*MyDevicePortal method*), 379, 1102, 1840, 2589
- `delete_by_id()` (*NativeSupplicantProfile method*), 385, 1109, 1847, 2596
- `delete_by_id()` (*NbarApp method*), 719, 1454, 2192
- `delete_by_id()` (*NetworkAccessAuthenticationRules method*), 391, 1115, 1853, 2603
- `delete_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 396, 1120, 1858, 2607
- `delete_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 400, 1124, 1862, 2611
- `delete_by_id()` (*NetworkAccessAuthorizationRules method*), 405, 1129, 1867, 2616
- `delete_by_id()` (*NetworkAccessConditions method*), 415, 1139, 1877, 2627
- `delete_by_id()` (*NetworkAccessNetworkConditions method*), 430, 1154, 1892, 2642
- `delete_by_id()` (*NetworkAccessPolicySet method*), 435, 1159, 1897, 2647
- `delete_by_id()` (*NetworkAccessTimeDateConditions method*), 443, 1167, 1905, 2655
- `delete_by_id()` (*NetworkDevice method*), 453, 1178, 1916, 2666
- `delete_by_id()` (*NetworkDeviceGroup method*), 461, 1186, 1924, 2674
- `delete_by_id()` (*PortalTheme method*), 486, 1222, 1960, 2710
- `delete_by_id()` (*RadiusServerSequence method*), 513, 1249, 1987, 2737
- `delete_by_id()` (*RestidStore method*), 522, 1258, 1996, 2746
- `delete_by_id()` (*SecurityGroups method*), 566, 1302, 2040, 2790
- `delete_by_id()` (*SecurityGroupsAcls method*), 574, 1309, 2047, 2797
- `delete_by_id()` (*SecurityGroupToVirtualNetwork method*), 558, 1294, 2032, 2782
- `delete_by_id()` (*SelfRegisteredPortal method*), 603, 1338, 2076, 2826
- `delete_by_id()` (*SgVnMapping method*), 736, 1472, 2210
- `delete_by_id()` (*SponsoredGuestPortal method*), 651,

- 1386, 2124, 2874
- `delete_by_id()` (*SponsorGroup method*), 616, 1351, 2089, 2839
- `delete_by_id()` (*SponsorPortal method*), 633, 1368, 2106, 2856
- `delete_by_id()` (*SxpConnections method*), 537, 1272, 2010, 2760
- `delete_by_id()` (*SxpLocalBindings method*), 544, 1280, 2018, 2768
- `delete_by_id()` (*SxpVpns method*), 551, 1286, 2024, 2774
- `delete_by_id()` (*TacacsCommandSets method*), 673, 1408, 2146, 2902
- `delete_by_id()` (*TacacsExternalServers method*), 679, 1414, 2152, 2908
- `delete_by_id()` (*TacacsProfile method*), 685, 1420, 2158, 2914
- `delete_by_id()` (*TacacsServerSequence method*), 691, 1426, 2164, 2920
- `delete_by_id()` (*VirtualNetwork method*), 744, 1482, 2220
- `delete_by_name()` (*DeviceAdministrationConditions method*), 197, 915, 1653, 2396
- `delete_by_name()` (*GuestUser method*), 291, 1009, 1747, 2496
- `delete_by_name()` (*InternalUser method*), 350, 1068, 1806, 2555
- `delete_by_name()` (*NetworkAccessConditions method*), 412, 1136, 1874, 2623
- `delete_by_name()` (*NetworkAccessDictionary method*), 419, 1143, 1881, 2630
- `delete_by_name()` (*NetworkAccessDictionaryAttribute method*), 423, 1147, 1885, 2635
- `delete_by_name()` (*NetworkDevice method*), 451, 1176, 1914, 2663
- `delete_by_name()` (*PxGridNode method*), 727, 1463, 2201, 2952
- `delete_by_name()` (*Repository method*), 530, 1265, 2003, 2753
- `delete_by_name()` (*RestidStore method*), 520, 1256, 1994, 2744
- `delete_byod_portal_by_id()` (*ByodPortal method*), 121, 835, 1573, 2311
- `delete_connector_config_by_connector_name()` (*Edda method*), 2428
- `delete_csr_by_id()` (*Certificates method*), 147, 861, 1599, 2337
- `delete_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules method*), 176, 894, 1632, 2374
- `delete_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules method*), 189, 907, 1645, 2388
- `delete_device_admin_condition_by_id()` (*DeviceAdministrationConditions method*), 200, 918, 1656, 2399
- `delete_device_admin_condition_by_name()` (*DeviceAdministrationConditions method*), 197, 915, 1653, 2396
- `delete_device_admin_local_exception_rule_by_id()` (*DeviceAdministrationAuthorizationExceptionRules method*), 180, 898, 1636, 2379
- `delete_device_admin_network_condition_by_id()` (*DeviceAdministrationNetworkConditions method*), 207, 925, 1663, 2406
- `delete_device_admin_policy_set_by_id()` (*DeviceAdministrationPolicySet method*), 211, 929, 1667, 2411
- `delete_device_admin_policy_set_global_exception_by_rule_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 185, 903, 1641, 2383
- `delete_device_admin_time_condition_by_id()` (*DeviceAdministrationTimeDateConditions method*), 219, 937, 1675, 2419
- `delete_downloadable_acl_by_id()` (*DownloadableAcl method*), 222, 940, 1678, 2422
- `delete_egress_matrix_cell_by_id()` (*EgressMatrixCell method*), 229, 947, 1685, 2434
- `delete_endpoint_by_id()` (*Endpoint method*), 708, 1443, 2181, 2937
- `delete_endpoint_group_by_id()` (*EndpointIdentityGroup method*), 240, 958, 1696, 2445
- `delete_external_radius_server_by_id()` (*ExternalRadiusServer method*), 249, 967, 1705, 2454
- `delete_filter_policy_by_id()` (*FilterPolicy method*), 255, 973, 1711, 2460
- `delete_guest_ssid_by_id()` (*GuestSsid method*), 271, 989, 1727, 2476
- `delete_guest_type_by_id()` (*GuestType method*), 279, 997, 1735, 2484
- `delete_guest_user_by_id()` (*GuestUser method*), 295, 1013, 1751, 2500
- `delete_guest_user_by_name()` (*GuestUser method*), 290, 1008, 1746, 2495
- `delete_hotspot_portal_by_id()` (*HotspotPortal method*), 311, 1029, 1767, 2516
- `delete_identity_sequence_by_id()` (*IdentitySequence method*), 342, 1060, 1798, 2547
- `delete_internal_user_by_id()` (*InternalUser method*), 352, 1070, 1808, 2557
- `delete_internal_user_by_name()` (*InternalUser method*), 349, 1067, 1805, 2554
- `delete_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping method*), 319, 1037, 1775, 2524
- `delete_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup method*), 328, 1046, 1784, 2533

`delete_my_device_portal_by_id()` (*MyDevicePortal* method), 378, 1101, 1839, 2588
`delete_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile* method), 385, 1109, 1847, 2596
`delete_nbar_app_by_id()` (*NbarApp* method), 719, 1454, 2192
`delete_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules* method), 391, 1115, 1853, 2602
`delete_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules* method), 404, 1128, 1866, 2615
`delete_network_access_condition_by_id()` (*NetworkAccessConditions* method), 415, 1139, 1877, 2626
`delete_network_access_condition_by_name()` (*NetworkAccessConditions* method), 411, 1135, 1873, 2622
`delete_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute* method), 423, 1147, 1885, 2634
`delete_network_access_dictionary_by_name()` (*NetworkAccessDictionary* method), 418, 1142, 1880, 2630
`delete_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules* method), 395, 1119, 1857, 2606
`delete_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions* method), 429, 1154, 1892, 2641
`delete_network_access_policy_set_by_id()` (*NetworkAccessPolicySet* method), 434, 1159, 1897, 2646
`delete_network_access_policy_set_global_exception_rule_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 400, 1124, 1862, 2611
`delete_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions* method), 442, 1167, 1905, 2655
`delete_network_device_by_id()` (*NetworkDevice* method), 453, 1178, 1916, 2665
`delete_network_device_by_name()` (*NetworkDevice* method), 450, 1175, 1913, 2663
`delete_network_device_group_by_id()` (*NetworkDeviceGroup* method), 461, 1186, 1924, 2674
`delete_node()` (*NodeDeployment* method), 468, 1193, 1931, 2681
`delete_node_group()` (*NodeGroup* method), 471, 1199, 1937, 2687
`delete_portal_theme_by_id()` (*PortalTheme* method), 486, 1222, 1960, 2710
`delete_px_grid_node_by_name()` (*PxGridNode* method), 726, 1463, 2201, 2952
`delete_radius_server_sequence_by_id()` (*RadiusServerSequence* method), 513, 1249, 1987, 2737
`delete_repository()` (*Repository* method), 529, 1265, 2003, 2753
`delete_rest_id_store_by_id()` (*RestidStore* method), 522, 1258, 1996, 2746
`delete_rest_id_store_by_name()` (*RestidStore* method), 520, 1256, 1994, 2744
`delete_security_group_by_id()` (*SecurityGroups* method), 566, 1301, 2039, 2789
`delete_security_groups_acl_by_id()` (*SecurityGroupsAcls* method), 574, 1309, 2047, 2797
`delete_security_groups_to_vn_to_vlan_by_id()` (*SecurityGroupToVirtualNetwork* method), 558, 1293, 2031, 2781
`delete_self_registered_portal_by_id()` (*SelfRegisteredPortal* method), 603, 1338, 2076, 2826
`delete_sg_vn_mapping_by_id()` (*SgVnMapping* method), 735, 1472, 2210
`delete_sponsor_group_by_id()` (*SponsorGroup* method), 616, 1351, 2089, 2839
`delete_sponsor_portal_by_id()` (*SponsorPortal* method), 633, 1368, 2106, 2856
`delete_sponsored_guest_portal_by_id()` (*SponsoredGuestPortal* method), 651, 1386, 2124, 2874
`delete_subscriber()` (*Subscriber* method), 2883
`delete_sxp_connections_by_id()` (*SxpConnections* method), 536, 1272, 2010, 2760
`delete_sxp_local_bindings_by_id()` (*SxpLocalBindings* method), 544, 1279, 2017, 2767
`delete_sxp_vpn_by_id()` (*SxpVpns* method), 551, 1286, 2024, 2774
`delete_system_certificate_by_id()` (*Certificates* method), 158, 876, 1614, 2352
`delete_tacacs_command_sets_by_id()` (*TacacsCommandSets* method), 672, 1407, 2145, 2901
`delete_tacacs_external_servers_by_id()` (*TacacsExternalServers* method), 678, 1413, 2151, 2907
`delete_tacacs_profile_by_id()` (*TacacsProfile* method), 684, 1419, 2157, 2913
`delete_tacacs_server_sequence_by_id()` (*TacacsServerSequence* method), 691, 1426, 2164, 2920
`delete_trusted_certificate_by_id()` (*Certificates* method), 167, 885, 1623, 2361
`delete_virtual_network_by_id()` (*VirtualNetwork* method), 743, 1481, 2219

`delete_vn_vlan_mapping_by_id()` (*VnVlanMapping* method), 750, 1488, 2226
`deny_by_id()` (*GuestUser* method), 294, 1012, 1750, 2499
`deny_guest_user_by_id()` (*GuestUser* method), 293, 1011, 1749, 2498
`deploy_all()` (*IpToSgtMapping* method), 317, 1035, 1773, 2522
`deploy_all_ip_to_sgt_mapping()` (*IpToSgtMapping* method), 316, 1034, 1772, 2521
`deploy_all_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup* method), 326, 1044, 1782, 2531
`deploy_by_id()` (*IpToSgtMapping* method), 316, 1034, 1772, 2521
`deploy_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping* method), 316, 1034, 1772, 2521
`deploy_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup* method), 325, 1043, 1781, 2530
`deregister()` (*Endpoint* method), 705, 1440, 2178, 2934
`deregister_endpoint()` (*Endpoint* method), 704, 1439, 2177, 2933
`description` (*ApiError* attribute), 2959
`details` (*ApiError* attribute), 2959
`details_str` (*ApiError* attribute), 2959
DeviceAdministrationAuthenticationRules
(class in *ciscoisesdk.api.v3_1_0.device_administration_authentication_rules*), 172
DeviceAdministrationAuthenticationRules
(class in *ciscoisesdk.api.v3_1_1.device_administration_authentication_rules*), 890
DeviceAdministrationAuthenticationRules
(class in *ciscoisesdk.api.v3_1_patch_1.device_administration_authentication_rules*), 1628
DeviceAdministrationAuthenticationRules
(class in *ciscoisesdk.api.v3_2_beta.device_administration_authentication_rules*), 2370
DeviceAdministrationAuthorizationExceptionRules
(class in *ciscoisesdk.api.v3_1_0.device_administration_authorization_exception_rules*), 177
DeviceAdministrationAuthorizationExceptionRules
(class in *ciscoisesdk.api.v3_1_1.device_administration_authorization_exception_rules*), 895
DeviceAdministrationAuthorizationExceptionRules
(class in *ciscoisesdk.api.v3_1_patch_1.device_administration_authorization_exception_rules*), 1646
1633
DeviceAdministrationAuthorizationExceptionRules
(class in *ciscoisesdk.api.v3_2_beta.device_administration_authorization_exception_rules*), 2375
DeviceAdministrationAuthorizationGlobalExceptionRules
(class in *ciscoisesdk.api.v3_1_0.device_administration_authorization_global_exception_rules*), 181
DeviceAdministrationAuthorizationGlobalExceptionRules
(class in *ciscoisesdk.api.v3_1_1.device_administration_authorization_global_exception_rules*), 899
DeviceAdministrationAuthorizationGlobalExceptionRules
(class in *ciscoisesdk.api.v3_1_patch_1.device_administration_authorization_global_exception_rules*), 1637
DeviceAdministrationAuthorizationGlobalExceptionRules
(class in *ciscoisesdk.api.v3_2_beta.device_administration_authorization_global_exception_rules*), 2380
DeviceAdministrationAuthorizationRules
(class in *ciscoisesdk.api.v3_1_0.device_administration_authorization_rules*), 185
DeviceAdministrationAuthorizationRules
(class in *ciscoisesdk.api.v3_1_1.device_administration_authorization_rules*), 903
DeviceAdministrationAuthorizationRules
(class in *ciscoisesdk.api.v3_1_patch_1.device_administration_authorization_rules*), 1641
DeviceAdministrationAuthorizationRules
(class in *ciscoisesdk.api.v3_2_beta.device_administration_authorization_rules*), 2384
DeviceAdministrationCommandSet (class in *ciscoisesdk.api.v3_1_0.device_administration_command_set*), 190
DeviceAdministrationCommandSet (class in *ciscoisesdk.api.v3_1_1.device_administration_command_set*), 908
DeviceAdministrationCommandSet (class in *ciscoisesdk.api.v3_1_patch_1.device_administration_command_set*), 1646
DeviceAdministrationCommandSet (class in *ciscoisesdk.api.v3_2_beta.device_administration_command_set*), 2388
DeviceAdministrationConditions (class in *ciscoisesdk.api.v3_1_0.device_administration_conditions*), 190
DeviceAdministrationConditions (class in *ciscoisesdk.api.v3_1_patch_1.device_administration_conditions*), 1646

908	DeviceAdministrationConditions (class in ciscois-esdk.api.v3_1_patch_1.device_administration_conditions),	2403	DeviceAdministrationPolicySet (class in ciscois-esdk.api.v3_1_0.device_administration_policy_set),
1646		207	
DeviceAdministrationConditions (class in ciscois-esdk.api.v3_2_beta.device_administration_conditions),		DeviceAdministrationPolicySet (class in ciscois-esdk.api.v3_1_1.device_administration_policy_set),	
2389		925	
DeviceAdministrationDictionaryAttributesList (class in ciscois-esdk.api.v3_1_0.device_administration_dictionary_attributes_list),		DeviceAdministrationPolicySet (class in ciscois-esdk.api.v3_1_patch_1.device_administration_policy_set),	
201		DeviceAdministrationPolicySet (class in ciscois-esdk.api.v3_2_beta.device_administration_policy_set),	
DeviceAdministrationDictionaryAttributesList (class in ciscois-esdk.api.v3_1_1.device_administration_dictionary_attributes_list),		2407	
919		DeviceAdministrationProfiles (class in ciscois-esdk.api.v3_1_0.device_administration_profiles),	
DeviceAdministrationDictionaryAttributesList (class in ciscois-esdk.api.v3_1_patch_1.device_administration_dictionary_attributes_list),		212	
1657		DeviceAdministrationProfiles (class in ciscois-esdk.api.v3_1_1.device_administration_profiles),	
DeviceAdministrationDictionaryAttributesList (class in ciscois-esdk.api.v3_2_beta.device_administration_dictionary_attributes_list),		930	
2400		DeviceAdministrationProfiles (class in ciscois-esdk.api.v3_1_patch_1.device_administration_profiles),	
DeviceAdministrationIdentityStores (class in ciscois-esdk.api.v3_1_0.device_administration_identity_stores),		DeviceAdministrationProfiles (class in ciscois-esdk.api.v3_2_beta.device_administration_profiles),	
203		2412	
DeviceAdministrationIdentityStores (class in ciscois-esdk.api.v3_1_1.device_administration_identity_stores),		DeviceAdministrationServiceNames (class in ciscois-esdk.api.v3_1_0.device_administration_service_names),	
921		213	
DeviceAdministrationIdentityStores (class in ciscois-esdk.api.v3_1_patch_1.device_administration_identity_stores),		DeviceAdministrationServiceNames (class in ciscois-esdk.api.v3_1_1.device_administration_service_names),	
1659		931	
DeviceAdministrationIdentityStores (class in ciscois-esdk.api.v3_2_beta.device_administration_identity_stores),		DeviceAdministrationServiceNames (class in ciscois-esdk.api.v3_1_patch_1.device_administration_service_names),	
2402		1669	
DeviceAdministrationNetworkConditions (class in ciscois-esdk.api.v3_1_0.device_administration_network_conditions),		DeviceAdministrationServiceNames (class in ciscois-esdk.api.v3_2_beta.device_administration_service_names),	
204		2413	
DeviceAdministrationNetworkConditions (class in ciscois-esdk.api.v3_1_1.device_administration_network_conditions),		DeviceAdministrationTimeDateConditions (class in ciscois-esdk.api.v3_1_0.device_administration_time_date_conditions),	
922		214	
DeviceAdministrationNetworkConditions (class in ciscois-esdk.api.v3_1_patch_1.device_administration_network_conditions),		DeviceAdministrationTimeDateConditions (class in ciscois-esdk.api.v3_1_1.device_administration_time_date_conditions),	
1660		932	
DeviceAdministrationNetworkConditions (class in ciscois-esdk.api.v3_2_beta.device_administration_network_conditions),		DeviceAdministrationTimeDateConditions (class in ciscois-esdk.api.v3_1_patch_1.device_administration_time_date_conditions),	
		1670	
		DeviceAdministrationTimeDateConditions	

(class in *ciscoisesdk.api.v3_2_beta.device_administration_time_date_conditions*), 2414

dirpath (*DownloadResponse* property), 2958

disable_pan_ha() (*PanHa* method), 478

download() (*SupportBundleDownload* method), 656, 1391, 2129, 2885

download_support_bundle() (*SupportBundleDownload* method), 656, 1391, 2129, 2885

DownloadableAcl (class in *ciscoisesdk.api.v3_1_0.downloadable_acl*), 219

DownloadableAcl (class in *ciscoisesdk.api.v3_1_1.downloadable_acl*), 937

DownloadableAcl (class in *ciscoisesdk.api.v3_1_patch_1.downloadable_acl*), 1675

DownloadableAcl (class in *ciscoisesdk.api.v3_2_beta.downloadable_acl*), 2420

DownloadFailure, 2960

DownloadResponse (class in *ciscoisesdk.restsession*), 2958

E

Edda (class in *ciscoisesdk.api.v3_2_beta.edda*), 2425

EgressMatrixCell (class in *ciscoisesdk.api.v3_1_0.egress_matrix_cell*), 225

EgressMatrixCell (class in *ciscoisesdk.api.v3_1_1.egress_matrix_cell*), 943

EgressMatrixCell (class in *ciscoisesdk.api.v3_1_patch_1.egress_matrix_cell*), 1681

EgressMatrixCell (class in *ciscoisesdk.api.v3_2_beta.egress_matrix_cell*), 2430

enable_pan_ha() (*PanHa* method), 478

Endpoint (class in *ciscoisesdk.api.v3_1_0.endpoint*), 703

Endpoint (class in *ciscoisesdk.api.v3_1_1.endpoint*), 1438

Endpoint (class in *ciscoisesdk.api.v3_1_patch_1.endpoint*), 2176

Endpoint (class in *ciscoisesdk.api.v3_2_beta.endpoint*), 2932

EndpointCertificate (class in *ciscoisesdk.api.v3_1_0.endpoint_certificate*), 235

EndpointCertificate (class in *ciscoisesdk.api.v3_1_1.endpoint_certificate*), 953

EndpointCertificate (class in *ciscoisesdk.api.v3_1_patch_1.endpoint_certificate*), 1691

EndpointCertificate (class in *ciscoisesdk.api.v3_2_beta.endpoint_certificate*), 2440

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_1_0.endpoint_identity_group*), 238

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_1_1.endpoint_identity_group*), 956

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_1_patch_1.endpoint_identity_group*), 1694

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_2_beta.endpoint_identity_group*), 2443

ers_base_url (*IdentityServicesEngineAPI* property), 34

export_csr() (*Certificates* method), 145, 859, 1597, 2335

export_system_certificate() (*Certificates* method), 151, 865, 1603, 2341

export_trusted_certificate() (*Certificates* method), 161, 878, 1616, 2354

ExternalRadiusServer (class in *ciscoisesdk.api.v3_1_0.external_radius_server*), 244

ExternalRadiusServer (class in *ciscoisesdk.api.v3_1_1.external_radius_server*), 962

ExternalRadiusServer (class in *ciscoisesdk.api.v3_1_patch_1.external_radius_server*), 1700

ExternalRadiusServer (class in *ciscoisesdk.api.v3_2_beta.external_radius_server*), 2449

F

filename (*DownloadResponse* property), 2958

FilterPolicy (class in *ciscoisesdk.api.v3_1_0.filter_policy*), 253

FilterPolicy (class in *ciscoisesdk.api.v3_1_1.filter_policy*), 971

FilterPolicy (class in *ciscoisesdk.api.v3_1_patch_1.filter_policy*), 1709

FilterPolicy (class in *ciscoisesdk.api.v3_2_beta.filter_policy*), 2458

G

generate_csr() (*Certificates* method), 143, 857, 1595, 2333

generate_intermediate_ca_csr() (*Certificates* method), 146, 860, 1598, 2336

generate_self_signed_certificate() (*Certificates* method), 866, 1604, 2342

get() (*MyDict* method), 2958

get_account_status_by_mac() (*Misc* method), 367, 1091, 1829, 2578

`get_aci_bindings()` (*AciBindings method*), 38, 752, 1490, 2228
`get_aci_bindings_generator()` (*AciBindings method*), 39, 753, 1491, 2229
`get_aci_settings()` (*AciSettings method*), 41, 755, 1493, 2231
`get_active_count()` (*Misc method*), 359, 1082, 1820, 2569
`get_active_directory()` (*ActiveDirectory method*), 66, 780, 1518, 2256
`get_active_directory_by_id()` (*ActiveDirectory method*), 65, 779, 1517, 2255
`get_active_directory_by_name()` (*ActiveDirectory method*), 59, 773, 1511, 2249
`get_active_directory_generator()` (*ActiveDirectory method*), 67, 781, 1519, 2257
`get_active_list()` (*Misc method*), 359, 1083, 1821, 2570
`get_admin_user_by_id()` (*AdminUser method*), 70, 784, 1522, 2260
`get_admin_users()` (*AdminUser method*), 71, 785, 1523, 2261
`get_admin_users_generator()` (*AdminUser method*), 72, 786, 1524, 2262
`get_all()` (*AciBindings method*), 39, 753, 1491, 2229
`get_all()` (*AciSettings method*), 42, 756, 1494, 2232
`get_all()` (*ActiveDirectory method*), 67, 781, 1519, 2257
`get_all()` (*AdminUser method*), 72, 786, 1524, 2262
`get_all()` (*AllowedProtocols method*), 88, 802, 1540, 2278
`get_all()` (*AncEndpoint method*), 48, 762, 1500, 2238
`get_all()` (*AncPolicy method*), 96, 810, 1548, 2286
`get_all()` (*AuthorizationProfile method*), 108, 822, 1560, 2298
`get_all()` (*ByodPortal method*), 122, 836, 1574, 2312
`get_all()` (*CertificateProfile method*), 135, 849, 1587, 2325
`get_all()` (*CertificateTemplate method*), 140, 854, 1592, 2330
`get_all()` (*DeviceAdministrationAuthenticationRules method*), 172, 890, 1628, 2371
`get_all()` (*DeviceAdministrationAuthorizationExceptionRules method*), 177, 895, 1633, 2376
`get_all()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 182, 900, 1638, 2380
`get_all()` (*DeviceAdministrationAuthorizationRules method*), 186, 904, 1642, 2385
`get_all()` (*DeviceAdministrationCommandSet method*), 190, 908, 1646, 2389
`get_all()` (*DeviceAdministrationConditions method*), 191, 909, 1647, 2390
`get_all()` (*DeviceAdministrationIdentityStores method*), 203, 921, 1659, 2402
`get_all()` (*DeviceAdministrationNetworkConditions method*), 204, 922, 1660, 2403
`get_all()` (*DeviceAdministrationPolicySet method*), 208, 926, 1664, 2408
`get_all()` (*DeviceAdministrationProfiles method*), 213, 931, 1669, 2413
`get_all()` (*DeviceAdministrationServiceNames method*), 213, 931, 1669, 2413
`get_all()` (*DeviceAdministrationTimeDateConditions method*), 214, 932, 1670, 2414
`get_all()` (*DownloadableAcl method*), 223, 941, 1679, 2423
`get_all()` (*EgressMatrixCell method*), 230, 948, 1686, 2436
`get_all()` (*Endpoint method*), 711, 1446, 2184, 2940
`get_all()` (*EndpointIdentityGroup method*), 242, 960, 1698, 2447
`get_all()` (*ExternalRadiusServer method*), 250, 968, 1706, 2455
`get_all()` (*FilterPolicy method*), 256, 974, 1712, 2461
`get_all()` (*GuestLocation method*), 261, 979, 1717, 2466
`get_all()` (*GuestSntpNotificationConfiguration method*), 266, 984, 1722, 2471
`get_all()` (*GuestSsid method*), 272, 990, 1728, 2477
`get_all()` (*GuestType method*), 281, 999, 1737, 2486
`get_all()` (*GuestUser method*), 297, 1015, 1753, 2502
`get_all()` (*HotspotPortal method*), 312, 1030, 1768, 2517
`get_all()` (*IdentityGroups method*), 337, 1055, 1793, 2542
`get_all()` (*IdentitySequence method*), 344, 1062, 1800, 2549
`get_all()` (*InternalUser method*), 353, 1071, 1809, 2558
`get_all()` (*IpToSgtMapping method*), 321, 1039, 1777, 2526
`get_all()` (*IpToSgtMappingGroup method*), 330, 1048, 1786, 2535
`get_all()` (*Mdm method*), 357, 1080, 1818, 2567
`get_all()` (*MyDevicePortal method*), 379, 1103, 1841, 2590
`get_all()` (*NativeSupplicantProfile method*), 386, 1110, 1848, 2597
`get_all()` (*NbarApp method*), 716, 1451, 2189
`get_all()` (*NetworkAccessAuthenticationRules method*), 388, 1112, 1850, 2599
`get_all()` (*NetworkAccessAuthorizationExceptionRules method*), 392, 1116, 1854, 2603
`get_all()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 397, 1121, 1859, 2608
`get_all()` (*NetworkAccessAuthorizationRules method*), 401, 1125, 1863, 2612

`get_all()` (*NetworkAccessConditions* method), 405, 1129, 1867, 2617

`get_all()` (*NetworkAccessDictionary* method), 416, 1140, 1878, 2627

`get_all()` (*NetworkAccessDictionaryAttribute* method), 420, 1144, 1882, 2631

`get_all()` (*NetworkAccessIdentityStores* method), 426, 1150, 1888, 2637

`get_all()` (*NetworkAccessNetworkConditions* method), 427, 1151, 1889, 2638

`get_all()` (*NetworkAccessPolicySet* method), 430, 1155, 1893, 2643

`get_all()` (*NetworkAccessProfiles* method), 435, 1160, 1898, 2648

`get_all()` (*NetworkAccessSecurityGroups* method), 436, 1161, 1899, 2648

`get_all()` (*NetworkAccessServiceNames* method), 437, 1162, 1900, 2649

`get_all()` (*NetworkAccessTimeDateConditions* method), 437, 1162, 1900, 2650

`get_all()` (*NetworkDevice* method), 454, 1179, 1917, 2667

`get_all()` (*NetworkDeviceGroup* method), 462, 1187, 1925, 2675

`get_all()` (*NodeDeployment* method), 467, 1192, 1930, 2680

`get_all()` (*NodeDetails* method), 475, 1208, 1946, 2696

`get_all()` (*Portal* method), 722, 1457, 2195, 2946

`get_all()` (*PortalGlobalSetting* method), 482, 1218, 1956, 2706

`get_all()` (*PortalTheme* method), 487, 1223, 1961, 2711

`get_all()` (*ProfilerProfile* method), 493, 1229, 1967, 2717

`get_all()` (*PsnNodeDetailsWithRadiusService* method), 499, 1235, 1973, 2723

`get_all()` (*PullDeploymentInfo* method), 505, 1241, 1979, 2729

`get_all()` (*PxGridNode* method), 728, 1464, 2202, 2954

`get_all()` (*RadiusServerSequence* method), 514, 1250, 1988, 2738

`get_all()` (*Repository* method), 527, 1262, 2000, 2750

`get_all()` (*RestidStore* method), 523, 1259, 1997, 2747

`get_all()` (*SecurityGroups* method), 567, 1303, 2041, 2791

`get_all()` (*SecurityGroupsAcls* method), 575, 1310, 2048, 2798

`get_all()` (*SecurityGroupToVirtualNetwork* method), 559, 1295, 2033, 2783

`get_all()` (*SelfRegisteredPortal* method), 604, 1339, 2077, 2827

`get_all()` (*SgVnMapping* method), 730, 1466, 2204

`get_all()` (*SmsProvider* method), 532, 1268, 2006, 2756

`get_all()` (*SponsoredGuestPortal* method), 652, 1387, 2125, 2875

`get_all()` (*SponsorGroup* method), 617, 1352, 2090, 2840

`get_all()` (*SponsorGroupMember* method), 621, 1356, 2094, 2844

`get_all()` (*SponsorPortal* method), 634, 1369, 2107, 2857

`get_all()` (*SupportBundleStatus* method), 659, 1394, 2132, 2888

`get_all()` (*SxpConnections* method), 538, 1273, 2011, 2761

`get_all()` (*SxpLocalBindings* method), 545, 1281, 2019, 2769

`get_all()` (*SxpVpns* method), 552, 1287, 2025, 2775

`get_all()` (*TacacsCommandSets* method), 673, 1408, 2146, 2902

`get_all()` (*TacacsExternalServers* method), 679, 1414, 2152, 2908

`get_all()` (*TacacsProfile* method), 685, 1420, 2158, 2914

`get_all()` (*TacacsServerSequence* method), 692, 1427, 2165, 2921

`get_all()` (*TelemetryInformation* method), 696, 1431, 2169, 2925

`get_all()` (*TrustSecConfiguration* method), 699, 1434, 2172, 2928

`get_all()` (*VersionAndPatch* method), 702, 1437, 2175, 2931

`get_all()` (*VirtualNetwork* method), 738, 1476, 2214

`get_all()` (*VnVlanMapping* method), 745, 1483, 2221

`get_all_authentication()` (*DeviceAdministrationDictionaryAttributesList* method), 201, 919, 1657, 2401

`get_all_authentication()` (*NetworkAccessDictionaryAttributesList* method), 424, 1148, 1886, 2636

`get_all_authentication_rules()` (*DeviceAdministrationConditions* method), 194, 912, 1650, 2392

`get_all_authorization()` (*DeviceAdministrationDictionaryAttributesList* method), 202, 920, 1658, 2401

`get_all_authorization()` (*NetworkAccessDictionaryAttributesList* method), 425, 1149, 1887, 2636

`get_all_authorization_rules()` (*DeviceAdministrationConditions* method), 194, 912, 1650, 2393

`get_all_for_policy_sets()` (*DeviceAdministrationConditions* method), 198, 916, 1654, 2397

`get_all_for_policy_sets()` (*NetworkAccessConditions* method), 412, 1136, 1874, 2624

[get_all_generator\(\)](#) (*AciBindings method*), 40, 754, 1492, 2230
[get_all_generator\(\)](#) (*ActiveDirectory method*), 67, 781, 1519, 2257
[get_all_generator\(\)](#) (*AdminUser method*), 73, 787, 1525, 2263
[get_all_generator\(\)](#) (*AllowedProtocols method*), 88, 802, 1540, 2278
[get_all_generator\(\)](#) (*AncEndpoint method*), 49, 763, 1501, 2239
[get_all_generator\(\)](#) (*AncPolicy method*), 97, 811, 1549, 2287
[get_all_generator\(\)](#) (*AuthorizationProfile method*), 108, 822, 1560, 2298
[get_all_generator\(\)](#) (*ByodPortal method*), 123, 837, 1575, 2313
[get_all_generator\(\)](#) (*CertificateProfile method*), 136, 850, 1588, 2326
[get_all_generator\(\)](#) (*CertificateTemplate method*), 141, 855, 1593, 2331
[get_all_generator\(\)](#) (*DownloadableAcl method*), 223, 941, 1679, 2424
[get_all_generator\(\)](#) (*EgressMatrixCell method*), 231, 949, 1687, 2437
[get_all_generator\(\)](#) (*Endpoint method*), 712, 1447, 2185, 2941
[get_all_generator\(\)](#) (*EndpointIdentityGroup method*), 243, 961, 1699, 2448
[get_all_generator\(\)](#) (*ExternalRadiusServer method*), 251, 969, 1707, 2456
[get_all_generator\(\)](#) (*FilterPolicy method*), 257, 975, 1713, 2462
[get_all_generator\(\)](#) (*GuestLocation method*), 262, 980, 1718, 2467
[get_all_generator\(\)](#) (*GuestSmtptNotificationConfiguration method*), 267, 985, 1723, 2472
[get_all_generator\(\)](#) (*GuestSsid method*), 274, 992, 1730, 2479
[get_all_generator\(\)](#) (*GuestType method*), 282, 1000, 1738, 2487
[get_all_generator\(\)](#) (*GuestUser method*), 298, 1016, 1754, 2503
[get_all_generator\(\)](#) (*HotspotPortal method*), 314, 1032, 1770, 2519
[get_all_generator\(\)](#) (*IdentityGroups method*), 338, 1056, 1794, 2543
[get_all_generator\(\)](#) (*IdentitySequence method*), 344, 1062, 1800, 2549
[get_all_generator\(\)](#) (*InternalUser method*), 354, 1072, 1810, 2559
[get_all_generator\(\)](#) (*IpToSgtMapping method*), 322, 1040, 1778, 2527
[get_all_generator\(\)](#) (*IpToSgtMappingGroup method*), 331, 1049, 1787, 2536
[get_all_generator\(\)](#) (*MyDevicePortal method*), 381, 1104, 1842, 2591
[get_all_generator\(\)](#) (*NativeSupplicantProfile method*), 386, 1110, 1848, 2597
[get_all_generator\(\)](#) (*NbarApp method*), 717, 1452, 2190
[get_all_generator\(\)](#) (*NetworkDevice method*), 455, 1180, 1918, 2668
[get_all_generator\(\)](#) (*NetworkDeviceGroup method*), 463, 1188, 1926, 2676
[get_all_generator\(\)](#) (*NodeDetails method*), 476, 1209, 1947, 2697
[get_all_generator\(\)](#) (*Portal method*), 723, 1458, 2196, 2947
[get_all_generator\(\)](#) (*PortalGlobalSetting method*), 483, 1219, 1957, 2707
[get_all_generator\(\)](#) (*PortalTheme method*), 488, 1224, 1962, 2712
[get_all_generator\(\)](#) (*ProfilerProfile method*), 494, 1230, 1968, 2718
[get_all_generator\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 500, 1236, 1974, 2724
[get_all_generator\(\)](#) (*PxGridNode method*), 728, 1465, 2203, 2954
[get_all_generator\(\)](#) (*RadiusServerSequence method*), 514, 1250, 1988, 2738
[get_all_generator\(\)](#) (*RestidStore method*), 524, 1260, 1998, 2748
[get_all_generator\(\)](#) (*SecurityGroups method*), 568, 1304, 2042, 2792
[get_all_generator\(\)](#) (*SecurityGroupsAcls method*), 576, 1312, 2050, 2800
[get_all_generator\(\)](#) (*SecurityGroupToVirtualNetwork method*), 560, 1296, 2034, 2784
[get_all_generator\(\)](#) (*SelfRegisteredPortal method*), 605, 1340, 2078, 2828
[get_all_generator\(\)](#) (*SgVnMapping method*), 731, 1467, 2205
[get_all_generator\(\)](#) (*SmsProvider method*), 533, 1269, 2007, 2757
[get_all_generator\(\)](#) (*SponsoredGuestPortal method*), 653, 1388, 2126, 2876
[get_all_generator\(\)](#) (*SponsorGroup method*), 618, 1353, 2091, 2841
[get_all_generator\(\)](#) (*SponsorGroupMember method*), 622, 1357, 2095, 2845
[get_all_generator\(\)](#) (*SponsorPortal method*), 636, 1371, 2109, 2859
[get_all_generator\(\)](#) (*SupportBundleStatus method*), 660, 1395, 2133, 2889
[get_all_generator\(\)](#) (*SxpConnections method*), 539, 1274, 2012, 2762
[get_all_generator\(\)](#) (*SxpLocalBindings method*), 546, 1282, 2020, 2770

`get_all_generator()` (*SxpVpns method*), 553, 1289, 2027, 2777
`get_all_generator()` (*TacacsCommandSets method*), 674, 1409, 2147, 2903
`get_all_generator()` (*TacacsExternalServers method*), 680, 1415, 2153, 2909
`get_all_generator()` (*TacacsProfile method*), 686, 1421, 2159, 2915
`get_all_generator()` (*TacacsServerSequence method*), 692, 1427, 2165, 2921
`get_all_generator()` (*TelemetryInformation method*), 697, 1432, 2170, 2926
`get_all_generator()` (*VirtualNetwork method*), 739, 1477, 2215
`get_all_generator()` (*VnVlanMapping method*), 746, 1484, 2222
`get_all_policy_set()` (*DeviceAdministrationDictionaryAttributesList method*), 203, 921, 1659, 2402
`get_all_policy_set()` (*NetworkAccessDictionaryAttributesList method*), 425, 1149, 1887, 2637
`get_all_subscribers()` (*Subscriber method*), 2878
`get_all_subscribers_generator()` (*Subscriber method*), 2879
`get_allowed_protocol_by_id()` (*AllowedProtocols method*), 84, 798, 1536, 2274
`get_allowed_protocol_by_name()` (*AllowedProtocols method*), 83, 797, 1535, 2273
`get_allowed_protocols()` (*AllowedProtocols method*), 87, 801, 1539, 2277
`get_allowed_protocols_generator()` (*AllowedProtocols method*), 88, 802, 1540, 2278
`get_anc_endpoint()` (*AncEndpoint method*), 47, 761, 1499, 2237
`get_anc_endpoint_by_id()` (*AncEndpoint method*), 46, 760, 1498, 2236
`get_anc_endpoint_generator()` (*AncEndpoint method*), 48, 762, 1500, 2238
`get_anc_policy()` (*AncPolicy method*), 95, 809, 1547, 2285
`get_anc_policy_by_id()` (*AncPolicy method*), 93, 807, 1545, 2283
`get_anc_policy_by_name()` (*AncPolicy method*), 92, 806, 1544, 2282
`get_anc_policy_generator()` (*AncPolicy method*), 96, 810, 1548, 2286
`get_authentication_status_by_mac()` (*Misc method*), 366, 1089, 1827, 2576
`get_authorization_profile_by_id()` (*AuthorizationProfile method*), 104, 818, 1556, 2294
`get_authorization_profile_by_name()` (*AuthorizationProfile method*), 103, 817, 1555, 2293
`get_authorization_profiles()` (*AuthorizationProfile method*), 107, 821, 1559, 2297
`get_authorization_profiles_generator()` (*AuthorizationProfile method*), 108, 822, 1560, 2298
`get_bindings()` (*TrustSecSxp method*), 701, 1436, 2174, 2930
`get_by_id()` (*ActiveDirectory method*), 65, 779, 1517, 2255
`get_by_id()` (*AdminUser method*), 71, 785, 1523, 2261
`get_by_id()` (*AllowedProtocols method*), 84, 798, 1536, 2274
`get_by_id()` (*AncEndpoint method*), 46, 760, 1498, 2236
`get_by_id()` (*AncPolicy method*), 93, 807, 1545, 2283
`get_by_id()` (*AuthorizationProfile method*), 105, 819, 1557, 2295
`get_by_id()` (*ByodPortal method*), 120, 834, 1572, 2310
`get_by_id()` (*CertificateProfile method*), 133, 847, 1585, 2323
`get_by_id()` (*CertificateTemplate method*), 140, 854, 1592, 2330
`get_by_id()` (*DeviceAdministrationAuthenticationRules method*), 175, 893, 1631, 2373
`get_by_id()` (*DeviceAdministrationAuthorizationExceptionRules method*), 179, 897, 1635, 2378
`get_by_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 184, 902, 1640, 2382
`get_by_id()` (*DeviceAdministrationAuthorizationRules method*), 188, 906, 1644, 2387
`get_by_id()` (*DeviceAdministrationConditions method*), 198, 916, 1654, 2397
`get_by_id()` (*DeviceAdministrationNetworkConditions method*), 206, 924, 1662, 2405
`get_by_id()` (*DeviceAdministrationPolicySet method*), 210, 928, 1666, 2410
`get_by_id()` (*DeviceAdministrationTimeDateConditions method*), 217, 935, 1673, 2417
`get_by_id()` (*DownloadableAcl method*), 221, 939, 1677, 2421
`get_by_id()` (*EgressMatrixCell method*), 228, 946, 1684, 2433
`get_by_id()` (*Endpoint method*), 707, 1442, 2180, 2936
`get_by_id()` (*EndpointIdentityGroup method*), 239, 957, 1695, 2444
`get_by_id()` (*ExternalRadiusServer method*), 248, 966, 1704, 2453
`get_by_id()` (*FilterPolicy method*), 254, 972, 1710, 2459
`get_by_id()` (*GuestLocation method*), 260, 978, 1716, 2465
`get_by_id()` (*GuestSmtptNotificationConfiguration method*), 264, 982, 1720, 2469

`get_by_id()` (*GuestSsid method*), 270, 988, 1726, 2475
`get_by_id()` (*GuestType method*), 278, 996, 1734, 2483
`get_by_id()` (*GuestUser method*), 294, 1012, 1750, 2499
`get_by_id()` (*HotspotPortal method*), 310, 1028, 1766, 2515
`get_by_id()` (*IdentityGroups method*), 335, 1053, 1791, 2540
`get_by_id()` (*IdentitySequence method*), 341, 1059, 1797, 2546
`get_by_id()` (*InternalUser method*), 350, 1068, 1806, 2555
`get_by_id()` (*IpToSgtMapping method*), 318, 1036, 1774, 2523
`get_by_id()` (*IpToSgtMappingGroup method*), 327, 1045, 1783, 2532
`get_by_id()` (*MyDevicePortal method*), 377, 1100, 1838, 2587
`get_by_id()` (*NativeSupplicantProfile method*), 384, 1108, 1846, 2595
`get_by_id()` (*NbarApp method*), 718, 1453, 2191
`get_by_id()` (*NetworkAccessAuthenticationRules method*), 390, 1114, 1852, 2601
`get_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 394, 1118, 1856, 2606
`get_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 399, 1123, 1861, 2610
`get_by_id()` (*NetworkAccessAuthorizationRules method*), 403, 1127, 1865, 2614
`get_by_id()` (*NetworkAccessConditions method*), 413, 1137, 1875, 2624
`get_by_id()` (*NetworkAccessNetworkConditions method*), 428, 1153, 1891, 2640
`get_by_id()` (*NetworkAccessPolicySet method*), 433, 1158, 1896, 2645
`get_by_id()` (*NetworkAccessTimeDateConditions method*), 440, 1165, 1903, 2653
`get_by_id()` (*NetworkDevice method*), 451, 1176, 1914, 2664
`get_by_id()` (*NetworkDeviceGroup method*), 460, 1185, 1923, 2673
`get_by_id()` (*NodeDetails method*), 474, 1207, 1945, 2695
`get_by_id()` (*Portal method*), 721, 1456, 2194, 2945
`get_by_id()` (*PortalGlobalSetting method*), 480, 1216, 1954, 2704
`get_by_id()` (*PortalTheme method*), 485, 1221, 1959, 2709
`get_by_id()` (*ProfilerProfile method*), 492, 1228, 1966, 2716
`get_by_id()` (*PsnNodeDetailsWithRadiusService method*), 499, 1235, 1973, 2723
`get_by_id()` (*PxGridNode method*), 727, 1464, 2202, 2953
`get_by_id()` (*RadiusServerSequence method*), 511, 1247, 1985, 2735
`get_by_id()` (*RestidStore method*), 521, 1257, 1995, 2745
`get_by_id()` (*SecurityGroups method*), 565, 1300, 2038, 2788
`get_by_id()` (*SecurityGroupsAcls method*), 573, 1308, 2046, 2796
`get_by_id()` (*SecurityGroupToVirtualNetwork method*), 557, 1292, 2030, 2780
`get_by_id()` (*SelfRegisteredPortal method*), 602, 1337, 2075, 2825
`get_by_id()` (*SgVnMapping method*), 734, 1471, 2209
`get_by_id()` (*SponsoredGuestPortal method*), 650, 1385, 2123, 2873
`get_by_id()` (*SponsorGroup method*), 614, 1349, 2087, 2837
`get_by_id()` (*SponsorPortal method*), 632, 1367, 2105, 2855
`get_by_id()` (*SupportBundleStatus method*), 658, 1393, 2131, 2887
`get_by_id()` (*SxpConnections method*), 535, 1271, 2009, 2759
`get_by_id()` (*SxpLocalBindings method*), 543, 1278, 2016, 2766
`get_by_id()` (*SxpVpns method*), 551, 1286, 2024, 2774
`get_by_id()` (*TacacsCommandSets method*), 671, 1406, 2144, 2900
`get_by_id()` (*TacacsExternalServers method*), 677, 1412, 2150, 2906
`get_by_id()` (*TacacsProfile method*), 683, 1418, 2156, 2912
`get_by_id()` (*TacacsServerSequence method*), 689, 1424, 2162, 2918
`get_by_id()` (*TelemetryInformation method*), 695, 1430, 2168, 2924
`get_by_id()` (*VirtualNetwork method*), 742, 1480, 2218
`get_by_id()` (*VnVlanMapping method*), 749, 1487, 2225
`get_by_name()` (*ActiveDirectory method*), 59, 773, 1511, 2249
`get_by_name()` (*AllowedProtocols method*), 84, 798, 1536, 2274
`get_by_name()` (*AncPolicy method*), 93, 807, 1545, 2283
`get_by_name()` (*AuthorizationProfile method*), 104, 818, 1556, 2294
`get_by_name()` (*CertificateProfile method*), 133, 847, 1585, 2323
`get_by_name()` (*CertificateTemplate method*), 139, 853, 1591, 2329
`get_by_name()` (*DeviceAdministrationConditions method*), 195, 913, 1651, 2394

`get_by_name()` (*Endpoint method*), 706, 1441, 2179, 2935

`get_by_name()` (*EndpointIdentityGroup method*), 239, 957, 1695, 2444

`get_by_name()` (*ExternalRadiusServer method*), 247, 965, 1703, 2452

`get_by_name()` (*GuestUser method*), 289, 1007, 1745, 2494

`get_by_name()` (*IdentityGroups method*), 335, 1053, 1791, 2540

`get_by_name()` (*IdentitySequence method*), 341, 1059, 1797, 2546

`get_by_name()` (*InternalUser method*), 348, 1066, 1804, 2553

`get_by_name()` (*NetworkAccessConditions method*), 409, 1133, 1871, 2620

`get_by_name()` (*NetworkAccessDictionary method*), 417, 1141, 1879, 2629

`get_by_name()` (*NetworkAccessDictionaryAttribute method*), 421, 1145, 1883, 2633

`get_by_name()` (*NetworkDevice method*), 449, 1174, 1912, 2662

`get_by_name()` (*NetworkDeviceGroup method*), 459, 1184, 1922, 2672

`get_by_name()` (*NodeDetails method*), 474, 1207, 1945, 2694

`get_by_name()` (*PsnNodeDetailsWithRadiusService method*), 498, 1234, 1972, 2722

`get_by_name()` (*PxGridNode method*), 726, 1463, 2201, 2952

`get_by_name()` (*Repository method*), 528, 1264, 2002, 2752

`get_by_name()` (*RestidStore method*), 519, 1255, 1993, 2743

`get_by_name()` (*SessionDirectory method*), 610, 1345, 2083, 2833

`get_by_name()` (*TacacsCommandSets method*), 671, 1406, 2144, 2900

`get_by_name()` (*TacacsExternalServers method*), 676, 1411, 2149, 2905

`get_by_name()` (*TacacsProfile method*), 683, 1418, 2156, 2912

`get_by_name()` (*TacacsServerSequence method*), 689, 1424, 2162, 2918

`get_byod_portal()` (*ByodPortal method*), 121, 835, 1573, 2311

`get_byod_portal_by_id()` (*ByodPortal method*), 119, 833, 1571, 2309

`get_byod_portal_generator()` (*ByodPortal method*), 122, 836, 1574, 2312

`get_certificate_profile()` (*CertificateProfile method*), 135, 849, 1587, 2325

`get_certificate_profile_by_id()` (*CertificateProfile method*), 133, 847, 1585, 2323

`get_certificate_profile_by_name()` (*CertificateProfile method*), 132, 846, 1584, 2322

`get_certificate_profile_generator()` (*CertificateProfile method*), 135, 849, 1587, 2325

`get_certificate_template()` (*CertificateTemplate method*), 140, 854, 1592, 2330

`get_certificate_template_by_id()` (*CertificateTemplate method*), 139, 853, 1591, 2329

`get_certificate_template_by_name()` (*CertificateTemplate method*), 138, 852, 1590, 2328

`get_certificate_template_generator()` (*CertificateTemplate method*), 140, 854, 1592, 2330

`get_configuration()` (*Configuration method*), 2363

`get_connection_type()` (*Licensing method*), 1074, 1812, 2561

`get_connector_config()` (*Edda method*), 2425

`get_connector_config_by_connector_name()` (*Edda method*), 2427

`get_csr_by_id()` (*Certificates method*), 146, 860, 1598, 2336

`get_csrs()` (*Certificates method*), 142, 856, 1594, 2332

`get_csrs_generator()` (*Certificates method*), 143, 857, 1595, 2333

`get_dataconnect_service()` (*DataconnectServices method*), 2368

`get_deploy_status()` (*IpToSgtMapping method*), 317, 1035, 1773, 2522

`get_deploy_status_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 317, 1035, 1773, 2522

`get_deploy_status_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup method*), 326, 1044, 1782, 2531

`get_deployment_info()` (*PullDeploymentInfo method*), 505, 1241, 1979, 2729

`get_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules method*), 174, 892, 1630, 2373

`get_device_admin_authentication_rules()` (*DeviceAdministrationAuthenticationRules method*), 172, 890, 1628, 2370

`get_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules method*), 187, 905, 1643, 2386

`get_device_admin_authorization_rules()` (*DeviceAdministrationAuthorizationRules method*), 185, 903, 1641, 2384

`get_device_admin_command_sets()` (*DeviceAdministrationCommandSet method*), 190, 908, 1646, 2388

`get_device_admin_condition_by_id()` (*DeviceAdministrationConditions method*), 198, 916, 1654, 2397

`get_device_admin_condition_by_name()` (*De-*

viceAdministrationConditions method), 194, 912, 1650, 2393
 get_device_admin_conditions() (*DeviceAdministrationConditions* method), 190, 908, 1646, 2389
 get_device_admin_conditions_for_authentication_rules() (*DeviceAdministrationConditions* method), 193, 911, 1649, 2392
 get_device_admin_conditions_for_authorization_rules() (*DeviceAdministrationConditions* method), 194, 912, 1650, 2392
 get_device_admin_conditions_for_policy_sets() (*DeviceAdministrationConditions* method), 197, 915, 1653, 2396
 get_device_admin_dictionaries_authentication() (*DeviceAdministrationDictionaryAttributesList* method), 201, 919, 1657, 2400
 get_device_admin_dictionaries_authorization() (*DeviceAdministrationDictionaryAttributesList* method), 202, 920, 1658, 2401
 get_device_admin_dictionaries_policy_set() (*DeviceAdministrationDictionaryAttributesList* method), 202, 920, 1658, 2401
 get_device_admin_identity_stores() (*DeviceAdministrationIdentityStores* method), 203, 921, 1659, 2402
 get_device_admin_local_exception_rule_by_id() (*DeviceAdministrationAuthorizationExceptionRules* method), 179, 897, 1635, 2377
 get_device_admin_local_exception_rules() (*DeviceAdministrationAuthorizationExceptionRules* method), 177, 895, 1633, 2375
 get_device_admin_network_condition_by_id() (*DeviceAdministrationNetworkConditions* method), 205, 923, 1661, 2404
 get_device_admin_network_conditions() (*DeviceAdministrationNetworkConditions* method), 204, 922, 1660, 2403
 get_device_admin_policy_set_by_id() (*DeviceAdministrationPolicySet* method), 210, 928, 1666, 2410
 get_device_admin_policy_set_global_exception_rules_by_id() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 183, 901, 1639, 2382
 get_device_admin_policy_set_global_exception_rules() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 181, 899, 1637, 2380
 get_device_admin_policy_sets() (*DeviceAdministrationPolicySet* method), 207, 925, 1663, 2407
 get_device_admin_profiles() (*DeviceAdministrationProfiles* method), 212, 930, 1668, 2412
 get_device_admin_service_names() (*DeviceAdministrationServiceNames* method), 213, 931, 1669, 2413
 get_device_admin_time_condition_by_id() (*DeviceAdministrationTimeDateConditions* method), 216, 934, 1672, 2416
 get_device_admin_time_conditions() (*DeviceAdministrationTimeDateConditions* method), 214, 932, 1670, 2414
 get_downloadable_acl() (*DownloadableAcl* method), 222, 940, 1678, 2422
 get_downloadable_acl_by_id() (*DownloadableAcl* method), 220, 938, 1676, 2420
 get_downloadable_acl_generator() (*DownloadableAcl* method), 223, 941, 1679, 2423
 get_edda_dictionary_references() (*Edda* method), 2429
 get_egress_matrices() (*TrustSecConfiguration* method), 700, 1435, 2173, 2929
 get_egress_matrix_cell() (*EgressMatrixCell* method), 229, 947, 1685, 2435
 get_egress_matrix_cell_by_id() (*EgressMatrixCell* method), 227, 945, 1683, 2433
 get_egress_matrix_cell_generator() (*EgressMatrixCell* method), 230, 948, 1686, 2436
 get_egress_policies() (*TrustSecConfiguration* method), 699, 1434, 2172, 2928
 get_endpoint_by_id() (*Endpoint* method), 706, 1441, 2179, 2935
 get_endpoint_by_mac_address() (*Mdm* method), 357, 1080, 1818, 2567
 get_endpoint_by_name() (*Endpoint* method), 706, 1441, 2179, 2935
 get_endpoint_group_by_id() (*EndpointIdentityGroup* method), 239, 957, 1695, 2444
 get_endpoint_group_by_name() (*EndpointIdentityGroup* method), 238, 956, 1694, 2443
 get_endpoint_groups() (*EndpointIdentityGroup* method), 241, 959, 1697, 2446
 get_endpoint_groups_generator() (*EndpointIdentityGroup* method), 242, 960, 1698, 2447
 get_endpoints() (*Endpoint* method), 710, 1445, 2183, 2939
 get_endpoints_by_id() (*Mdm* method), 357, 1080, 1818, 2567
 get_endpoints_by_os_type() (*Mdm* method), 358, 1081, 1819, 2568
 get_endpoints_by_type() (*Mdm* method), 358, 1081, 1819, 2568
 get_endpoints_generator() (*Endpoint* method), 711, 1446, 2184, 2940
 get_eval_license_info() (*Licensing* method), 1075, 1813, 2562
 get_external_radius_server() (*ExternalRadiusServer* method), 250, 968, 1706, 2455
 get_external_radius_server_by_id() (*ExternalRadiusServer* method), 250, 968, 1706, 2455

`nalRadiusServer` method), 247, 965, 1703, 2452
`get_external_radius_server_by_name()` (*ExternalRadiusServer* method), 247, 965, 1703, 2452
`get_external_radius_server_generator()` (*ExternalRadiusServer* method), 250, 968, 1706, 2455
`get_failure_reasons()` (*Misc* method), 365, 1088, 1826, 2575
`get_failures()` (*RadiusFailure* method), 508, 1244, 1982, 2732
`get_feature_to_tier_mapping()` (*Licensing* method), 1075, 1813, 2562
`get_files()` (*Repository* method), 530, 1266, 2004, 2754
`get_filter_policy()` (*FilterPolicy* method), 256, 974, 1712, 2461
`get_filter_policy_by_id()` (*FilterPolicy* method), 254, 972, 1710, 2459
`get_filter_policy_generator()` (*FilterPolicy* method), 256, 974, 1712, 2461
`get_groups_by_domain()` (*ActiveDirectory* method), 64, 778, 1516, 2254
`get_guest_location()` (*GuestLocation* method), 260, 978, 1716, 2465
`get_guest_location_by_id()` (*GuestLocation* method), 259, 977, 1715, 2464
`get_guest_location_generator()` (*GuestLocation* method), 261, 979, 1717, 2466
`get_guest_smtp_notification_settings()` (*GuestSmtpNotificationConfiguration* method), 265, 983, 1721, 2470
`get_guest_smtp_notification_settings_by_id()` (*GuestSmtpNotificationConfiguration* method), 263, 981, 1719, 2468
`get_guest_smtp_notification_settings_generator()` (*GuestSmtpNotificationConfiguration* method), 266, 984, 1722, 2471
`get_guest_ssid()` (*GuestSsid* method), 272, 990, 1728, 2477
`get_guest_ssid_by_id()` (*GuestSsid* method), 270, 988, 1726, 2475
`get_guest_ssid_generator()` (*GuestSsid* method), 273, 991, 1729, 2478
`get_guest_type()` (*GuestType* method), 280, 998, 1736, 2485
`get_guest_type_by_id()` (*GuestType* method), 278, 996, 1734, 2483
`get_guest_type_generator()` (*GuestType* method), 281, 999, 1737, 2486
`get_guest_user_by_id()` (*GuestUser* method), 294, 1012, 1750, 2499
`get_guest_user_by_name()` (*GuestUser* method), 288, 1006, 1744, 2493
`get_guest_users()` (*GuestUser* method), 296, 1014, 1752, 2501
`get_guest_users_generator()` (*GuestUser* method), 297, 1015, 1753, 2502
`get_healths()` (*SystemHealth* method), 665, 1399, 2137, 2893
`get_hotspot_portal()` (*HotspotPortal* method), 312, 1030, 1768, 2517
`get_hotspot_portal_by_id()` (*HotspotPortal* method), 309, 1027, 1765, 2514
`get_hotspot_portal_generator()` (*HotspotPortal* method), 313, 1031, 1769, 2518
`get_identity_group_by_id()` (*IdentityGroups* method), 335, 1053, 1791, 2540
`get_identity_group_by_name()` (*IdentityGroups* method), 334, 1052, 1790, 2539
`get_identity_groups()` (*IdentityGroups* method), 336, 1054, 1792, 2541
`get_identity_groups_generator()` (*IdentityGroups* method), 337, 1055, 1793, 2542
`get_identity_sequence()` (*IdentitySequence* method), 343, 1061, 1799, 2548
`get_identity_sequence_by_id()` (*IdentitySequence* method), 341, 1059, 1797, 2546
`get_identity_sequence_by_name()` (*IdentitySequence* method), 340, 1058, 1796, 2545
`get_identity_sequence_generator()` (*IdentitySequence* method), 344, 1062, 1800, 2549
`get_interfaces()` (*NodeServices* method), 1202, 1940, 2689
`get_internal_user()` (*InternalUser* method), 352, 1070, 1808, 2557
`get_internal_user_by_id()` (*InternalUser* method), 350, 1068, 1806, 2555
`get_internal_user_by_name()` (*InternalUser* method), 347, 1065, 1803, 2552
`get_internal_user_generator()` (*InternalUser* method), 353, 1071, 1809, 2558
`get_ip_to_sgt_mapping()` (*IpToSgtMapping* method), 320, 1038, 1776, 2525
`get_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping* method), 318, 1036, 1774, 2523
`get_ip_to_sgt_mapping_generator()` (*IpToSgtMapping* method), 321, 1039, 1777, 2526
`get_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup* method), 329, 1047, 1785, 2534
`get_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup* method), 327, 1045, 1783, 2532
`get_ip_to_sgt_mapping_group_generator()` (*IpToSgtMappingGroup* method), 330, 1048, 1786, 2535
`get_ise_version_and_patch()` (*VersionAndPatch* method), 701, 1436, 2174, 2930

`get_last_config_backup_status()` (*BackupAndRestore method*), 126, 840, 1578, 2316
`get_last_status()` (*BackupAndRestore method*), 127, 841, 1579, 2317
`get_mnt_version()` (*Misc method*), 365, 1088, 1826, 2575
`get_my_device_portal()` (*MyDevicePortal method*), 379, 1102, 1840, 2589
`get_my_device_portal_by_id()` (*MyDevicePortal method*), 376, 1100, 1838, 2587
`get_my_device_portal_generator()` (*MyDevicePortal method*), 380, 1103, 1841, 2590
`get_native_suppllicant_profile()` (*NativeSuppllicantProfile method*), 385, 1109, 1847, 2596
`get_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile method*), 383, 1107, 1845, 2594
`get_native_suppllicant_profile_generator()` (*NativeSuppllicantProfile method*), 386, 1110, 1848, 2597
`get_nbar_app_by_id()` (*NbarApp method*), 718, 1453, 2191
`get_nbar_apps()` (*NbarApp method*), 715, 1450, 2188
`get_nbar_apps_generator()` (*NbarApp method*), 716, 1451, 2189
`get_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules method*), 389, 1113, 1851, 2600
`get_network_access_authentication_rules()` (*NetworkAccessAuthenticationRules method*), 387, 1111, 1849, 2598
`get_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules method*), 402, 1126, 1864, 2614
`get_network_access_authorization_rules()` (*NetworkAccessAuthorizationRules method*), 400, 1124, 1862, 2612
`get_network_access_condition_by_id()` (*NetworkAccessConditions method*), 412, 1136, 1874, 2624
`get_network_access_condition_by_name()` (*NetworkAccessConditions method*), 408, 1132, 1870, 2620
`get_network_access_conditions()` (*NetworkAccessConditions method*), 405, 1129, 1867, 2616
`get_network_access_conditions_for_authentication_rules()` (*NetworkAccessConditions method*), 407, 1131, 1869, 2619
`get_network_access_conditions_for_authorization_rules()` (*NetworkAccessConditions method*), 408, 1132, 1870, 2619
`get_network_access_conditions_for_policy_sets()` (*NetworkAccessConditions method*), 412, 1136, 1874, 2623
`get_network_access_dictionaries()` (*NetworkAccessDictionary method*), 415, 1139, 1877, 2627
`get_network_access_dictionaries_authentication()` (*NetworkAccessDictionaryAttributesList method*), 424, 1148, 1886, 2635
`get_network_access_dictionaries_authorization()` (*NetworkAccessDictionaryAttributesList method*), 424, 1148, 1886, 2636
`get_network_access_dictionaries_policy_set()` (*NetworkAccessDictionaryAttributesList method*), 425, 1149, 1887, 2636
`get_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute method*), 421, 1145, 1883, 2632
`get_network_access_dictionary_attributes_by_dictionary_name()` (*NetworkAccessDictionaryAttribute method*), 419, 1143, 1881, 2631
`get_network_access_dictionary_by_name()` (*NetworkAccessDictionary method*), 417, 1141, 1879, 2628
`get_network_access_identity_stores()` (*NetworkAccessIdentityStores method*), 425, 1149, 1887, 2637
`get_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 394, 1118, 1856, 2605
`get_network_access_local_exception_rules()` (*NetworkAccessAuthorizationExceptionRules method*), 392, 1116, 1854, 2603
`get_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions method*), 428, 1152, 1890, 2639
`get_network_access_network_conditions()` (*NetworkAccessNetworkConditions method*), 426, 1150, 1888, 2638
`get_network_access_policy_set_by_id()` (*NetworkAccessPolicySet method*), 432, 1157, 1895, 2645
`get_network_access_policy_set_global_exception_rule_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 398, 1122, 1860, 2609
`get_network_access_policy_set_global_exception_rules()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 396, 1120, 1858, 2607
`get_network_access_policy_sets()` (*NetworkAccessPolicySet method*), 430, 1155, 1893, 2642
`get_network_access_profiles()` (*NetworkAccessProfiles method*), 435, 1160, 1898, 2647
`get_network_access_security_groups()` (*NetworkAccessSecurityGroups method*), 435, 1160, 1898, 2648

`get_network_access_service_names()` (*NetworkAccessServiceNames method*), 436, 1161, 1899, 2649
`get_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions method*), 439, 1164, 1902, 2652
`get_network_access_time_conditions()` (*NetworkAccessTimeDateConditions method*), 437, 1162, 1900, 2649
`get_network_device()` (*NetworkDevice method*), 453, 1178, 1916, 2666
`get_network_device_by_id()` (*NetworkDevice method*), 451, 1176, 1914, 2663
`get_network_device_by_name()` (*NetworkDevice method*), 448, 1173, 1911, 2661
`get_network_device_generator()` (*NetworkDevice method*), 454, 1179, 1917, 2667
`get_network_device_group()` (*NetworkDeviceGroup method*), 461, 1186, 1924, 2674
`get_network_device_group_by_id()` (*NetworkDeviceGroup method*), 460, 1185, 1923, 2672
`get_network_device_group_by_name()` (*NetworkDeviceGroup method*), 459, 1184, 1922, 2672
`get_network_device_group_generator()` (*NetworkDeviceGroup method*), 462, 1187, 1925, 2675
`get_node_detail_by_id()` (*NodeDetails method*), 474, 1207, 1945, 2695
`get_node_detail_by_name()` (*NodeDetails method*), 473, 1206, 1944, 2694
`get_node_details()` (*NodeDeployment method*), 467, 1192, 1930, 2679
`get_node_details()` (*NodeDetails method*), 474, 1207, 1945, 2695
`get_node_details_generator()` (*NodeDetails method*), 475, 1208, 1946, 2696
`get_node_group()` (*NodeGroup method*), 469, 1197, 1935, 2685
`get_node_groups()` (*NodeGroup method*), 469, 1196, 1934, 2683
`get_node_replication_status()` (*ReplicationStatus method*), 526
`get_nodes()` (*NodeDeployment method*), 465, 1190, 1928, 2678
`get_nodes()` (*NodeGroup method*), 1200, 1938, 2688
`get_odbc_detail()` (*DataconnectServices method*), 2367
`get_pan_ha_status()` (*PanHa method*), 477, 1210, 1948, 2698
`get_performances()` (*SystemHealth method*), 665, 1400, 2138, 2894
`get_portal_by_id()` (*Portal method*), 720, 1455, 2193, 2944
`get_portal_global_setting_by_id()` (*PortalGlobalSetting method*), 480, 1216, 1954, 2704
`get_portal_global_settings()` (*PortalGlobalSetting method*), 481, 1217, 1955, 2705
`get_portal_global_settings_generator()` (*PortalGlobalSetting method*), 482, 1218, 1956, 2706
`get_portal_theme_by_id()` (*PortalTheme method*), 484, 1220, 1958, 2708
`get_portal_themes()` (*PortalTheme method*), 486, 1222, 1960, 2710
`get_portal_themes_generator()` (*PortalTheme method*), 487, 1223, 1961, 2711
`get_portals()` (*Portal method*), 721, 1456, 2194, 2945
`get_portals_generator()` (*Portal method*), 722, 1457, 2195, 2946
`get_posture_count()` (*Misc method*), 360, 1084, 1822, 2571
`get_profiler_count()` (*Misc method*), 361, 1084, 1822, 2571
`get_profiler_probe_config()` (*NodeServices method*), 1203, 1941, 2691
`get_profiler_profile_by_id()` (*ProfilerProfile method*), 491, 1227, 1965, 2715
`get_profiler_profiles()` (*ProfilerProfile method*), 492, 1228, 1966, 2716
`get_profiler_profiles_generator()` (*ProfilerProfile method*), 493, 1229, 1967, 2717
`get_profiles()` (*Profiler method*), 490, 1226, 1964, 2714
`get_proxy_connection()` (*Proxy method*), 1459, 2197, 2948
`get_px_grid_node()` (*PxGridNode method*), 727, 1464, 2202, 2953
`get_px_grid_node_by_id()` (*PxGridNode method*), 727, 1463, 2201, 2952
`get_px_grid_node_by_name()` (*PxGridNode method*), 725, 1462, 2200, 2951
`get_px_grid_node_generator()` (*PxGridNode method*), 728, 1464, 2202, 2954
`get_radius_server_sequence()` (*RadiusServerSequence method*), 513, 1249, 1987, 2737
`get_radius_server_sequence_by_id()` (*RadiusServerSequence method*), 511, 1247, 1985, 2735
`get_radius_server_sequence_generator()` (*RadiusServerSequence method*), 514, 1250, 1988, 2738
`get_registration_info()` (*Licensing method*), 1076, 1814, 2563
`get_rejected()` (*Endpoint method*), 706, 1441, 2179, 2935
`get_rejected_endpoints()` (*Endpoint method*), 705, 1440, 2178, 2934
`get_repositories()` (*Repository method*), 526, 1262,

2000, 2750

`get_repository()` (*Repository method*), 528, 1263, 2001, 2751

`get_repository_files()` (*Repository method*), 530, 1265, 2003, 2753

`get_rest_id_store()` (*RestidStore method*), 522, 1258, 1996, 2746

`get_rest_id_store_by_id()` (*RestidStore method*), 520, 1256, 1994, 2744

`get_rest_id_store_by_name()` (*RestidStore method*), 518, 1254, 1992, 2742

`get_rest_id_store_generator()` (*RestidStore method*), 523, 1259, 1997, 2747

`get_security_group_acls()` (*TrustSecConfiguration method*), 699, 1434, 2172, 2928

`get_security_group_by_id()` (*SecurityGroups method*), 564, 1300, 2038, 2788

`get_security_groups()` (*SecurityGroups method*), 566, 1302, 2040, 2790

`get_security_groups()` (*TrustSecConfiguration method*), 698, 1433, 2171, 2927

`get_security_groups_acl()` (*SecurityGroupsAcls method*), 574, 1310, 2048, 2798

`get_security_groups_acl_by_id()` (*SecurityGroupsAcls method*), 572, 1307, 2045, 2795

`get_security_groups_acl_generator()` (*SecurityGroupsAcls method*), 575, 1311, 2049, 2799

`get_security_groups_generator()` (*SecurityGroups method*), 567, 1303, 2041, 2791

`get_security_groups_to_vn_to_vlan()` (*SecurityGroupToVirtualNetwork method*), 558, 1294, 2032, 2782

`get_security_groups_to_vn_to_vlan_by_id()` (*SecurityGroupToVirtualNetwork method*), 556, 1292, 2030, 2780

`get_security_groups_to_vn_to_vlan_generator()` (*SecurityGroupToVirtualNetwork method*), 559, 1295, 2033, 2783

`get_self_registered_portal_by_id()` (*SelfRegisteredPortal method*), 601, 1336, 2074, 2824

`get_self_registered_portals()` (*SelfRegisteredPortal method*), 603, 1338, 2076, 2826

`get_self_registered_portals_generator()` (*SelfRegisteredPortal method*), 604, 1339, 2077, 2827

`get_session_auth_list()` (*Misc method*), 360, 1083, 1821, 2570

`get_session_by_ip_address()` (*SessionDirectory method*), 608, 1343, 2081, 2831

`get_session_by_mac_address()` (*SessionDirectory method*), 609, 1344, 2082, 2832

`get_session_service_node()` (*PsnNodeDetailsWithRadiusService method*), 499, 1235, 1973, 2723

`get_session_service_node_by_id()` (*PsnNodeDetailsWithRadiusService method*), 498, 1234, 1972, 2722

`get_session_service_node_by_name()` (*PsnNodeDetailsWithRadiusService method*), 497, 1234, 1972, 2721

`get_session_service_node_generator()` (*PsnNodeDetailsWithRadiusService method*), 499, 1235, 1973, 2723

`get_sessions()` (*SessionDirectory method*), 607, 1342, 2080, 2830

`get_sessions_by_endpoint_ip()` (*Misc method*), 363, 1086, 1824, 2573

`get_sessions_by_mac()` (*Misc method*), 361, 1085, 1823, 2572

`get_sessions_by_nas_ip()` (*Misc method*), 363, 1086, 1824, 2573

`get_sessions_by_session_id()` (*Misc method*), 364, 1087, 1825, 2574

`get_sessions_by_username()` (*Misc method*), 362, 1085, 1823, 2572

`get_sessions_for_recovery()` (*SessionDirectory method*), 608, 1343, 2081, 2831

`get_sg_vn_mapping_by_id()` (*SgVnMapping method*), 734, 1470, 2208

`get_sg_vn_mappings()` (*SgVnMapping method*), 729, 1466, 2204

`get_sg_vn_mappings_generator()` (*SgVnMapping method*), 730, 1467, 2205

`get_smart_state()` (*Licensing method*), 1077, 1815, 2564

`get_sms_provider()` (*SmsProvider method*), 531, 1267, 2005, 2755

`get_sms_provider_generator()` (*SmsProvider method*), 532, 1268, 2006, 2756

`get_sponsor_group()` (*SponsorGroup method*), 616, 1351, 2089, 2839

`get_sponsor_group_by_id()` (*SponsorGroup method*), 614, 1349, 2087, 2837

`get_sponsor_group_generator()` (*SponsorGroup method*), 617, 1352, 2090, 2840

`get_sponsor_group_member()` (*SponsorGroupMember method*), 620, 1355, 2093, 2843

`get_sponsor_group_member_generator()` (*SponsorGroupMember method*), 621, 1356, 2094, 2844

`get_sponsor_portal()` (*SponsorPortal method*), 634, 1369, 2107, 2857

`get_sponsor_portal_by_id()` (*SponsorPortal method*), 631, 1366, 2104, 2854

`get_sponsor_portal_generator()` (*SponsorPortal method*), 635, 1370, 2108, 2858

`get_sponsored_guest_portal_by_id()` (*SponsoredGuestPortal method*), 649, 1384, 2122, 2872

`get_sponsored_guest_portals()` (*SponsoredGuest-*

Portal method), 651, 1386, 2124, 2874

`get_sponsored_guest_portals_generator()` (*SponsoredGuestPortal method*), 652, 1387, 2125, 2875

`get_subscriber_by_id()` (*Subscriber method*), 2881

`get_subscriber_by_id()` (*Subscriber method*), 2882

`get_support_bundle_status()` (*SupportBundleStatus method*), 658, 1393, 2131, 2887

`get_support_bundle_status_by_id()` (*SupportBundleStatus method*), 658, 1393, 2131, 2887

`get_support_bundle_status_generator()` (*SupportBundleStatus method*), 659, 1394, 2132, 2888

`get_sxp_connections()` (*SxpConnections method*), 537, 1272, 2010, 2760

`get_sxp_connections_by_id()` (*SxpConnections method*), 534, 1270, 2008, 2758

`get_sxp_connections_generator()` (*SxpConnections method*), 538, 1273, 2011, 2761

`get_sxp_interface()` (*NodeServices method*), 1202, 1940, 2690

`get_sxp_local_bindings()` (*SxpLocalBindings method*), 544, 1280, 2018, 2768

`get_sxp_local_bindings_by_id()` (*SxpLocalBindings method*), 542, 1278, 2016, 2766

`get_sxp_local_bindings_generator()` (*SxpLocalBindings method*), 545, 1281, 2019, 2769

`get_sxp_vpn_by_id()` (*SxpVpns method*), 550, 1285, 2023, 2773

`get_sxp_vpns()` (*SxpVpns method*), 551, 1287, 2025, 2775

`get_sxp_vpns_generator()` (*SxpVpns method*), 552, 1288, 2026, 2776

`get_system_certificate_by_id()` (*Certificates method*), 156, 873, 1611, 2349

`get_system_certificates()` (*Certificates method*), 154, 871, 1609, 2347

`get_system_certificates_generator()` (*Certificates method*), 155, 872, 1610, 2348

`get_tacacs_command_sets()` (*TacacsCommandSets method*), 673, 1408, 2146, 2902

`get_tacacs_command_sets_by_id()` (*TacacsCommandSets method*), 671, 1406, 2144, 2900

`get_tacacs_command_sets_by_name()` (*TacacsCommandSets method*), 670, 1405, 2143, 2899

`get_tacacs_command_sets_generator()` (*TacacsCommandSets method*), 673, 1408, 2146, 2902

`get_tacacs_external_servers()` (*TacacsExternalServers method*), 679, 1414, 2152, 2908

`get_tacacs_external_servers_by_id()` (*TacacsExternalServers method*), 676, 1411, 2149, 2905

`get_tacacs_external_servers_by_name()` (*TacacsExternalServers method*), 676, 1411, 2149, 2905

`get_tacacs_external_servers_generator()` (*TacacsExternalServers method*), 679, 1414, 2152, 2908

`get_tacacs_profile()` (*TacacsProfile method*), 685, 1420, 2158, 2914

`get_tacacs_profile_by_id()` (*TacacsProfile method*), 683, 1418, 2156, 2912

`get_tacacs_profile_by_name()` (*TacacsProfile method*), 682, 1417, 2155, 2911

`get_tacacs_profile_generator()` (*TacacsProfile method*), 685, 1420, 2158, 2914

`get_tacacs_server_sequence()` (*TacacsServerSequence method*), 691, 1426, 2164, 2920

`get_tacacs_server_sequence_by_id()` (*TacacsServerSequence method*), 689, 1424, 2162, 2918

`get_tacacs_server_sequence_by_name()` (*TacacsServerSequence method*), 688, 1423, 2161, 2917

`get_tacacs_server_sequence_generator()` (*TacacsServerSequence method*), 692, 1427, 2165, 2921

`get_task_status()` (*Tasks method*), 736, 1473, 2211, 2955

`get_task_status_by_id()` (*Tasks method*), 737, 1473, 2211, 2955

`get_telemetry_info_by_id()` (*TelemetryInformation method*), 695, 1430, 2168, 2924

`get_telemetry_information()` (*TelemetryInformation method*), 695, 1430, 2168, 2924

`get_telemetry_information_generator()` (*TelemetryInformation method*), 696, 1431, 2169, 2925

`get_tier_state_info()` (*Licensing method*), 1078, 1816, 2565

`get_transport_gateway()` (*Telemetry method*), 1474, 2212, 2956

`get_trusted_certificate_by_id()` (*Certificates method*), 163, 881, 1619, 2357

`get_trusted_certificates()` (*Certificates method*), 159, 876, 1614, 2352

`get_trusted_certificates_generator()` (*Certificates method*), 160, 877, 1615, 2353

`get_trusted_domains()` (*ActiveDirectory method*), 62, 776, 1514, 2252

`get_user_group_by_user_name()` (*SessionDirectory method*), 610, 1345, 2083, 2833

`get_user_groups()` (*ActiveDirectory method*), 59, 773, 1511, 2249

`get_user_groups()` (*SessionDirectory method*), 609, 1344, 2082, 2832

[get_version\(\)](#) (*AciBindings method*), 40, 754, 1492, 2230
[get_version\(\)](#) (*AciSettings method*), 44, 758, 1496, 2234
[get_version\(\)](#) (*ActiveDirectory method*), 69, 783, 1521, 2259
[get_version\(\)](#) (*AdminUser method*), 73, 787, 1525, 2263
[get_version\(\)](#) (*AllowedProtocols method*), 90, 804, 1542, 2280
[get_version\(\)](#) (*AncEndpoint method*), 50, 764, 1502, 2240
[get_version\(\)](#) (*AncPolicy method*), 98, 812, 1550, 2288
[get_version\(\)](#) (*AuthorizationProfile method*), 110, 824, 1562, 2300
[get_version\(\)](#) (*ByodPortal method*), 124, 838, 1576, 2314
[get_version\(\)](#) (*CertificateProfile method*), 137, 851, 1589, 2327
[get_version\(\)](#) (*CertificateTemplate method*), 141, 855, 1593, 2331
[get_version\(\)](#) (*ClearThreatsAndVulnerabilities method*), 168, 886, 1624, 2362
[get_version\(\)](#) (*DownloadableAcl method*), 224, 942, 1680, 2424
[get_version\(\)](#) (*EgressMatrixCell method*), 232, 950, 1688, 2438
[get_version\(\)](#) (*Endpoint method*), 713, 1448, 2186, 2942
[get_version\(\)](#) (*EndpointCertificate method*), 237, 955, 1693, 2442
[get_version\(\)](#) (*EndpointIdentityGroup method*), 244, 962, 1700, 2449
[get_version\(\)](#) (*ExternalRadiusServer method*), 252, 970, 1708, 2457
[get_version\(\)](#) (*FilterPolicy method*), 258, 976, 1714, 2463
[get_version\(\)](#) (*GuestLocation method*), 262, 980, 1718, 2467
[get_version\(\)](#) (*GuestSntpNotificationConfiguration method*), 268, 986, 1724, 2473
[get_version\(\)](#) (*GuestSsid method*), 274, 992, 1730, 2479
[get_version\(\)](#) (*GuestType method*), 283, 1001, 1739, 2488
[get_version\(\)](#) (*GuestUser method*), 300, 1018, 1756, 2505
[get_version\(\)](#) (*HotspotPortal method*), 314, 1032, 1770, 2519
[get_version\(\)](#) (*IdentityGroups method*), 339, 1057, 1795, 2544
[get_version\(\)](#) (*IdentitySequence method*), 345, 1063, 1801, 2550
[get_version\(\)](#) (*InternalUser method*), 356, 1074, 1812, 2561
[get_version\(\)](#) (*IpToSgtMapping method*), 323, 1041, 1779, 2528
[get_version\(\)](#) (*IpToSgtMappingGroup method*), 332, 1050, 1788, 2537
[get_version\(\)](#) (*MyDevicePortal method*), 381, 1105, 1843, 2592
[get_version\(\)](#) (*NativeSupplicantProfile method*), 386, 1110, 1848, 2597
[get_version\(\)](#) (*NetworkDevice method*), 456, 1181, 1919, 2669
[get_version\(\)](#) (*NetworkDeviceGroup method*), 464, 1189, 1927, 2677
[get_version\(\)](#) (*NodeDetails method*), 476, 1209, 1947, 2697
[get_version\(\)](#) (*Portal method*), 723, 1458, 2196, 2947
[get_version\(\)](#) (*PortalGlobalSetting method*), 483, 1219, 1957, 2707
[get_version\(\)](#) (*PortalTheme method*), 489, 1225, 1963, 2713
[get_version\(\)](#) (*ProfilerProfile method*), 494, 1230, 1968, 2718
[get_version\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 500, 1236, 1974, 2724
[get_version\(\)](#) (*PullDeploymentInfo method*), 506, 1242, 1980, 2730
[get_version\(\)](#) (*PxGridNode method*), 728, 1465, 2203, 2954
[get_version\(\)](#) (*PxGridSettings method*), 507, 1243, 1981, 2731
[get_version\(\)](#) (*RadiusServerSequence method*), 516, 1252, 1990, 2740
[get_version\(\)](#) (*RestidStore method*), 525, 1261, 1999, 2749
[get_version\(\)](#) (*SecurityGroups method*), 569, 1305, 2043, 2793
[get_version\(\)](#) (*SecurityGroupsAcls method*), 577, 1313, 2051, 2801
[get_version\(\)](#) (*SecurityGroupToVirtualNetwork method*), 561, 1297, 2035, 2785
[get_version\(\)](#) (*SelfRegisteredPortal method*), 606, 1341, 2079, 2829
[get_version\(\)](#) (*SmsProvider method*), 533, 1269, 2007, 2757
[get_version\(\)](#) (*SponsoredGuestPortal method*), 654, 1389, 2127, 2877
[get_version\(\)](#) (*SponsorGroup method*), 619, 1354, 2092, 2842
[get_version\(\)](#) (*SponsorGroupMember method*), 622, 1357, 2095, 2845
[get_version\(\)](#) (*SponsorPortal method*), 636, 1371, 2109, 2859
[get_version\(\)](#) (*SupportBundleDownload method*),

- 656, 1391, 2129, 2885
- `get_version()` (*SupportBundleStatus* method), 660, 1395, 2133, 2889
- `get_version()` (*SupportBundleTriggerConfiguration* method), 663, 1398, 2136, 2892
- `get_version()` (*SxpConnections* method), 540, 1275, 2013, 2763
- `get_version()` (*SxpLocalBindings* method), 548, 1283, 2021, 2771
- `get_version()` (*SxpVpns* method), 554, 1289, 2027, 2777
- `get_version()` (*SystemCertificate* method), 668, 1403, 2141, 2897
- `get_version()` (*TacacsCommandSets* method), 675, 1410, 2148, 2904
- `get_version()` (*TacacsExternalServers* method), 681, 1416, 2154, 2910
- `get_version()` (*TacacsProfile* method), 687, 1422, 2160, 2916
- `get_version()` (*TacacsServerSequence* method), 694, 1429, 2167, 2923
- `get_version()` (*TelemetryInformation* method), 697, 1432, 2170, 2926
- `get_version_info()` (*VersionInfo* method), 702, 1437, 2175, 2931
- `get_virtual_network_by_id()` (*VirtualNetwork* method), 742, 1480, 2218
- `get_virtual_networks()` (*VirtualNetwork* method), 737, 1475, 2213
- `get_virtual_networks_generator()` (*VirtualNetwork* method), 738, 1476, 2214
- `get_vn_vlan_mapping_by_id()` (*VnVlanMapping* method), 749, 1487, 2225
- `get_vn_vlan_mappings()` (*VnVlanMapping* method), 744, 1482, 2220
- `get_vn_vlan_mappings_generator()` (*VnVlanMapping* method), 745, 1483, 2221
- `GuestLocation` (class in *ciscoisesdk.api.v3_1_0.guest_location*), 259
- `GuestLocation` (class in *ciscoisesdk.api.v3_1_1.guest_location*), 977
- `GuestLocation` (class in *ciscoisesdk.api.v3_1_patch_1.guest_location*), 1715
- `GuestLocation` (class in *ciscoisesdk.api.v3_2_beta.guest_location*), 2464
- `GuestSmtNotificationConfiguration` (class in *ciscoisesdk.api.v3_1_0.guest_smt_notification_configuration*), 262
- `GuestSmtNotificationConfiguration` (class in *ciscoisesdk.api.v3_1_1.guest_smt_notification_configuration*), 980
- `GuestSmtNotificationConfiguration` (class in *ciscoisesdk.api.v3_1_patch_1.guest_smt_notification_configuration*), 1718
- `GuestSmtNotificationConfiguration` (class in *ciscoisesdk.api.v3_2_beta.guest_smt_notification_configuration*), 2467
- `GuestSsid` (class in *ciscoisesdk.api.v3_1_0.guest_ssid*), 269
- `GuestSsid` (class in *ciscoisesdk.api.v3_1_1.guest_ssid*), 987
- `GuestSsid` (class in *ciscoisesdk.api.v3_1_patch_1.guest_ssid*), 1725
- `GuestSsid` (class in *ciscoisesdk.api.v3_2_beta.guest_ssid*), 2474
- `GuestType` (class in *ciscoisesdk.api.v3_1_0.guest_type*), 275
- `GuestType` (class in *ciscoisesdk.api.v3_1_1.guest_type*), 993
- `GuestType` (class in *ciscoisesdk.api.v3_1_patch_1.guest_type*), 1731
- `GuestType` (class in *ciscoisesdk.api.v3_2_beta.guest_type*), 2480
- `GuestUser` (class in *ciscoisesdk.api.v3_1_0.guest_user*), 284
- `GuestUser` (class in *ciscoisesdk.api.v3_1_1.guest_user*), 1002
- `GuestUser` (class in *ciscoisesdk.api.v3_1_patch_1.guest_user*), 1740
- `GuestUser` (class in *ciscoisesdk.api.v3_2_beta.guest_user*), 2489
- ## H
- `has_path()` (*MyDict* method), 2957
- `headers` (*RestResponse* property), 2958
- `HotspotPortal` (class in *ciscoisesdk.api.v3_1_0.hotspot_portal*), 302
- `HotspotPortal` (class in *ciscoisesdk.api.v3_1_1.hotspot_portal*), 1020
- `HotspotPortal` (class in *ciscoisesdk.api.v3_1_patch_1.hotspot_portal*), 1758
- `HotspotPortal` (class in *ciscoisesdk.api.v3_2_beta.hotspot_portal*), 2507
- ## I
- `IdentityGroups` (class in *ciscoisesdk.api.v3_1_0.identity_groups*), 334
- `IdentityGroups` (class in *ciscoisesdk.api.v3_1_1.identity_groups*), 1052
- `IdentityGroups` (class in *ciscoisesdk.api.v3_1_patch_1.identity_groups*), 1790
- `IdentityGroups` (class in *ciscoisesdk.api.v3_2_beta.identity_groups*), 2539

- IdentitySequence (class in *ciscoisesdk.api.v3_1_0.identity_sequence*), 340
- IdentitySequence (class in *ciscoisesdk.api.v3_1_1.identity_sequence*), 1058
- IdentitySequence (class in *ciscoisesdk.api.v3_1_patch_1.identity_sequence*), 1796
- IdentitySequence (class in *ciscoisesdk.api.v3_2_beta.identity_sequence*), 2545
- IdentityServicesEngineAPI (class in *ciscoisesdk*), 31
- import_system_certificate() (Certificates method), 151, 869, 1607, 2345
- import_trust_certificate() (Certificates method), 161, 879, 1617, 2355
- initialize_api_wrappers() (IdentityServicesEngineAPI method), 33
- initialize_authentication() (IdentityServicesEngineAPI method), 33
- initialize_sessions() (IdentityServicesEngineAPI method), 33
- install_hotpatch() (Patching method), 1212, 1950, 2700
- install_patch() (Patching method), 1214, 1952, 2702
- InternalUser (class in *ciscoisesdk.api.v3_1_0.internal_user*), 346
- InternalUser (class in *ciscoisesdk.api.v3_1_1.internal_user*), 1064
- InternalUser (class in *ciscoisesdk.api.v3_1_patch_1.internal_user*), 1802
- InternalUser (class in *ciscoisesdk.api.v3_2_beta.internal_user*), 2551
- IpToSgtMapping (class in *ciscoisesdk.api.v3_1_0.ip_to_sgt_mapping*), 315
- IpToSgtMapping (class in *ciscoisesdk.api.v3_1_1.ip_to_sgt_mapping*), 1033
- IpToSgtMapping (class in *ciscoisesdk.api.v3_1_patch_1.ip_to_sgt_mapping*), 1771
- IpToSgtMapping (class in *ciscoisesdk.api.v3_2_beta.ip_to_sgt_mapping*), 2520
- IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_1_0.ip_to_sgt_mapping_group*), 325
- IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_1_1.ip_to_sgt_mapping_group*), 1043
- IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_1_patch_1.ip_to_sgt_mapping_group*), 1781
- IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_2_beta.ip_to_sgt_mapping_group*), 2530
- is_encoded_auth() (IdentityServicesEngineAPI method), 34
- is_password() (IdentityServicesEngineAPI method), 34
- is_user_member_of_groups() (ActiveDirectory method), 62, 776, 1514, 2252
- ## J
- join_domain() (ActiveDirectory method), 66, 780, 1518, 2256
- join_domain_with_all_nodes() (ActiveDirectory method), 63, 777, 1515, 2253
- ## L
- leave_domain() (ActiveDirectory method), 61, 775, 1513, 2251
- leave_domain_with_all_nodes() (ActiveDirectory method), 63, 777, 1515, 2253
- Licensing (class in *ciscoisesdk.api.v3_1_1.licensing*), 1074
- Licensing (class in *ciscoisesdk.api.v3_1_patch_1.licensing*), 1812
- Licensing (class in *ciscoisesdk.api.v3_2_beta.licensing*), 2561
- list_installed_hotpatches() (Patching method), 1212, 1950, 2699
- list_installed_patches() (Patching method), 1213, 1951, 2701
- load_groups_from_domain() (ActiveDirectory method), 60, 774, 1512, 2250
- lookup_service() (Consumer method), 171, 889, 1627, 2366
- ## M
- make_primary() (NodeDeployment method), 1193, 1931, 2681
- make_standalone() (NodeDeployment method), 1195, 1933, 2682
- MalformedRequest, 2960
- Mdm (class in *ciscoisesdk.api.v3_1_0.mdm*), 356
- Mdm (class in *ciscoisesdk.api.v3_1_1.mdm*), 1079
- Mdm (class in *ciscoisesdk.api.v3_1_patch_1.mdm*), 1817
- Mdm (class in *ciscoisesdk.api.v3_2_beta.mdm*), 2566
- message (ApiError attribute), 2959
- Misc (class in *ciscoisesdk.api.v3_1_0.misc*), 359
- Misc (class in *ciscoisesdk.api.v3_1_1.misc*), 1082
- Misc (class in *ciscoisesdk.api.v3_1_patch_1.misc*), 1820
- Misc (class in *ciscoisesdk.api.v3_2_beta.misc*), 2569
- mnt_base_url (IdentityServicesEngineAPI property), 34
- module
- ciscoisesdk.config, 13
- monitor_bulk_status() (AncEndpoint method), 51, 765, 1503, 2241

- `monitor_bulk_status()` (*AncPolicy* method), 99, 813, 1551, 2289
- `monitor_bulk_status()` (*EgressMatrixCell* method), 234, 952, 1690, 2439
- `monitor_bulk_status()` (*Endpoint* method), 715, 1450, 2188, 2944
- `monitor_bulk_status()` (*GuestUser* method), 301, 1019, 1757, 2506
- `monitor_bulk_status()` (*IpToSgtMapping* method), 324, 1042, 1780, 2529
- `monitor_bulk_status()` (*IpToSgtMappingGroup* method), 333, 1051, 1789, 2538
- `monitor_bulk_status()` (*NetworkDevice* method), 458, 1183, 1921, 2671
- `monitor_bulk_status()` (*SecurityGroups* method), 571, 1306, 2044, 2794
- `monitor_bulk_status()` (*SecurityGroupsAcls* method), 579, 1314, 2052, 2802
- `monitor_bulk_status()` (*SecurityGroupToVirtualNetwork* method), 563, 1298, 2036, 2786
- `monitor_bulk_status()` (*SxpConnections* method), 541, 1277, 2015, 2765
- `monitor_bulk_status()` (*SxpLocalBindings* method), 549, 1285, 2023, 2773
- `monitor_bulk_status()` (*SxpVpns* method), 556, 1291, 2029, 2779
- `monitor_bulk_status_anc_endpoint()` (*AncEndpoint* method), 51, 765, 1503, 2241
- `monitor_bulk_status_anc_policy()` (*AncPolicy* method), 99, 813, 1551, 2289
- `monitor_bulk_status_egress_matrix_cell()` (*EgressMatrixCell* method), 234, 952, 1690, 2439
- `monitor_bulk_status_endpoint()` (*Endpoint* method), 714, 1449, 2187, 2943
- `monitor_bulk_status_guest_user()` (*GuestUser* method), 301, 1019, 1757, 2506
- `monitor_bulk_status_ip_to_sgt_mapping()` (*IpToSgtMapping* method), 324, 1042, 1780, 2529
- `monitor_bulk_status_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup* method), 333, 1051, 1789, 2538
- `monitor_bulk_status_network_device()` (*NetworkDevice* method), 458, 1183, 1921, 2670
- `monitor_bulk_status_security_group()` (*SecurityGroups* method), 570, 1306, 2044, 2794
- `monitor_bulk_status_security_groups_acl()` (*SecurityGroupsAcls* method), 578, 1314, 2052, 2802
- `monitor_bulk_status_security_groups_to_vn_to_vlan()` (*SecurityGroupToVirtualNetwork* method), 562, 1298, 2036, 2786
- `monitor_bulk_status_sxp_connections()` (*SxpConnections* method), 541, 1276, 2014, 2764
- `monitor_bulk_status_sxp_local_bindings()` (*SxpLocalBindings* method), 549, 1284, 2022, 2772
- `monitor_bulk_status_sxp_vpns()` (*SxpVpns* method), 555, 1290, 2028, 2778
- `MyDevicePortal` (class in *ciscoisesdk.api.v3_1_0.my_device_portal*), 368
- `MyDevicePortal` (class in *ciscoisesdk.api.v3_1_1.my_device_portal*), 1091
- `MyDevicePortal` (class in *ciscoisesdk.api.v3_1_patch_1.my_device_portal*), 1829
- `MyDevicePortal` (class in *ciscoisesdk.api.v3_2_beta.my_device_portal*), 2578
- `MyDict` (class in *ciscoisesdk.models.mydict*), 2957
- ## N
- `NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_1_0.native_supplicant_profile*), 382
- `NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_1_1.native_supplicant_profile*), 1106
- `NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_1_patch_1.native_supplicant_profile*), 1844
- `NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_2_beta.native_supplicant_profile*), 2593
- `NbarApp` (class in *ciscoisesdk.api.v3_1_0.nbar_app*), 715
- `NbarApp` (class in *ciscoisesdk.api.v3_1_1.nbar_app*), 1450
- `NbarApp` (class in *ciscoisesdk.api.v3_1_patch_1.nbar_app*), 2188
- `NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_1_0.network_access_authentication_rules*), 387
- `NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_1_1.network_access_authentication_rules*), 1111
- `NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_1_patch_1.network_access_authentication_rules*), 1849
- `NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_2_beta.network_access_authentication_rules*), 2598
- `NetworkAccessAuthorizationExceptionRules` (class in *ciscoisesdk*),

<code>esdk.api.v3_1_0.network_access_authorization_exception_rules</code>	<code>NetworkAccessDictionary</code> (class in <code>ciscois-esdk.api.v3_1_0.network_access_dictionary</code>),
392	415
<code>NetworkAccessAuthorizationExceptionRules</code>	
(class in <code>ciscois-esdk.api.v3_1_1.network_access_authorization_exception_rules</code>),	<code>NetworkAccessDictionary</code> (class in <code>ciscois-esdk.api.v3_1_1.network_access_dictionary</code>),
1116	1139
<code>NetworkAccessAuthorizationExceptionRules</code>	<code>NetworkAccessDictionary</code> (class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_dictionary</code>),
(class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_authorization_exception_rules</code>),	1877
1854	<code>NetworkAccessDictionary</code> (class in <code>ciscois-esdk.api.v3_2_beta.network_access_dictionary</code>),
<code>NetworkAccessAuthorizationExceptionRules</code>	2627
(class in <code>ciscois-esdk.api.v3_2_beta.network_access_authorization_exception_rules</code>),	<code>NetworkAccessDictionaryAttribute</code>
2603	(class in <code>ciscois-esdk.api.v3_1_0.network_access_dictionary_attribute</code>),
<code>NetworkAccessAuthorizationGlobalExceptionRules</code>	419
(class in <code>ciscois-esdk.api.v3_1_0.network_access_authorization_global_exception_rules</code>),	<code>NetworkAccessDictionaryAttribute</code>
396	(class in <code>ciscois-esdk.api.v3_1_1.network_access_dictionary_attribute</code>),
<code>NetworkAccessAuthorizationGlobalExceptionRules</code>	1143
(class in <code>ciscois-esdk.api.v3_1_1.network_access_authorization_global_exception_rules</code>),	<code>NetworkAccessDictionaryAttribute</code>
1120	(class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_dictionary_attribute</code>),
<code>NetworkAccessAuthorizationGlobalExceptionRules</code>	1881
(class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_authorization_global_exception_rules</code>),	<code>NetworkAccessDictionaryAttribute</code>
1858	(class in <code>ciscois-esdk.api.v3_2_beta.network_access_dictionary_attribute</code>),
<code>NetworkAccessAuthorizationGlobalExceptionRules</code>	2631
(class in <code>ciscois-esdk.api.v3_2_beta.network_access_authorization_global_exception_rules</code>),	<code>NetworkAccessDictionaryAttributesList</code>
2607	(class in <code>ciscois-esdk.api.v3_1_0.network_access_dictionary_attributes_list</code>),
<code>NetworkAccessAuthorizationRules</code> (class in <code>ciscois-esdk.api.v3_1_0.network_access_authorization_rules</code>),	424
400	<code>NetworkAccessDictionaryAttributesList</code>
<code>NetworkAccessAuthorizationRules</code> (class in <code>ciscois-esdk.api.v3_1_1.network_access_authorization_rules</code>),	(class in <code>ciscois-esdk.api.v3_1_1.network_access_dictionary_attributes_list</code>),
1124	1148
<code>NetworkAccessAuthorizationRules</code> (class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_authorization_rules</code>),	<code>NetworkAccessDictionaryAttributesList</code>
1862	(class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_dictionary_attributes_list</code>),
<code>NetworkAccessAuthorizationRules</code> (class in <code>ciscois-esdk.api.v3_2_beta.network_access_authorization_rules</code>),	1886
2612	<code>NetworkAccessDictionaryAttributesList</code>
<code>NetworkAccessConditions</code> (class in <code>ciscois-esdk.api.v3_1_0.network_access_conditions</code>),	(class in <code>ciscois-esdk.api.v3_2_beta.network_access_dictionary_attributes_list</code>),
405	2635
<code>NetworkAccessConditions</code> (class in <code>ciscois-esdk.api.v3_1_1.network_access_conditions</code>),	<code>NetworkAccessIdentityStores</code> (class in <code>ciscois-esdk.api.v3_1_0.network_access_identity_stores</code>),
1129	425
<code>NetworkAccessConditions</code> (class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_conditions</code>),	<code>NetworkAccessIdentityStores</code> (class in <code>ciscois-esdk.api.v3_1_1.network_access_identity_stores</code>),
1867	1149
<code>NetworkAccessConditions</code> (class in <code>ciscois-esdk.api.v3_2_beta.network_access_conditions</code>),	<code>NetworkAccessIdentityStores</code> (class in <code>ciscois-esdk.api.v3_1_patch_1.network_access_identity_stores</code>),
2616	1887
	<code>NetworkAccessIdentityStores</code> (class in <code>ciscois-</code>

esdk.api.v3_2_beta.network_access_identity_stores , 2637	esdk.api.v3_1_1.network_access_service_names , 1161
NetworkAccessNetworkConditions (class in cisco-esdk.api.v3_1_0.network_access_network_conditions), 426	NetworkAccessServiceNames (class in cisco-esdk.api.v3_1_patch_1.network_access_service_names), 1899
NetworkAccessNetworkConditions (class in cisco-esdk.api.v3_1_1.network_access_network_conditions), 1150	NetworkAccessServiceNames (class in cisco-esdk.api.v3_2_beta.network_access_service_names), 2649
NetworkAccessNetworkConditions (class in cisco-esdk.api.v3_1_patch_1.network_access_network_conditions), 1888	NetworkAccessTimeDateConditions (class in cisco-esdk.api.v3_1_0.network_access_time_date_conditions), 437
NetworkAccessNetworkConditions (class in cisco-esdk.api.v3_2_beta.network_access_network_conditions), 2638	NetworkAccessTimeDateConditions (class in cisco-esdk.api.v3_1_1.network_access_time_date_conditions), 1162
NetworkAccessPolicySet (class in cisco-esdk.api.v3_1_0.network_access_policy_set), 430	NetworkAccessTimeDateConditions (class in cisco-esdk.api.v3_1_patch_1.network_access_time_date_conditions), 1900
NetworkAccessPolicySet (class in cisco-esdk.api.v3_1_1.network_access_policy_set), 1155	NetworkAccessTimeDateConditions (class in cisco-esdk.api.v3_2_beta.network_access_time_date_conditions), 2649
NetworkAccessPolicySet (class in cisco-esdk.api.v3_1_patch_1.network_access_policy_set), 1893	NetworkDevice (class in cisco-esdk.api.v3_1_0.network_device), 443
NetworkAccessPolicySet (class in cisco-esdk.api.v3_2_beta.network_access_policy_set), 2642	NetworkDevice (class in cisco-esdk.api.v3_1_1.network_device), 1168
NetworkAccessProfiles (class in cisco-esdk.api.v3_1_0.network_access_profiles), 435	NetworkDevice (class in cisco-esdk.api.v3_1_patch_1.network_device), 1906
NetworkAccessProfiles (class in cisco-esdk.api.v3_1_1.network_access_profiles), 1160	NetworkDevice (class in cisco-esdk.api.v3_2_beta.network_device), 2655
NetworkAccessProfiles (class in cisco-esdk.api.v3_1_patch_1.network_access_profiles), 1898	NetworkDeviceGroup (class in cisco-esdk.api.v3_1_0.network_device_group), 458
NetworkAccessProfiles (class in cisco-esdk.api.v3_2_beta.network_access_profiles), 2647	NetworkDeviceGroup (class in cisco-esdk.api.v3_1_1.network_device_group), 1183
NetworkAccessSecurityGroups (class in cisco-esdk.api.v3_1_0.network_access_security_groups), 435	NetworkDeviceGroup (class in cisco-esdk.api.v3_1_patch_1.network_device_group), 1921
NetworkAccessSecurityGroups (class in cisco-esdk.api.v3_1_1.network_access_security_groups), 1160	NetworkDeviceGroup (class in cisco-esdk.api.v3_2_beta.network_device_group), 2671
NetworkAccessSecurityGroups (class in cisco-esdk.api.v3_1_patch_1.network_access_security_groups), 1898	NodeDeployment (class in cisco-esdk.api.v3_1_0.node_deployment), 465
NetworkAccessSecurityGroups (class in cisco-esdk.api.v3_2_beta.network_access_security_groups), 2648	NodeDeployment (class in cisco-esdk.api.v3_1_1.node_deployment), 1190
NetworkAccessServiceNames (class in cisco-esdk.api.v3_1_0.network_access_service_names), 436	NodeDeployment (class in cisco-esdk.api.v3_1_patch_1.node_deployment), 1928
NetworkAccessServiceNames (class in cisco-esdk.api.v3_1_1.network_access_service_names), 1205	NodeDeployment (class in cisco-esdk.api.v3_2_beta.node_deployment), 2678
	NodeDetails (class in cisco-esdk.api.v3_1_0.node_details), 472
	NodeDetails (class in cisco-esdk.api.v3_1_1.node_details), 1205

NodeDetails (class in *ciscoisesdk.api.v3_1_patch_1.node_details*), 1943

NodeDetails (class in *ciscoisesdk.api.v3_2_beta.node_details*), 2693

NodeGroup (class in *ciscoisesdk.api.v3_1_0.node_group*), 469

NodeGroup (class in *ciscoisesdk.api.v3_1_1.node_group*), 1196

NodeGroup (class in *ciscoisesdk.api.v3_1_patch_1.node_group*), 1934

NodeGroup (class in *ciscoisesdk.api.v3_2_beta.node_group*), 2683

NodeServices (class in *ciscoisesdk.api.v3_1_1.node_services*), 1202

NodeServices (class in *ciscoisesdk.api.v3_1_patch_1.node_services*), 1940

NodeServices (class in *ciscoisesdk.api.v3_2_beta.node_services*), 2689

O

object_factory (*IdentityServicesEngineAPI* property), 35

original_error (*DownloadFailure* attribute), 2960

P

PanHa (class in *ciscoisesdk.api.v3_1_0.pan_ha*), 477

PanHa (class in *ciscoisesdk.api.v3_1_1.pan_ha*), 1210

PanHa (class in *ciscoisesdk.api.v3_1_patch_1.pan_ha*), 1948

PanHa (class in *ciscoisesdk.api.v3_2_beta.pan_ha*), 2698

Patching (class in *ciscoisesdk.api.v3_1_1.patching*), 1212

Patching (class in *ciscoisesdk.api.v3_1_patch_1.patching*), 1950

Patching (class in *ciscoisesdk.api.v3_2_beta.patching*), 2699

path (*DownloadResponse* property), 2958

perform_initialize (*IdentityServicesEngineAPI* property), 34

Portal (class in *ciscoisesdk.api.v3_1_0.portal*), 720

Portal (class in *ciscoisesdk.api.v3_1_1.portal*), 1455

Portal (class in *ciscoisesdk.api.v3_1_patch_1.portal*), 2193

Portal (class in *ciscoisesdk.api.v3_2_beta.portal*), 2944

PortalGlobalSetting (class in *ciscoisesdk.api.v3_1_0.portal_global_setting*), 479

PortalGlobalSetting (class in *ciscoisesdk.api.v3_1_1.portal_global_setting*), 1215

PortalGlobalSetting (class in *ciscoisesdk.api.v3_1_patch_1.portal_global_setting*), 1953

PortalGlobalSetting (class in *ciscoisesdk.api.v3_2_beta.portal_global_setting*), 2703

PortalTheme (class in *ciscoisesdk.api.v3_1_0.portal_theme*), 484

PortalTheme (class in *ciscoisesdk.api.v3_1_1.portal_theme*), 1220

PortalTheme (class in *ciscoisesdk.api.v3_1_patch_1.portal_theme*), 1958

PortalTheme (class in *ciscoisesdk.api.v3_2_beta.portal_theme*), 2708

Profiler (class in *ciscoisesdk.api.v3_1_0.profiler*), 490

Profiler (class in *ciscoisesdk.api.v3_1_1.profiler*), 1226

Profiler (class in *ciscoisesdk.api.v3_1_patch_1.profiler*), 1964

Profiler (class in *ciscoisesdk.api.v3_2_beta.profiler*), 2714

ProfilerProfile (class in *ciscoisesdk.api.v3_1_0.profiler_profile*), 491

ProfilerProfile (class in *ciscoisesdk.api.v3_1_1.profiler_profile*), 1227

ProfilerProfile (class in *ciscoisesdk.api.v3_1_patch_1.profiler_profile*), 1965

ProfilerProfile (class in *ciscoisesdk.api.v3_2_beta.profiler_profile*), 2715

promote_node() (*NodeDeployment* method), 466, 1194, 1932, 2682

Provider (class in *ciscoisesdk.api.v3_1_0.provider*), 494

Provider (class in *ciscoisesdk.api.v3_1_1.provider*), 1231

Provider (class in *ciscoisesdk.api.v3_1_patch_1.provider*), 1969

Provider (class in *ciscoisesdk.api.v3_2_beta.provider*), 2718

Proxy (class in *ciscoisesdk.api.v3_1_1.proxy*), 1459

Proxy (class in *ciscoisesdk.api.v3_1_patch_1.proxy*), 2197

Proxy (class in *ciscoisesdk.api.v3_2_beta.proxy*), 2948

PsnNodeDetailsWithRadiusService (class in *ciscoisesdk.api.v3_1_0.psn_node_details_with_radius_service*), 497

PsnNodeDetailsWithRadiusService (class in *ciscoisesdk.api.v3_1_1.psn_node_details_with_radius_service*), 1233

PsnNodeDetailsWithRadiusService (class in *ciscoisesdk.api.v3_1_patch_1.psn_node_details_with_radius_service*), 1971

PsnNodeDetailsWithRadiusService (class in *ciscoisesdk.api.v3_2_beta.psn_node_details_with_radius_service*), 2721

PullDeploymentInfo (class in *ciscoisesdk.api.v3_1_0.pull_deployment_info*), 501

PullDeploymentInfo (class in *ciscois-*

`esdk.api.v3_1_1.pull_deployment_info`),
1237

`PullDeploymentInfo` (class in `ciscoisesdk.api.v3_1_patch_1.pull_deployment_info`),
1975

`PullDeploymentInfo` (class in `ciscoisesdk.api.v3_2_beta.pull_deployment_info`),
2725

`px_grid_base_url` (`IdentityServicesEngineAPI` property), 35

`PxGridNode` (class in `ciscoisesdk.api.v3_1_0.px_grid_node`), 724

`PxGridNode` (class in `ciscoisesdk.api.v3_1_1.px_grid_node`), 1460

`PxGridNode` (class in `ciscoisesdk.api.v3_1_patch_1.px_grid_node`), 2198

`PxGridNode` (class in `ciscoisesdk.api.v3_2_beta.px_grid_node`), 2949

`PxGridSettings` (class in `ciscoisesdk.api.v3_1_0.px_grid_settings`), 506

`PxGridSettings` (class in `ciscoisesdk.api.v3_1_1.px_grid_settings`), 1242

`PxGridSettings` (class in `ciscoisesdk.api.v3_1_patch_1.px_grid_settings`),
1980

`PxGridSettings` (class in `ciscoisesdk.api.v3_2_beta.px_grid_settings`), 2730

R

`RadiusFailure` (class in `ciscoisesdk.api.v3_1_0.radius_failure`), 508

`RadiusFailure` (class in `ciscoisesdk.api.v3_1_1.radius_failure`), 1244

`RadiusFailure` (class in `ciscoisesdk.api.v3_1_patch_1.radius_failure`), 1982

`RadiusFailure` (class in `ciscoisesdk.api.v3_2_beta.radius_failure`), 2732

`RadiusServerSequence` (class in `ciscoisesdk.api.v3_1_0.radius_server_sequence`),
509

`RadiusServerSequence` (class in `ciscoisesdk.api.v3_1_1.radius_server_sequence`),
1245

`RadiusServerSequence` (class in `ciscoisesdk.api.v3_1_patch_1.radius_server_sequence`),
1983

`RadiusServerSequence` (class in `ciscoisesdk.api.v3_2_beta.radius_server_sequence`),
2733

`RateLimitError`, 2959

`RateLimitWarning`, 2960

`raw` (`DownloadFailure` attribute), 2960

`regenerate_ise_root_ca`() (`Certificates` method),
147, 861, 1599, 2337

`register`() (`Endpoint` method), 710, 1445, 2183, 2939

`register_endpoint`() (`Endpoint` method), 708, 1443,
2181, 2937

`register_node`() (`NodeDeployment` method), 465,
1191, 1929, 2678

`register_service`() (`Provider` method), 495, 1231,
1969, 2719

`reinitialize`() (`IdentityServicesEngineAPI` method),
34

`reinstate_by_id`() (`GuestUser` method), 292, 1010,
1748, 2497

`reinstate_by_name`() (`GuestUser` method), 288, 1006,
1744, 2493

`reinstate_guest_user_by_id`() (`GuestUser`
method), 291, 1009, 1747, 2496

`reinstate_guest_user_by_name`() (`GuestUser`
method), 288, 1006, 1744, 2493

`release_rejected`() (`Endpoint` method), 704, 1439,
2177, 2933

`release_rejected_endpoint`() (`Endpoint` method),
704, 1439, 2177, 2933

`remove_node`() (`NodeGroup` method), 1201, 1939, 2688

`renew_certificates`() (`Certificates` method), 148,
862, 1600, 2338

`ReplicationStatus` (class in `ciscoisesdk.api.v3_1_0.replication_status`), 526

`Repository` (class in `ciscoisesdk.api.v3_1_0.repository`), 526

`Repository` (class in `ciscoisesdk.api.v3_1_1.repository`), 1262

`Repository` (class in `ciscoisesdk.api.v3_1_patch_1.repository`), 2000

`Repository` (class in `ciscoisesdk.api.v3_2_beta.repository`), 2750

`request` (`ApiError` attribute), 2959

`request` (`DownloadFailure` attribute), 2960

`reregister_service`() (`Provider` method), 496, 1232,
1970, 2720

`reset_guest_user_password_by_id`() (`GuestUser`
method), 291, 1009, 1747, 2496

`reset_hit_counts`() (`DeviceAdministrationAuthorizationGlobalExceptionRules` method), 183, 901,
1639, 2382

`reset_hit_counts`() (`DeviceAdministrationPolicySet`
method), 210, 928, 1666, 2409

`reset_hit_counts`() (`NetworkAccessAuthorizationGlobalExceptionRules` method), 398, 1122,
1860, 2609

`reset_hit_counts`() (`NetworkAccessPolicySet`
method), 432, 1157, 1895, 2644

`reset_hit_counts_by_id`() (`DeviceAdministrationAuthenticationRules` method), 174, 892, 1630,
2373

`reset_hit_counts_by_id`() (`DeviceAdministration`

- nAuthorizationExceptionRules* method), 179, 897, 1635, 2377
- `reset_hit_counts_by_id()` (*DeviceAdministrationAuthorizationRules* method), 187, 905, 1643, 2386
- `reset_hit_counts_by_id()` (*NetworkAccessAuthenticationRules* method), 389, 1113, 1851, 2600
- `reset_hit_counts_by_id()` (*NetworkAccessAuthorizationExceptionRules* method), 394, 1118, 1856, 2605
- `reset_hit_counts_by_id()` (*NetworkAccessAuthorizationRules* method), 402, 1126, 1864, 2614
- `reset_hit_counts_device_admin_authentication_rules()` (*DeviceAdministrationAuthenticationRules* method), 174, 892, 1630, 2372
- `reset_hit_counts_device_admin_authorization_rules()` (*DeviceAdministrationAuthorizationRules* method), 187, 905, 1643, 2385
- `reset_hit_counts_device_admin_global_exceptions()` (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 182, 900, 1638, 2381
- `reset_hit_counts_device_admin_local_exceptions()` (*DeviceAdministrationAuthorizationExceptionRules* method), 178, 896, 1634, 2377
- `reset_hit_counts_device_admin_policy_sets()` (*DeviceAdministrationPolicySet* method), 209, 927, 1665, 2409
- `reset_hit_counts_network_access_authentication_rules()` (*NetworkAccessAuthenticationRules* method), 389, 1113, 1851, 2600
- `reset_hit_counts_network_access_authorization_rules()` (*NetworkAccessAuthorizationRules* method), 402, 1126, 1864, 2613
- `reset_hit_counts_network_access_global_exceptions()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 398, 1122, 1860, 2609
- `reset_hit_counts_network_access_local_exceptions()` (*NetworkAccessAuthorizationExceptionRules* method), 393, 1117, 1855, 2604
- `reset_hit_counts_network_access_policy_sets()` (*NetworkAccessPolicySet* method), 432, 1156, 1894, 2644
- `reset_password_by_id()` (*GuestUser* method), 291, 1009, 1747, 2496
- `response` (*ApiError* attribute), 2959
- `response` (*DownloadFailure* attribute), 2960
- `response` (*RestResponse* property), 2958
- RestidStore* (class in *ciscoisesdk.api.v3_1_0.restid_store*), 517
- RestidStore* (class in *ciscoisesdk.api.v3_1_1.restid_store*), 1253
- RestidStore* (class in *ciscoisesdk.api.v3_1_patch_1.restid_store*), 1991
- RestidStore* (class in *ciscoisesdk.api.v3_2_beta.restid_store*), 2741
- `restore()` (*BackupAndRestore* method), 128, 842, 1580, 2318
- `restore_config_backup()` (*BackupAndRestore* method), 127, 841, 1579, 2317
- RestResponse* (class in *ciscoisesdk.restresponse*), 2958
- `retry_after` (*RateLimitError* attribute), 2959
- `retry_after` (*RateLimitWarning* attribute), 2960
- `rollback_hotpatch()` (*Patching* method), 1213, 1951, 2700
- `rollback_patch()` (*Patching* method), 1215, 1953, 2702
- ## S
- SecurityGroups* (class in *ciscoisesdk.api.v3_1_0.security_groups*), 563
- SecurityGroups* (class in *ciscoisesdk.api.v3_1_1.security_groups*), 1299
- SecurityGroups* (class in *ciscoisesdk.api.v3_1_patch_1.security_groups*), 2037
- SecurityGroups* (class in *ciscoisesdk.api.v3_2_beta.security_groups*), 2787
- SecurityGroupsAcls* (class in *ciscoisesdk.api.v3_1_0.security_groups_acls*), 571
- SecurityGroupsAcls* (class in *ciscoisesdk.api.v3_1_1.security_groups_acls*), 1307
- SecurityGroupsAcls* (class in *ciscoisesdk.api.v3_1_patch_1.security_groups_acls*), 2045
- SecurityGroupsAcls* (class in *ciscoisesdk.api.v3_2_beta.security_groups_acls*), 2795
- SecurityGroupToVirtualNetwork* (class in *ciscoisesdk.api.v3_1_0.security_group_to_virtual_network*), 556
- SecurityGroupToVirtualNetwork* (class in *ciscoisesdk.api.v3_1_1.security_group_to_virtual_network*), 1291
- SecurityGroupToVirtualNetwork* (class in *ciscoisesdk.api.v3_1_patch_1.security_group_to_virtual_network*), 2029
- SecurityGroupToVirtualNetwork* (class in *ciscoisesdk.api.v3_2_beta.security_group_to_virtual_network*), 2779
- SelfRegisteredPortal* (class in *ciscoisesdk.api.v3_1_0.self_registered_portal*), 579
- SelfRegisteredPortal* (class in *ciscoisesdk.api.v3_1_1.self_registered_portal*), 1315
- SelfRegisteredPortal* (class in *ciscoisesdk.api.v3_1_patch_1.self_registered_portal*), 1991

- 2053
- SelfRegisteredPortal (class in *ciscoisesdk.api.v3_2_beta.self_registered_portal*), 2803
- session (*IdentityServicesEngineAPI* property), 34
- session_disconnect() (*Misc* method), 367, 1090, 1828, 2577
- session_ers (*IdentityServicesEngineAPI* property), 34
- session_mnt (*IdentityServicesEngineAPI* property), 34
- session_px_grid (*IdentityServicesEngineAPI* property), 34
- session_reauthentication_by_mac() (*Misc* method), 366, 1089, 1827, 2576
- session_ui (*IdentityServicesEngineAPI* property), 34
- SessionDirectory (class in *ciscoisesdk.api.v3_1_0.session_directory*), 607
- SessionDirectory (class in *ciscoisesdk.api.v3_1_1.session_directory*), 1342
- SessionDirectory (class in *ciscoisesdk.api.v3_1_patch_1.session_directory*), 2080
- SessionDirectory (class in *ciscoisesdk.api.v3_2_beta.session_directory*), 2830
- set_all_cells_status() (*EgressMatrixCell* method), 226, 944, 1682, 2431
- set_data_connect_service() (*DataconnectServices* method), 2370
- set_profiler_probe_config() (*NodeServices* method), 1204, 1942, 2692
- set_status() (*EgressMatrixCell* method), 227, 945, 1683, 2432
- set_sxp_interface() (*NodeServices* method), 1203, 1941, 2690
- SgVnMapping (class in *ciscoisesdk.api.v3_1_0.sg_vn_mapping*), 729
- SgVnMapping (class in *ciscoisesdk.api.v3_1_1.sg_vn_mapping*), 1466
- SgVnMapping (class in *ciscoisesdk.api.v3_1_patch_1.sg_vn_mapping*), 2204
- single_request_timeout (*Authentication* property), 35
- single_request_timeout (*IdentityServicesEngineAPI* property), 35
- SmsProvider (class in *ciscoisesdk.api.v3_1_0.sms_provider*), 531
- SmsProvider (class in *ciscoisesdk.api.v3_1_1.sms_provider*), 1266
- SmsProvider (class in *ciscoisesdk.api.v3_1_patch_1.sms_provider*), 2004
- SmsProvider (class in *ciscoisesdk.api.v3_2_beta.sms_provider*), 2754
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_1_0.sponsored_guest_portal*), 637
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_1_1.sponsored_guest_portal*), 1372
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_1_patch_1.sponsored_guest_portal*), 2110
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_2_beta.sponsored_guest_portal*), 2860
- SponsorGroup (class in *ciscoisesdk.api.v3_1_0.sponsor_group*), 610
- SponsorGroup (class in *ciscoisesdk.api.v3_1_1.sponsor_group*), 1345
- SponsorGroup (class in *ciscoisesdk.api.v3_1_patch_1.sponsor_group*), 2083
- SponsorGroup (class in *ciscoisesdk.api.v3_2_beta.sponsor_group*), 2833
- SponsorGroupMember (class in *ciscoisesdk.api.v3_1_0.sponsor_group_member*), 620
- SponsorGroupMember (class in *ciscoisesdk.api.v3_1_1.sponsor_group_member*), 1355
- SponsorGroupMember (class in *ciscoisesdk.api.v3_1_patch_1.sponsor_group_member*), 2093
- SponsorGroupMember (class in *ciscoisesdk.api.v3_2_beta.sponsor_group_member*), 2843
- SponsorPortal (class in *ciscoisesdk.api.v3_1_0.sponsor_portal*), 623
- SponsorPortal (class in *ciscoisesdk.api.v3_1_1.sponsor_portal*), 1358
- SponsorPortal (class in *ciscoisesdk.api.v3_1_patch_1.sponsor_portal*), 2096
- SponsorPortal (class in *ciscoisesdk.api.v3_2_beta.sponsor_portal*), 2846
- status (*ApiError* attribute), 2959
- status (*DownloadFailure* attribute), 2960
- status_code (*ApiError* attribute), 2959
- status_code (*DownloadFailure* attribute), 2960
- status_code (*RestResponse* property), 2958
- Subscriber (class in *ciscoisesdk.api.v3_2_beta.subscriber*), 2878
- SupportBundleDownload (class in *ciscoisesdk.api.v3_1_0.support_bundle_download*), 655
- SupportBundleDownload (class in *ciscoisesdk.api.v3_1_1.support_bundle_download*), 1390
- SupportBundleDownload (class in *ciscois-*

- `esdk.api.v3_1_patch_1.support_bundle_download` (class in `ciscoisesdk.api.v3_1_patch_1.support_bundle_download`), 2128
- `SupportBundleDownload` (class in `ciscoisesdk.api.v3_2_beta.support_bundle_download`), 2884
- `SupportBundleStatus` (class in `ciscoisesdk.api.v3_1_0.support_bundle_status`), 657
- `SupportBundleStatus` (class in `ciscoisesdk.api.v3_1_1.support_bundle_status`), 1392
- `SupportBundleStatus` (class in `ciscoisesdk.api.v3_1_patch_1.support_bundle_status`), 2130
- `SupportBundleStatus` (class in `ciscoisesdk.api.v3_2_beta.support_bundle_status`), 2886
- `SupportBundleTriggerConfiguration` (class in `ciscoisesdk.api.v3_1_0.support_bundle_trigger_configuration`), 660
- `SupportBundleTriggerConfiguration` (class in `ciscoisesdk.api.v3_1_1.support_bundle_trigger_configuration`), 1395
- `SupportBundleTriggerConfiguration` (class in `ciscoisesdk.api.v3_1_patch_1.support_bundle_trigger_configuration`), 2133
- `SupportBundleTriggerConfiguration` (class in `ciscoisesdk.api.v3_2_beta.support_bundle_trigger_configuration`), 2889
- `suspend_by_id()` (`GuestUser` method), 300, 1018, 1756, 2505
- `suspend_by_name()` (`GuestUser` method), 288, 1006, 1744, 2493
- `suspend_guest_user_by_id()` (`GuestUser` method), 299, 1017, 1755, 2504
- `suspend_guest_user_by_name()` (`GuestUser` method), 287, 1005, 1743, 2492
- `SxpConnections` (class in `ciscoisesdk.api.v3_1_0.sxp_connections`), 534
- `SxpConnections` (class in `ciscoisesdk.api.v3_1_1.sxp_connections`), 1269
- `SxpConnections` (class in `ciscoisesdk.api.v3_1_patch_1.sxp_connections`), 2007
- `SxpConnections` (class in `ciscoisesdk.api.v3_2_beta.sxp_connections`), 2757
- `SxpLocalBindings` (class in `ciscoisesdk.api.v3_1_0.sxp_local_bindings`), 542
- `SxpLocalBindings` (class in `ciscoisesdk.api.v3_1_1.sxp_local_bindings`), 1277
- `SxpLocalBindings` (class in `ciscoisesdk.api.v3_1_patch_1.sxp_local_bindings`), 2015
- `SxpLocalBindings` (class in `ciscoisesdk.api.v3_2_beta.sxp_local_bindings`), 2765
- `SxpVpns` (class in `ciscoisesdk.api.v3_1_0.sxp_vpns`), 550
- `SxpVpns` (class in `ciscoisesdk.api.v3_1_1.sxp_vpns`), 1285
- `SxpVpns` (class in `ciscoisesdk.api.v3_1_patch_1.sxp_vpns`), 2023
- `SxpVpns` (class in `ciscoisesdk.api.v3_2_beta.sxp_vpns`), 2773
- `sync_node()` (`NodeDeployment` method), 1195, 1933, 2683
- `sync_node()` (`SyncIseNode` method), 664
- `SyncIseNode` (class in `ciscoisesdk.api.v3_1_0.sync_ise_node`), 664
- `SystemCertificate` (class in `ciscoisesdk.api.v3_1_0.system_certificate`), 666
- `SystemCertificate` (class in `ciscoisesdk.api.v3_1_1.system_certificate`), 1400
- `SystemCertificate` (class in `ciscoisesdk.api.v3_1_patch_1.system_certificate`), 2138
- `SystemCertificate` (class in `ciscoisesdk.api.v3_2_beta.system_certificate`), 2894
- `SystemHealth` (class in `ciscoisesdk.api.v3_1_0.system_health`), 665
- `SystemHealth` (class in `ciscoisesdk.api.v3_1_1.system_health`), 1399
- `SystemHealth` (class in `ciscoisesdk.api.v3_1_patch_1.system_health`), 2137
- `SystemHealth` (class in `ciscoisesdk.api.v3_2_beta.system_health`), 2893

T

- `TacacsCommandSets` (class in `ciscoisesdk.api.v3_1_0.tacacs_command_sets`), 669
- `TacacsCommandSets` (class in `ciscoisesdk.api.v3_1_1.tacacs_command_sets`), 1404
- `TacacsCommandSets` (class in `ciscoisesdk.api.v3_1_patch_1.tacacs_command_sets`), 2142
- `TacacsCommandSets` (class in `ciscoisesdk.api.v3_2_beta.tacacs_command_sets`), 2898
- `TacacsExternalServers` (class in `ciscoisesdk.api.v3_1_0.tacacs_external_servers`), 675
- `TacacsExternalServers` (class in `ciscoisesdk.api.v3_1_1.tacacs_external_servers`),

- 1410
- TacacsExternalServers (class in ciscoesdk.api.v3_1_patch_1.tacacs_external_servers), 2148
- TacacsExternalServers (class in ciscoesdk.api.v3_2_beta.tacacs_external_servers), 2904
- TacacsProfile (class in ciscoesdk.api.v3_1_0.tacacs_profile), 681
- TacacsProfile (class in ciscoesdk.api.v3_1_1.tacacs_profile), 1416
- TacacsProfile (class in ciscoesdk.api.v3_1_patch_1.tacacs_profile), 2154
- TacacsProfile (class in ciscoesdk.api.v3_2_beta.tacacs_profile), 2910
- TacacsServerSequence (class in ciscoesdk.api.v3_1_0.tacacs_server_sequence), 687
- TacacsServerSequence (class in ciscoesdk.api.v3_1_1.tacacs_server_sequence), 1422
- TacacsServerSequence (class in ciscoesdk.api.v3_1_patch_1.tacacs_server_sequence), 2160
- TacacsServerSequence (class in ciscoesdk.api.v3_2_beta.tacacs_server_sequence), 2916
- Tasks (class in ciscoesdk.api.v3_1_0.tasks), 736
- Tasks (class in ciscoesdk.api.v3_1_1.tasks), 1473
- Tasks (class in ciscoesdk.api.v3_1_patch_1.tasks), 2211
- Tasks (class in ciscoesdk.api.v3_2_beta.tasks), 2955
- Telemetry (class in ciscoesdk.api.v3_1_1.telemetry), 1474
- Telemetry (class in ciscoesdk.api.v3_1_patch_1.telemetry), 2212
- Telemetry (class in ciscoesdk.api.v3_2_beta.telemetry), 2956
- TelemetryInformation (class in ciscoesdk.api.v3_1_0.telemetry_information), 694
- TelemetryInformation (class in ciscoesdk.api.v3_1_1.telemetry_information), 1429
- TelemetryInformation (class in ciscoesdk.api.v3_1_patch_1.telemetry_information), 2167
- TelemetryInformation (class in ciscoesdk.api.v3_2_beta.telemetry_information), 2923
- test_aci_connectivity() (AciSettings method), 42, 756, 1494, 2232
- test_connector() (Edda method), 2429
- text (RestResponse property), 2958
- to_json() (MyDict method), 2958
- TrustSecConfiguration (class in ciscoesdk.api.v3_1_0.trust_sec_configuration), 698
- TrustSecConfiguration (class in ciscoesdk.api.v3_1_1.trust_sec_configuration), 1433
- TrustSecConfiguration (class in ciscoesdk.api.v3_1_patch_1.trust_sec_configuration), 2171
- TrustSecConfiguration (class in ciscoesdk.api.v3_2_beta.trust_sec_configuration), 2927
- TrustSecSxp (class in ciscoesdk.api.v3_1_0.trust_sec_sxp), 700
- TrustSecSxp (class in ciscoesdk.api.v3_1_1.trust_sec_sxp), 1435
- TrustSecSxp (class in ciscoesdk.api.v3_1_patch_1.trust_sec_sxp), 2173
- TrustSecSxp (class in ciscoesdk.api.v3_2_beta.trust_sec_sxp), 2929
- ## U
- ui_base_url (IdentityServicesEngineAPI property), 34
- unregister_service() (Provider method), 495, 1231, 1969, 2719
- update() (BackupAndRestore method), 129, 843, 1581, 2319
- update_aci_settings_by_id() (AciSettings method), 42, 756, 1494, 2232
- update_allowed_protocol_by_id() (AllowedProtocols method), 84, 798, 1536, 2274
- update_anc_policy_by_id() (AncPolicy method), 93, 807, 1545, 2283
- update_authorization_profile_by_id() (AuthorizationProfile method), 105, 819, 1557, 2295
- update_by_id() (AciSettings method), 44, 758, 1496, 2234
- update_by_id() (AllowedProtocols method), 86, 800, 1538, 2276
- update_by_id() (AncPolicy method), 94, 808, 1546, 2284
- update_by_id() (AuthorizationProfile method), 106, 820, 1558, 2296
- update_by_id() (ByodPortal method), 120, 834, 1572, 2310
- update_by_id() (CertificateProfile method), 135, 849, 1587, 2325
- update_by_id() (DeviceAdministrationAuthenticationRules method), 176, 894, 1632, 2374
- update_by_id() (DeviceAdministrationAuthorizationExceptionRules method), 180, 898, 1636, 2379

- `update_by_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 184, 902, 1640, 2383
- `update_by_id()` (*DeviceAdministrationAuthorizationRules method*), 189, 907, 1645, 2388
- `update_by_id()` (*DeviceAdministrationConditions method*), 200, 918, 1656, 2399
- `update_by_id()` (*DeviceAdministrationNetworkConditions method*), 206, 924, 1662, 2406
- `update_by_id()` (*DeviceAdministrationPolicySet method*), 211, 929, 1667, 2411
- `update_by_id()` (*DeviceAdministrationTimeDateConditions method*), 218, 936, 1674, 2419
- `update_by_id()` (*DownloadableAcl method*), 221, 939, 1677, 2422
- `update_by_id()` (*EgressMatrixCell method*), 229, 947, 1685, 2434
- `update_by_id()` (*Endpoint method*), 708, 1443, 2181, 2937
- `update_by_id()` (*EndpointIdentityGroup method*), 240, 958, 1696, 2445
- `update_by_id()` (*ExternalRadiusServer method*), 249, 967, 1705, 2454
- `update_by_id()` (*FilterPolicy method*), 255, 973, 1711, 2460
- `update_by_id()` (*GuestSmtNotificationConfiguration method*), 265, 983, 1721, 2470
- `update_by_id()` (*GuestSsid method*), 271, 989, 1727, 2476
- `update_by_id()` (*GuestType method*), 279, 997, 1735, 2484
- `update_by_id()` (*GuestUser method*), 295, 1013, 1751, 2500
- `update_by_id()` (*HotspotPortal method*), 311, 1029, 1767, 2516
- `update_by_id()` (*IdentityGroups method*), 336, 1054, 1792, 2541
- `update_by_id()` (*IdentitySequence method*), 342, 1060, 1798, 2547
- `update_by_id()` (*InternalUser method*), 352, 1070, 1808, 2557
- `update_by_id()` (*IpToSgtMapping method*), 319, 1037, 1775, 2524
- `update_by_id()` (*IpToSgtMappingGroup method*), 328, 1046, 1784, 2533
- `update_by_id()` (*MyDevicePortal method*), 378, 1101, 1839, 2588
- `update_by_id()` (*NativeSupplicantProfile method*), 384, 1108, 1846, 2595
- `update_by_id()` (*NbarApp method*), 719, 1454, 2192
- `update_by_id()` (*NetworkAccessAuthenticationRules method*), 391, 1115, 1853, 2602
- `update_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 395, 1119, 1857, 2606
- `update_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 400, 1124, 1862, 2611
- `update_by_id()` (*NetworkAccessAuthorizationRules method*), 404, 1128, 1866, 2615
- `update_by_id()` (*NetworkAccessConditions method*), 415, 1139, 1877, 2626
- `update_by_id()` (*NetworkAccessNetworkConditions method*), 429, 1154, 1892, 2641
- `update_by_id()` (*NetworkAccessPolicySet method*), 434, 1159, 1897, 2646
- `update_by_id()` (*NetworkAccessTimeDateConditions method*), 442, 1167, 1905, 2654
- `update_by_id()` (*NetworkDevice method*), 453, 1178, 1916, 2665
- `update_by_id()` (*NetworkDeviceGroup method*), 461, 1186, 1924, 2674
- `update_by_id()` (*PortalGlobalSetting method*), 481, 1217, 1955, 2705
- `update_by_id()` (*PortalTheme method*), 485, 1222, 1960, 2709
- `update_by_id()` (*RadiusServerSequence method*), 512, 1248, 1986, 2736
- `update_by_id()` (*RestidStore method*), 521, 1257, 1995, 2745
- `update_by_id()` (*SecurityGroups method*), 566, 1301, 2039, 2789
- `update_by_id()` (*SecurityGroupsAcls method*), 574, 1309, 2047, 2797
- `update_by_id()` (*SecurityGroupToVirtualNetwork method*), 558, 1293, 2031, 2781
- `update_by_id()` (*SelfRegisteredPortal method*), 602, 1337, 2075, 2825
- `update_by_id()` (*SgVnMapping method*), 735, 1472, 2210
- `update_by_id()` (*SponsoredGuestPortal method*), 651, 1386, 2124, 2874
- `update_by_id()` (*SponsorGroup method*), 616, 1351, 2089, 2839
- `update_by_id()` (*SponsorPortal method*), 633, 1368, 2106, 2856
- `update_by_id()` (*SxpConnections method*), 536, 1271, 2009, 2759
- `update_by_id()` (*SxpLocalBindings method*), 544, 1279, 2017, 2767
- `update_by_id()` (*TacacsCommandSets method*), 672, 1407, 2145, 2901
- `update_by_id()` (*TacacsExternalServers method*), 678, 1413, 2151, 2907
- `update_by_id()` (*TacacsProfile method*), 684, 1419, 2157, 2913
- `update_by_id()` (*TacacsServerSequence method*), 690, 1425, 2163, 2919
- `update_by_id()` (*VirtualNetwork method*), 743, 1481,

2219

`update_by_name()` (*DeviceAdministrationConditions* method), 196, 914, 1652, 2395

`update_by_name()` (*GuestUser* method), 290, 1008, 1746, 2495

`update_by_name()` (*InternalUser* method), 349, 1067, 1805, 2554

`update_by_name()` (*NetworkAccessConditions* method), 411, 1135, 1873, 2622

`update_by_name()` (*NetworkAccessDictionary* method), 418, 1142, 1880, 2630

`update_by_name()` (*NetworkAccessDictionaryAttribute* method), 423, 1147, 1885, 2634

`update_by_name()` (*NetworkDevice* method), 450, 1175, 1913, 2663

`update_by_name()` (*Repository* method), 529, 1265, 2003, 2753

`update_by_name()` (*RestidStore* method), 519, 1255, 1993, 2743

`update_byod_portal_by_id()` (*ByodPortal* method), 120, 834, 1572, 2310

`update_certificate_profile_by_id()` (*CertificateProfile* method), 133, 847, 1585, 2323

`update_configuration()` (*Configuration* method), 2363

`update_connector_config_by_connector_name()` (*Edda* method), 2427

`update_dataconnect_password()` (*DataconnectServices* method), 2368

`update_dataconnect_password_expiry()` (*DataconnectServices* method), 2369

`update_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules* method), 175, 893, 1631, 2373

`update_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules* method), 188, 906, 1644, 2387

`update_device_admin_condition_by_id()` (*DeviceAdministrationConditions* method), 198, 916, 1654, 2397

`update_device_admin_condition_by_name()` (*DeviceAdministrationConditions* method), 195, 913, 1651, 2394

`update_device_admin_local_exception_rule_by_id()` (*DeviceAdministrationAuthorizationExceptionRules* method), 179, 897, 1635, 2378

`update_device_admin_network_condition_by_id()` (*DeviceAdministrationNetworkConditions* method), 206, 924, 1662, 2405

`update_device_admin_policy_set_by_id()` (*DeviceAdministrationPolicySet* method), 210, 928, 1666, 2410

`update_device_admin_policy_set_global_exception_rule_by_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 184, 902, 1640, 2382

`update_device_admin_time_condition_by_id()` (*DeviceAdministrationTimeDateConditions* method), 217, 935, 1673, 2417

`update_downloadable_acl_by_id()` (*DownloadableAcl* method), 221, 939, 1677, 2421

`update_egress_matrix_cell_by_id()` (*EgressMatrixCell* method), 228, 946, 1684, 2433

`update_email()` (*GuestType* method), 277, 995, 1733, 2482

`update_email()` (*GuestUser* method), 292, 1010, 1748, 2497

`update_endpoint_by_id()` (*Endpoint* method), 707, 1442, 2180, 2936

`update_endpoint_group_by_id()` (*EndpointIdentityGroup* method), 240, 958, 1696, 2445

`update_external_radius_server_by_id()` (*ExternalRadiusServer* method), 248, 966, 1704, 2453

`update_filter_policy_by_id()` (*FilterPolicy* method), 254, 972, 1710, 2459

`update_guest_smtp_notification_settings_by_id()` (*GuestSmtpNotificationConfiguration* method), 264, 982, 1720, 2469

`update_guest_ssid_by_id()` (*GuestSsid* method), 270, 988, 1726, 2475

`update_guest_type_by_id()` (*GuestType* method), 278, 996, 1734, 2483

`update_guest_type_email()` (*GuestType* method), 277, 995, 1733, 2482

`update_guest_type_sms()` (*GuestType* method), 277, 995, 1733, 2482

`update_guest_user_by_id()` (*GuestUser* method), 294, 1012, 1750, 2499

`update_guest_user_by_name()` (*GuestUser* method), 289, 1007, 1745, 2494

`update_guest_user_email()` (*GuestUser* method), 292, 1010, 1748, 2497

`update_guest_user_sms()` (*GuestUser* method), 292, 1010, 1748, 2497

`update_hotspot_portal_by_id()` (*HotspotPortal* method), 310, 1028, 1766, 2515

`update_identity_group_by_id()` (*IdentityGroups* method), 335, 1053, 1791, 2540

`update_identity_sequence_by_id()` (*IdentitySequence* method), 342, 1060, 1798, 2547

`update_internal_user_by_id()` (*InternalUser* method), 350, 1068, 1806, 2555

`update_internal_user_by_name()` (*InternalUser* method), 348, 1066, 1804, 2553

`update_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping* method), 318, 1036, 1774, 2523

`update_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup* method), 327, 1045,

- 1783, 2532
- `update_my_device_portal_by_id()` (*MyDevicePortal* method), 377, 1100, 1838, 2587
- `update_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile* method), 384, 1108, 1846, 2595
- `update_nbar_app_by_id()` (*NbarApp* method), 718, 1453, 2191
- `update_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules* method), 390, 1114, 1852, 2601
- `update_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules* method), 403, 1127, 1865, 2614
- `update_network_access_condition_by_id()` (*NetworkAccessConditions* method), 413, 1137, 1875, 2624
- `update_network_access_condition_by_name()` (*NetworkAccessConditions* method), 409, 1133, 1871, 2620
- `update_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute* method), 421, 1145, 1883, 2633
- `update_network_access_dictionary_by_name()` (*NetworkAccessDictionary* method), 417, 1141, 1879, 2629
- `update_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules* method), 394, 1118, 1856, 2606
- `update_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions* method), 428, 1153, 1891, 2640
- `update_network_access_policy_set_by_id()` (*NetworkAccessPolicySet* method), 433, 1158, 1896, 2645
- `update_network_access_policy_set_global_exception_rule_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 399, 1123, 1861, 2610
- `update_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions* method), 440, 1165, 1903, 2653
- `update_network_device_by_id()` (*NetworkDevice* method), 451, 1176, 1914, 2664
- `update_network_device_by_name()` (*NetworkDevice* method), 449, 1174, 1912, 2662
- `update_network_device_group_by_id()` (*NetworkDeviceGroup* method), 460, 1185, 1923, 2673
- `update_node()` (*NodeDeployment* method), 467, 1192, 1930, 2680
- `update_node_group()` (*NodeGroup* method), 471, 1198, 1936, 2686
- `update_pan_ha()` (*PanHa* method), 1211, 1949, 2698
- `update_portal_global_setting_by_id()` (*PortalGlobalSetting* method), 480, 1217, 1955, 2704
- `update_portal_theme_by_id()` (*PortalTheme* method), 485, 1221, 1959, 2709
- `update_proxy_connection()` (*Proxy* method), 1459, 2197, 2948
- `update_radius_server_sequence_by_id()` (*RadiusServerSequence* method), 511, 1247, 1985, 2735
- `update_repository()` (*Repository* method), 528, 1264, 2002, 2752
- `update_rest_id_store_by_id()` (*RestidStore* method), 521, 1257, 1995, 2745
- `update_rest_id_store_by_name()` (*RestidStore* method), 519, 1255, 1993, 2743
- `update_scheduled_config_backup()` (*BackupAndRestore* method), 128, 842, 1580, 2318
- `update_security_group_by_id()` (*SecurityGroups* method), 565, 1300, 2038, 2788
- `update_security_groups_acl_by_id()` (*SecurityGroupsAcls* method), 573, 1308, 2046, 2796
- `update_security_groups_to_vn_to_vlan_by_id()` (*SecurityGroupToVirtualNetwork* method), 557, 1292, 2030, 2780
- `update_self_registered_portal_by_id()` (*SelfRegisteredPortal* method), 602, 1337, 2075, 2825
- `update_sg_vn_mapping_by_id()` (*SgVnMapping* method), 734, 1471, 2209
- `update_sms()` (*GuestType* method), 278, 996, 1734, 2483
- `update_sms()` (*GuestUser* method), 293, 1011, 1749, 2498
- `update_sponsor_group_by_id()` (*SponsorGroup* method), 615, 1350, 2088, 2838
- `update_sponsor_portal_by_id()` (*SponsorPortal* method), 632, 1367, 2105, 2855
- `update_sponsored_guest_portal_by_id()` (*SponsoredGuestPortal* method), 650, 1385, 2123, 2873
- `update_subscriber()` (*Subscriber* method), 2882
- `update_sxp_connections_by_id()` (*SxpConnections* method), 535, 1271, 2009, 2759
- `update_sxp_local_bindings_by_id()` (*SxpLocalBindings* method), 543, 1278, 2016, 2766
- `update_system_certificate()` (*Certificates* method), 156, 874, 1612, 2350
- `update_tacacs_command_sets_by_id()` (*TacacsCommandSets* method), 671, 1406, 2144, 2900
- `update_tacacs_external_servers_by_id()` (*TacacsExternalServers* method), 677, 1412, 2150, 2906

`update_tacacs_profile_by_id()` (*TacacsProfile* method), 683, 1418, 2156, 2912

`update_tacacs_server_sequence_by_id()` (*TacacsServerSequence* method), 689, 1424, 2162, 2918

`update_tier_state_info()` (*Licensing* method), 1079, 1817, 2566

`update_transport_gateway()` (*Telemetry* method), 1474, 2212, 2957

`update_trusted_certificate()` (*Certificates* method), 164, 881, 1619, 2357

`update_virtual_network_by_id()` (*VirtualNetwork* method), 742, 1480, 2218

`update_vn_vlan_mapping_by_id()` (*VnVlanMapping* method), 749, 1487, 2225

`username` (*IdentityServicesEngineAPI* property), 34

`uses_api_gateway` (*IdentityServicesEngineAPI* property), 34

`uses_csrf_token` (*IdentityServicesEngineAPI* property), 35

V

`validator` (*IdentityServicesEngineAPI* property), 35

`verify` (*Authentication* property), 35

`verify` (*IdentityServicesEngineAPI* property), 35

`version` (*IdentityServicesEngineAPI* property), 35

`VersionAndPatch` (class in *ciscoisesdk.api.v3_1_0.version_and_patch*), 701

`VersionAndPatch` (class in *ciscoisesdk.api.v3_1_1.version_and_patch*), 1436

`VersionAndPatch` (class in *ciscoisesdk.api.v3_1_patch_1.version_and_patch*), 2174

`VersionAndPatch` (class in *ciscoisesdk.api.v3_2_beta.version_and_patch*), 2930

`VersionError`, 2959

`VersionInfo` (class in *ciscoisesdk.api.v3_1_0.version_info*), 702

`VersionInfo` (class in *ciscoisesdk.api.v3_1_1.version_info*), 1437

`VersionInfo` (class in *ciscoisesdk.api.v3_1_patch_1.version_info*), 2175

`VersionInfo` (class in *ciscoisesdk.api.v3_2_beta.version_info*), 2931

`VirtualNetwork` (class in *ciscoisesdk.api.v3_1_0.virtual_network*), 737

`VirtualNetwork` (class in *ciscoisesdk.api.v3_1_1.virtual_network*), 1475

`VirtualNetwork` (class in *ciscoisesdk.api.v3_1_patch_1.virtual_network*), 2213

`VnVlanMapping` (class in *ciscoisesdk.api.v3_1_0.vn_vlan_mapping*), 744

`VnVlanMapping` (class in *ciscoisesdk.api.v3_1_1.vn_vlan_mapping*), 1482

`VnVlanMapping` (class in *ciscoisesdk.api.v3_1_patch_1.vn_vlan_mapping*), 2220

W

`wait_on_rate_limit` (*IdentityServicesEngineAPI* property), 35