
ciscoisesdk Documentation

Release 1.2.0

Nov 24, 2021

CONTENTS

| | | |
|----------|---|-------------|
| 1 | The User Guide | 3 |
| 1.1 | Installation | 3 |
| 1.2 | Introduction | 4 |
| 1.3 | Quickstart | 7 |
| 1.4 | User API Doc | 20 |
| 2 | The Development Community | 1089 |
| 2.1 | Contributor Covenant Code of Conduct | 1089 |
| 2.2 | Contributing | 1090 |
| 3 | General Information about the Identity Services Engine Service | 1093 |
| 3.1 | What is Identity Services Engine? | 1093 |
| 3.2 | Identity Services Engine for Developers | 1093 |
| | Python Module Index | 1095 |
| | Index | 1097 |

Simple, lightweight, scalable Python API wrapper for the Identity Services Engine APIs

Welcome to the docs! `ciscoisesdk` is a *community developed* Pythonic wrapping of the Identity Services Engine APIs (for API versions: 3.0.0 and 3.1.0). The package represents all of the Cisco Identity Services Engine API interactions via native Python tools. Making working with the Cisco Identity Services Engine APIs in Python a *native* and *natural* experience.

`ciscoisesdk` helps you get things done faster. We take care of the API semantics, and you can focus on writing your code.

With `ciscoisesdk`, you can easily:

- Interact with the Identity Services Engine APIs in an interactive Python session
- Quickly create code that enables you get something done in Identity Services Engine
- Leverage the API wrapper to cleanly add Identity Services Engine functionality to your project without having to write the boilerplate code for working with the Identity Services Engine APIs

To *dive in* and see how `ciscoisesdk` makes your life better, check out the [Quickstart](#)!

| |
|---|
| Warning: The minimum supported version is ISE 3.1. Future releases may drop the ISE version 3.0.0. |
|---|

THE USER GUIDE

1.1 Installation

1.1.1 PIP Install

ciscoisesdk is available via PIP and the [Python Package Index \(PyPI\)](#). To install ciscoisesdk, simply run this command from your terminal of choice:

```
$ pip install ciscoisesdk
```

The ciscoisesdk package is distributed as a *source distribution* (no binaries).

1.1.2 PIP Upgrade

To ensure that you have the latest version, check-for and install upgrades via PIP:

```
$ pip install ciscoisesdk --upgrade
```

1.1.3 Get the Source Code

ciscoisesdk is developed on GitHub. If you like and use this package, please take a few seconds to Star the package on the [CiscoISE/ciscoisesdk](#) GitHub page. Your feedback and contributions are always welcome.

Use the following command to download the source code (GIT repository):

```
$ git clone https://github.com/CiscoISE/ciscoisesdk.git
```

You can then install the package to your environment, with the following command:

```
$ python setup.py install
```

Copyright (c) 2021 Cisco and/or its affiliates.

1.2 Introduction

1.2.1 Work with the Identity Services Engine APIs in Native Python!

Sure, working with the Identity Services Engine APIs is easy (see [api_docs](#)). They are RESTful, naturally structured, require only a simple Access Token for authentication, and the data is elegantly represented in intuitive JSON. What could be easier?

```
import requests

URL = 'https://dcloud-dna-ise-rtp.cisco.com/ers/config/networkdevice'
ACCESS_TOKEN = '<your_access_token>'

filter_query = '<filter_query>'
headers = {'authorization': ACCESS_TOKEN,
           'Content-type': 'application/json;charset=utf-8'}
params_data = { 'filter': filter_query }
response = requests.get(URL, params=params_data, headers=headers)
if response.status_code == 200:
    device_response = response.json
    if device_response.get('SearchResult') and device_response['SearchResult'].get(
↳ 'resources'):
        for device in device_response['SearchResult']['resources']:
            print('{:20s}{}'.format(device['id'], device['name']))
else:
    # Oops something went wrong... Better do something about it.
    print(response.status_code, response.text)
```

Like I said, EASY. However, in use, the code can become rather repetitive...

- You have to setup the environment every time
- You have to remember URLs, request parameters and JSON formats (or reference the docs)
- You have to parse the returned JSON and work with multiple layers of list and dictionary indexes

Enter **ciscoisesdk**, a simple API wrapper that wraps all of the Identity Services Engine API calls and returned JSON objects within native Python objects and methods.

With **ciscoisesdk**, the above Python code can be consolidated to the following:

```
from ciscoisesdk import api

api_ = api.IdentityServicesEngineAPI(username='admin',
                                     password='C1sco12345',
                                     uses_api_gateway=True,
                                     base_url='https://dcloud-dna-ise-rtp.cisco.com',
                                     version='3.1.0',
                                     verify=True)
# Or even just api_ = api.IdentityServicesEngineAPI(username='admin', password='C1sco12345
↳ ') as others have those values by default.
try:
    device_response = api_.network_device.get_network_device(filter='name.EQ.Test').
↳ response
    if device_response.SearchResult and device_response.SearchResult.resources:
```

(continues on next page)

(continued from previous page)

```

        for device in device_response.SearchResult.resources:
            print('{:20s}{}'.format(device.hostname, device.upTime))
except ApiError as e:
    print(e)

```

ciscoisesdk handles all of this for you:

- Reads your Identity Services Engine credentials from environment variables (IDENTITY_SERVICES_ENGINE_ENCODED_AUTH, IDENTITY_SERVICES_ENGINE_USERNAME, IDENTITY_SERVICES_ENGINE_PASSWORD)
- Reads your Identity Services Engine API version from environment variable IDENTITY_SERVICES_ENGINE_VERSION. Supported versions: 3.0.0 and 3.1.0. Now with version and base_url, you have more control.
- Controls whether to verify the server's TLS certificate or not according to the verify parameter.
- Reads your Identity Services Engine debug from environment variable IDENTITY_SERVICES_ENGINE_DEBUG. Boolean, it controls whether to log information about Identity Services Engine APIs' request and response process.
- Wraps and represents all Identity Services Engine API calls as a simple hierarchical tree of native-Python methods (with default arguments provided everywhere possible!)
- If your Python IDE supports **auto-completion** (like [PyCharm](#)), you can navigate the available methods and object attributes right within your IDE
- Represents all returned JSON objects as native Python objects - you can access all of the object's attributes using native *dot.syntax*
- **Automatic Rate-Limit Handling** Sending a lot of requests to Identity Services Engine? Don't worry; we have you covered. Identity Services Engine will respond with a rate-limit response, which will automatically be caught and "handled" for you. Your requests and script will automatically be "paused" for the amount of time specified by Identity Services Engine, while we wait for the Identity Services Engine rate-limit timer to cool down. After the cool-down, your request will automatically be retried, and your script will continue to run as normal. Handling all of this requires zero (0) changes to your code - you're welcome.

Just know that if you are sending a lot of requests, your script might take longer to run if your requests are getting rate limited.

All of this, combined, lets you do powerful things simply:

```

from ciscoisesdk import IdentityServicesEngineAPI
from ciscoisesdk.exceptions import ApiError

# Get allowed protocols
search_result = api_.allowed_protocols.get_all().response.SearchResult
if search_result and search_result.resources:
    for resource in search_result.resources:
        resource_detail = api_.allowed_protocols.get_by_id(resource.id).response.
↪ AllowedProtocols
        print("Id {} \nName {} \nallowChap {} \n".format(resource_detail.id, resource_detail.
↪ name, resource_detail.allowChap))

# Filter network device
device_list_response = api_.network_device.get_all(filter='name.EQ.ISE_EST_Local_Host_19
↪ ')

```

(continues on next page)

(continued from previous page)

```

device_responses = device_list_response.response.SearchResult.resources
device_response = device_responses[0]

# Get network device detail
device_response_detail = api_.network_device.get_by_id(device_response.id).response.
↳NetworkDevice

# Delete network device
delete_device = api_.network_device.delete_by_id(device_response.id)

# Create network device
try:
    network_device_response = api_.network_device.create(name='ISE_EST_Local_Host_19',
↳network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
    print("Created, new Location {}".format(network_device_response.headers.Location))
except api_Error as e:
    print(e)

```

Head over to the [Quickstart](#) page to begin working with the **Identity Services Engine APIs in native Python!**

1.2.2 MIT License

ciscoisesdk is currently licensed under the [MIT Open Source License](#), and distributed as a source distribution (no binaries) via [PyPI](#), and the complete [source code](#) is available on GitHub.

1.2.3 ciscoisesdk License

MIT License

Copyright (c) 2021 Cisco and/or its affiliates.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Copyright (c) 2021 Cisco and/or its affiliates.

1.3 Quickstart

Dive in! ...to get started using the ciscoisesdk package:

Make sure that you have:

- ciscoisesdk *installed*
- ciscoisesdk *upgraded to the latest version*

1.3.1 Pass your Identity Services Engine Access Token

To interact with the Identity Services Engine APIs, you must have a **Identity Services Engine Access Token**. A Identity Services Engine Access Token is how the Identity Services Engine APIs validate access and identify the requesting user.

As a [best practice](#), you can store your Identity Services Engine ‘credentials’ as an environment variables in your development or production environment.

By default, ciscoisesdk will look for the following environment variables to create new connection objects:

- `IDENTITY_SERVICES_ENGINE_DEBUG` - Tells the SDK whether to log request and response information. Useful for debugging and seeing what is going on under the hood. Defaults to False.
- `IDENTITY_SERVICES_ENGINE_VERSION` - Identity Services Engine API version to use. Defaults to ‘3.1.0’.
- `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - It takes priority. It is the *username:password* encoded in base 64. For example ‘ZGV2bmV0dXNlcjpaXNjbzEyMyEK’ which decoded is ‘devnetuser:Cisco123!’
- `IDENTITY_SERVICES_ENGINE_USERNAME` - HTTP Basic Auth username.
- `IDENTITY_SERVICES_ENGINE_PASSWORD` - HTTP Basic Auth password.
- `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` - Enables or disables the usage of the API Gateway. Defaults to True.
- `IDENTITY_SERVICES_ENGINE_BASE_URL` - The base URL to be prefixed to the individual API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is True. Defaults to ‘<https://dcloud-dna-ise-rtp.cisco.com>’.
- `IDENTITY_SERVICES_ENGINE_UI_BASE_URL` - The UI base URL to be prefixed to the individual ISE UI API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_ERS_BASE_URL` - The ERS base URL to be prefixed to the individual ISE ERS API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_MNT_BASE_URL` - The MNT base URL to be prefixed to the individual ISE MNT API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_PX_GRID_BASE_URL` - The `PX_GRID` base URL to be prefixed to the individual ISE `PX_GRID` API endpoint suffixes. It is used if the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` is False.
- `IDENTITY_SERVICES_ENGINE_SINGLE_REQUEST_TIMEOUT` - Timeout (in seconds) for RESTful HTTP requests. Defaults to 60.
- `IDENTITY_SERVICES_ENGINE_WAIT_ON_RATE_LIMIT` - Enables or disables automatic rate-limit handling. Defaults to True.
- `IDENTITY_SERVICES_ENGINE_VERIFY` - Controls whether to verify the server’s TLS certificate or not. Defaults to True.

However, you choose to set it, if you have `IDENTITY_SERVICES_ENGINE_VERSION`, `IDENTITY_SERVICES_ENGINE_USERNAME` and `IDENTITY_SERVICES_ENGINE_PASSWORD`, or `IDENTITY_SERVICES_ENGINE_VERSION` and `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` environment variables, you are good to go. `ciscoisesdk` will use them to create your access token when creating new *IdentityServicesEngineAPI* objects.

If you don't want to set your credentials as environment variables, you can manually provide them as parameters when creating a *IdentityServicesEngineAPI* object.

Note: The `ciscoisesdk` assumes that the ERS APIs and OpenAPIs are enabled. If `uses_api_gateway` is `True`, the `ciscoisesdk` assumes that your ISE API Gateway is enabled as well.

1.3.2 Set credentials as environment variables

There are many places and diverse ways that you can set an environment variable, which can include:

- A setting within your development IDE
- A setting in your container / PaaS service
- A statement in a shell script that configures and launches your app

It can be as simple as setting it in your CLI before running your script...

```
$ IDENTITY_SERVICES_ENGINE_USERNAME=your_username_here
$ IDENTITY_SERVICES_ENGINE_PASSWORD=your_password_here
$ python myscript.py
```

...or putting your credentials in a shell script that you source when your shell starts up or before you run a script:

```
$ cat mycredentials.sh
export IDENTITY_SERVICES_ENGINE_ENCODED_AUTH=your_encoded_auth_here
$ source mycredentials.sh
$ python myscript.py
```

1.3.3 Create a *IdentityServicesEngineAPI* “Connection Object”

To make interacting with the Identity Services Engine APIs as simple and intuitive as possible, all of the APIs have ‘wrapped’ underneath a single interface. To get started, import the *IdentityServicesEngineAPI* class and create an API “connection object”.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI()
```

As discussed above (*Pass your Identity Services Engine Access Token*), `ciscoisesdk` defaults to pulling from environment variables to generate your access token. If you do not have those environment variables set and you try to create a new *IdentityServicesEngineAPI* object without providing them, a *AccessTokenError* will be raised (a *ciscoisesdkException* subclass).

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
```

(continues on next page)

(continued from previous page)

```
File "ciscoisesdk/api/__init__.py", line 356, in __init__
    raise AccessTokenError(error_message)
AccessTokenError: You need an access token to interact with the Identity Services Engine APIs. Identity Services Engine uses HTTP Basic Auth to create an access token. You must provide the username and password or just the encoded_auth, either by setting each parameter or its environment variable counterpart (IDENTITY_SERVICES_ENGINE_USERNAME, IDENTITY_SERVICES_ENGINE_PASSWORD, IDENTITY_SERVICES_ENGINE_ENCODED_AUTH).
```

If you don't provide a known version and try to create a new *IdentityServicesEngineAPI*, a *VersionError* will be raised.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> api = IdentityServicesEngineAPI(username='devnetuser',
                                   password='Cisco123!',
                                   base_url='https://dcloud-dna-ise-rtp.cisco.com',
                                   version='0.1.12')

Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "ciscoisesdk/api/__init__.py", line 344, in __init__
    raise VersionError(error_message)
VersionError: Unknown API version, known versions are 3.0.0 and 3.1.0.
```

Use the arguments to manually provide enough information for the HTTP Basic Auth process, when creating a new *IdentityServicesEngineAPI* connection object.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using encoded_auth, with Identity Services Engine API version 3.1.0
>>> api = IdentityServicesEngineAPI(encoded_auth='YWRtaW46QzFzY28xMjM0NQo=',
                                   base_url="https://dcloud-dna-ise-rtp.cisco.com",
                                   version='3.1.0',
                                   uses_api_gateway=True)
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using username, and password, with ISE API version 3.1.0
>>> api = IdentityServicesEngineAPI(username='admin', password='Cisco12345',
                                   uses_api_gateway=True,
                                   base_url="https://dcloud-dna-ise-rtp.cisco.com",
                                   version='3.1.0')
```

Use the arguments to provide the URLs required depending on the `uses_api_gateway` value.

Note: If `uses_api_gateway` is `True`, the `ciscoisesdk` assumes that your ISE API Gateway is enabled.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # Using API Gateway (since it was enabled on ISE)
>>> api = IdentityServicesEngineAPI(username='admin',
                                   password='Cisco12345',
                                   uses_api_gateway=True,
                                   base_url='https://dcloud-dna-ise-rtp.cisco.com',
```

(continues on next page)

(continued from previous page)

```

...                               version='3.1.0',
...                               verify=True)
>>> # Not using API Gateway
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!',
...                               uses_api_gateway=False,
...                               ers_base_url="https://dcloud-dna-ise-rtp.cisco.
↳com:9060",
...                               ui_base_url="https://dcloud-dna-ise-rtp.cisco.com:443
↳",
...                               mnt_base_url="https://dcloud-dna-ise-rtp.cisco.
↳com:443",
...                               px_grid_base_url="https://dcloud-dna-ise-rtp.cisco.
↳com:8910",
...                               version='3.1.0')

```

Note that this can be very useful if you are reading authentication credentials from a file or database and/or when you want to create more than one connection object.

```

>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> kingston_auth = 'ZG5hY2VudGVydXNlcjpDaXNjbzEyMyEK'
>>> london_auth = ('london', 'rcx0cf43!')
>>> kingston_api = IdentityServicesEngineAPI(encoded_auth=kingston_auth, base_url=
↳"https://dcloud-dna-ise-rtp.cisco.com", version='3.1.0')
>>> london_api = IdentityServicesEngineAPI(*london_auth, base_url="https://128.107.71.
↳199:443",
...                                       version='3.1.0', uses_api_gateway=True) # *
↳Unpacks tuple

```

1.3.4 API Gateway

If `uses_api_gateway` is `True`, the `ciscoisesdk` assumes that the API Gateway is enabled.

If `uses_api_gateway` is `True` you only need to set your `base_url`.

If `uses_api_gateway` is `False` you need to set the `ers_base_url`, `ui_base_url`, `mnt_base_url` and `px_grid_base_url`.

Warning:

1. Ensure that you have enabled the ERS APIs and OpenAPIs.
2. Make sure to check the ISE settings for the API Gateway, and set the `uses_api_gateway` accordingly.

If you don't provide the URLs necessary and try to create a new `IdentityServicesEngineAPI`, a `TypeError` will be raised.

```

>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> # Create a IdentityServicesEngineAPI connection object;
>>> # it uses Identity Services Engine username and password, with ISE API version 3.1.0
>>> # The base_url used by default is `from ciscoisesdk.config import DEFAULT_BASE_URL`
>>> api = IdentityServicesEngineAPI(username='admin',
...                               password='Cisco12345',
...                               uses_api_gateway=True,

```

(continues on next page)

(continued from previous page)

```

...         base_url=None,
...         version='3.1.0',
...         verify=True)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    api = IdentityServicesEngineAPI(username='admin',
  File "ciscoisesdk/api/__init__.py", line 336, in __init__
  File "ciscoisesdk/utils.py", line 165, in check_type
TypeError: We were expecting to receive an instance of one of the following types:
'basestring'; but instead we received None which is a 'NoneType'.

```

```

>>> # Other way to create IdentityServicesEngineAPI connection object; if it does not
    use the API Gateway
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!',
...     uses_api_gateway=False,
...     ers_base_url="https://dcloud-dna-ise-rtp.cisco.
    com:9060",
...     ui_base_url="https://dcloud-dna-ise-rtp.cisco.com:443",
...     mnt_base_url="https://dcloud-dna-ise-rtp.cisco.
    com:443",
...     # px_grid_base_url="https://dcloud-dna-ise-rtp.cisco.
    com:8910",
...     version='3.1.0')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    api = IdentityServicesEngineAPI(username='admin',
  File "ciscoisesdk/api/__init__.py", line 341, in __init__
  File "ciscoisesdk/utils.py", line 165, in check_type
TypeError: We were expecting to receive an instance of one of the following types:
'basestring'; but instead we received None which is a 'NoneType'.

```

1.3.5 Certificates

Besides username, password, encoded_auth, base_url, and version, there are other parameters when creating the *IdentityServicesEngineAPI*, many of them have a default value (check *Package Constants* for more).

When dealing with certificates, the most important one is the `verify` parameter.

To avoid getting errors like the following:

```

>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> own_api = IdentityServicesEngineAPI(encoded_auth='dXNlcm5hbWU6cGFzc3dvcmQK',
...     base_url="https://128.107.71.199:443", version='3.1.0', uses_api_gateway=True)
requests.exceptions.SLError: HTTPSConnectionPool(host='128.107.71.199', port=443):
Max retries exceeded with url: /dna/system/api/v1/auth/token (Caused by
SSLError (SSLCertVerificationError(1, '[SSL: CERTIFICATE_VERIFY_FAILED] certificate
verify failed: self signed certificate in certificate chain (_ssl.c:1076)'))))
>>>

```

Include the `verify` parameter and set it to `False`:


```
>>> from ciscoisesdk import IdentityServicesEngineAPI
>>> own_api = IdentityServicesEngineAPI(encoded_auth='dXN1cm5hbWU6cGFzc3dvcmQK',
... base_url="https://128.107.71.199:443", version='1.3.0',
... verify=False)
InsecureRequestWarning: Unverified HTTPS request is being made. Adding certificate
  verification is strongly advised. See: https://urllib3.readthedocs.io/en/latest/
  ↪advanced-usage.html#ssl-warnings
  InsecureRequestWarning)
>>>
```

You will see urllib3 warnings instead. If you want to disable them, the easiest way is with:

```
>>> import urllib3
>>> urllib3.disable_warnings()
```

1.3.6 Package Constants

The following are the default values pulled from `ciscoisesdk.config` and used when creating the connection object.

DEFAULT_DEBUG = 'False'
debug default value.

DEFAULT_VERSION = '3.1.0'
version default value.

DEFAULT_BASE_URL = 'https://dcloud-dna-ise-rtp.cisco.com'
base_url default value.

DEFAULT_SINGLE_REQUEST_TIMEOUT = 60
single_request_timeout default value. Timeout (in seconds) for the RESTful HTTP requests.

DEFAULT_WAIT_ON_RATE_LIMIT = True
wait_on_rate_limit default value. Enables or disables automatic rate-limit handling.

DEFAULT_VERIFY = True
verify default value. Controls whether to verify the server's TLS certificate or not.

DEFAULT_USES_API_GATEWAY = True
uses_api_gateway default value. Controls whether ISE use the gateway or not.

USES_API_GATEWAY_ENVIRONMENT_VARIABLE = 'IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY'
name of the environment uses_api_gateway variable

UI_BASE_URL_ENVIRONMENT_VARIABLE = 'IDENTITY_SERVICES_ENGINE_UI_BASE_URL'
name of the environment ui_base_url variable

ERS_BASE_URL_ENVIRONMENT_VARIABLE = 'IDENTITY_SERVICES_ENGINE_ERS_BASE_URL'
name of the environment ers_base_url variable

MNT_BASE_URL_ENVIRONMENT_VARIABLE = 'IDENTITY_SERVICES_ENGINE_MNT_BASE_URL'
name of the environment mnt_base_url variable

PX_GRID_BASE_URL_ENVIRONMENT_VARIABLE = 'IDENTITY_SERVICES_ENGINE_PX_GRID_BASE_URL'
name of the environment px_grid_base_url variable

1.3.7 Making API Calls

Now that you have created a `IdentityServicesEngineAPI` “connection object,” you are ready to start making API calls.

```
>>> api.network_device.get_all(page=1,size=3).response.SearchResult.resources
[{'id': '4969bc30-ad2a-11eb-95af-f263cf05f605',
  'name': 'ISE_EST_Local_Host_19',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/4969bc30-ad2a-11eb-95af-
↪f263cf05f605',
  'type': 'application/json'}},
{'id': 'a56f6360-a9fe-11eb-95af-f263cf05f605',
  'name': 'ISE_EST_Local_Host_92348',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/a56f6360-a9fe-11eb-95af-
↪f263cf05f605',
  'type': 'application/json'}},
{'id': '2ea03580-aa02-11eb-95af-f263cf05f605',
  'name': 'Test_Device_4',
  'description': '',
  'link': {'rel': 'self',
  'href': 'https://198.18.133.27/ers/config/networkdevice/2ea03580-aa02-11eb-95af-
↪f263cf05f605',
  'type': 'application/json'}]}
```

It really is that easy.

All of the calls have been wrapped and represented as native Python method calls, like `IdentityServicesEngineAPI.network_device.get_all()` which gets the network devices summaries for the Cisco ISE ERS - see the [Network Device - Get All](#) API endpoint documentation.

As you can see, we have represented the API endpoints using simple terms that are aligned with the API docs; for example, representing the `/ers/config/networkdevice` API endpoint as a `network_device.get_network_device()` method available underneath the `IdentityServicesEngineAPI` connection object.

A full list of the available API methods, with their descriptions and parameters, is available in the [User API Doc](#).

A summary of the structure is available for each version supported

- [v3.0.0](#)
- [v3.1.0](#)

You can easily access and call any of these methods directly from your `IdentityServicesEngineAPI` connection object:

```
>>> api.network_access_policy_set.get_all().response.response
[{'default': False,
  'id': 'f22b6a01-759b-47e2-99ea-2e062abdb6ed',
  'name': 'Test Policy Set 1',
  'description': 'Test Policy Set',
  'hitCounts': 0,
  'rank': 0,
  'state': 'enabled',
```

(continues on next page)

(continued from previous page)

```
'condition': {'link': None,
'conditionType': 'ConditionReference',
'isNegate': False,
'name': 'My New Condition',
'id': '92bba708-1df6-4f03-9d40-d28b4cb2d982',
'description': 'New optional Description'},
'serviceName': 'Default Network Access',
'isProxy': False,
'link': {'rel': 'self',
'href': 'https://198.18.133.27/api/v1/policy/network-access/policy-set/f22b6a01-759b-
47e2-99ea-2e062abdb6ed',
'type': 'application/json'}}}]
```

1.3.8 Catching Exceptions

If something should go wrong with the API call, an exception will be raised. `ApiError` exceptions are raised when an error condition is returned from the Identity Services Engine cloud. Details will be provided in the error message.

```
>>> from ciscoisesdk import IdentityServicesEngineAPI, ApiError
>>> api = IdentityServicesEngineAPI(username='devnetuser', password='Cisco123!')
>>> # The uses_api_gateway is True by default and the base_url used by default is `from_
↳ ciscoisesdk.config import DEFAULT_BASE_URL`
>>> network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])

-----
ApiError                                Traceback (most recent call last)
<ipython-input-71-afadb5c98c43> in <module>
----> 1 network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
      2
ciscoisesdk/misc.py in check_response_code(response, expected_response_code)
      63         raise RateLimitError(response)
      64     else:
--> 65         raise ApiError(response)
      66

ApiError: [400] - The request was invalid or cannot be otherwise served.
{
  "ERSResponse" : {
    "operation" : "POST-create-networkdevice",
    "messages" : [ {
      "title" : "Network Device Create failed: Device Name Already Exist",
      "type" : "ERROR",
      "code" : "Application resource validation exception"
    } ],
    "link" : {
      "rel" : "related",
      "href" : "https://198.18.133.27/ers/config/networkdevice",
      "type" : "application/xml"
    }
  }
}
```

(continues on next page)

(continued from previous page)

>>>

You can catch any errors returned by the Identity Services Engine cloud by catching `ApiError` exceptions in a try-except block.

```
>>> from ciscoisesdk.exceptions import ApiError
>>> try:
...     network_device_response = api.network_device.create_network_device(name='ISE_EST_
↳ Local_Host_19', network_device_iplist=[{"ipaddress": "127.35.0.1", "mask": 32}])
... except ApiError as e:
...     print(e)
ApiError: [400] - The request was invalid or cannot be otherwise served.
{
  "ERSResponse" : {
    "operation" : "POST-create-networkdevice",
    "messages" : [ {
      "title" : "Network Device Create failed: Device Name Already Exist",
      "type" : "ERROR",
      "code" : "Application resource validation exception"
    } ],
    "link" : {
      "rel" : "related",
      "href" : "https://198.18.133.27/ers/config/networkdevice",
      "type" : "application/xml"
    }
  }
}
```

ciscoisesdk will also raise a number of other standard errors (`TypeError`, `ValueError`, etc.); however, these errors are usually caused by incorrect use of the package or methods and should be sorted while debugging your app.

1.3.9 Working with Returned Objects

The Identity Services Engine cloud returns data objects in JSON format, like so:

```
[
{
  "default": false,
  "id": "f22b6a01-759b-47e2-99ea-2e062abdb6ed",
  "name": "Test Policy Set 1",
  "description": "Test Policy Set",
  "hitCounts": 0,
  "rank": 0,
  "state": "enabled",
  "condition": {
    "link": null,
    "conditionType": "ConditionReference",
    "isNegate": false,
    "name": "My New Condition",
    "id": "92bba708-1df6-4f03-9d40-d28b4cb2d982",
```

(continues on next page)

(continued from previous page)

```

    "description": "New optional Description"
  },
  "serviceName": "Default Network Access",
  "isProxy": false,
  "link": {
    "rel": "self",
    "href": "https://198.18.133.27/api/v1/policy/network-access/policy-set/f22b6a01-
↪759b-47e2-99ea-2e062abdb6ed",
    "type": "application/json"
  }
}
]

```

Sure, JSON data objects can easily be parsed and represented in Python using dictionaries, but when working with an ‘object’ wouldn’t it be nice to be able to work with it like an object - using native object syntax (like accessing attributes using ‘.’ notation)? ciscoisesdk enables you to do just that:

```

>>> policy_set = api.network_access_policy_set.get_all().response.response
>>> policy_set[0].id
'f22b6a01-759b-47e2-99ea-2e062abdb6ed'
>>> policy_set[0].condition.conditionType
'ConditionReference'
>>> policy_set[0].condition.name
'My New Condition'

```

Representing and treating Identity Services Engine data objects as Python data objects, can really help clean up your code and make coding easier:

1. You don’t need to create variables to hold all the data attributes, just use the attributes available underneath the data object.

```

>>> # Do this
>>> device_list_response = api.network_device.get_all(filter='name.EQ.ISE_EST_Local_
↪Host_19')
>>> device_response = device_list_response.response.SearchResult.resources[0]
>>> device_response_detail = api.network_device.get_by_id(device_response.id).
↪response.NetworkDevice

>>> # or even this
>>> filter_query = 'name.EQ.ISE_EST_Local_Host_19'
>>> device_response_id = api.network_device.get_all(filter=filter_query).response.
↪SearchResult.resources[0].id
>>> device_response_detail = api.network_device.get_by_id(device_response_id).
↪response.NetworkDevice

```

2. When accessing ‘optional’ attributes, like `device_list_response.response.SearchResult.resources[0].id` attribute of Identity Services Engine NetworkDevice object, the response object will return None when the attribute is not present and will return the attribute’s value when it is present. This avoids some boiler plate code and/or needless exception handling, when working with optional attributes.

```

>>> devices_response = api.network_device.get_all().response
>>> # Instead of doing this
>>> if hasattr(devices_response, 'SearchResult') and hasattr(devices_response.
↪SearchResult, 'resources'):

```

(continues on next page)

(continued from previous page)

```

...     devices = devices_response.SearchResult.resources
...     for d in devices:
...         if hasattr(d, 'id') and hasattr(d, 'description'):
...             # Do something with the configList attribute
...             print(d.id, d.description)
>>> # Or this
... try:
...     devices = devices_response.SearchResult.resources
... except AttributeError as e:
...     pass
... for d in devices:
...     # Do something with the configList attribute
...     print(d.id, d.description)
... except AttributeError as e:
...     pass
>>> # You can do this, which is cleaner
>>> if devices_response.SearchResult and devices_response.SearchResult.resources:
...     for d in devices_response.SearchResult.resources:
...         if d.id and d.description:
...             # Do something with the configList attribute
...             print(d.id, d.description)

```

3. It just feels more *natural*. :-) When iterating through sequences, and working with objects in those sequences (see the next section), working with objects as objects is definitely more Pythonic.

The Zen of Python (PEP 20): “Beautiful is better than ugly.” “Simple is better than complex.”

The currently modeled *Identity Services Engine Data Object* with its functions, is available [here](#) in the *User API Doc*.

What if Identity Services Engine adds new data attributes?

Attribute access WILL WORK for the newly added attributes (yes, without a package update!). ciscoisesdk is written to automatically take advantage of new attributes and data as they are returned.

1.3.10 Configuring Logging for ciscoisesdk

The main ciscoisesdk logger is ciscoisesdk.

Other loggers are ciscoisesdk.exceptions, ciscoisesdk.restsession and ciscoisesdk.api.custom_caller.

The ciscoisesdk adds only the logging.NullHandler following the [logging recommendations for libraries](#)

So you can add your logging handlers according to your needs.

```

import logging
import warnings
from ciscoisesdk import IdentityServicesEngineAPI

# Another way to disable warnings caused by (verify=False)
warnings.filterwarnings('ignore', message='Unverified HTTPS request')

logger = logging.getLogger('simple_example')
logger.setLevel(logging.DEBUG)
# create console handler and set level to debug
ch = logging.StreamHandler()

```

(continues on next page)

(continued from previous page)

```
# create formatter
formatter = logging.Formatter('%(asctime)s - %(name)s - %(levelname)s - %(message)s')
# add formatter to ch
ch.setFormatter(formatter)
# add ch to logger
logger.addHandler(ch)

ch_ = logging.StreamHandler()
api = IdentityServicesEngineAPI(verify=False, debug=True)
logging.getLogger('ciscoisesdk').addHandler(ch_)

logger.debug('simple message')
api.network_device.get_all().response
```

1.3.11 Adding API call definitions

Custom caller functions help you:

1. Add support for custom API calls.
2. Add support for API calls that are/were not documented when the SDK was released.

```
from ciscoisesdk import api

# Create a IdentityServicesEngineAPI connection object;
# it uses Identity Services Engine sandbox URL, username and password, with Identity_
↳ Services Engine API version 3.1.0.,
# and requests to verify the server's TLS certificate with verify=True.
api_ = api.IdentityServicesEngineAPI(username="devnetuser",
    password="Cisco123!",
    base_url="https://dcloud-dna-ise-rtp.cisco.com",
    version='3.1.0',
    verify=True
)

# Add your custom API call to the connection object.
# Define the get_hotspotportal function.
# Call it with:
#     get_hotspotportal(params={'filter': 'name.EQ.Hotspot Guest Portal'})
def get_hotspotportal(params):
    return api_.custom_caller.call_api('GET', '/ers/config/hotspotportal', params)

# Add your custom API call to the connection object.
# Define the delete_hotspotportal_by_id function
# under the custom_caller wrapper.
# Call it with:
#     api_.custom_caller.delete_hotspotportal_by_id('be456g16-14fd-4cac-94b7-ac3b8f9f')
api_.custom_caller.add_api('delete_hotspotportal_by_id',
    lambda _id:
        api_.custom_caller.call_api(
            'DELETE',
            '/ers/config/hotspotportal/{id}',
```

(continues on next page)

(continued from previous page)

```

        path_params={
            'id': _id,
        })
    )

# Advance usage example using Custom Caller functions.
def setup_custom():
    """
    Defines the get_hotspotportal_by_id and delete_hotspotportal_by_id functions
    under the custom_caller wrapper, and with help documentation
    in two different ways.

    Check that they have been added with
    'get_hotspotportal_by_id' in dir(api_.custom_caller)
    'delete_hotspotportal_by_id' in dir(api_.custom_caller)

    Quickly check that you indeed have them as functions with
    type(getattr(api_.custom_caller, 'get_hotspotportal_by_id'))
    type(getattr(api_.custom_caller, 'delete_hotspotportal_by_id'))

    Check the documentation with
    help(api_.custom_caller.get_hotspotportal_by_id)
    help(api_.custom_caller.delete_hotspotportal_by_id)

    """

    # Alternative 1: Definition with helper function.
    def _get_hotspotportal_by_id(_id):
        """Custom hostport portal API call, returns response attribute

        Args:
            _id(str): Hostport portal id.

        Returns:
            RestResponse: REST response with following properties:
            - headers(MyDict): response headers.
            - response(MyDict): response body as a MyDict object. Access the object
            ↪'s properties by using the dot notation
              or the bracket notation.
            - content(bytes): representation of the request's response
            - text(str): representation of the request's response

        """
        return api_.custom_caller.call_api(
            'GET',
            '/ers/config/hotspotportal/{id}',
            path_params={
                'id': _id,
            })

    # Finally add the function as an attribute.
    api_.custom_caller.add_api('get_hotspotportal_by_id', _get_hotspotportal_by_id)

    # Alternative 2: Definition with lambda function.

```

(continues on next page)

(continued from previous page)

```

api_.custom_caller.add_api('delete_hotspotportal_by_id',
    lambda _id:
        api_.custom_caller.call_api(
            'DELETE',
            '/ers/config/hotspotportal/{id}',
            path_params={
                'id': _id,
            })
        )
# Finally add the documentation
api_.custom_caller.delete_hotspotportal_by_id.__doc__ = """
    Custom global credential API call to delete hostport portal

    Args:
        _id(str): Hostport portal id.

    Returns:
        RestResponse: REST response with following properties:
            - headers(MyDict): response headers.
            - response(MyDict): response body as a MyDict object. Access the object's
↳ properties by using the dot notation
              or the bracket notation.
            - content(bytes): representation of the request's response
            - text(str): representation of the request's response
    """

```

Check out the [Custom Caller](#) documentation to begin using it.

Copyright (c) 2021 Cisco and/or its affiliates.

1.4 User API Doc

1.4.1 IdentityServicesEngineAPI

The *IdentityServicesEngineAPI* class creates “connection objects” for working with the Identity Services Engine APIs and hierarchically organizes the Identity Services Engine APIs and their endpoints underneath these connection objects.

Warning: The minimum supported version is ISE 3.1. Future releases may drop the ISE version 3.0.0.

IdentityServicesEngineAPI summary structure

v3.0.0 summary

| | | |
|----------------------------------|---|--|
| <i>IdentityServicesEngineAPI</i> | <i>aci_bindings</i> | <i>get_aci_bindings()</i> <i>get_aci</i> |
| | <i>aci_settings</i> | <i>get_aci_settings()</i> <i>get_ver</i> |
| | <i>active_directory</i> | <i>create_active_directory()</i> |
| | <i>admin_user</i> | <i>get_admin_user_by_id()</i> <i>get</i> |
| | <i>allowed_protocols</i> | <i>create_allowed_protocol()</i> |
| | <i>anc_endpoint</i> | <i>apply_anc_endpoint()</i> <i>bulk</i> |
| | <i>anc_policy</i> | <i>bulk_request_for_anc_poli</i> |
| | <i>authentication</i> | <i>authentication_api()</i> |
| | <i>authorization_profile</i> | <i>create_authorization_prof</i> |
| | <i>backup_and_restore</i> | <i>cancel_backup()</i> <i>config_bac</i> |
| | <i>byod_portal</i> | <i>create_byod_portal()</i> <i>delet</i> |
| | <i>certificate_profile</i> | <i>create_certificate_profil</i> |
| | <i>certificate_template</i> | <i>get_certificate_template()</i> |
| | <i>certificates</i> | <i>bind_csr()</i> <i>delete_csr_by_i</i> |
| | <i>clear_threats_and_vulnerabilities</i> | <i>clear_threats_and_vulnera</i> |
| | <i>consumer</i> | <i>access_secret()</i> <i>activate_a</i> |
| | <i>custom_caller</i> | <i>add_api()</i> <i>call_api()</i> |
| | <i>device_administration_authentication_rules</i> | <i>create_device_admin_authen</i> |
| | <i>device_administration_authorization_exception_rules</i> | <i>create_device_admin_local</i> |
| | <i>device_administration_authorization_global_exception_rules</i> | <i>create_device_admin_polic</i> |
| | <i>device_administration_authorization_rules</i> | <i>create_device_admin_autho</i> |
| | <i>device_administration_command_set</i> | <i>get_device_admin_command_</i> |
| | <i>device_administration_conditions</i> | <i>create_device_admin_condi</i> |
| | <i>device_administration_dictionary_attributes_list</i> | <i>get_device_admin_dictiona</i> |
| | <i>device_administration_identity_stores</i> | <i>get_device_admin_identity</i> |
| | <i>device_administration_network_conditions</i> | <i>create_device_admin_netwo</i> |
| | <i>device_administration_policy_set</i> | <i>create_device_admin_polic</i> |
| | <i>device_administration_profiles</i> | <i>get_device_admin_profiles</i> |
| | <i>device_administration_service_names</i> | <i>get_device_admin_service_</i> |
| | <i>device_administration_time_date_conditions</i> | <i>create_device_admin_time_</i> |
| | <i>downloadable_acl</i> | <i>create_downloadable_acl()</i> |
| | <i>egress_matrix_cell</i> | <i>bulk_request_for_egress_m</i> |
| | <i>endpoint</i> | <i>bulk_request_for_endpoint</i> |
| | <i>endpoint_certificate</i> | <i>create_endpoint_certifica</i> |
| | <i>endpoint_identity_group</i> | <i>create_endpoint_group()</i> <i>de</i> |
| | <i>external_radius_server</i> | <i>create_external_radius_se</i> |
| | <i>filter_policy</i> | <i>create_filter_policy()</i> <i>del</i> |
| | <i>guest_location</i> | <i>get_guest_location()</i> <i>get_g</i> |
| | <i>guest_smtp_notification_configuration</i> | <i>create_guest_smtp_notifica</i> |
| | <i>guest_ssid</i> | <i>create_guest_ssid()</i> <i>delete</i> |
| | <i>guest_type</i> | <i>create_guest_type()</i> <i>delete</i> |
| | <i>guest_user</i> | <i>approve_guest_user_by_id()</i> |
| | <i>hotspot_portal</i> | <i>create_hotspot_portal()</i> <i>de</i> |
| | <i>identity_groups</i> | <i>create_identity_group()</i> <i>ge</i> |
| | <i>identity_sequence</i> | <i>create_identity_sequence()</i> |
| | <i>internal_user</i> | <i>create_internal_user()</i> <i>del</i> |

| | | |
|--|--|--|
| | <i>ip_to_sgt_mapping</i> | <i>bulk_request_for_ip_to_sg</i> |
| | <i>ip_to_sgt_mapping_group</i> | <i>bulk_request_for_ip_to_sg</i> |
| | <i>mdm</i> | <i>get_endpoint_by_mac_addre</i> |
| | <i>misc</i> | <i>delete_all_sessions()</i> <i>get_</i> |
| | <i>my_device_portal</i> | <i>create_my_device_portal()</i> |
| | <i>native_suppllicant_profile</i> | <i>delete_native_suppllicant_</i> |
| | <i>network_access_authentication_rules</i> | <i>create_network_access_aut</i> |
| | <i>network_access_authorization_exception_rules</i> | <i>create_network_access_loc</i> |
| | <i>network_access_authorization_global_exception_rules</i> | <i>create_network_access_pol</i> |
| | <i>network_access_authorization_rules</i> | <i>create_network_access_aut</i> |
| | <i>network_access_conditions</i> | <i>create_network_access_con</i> |
| | <i>network_access_dictionary</i> | <i>create_network_access_dic</i> |
| | <i>network_access_dictionary_attribute</i> | <i>create_network_access_dic</i> |
| | <i>network_access_dictionary_attributes_list</i> | <i>get_network_access_diction</i> |
| | <i>network_access_identity_stores</i> | <i>get_network_access_identi</i> |
| | <i>network_access_network_conditions</i> | <i>create_network_access_net</i> |
| | <i>network_access_policy_set</i> | <i>create_network_access_pol</i> |
| | <i>network_access_profiles</i> | <i>get_network_access_profil</i> |
| | <i>network_access_security_groups</i> | <i>get_network_access_securi</i> |
| | <i>network_access_service_names</i> | <i>get_network_access_servic</i> |
| | <i>network_access_time_date_conditions</i> | <i>create_network_access_tim</i> |
| | <i>network_device</i> | <i>bulk_request_for_network_</i> |
| | <i>network_device_group</i> | <i>create_network_device_gro</i> |
| | <i>node_deployment</i> | <i>delete_node()</i> <i>get_node_det</i> |
| | <i>node_details</i> | <i>get_node_detail_by_id()</i> <i>ge</i> |
| | <i>node_group</i> | <i>create_node_group()</i> <i>delete</i> |
| | <i>pan_ha</i> | <i>disable_pan_ha()</i> <i>enable_pa</i> |
| | <i>portal</i> | <i>get_portal_by_id()</i> <i>get_por</i> |
| | <i>portal_global_setting</i> | <i>get_portal_global_setting</i> |
| | <i>portal_theme</i> | <i>create_portal_theme()</i> <i>dele</i> |
| | <i>profiler</i> | <i>get_profiles()</i> |
| | <i>profiler_profile</i> | <i>get_profiler_profile_by_i</i> |
| | <i>provider</i> | <i>authorization()</i> <i>register_s</i> |
| | <i>psn_node_details_with_radius_service</i> | <i>get_session_service_node()</i> |
| | <i>pull_deployment_info</i> | <i>get_deployment_info()</i> <i>get_</i> |
| | <i>px_grid_node</i> | <i>approve_px_grid_node()</i> <i>del</i> |
| | <i>px_grid_settings</i> | <i>autoapprove_px_grid_settin</i> |
| | <i>radius_failure</i> | <i>get_failures()</i> |
| | <i>radius_server_sequence</i> | <i>create_radius_server_sequ</i> |
| | <i>replication_status</i> | <i>get_node_replication_stat</i> |
| | <i>repository</i> | <i>create_repository()</i> <i>delete</i> |
| | <i>restid_store</i> | <i>create_rest_id_store()</i> <i>del</i> |
| | <i>security_group_to_virtual_network</i> | <i>bulk_request_for_security</i> |
| | <i>security_groups</i> | <i>bulk_request_for_security</i> |
| | <i>security_groups_acls</i> | <i>bulk_request_for_security</i> |
| | <i>self_registered_portal</i> | <i>create_self_registered_por</i> |
| | <i>session_directory</i> | <i>get_session_by_ip_address</i> |
| | <i>sms_provider</i> | <i>get_sms_provider()</i> <i>get_sms</i> |
| | <i>sponsor_group</i> | <i>create_sponsor_group()</i> <i>del</i> |
| | <i>sponsor_group_member</i> | <i>get_sponsor_group_member()</i> |

| | | |
|--|---|-----------------------------------|
| | <i>sponsor_portal</i> | <i>create_sponsor_portal()</i> de |
| | <i>sponsored_guest_portal</i> | <i>create_sponsored_guest_po</i> |
| | <i>support_bundle_download</i> | <i>download_support_bundle()</i> |
| | <i>support_bundle_status</i> | <i>get_support_bundle_status</i> |
| | <i>support_bundle_trigger_configuration</i> | <i>create_support_bundle() ge</i> |
| | <i>sxp_connections</i> | <i>bulk_request_for_sxp_conn</i> |
| | <i>sxp_local_bindings</i> | <i>bulk_request_for_sxp_loca</i> |
| | <i>sxp_vpns</i> | <i>bulk_request_for_sxp_vpns</i> |
| | <i>sync_ise_node</i> | <i>sync_node()</i> |
| | <i>system_certificate</i> | <i>create_system_certificate</i> |
| | <i>system_health</i> | <i>get_healths() get_performa</i> |
| | <i>tacacs_command_sets</i> | <i>create_tacacs_command_set.</i> |
| | <i>tacacs_external_servers</i> | <i>create_tacacs_external_ser</i> |
| | <i>tacacs_profile</i> | <i>create_tacacs_profile() de</i> |
| | <i>tacacs_server_sequence</i> | <i>create_tacacs_server_sequ</i> |
| | <i>tasks</i> | <i>get_task_status() get_task</i> |
| | <i>telemetry_information</i> | <i>get_telemetry_info_by_id()</i> |
| | <i>trust_sec_configuration</i> | <i>get_egress_matrices() get_</i> |
| | <i>trust_sec_sxp</i> | <i>get_bindings()</i> |
| | <i>version_and_patch</i> | <i>get_ise_version_and_patch</i> |
| | <i>version_info</i> | <i>get_version_info()</i> |

v3.1.0 summary

| | | |
|----------------------------------|---|-----------------------------------|
| <i>IdentityServicesEngineAPI</i> | <i>aci_bindings</i> | <i>get_aci_bindings() get_aci</i> |
| | <i>aci_settings</i> | <i>get_aci_settings() get_ver</i> |
| | <i>active_directory</i> | <i>create_active_directory()</i> |
| | <i>admin_user</i> | <i>get_admin_user_by_id() get</i> |
| | <i>allowed_protocols</i> | <i>create_allowed_protocol()</i> |
| | <i>anc_endpoint</i> | <i>apply_anc_endpoint() bulk</i> |
| | <i>anc_policy</i> | <i>bulk_request_for_anc_poli</i> |
| | <i>authentication</i> | <i>authentication_api()</i> |
| | <i>authorization_profile</i> | <i>create_authorization_prof</i> |
| | <i>backup_and_restore</i> | <i>cancel_backup() config_bac</i> |
| | <i>byod_portal</i> | <i>create_byod_portal() delet</i> |
| | <i>certificate_profile</i> | <i>create_certificate_profil</i> |
| | <i>certificate_template</i> | <i>get_certificate_template()</i> |
| | <i>certificates</i> | <i>bind_csr() delete_csr_by_i</i> |
| | <i>clear_threats_and_vulnerabilities</i> | <i>clear_threats_and_vulnera</i> |
| | <i>consumer</i> | <i>access_secret() activate_a</i> |
| | <i>custom_caller</i> | <i>add_api() call_api()</i> |
| | <i>device_administration_authentication_rules</i> | <i>create_device_admin_auther</i> |
| | <i>device_administration_authorization_exception_rules</i> | <i>create_device_admin_local</i> |
| | <i>device_administration_authorization_global_exception_rules</i> | <i>create_device_admin_polic</i> |
| | <i>device_administration_authorization_rules</i> | <i>create_device_admin_autho</i> |
| | <i>device_administration_command_set</i> | <i>get_device_admin_command.</i> |
| | <i>device_administration_conditions</i> | <i>create_device_admin_condi</i> |
| | <i>device_administration_dictionary_attributes_list</i> | <i>get_device_admin_dictiona</i> |

| | | |
|--|--|---|
| | <i>device_administration_identity_stores</i> | <i>get_device_admin_identity_stores()</i> |
| | <i>device_administration_network_conditions</i> | <i>create_device_admin_network_conditions()</i> |
| | <i>device_administration_policy_set</i> | <i>create_device_admin_policy_set()</i> |
| | <i>device_administration_profiles</i> | <i>get_device_admin_profiles()</i> |
| | <i>device_administration_service_names</i> | <i>get_device_admin_service_names()</i> |
| | <i>device_administration_time_date_conditions</i> | <i>create_device_admin_time_date_conditions()</i> |
| | <i>downloadable_acl</i> | <i>create_downloadable_acl()</i> |
| | <i>egress_matrix_cell</i> | <i>bulk_request_for_egress_matrix_cell()</i> |
| | <i>endpoint</i> | <i>bulk_request_for_endpoint()</i> |
| | <i>endpoint_certificate</i> | <i>create_endpoint_certificate()</i> |
| | <i>endpoint_identity_group</i> | <i>create_endpoint_group()</i> |
| | <i>external_radius_server</i> | <i>create_external_radius_server()</i> |
| | <i>filter_policy</i> | <i>create_filter_policy()</i> |
| | <i>guest_location</i> | <i>get_guest_location()</i> |
| | <i>guest_smtp_notification_configuration</i> | <i>create_guest_smtp_notification_configuration()</i> |
| | <i>guest_ssid</i> | <i>create_guest_ssid()</i> |
| | <i>guest_type</i> | <i>create_guest_type()</i> |
| | <i>guest_user</i> | <i>approve_guest_user_by_id()</i> |
| | <i>hotspot_portal</i> | <i>create_hotspot_portal()</i> |
| | <i>identity_groups</i> | <i>create_identity_group()</i> |
| | <i>identity_sequence</i> | <i>create_identity_sequence()</i> |
| | <i>internal_user</i> | <i>create_internal_user()</i> |
| | <i>ip_to_sgt_mapping</i> | <i>bulk_request_for_ip_to_sgt_mapping()</i> |
| | <i>ip_to_sgt_mapping_group</i> | <i>bulk_request_for_ip_to_sgt_mapping_group()</i> |
| | <i>mdm</i> | <i>get_endpoint_by_mac_address()</i> |
| | <i>misc</i> | <i>delete_all_sessions()</i> |
| | <i>my_device_portal</i> | <i>create_my_device_portal()</i> |
| | <i>native_suppllicant_profile</i> | <i>delete_native_suppllicant_profile()</i> |
| | <i>nbar_app</i> | <i>create_nbar_app()</i> |
| | <i>network_access_authentication_rules</i> | <i>create_network_access_authentication_rules()</i> |
| | <i>network_access_authorization_exception_rules</i> | <i>create_network_access_authorization_exception_rules()</i> |
| | <i>network_access_authorization_global_exception_rules</i> | <i>create_network_access_authorization_global_exception_rules()</i> |
| | <i>network_access_authorization_rules</i> | <i>create_network_access_authorization_rules()</i> |
| | <i>network_access_conditions</i> | <i>create_network_access_conditions()</i> |
| | <i>network_access_dictionary</i> | <i>create_network_access_dictionary()</i> |
| | <i>network_access_dictionary_attribute</i> | <i>create_network_access_dictionary_attribute()</i> |
| | <i>network_access_dictionary_attributes_list</i> | <i>get_network_access_dictionary_attributes_list()</i> |
| | <i>network_access_identity_stores</i> | <i>get_network_access_identity_stores()</i> |
| | <i>network_access_network_conditions</i> | <i>create_network_access_network_conditions()</i> |
| | <i>network_access_policy_set</i> | <i>create_network_access_policy_set()</i> |
| | <i>network_access_profiles</i> | <i>get_network_access_profiles()</i> |
| | <i>network_access_security_groups</i> | <i>get_network_access_security_groups()</i> |
| | <i>network_access_service_names</i> | <i>get_network_access_service_names()</i> |
| | <i>network_access_time_date_conditions</i> | <i>create_network_access_time_date_conditions()</i> |
| | <i>network_device</i> | <i>bulk_request_for_network_device()</i> |
| | <i>network_device_group</i> | <i>create_network_device_group()</i> |
| | <i>node_deployment</i> | <i>delete_node()</i> |
| | <i>node_details</i> | <i>get_node_detail_by_id()</i> |
| | <i>node_group</i> | <i>create_node_group()</i> |
| | <i>pan_ha</i> | <i>disable_pan_ha()</i> |

| | | |
|--|---|--|
| | <i>portal</i> | <i>get_portal_by_id()</i> <i>get_por</i> |
| | <i>portal_global_setting</i> | <i>get_portal_global_setting</i> |
| | <i>portal_theme</i> | <i>create_portal_theme()</i> <i>dele</i> |
| | <i>profiler</i> | <i>get_profiles()</i> |
| | <i>profiler_profile</i> | <i>get_profiler_profile_by_i</i> |
| | <i>provider</i> | <i>authorization()</i> <i>register_s</i> |
| | <i>psn_node_details_with_radius_service</i> | <i>get_session_service_node()</i> |
| | <i>pull_deployment_info</i> | <i>get_deployment_info()</i> <i>get_</i> |
| | <i>px_grid_node</i> | <i>approve_px_grid_node()</i> <i>del</i> |
| | <i>px_grid_settings</i> | <i>autoapprove_px_grid_settin</i> |
| | <i>radius_failure</i> | <i>get_failures()</i> |
| | <i>radius_server_sequence</i> | <i>create_radius_server_sequ</i> |
| | <i>replication_status</i> | <i>get_node_replication_statu</i> |
| | <i>repository</i> | <i>create_repository()</i> <i>delete</i> |
| | <i>restid_store</i> | <i>create_rest_id_store()</i> <i>del</i> |
| | <i>security_group_to_virtual_network</i> | <i>bulk_request_for_security</i> |
| | <i>security_groups</i> | <i>bulk_request_for_security</i> |
| | <i>security_groups_acls</i> | <i>bulk_request_for_security</i> |
| | <i>self_registered_portal</i> | <i>create_self_registered_por</i> |
| | <i>session_directory</i> | <i>get_session_by_ip_address</i> |
| | <i>sg_vn_mapping</i> | <i>bulk_create_sg_vn_mapping</i> |
| | <i>sms_provider</i> | <i>get_sms_provider()</i> <i>get_sms</i> |
| | <i>sponsor_group</i> | <i>create_sponsor_group()</i> <i>del</i> |
| | <i>sponsor_group_member</i> | <i>get_sponsor_group_member()</i> |
| | <i>sponsor_portal</i> | <i>create_sponsor_portal()</i> <i>de</i> |
| | <i>sponsored_guest_portal</i> | <i>create_sponsored_guest_por</i> |
| | <i>support_bundle_download</i> | <i>download_support_bundle()</i> |
| | <i>support_bundle_status</i> | <i>get_support_bundle_status</i> |
| | <i>support_bundle_trigger_configuration</i> | <i>create_support_bundle()</i> <i>ge</i> |
| | <i>sxp_connections</i> | <i>bulk_request_for_sxp_conne</i> |
| | <i>sxp_local_bindings</i> | <i>bulk_request_for_sxp_loca</i> |
| | <i>sxp_vpns</i> | <i>bulk_request_for_sxp_vpns</i> |
| | <i>sync_ise_node</i> | <i>sync_node()</i> |
| | <i>system_certificate</i> | <i>create_system_certificate</i> |
| | <i>system_health</i> | <i>get_healths()</i> <i>get_performa</i> |
| | <i>tacacs_command_sets</i> | <i>create_tacacs_command_set</i> |
| | <i>tacacs_external_servers</i> | <i>create_tacacs_external_se</i> |
| | <i>tacacs_profile</i> | <i>create_tacacs_profile()</i> <i>de</i> |
| | <i>tacacs_server_sequence</i> | <i>create_tacacs_server_sequ</i> |
| | <i>tasks</i> | <i>get_task_status()</i> <i>get_task</i> |
| | <i>telemetry_information</i> | <i>get_telemetry_info_by_id()</i> |
| | <i>trust_sec_configuration</i> | <i>get_egress_matrices()</i> <i>get_</i> |
| | <i>trust_sec_sxp</i> | <i>get_bindings()</i> |
| | <i>version_and_patch</i> | <i>get_ise_version_and_patch</i> |
| | <i>version_info</i> | <i>get_version_info()</i> |
| | <i>virtual_network</i> | <i>bulk_create_virtual_networ</i> |
| | <i>vn_vlan_mapping</i> | <i>bulk_create_vn_vlan_mappin</i> |

IdentityServicesEngineAPI Class

class IdentityServicesEngineAPI

Identity Services Engine API wrapper.

Creates a 'session' for all API calls through a created IdentityServicesEngineAPI object. The 'session' handles authentication, provides the needed headers, and checks all responses for error conditions.

IdentityServicesEngineAPI wraps all of the individual Identity Services Engine APIs and represents them in a simple hierarchical structure.

```
__init__(username=None, password=None, encoded_auth=None, uses_api_gateway=True,
          base_url='https://dcloud-dna-ise-rtp.cisco.com', ui_base_url=None, ers_base_url=None,
          mnt_base_url=None, px_grid_base_url=None, single_request_timeout=60,
          wait_on_rate_limit=True, verify=True, version='3.1.0', debug='False', object_factory=<function
          mydict_data_factory>, validator=<class
          'ciscoisesdk.models.schema_validator.SchemaValidator'>)
```

Create a new IdentityServicesEngineAPI object. An access token is required to interact with the Identity Services Engine APIs. This package supports two methods for you to pass the authorization token:

1. Provide a `encoded_auth` value (username:password encoded in base 64). *This has priority over the following method*
2. Provide username and password values.

This package supports two methods for you to set those values:

1. Provide the parameter. That is the `encoded_auth` or username and password parameters.
2. If an argument is not supplied, the package checks for its environment variable counterpart. That is the `IDENTITY_SERVICES_ENGINE_ENCODED_AUTH`, `IDENTITY_SERVICES_ENGINE_USERNAME`, `IDENTITY_SERVICES_ENGINE_PASSWORD`.

When not given enough parameters an `AccessTokenError` is raised.

Parameters

- **uses_api_gateway** (*bool, basestring*) – Controls whether we use the ISE's API Gateway to make the request. Defaults to the `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY` (or `IDENTITY_SERVICES_ENGINE_USES_API_GATEWAY_STRING`) environment variable or `ciscoisesdk.config.DEFAULT_USES_API_GATEWAY` if the environment variables are not set.
- **base_url** (*basestring*) – The base URL to be prefixed to the individual API endpoint suffixes, used when `uses_api_gateway` is `True`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable or `ciscoisesdk.config.DEFAULT_BASE_URL` if the environment variable is not set.
- **ui_base_url** (*basestring*) – The UI base URL to be prefixed to the individual ISE UI API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **ers_base_url** (*basestring*) – The ERS base URL to be prefixed to the individual ISE ERS API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **mnt_base_url** (*basestring*) – The MNT base URL to be prefixed to the individual ISE MNT API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.

- **px_grid_base_url** (*basestring*) – The PxGrid base URL to be prefixed to the individual ISE PxGrid API endpoint suffixes, used when `uses_api_gateway` is `False`. Defaults to the `IDENTITY_SERVICES_ENGINE_BASE_URL` environment variable if set.
- **username** (*basestring*) – HTTP Basic Auth username.
- **password** (*basestring*) – HTTP Basic Auth password.
- **encoded_auth** (*basestring*) – HTTP Basic Auth base64 encoded string.
- **single_request_timeout** (*int*) – Timeout (in seconds) for RESTful HTTP requests. Defaults to the `IDENTITY_SERVICES_ENGINE_SINGLE_REQUEST_TIMEOUT` environment variable or `ciscoisesdk.config.DEFAULT_SINGLE_REQUEST_TIMEOUT` if the environment variable is not set.
- **wait_on_rate_limit** (*bool*) – Enables or disables automatic rate-limit handling. Defaults to the `IDENTITY_SERVICES_ENGINE_WAIT_ON_RATE_LIMIT` environment variable or `ciscoisesdk.config.DEFAULT_WAIT_ON_RATE_LIMIT` if the environment variable is not set.
- **verify** (*bool, basestring*) – Controls whether we verify the server's TLS certificate, or a string, in which case it must be a path to a CA bundle to use. Defaults to the `IDENTITY_SERVICES_ENGINE_VERIFY` (or `IDENTITY_SERVICES_ENGINE_VERIFY_STRING`) environment variable or `ciscoisesdk.config.DEFAULT_VERIFY` if the environment variables are not set.
- **version** (*basestring*) – Controls which version of `IDENTITY_SERVICES_ENGINE` to use. Defaults to the `IDENTITY_SERVICES_ENGINE_VERSION` environment variable or `ciscoisesdk.config.DEFAULT_VERSION` if the environment variable is not set.
- **debug** (*bool, basestring*) – Controls whether to log information about Identity Services Engine APIs' request and response process. Defaults to the `IDENTITY_SERVICES_ENGINE_DEBUG` environment variable or `False` if the environment variable is not set.
- **object_factory** (*callable*) – The factory function to use to create Python objects from the returned Identity Services Engine JSON data objects.
- **validator** (*callable*) – The factory class with function `json_schema_validate(model:string)` that returns an object with function `validate(obj:dict)` is used to validate Python objects sent in the request body.

Returns A new `IdentityServicesEngineAPI` object.

Return type *IdentityServicesEngineAPI*

Raises

- **TypeError** – If the parameter types are incorrect.
- **AccessTokenError** – If an access token is not provided via the `access_token` argument or an environment variable.
- **VersionError** – If the version is not provided via the `version` argument or an environment variable, or it is not a Identity Services Engine API supported version [`'3.0.0'`, `'3.1.0'`].

property uses_api_gateway

If the Identity Services Engine API uses an API Gateway.

property session

The Identity Services Engine API session.

property session_ui

The Identity Services Engine UI API session.

property session_ers

The Identity Services Engine ERS API session.

property session_mnt

The Identity Services Engine MNT API session.

property session_px_grid

The Identity Services Engine PxGrid API session.

property access_token

The access token used for API calls to the Identity Services Engine service.

property version

The API version of Identity Services Engine.

property verify

The verify (TLS Certificate) for the API endpoints.

property base_url

The base URL prefixed to the individual API endpoint suffixes for ERS and Custom Caller operations.

property single_request_timeout

Timeout (in seconds) for an single HTTP request.

property wait_on_rate_limit

Automatic rate-limit handling enabled / disabled.

property ui_base_url

The ui base URL prefixed to the individual API endpoint suffixes for UI operations.

property ers_base_url

The ers base URL prefixed to the individual API endpoint suffixes for ERS operations.

property mnt_base_url

The mnt base URL prefixed to the individual API endpoint suffixes for MNT operations.

property px_grid_base_url

The px_grid base URL prefixed to the individual API endpoint suffixes for PxGrid operations

authentication

class Authentication

Identity Services Engine Authentication API.

Wraps the Identity Services Engine Authentication API and exposes the API as native Python methods that return native Python objects.

property verify

The verify (TLS Certificate) for the API endpoints.

property base_url

The base URL for the API endpoints.

property single_request_timeout

Timeout in seconds for the API requests.

authentication_api(*username, password, encoded_auth=None*)

Exchange basic auth data for a Authorization Basic encoded value that can be used to invoke the APIs.

Parameters

- **username** (*basestring*) – HTTP Basic Auth username.
- **password** (*basestring*) – HTTP Basic Auth password.
- **encoded_auth** (*basestring*) – HTTP Basic Auth base64 encoded string.

Returns An AccessToken object with the access token provided by the Identity Services Engine cloud.

Return type AccessToken

Raises **TypeError** – If the parameter types are incorrect.

custom_caller**class CustomCaller**

Identity Services Engine CustomCaller.

Identity Services Engine CustomCaller allows API creation.

add_api (*name*, *obj*)

Adds an api call to the CustomCaller.

Parameters

- **name** (*str*) – name you want to set to the api client, has to follow python variable naming rule.
- **obj** (*object*) – api call which is actually a calling call_api method.

call_api (*method*, *resource_path*, *raise_exception=True*, *original_response=False*, ***kwargs*)

Handles the requests and response.

Parameters

- **method** (*basestring*) – type of request.
- **resource_path** (*basestring*) – URL in the request object.
- **raise_exception** (*bool*) – If True, http exceptions will be raised.
- **original_response** (*bool*) – If True, MyDict (JSON response) is returned, else response object.
- **path_params** (*dict*) (*optional*) – Find each path_params' key in the resource_path and replace it with path_params' value.
- **params** (*optional*) – Dictionary or bytes to be sent in the query string for the Request.
- **data** (*optional*) – Dictionary, bytes, or file-like object to send in the body of the Request.
- **json** (*optional*) – json data to send in the body of the Request.
- **headers** (*optional*) – Dictionary of HTTP Headers to send with the Request.
- **cookies** (*optional*) – Dict or CookieJar object to send with the Request.
- **files** (*optional*) – Dictionary of 'name': file-like-objects (or {'name': ('filename', fileobj)}) for multipart encoding upload.
- **auth** (*optional*) – Auth tuple to enable Basic/Digest/Custom HTTP Auth.
- **timeout** (*float*, *tuple*) (*optional*) – How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.

- **allow_redirects** (*bool*) (*optional*) – bool. Set to True if POST/PUT/DELETE redirect following is allowed.
- **proxies** (*optional*) – Dictionary mapping protocol to the URL of the proxy.
- **verify** (*bool*, *string*) (*optional*) – if True, the SSL cert will be verified. A CA_BUNDLE path can also be provided as a string.
- **stream** (*optional*) – if False, the response content will be immediately downloaded.
- **cert** (*basestring*, *tuple*) (*optional*) – if String, path to ssl client cert file (.pem). If Tuple, ('cert', 'key') pair

Returns If original_response is True returns the original object response, else returns a JSON response with access to the object's properties by using the dot notation or the bracket notation. Defaults to False.

Return type *RestResponse* or *object*

Raises

- **TypeError** – If the parameter types are incorrect.
- **HTTPError** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.0.0

aci_bindings

class AciBindings

Identity Services Engine ACIBindings API (version: 3.0.0).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

get_aci_bindings (*filter_by=None*, *filter_value=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring*, *list*, *set*, *tuple*) – filterBy query parameter.
- **filter_value** (*basestring*, *list*, *set*, *tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.0.0).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

get_aci_settings(*headers=None, **query_parameters*)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

`test_aci_connectivity`(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
update_aci_settings_by_id(id, aci50=None, aci51=None, aciipaddress=None, acipassword=None,  
                           aciuser_name=None, admin_name=None, admin_password=None,  
                           all_sxp_domain=None, default_sgt_name=None, enable_aci=None,  
                           enable_data_plane=None, enable_elements_limit=None,  
                           ip_address_host_name=None, l3_route_network=None,  
                           max_num_iepg_from_aci=None, max_num_sgt_to_aci=None,  
                           specific_sxp_domain=None, specifix_sxp_domain_list=None,  
                           suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None,  
                           untagged_packet_iepg_name=None, headers=None, payload=None,  
                           active_validation=True, **query_parameters)
```

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.
- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint

class AncEndpoint

Identity Services Engine ANCEndpoint API (version: 3.0.0).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

get_anc_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_anc_endpoint_by_id*

clear_anc_endpoint(*additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to clear the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data (list)** – additionalData, property of the request body (list of objects).
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for [*apply_anc_endpoint*](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory**class ActiveDirectory**

Identity Services Engine ActiveDirectory API (version: 3.0.0).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

get_active_directory_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
load_groups_from_domain(id, ad_attributes=None, ad_scopes_names=None, adgroups=None,
                        advanced_settings=None, description=None, domain=None,
                        enable_domain_white_list=None, name=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

is_user_member_of_groups(*id*, *additional_data*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

This API verifies if the user is a member of the given groups.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_domains`(*id*, *headers=None*, ***query_parameters*)

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`join_domain_with_all_nodes`(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **`additional_data`** (*list*) – additionalData, property of the request body (list of objects).
- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain_with_all_nodes(*id*, *additional_data=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetchs the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_active_directory`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_active_directory`*

`get_active_directory_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

create_active_directory(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None, description=None, domain=None, enable_domain_white_list=None, id=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_active_directory*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.0.0).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

get_admin_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

allowed_protocols

class AllowedProtocols

Identity Services Engine AllowedProtocols API (version: 3.0.0).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

`get_allowed_protocol_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an allowed protocol by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_allowed_protocol_by_name`

`get_allowed_protocol_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_allowed_protocol_by_id*

update_allowed_protocol_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_tls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.

- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap*=None, *allow_eap_fast*=None, *allow_eap_md5*=None, *allow_eap_tls*=None, *allow_eap_ttls*=None, *allow_leap*=None, *allow_ms_chap_v1*=None, *allow_ms_chap_v2*=None, *allow_pap_ascii*=None, *allow_peap*=None, *allow_preferred_eap_protocol*=None, *allow_teap*=None, *allow_weak_ciphers_for_eap*=None, *description*=None, *eap_fast*=None, *eap_tls*=None, *eap_tls_l_bit*=None, *eap_ttls*=None, *name*=None, *peap*=None, *preferred_eap_protocol*=None, *process_host_lookup*=None, *require_message_auth*=None, *teap*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers*=None, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page*=None, *size*=None, *headers*=None, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for [*get_allowed_protocols_generator*](#)

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None,
allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None,
allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None,
allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None,
eap_ttls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None,
process_host_lookup=None, require_message_auth=None, teap=None, headers=None,
payload=None, active_validation=True, **query_parameters)
```

Alias for *create_allowed_protocol*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy**class AncPolicy**

Identity Services Engine AncPolicy API (version: 3.0.0).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

`get_anc_policy_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_anc_policy_by_name*

get_anc_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_anc_policy_by_id*

update_anc_policy_by_id(*id*, *actions=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *actions=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_anc_policy_by_id*

delete_anc_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_anc_policy_generator`

create_anc_policy(actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are ‘QUARANTINE’, ‘PORTBOUNCE’, ‘SHUTDOWN’ and ‘RE_AUTHENTICATE’).
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_anc_policy*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_policy(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **`bulkid`** (*basestring*) – `bulkid` path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.0.0).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

get_authorization_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(name, headers=None, **query_parameters)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(id, headers=None, **query_parameters)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(id, headers=None, **query_parameters)

Alias for *get_authorization_profile_by_id*

update_authorization_profile_by_id(id, access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API allows the client to update an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type=None*, *acl=None*, *advanced_attributes=None*, *agentless_posture=None*, *airespace_acl=None*, *airespace_ipv6_acl=None*, *asa_vpn=None*, *authz_profile_type=None*, *auto_smart_port=None*, *avc_profile=None*, *dacl_name=None*, *description=None*, *easywired_session_candidate=None*, *interface_template=None*, *ipv6_acl_filter=None*, *ipv6_dacl_name=None*, *mac_sec_policy=None*, *name=None*, *neat=None*, *profile_name=None*, *reauth=None*, *service_template=None*, *track_movement=None*, *vlan=None*, *voice_domain_permission=None*, *web_auth=None*, *web_redirection=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_authorization_profile_by_id*

delete_authorization_profile_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_authorization_profile_by_id*

get_authorization_profiles(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profiles*

get_authorization_profiles_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_authorization_profiles_generator`*

`create_authorization_profile`(*access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an authorization profile.

Parameters

- **`access_type`** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **`acl`** (*string*) – acl, property of the request body.
- **`advanced_attributes`** (*list*) – advancedAttributes, property of the request body (list of objects).
- **`agentless_posture`** (*boolean*) – agentlessPosture, property of the request body.
- **`airespace_acl`** (*string*) – airespaceACL, property of the request body.
- **`airespace_ipv6_acl`** (*string*) – airespaceIPv6ACL, property of the request body.
- **`asa_vpn`** (*string*) – asaVpn, property of the request body.
- **`authz_profile_type`** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **`auto_smart_port`** (*string*) – autoSmartPort, property of the request body.
- **`avc_profile`** (*string*) – avcProfile, property of the request body.
- **`dacl_name`** (*string*) – daclName, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`easywired_session_candidate`** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **`id`** (*string*) – Resource UUID value, property of the request body.

- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(access_type=None, acl=None, advanced_attributes=None, agentless_posture=None,
        airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,
        auto_smart_port=None, avc_profile=None, dacl_name=None, description=None,
        easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None,
        ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None,
        reauth=None, service_template=None, track_movement=None, vlan=None,
        voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None,
        payload=None, active_validation=True, **query_parameters)
```

Alias for [create_authorization_profile](#)

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

byod_portal

class ByodPortal

Identity Services Engine BYODPortal API (version: 3.0.0).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

```
get_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API allows the client to get a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_byod_portal_by_id`

`update_byod_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a BYOD portal by ID.

Parameters

- **`customizations (object)`** – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – Resource UUID, mandatory for update, property of the request body.
- **`name (string)`** – Resource Name, property of the request body.
- **`portal_test_url (string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type (string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings (object)`** – Defines all of the settings groups available for a BYOD, property of the request body.
- **`id`** – id path parameter. Portal id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_byod_portal_by_id*

delete_byod_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a BYOD portal by ID.

Parameters

- **`id (basestring)`** – id path parameter. Portal id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_byod_portal_by_id*

get_byod_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdesc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
Alias for *get_byod_portal*

get_byod_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*string*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_byod_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- ***TypeError*** – If the parameter types are incorrect.
- ***MalformedRequest*** – If the request body created is invalid.
- ***ApiError*** – If the Identity Services Engine cloud returns an error.

backup_and_restore

class BackupAndRestore

Identity Services Engine Backup And Restore API (version: 3.0.0).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_last_status(*headers=None, **query_parameters*)

Alias for *get_last_config_backup_status*

restore_config_backup(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key which was provided at the time of taking backup., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the backup file exists., property of the request body.
- **restore_file** (*string*) – Name of the backup file to be restored on ISE node., property of the request body.
- **restore_include_adeos** (*string*) – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

restore(*backup_encryption_key=None, repository_name=None, restore_file=None, restore_include_adeos=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [restore_config_backup](#)

update_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node. Allowed values ONCE, DAILY, WEEKLY, MONTHLY, property of the request body. Available values are 'ONCE', 'DAILY', 'WEEKLY' and 'MONTHLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are 'ENABLE' and 'DISABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY. Allowed values MON, TUE, WED, THU, FRI, SAT, SUN., property of the request body. Available values are 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT' and 'SUN'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node. Allowed values ONCE, DAILY, WEEKLY, MONTHLY, property of the request body. Available values are 'ONCE', 'DAILY', 'WEEKLY' and 'MONTHLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.

- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are ‘ENABLE’ and ‘DISABLE’.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY. Allowed values MON, TUE, WED, THU, FRI, SAT, SUN., property of the request body. Available values are ‘MON’, ‘TUE’, ‘WED’, ‘THU’, ‘FRI’, ‘SAT’ and ‘SUN’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.0.0).

Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

get_certificate_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_name*

get_certificate_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile_by_id*

update_certificate_profile_by_id(*id*, *allowed_as_user_name=None*,
certificate_attribute_name=None, *description=None*,
external_identity_store_name=None, *match_mode=None*,
name=None, *username_from=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – *allowedAsUserName*, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when *CERTIFICATE* is chosen in *usernameFrom*. Allowed values: *SUBJECT_COMMON_NAME* *SUBJECT_ALTERNATIVE_NAME* *SUBJECT_SERIAL_NUMBER* *SUBJECT* *SUBJECT_ALTERNATIVE_NAME_OTHER_NAME* *SUBJECT_ALTERNATIVE_NAME_EMAIL* *SUBJECT_ALTERNATIVE_NAME_DNS*. Additional internal value *ALL_SUBJECT_AND_ALTERNATIVE_NAMES* is used automatically when *usernameFrom=UPN*, property of the request body.
- **description** (*string*) – *description*, property of the request body.
- **external_identity_store_name** (*string*) – Referred *IDStore* name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – *id*, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: *NEVER* *RESOLVE_IDENTITY_AMBIGUITY* *BINARY_COMPARISON*, property of the request body.
- **name** (*string*) – *name*, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: *CERTIFICATE* (for a specific attribute as defined in *certificateAttributeName*) *UPN* (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – *id* path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to *True*.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allowed_as_user_name=None*, *certificate_attribute_name=None*, *description=None*, *external_identity_store_name=None*, *match_mode=None*, *name=None*, *username_from=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_certificate_profile_by_id*

get_certificate_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_profile*

get_certificate_profile_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.

- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(allowed_as_user_name=None, certificate_attribute_name=None, description=None,  
        external_identity_store_name=None, id=None, match_mode=None, name=None,  
        username_from=None, headers=None, payload=None, active_validation=True,  
        **query_parameters)
```

Alias for *create_certificate_profile*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificate_template

class CertificateTemplate

Identity Services Engine CertificateTemplate API (version: 3.0.0).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

`get_certificate_template_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_certificate_template_by_name`

`get_certificate_template_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_template_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.0.0).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_csrs_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

generate_csr(*allow_wild_card_cert=None, certificate_policies=None, digest_type=None, hostnames=None, key_length=None, key_type=None, portal_group_tag=None, san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None, subject_common_name=None, subject_country=None, subject_org=None, subject_org_unit=None, subject_state=None, used_for=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following Parameters are present in POST request body
PARAMETER DESCRIPTION
EXAMPLE hostnames List of ise node hostnames for which CSRs should be generated [ise-host1, ise-host2]
allowWildCardCert Allow use of WildCards in certificates false
keyLength Length of the Key used for CSR generation (required) 512
keyType Type of key used for CSR generation either RSA or ECDSA(required) RSA
digestType Hash algorithm used for signing CSR(required) SHA-256
usedFor Certificate Usage(required) MULTI-USE
subjectCommonName Certificate common name(CN)(required) \$FQDN\$
subjectOrgUnit Certificate organizational unit(OU) Engineering
subjectOrg Certificate organization (O) Cisco
subjectCity Certificate city or locality (L) San Jose
subjectState Certificate state (ST) California
subjectCountry Certificate country (C) US
sanDNS Array of SAN(Subject Alternative Name) DNS entries(optional) [ise.example.com]
sanIP Array of SAN IP entries(optional) [1.1.1.1]
sanURI Array of SAN URI entries(optional) [https://1.1.1.1]
sanDir Array of SAN DIR entries(optional) [CN=AAA,DC=COM,C=IL]
portalGroupTag Portal Group Tag when using certificate for PORTAL service Default Portal Certificate Group
NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames
When Certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are 'SHA-256', 'SHA-384' and 'SHA-512'.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are '512', '1024', '2048' and '4096'.
- **key_type** (*string*) – keyType, property of the request body. Available values are 'RSA' and 'ECDSA'.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.

- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.
- **used_for** (*string*) – usedFor, property of the request body. Available values are 'MULTI-USE', 'ADMIN', 'EAP-AUTH', 'DTLS-AUTH', 'PORTAL', 'PXGRID', 'SAML' and 'IMS'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname*, *id*, *dirpath=None*, *save_file=None*, *headers=None*, ***query_parameters*)

The response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. The hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. The ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. The ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_csr_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be deleted.
- **id** (*basestring*) – id path parameter. The ID of the Certificate Signing Request to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

regenerate_ise_root_ca(*remove_existing_ise_intermediate_csr=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API will initiate regeneration of ISE root CA certificate chain. Response contains id which can be used to track the status. Setting “removeExistingISEIntermediateCSR” to true will remove existing ISE Intermediate CSR.

Parameters

- **remove_existing_ise_intermediate_csr** (*boolean*) – Setting this attribute to true will remove existing ISE Intermediate CSR, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

renew_certificates(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API will initiate regeneration of certificates. Response contains id which can be used to track the status.

Parameters

- **cert_type** (*string*) – certType, property of the request body. Available values are 'OCSP' and 'IMS'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
         allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
         data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
         portal_group_tag=None, pxgrid=None, radius=None, saml=None,
         validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
         **query_parameters)
```

Bind CA Signed Certificate. NOTE: This API requires an existing Certificate Signing Request, and the root certificate must already be trusted. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
PARAMETER DESCRIPTION
EXAMPLE name Friendly name of the certificate. Signed Certificate data Plain-text contents of the certificate file (required) Signed Certificate in escaped format allowExtendedValidity Allow the certificates greater than validity of 398 days (required) false allowOutOfDateCert Allow out of date certificates (required) false allowReplacementOfCertificates Allow Replacement of certificates (required) false allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADSec server false pxgrid Use certificate for the pxGrid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group validateCertificateExtensions Validate Certificate Extensions false
 Following Roles can be used in any combinations
ROLE **DEFAULT** **WARNING**
 Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node.
 Note: Make sure required Certificate Chain is imported under Trusted Certificates
 EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate.
 Note: Make sure required Certificate Chain is imported under Trusted Certificates
 RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate.
 Note: Make sure required Certificate Chain is imported under Trusted Certificates
 SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage.
 Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the ISE Admin Portal, property of the request body.
- **allow_extended_validity** (*boolean*) – Allow import of certificates with validity greater than 398 days, property of the request body.
- **allow_out_of_date_cert** (*boolean*) – Allow out of date certificates (required), property of the request body.
- **allow_replacement_of_certificates** (*boolean*) – Allow Replacement of certificates (required), property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **data** (*string*) – Signed Certificate in escaped format, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **host_name** (*string*) – Name of Host whose CSR ID has been provided, property of the request body.
- **id** (*string*) – ID of the generated CSR, property of the request body.

- **ims** (*boolean*) – Use certificate for the ISE Messaging Service, property of the request body.
- **name** (*string*) – Friendly Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **validate_certificate_extensions** (*boolean*) – Validate Certificate Extensions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_system_certificate(*export=None, id=None, password=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Export System Certificate. Following Parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE id ID of a System Certificate(required) < SYSTEM_CERT_ID > export One of the below option is required "CERTIFICATE" : Export only Certificate without Private Key "CERTIFICATE_WITH_PRIVATE_KEY" : Export both Certificate and Private Key("certificatePassword" is required) CERTIFICATE_WITH_PRIVATE_KEY password Certificate Password (required if "export" : CERTIFICATE_WITH_PRIVATE_KEY) Password Constraints: Alphanumeric Minimum of 8 Characters Maximum of 100 Characters Passw*** NOTE: The response of this API carries a ZIP file containing the certificate and private key if "export" : "CERTIFICATE_WITH_PRIVATE_KEY" in the request. If "export" : "CERTIFICATE" in request body, the response carries a ZIP file containing only the certificate. WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are ‘CERTIFICATE’ and ‘CERTIFICATE_WITH_PRIVATE_KEY’.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_system_certificate(admin=None, allow_extended_validity=None,
                        allow_out_of_date_cert=None, allow_replacement_of_certificates=None,
                        allow_replacement_of_portal_group_tag=None,
                        allow_sha1_certificates=None, allow_wild_card_certificates=None,
                        data=None, eap=None, ims=None, name=None, password=None,
                        portal=None, portal_group_tag=None, private_key_data=None,
                        pxgrid=None, radius=None, saml=None,
                        validate_certificate_extensions=None, headers=None, payload=None,
                        active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body

| PARAMETER | DESCRIPTION | EXAMPLE | name | Friendly name of the certificate. | System Certificate |
|-----------------------|---|----------------------------------|--|--|-------------------------------|
| password | Password of the certificate to be imported (required). | Passw*** | data | Plain-text contents of the certificate file (required) | System Certificate |
| private_key_data | Private Key in escaped format | privateKeyData | Plain-text contents of the private key file (required) | System Certificate | Private Key in escaped format |
| allowOutOfDateCert | Allow out of date certificates (required) | false | allowSHA1Certificates | Allow SHA1 based certificates (required) | false |
| allowExtendedValidity | Allow the certificates greater than validity of 398 days (required) | false | admin | Use certificate to authenticate the ISE Admin Portal | false |
| eap | Use certificate for EAP protocols that use SSL/TLS tunneling | false | radius | Use certificate for RADSec server | false |
| pxgrid | Use certificate for the pxGrid Controller | false | ims | Use certificate for the ISE Messaging Service | false |
| saml | Use certificate for SAML Signing | false | portal | Use certificate for portal | false |
| portalGroupTag | Portal Group Tag for using certificate with portal role | Default Portal Certificate Group | allowReplacementOfPortalGroupTag | Allow Replacement | |

of Portal Group Tag (required) false allowWildcardCertificates Allow use of WildCards in certificates false validateCertificateExtensions Validate Certificate Extensions false Following Roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the ISE Admin Portal, property of the request body.
- **allow_extended_validity** (*boolean*) – Allow import of certificates with validity greater than 398 days, property of the request body.
- **allow_out_of_date_cert** (*boolean*) – Allow out of date certificates (required), property of the request body.
- **allow_replacement_of_certificates** (*boolean*) – Allow Replacement of certificates (required), property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **allow_sha1_certificates** (*boolean*) – Allow SHA1 based certificates (required), property of the request body.
- **allow_wild_card_certificates** (*boolean*) – Allow Wildcard Certificates, property of the request body.
- **data** (*string*) – Certificate Content (required), property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **ims** (*boolean*) – Use certificate for the ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **password** (*string*) – Certificate Password (required)., property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **private_key_data** (*string*) – Private Key data (required), property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **validate_certificate_extensions** (*boolean*) – Validate Certificate Extensions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name, filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name (basestring)** – hostName path parameter. Name of the host of which system certificates should be returned.
- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sort (basestring)** – sort query parameter. sort type asc or desc.
- **sort_by (basestring)** – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter (basestring, list, set, tuple)** – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_system_certificate_by_id(host_name, id, headers=None, **query_parameters)`

This API displays details of a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **`host_name (basestring)`** – `hostName` path parameter. Name of the host of which system certificates should be returned.
- **`id (basestring)`** – `id` path parameter. The id of the system certificate.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
update_system_certificate(host_name, id, admin=None,
                           allow_replacement_of_portal_group_tag=None, description=None,
                           eap=None, expiration_ttl_period=None, expiration_ttl_units=None,
                           ims=None, name=None, portal=None, portal_group_tag=None,
                           pxgrid=None, radius=None, renew_self_signed_certificate=None,
                           saml=None, headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

Update a System Certificate. NOTE: Renewing a certificate will cause an application server restart on the selected node. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body

| PARAMETER | DESCRIPTION | EXAMPLE |
|----------------------------------|--|---------|
| name | Friendly name of the certificate. | |
| description | Description of the Certificate | |
| default | Description | |
| admin | Use certificate to authenticate the ISE Admin Portal | false |
| eap | Use certificate for EAP protocols that use SSL/TLS tunneling | false |
| radius | Use certificate for RADIUS server | false |
| pxgrid | Use certificate for the pxGrid Controller | false |
| ims | Use certificate for the ISE Messaging Service | false |
| saml | Use certificate for SAML Signing | false |
| portal | Use certificate for portal | false |
| portalGroupTag | Portal Group Tag for using certificate with portal role | Default |
| allowReplacementOfPortalGroupTag | Allow Replacement of Portal Group Tag (required) | false |
| renewSelfSignedCertificate | Renew Self Signed Certificate | false |
| expirationTTLPeriod | Expiration Period | 365 |
| expirationTTLUnits | Expiration Units in one of the below formats days / weeks / months / years | days |

Following Roles can be used in any combinations

| ROLE | DEFAULT | WARNING |
|--------------------|---------|---|
| Admin | False | Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates |
| EAP Authentication | False | Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates |
| RADIUS DTLS | False | Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates |
| SAML | False | SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates |

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the ISE Admin Portal, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.
- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are 'days', 'weeks', 'months' and 'years'.
- **ims** (*boolean*) – Use certificate for the ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.

- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self Signed Certificate, property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_system_certificate_by_id(*host_name, id, headers=None, **query_parameters*)

This API deletes a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host from which the System Certificate needs to be deleted.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_trusted_certificate(*id*, *dirpath=None*, *save_file=None*, *headers=None*, ***query_parameters*)

The response of this API carries a trusted certificate file mapped to the requested id.

Parameters

- **id** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_trust_certificate(allow_basic_constraint_cafalse=None, allow_out_of_date_cert=None,  
                        allow_sha1_certificates=None, data=None, description=None, name=None,  
                        trust_for_certificate_based_admin_auth=None,  
                        trust_for_cisco_services_auth=None, trust_for_client_auth=None,  
                        trust_for_ise_auth=None, validate_certificate_extensions=None,  
                        headers=None, payload=None, active_validation=True,  
                        **query_parameters)
```

Import an X509 certificate as a trust certificate. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
PARAMETER DESCRIPTION
EXAMPLE name Friendly name of the certificate
Trust Certificate description Description of the certificate
Passw*** data Plain-text contents of the certificate file (required)
Trust Certificate in escaped format
allowOutOfDateCert Allow out of date certificates (required) false
allowSHA1Certificates Allow SHA1 based certificates (required) false
trustForIseAuth Trust for authentication within ISE false
trustForClientAuth Trust for client authentication and Syslog false
trustForCertificateBasedAdminAuth Trust for Certificate based Admin authentication false
trustForCiscoServicesAuth Trust for authentication of Cisco Services false
validateCertificateExtensions Validate extensions for trust certificate false
NOTE: If name is not set, a default name of the following format will be generated: common-name#issuer#nnnnn where “nnnnn” is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate will be trusted in ISE. The objective here is to distinguish between certificates that are used for trust within an ISE deployment and public certificates that are used to trust Cisco services. Typically, you will not want to use a given certificate for both purposes. Trusted For Usage Authentication within ISE Use “trustForIseAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes
Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted

under KeyUsage extension for this certificate. Note: “” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Parameters

- **allow_basic_constraint_cafalse** (*boolean*) – Allow Certificates with Basic Constraints CA Field as False (required), property of the request body.
- **allow_out_of_date_cert** (*boolean*) – Allow out of date certificates (required), property of the request body.
- **allow_sha1_certificates** (*boolean*) – Allow SHA1 based certificates (required), property of the request body.
- **data** (*string*) – Certificate content (required), property of the request body.
- **description** (*string*) – Description of the certificate, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within ISE, property of the request body.
- **validate_certificate_extensions** (*boolean*) – Validate trust certificate extension, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. The id of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_trusted_certificate(*id*, *authenticate_before_crl_received=None*, *automatic_crl_update=None*, *automatic_crl_update_period=None*, *automatic_crl_update_units=None*, *crl_distribution_url=None*, *crl_download_failure_retries=None*, *crl_download_failure_retries_units=None*, *description=None*, *download_crl=None*, *enable_ocsp_validation=None*, *enable_server_identity_check=None*, *ignore_crl_expiration=None*, *name=None*, *non_automatic_crl_update_period=None*, *non_automatic_crl_update_units=None*, *reject_if_no_status_from_ocs_p=None*, *reject_if_unreachable_from_ocs_p=None*, *selected_ocsp_service=None*, *status=None*, *trust_for_certificate_based_admin_auth=None*, *trust_for_cisco_services_auth=None*, *trust_for_client_auth=None*, *trust_for_ise_auth=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update a trusted certificate present in ISE trust store. Following Parameters are used in PUT request body

| PARAMETER | DESCRIPTION | EXAMPLE |
|-----------------------------------|--|--------------------------------|
| name | Friendly name of the certificate(required) | Trust Certificate |
| status | Status of the certificate | Enabled |
| description | Description of the certificate | Description of the certificate |
| trustForIseAuth | Trust for authentication within ISE | false |
| trustForClientAuth | Trust for client authentication and Syslog | false |
| trustForCertificateBasedAdminAuth | Trust for Certificate based Admin authentication | false |
| trustForCiscoServicesAuth | Trust for authentication of Cisco Services | false |
| enableOCSPValidation | Switch to enable/disable OCSP Validation | false |
| selectedOCSPService | Name of selected OCSP Service | INTERNAL_OCSP_SERVICE |
| rejectIfNoStatusFromOCSP | Switch to reject certificate if there is no status from OCSP | false |
| rejectIfUnreachableFromOCSP | Switch to reject certificate if | |

unreachable from OSCP false downloadCRL Switch to enable/disable download of CRL false crlDistributionUrl Certificate Revocation List Distribution URL automaticCRLUpdate Switch to enable/disable automatic CRL update false automaticCRLUpdatePeriod Automatic CRL update period 5 automaticCRLUpdateUnits Unit of time for automatic CRL update Minutes nonAutomaticCRLUpdatePeriod Non automatic CRL update period 1 nonAutomaticCRLUpdateUnits Unit of time of non automatic CRL update Hours crlDownloadFailureRetries If CRL download fails, wait time before retry 10 crlDownloadFailureRetriesUnits Unit of time before retry if CRL download fails Minutes enableServerIdentityCheck Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL false authenticateBeforeCRLReceived Switch to enable/disable CRL Verification if CRL is not Received false ignoreCRLExpiration Switch to enable/disable ignore CRL Expiration false Trusted For Usage Authentication within ISE Use “trustForIseAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Client authentication and Syslog Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “trustForClientAuth” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. OSCP Configuration Usage Validation against OSCP service Use “enableOCSPValidation”:true to validate the certificate against OSCP service mentioned in the field selectedOCSPService OSCP Service name Use “selectedOCSPService”:“Name of OSCP Service” Name of the OSCP service against which the certificate should be validated Note: “selectedOCSPService” value will on be used if “enableOCSPValidation” has been set true. Reject the request if OSCP returns UNKNOWN status Use “rejectIfNoStatusFromOCSP”:true to reject the certificate if the OSCP service returns UNKNOWN status Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OSCP Responder is unreachable Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OSCP service is unreachable. Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field crlDistributionUrl CRL distribution url Use “crlDistributionUrl” to specify the URL from where the CRL should be downloaded Note: “crlDistributionUrl” value will only be used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and automaticCRLUpdatePeriod, automaticCRLUpdatePeriod to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod, nonAutomaticCRLUpdateUnits to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “crlDownloadFailureRetries” and “crlDownloadFailureRetriesUnits” to set retry time period if CRL download fails Note: “crlDownloadFailureRetries” and “crlDownloadFailureRetriesUnits” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable/disable CRL Verification if CRL is not Received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable/disable automatic CRL update,

property of the request body.

- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are 'Minutes', 'Hours', 'Days' and 'Weeks'.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are 'Minutes', 'Hours', 'Days' and 'Weeks'.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable/disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable/disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.
- **ignore_crl_expiration** (*boolean*) – Switch to enable/disable ignore CRL Expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.
- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are 'Minutes', 'Hours', 'Days' and 'Weeks'.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocsp_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are 'Enabled' and 'Disabled'.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.

- **trust_for_ise_auth** (*boolean*) – Trust for authentication within ISE, property of the request body.
- **id** (*basestring*) – id path parameter. The id of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities

class ClearThreatsAndVulnerabilities

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.0.0).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *clear_threats_and_vulnerabilities*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

consumer**class Consumer**

Identity Services Engine Consumer API (version: 3.0.0).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

create_account(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountCreate.

Parameters

- **node_name** (*string*) – nodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_account*

activate_account(*description=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`access_secret`(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

`AccessSecret`.

Parameters

- **`peer_node_name`** (*string*) – `peerNodeName`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules

class DeviceAdministrationAuthenticationRules

Identity Services Engine Device Administration - Authentication Rules API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authentication_rules*

create_device_admin_authentication_rule(*policy_id*, *identity_source_id=None*,
identity_source_name=None, *if_auth_fail=None*,
if_process_fail=None, *if_user_not_found=None*,
link=None, *rule=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Device Admin Create authentication rule.

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.

- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authentication_rule*

reset_hit_counts_device_admin_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id(policy_id, headers=None, **query_parameters)`

Alias for *`reset_hit_counts_device_admin_authentication_rules`*

`get_device_admin_authentication_rule_by_id(id, policy_id, headers=None, **query_parameters)`

Device Admin Get rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rule_by_id`*

`update_device_admin_authentication_rule_by_id(id, policy_id, identity_source_id=None, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update rule.

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *identity_source_id*=None, *identity_source_name*=None, *if_auth_fail*=None, *if_process_fail*=None, *if_user_not_found*=None, *link*=None, *rule*=None, *headers*=None, *payload*=None, *active_validation*=True, ****query_parameters**)

Alias for *update_device_admin_authentication_rule_by_id*

delete_device_admin_authentication_rule_by_id(*id*, *policy_id*, *headers*=None, ****query_parameters**)

Device Admin Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_authentication_rule_by_id*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for `get_device_admin_local_exception_rules`

`create_device_admin_local_exception_rule`(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule.

Parameters

- **`commands`** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **`link`** (*object*) – link, property of the request body.
- **`profile`** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **`rule`** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*create_device_admin_local_exception_rule*](#)

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for [*reset_hit_counts_device_admin_local_exceptions*](#)

get_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_device_admin_local_exception_rule_by_id*

update_device_admin_local_exception_rule_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update local exception rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_device_admin_local_exception_rule_by_id*](#)

delete_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for [*delete_device_admin_local_exception_rule_by_id*](#)

device_administration_authorization_global_exception_rules

class DeviceAdministrationAuthorizationGlobalExceptionRules

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_set_global_exception_rules(*headers=None*, ***query_parameters*)

Device Admin Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_rules*

`create_device_admin_policy_set_global_exception`(*commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create global exception authorization rule.

Parameters

- **`commands`** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **`link`** (*object*) – link, property of the request body.
- **`profile`** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **`rule`** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_global_exceptions*

get_device_admin_policy_set_global_exception_by_rule_id(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_by_rule_id*

update_device_admin_policy_set_global_exception_by_rule_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_global_exception_by_rule_id*

device_administration_authorization_rules

class DeviceAdministrationAuthorizationRules

Identity Services Engine Device Administration - Authorization Rules API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_authorization_rules*

create_device_admin_authorization_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_authorization_rule*

reset_hit_counts_device_admin_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

get_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for `get_device_admin_authorization_rule_by_id`

`update_device_admin_authorization_rule_by_id(id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update authorization rule.

Parameters

- **`commands (list)`** – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **`link (object)`** – link, property of the request body.
- **`profile (string)`** – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **`rule (object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_device_admin_authorization_rule_by_id*

delete_device_admin_authorization_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Device Admin Delete authorization rule.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_device_admin_authorization_rule_by_id*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_command_sets(*headers=None, **query_parameters*)

Device Admin Return list of command sets. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_conditions(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *`get_device_admin_conditions`*

`create_device_admin_condition`(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates a library condition.

Parameters

- **`attribute_id`** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **`attribute_name`** (*string*) – Dictionary attribute name, property of the request body.
- **`attribute_value`** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children`** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type`** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **`dates_range`** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **`dates_range_exception`** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific

dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

get_device_admin_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_authorization_rules(headers=None, **query_parameters)`

Alias for *`get_device_admin_conditions_for_authorization_rules`*

`get_device_admin_condition_by_name(name, headers=None, **query_parameters)`

Device Admin Returns a library condition.

Parameters

- **`name (basestring)`** – name path parameter. Condition name.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_device_admin_condition_by_name`*

```
update_device_admin_condition_by_name(name, attribute_id=None, attribute_name=None,
                                     attribute_value=None, children=None,
                                     condition_type=None, dates_range=None,
                                     dates_range_exception=None, description=None,
                                     dictionary_name=None, dictionary_value=None,
                                     hours_range=None, hours_range_exception=None,
                                     id=None, is_negate=None, link=None, operator=None,
                                     week_days=None, week_days_exception=None,
                                     headers=None, payload=None, active_validation=True,
                                     **query_parameters)
```

Device Admin Update library condition using condition name.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_name(name, attribute_id=None, attribute_name=None, attribute_value=None, children=None,
               condition_type=None, dates_range=None, dates_range_exception=None,
               description=None, dictionary_name=None, dictionary_value=None, hours_range=None,
               hours_range_exception=None, id=None, is_negate=None, link=None, operator=None,
               week_days=None, week_days_exception=None, headers=None, payload=None,
               active_validation=True, **query_parameters)
```

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers=None*, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_policy_sets*

get_device_admin_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_condition_by_id*

update_device_admin_condition_by_id(*id, attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.

- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **id** – id path parameter. Condition id.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_id*

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_id*

device_administration_dictionary_attributes_list

class DeviceAdministrationDictionaryAttributesList

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_device_admin_dictionaries_authentication(*headers=None*, ***query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None*, ***query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None*, ***query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_authorization(headers=None, **query_parameters)`

Alias for *`get_device_admin_dictionaries_authorization`*

`get_device_admin_dictionaries_policy_set(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_policy_set(headers=None, **query_parameters)`

Alias for *`get_device_admin_dictionaries_policy_set`*

device_administration_identity_stores

class DeviceAdministrationIdentityStores

Identity Services Engine Device Administration - Identity Stores API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_device_admin_identity_stores(*headers=None, **query_parameters*)

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_identity_stores*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_network_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_device_admin_network_conditions*

`create_device_admin_network_condition`(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **`condition_type`** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'EndstationCondition', 'DeviceCondition' and 'DevicePortCondition'.
- **`conditions`** (*list*) – conditions, property of the request body (list of objects).
- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Network Condition name, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_network_condition_by_id*

update_device_admin_network_condition_by_id(*id, condition_type=None, conditions=None, description=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'EndstationCondition', 'DeviceCondition' and 'DevicePortCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)
Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set**class DeviceAdministrationPolicySet**

Identity Services Engine Device Administration - Policy Set API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_sets(*headers=None*, ***query_parameters*)
Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)
Alias for *get_device_admin_policy_sets*

create_device_admin_policy_set(*condition=None*, *default=None*, *description=None*, *hit_counts=None*, *id=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create a new policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.

- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_device_admin_policy_sets*

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [get_device_admin_policy_set_by_id](#)

update_device_admin_policy_set_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_policy_set_by_id*

device_administration_profiles

class DeviceAdministrationProfiles

Identity Services Engine Device Administration - Profiles API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

get_device_admin_profiles(*headers=None*, ***query_parameters*)

Device Admin Returns list of profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_profiles*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_service_names*

device_administration_time_date_conditions**class DeviceAdministrationTimeDateConditions**

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_time_conditions(*headers=None, **query_parameters*)
Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_time_conditions*


```
create_device_admin_time_condition(attribute_id=None, attribute_name=None,
                                  attribute_value=None, children=None, condition_type=None,
                                  dates_range=None, dates_range_exception=None,
                                  description=None, dictionary_name=None,
                                  dictionary_value=None, hours_range=None,
                                  hours_range_exception=None, id=None, is_negate=None,
                                  link=None, name=None, operator=None, week_days=None,
                                  week_days_exception=None, headers=None, payload=None,
                                  active_validation=True, **query_parameters)
```

Device Admin Creates time/date condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_id=None, attribute_name=None, attribute_value=None, children=None,
        condition_type=None, dates_range=None, dates_range_exception=None, description=None,
        dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None,
        id=None, is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_device_admin_time_condition*

```
get_device_admin_time_condition_by_id(id, headers=None, **query_parameters)
```

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_time_condition_by_id*

update_device_admin_time_condition_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).

- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_time_condition_by_id*

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)
Alias for *delete_device_admin_time_condition_by_id*

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.0.0).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

get_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)
This API allows the client to get a downloadable ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)
Alias for *get_downloadable_acl_by_id*

update_downloadable_acl_by_id(*id*, *dacl=None*, *dacl_type=None*, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string n for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.

- **description** (*string*) – Use the string `n` for a newline, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [`_.-`], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *dac*`l=None`, *dac*`l_type=None`, *description=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_downloadable_acl_by_id*

delete_downloadable_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a downloadable ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_downloadable_acl_by_id*

get_downloadable_acl(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_downloadable_acl*

get_downloadable_acl_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for `get_downloadable_acl_generator`

`create_downloadable_acl`(*dac1=None, dac1_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **`dac1`** (*string*) – The DACL Content. Use the string `n` for a newline, property of the request body.
- **`dac1_type`** (*string*) – Allowed values: `IPV4`, `IPV6`, `IP_AGNOSTIC`, property of the request body.
- **`description`** (*string*) – Use the string `n` for a newline, property of the request body.
- **`name`** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters `[_.-]`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell**class EgressMatrixCell**

Identity Services Engine EgressMatrixCell API (version: 3.0.0).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`clear(headers=None, **query_parameters)`

Alias for *`clear_all_matrix_cells`*

`set_all_cells_status(status, headers=None, **query_parameters)`

This API allows the client to set status of all the egress matrix cells.

Parameters

- **`status`** (*basestring*) – status path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`set_status(status, headers=None, **query_parameters)`

Alias for *`set_all_cells_status`*

`clone_matrix_cell(dst_sgt_id, id, src_sgt_id, headers=None, **query_parameters)`

This API allows the client to clone an egress matrix cell.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`src_sgt_id`** (*basestring*) – srcSgtId path parameter.

- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id, id, src_sgt_id, headers=None, **query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [get_egress_matrix_cell_by_id](#)

update_egress_matrix_cell_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*, *matrix_cell_status=None*, *name=None*, *sgacls=None*, *source_sgt_id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacls** (*list*) – sgacls, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*, *matrix_cell_status=None*, *name=None*, *sgacls=None*, *source_sgt_id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_egress_matrix_cell_by_id](#)

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell_generator*

create_egress_matrix_cell(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacls=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacls** (*list*) – sgacls, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_egress_matrix_cell*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status`(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.0.0).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

`create_endpoint_certificate`(*cert_template_name=None*, *certificate_request=None*, *format=None*, *password=None*, *dirpath=None*, *save_file=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to create an endpoint certificate.

Parameters

- **`cert_template_name`** (*string*) – Name of an Internal CA template, property of the request body.
- **`certificate_request`** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.
- **`format`** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **`password`** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **`dirpath`** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **`save_file`** (*bool*) – Enable or disable automatic file creation of raw response.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

create(*cert_template_name=None, certificate_request=None, format=None, password=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_certificate*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group

class EndpointIdentityGroup

Identity Services Engine EndpointIdentityGroup API (version: 3.0.0).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

get_endpoint_group_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_id*

```
update_endpoint_group_by_id(id, description=None, name=None, system_defined=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, name=None, system_defined=None, headers=None, payload=None,
              active_validation=True, **query_parameters)
```

Alias for *update_endpoint_group_by_id*

```
delete_endpoint_group_by_id(id, headers=None, **query_parameters)
```

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_endpoint_group_by_id`

`get_endpoint_groups(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups*

`get_endpoint_groups_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_endpoint_groups_generator`

`create_endpoint_group`(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`system_defined`** (*boolean*) – `systemDefined`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for `create_endpoint_group`

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

external_radius_server

class ExternalRadiusServer

Identity Services Engine ExternalRADIUSServer API (version: 3.0.0).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

get_external_radius_server_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_id*

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.

- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECEMIAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECEMIAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECEMIAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed charactera are alphanumeric and _ (underscore)., property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_external_radius_server_by_id*](#)

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_external_radius_server_by_id*](#)

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server*

`get_external_radius_server_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

```
create_external_radius_server(accounting_port=None, authentication_port=None,
                             authenticator_key=None, description=None, enable_key_wrap=None,
                             encryption_key=None, host_ip=None, key_input_format=None,
                             name=None, proxy_timeout=None, retries=None,
                             shared_secret=None, timeout=None, headers=None, payload=None,
                             active_validation=True, **query_parameters)
```

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore), property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_external_radius_server*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

filter_policy

class FilterPolicy

Identity Services Engine FilterPolicy API (version: 3.0.0).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_filter_policy_by_id*](#)

get_filter_policy(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for [*get_filter_policy*](#)

get_filter_policy_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the filter policies.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for `get_filter_policy_generator`

`create_filter_policy`(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **`domains`** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **`sgt`** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **`subnet`** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **`vn`** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for `create_filter_policy`

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.0.0).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

get_guest_location_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location*

get_guest_location_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration

class GuestSmtpNotificationConfiguration

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.0.0).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

get_guest_smtp_notification_settings_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_guest_smtp_notification_settings_by_id`*

`update_guest_smtp_notification_settings_by_id(id, connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlssor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a SMTP configuration setting.

Parameters

- **`connection_timeout (string)`** – Interval in seconds for all the SMTP client connections, property of the request body.
- **`default_from_address (string)`** – The default from email address to be used to send emails from, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`notification_enabled (boolean)`** – Indicates if the email notification service is to be enabled, property of the request body.
- **`password (string)`** – Password of Secure SMTP server, property of the request body.
- **`smtp_port (string)`** – Port at which SMTP Secure Server is listening, property of the request body.
- **`smtp_server (string)`** – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **`use_default_from_address (boolean)`** – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **`use_password_authentication (boolean)`** – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **`use_tlssor_ssl_encryption (boolean)`** – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **`user_name (string)`** – Username of Secure SMTP server, property of the request body.

- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlsor_ssl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

get_guest_smtp_notification_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings*

get_guest_smtp_notification_settings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_smtp_notification_settings_generator*

create_guest_smtp_notification_settings(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.
- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.

- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlslor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlslor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_guest_smtp_notification_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_ssid**class GuestSsid**

Identity Services Engine GuestSSID API (version: 3.0.0).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

`get_guest_ssid_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest SSID by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_ssid_by_id*

update_guest_ssid_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest SSID by ID.

Parameters

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_guest_ssid_by_id`

`get_guest_ssid(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid*

`get_guest_ssid_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_guest_ssid_generator`*

`create_guest_ssid`(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **`name`** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [`_`,`-`], property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *`RestResponse`*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`create_guest_ssid`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_type**class GuestType**

Identity Services Engine GuestType API (version: 3.0.0).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

update_guest_type_email (*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*,
 active_validation=True, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **`additional_data (list)`** – `additionalData`, property of the request body (list of objects).
- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_type_sms*

get_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest type by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_type_by_id*

update_guest_type_by_id(*id*, *access_time=None*, *description=None*, *expiration_notification=None*, *is_default_type=None*, *login_options=None*, *name=None*, *sponsor_groups=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_time=None*, *description=None*, *expiration_notification=None*,
is_default_type=None, *login_options=None*, *name=None*, *sponsor_groups=None*,
headers=None, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_type_by_id*

get_guest_type(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*


```
create_guest_type(access_time=None, description=None, expiration_notification=None,
                  is_default_type=None, login_options=None, name=None, sponsor_groups=None,
                  headers=None, payload=None, active_validation=True, **query_parameters)
```

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(access_time=None, description=None, expiration_notification=None, is_default_type=None,
      login_options=None, name=None, sponsor_groups=None, headers=None, payload=None,
      active_validation=True, **query_parameters)
```

Alias for *create_guest_type*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_user**class GuestUser**

Identity Services Engine GuestUser API (version: 3.0.0).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

`approve_guest_user_by_id(id, headers=None, **query_parameters)`

This API allows the client to approve a guest user by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

approve_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *approve_guest_user_by_id*

change_sponsor_password(*portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to change the sponsor password.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to suspend a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *suspend_guest_user_by_name*

reinstate_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reinstate_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *reinstate_guest_user_by_name*

get_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_guest_user_by_name`

`update_guest_user_by_name`(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by name.

Parameters

- **`custom_fields`** (*object*) – Key value map, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`guest_access_info`** (*object*) – `guestAccessInfo`, property of the request body.
- **`guest_info`** (*object*) – `guestInfo`, property of the request body.
- **`guest_type`** (*string*) – `guestType`, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*basestring*) – name, property of the request body.
- **`portal_id`** (*string*) – `portalId`, property of the request body.
- **`reason_for_visit`** (*string*) – `reasonForVisit`, property of the request body.
- **`sponsor_user_id`** (*string*) – `sponsorUserId`, property of the request body.
- **`sponsor_user_name`** (*string*) – `sponsorUserName`, property of the request body.
- **`status`** (*string*) – status, property of the request body.
- **`status_reason`** (*string*) – `statusReason`, property of the request body.
- **`name`** – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_name`(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_guest_user_by_name`*

`delete_guest_user_by_name`(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_guest_user_by_name`*

`reset_guest_user_password_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reinstate_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reinstate_guest_user_by_id*

update_guest_user_email(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *portal_id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_email*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_sms(id, portal_id, headers=None, **query_parameters)`

Alias for *`update_guest_user_sms`*

`deny_guest_user_by_id(id, headers=None, **query_parameters)`

This API allows the client to deny a guest user by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deny_by_id(id, headers=None, **query_parameters)`

Alias for *`deny_guest_user_by_id`*

`get_guest_user_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a guest user by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_id*

delete_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_guest_user_by_id*](#)

get_guest_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for `get_guest_users`

```
get_guest_users_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                           sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users_generator*

create_guest_user(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(custom_fields=None, description=None, guest_access_info=None, guest_info=None,
        guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None,
        sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_guest_user*

```
suspend_guest_user_by_id(id, additional_data=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

This API allows the client to suspend a guest user by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
suspend_by_id(id, additional_data=None, headers=None, payload=None, active_validation=True,
                **query_parameters)
```

Alias for *suspend_guest_user_by_id*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_guest_user`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_guest_user`*

`monitor_bulk_status_guest_user`(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_guest_user*

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.0.0).

Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

get_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal*

get_hotspot_portal_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

create_hotspot_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.

- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_hotspot_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMapping API (version: 3.0.0).

Wraps the Identity Services Engine IPToSGTMapping API and exposes the API as native Python methods that return native Python objects.

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all(headers=None, **query_parameters)`

Alias for *`deploy_all_ip_to_sgt_mapping`*

`get_deploy_status_ip_to_sgt_mapping(headers=None, **query_parameters)`

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status(headers=None, **query_parameters)`

Alias for *`get_deploy_status_ip_to_sgt_mapping`*

`get_ip_to_sgt_mapping_by_id(id, headers=None, **query_parameters)`

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **`id(basestring)`** – id path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deployType=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if hostName is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if hostIp is empty, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless sgt and deployTo and deployType are set, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for `update_ip_to_sgt_mapping_by_id`

`delete_ip_to_sgt_mapping_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for `delete_ip_to_sgt_mapping_by_id`

`get_ip_to_sgt_mapping`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET

/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_generator*

create_ip_to_sgt_mapping(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deployType=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if hostName is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if hostIp is empty, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless sgt and deployTo and deployType are set, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_ip_to_sgt_mapping`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_ip_to_sgt_mapping`*

`monitor_bulk_status_ip_to_sgt_mapping`(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group**class IpToSgtMappingGroup**

Identity Services Engine IPToSGTMappingGroup API (version: 3.0.0).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deploy_all_ip_to_sgt_mapping_group`(*headers=None, **query_parameters*)

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_deploy_status_ip_to_sgt_mapping_group`(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_by_id*

update_ip_to_sgt_mapping_group_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_ip_to_sgt_mapping_group_by_id*

get_ip_to_sgt_mapping_group(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group*

```
get_ip_to_sgt_mapping_group_generator(filter=None, filter_type=None, page=None, size=None,
                                       sortasc=None, sortdsc=None, headers=None,
                                       **query_parameters)
```

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

Alias for `get_ip_to_sgt_mapping_group_generator`

```
create_ip_to_sgt_mapping_group(deploy_to=None, deploy_type=None, name=None, sgt=None,  
                                headers=None, payload=None, active_validation=True,  
                                **query_parameters)
```

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None,  
        active_validation=True, **query_parameters)
```

Alias for *create_ip_to_sgt_mapping_group*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_ip_to_sgt_mapping_group`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_ip_to_sgt_mapping_group`*

`monitor_bulk_status_ip_to_sgt_mapping_group`(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.0.0).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_group_by_name*

get_identity_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_group_by_id*

update_identity_group_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

get_identity_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups*

get_identity_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

create_identity_group(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity group.

Parameters

- **description (string)** – description, property of the request body.
- **name (string)** – name, property of the request body.
- **parent (string)** – parent, property of the request body.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.0.0).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

get_identity_sequence_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

`get_identity_sequence_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

`update_identity_sequence_by_id`(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*, *id_seq_item=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

delete_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_identity_sequence_by_id`*

`get_identity_sequence(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the identity sequences.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`

Alias for *`get_identity_sequence`*

`get_identity_sequence_generator(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the identity sequences.

Parameters

- **`page(int)`** – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

internal_user

class InternalUser

Identity Services Engine InternalUser API (version: 3.0.0).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

get_internal_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_name*

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.

- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be ‘Enabled’ or ‘Disabled’. The values are case sensitive. For example, ‘[ERSObjectURL]?filter=enabled.EQ.Enabled’, property of the request body.
- **expiry_date** (*string*) – To store the internal user’s expiry date information. It’s format is = ‘YYYY-MM-DD’, property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user’s password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_name(name, change_password=None, custom_attributes=None, description=None, email=None,
    enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
    first_name=None, id=None, identity_groups=None, last_name=None, password=None,
    password_idstore=None, headers=None, payload=None, active_validation=True,
    **query_parameters)
```

Alias for *update_internal_user_by_name*

```
delete_internal_user_by_name(name, headers=None, **query_parameters)
```

This API deletes an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_name*

get_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_by_id(id, headers=None, **query_parameters)
```

Alias for `get_internal_user_by_id`

```
update_internal_user_by_id(id, change_password=None, custom_attributes=None, description=None,
                             email=None, enable_password=None, enabled=None, expiry_date=None,
                             expiry_date_enabled=None, first_name=None, identity_groups=None,
                             last_name=None, name=None, password=None, password_idstore=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_internal_user_by_id*

get_internal_user(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
Alias for *get_internal_user*

get_internal_user_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.

- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(change_password=None, custom_attributes=None, description=None, email=None,
       enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None,
       first_name=None, identity_groups=None, last_name=None, name=None, password=None,
       password_idstore=None, headers=None, payload=None, active_validation=True,
       **query_parameters)
```

Alias for *create_internal_user*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the internal user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

mdm

class Mdm

Identity Services Engine MDM API (version: 3.0.0).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

get_endpoints(*headers=None, **query_parameters*)

getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)

getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)

getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)
getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc**class Misc**

Identity Services Engine Misc API (version: 3.0.0).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

get_active_count(*headers=None, **query_parameters*)
ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_active_list`(*headers=None, **query_parameters*)
ActiveList.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_session_auth_list`(*headers=None, **query_parameters*)
Session/AuthList.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_posture_count`(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_profiler_count`(*headers=None, **query_parameters*)

ProfilerCount.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac*, *headers=None*, ***query_parameters*)

Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_session_id(*session_id*, *headers=None*, ***query_parameters*)

Sessions by SessionID.

Parameters

- **session_id** (*basestring*) – session_id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_all_sessions(*headers=None*, ***query_parameters*)

Delete All Sessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_mnt_version(*headers=None, **query_parameters*)
MNT Version.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_failure_reasons(*headers=None, **query_parameters*)
FailureReasons.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_authentication_status_by_mac(*mac*, *rec_ord_s*, *sec_ond_s*, *headers=None*, ***query_parameters*)
AuthenticationStatus by MAC.

Parameters

- **mac** (*basestring*) – MAC path parameter.
- **sec_ond_s** (*basestring*) – SECONDS path parameter.
- **rec_ord_s** (*basestring*) – RECORDS path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_reauthentication_by_mac(*end_poi_ntm_ac*, *psn_nam_e*, *rea_uth_typ_e*, *headers=None*, ***query_parameters*)

Session Reauthentication by MAC.

Parameters

- **psn_nam_e** (*basestring*) – PSN_NAME path parameter.
- **end_poi_ntm_ac** (*basestring*) – ENDPOINT_MAC path parameter.
- **rea_uth_typ_e** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`session_disconnect`(*dis_con_nec_tty_pe*, *end_poi_nti_p*, *mac*, *nas_ipv4*, *psn_nam_e*, *headers=None*,
 ***query_parameters*)

Session Disconnect.

Parameters

- **`end_poi_nti_p`** (*basestring*) – ENDPOINT_IP path parameter.
- **`psn_nam_e`** (*basestring*) – PSN_NAME path parameter.
- **`mac`** (*basestring*) – MAC path parameter.
- **`dis_con_nec_tty_pe`** (*basestring*) – DISCONNECT_TYPE path parameter.
- **`nas_ipv4`** (*basestring*) – NAS_IPV4 path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_account_status_by_mac`(*duration*, *mac*, *headers=None*, ***query_parameters*)

AccountStatus by MAC.

Parameters

- **`mac`** (*basestring*) – mac path parameter.
- **`duration`** (*basestring*) – duration path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.0.0).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*get_my_device_portal_by_id*](#)

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_my_device_portal_by_id*

get_my_device_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal*

get_my_device_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_my_device_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

native_suppliant_profile

class NativeSuppliantProfile

Identity Services Engine NativeSuppliantProfile API (version: 3.0.0).

Wraps the Identity Services Engine NativeSuppliantProfile API and exposes the API as native Python methods that return native Python objects.

get_native_suppliant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a native suppliant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_native_suppliant_profile_by_id*

update_native_suppliant_profile_by_id(*id*, *description=None*, *name=None*,
wireless_profiles=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update a native suppliant profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **wireless_profiles** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_native_suppllicant_profile_by_id*

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native supplicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_native_suppllicant_profile_by_id*

get_native_suppllicant_profile(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

get_native_suppllicant_profile_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native supplicant profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authentication_rules(*policy_id, headers=None, **query_parameters*)

Network Access Get authentication rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rules*

create_network_access_authentication_rule(*policy_id*, *identity_source_id=None*,
identity_source_name=None, *if_auth_fail=None*,
if_process_fail=None, *if_user_not_found=None*,
link=None, *rule=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id, identity_source_id=None, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id, headers=None, **query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authentication_rule_by_id*

update_network_access_authentication_rule_by_id(*id*, *policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update rule.

Parameters

- **identity_source_id** (*string*) – Identity source id from the identity stores, property of the request body.
- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.

- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *identity_source_id=None*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

delete_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for *`delete_network_access_authentication_rule_by_id`*

network_access_authorization_exception_rules

class `NetworkAccessAuthorizationExceptionRules`

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

`get_network_access_local_exception_rules(policy_id, headers=None, **query_parameters)`

Network Access Get local exception rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_local_exception_rules*

create_network_access_local_exception_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*,
security_group=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_local_exception_rule*

reset_hit_counts_network_access_local_exceptions(*policy_id*, *headers=None*,
***query_parameters*)

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_local_exceptions*

get_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers*=None, ***query_parameters*)

Alias for *get_network_access_local_exception_rule_by_id*

update_network_access_local_exception_rule_by_id(*id*, *policy_id*, *link*=None, *profile*=None, *rule*=None, *security_group*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link*=None, *profile*=None, *rule*=None, *security_group*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_set_global_exception_rules(*headers=None, **query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rules*

`create_network_access_policy_set_global_exception_rule`(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` or dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **`link`** (*object*) – link, property of the request body.
- **`profile`** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **`rule`** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **`security_group`** (*string*) – Security group used in authorization policies, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_network_access_policy_set_global_exception_rule_by_id`*

`update_network_access_policy_set_global_exception_rule_by_id(id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update global exception authorization rule.

Parameters

- **`link(object)`** – link, property of the request body.
- **`profile(list)`** – The authorization profile/s, property of the request body (list of strings).
- **`rule(object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`security_group(string)`** – Security group used in authorization policies, property of the request body.
- **`id(basestring)`** – id path parameter. Rule id.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

delete_network_access_policy_set_global_exception_rule_by_id(*id*, *headers=None*,
***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_global_exception_rule_by_id*

network_access_authorization_rules**class NetworkAccessAuthorizationRules**

Identity Services Engine Network Access - Authorization Rules API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rules*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

`reset_hit_counts_network_access_authorization_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts_by_id`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authorization_rules*

`get_network_access_authorization_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rule attributes.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_network_access_authorization_rule_by_id*

update_network_access_authorization_rule_by_id(*id, policy_id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

`delete_network_access_authorization_rule_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete authorization rule.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authorization_rule_by_id*

network_access_conditions

class NetworkAccessConditions

Identity Services Engine Network Access - Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_conditions(headers=None, **query_parameters)

Network Access Returns all library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(headers=None, **query_parameters)

Alias for *get_network_access_conditions*

create_network_access_condition(attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to existing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be

included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.

- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)
Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_network_access_conditions_for_authorization_rules`(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_network_access_condition_by_name`(*name, headers=None, **query_parameters*)

Network Access Returns a library condition.

Parameters

- **`name (basestring)`** – name path parameter. Condition name.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`get_network_access_condition_by_name`*

`update_network_access_condition_by_name`(*name*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition using condition name.

Parameters

- **`attribute_id`** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **`attribute_name`** (*string*) – Dictionary attribute name, property of the request body.
- **`attribute_value`** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children`** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type`** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **`dates_range`** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates

In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_name`(*name*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_network_access_condition_by_name`*

`delete_network_access_condition_by_name`(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **`name`** (*basestring*) – name path parameter. Condition name.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_access_condition_by_name`*

`get_network_access_conditions_for_policy_sets`(*headers=None*, ***query_parameters*)

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None, **query_parameters*)

Alias for *get_network_access_conditions_for_policy_sets*

get_network_access_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_condition_by_id*


```
update_network_access_condition_by_id(id, attribute_id=None, attribute_name=None,
                                     attribute_value=None, children=None,
                                     condition_type=None, dates_range=None,
                                     dates_range_exception=None, description=None,
                                     dictionary_name=None, dictionary_value=None,
                                     hours_range=None, hours_range_exception=None,
                                     is_negate=None, link=None, name=None, operator=None,
                                     week_days=None, week_days_exception=None,
                                     headers=None, payload=None, active_validation=True,
                                     **query_parameters)
```

Network Access Update library condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_id*

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_condition_by_id*

network_access_dictionary

class NetworkAccessDictionary

Identity Services Engine Network Access - Dictionary API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries(*headers=None*, ***query_parameters*)

Get all Dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for `get_network_access_dictionaries`

`create_network_access_dictionaries`(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **`description`** (*string*) – The description of the Dictionary, property of the request body.
- **`dictionary_attr_type`** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **`id`** (*string*) – Identifier for the dictionary, property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – The dictionary name, property of the request body.
- **`version`** (*string*) – The dictionary version, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [create_network_access_dictionaries](#)

get_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

GET a dictionary by name.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for [get_network_access_dictionary_by_name](#)

update_network_access_dictionary_by_name(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_dictionary_by_name*

delete_network_access_dictionary_by_name(*name, headers=None, **query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_by_name*

network_access_dictionary_attribute

class NetworkAccessDictionaryAttribute

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionary_attributes_by_dictionary_name(*dictionary_name*,
headers=None,
**query_parameters)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, headers=None, **query_parameters)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

create_network_access_dictionary_attribute(*dictionary_name*, allowed_values=None,
data_type=None, description=None,
direction_type=None, id=None, internal_name=None,
name=None, headers=None, payload=None,
active_validation=True, **query_parameters)

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UNIT32' and 'UINT64'.

- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'IN', 'OUT', 'NONE' and 'BOTH'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute's name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

update_network_access_dictionary_attribute_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6', 'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UNIT32' and 'UINT64'.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'IN', 'OUT', 'NONE' and 'BOTH'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.

- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name, name, allowed_values=None, data_type=None, description=None, direction_type=None, id=None, internal_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(dictionary_name, name, headers=None, **query_parameters)`

Alias for *`delete_network_access_dictionary_attribute_by_name`*

`network_access_dictionary_attributes_list`

`class NetworkAccessDictionaryAttributesList`

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

`get_network_access_dictionaries_authentication(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_authentication(headers=None, **query_parameters)`

Alias for *`get_network_access_dictionaries_authentication`*

`get_network_access_dictionaries_authorization(headers=None, **query_parameters)`

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authorization*

get_network_access_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers (*dict*)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_policy_set*

network_access_identity_stores

class NetworkAccessIdentityStores

Identity Services Engine Network Access - Identity Stores API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_network_access_identity_stores(*headers=None, **query_parameters*)

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_identity_stores*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_network_access_network_conditions*

`create_network_access_network_condition`(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **`condition_type`** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'EndstationCondition', 'DeviceCondition' and 'DevicePortCondition'.
- **`conditions`** (*list*) – conditions, property of the request body (list of objects).
- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Network Condition name, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_network_condition_by_id*

update_network_access_network_condition_by_id(*id, condition_type=None, conditions=None, description=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'EndstationCondition', 'DeviceCondition' and 'DevicePortCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_network_condition_by_id*

delete_network_access_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_network_access_network_condition_by_id`*

`network_access_policy_set`

`class NetworkAccessPolicySet`

Identity Services Engine Network Access - Policy Set API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

`get_network_access_policy_sets(headers=None, **query_parameters)`

Get all network access policy sets.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for *`get_network_access_policy_sets`*

`create_network_access_policy_set(condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Create a new policy set: Policy must include name , service identifier (either server se-

quence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_network_access_policy_set*

reset_hit_counts_network_access_policy_sets(*headers=None, **query_parameters*)
Network Access Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)
Alias for *reset_hit_counts_network_access_policy_sets*

get_network_access_policy_set_by_id(*id, headers=None, **query_parameters*)
Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_by_id*

update_network_access_policy_set_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘enabled’, ‘disabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_network_access_policy_set_by_id`*

`delete_network_access_policy_set_by_id`(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **`id`** (*basestring*) – id path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *`delete_network_access_policy_set_by_id`*

network_access_profiles

class NetworkAccessProfiles

Identity Services Engine Network Access - Profiles API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

get_network_access_profiles(*headers=None, **query_parameters*)

Network Access Returns list of profiles. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)
Alias for *get_network_access_security_groups*

network_access_service_names**class NetworkAccessServiceNames**

Identity Services Engine Network Access - Service Names API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

`get_network_access_service_names`(*headers=None, **query_parameters*)
Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_network_access_service_names*

network_access_time_date_conditions

class NetworkAccessTimeDateConditions

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.0.0).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_time_conditions(*headers=None, **query_parameters*)
Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_network_access_time_conditions*

create_network_access_time_condition(*attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Network Access Creates time/date condition.

Parameters

- **attribute_id** (*string*) – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionReference’, ‘Condition-Attributes’, ‘LibraryConditionAttributes’, ‘ConditionAndBlock’, ‘LibraryConditionAnd-Block’, ‘ConditionOrBlock’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘equals’, ‘notEquals’, ‘contains’, ‘notContains’, ‘matches’, ‘in’, ‘notIn’, ‘startsWith’, ‘notStartsWith’, ‘endsWith’, ‘notEndsWith’, ‘greaterThan’, ‘lessThan’, ‘greaterOrEquals’, ‘lessOrEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipEquals’ and ‘ipNotEquals’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list

of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Sunday’, ‘Monday’, ‘Tuesday’, ‘Wednesday’, ‘Thursday’, ‘Friday’ and ‘Saturday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_id=None, attribute_name=None, attribute_value=None, children=None,
        condition_type=None, dates_range=None, dates_range_exception=None, description=None,
        dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None,
        id=None, is_negate=None, link=None, name=None, operator=None, week_days=None,
        week_days_exception=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_network_access_time_condition*

```
get_network_access_time_condition_by_id(id, headers=None, **query_parameters)
```

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_network_access_time_condition_by_id`

`update_network_access_time_condition_by_id(id, attribute_id=None, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update network condition.

Parameters

- **`attribute_id (string)`** – Dictionary attribute id (Optional), used for additional verification, property of the request body.
- **`attribute_name (string)`** – Dictionary attribute name, property of the request body.
- **`attribute_value (string)`** – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children (list)`** – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type (string)`** – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that "conditionId" OR "ConditionAttrs" fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are 'ConditionReference', 'Condition-Attributes', 'LibraryConditionAttributes', 'ConditionAndBlock', 'LibraryConditionAnd-Block', 'ConditionOrBlock', 'LibraryConditionOrBlock' and 'TimeAndDateCondition'.
- **`dates_range (object)`** – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched or NOT matched if used in exceptionDates prooperty Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy-mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched or not matched if used in exceptionHours property Time foramt hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'equals', 'notEquals', 'contains', 'notContains', 'matches', 'in', 'notIn', 'startsWith', 'notStartsWith', 'endsWith', 'notEndsWith', 'greaterThan', 'lessThan', 'greaterOrEquals', 'lessOrEquals', 'ipGreaterThan', 'ipLessThan', 'ipEquals' and 'ipNotEquals'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday' and 'Saturday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_id=None*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_time_condition_by_id*

delete_network_access_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_time_condition_by_id*

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.0.0).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.

- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_by_name*

get_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_id*

update_network_device_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_id*

delete_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_by_id*

get_network_device(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device*

get_network_device_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).

- **network_device_iplist** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,  
        model_name=None, name=None, network_device_group_list=None, network_device_iplist=None,  
        profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None,  
        trustsecsettings=None, headers=None, payload=None, active_validation=True,  
        **query_parameters)
```

Alias for *create_network_device*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group

class NetworkDeviceGroup

Identity Services Engine NetworkDeviceGroup API (version: 3.0.0).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

get_network_device_group_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_network_device_group_by_name`*

`get_network_device_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a network device group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_network_device_group_by_id`*

`update_network_device_group_by_id(id, description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_group_by_id*

delete_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_network_device_group_by_id`

`get_network_device_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group*

get_network_device_group_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_deployment

class NodeDeployment

Identity Services Engine Node Deployment API (version: 3.0.0).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

get_nodes(*headers=None, **query_parameters*)

Discovers all deployment nodes in the cluster. It provides basic information about each of deployed nodes in the cluster like Hostname, personas, status, roles and services. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register_node(*administration=None, fdqn=None, general_settings=None, password=None, profile_configuration=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Register ISE node to form a multi-node deployment .

Parameters

- **administration** (*object*) – administration, property of the request body.
- **fdqn** (*string*) – fdqn, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **general_settings** (*object*) – generalSettings, property of the request body.
- **password** (*string*) – password, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **user_name** (*string*) – userName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

promote_node(*promotion_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Changes the cluster setting by promoting a node to primary when executed on standalone or secondary node. It could also be used to convert a deployment node to standalone node. .

Parameters

- **promotion_type** (*string*) – promotionType, property of the request body. Available values are 'SECONDARY_TO_PRIMARY', 'STANDALONE_TO_PRIMARY' and 'TO_STANDALONE'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(*hostname*, *headers=None*, ***query_parameters*)

It provides detailed information of the deployed node in the cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*hostname*, *headers=None*, ***query_parameters*)

Alias for *get_node_details*

update_node(*hostname*, *general_settings=None*, *profile_configuration=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Updates the deployed ISE node with the information provided .

Parameters

- **general_settings** (*object*) – generalSettings, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node(hostname, headers=None, **query_parameters)

The de-register ednode becomes a standalone Cisco ISE node. It retains the last configuration that it received from the PrimaryPAN and assumes the default personas of a standalone node that are Administration, PolicyService, and Monitoring. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. node name of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_group**class NodeGroup**

Identity Services Engine Node Group API (version: 3.0.0).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

get_node_groups(*headers=None, **query_parameters*)

Get details of all the node groups in the cluster. To detect node failure and to reset all URL-redirceted sessions on the failed node, two or more Policy Service nodes can be placed in the same node group. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all URL-redirceted sessions on the failed node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name, headers=None, **query_parameters*)

Get details of a node group in the cluster.

Parameters

- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*node_group_name, description=None, mar_cache=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Developers need to create node group in the system. Node Group is a group of PSNs, mainly used for terminating posture pending sessions when a PSN in local node group fails. Node group members can communicate over TCP/7800.

Parameters

- **description** (*string*) – description, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **mar_cache** (*object*) – mar-cache, property of the request body.
- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_node_group`(*node_group_name*, *description=None*, *mar_cache=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

API updates an existing node group in the system.

Parameters

- **`description`** (*string*) – description, property of the request body. Constraints: `maxLength` set to 256 and `minLength` set to 1.
- **`mar_cache`** (*object*) – mar-cache, property of the request body.
- **`node_group_name`** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **`headers(MyDict)`**: response headers.
- **`response(MyDict)`**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **`content(bytes)`**: representation of the request's response
- **`text(str)`**: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_node_group`(*node_group_name*, *headers=None*, ***query_parameters*)

Developers need to delete node group in the system.

Parameters

- **`node_group_name`** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **`headers(MyDict)`**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_details

class NodeDetails

Identity Services Engine NodeDetails API (version: 3.0.0).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

`get_node_detail_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_node_detail_by_name`

`get_node_detail_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page(int)** – page query parameter. Page number.
- **size(int)** – size query parameter. Number of objects returned per page.
- **filter(basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type(basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- `TypeError` – If the parameter types are incorrect.
- `MalformedRequest` – If the request body created is invalid.
- `ApiError` – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for `get_node_details_generator`

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the node details.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- `TypeError` – If the parameter types are incorrect.
- `MalformedRequest` – If the request body created is invalid.
- `ApiError` – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.0.0).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

get_pan_ha_status(*headers=None, **query_parameters*)

In a high availability configuration, the Primary Administration Node (PAN) is in the active state. The Secondary PAN (backup PAN) is in the standby state, which means it receives all configuration updates from the Primary PAN, but is not active in the ISE network. You can configure ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

enable_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or a combination of these. If the PANs are in different data centers, you must have a health check node for each PAN.

Parameters

- **failed_attempts** (*integer*) – failedAttempts, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **polling_interval** (*integer*) – pollingInterval, property of the request body.
- **primary_health_check_node** (*string*) – primaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **secondary_health_check_node** (*string*) – secondaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

disable_pan_ha(*headers=None, **query_parameters*)

Disable the automatic PAN failover.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting

class PortalGlobalSetting

Identity Services Engine PortalGlobalSetting API (version: 3.0.0).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
 sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

`get_portal_global_settings_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`sortasc (basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc (basestring)`** – sortdsc query parameter. sort desc.
- **`filter (basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type (basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_portal_global_settings_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

portal_theme

class PortalTheme

Identity Services Engine PortalTheme API (version: 3.0.0).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_theme_by_id*

update_portal_theme_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_theme_by_id*

delete_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_portal_theme_by_id*

get_portal_themes(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

get_portal_themes_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes_generator*

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_portal_theme*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler

class Profiler

Identity Services Engine Profiler API (version: 3.0.0).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

`get_profiles(headers=None, **query_parameters)`
getProfiles.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler_profile

class ProfilerProfile

Identity Services Engine ProfilerProfile API (version: 3.0.0).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

get_profiler_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profile_by_id*

get_profiler_profiles(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.0.0).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

register_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reregister_service(*headers=None, **query_parameters*)
ServiceReregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

authorization(*headers=None, **query_parameters*)
Authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service**class PsnNodeDetailsWithRadiusService**

Identity Services Engine `PsnNodeDetailsWithRadiusService` API (version: 3.0.0).

Wraps the Identity Services Engine `PsnNodeDetailsWithRadiusService` API and exposes the API as native Python methods that return native Python objects.

`get_session_service_node_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_id*

get_session_service_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node*

get_session_service_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

pull_deployment_info

class PullDeploymentInfo

Identity Services Engine PullDeploymentInfo API (version: 3.0.0).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **`timeout`** (*float, tuple*) – How long to wait for the server to send data before giving up.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings**class PxGridSettings**

Identity Services Engine PxGridSettings API (version: 3.0.0).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

```
autoapprove_px_grid_settings(allow_password_based_accounts=None,  
                               auto_approve_cert_based_accounts=None, headers=None,  
                               payload=None, active_validation=True, **query_parameters)
```

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`autoapprove`(*allow_password_based_accounts=None, auto_approve_cert_based_accounts=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *autoapprove_px_grid_settings*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.0.0).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

`get_failures`(*headers=None, **query_parameters*)
getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.0.0).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_radius_server_sequence_by_id*

delete_radius_server_sequence_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_radius_server_sequence_by_id*

get_radius_server_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence*

get_radius_server_sequence_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for `get_radius_server_sequence_generator`

`create_radius_server_sequence`(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a RADIUS server sequence.

Parameters

- **`before_accept_attr_manipulators_list`** (*list*) – The `beforeAcceptAttrManipulators` is required only if `useAttrSetBeforeAcc` is true, property of the request body (list of objects).
- **`on_request_attr_manipulator_list`** (*list*) – The `onRequestAttrManipulators` is required only if `useAttrSetOnRequest` is true, property of the request body (list of objects).
- **`radius_server_list`** (*list*) – `RadiusServerList`, property of the request body (list of strings).
- **`continue_authorz_policy`** (*boolean*) – `continueAuthorzPolicy`, property of the request body.
- **`description`** (*string*) – `description`, property of the request body.
- **`local_accounting`** (*boolean*) – `localAccounting`, property of the request body.
- **`name`** (*string*) – `name`, property of the request body.
- **`prefix_separator`** (*string*) – The `prefixSeparator` is required only if `stripPrefix` is true. The maximum length is 1 character, property of the request body.
- **`remote_accounting`** (*boolean*) – `remoteAccounting`, property of the request body.
- **`strip_prefix`** (*boolean*) – `stripPrefix`, property of the request body.
- **`strip_suffix`** (*boolean*) – `stripSuffix`, property of the request body.
- **`suffix_separator`** (*string*) – The `suffixSeparator` is required only if `stripSuffix` is true. The maximum length is 1 character, property of the request body.

- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.0.0).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

get_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **`description`** (*string*) – description, property of the request body.

- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_name*

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_name*

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
 Alias for *get_rest_id_store*

get_rest_id_store_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

replication_status

class ReplicationStatus

Identity Services Engine Replication Status API (version: 3.0.0).

Wraps the Identity Services Engine Replication Status API and exposes the API as native Python methods that return native Python objects.

`get_node_replication_status`(*node*, *headers=None*, ***query_parameters*)

Retrives replication status of a node.

Parameters

- **`node`** (*basestring*) – node path parameter. ID of the existing node.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.0.0).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None, **query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_repositories*

create_repository(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body. Constraints: maxLength set to 80 and minLength set to 1.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘DISK’, ‘FTP’, ‘SFTP’, ‘TFTP’, ‘NFS’, ‘CDROM’, ‘HTTP’ and ‘HTTPS’.

- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username can contain alphanumeric characters., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_repository*

get_repository(*name, headers=None, **query_parameters*)
Get a specific repository identified by the name passed in the URL. .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_repository*

update_repository(*name*, *enable_pki=None*, *password=None*, *path=None*, *protocol=None*,
server_name=None, *user_name=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*basestring*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body. Constraints: maxLength set to 80 and minLength set to 1.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘DISK’, ‘FTP’, ‘SFTP’, ‘TFTP’, ‘NFS’, ‘CDROM’, ‘HTTP’ and ‘HTTPS’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username can contain alphanumeric characters., property of the request body.
- **name** – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *enable_pki=None*, *password=None*, *path=None*, *protocol=None*, *server_name=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_repository*

delete_repository(*name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_files`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider

class SmsProvider

Identity Services Engine SMSProvider API (version: 3.0.0).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

`get_sms_provider`(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all` (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider*

`get_sms_provider_generator` (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`sortasc (basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc (basestring)`** – sortdsc query parameter. sort desc.
- **`filter (basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type (basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sms_provider_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sxp_connections

class SxpConnections

Identity Services Engine SXPConnections API (version: 3.0.0).

Wraps the Identity Services Engine SXPConnections API and exposes the API as native Python methods that return native Python objects.

get_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.

- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_connections_by_id*

delete_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP connection.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_connections_by_id*

get_sxp_connections(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

create_sxp_connections(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_connections*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_connections(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_connections*

sxp_local_bindings

class SxpLocalBindings

Identity Services Engine SXPLocalBindings API (version: 3.0.0).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

get_sxp_local_bindings_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_local_bindings_by_id*

update_sxp_local_bindings_by_id(*id*, *binding_name=None*, *description=None*,
ip_address_or_host=None, *sgt=None*, *sxp_vpn=None*, *vns=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *binding_name=None*, *description=None*, *ip_address_or_host=None*, *sgt=None*, *sxp_vpn=None*, *vns=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_local_bindings_by_id*

delete_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP local binding.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

get_sxp_local_bindings_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

```
create_sxp_local_bindings(binding_name=None, description=None, id=None,  
                           ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None,  
                           headers=None, payload=None, active_validation=True,  
                           **query_parameters)
```

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: sxpVpn or vns should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None,  
        sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True,  
        **query_parameters)
```

Alias for *create_sxp_local_bindings*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_local_bindings(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_local_bindings*

monitor_bulk_status_sxp_local_bindings(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_local_bindings*

sxp_vpns

class SxpVpns

Identity Services Engine SXPVPNs API (version: 3.0.0).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

get_sxp_vpn_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_sxp_vpn_by_id`*

`delete_sxp_vpn_by_id(id, headers=None, **query_parameters)`

This API deletes a SXP VPN.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_sxp_vpn_by_id`*

`get_sxp_vpns(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY

(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – `sxpVpnName`, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_sxp_vpn*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_vpns(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_vpns*

monitor_bulk_status_sxp_vpns(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status`(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.0.0).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

`get_security_groups_to_vn_to_vlan_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

```
update_security_groups_to_vn_to_vlan_by_id(id, description=None, name=None, sgt_id=None,
                                           virtualnetworklist=None, headers=None,
                                           payload=None, active_validation=True,
                                           **query_parameters)
```

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None,
             payload=None, active_validation=True, **query_parameters)
```

Alias for *update_security_groups_to_vn_to_vlan_by_id*

```
delete_security_groups_to_vn_to_vlan_by_id(id, headers=None, **query_parameters)
```

This API deletes a security group ACL to virtual network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_security_groups_to_vn_to_vlan_by_id`*

`get_security_groups_to_vn_to_vlan(filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)
Alias for *get_security_groups_to_vn_to_vlan*

`get_security_groups_to_vn_to_vlan_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for `get_security_groups_to_vn_to_vlan_generator`

`create_security_groups_to_vn_to_vlan`(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group to virtual network.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*string*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`sgt_id`** (*string*) – sgtId, property of the request body.
- **`virtualnetworklist`** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_to_vn_to_vlan*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_groups_to_vn_to_vlan(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_to_vn_to_vlan*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.0.0).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

get_security_group_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_group_by_id*

update_security_group_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACLs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 or 65519 or -1 to auto- generate, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

```
get_security_groups(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                    sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for *get_security_groups*

get_security_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*


```
create_security_group(default_sgacIs=None, description=None, generation_id=None,
                       is_read_only=None, name=None, propogate_to_apic=None, value=None,
                       headers=None, payload=None, active_validation=True, **query_parameters)
```

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACIs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propogate_to_apic** (*boolean*) – propogateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None,
        propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True,
        **query_parameters)
```

Alias for *create_security_group*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_group`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_security_group`*

monitor_bulk_status_security_group(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.0.0).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_security_groups_acl_by_id`*

`update_security_groups_acl_by_id(id, aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a security group ACL.

Parameters

- **`aclcontent`** (*string*) – aclcontent, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`generation_id`** (*string*) – generationId, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`ip_version`** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **`is_read_only`** (*boolean*) – isReadOnly, property of the request body.
- **`modelled_content`** (*object*) – Modelled content of contract, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_acl_by_id*

delete_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.

- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl*

get_security_groups_acl_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None*, *description=None*, *generation_id=None*, *ip_version=None*, *is_read_only=None*, *modelled_content=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.

- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_security_groups_acl*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_groups_acl(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_acl*

monitor_bulk_status_security_groups_acl(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status(bulkid, headers=None, **query_parameters)`

Alias for *`monitor_bulk_status_security_groups_acl`*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.0.0).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

`get_self_registered_portal_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a self registered portal by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_self_registered_portal_by_id*

delete_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_self_registered_portal_by_id*

get_self_registered_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals_generator*

create_self_registered_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_self_registered_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory

class SessionDirectory

Identity Services Engine Session Directory API (version: 3.0.0).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

get_sessions(*headers=None, **query_parameters*)
getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_for_recovery(*headers=None, **query_parameters*)
getSessionsForRecovery.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_ip_address(*headers=None, **query_parameters*)
getSessionByIpAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_by_mac_address(*headers=None, **query_parameters*)
getSessionByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- ***ApiError*** – If the Identity Services Engine cloud returns an error.

get_user_groups(*headers=None, **query_parameters*)
getUserGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- ***TypeError*** – If the parameter types are incorrect.
- ***MalformedRequest*** – If the request body created is invalid.
- ***ApiError*** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)
getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- ***TypeError*** – If the parameter types are incorrect.
- ***MalformedRequest*** – If the request body created is invalid.
- ***ApiError*** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)

Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.0.0).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

get_sponsor_group_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_sponsor_group_by_id*

update_sponsor_group_by_id(*id, auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update a sponsor group by ID.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).

- **id** (*basestring*) – id, property of the request body.
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsor_group_by_id*

delete_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_sponsor_group_by_id`

`get_sponsor_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all` (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group*

`get_sponsor_group_generator` (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)

Alias for *get_sponsor_group_generator*

create_sponsor_group(auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters)

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sponsor_group_member

class SponsorGroupMember

Identity Services Engine SponsorGroupMember API (version: 3.0.0).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal

class SponsorPortal

Identity Services Engine SponsorPortal API (version: 3.0.0).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

get_sponsor_portal_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_sponsor_portal_by_id`*

`update_sponsor_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsor portal by ID.

Parameters

- **`customizations (object)`** – customizations, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`portal_test_url (string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type (string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings (object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_portal_by_id*

get_sponsor_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.

- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal*

get_sponsor_portal_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.

- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_sponsor_portal*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.0.0).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

get_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsored_guest_portal_by_id*

update_sponsored_guest_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsored_guest_portal_by_id*

delete_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsored_guest_portal_by_id*

get_sponsored_guest_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_sponsored_guest_portals`*

`get_sponsored_guest_portals_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_sponsored_guest_portals_generator`

`create_sponsored_guest_portal`(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **`customizations (object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`portal_test_url (string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type (string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings (object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sponsored_guest_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download

class SupportBundleDownload

Identity Services Engine SupportBundleDownload API (version: 3.0.0).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

download_support_bundle(*file_name=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [download_support_bundle](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_status

class SupportBundleStatus

Identity Services Engine SupportBundleStatus API (version: 3.0.0).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

get_support_bundle_status_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a support bundle status by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_support_bundle_status`*

`get_support_bundle_status_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_support_bundle_status_generator`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration**class SupportBundleTriggerConfiguration**

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.0.0).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

```
create_support_bundle(description=None, host_name=None, name=None,  
                        support_bundle_include_options=None, headers=None, payload=None,  
                        active_validation=True, **query_parameters)
```

This API allows the client to create a support bundle trigger configuration.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`host_name`** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **`name`** (*string*) – Resource Name, property of the request body.
- **`support_bundle_include_options`** (*object*) – supportBundleIncludeOptions, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sync_ise_node

class SyncIseNode

Identity Services Engine Sync ISE Node API (version: 3.0.0).

Wraps the Identity Services Engine Sync ISE Node API and exposes the API as native Python methods that return native Python objects.

sync_node(*hostname=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Performing a manual sync will involve a reload of the target node, but not the primary PAN. There might be situations where if the node has been out of sync for a long time, it may not be possible to recover via a manual sync.

Parameters

- **hostname** (*string*) – hostname, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health

class SystemHealth

Identity Services Engine System Health API (version: 3.0.0).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

get_healths(*headers=None, **query_parameters*)
getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)

getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_certificate

class SystemCertificate

Identity Services Engine SystemCertificate API (version: 3.0.0).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

create_system_certificate(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_system_certificate*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_command_sets

class TacacsCommandSets

Identity Services Engine TACACSCCommandSets API (version: 3.0.0).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*,
permit_unmatched=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*,
headers=None, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_command_sets_generator*

create_tacacs_command_sets(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers

class TacacsExternalServers

Identity Services Engine TACACSExternalServers API (version: 3.0.0).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_tacacs_external_servers_by_id`

`update_tacacs_external_servers_by_id(id, connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update TACACS external servers.

Parameters

- **`connection_port (integer)`** – The port to connect the server, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`host_ip (string)`** – The server IPV4 address, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`shared_secret (string)`** – The server shared secret, property of the request body.
- **`single_connect (boolean)`** – Define the use of single connection, property of the request body.
- **`timeout (integer)`** – The server timeout, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_tacacs_external_servers_by_id*](#)

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_tacacs_external_servers_by_id*](#)

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_tacacs_external_servers`*

`get_tacacs_external_servers_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_tacacs_external_servers_generator`*

`create_tacacs_external_servers`(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

tacacs_profile

class TacacsProfile

Identity Services Engine TACACSProfile API (version: 3.0.0).

Wraps the Identity Services Engine TACACSProfile API and exposes the API as native Python methods that return native Python objects.

`get_tacacs_profile_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_profile_by_name*

get_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_profile_by_id*

update_tacacs_profile_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*,
headers=None, *payload=None*, *active_validation=True*,
***query_parameters*)

This API allows the client to update a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *session_attributes=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_profile_by_id*

delete_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS profile.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_profile_by_id*

get_tacacs_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile*

get_tacacs_profile_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type *Generator*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile_generator*

create_tacacs_profile(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.0.0).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

`get_tacacs_server_sequence_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_tacacs_server_sequence_by_name`

`get_tacacs_server_sequence_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_server_sequence_by_id*

update_tacacs_server_sequence_by_id(*id*, *description=None*, *local_accounting=None*, *name=None*, *prefix_delimiter=None*, *prefix_strip=None*, *remote_accounting=None*, *server_list=None*, *suffix_delimiter=None*, *suffix_strip=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.

- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *local_accounting=None*, *name=None*, *prefix_delimiter=None*, *prefix_strip=None*, *remote_accounting=None*, *server_list=None*, *suffix_delimiter=None*, *suffix_strip=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_server_sequence_by_id*

delete_tacacs_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_server_sequence_by_id*

get_tacacs_server_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_server_sequence*

get_tacacs_server_sequence_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_server_sequence_generator*

create_tacacs_server_sequence(*description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.0.0).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)
Alias for *get_telemetry_information*

get_telemetry_information_generator (*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration

class TrustSecConfiguration

Identity Services Engine TrustSec Configuration API (version: 3.0.0).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

get_security_groups(*headers=None, **query_parameters*)
getSecurityGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_security_groups*

get_security_group_acls(*headers=None, **query_parameters*)
getSecurityGroupAcls.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_egress_policies(*headers=None, **query_parameters*)
getEgressPolicies.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_egress_matrices(*headers=None, **query_parameters*)
getEgressMatrices.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

trust_sec_sxp

class TrustSecSxp

Identity Services Engine TrustSec SXP API (version: 3.0.0).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

get_bindings(*headers=None, **query_parameters*)
getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.0.0).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

get_ise_version_and_patch(*headers=None, **query_parameters*)
This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info**class VersionInfo**

Identity Services Engine VersionInfo API (version: 3.0.0).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

`get_version_info`(*resource, headers=None, **query_parameters*)

Get all VersionInfo.

Parameters

- **`resource`** (*basestring*) – resource path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint

class Endpoint

Identity Services Engine endpoint API (version: 3.0.0).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

release_rejected(*id*, *headers=None*, ***query_parameters*)

Alias for *release_rejected_endpoint*

deregister_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to de-register an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deregister`(*id*, *headers=None*, ***query_parameters*)

Alias for *`deregister_endpoint`*

`get_rejected_endpoints`(*headers=None*, ***query_parameters*)

This API allows the client to get the rejected endpoints.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_rejected`(*headers=None*, ***query_parameters*)

Alias for *`get_rejected_endpoints`*

`get_endpoint_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_by_id*

```
update_endpoint_by_id(id, custom_attributes=None, description=None, group_id=None,
                      identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None,
                      name=None, portal_user=None, profile_id=None,
                      static_group_assignment=None, static_profile_assignment=None, headers=None,
                      payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_endpoint_by_id*](#)

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_endpoint_by_id*](#)

register_endpoint(*custom_attributes=None*, *description=None*, *group_id=None*, *id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.

- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *register_endpoint*

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: `/ers/config/endpoint?filter={filter name}.{operator}.{logical profile name}` Example: `https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple` Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET `/ers/config/guestuser/?filter=toDate.CONTAINS.13`

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical

Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints_generator*

```
create_endpoint(custom_attributes=None, description=None, group_id=None, identity_store=None,
                identity_store_id=None, mac=None, mdm_attributes=None, name=None,
                portal_user=None, profile_id=None, static_group_assignment=None,
                static_profile_assignment=None, headers=None, payload=None, active_validation=True,
                **query_parameters)
```

This API creates an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(custom_attributes=None, description=None, group_id=None, identity_store=None,
        identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None,
        profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None,
        payload=None, active_validation=True, **query_parameters)
```

Alias for *create_endpoint*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
bulk_request_for_endpoint(operation_type=None, resource_media_type=None, headers=None,
                           payload=None, active_validation=True, **query_parameters)
```

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_endpoint*

portal

class Portal

Identity Services Engine portal API (version: 3.0.0).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

get_portal_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_by_id*

get_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals*

get_portals_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_portals_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the portal.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.0.0).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_name*

delete_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_px_grid_node_by_name*

get_px_grid_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_px_grid_node_by_id`*

`get_px_grid_node(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`

Alias for *`get_px_grid_node`*

`get_px_grid_node_generator(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the npxGrid nodes.

Parameters

- **`page(int)`** – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tasks

class Tasks

Identity Services Engine tasks API (version: 3.0.0).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

get_task_status(*headers=None, **query_parameters*)
get all task status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_task_status_by_id(*task_id, headers=None, **query_parameters*)
Monitor task status.

Parameters

- **task_id** (*basestring*) – taskId path parameter. The id of the task executed before.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

IdentityServicesEngineAPI v3.1.0**aci_bindings****class AciBindings**

Identity Services Engine ACIBindings API (version: 3.1.0).

Wraps the Identity Services Engine ACIBindings API and exposes the API as native Python methods that return native Python objects.

get_aci_bindings(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings*

get_aci_bindings_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API allows clients to retrieve all the bindings that were sent to Cisco ISE by ACI or received on ACI from Cisco ISE. The binding information will be identical to the information on ACI bindings page in the Cisco ISE UI. Filtering will be based on one attribute only, such as ip/sgt/vn/psn/learnedFrom/learnedBy with CONTAINS mode of search.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter_by** (*basestring, list, set, tuple*) – filterBy query parameter.
- **filter_value** (*basestring, list, set, tuple*) – filterValue query parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter_by=None, filter_value=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_aci_bindings_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

aci_settings

class AciSettings

Identity Services Engine ACISettings API (version: 3.1.0).

Wraps the Identity Services Engine ACISettings API and exposes the API as native Python methods that return native Python objects.

get_aci_settings(*headers=None, **query_parameters*)

This API allows the client to get ACI Settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_aci_settings*

test_aci_connectivity(*headers=None, **query_parameters*)

This API allows the client to test ACI Domain Manager connection.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_aci_settings_by_id(*id, aci50=None, aci51=None, aciipaddress=None, acipassword=None, aciuser_name=None, admin_name=None, admin_password=None, all_sxp_domain=None, default_sgt_name=None, enable_aci=None, enable_data_plane=None, enable_elements_limit=None, ip_address_host_name=None, l3_route_network=None, max_num_iepg_from_aci=None, max_num_sgt_to_aci=None, specific_sxp_domain=None, specifix_sxp_domain_list=None, suffix_to_epg=None, suffix_to_sgt=None, tenant_name=None, untagged_packet_iepg_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update ACI settings.

Parameters

- **aci50** (*boolean*) – Enable 5.0 ACI Version, property of the request body.
- **aci51** (*boolean*) – Enable 5.1 ACI Version, property of the request body.
- **aciipaddress** (*string*) – ACI Domain manager Ip Address., property of the request body.
- **acipassword** (*string*) – ACI Domain manager Password., property of the request body.
- **aciuser_name** (*string*) – ACI Domain manager Username., property of the request body.
- **admin_name** (*string*) – ACI Cluster Admin name, property of the request body.

- **admin_password** (*string*) – ACI Cluster Admin password, property of the request body.
- **all_sxp_domain** (*boolean*) – allSxpDomain, property of the request body.
- **default_sgt_name** (*string*) – defaultSgtName, property of the request body.
- **enable_aci** (*boolean*) – Enable ACI Integration, property of the request body.
- **enable_data_plane** (*boolean*) – enableDataPlane, property of the request body.
- **enable_elements_limit** (*boolean*) – enableElementsLimit, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **ip_address_host_name** (*string*) – ACI Cluster IP Address / Host name, property of the request body.
- **l3_route_network** (*string*) – l3RouteNetwork, property of the request body.
- **max_num_iepg_from_aci** (*integer*) – maxNumIepgFromAci, property of the request body.
- **max_num_sgt_to_aci** (*integer*) – maxNumSgtToAci, property of the request body.
- **specific_sxp_domain** (*boolean*) – specificSxpDomain, property of the request body.
- **specifix_sxp_domain_list** (*list*) – specifixSxpDomainList, property of the request body (list of strings).
- **suffix_to_epg** (*string*) – suffixToEpg, property of the request body.
- **suffix_to_sgt** (*string*) – suffixToSgt, property of the request body.
- **tenant_name** (*string*) – tenantName, property of the request body.
- **untagged_packet_iepg_name** (*string*) – untaggedPacketIepgName, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *aci50=None*, *aci51=None*, *aciipaddress=None*, *acipassword=None*, *aciuser_name=None*, *admin_name=None*, *admin_password=None*, *all_sxp_domain=None*, *default_sgt_name=None*, *enable_aci=None*, *enable_data_plane=None*, *enable_elements_limit=None*, *ip_address_host_name=None*, *l3_route_network=None*, *max_num_iepg_from_aci=None*, *max_num_sgt_to_aci=None*, *specific_sxp_domain=None*, *specifix_sxp_domain_list=None*, *suffix_to_epg=None*, *suffix_to_sgt=None*, *tenant_name=None*, *untagged_packet_iepg_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_aci_settings_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the Cisco ACI settings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

anc_endpoint

class AncEndpoint

Identity Services Engine ANCEndpoint API (version: 3.1.0).

Wraps the Identity Services Engine ANCEndpoint API and exposes the API as native Python methods that return native Python objects.

get_anc_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_anc_endpoint_by_id*

clear_anc_endpoint(*additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to clear the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *clear_anc_endpoint*

get_anc_endpoint(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint*

get_anc_endpoint_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC endpoints. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_endpoint_generator*

apply_anc_endpoint(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to apply the required configuration.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

apply(*additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *apply_anc_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC Endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_anc_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_endpoint*

monitor_bulk_status_anc_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status`(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_endpoint*

active_directory

class `ActiveDirectory`

Identity Services Engine ActiveDirectory API (version: 3.1.0).

Wraps the Identity Services Engine ActiveDirectory API and exposes the API as native Python methods that return native Python objects.

`get_active_directory_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get Active Directory by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_name*

get_user_groups(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to get groups of which a given user is a member.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

load_groups_from_domain(*id*, *ad_attributes=None*, *ad_scopes_names=None*, *adgroups=None*, *advanced_settings=None*, *description=None*, *domain=None*, *enable_domain_white_list=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API loads domain groups configuration from Active Directory into Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.

- **id** (*basestring*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and `./_` characters, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

leave_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API makes a Cisco ISE node to leave an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`is_user_member_of_groups`(*id*, *additional_data=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API verifies if the user is a member of the given groups.

Parameters

- **`additional_data`** (*list*) – *additionalData*, property of the request body (list of objects).
- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_trusted_domains`(*id*, *headers=None*, ***query_parameters*)

This API gets the list of domains that are accessible through the given join point via trust relationships.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`join_domain_with_all_nodes`(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins all Cisco ISE Nodes to an Active Directory domain.

Parameters

- **`additional_data`** (*list*) – `additionalData`, property of the request body (list of objects).
- **`id`** (*basestring*) – `id` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`leave_domain_with_all_nodes`(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins makes all Cisco ISE nodes leave an Active Directory domain.

Parameters

- **`additional_data`** (*list*) – `additionalData`, property of the request body (list of objects).

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_groups_by_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API lists the groups of the given domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API fetchs the join point details by ID. The ID can be retrieved with the Get All operation.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_active_directory_by_id*

delete_active_directory_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an AD join point from Cisco ISE.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_active_directory_by_id*

join_domain(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API joins a Cisco ISE node to an Active Directory domain.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_directory(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory*

get_active_directory_generator(*page=None, size=None, headers=None, **query_parameters*)

This API lists all the join points for Active Directory domains in Cisco ISE.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- *RestResponse*: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type *Generator*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_active_directory_generator*

```
create_active_directory(ad_attributes=None, ad_scopes_names=None, adgroups=None,  
                        advanced_settings=None, description=None, domain=None,  
                        enable_domain_white_list=None, id=None, name=None, headers=None,  
                        payload=None, active_validation=True, **query_parameters)
```

This API creates an AD join point in Cisco ISE.

Parameters

- **ad_attributes** (*object*) – Holds list of AD Attributes, property of the request body.
- **ad_scopes_names** (*string*) – String that contains the names of the scopes that the active directory belongs to. Names are separated by comma. Alphanumeric, underscore (_) characters are allowed, property of the request body.
- **adgroups** (*object*) – Holds list of AD Groups, property of the request body.
- **advanced_settings** (*object*) – advancedSettings, property of the request body.
- **description** (*string*) – No character restriction, property of the request body.
- **domain** (*string*) – The AD domain. Alphanumeric, hyphen (-) and dot (.) characters are allowed, property of the request body.
- **enable_domain_white_list** (*boolean*) – enableDomainWhiteList, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **name** (*string*) – Resource Name. Maximum 32 characters allowed. Allowed characters are alphanumeric and .-/characters, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(ad_attributes=None, ad_scopes_names=None, adgroups=None, advanced_settings=None,  
      description=None, domain=None, enable_domain_white_list=None, id=None, name=None,  
      headers=None, payload=None, active_validation=True, **query_parameters)
```

Alias for *create_active_directory*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the active directory.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

admin_user

class AdminUser

Identity Services Engine AdminUser API (version: 3.1.0).

Wraps the Identity Services Engine AdminUser API and exposes the API as native Python methods that return native Python objects.

get_admin_user_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an admin user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_admin_user_by_id*

get_admin_users(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users*

get_admin_users_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the admin users. Filter: [firstName, lastName, adminGroups, name, description, inactiveAccountNeverDisabled, includeSystemAlarmsInEmail, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_admin_users_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the admin user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

allowed_protocols**class AllowedProtocols**

Identity Services Engine AllowedProtocols API (version: 3.1.0).

Wraps the Identity Services Engine AllowedProtocols API and exposes the API as native Python methods that return native Python objects.

get_allowed_protocol_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an allowed protocol by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *get_allowed_protocol_by_name*

`get_allowed_protocol_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an allowed protocol by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *get_allowed_protocol_by_id*

```
update_allowed_protocol_by_id(id, allow_chap=None, allow_eap_fast=None, allow_eap_md5=None,
                              allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None,
                              allow_ms_chap_v1=None, allow_ms_chap_v2=None,
                              allow_pap_ascii=None, allow_peap=None,
                              allow_preferred_eap_protocol=None, allow_teap=None,
                              allow_weak_ciphers_for_eap=None, description=None,
                              eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None,
                              name=None, peap=None, preferred_eap_protocol=None,
                              process_host_lookup=None, require_message_auth=None, teap=None,
                              headers=None, payload=None, active_validation=True,
                              **query_parameters)
```

This API allows the client to update an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.
- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **id** (*basestring*) – Resource UUID, Mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.

- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *allow_chap=None*, *allow_eap_fast=None*, *allow_eap_md5=None*, *allow_eap_tls=None*, *allow_eap_ttls=None*, *allow_leap=None*, *allow_ms_chap_v1=None*, *allow_ms_chap_v2=None*, *allow_pap_ascii=None*, *allow_peap=None*, *allow_preferred_eap_protocol=None*, *allow_teap=None*, *allow_weak_ciphers_for_eap=None*, *description=None*, *eap_fast=None*, *eap_tls=None*, *eap_ttls_l_bit=None*, *eap_ttls=None*, *name=None*, *peap=None*, *preferred_eap_protocol=None*, *process_host_lookup=None*, *require_message_auth=None*, *teap=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_allowed_protocol_by_id*

delete_allowed_protocol_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an allowed protocol.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_allowed_protocol_by_id*

get_allowed_protocols(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_allowed_protocols*

get_allowed_protocols_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the allowed protocols.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_allowed_protocols_generator*

create_allowed_protocol(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_tls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an allowed protocol.

Parameters

- **allow_chap** (*boolean*) – allowChap, property of the request body.
- **allow_eap_fast** (*boolean*) – allowEapFast, property of the request body.
- **allow_eap_md5** (*boolean*) – allowEapMd5, property of the request body.
- **allow_eap_tls** (*boolean*) – allowEapTls, property of the request body.
- **allow_eap_ttls** (*boolean*) – allowEapTtls, property of the request body.
- **allow_leap** (*boolean*) – allowLeap, property of the request body.

- **allow_ms_chap_v1** (*boolean*) – allowMsChapV1, property of the request body.
- **allow_ms_chap_v2** (*boolean*) – allowMsChapV2, property of the request body.
- **allow_pap_ascii** (*boolean*) – allowPapAscii, property of the request body.
- **allow_peap** (*boolean*) – allowPeap, property of the request body.
- **allow_preferred_eap_protocol** (*boolean*) – allowPreferredEapProtocol, property of the request body.
- **allow_teap** (*boolean*) – allowTeap, property of the request body.
- **allow_weak_ciphers_for_eap** (*boolean*) – allowWeakCiphersForEap, property of the request body.
- **description** (*string*) – description, property of the request body.
- **eap_fast** (*object*) – The eapFast is required only if allowEapFast is true, otherwise it must be ignored. The object eapFast contains the settings for EAP FAST protocol, property of the request body.
- **eap_tls** (*object*) – The eapTls is required only if allowEapTls is true, otherwise it must be ignored. The object eapTls contains the settings for EAP TLS protocol, property of the request body.
- **eap_tls_l_bit** (*boolean*) – eapTlsLBit, property of the request body.
- **eap_ttls** (*object*) – The eapTtls is required only if allowEapTtls is true, otherwise it must be ignored. The object eapTtls contains the settings for EAP TTLS protocol, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **peap** (*object*) – peap, property of the request body.
- **preferred_eap_protocol** (*string*) – The preferredEapProtocol is required only if allowPreferredEapProtocol is true, otherwise it must be ignored. Allowed Values: EAP_FAST, PEAP, LEAP, EAP_MD5, EAP_TLS, EAP_TTLS, TEAP, property of the request body.
- **process_host_lookup** (*boolean*) – processHostLookup, property of the request body.
- **require_message_auth** (*boolean*) – requireMessageAuth, property of the request body.
- **teap** (*object*) – The teap is required only if allowTeap is true, otherwise it must be ignored. The object teap contains the settings for TEAP protocol, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*allow_chap=None, allow_eap_fast=None, allow_eap_md5=None, allow_eap_tls=None, allow_eap_ttls=None, allow_leap=None, allow_ms_chap_v1=None, allow_ms_chap_v2=None, allow_pap_ascii=None, allow_peap=None, allow_preferred_eap_protocol=None, allow_teap=None, allow_weak_ciphers_for_eap=None, description=None, eap_fast=None, eap_tls=None, eap_ttls_l_bit=None, eap_ttls=None, name=None, peap=None, preferred_eap_protocol=None, process_host_lookup=None, require_message_auth=None, teap=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_allowed_protocol*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the allowed protocols.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

anc_policy

class AncPolicy

Identity Services Engine AncPolicy API (version: 3.1.0).

Wraps the Identity Services Engine AncPolicy API and exposes the API as native Python methods that return native Python objects.

get_anc_policy_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_anc_policy_by_name*

get_anc_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an ANC policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_anc_policy_by_id`

`update_anc_policy_by_id(id, actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an ANC policy.

Parameters

- **`actions (list)`** – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *actions=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_anc_policy_by_id*

delete_anc_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to delete an ANC policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_anc_policy_by_id*

get_anc_policy(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*,
 headers=None, ***query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy*

get_anc_policy_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the ANC policies. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_anc_policy_generator*

create_anc_policy(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an ANC policy.

Parameters

- **actions** (*list*) – QUARANTINE: Allows you to use Exception policies (authorization policies) to limit or deny an endpoint access to the network. PORTBOUNCE: Resets the port on the network device to which the endpoint is connected. SHUTDOWN : Shuts down the port on the network device to which the endpoint is connected. RE_AUTHENTICATE: Re-authenticates the session from the endpoint., property of the request body (list of strings. Available values are 'QUARANTINE', 'PORTBOUNCE', 'SHUTDOWN' and 'RE_AUTHENTICATE').
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*actions=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_anc_policy*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the ANC policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_anc_policy`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type (string)`** – operationType, property of the request body.
- **`resource_media_type (string)`** – resourceMediaType, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_anc_policy*

monitor_bulk_status_anc_policy(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_anc_policy*

authorization_profile

class AuthorizationProfile

Identity Services Engine AuthorizationProfile API (version: 3.1.0).

Wraps the Identity Services Engine AuthorizationProfile API and exposes the API as native Python methods that return native Python objects.

get_authorization_profile_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_authorization_profile_by_name*

get_authorization_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an authorization profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_authorization_profile_by_id`

`update_authorization_profile_by_id(id, access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an authorization profile.

Parameters

- **`access_type (string)`** – Allowed Values: `ACCESS_ACCEPT`, `ACCESS_REJECT`, property of the request body.
- **`acl (string)`** – `acl`, property of the request body.
- **`advanced_attributes (list)`** – `advancedAttributes`, property of the request body (list of objects).
- **`agentless_posture (boolean)`** – `agentlessPosture`, property of the request body.
- **`airespace_acl (string)`** – `airespaceACL`, property of the request body.
- **`airespace_ipv6_acl (string)`** – `airespaceIPv6ACL`, property of the request body.
- **`asa_vpn (string)`** – `asaVpn`, property of the request body.
- **`authz_profile_type (string)`** – Allowed Values: `SWITCH`, `TRUSTSEC`, `TACACS` `SWITCH` is used for Standard Authorization Profiles, property of the request body.
- **`auto_smart_port (string)`** – `autoSmartPort`, property of the request body.
- **`avc_profile (string)`** – `avcProfile`, property of the request body.
- **`dacl_name (string)`** – `daclName`, property of the request body.
- **`description (string)`** – `description`, property of the request body.

- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*basestring*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.
- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_type*=None, *acl*=None, *advanced_attributes*=None, *agentless_posture*=None, *airespace_acl*=None, *airespace_ipv6_acl*=None, *asa_vpn*=None, *authz_profile_type*=None, *auto_smart_port*=None, *avc_profile*=None, *dacl_name*=None, *description*=None, *easywired_session_candidate*=None, *interface_template*=None, *ipv6_acl_filter*=None, *ipv6_dacl_name*=None, *mac_sec_policy*=None, *name*=None, *neat*=None, *profile_name*=None, *reauth*=None, *service_template*=None, *track_movement*=None, *vlan*=None, *voice_domain_permission*=None, *web_auth*=None, *web_redirection*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for [update_authorization_profile_by_id](#)

delete_authorization_profile_by_id(*id*, *headers*=None, ***query_parameters*)

This API deletes an authorization profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers*=None, ***query_parameters*)

Alias for [delete_authorization_profile_by_id](#)

get_authorization_profiles(*page*=None, *size*=None, *headers*=None, ***query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_authorization_profiles*

`get_authorization_profiles_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all authorization profiles.

Parameters

- **`page (int)`** – page query parameter. Page number.
- **`size (int)`** – size query parameter. Number of objects returned per page.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_authorization_profiles_generator*

```
create_authorization_profile(access_type=None, acl=None, advanced_attributes=None,  
                             agentless_posture=None, airespace_acl=None,  
                             airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None,  
                             auto_smart_port=None, avc_profile=None, dacl_name=None,  
                             description=None, easywired_session_candidate=None, id=None,  
                             interface_template=None, ipv6_acl_filter=None,  
                             ipv6_dacl_name=None, mac_sec_policy=None, name=None,  
                             neat=None, profile_name=None, reauth=None, service_template=None,  
                             track_movement=None, vlan=None, voice_domain_permission=None,  
                             web_auth=None, web_redirection=None, headers=None,  
                             payload=None, active_validation=True, **query_parameters)
```

This API creates an authorization profile.

Parameters

- **access_type** (*string*) – Allowed Values: ACCESS_ACCEPT, ACCESS_REJECT, property of the request body.
- **acl** (*string*) – acl, property of the request body.
- **advanced_attributes** (*list*) – advancedAttributes, property of the request body (list of objects).
- **agentless_posture** (*boolean*) – agentlessPosture, property of the request body.
- **airespace_acl** (*string*) – airespaceACL, property of the request body.
- **airespace_ipv6_acl** (*string*) – airespaceIPv6ACL, property of the request body.
- **asa_vpn** (*string*) – asaVpn, property of the request body.
- **authz_profile_type** (*string*) – Allowed Values: SWITCH, TRUSTSEC, TACACS SWITCH is used for Standard Authorization Profiles, property of the request body.
- **auto_smart_port** (*string*) – autoSmartPort, property of the request body.
- **avc_profile** (*string*) – avcProfile, property of the request body.
- **dacl_name** (*string*) – daclName, property of the request body.
- **description** (*string*) – description, property of the request body.
- **easywired_session_candidate** (*boolean*) – easywiredSessionCandidate, property of the request body.
- **id** (*string*) – Resource UUID value, property of the request body.
- **interface_template** (*string*) – interfaceTemplate, property of the request body.
- **ipv6_acl_filter** (*string*) – ipv6ACLFILTER, property of the request body.
- **ipv6_dacl_name** (*string*) – ipv6DaclName, property of the request body.
- **mac_sec_policy** (*string*) – Allowed Values: MUST_SECURE, MUST_NOT_SECURE, SHOULD_SECURE, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **neat** (*boolean*) – neat, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **reauth** (*object*) – reauth, property of the request body.
- **service_template** (*boolean*) – serviceTemplate, property of the request body.

- **track_movement** (*boolean*) – trackMovement, property of the request body.
- **vlan** (*object*) – vlan, property of the request body.
- **voice_domain_permission** (*boolean*) – voiceDomainPermission, property of the request body.
- **web_auth** (*boolean*) – webAuth, property of the request body.
- **web_redirection** (*object*) – webRedirection, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*access_type=None, acl=None, advanced_attributes=None, agentless_posture=None, airespace_acl=None, airespace_ipv6_acl=None, asa_vpn=None, authz_profile_type=None, auto_smart_port=None, avc_profile=None, dacl_name=None, description=None, easywired_session_candidate=None, id=None, interface_template=None, ipv6_acl_filter=None, ipv6_dacl_name=None, mac_sec_policy=None, name=None, neat=None, profile_name=None, reauth=None, service_template=None, track_movement=None, vlan=None, voice_domain_permission=None, web_auth=None, web_redirection=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_authorization_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the authorization profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

byod_portal

class ByodPortal

Identity Services Engine BYODPortal API (version: 3.1.0).

Wraps the Identity Services Engine BYODPortal API and exposes the API as native Python methods that return native Python objects.

`get_byod_portal_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a BYOD portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter. Portal id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_byod_portal_by_id`

```
update_byod_portal_by_id(id, customizations=None, description=None, name=None,
                        portal_test_url=None, portal_type=None, settings=None, headers=None,
                        payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a BYOD portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – Resource UUID, mandatory for update, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, customizations=None, description=None, name=None, portal_test_url=None,
            portal_type=None, settings=None, headers=None, payload=None, active_validation=True,
            **query_parameters)
```

Alias for *update_byod_portal_by_id*

```
delete_byod_portal_by_id(id, headers=None, **query_parameters)
```

This API deletes a BYOD portal by ID.

Parameters

- **id** (*basestring*) – id path parameter. Portal id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_byod_portal_by_id*

get_byod_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal*

get_byod_portal_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the BYOD portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_byod_portal_generator*

create_byod_portal(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a BYOD portal.

Parameters

- **customizations (object)** – Defines all of the Portal Customizations available for a BYOD, property of the request body.
- **description (string)** – description, property of the request body.
- **id (string)** – Resource UUID, mandatory for update, property of the request body.
- **name (string)** – Resource Name, property of the request body.
- **portal_test_url (string)** – URL to bring up a test page for this portal, property of the request body.
- **portal_type (string)** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings (object)** – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, id=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_byod_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the BYOD portal.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

backup_and_restore

class BackupAndRestore

Identity Services Engine Backup And Restore API (version: 3.1.0).

Wraps the Identity Services Engine Backup And Restore API and exposes the API as native Python methods that return native Python objects.

config_backup(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Triggers on demand configuration backup on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

config(*backup_encryption_key=None, backup_name=None, repository_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *config_backup*

cancel_backup(*headers=None, **query_parameters*)

Cancels the backup job running on the node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

cancel(*headers=None, **query_parameters*)

Alias for *cancel_backup*

get_last_config_backup_status(*headers=None, **query_parameters*)

Gives the last backup status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_last_status(*headers=None, **query_parameters*)

Alias for *get_last_config_backup_status*

```
restore_config_backup(backup_encryption_key=None, repository_name=None, restore_file=None,  
                      restore_include_adeos=None, headers=None, payload=None,  
                      active_validation=True, **query_parameters)
```

Triggers a configuration DB restore job on the ISE node. The API returns the task ID. Use the Task Service status API to get the status of the backup job.

Parameters

- **backup_encryption_key** (*string*) – The encryption key which was provided at the time of taking backup., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the backup file exists., property of the request body.
- **restore_file** (*string*) – Name of the backup file to be restored on ISE node., property of the request body.
- **restore_include_adeos** (*string*) – Determines whether the ADE-OS configure is restored. Possible values true, false, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
restore(backup_encryption_key=None, repository_name=None, restore_file=None,  
        restore_include_adeos=None, headers=None, payload=None, active_validation=True,  
        **query_parameters)
```

Alias for *restore_config_backup*

```
update_scheduled_config_backup(backup_description=None, backup_encryption_key=None,  
                                backup_name=None, end_date=None, frequency=None,  
                                month_day=None, repository_name=None, start_date=None,  
                                status=None, time=None, week_day=None, headers=None,  
                                payload=None, active_validation=True, **query_parameters)
```

Update the Schedule of the configuration backup on the ISE node as per the input parameters. This API only helps in editing the schedule.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcliSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node., property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_scheduled_config_backup*

create_scheduled_config_backup(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Schedules the configuration backup on the ISE node as per the input parameters. This API helps in creating the schedule for the first time.

Parameters

- **backup_description** (*string*) – Description of the backup., property of the request body.
- **backup_encryption_key** (*string*) – The encryption key for the backed up file. Encryption key must satisfy the following criteria Contains at least one uppercase letter [A-Z], Contains at least one lowercase letter [a-z], Contains at least one digit [0-9], Contain only [A-Z][a-z][0-9]_#, Has at least 8 characters, Has not more than 15 characters, Must not contain 'CcLiSsCco', Must not begin with, property of the request body.
- **backup_name** (*string*) – The backup file will get saved with this name., property of the request body.
- **end_date** (*string*) – End date of the scheduled backup job. Allowed format MM/DD/YYYY. End date is not required in case of ONE_TIME frequency., property of the request body.
- **frequency** (*string*) – Frequency with which the backup will get scheduled in the ISE node., property of the request body. Available values are 'DAILY', 'MONTHLY', 'ONCE' and 'WEEKLY'.
- **month_day** (*string*) – Day of month you want backup to be performed on when scheduled frequency is MONTHLY. Allowed values from 1 to 28., property of the request body.
- **repository_name** (*string*) – Name of the configured repository where the generated backup file will get copied., property of the request body.
- **start_date** (*string*) – Start date for scheduling the backup job. Allowed format MM/DD/YYYY., property of the request body.
- **status** (*string*) – Enable or disable scheduled backup., property of the request body. Available values are 'DISABLE' and 'ENABLE'.
- **time** (*string*) – Time at which backup job get scheduled. example 12:00 AM, property of the request body.
- **week_day** (*string*) – Day of week you want backup to be performed on when scheduled frequency is WEEKLY, property of the request body. Available values are 'FRI', 'MON', 'SAT', 'SUN', 'THU', 'TUE' and 'WED'.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*backup_description=None, backup_encryption_key=None, backup_name=None, end_date=None, frequency=None, month_day=None, repository_name=None, start_date=None, status=None, time=None, week_day=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_scheduled_config_backup*

certificate_profile

class CertificateProfile

Identity Services Engine CertificateProfile API (version: 3.1.0).

Wraps the Identity Services Engine CertificateProfile API and exposes the API as native Python methods that return native Python objects.

get_certificate_profile_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get a certificate profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_certificate_profile_by_name`*

`get_certificate_profile_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a certificate profile by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_certificate_profile_by_id`*

`update_certificate_profile_by_id(id, allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – allowedAsUserName, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when CERTIFICATE is chosen in usernameFrom. Allowed values: SUBJECT_COMMON_NAME SUBJECT_ALTERNATIVE_NAME SUBJECT_SERIAL_NUMBER SUBJECT_ALTERNATIVE_NAME_OTHER_NAME SUBJECT_ALTERNATIVE_NAME_EMAIL SUBJECT_ALTERNATIVE_NAME_DNS. Additional internal value ALL_SUBJECT_AND_ALTERNATIVE_NAMES is used automatically when usernameFrom=UPN, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: NEVER RESOLVE_IDENTITY_AMBIGUITY BINARY_COMPARISON, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: CERTIFICATE (for a specific attribute as defined in certificateAttributeName) UPN (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, allowed_as_user_name=None, certificate_attribute_name=None, description=None,
              external_identity_store_name=None, match_mode=None, name=None,
              username_from=None, headers=None, payload=None, active_validation=True,
              **query_parameters)
```

Alias for *update_certificate_profile_by_id*

```
get_certificate_profile(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(page=None, size=None, headers=None, **query_parameters)
```

Alias for *get_certificate_profile*

```
get_certificate_profile_generator(page=None, size=None, headers=None, **query_parameters)
```

This API allows the client to get all the certificate profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_certificate_profile_generator*

create_certificate_profile(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a certificate profile.

Parameters

- **allowed_as_user_name** (*boolean*) – `allowedAsUserName`, property of the request body.
- **certificate_attribute_name** (*string*) – Attribute name of the Certificate Profile used only when `CERTIFICATE` is chosen in `usernameFrom`. Allowed values: `SUBJECT_COMMON_NAME` `SUBJECT_ALTERNATIVE_NAME` `SUBJECT_SERIAL_NUMBER` `SUBJECT` `SUBJECT_ALTERNATIVE_NAME_OTHER_NAME` `SUBJECT_ALTERNATIVE_NAME_EMAIL` `SUBJECT_ALTERNATIVE_NAME_DNS`. Additional internal value `ALL_SUBJECT_AND_ALTERNATIVE_NAMES` is used automatically when `usernameFrom=UPN`, property of the request body.
- **description** (*string*) – description, property of the request body.
- **external_identity_store_name** (*string*) – Referred IDStore name for the Certificate Profile or [not applicable] in case no identity store is chosen, property of the request body.
- **id** (*string*) – id, property of the request body.
- **match_mode** (*string*) – Match mode of the Certificate Profile. Allowed values: `NEVER` `RESOLVE_IDENTITY_AMBIGUITY` `BINARY_COMPARISON`, property of the request body.
- **name** (*string*) – name, property of the request body.
- **username_from** (*string*) – The attribute in the certificate where the user name should be taken from. Allowed values: `CERTIFICATE` (for a specific attribute as defined in `certificateAttributeName`) `UPN` (for using any Subject or Alternative Name Attributes in the Certificate an option only in AD), property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*allowed_as_user_name=None, certificate_attribute_name=None, description=None, external_identity_store_name=None, id=None, match_mode=None, name=None, username_from=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_certificate_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

certificate_template

class CertificateTemplate

Identity Services Engine CertificateTemplate API (version: 3.1.0).

Wraps the Identity Services Engine CertificateTemplate API and exposes the API as native Python methods that return native Python objects.

get_certificate_template_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_name*

get_certificate_template_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a certificate template by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template_by_id*

get_certificate_template(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_certificate_template*

get_certificate_template_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get aall the certificate templates.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *`get_certificate_template_generator`*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the certificate template.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *`RestResponse`*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

certificates

class Certificates

Identity Services Engine Certificates API (version: 3.1.0).

Wraps the Identity Services Engine Certificates API and exposes the API as native Python methods that return native Python objects.

get_csrs(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csrs_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject timeStamp Supported Date Format: yyyy-MM-dd HH:mm:ss.SSS Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
generate_csr(allow_wild_card_cert=None, certificate_policies=None, digest_type=None,
             hostnames=None, key_length=None, key_type=None, portal_group_tag=None,
             san_dir=None, san_dns=None, san_ip=None, san_uri=None, subject_city=None,
             subject_common_name=None, subject_country=None, subject_org=None,
             subject_org_unit=None, subject_state=None, used_for=None, headers=None,
             payload=None, active_validation=True, **query_parameters)
```

Generate a certificate signing request for Multi-Use, Admin, EAP Authentication, RADIUS DTLS, Px-Grid, SAML, Portal and IMS Services. Following Parameters are present in POST request body

PARAMETER DESCRIPTION EXAMPLE

hostnames List of ise node hostnames for which CSRs should be generated [ise-host1, ise-host2]

allowWildCardCert Allow use of WildCards in certificates false

keyLength Length of the Key used for CSR generation (required) 512

keyType Type of key used for CSR generation either RSA or ECDSA(required) RSA

digestType Hash algorithm used for signing CSR(required) SHA-256

usedFor Certificate Usage(required) MULTI-USE

subjectCommonName Certificate common name(CN)(required) \$FQDN\$

subjectOrgUnit Certificate organizational unit(OU) Engineering

subjectOrg Certificate organization (O) Cisco

subjectCity Certificate city or locality (L) San Jose

subjectState Certificate state (ST) California

subjectCountry Certificate country (C) US

sanDNS Array of SAN(Subject Alternative Name) DNS entries(optional) [ise.example.com]

sanIP Array of SAN IP entries(optional) [1.1.1.1]

sanURI Array of SAN URI entries(optional) [https://1.1.1.1]

sanDir Array of SAN DIR entries(optional) [CN=AAA,DC=COM,C=IL]

portalGroupTag Portal Group Tag when using certificate for PORTAL service Default Portal Certificate Group

NOTE: For allowWildCardCert to be false, the below mentioned parameter is mandatory: hostnames

When Certificate is selected to be used for Portal Service, the below mentioned parameter is mandatory: portalGroupTag .

Parameters

- **allow_wild_card_cert** (*boolean*) – allowWildCardCert, property of the request body.
- **certificate_policies** (*string*) – certificatePolicies, property of the request body.
- **digest_type** (*string*) – digestType, property of the request body. Available values are ‘SHA-256’, ‘SHA-384’ and ‘SHA-512’.
- **hostnames** (*list*) – hostnames, property of the request body (list of strings).
- **key_length** (*string*) – keyLength, property of the request body. Available values are ‘1024’, ‘2048’, ‘4096’ and ‘512’.
- **key_type** (*string*) – keyType, property of the request body. Available values are ‘ECDSA’ and ‘RSA’.
- **portal_group_tag** (*string*) – portalGroupTag, property of the request body.
- **san_dns** (*list*) – sanDNS, property of the request body (list of strings).
- **san_dir** (*list*) – sanDir, property of the request body (list of strings).
- **san_ip** (*list*) – sanIP, property of the request body (list of strings).
- **san_uri** (*list*) – sanURI, property of the request body (list of strings).
- **subject_city** (*string*) – subjectCity, property of the request body.
- **subject_common_name** (*string*) – subjectCommonName, property of the request body.
- **subject_country** (*string*) – subjectCountry, property of the request body.
- **subject_org** (*string*) – subjectOrg, property of the request body.
- **subject_org_unit** (*string*) – subjectOrgUnit, property of the request body.
- **subject_state** (*string*) – subjectState, property of the request body.

- **used_for** (*string*) – usedFor, property of the request body. Available values are ‘ADMIN’, ‘DTLS- AUTH’, ‘EAP-AUTH’, ‘IMS’, ‘MULTI-USE’, ‘PORTAL’, ‘PXGRID’ and ‘SAML’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_csr(*hostname, id, dirpath=None, save_file=None, headers=None, **query_parameters*)

The response of this API carries a CSR corresponding to the requested ID.

Parameters

- **hostname** (*basestring*) – hostname path parameter. The hostname to which the CSR belongs.
- **id** (*basestring*) – id path parameter. The ID of the CSR to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type urllib3.response.HTTPResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

generate_intermediate_ca_csr(*headers=None, **query_parameters*)

CSR Generation for Intermediate Certificates.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_csr_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be returned.
- **id** (*basestring*) – id path parameter. The ID of the Certificate Signing Request returned.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_csr_by_id(*host_name*, *id*, *headers=None*, ***query_parameters*)

This API deletes a Certificate Signing Request of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which CSR's should be deleted.
- **id** (*basestring*) – id path parameter. The ID of the Certificate Signing Request to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

regenerate_ise_root_ca(*remove_existing_ise_intermediate_csr=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API will initiate regeneration of ISE root CA certificate chain. Response contains id which can be used to track the status. Setting “removeExistingISEIntermediateCSR” to true will remove existing ISE Intermediate CSR.

Parameters

- **remove_existing_ise_intermediate_csr** (*boolean*) – Setting this attribute to true will remove existing ISE Intermediate CSR, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`renew_certificates`(*cert_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API will initiate regeneration of certificates. Response contains id which can be used to track the status.

Parameters

- **`cert_type`** (*string*) – `certType`, property of the request body. Available values are 'IMS' and 'OCSP'.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

```
bind_csr(admin=None, allow_extended_validity=None, allow_out_of_date_cert=None,
allow_replacement_of_certificates=None, allow_replacement_of_portal_group_tag=None,
data=None, eap=None, host_name=None, id=None, ims=None, name=None, portal=None,
portal_group_tag=None, pxgrid=None, radius=None, saml=None,
validate_certificate_extensions=None, headers=None, payload=None, active_validation=True,
**query_parameters)
```

Bind CA Signed Certificate. **NOTE: This API requires an** existing Certificate Signing Request, and the root certificate must already be trusted. **NOTE:** The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. **NOTE:** Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. Signed Certificate data Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). awk 'NF {sub(/

/, ""); printf "%sn", \$0;}' <<your .pem file>> allowExtendedValidity Allow the certificates greater than validity of 398 days (required) false allowOutOfDateCert Allow out of date certificates (required) false allowReplacementOfCertificates Allow Replacement of certificates (required) false allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADSec server false pxgrid Use certificate for the pxGrid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group validateCertificateExtensions Validate Certificate Extensions false Following Roles can be used in any combinations **ROLE DEFAULT WARNING** Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Args:

admin(boolean): Use certificate to authenticate the ISE Admin Portal, property of the request body.

allow_extended_validity(boolean): Allow import of certificates with validity greater than 398 days (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_replacement_of_certificates(boolean): Allow Replacement of certificates (required), property of the request body.

allow_replacement_of_portal_group_tag(boolean): Allow Replacement of Portal Group Tag (required), property of the request body.

data(string): Signed Certificate data (required), property of the request body.

eap(boolean): Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.

host_name(string): Name of Host whose CSR ID has been provided (required), property of the request body.

id(string): ID of the generated CSR (required), property of the request body.

ims(boolean): Use certificate for the ISE Messaging Service, property of the request body.

name(string): Friendly Name of the certificate, property of the request body.

portal(boolean): Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Raises: TypeError: If the parameter types are incorrect. MalformedRequest: If the request body created is invalid. ApiError: If the Identity Services Engine cloud returns an error.

export_system_certificate(*export=None, id=None, password=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Export System Certificate. Following Parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE
id ID of a System Certificate(required) < SYSTEM_CERT_ID >
export One of the below option is required
"CERTIFICATE" : Export only Certificate without Private Key
"CERTIFICATE_WITH_PRIVATE_KEY" : Export both Certificate and Private Key("certificatePassword" is required)
CERTIFICATE_WITH_PRIVATE_KEY password Certificate Password (required if "export" : CERTIFICATE_WITH_PRIVATE_KEY)
Password Constraints: Alphanumeric Minimum of 8 Characters Maximum of 100 Characters
Passw*** NOTE: The response of this API carries a ZIP file containing the certificate and private key if "export" : "CERTIFICATE_WITH_PRIVATE_KEY" in the request. If "export" : "CERTIFICATE" in request body, the response carries a ZIP file containing only the certificate.
WARNING: Exporting a private key is not a secure operation. It could lead to possible exposure of the private key. .

Parameters

- **export** (*string*) – export, property of the request body. Available values are ‘CERTIFICATE’ and ‘CERTIFICATE_WITH_PRIVATE_KEY’.
- **id** (*string*) – id, property of the request body.
- **password** (*string*) – password, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type urllib3.response.HTTPResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_system_certificate(admin=None, allow_extended_validity=None,
                        allow_out_of_date_cert=None, allow_replacement_of_certificates=None,
                        allow_replacement_of_portal_group_tag=None,
                        allow_shal_certificates=None, allow_wild_card_certificates=None,
                        data=None, eap=None, ims=None, name=None, password=None,
                        portal=None, portal_group_tag=None,
                        portal_tag_transfer_for_same_subject=None, private_key_data=None,
                        pxgrid=None, radius=None, role_transfer_for_same_subject=None,
                        saml=None, validate_certificate_extensions=None, headers=None,
                        payload=None, active_validation=True, **query_parameters)
```

Import an X509 certificate as a system certificate. NOTE: The certificate may have a validity period longer than 398 days. It may be untrusted by many browsers. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
 PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate. Sys-
 tem Certificate password Password of the certificate to be imported (required). Passw*** data Plain-
 text contents of the certificate file. Every space needs to be replaced with newline escape sequence
 (

) (required). awk ‘NF {sub(/

/, “”); printf ““%sn”, \$0;}’ <<your .pem file>> privateKeyData Plain-text contents of the private key file.
 Every space needs to be replaced with newline escape sequence (

) (required). awk ‘NF {sub(/ /,

```
“”); printf(“%sn”, $0; }’ <<your .pem file>> allowOutOfDateCert Allow out of date certificates (required) false allowSHA1Certificates Allow SHA1 based certificates (required) false allowExtendedValidity Allow the certificates greater than validity of 398 days (required) false roleTransferForSameSubject Allow the transfer of roles to certificates with same subject false portalTagTransferForSameSubject Acquire the group tag of the matching certificate false admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADSec server false pxgrid Use certificate for the px-Grid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false allowWildcardCertificates Allow use of WildCards in certificates false validateCertificateExtensions Validate Certificate Extensions false Following Roles can be used in any combinations ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .
```

Args:

- admin(boolean):** Use certificate to authenticate the ISE Admin Portal, property of the request body.
- allow_extended_validity(boolean):** Allow import of certificates with validity greater than 398 days (required), property of the request body.
- allow_out_of_date_cert(boolean):** Allow out of date certificates (required), property of the request body.
- allow_replacement_of_certificates(boolean):** Allow Replacement of certificates (required), property of the request body.
- allow_replacement_of_portal_group_tag(boolean):** Allow Replacement of Portal Group Tag (required), property of the request body.
- allow_sha1_certificates(boolean):** Allow SHA1 based certificates (required), property of the request body.
- allow_wild_card_certificates(boolean):** Allow Wildcard Certificates, property of the request body.
- data(string):** Certificate Content (required), property of the request body.
- eap(boolean):** Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- ims(boolean):** Use certificate for the ISE Messaging Service, property of the request body.
- name(string):** Name of the certificate, property of the request body.
- password(string):** Certificate Password (required), property of the request body.
- portal(boolean):** Use for portal, property of the request body.

portal_group_tag(string): Set Group tag, property of the request body.

portal_tag_transfer_for_same_subject(boolean): Allow overwriting the portal tag from matching certificate of same subject, property of the request body.

private_key_data(string): Private Key data (required), property of the request body.

pxgrid(boolean): Use certificate for the pxGrid Controller, property of the request body.

radius(boolean): Use certificate for the RADSec server, property of the request body.

role_transfer_for_same_subject(boolean): Allow transfer of roles for certificate with matching subject, property of the request body.

saml(boolean): Use certificate for SAML Signing, property of the request body.

validate_certificate_extensions(boolean): Validate Certificate Extensions, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises: TypeError: If the parameter types are incorrect. MalformedRequest: If the request body created is invalid. ApiError: If the Identity Services Engine cloud returns an error.

get_system_certificates(*host_name, filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name (basestring)** – hostName path parameter. Name of the host of which system certificates should be returned.
- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sort (basestring)** – sort query parameter. sort type asc or desc.
- **sort_by (basestring)** – sortBy query parameter. sort column by which objects needs to be sorted.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificates_generator(*host_name*, *filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName issuedTo issuedBy validFrom Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT .

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a

triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_system_certificate_by_id(*host_name, id, headers=None, **query_parameters*)

This API displays details of a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host of which system certificates should be returned.
- **id** (*basestring*) – id path parameter. The id of the system certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_system_certificate(*host_name, id, admin=None, allow_replacement_of_portal_group_tag=None, description=None, eap=None, expiration_ttl_period=None, expiration_ttl_units=None, ims=None, name=None, portal=None, portal_group_tag=None, portal_tag_transfer_for_same_subject=None, pxgrid=None, radius=None, renew_self_signed_certificate=None, role_transfer_for_same_subject=None, saml=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update a System Certificate. NOTE: Renewing a certificate will cause an application server restart on the selected node. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body
PARAMETER DESCRIPTION EXAMPLE
name Friendly name of the certificate. System Certificate description Description of the Certificate Default Description admin Use certificate to authenticate the ISE Admin Portal false eap Use certificate for EAP protocols that use SSL/TLS tunneling false radius Use certificate for RADSec server false pxgrid Use certificate for the pxGrid Controller false ims Use certificate for the ISE Messaging Service false saml Use certificate for SAML Signing false portal Use certificate for portal false portalGroupTag Portal Group Tag for using certificate with portal role Default Portal Certificate Group allowReplacementOfPortalGroupTag Allow Replacement of Portal Group Tag (required) false roleTransferForSameSubject Allow the transfer of roles to certificates with same subject false portalTagTransferForSameSubject Acquire the group tag of the matching certificate false renewSelfSignedCertificate Renew Self Signed Certificate false expirationTTLPeriod Expiration Period 365 expirationTTLUnits Expiration Units in one of the below formats days / weeks / months / years days
Following Roles can be used in any combinations
ROLE DEFAULT WARNING Admin False Enabling Admin role for this certificate will cause an application server restart on the selected node. Note: Make sure required Certificate Chain is imported under Trusted Certificates EAP Authentication False Only one system certificate can be used for EAP. Assigning EAP to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates RADIUS DTLS False Only one system certificate can be used for DTLS. Assigning DTLS to this certificate will remove the assignment from another certificate. Note: Make sure required Certificate Chain is imported under Trusted Certificates SAML False SAML cannot be used with other Usage. Enabling SAML will uncheck all other Usage. Note: Make sure required Certificate Chain is imported under Trusted Certificates .

Parameters

- **admin** (*boolean*) – Use certificate to authenticate the ISE Admin Portal, property of the request body.
- **allow_replacement_of_portal_group_tag** (*boolean*) – Allow Replacement of Portal Group Tag (required), property of the request body.
- **description** (*string*) – Description of System Certificate, property of the request body.
- **eap** (*boolean*) – Use certificate for EAP protocols that use SSL/TLS tunneling, property of the request body.
- **expiration_ttl_period** (*integer*) – expirationTTLPeriod, property of the request body.

- **expiration_ttl_units** (*string*) – expirationTTLUnits, property of the request body. Available values are ‘days’, ‘months’, ‘weeks’ and ‘years’.
- **ims** (*boolean*) – Use certificate for the ISE Messaging Service, property of the request body.
- **name** (*string*) – Name of the certificate, property of the request body.
- **portal** (*boolean*) – Use for portal, property of the request body.
- **portal_group_tag** (*string*) – Set Group tag, property of the request body.
- **portal_tag_transfer_for_same_subject** (*boolean*) – Allow overwriting the portal tag from matching certificate of same subject, property of the request body.
- **pxgrid** (*boolean*) – Use certificate for the pxGrid Controller, property of the request body.
- **radius** (*boolean*) – Use certificate for the RADSec server, property of the request body.
- **renew_self_signed_certificate** (*boolean*) – Renew Self Signed Certificate, property of the request body.
- **role_transfer_for_same_subject** (*boolean*) – Allow transfer of roles for certificate with matching subject , property of the request body.
- **saml** (*boolean*) – Use certificate for SAML Signing, property of the request body.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be updated.
- **host_name** (*basestring*) – hostName path parameter. Name of Host whose certificate needs to be updated.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_system_certificate_by_id(*host_name, id, headers=None, **query_parameters*)

This API deletes a System Certificate of a particular node based on a given HostName and ID.

Parameters

- **host_name** (*basestring*) – hostName path parameter. Name of the host from which the System Certificate needs to be deleted.
- **id** (*basestring*) – id path parameter. The ID of the System Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM- dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_trusted_certificates_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

This API supports Filtering, Sorting and Pagination. Filtering and Sorting supported on below mentioned attributes: friendlyName subject issuedTo issuedBy validFrom Supported Date Format: yyyy-MM- dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT expirationDate Supported Date Format: yyyy-MM-dd HH:mm:ss Supported Operators: EQ, NEQ, GT and LT status Allowed values: enabled, disabled Supported Operators: EQ, NEQ .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

export_trusted_certificate(*id*, *dirpath=None*, *save_file=None*, *headers=None*, ****query_parameters**)

The response of this API carries a trusted certificate file mapped to the requested id.

Parameters

- **id** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be exported.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to `os.getcwd()`.
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

```
import_trust_certificate(allow_basic_constraint_cafalse=None, allow_out_of_date_cert=None,
                        allow_sha1_certificates=None, data=None, description=None, name=None,
                        trust_for_certificate_based_admin_auth=None,
                        trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                        trust_for_ise_auth=None, validate_certificate_extensions=None,
                        headers=None, payload=None, active_validation=True,
                        **query_parameters)
```

Import an X509 certificate as a trust certificate. NOTE: Request Parameters accepting True and False as input can be replaced by 1 and 0 respectively. Following Parameters are used in POST body PARAMETER DESCRIPTION EXAMPLE name Friendly name of the certificate Trust Certificate description Description of the certificate Passw*** data Plain-text contents of the certificate file. Every space needs to be replaced with newline escape sequence (

) (required). awk 'NF {sub(/

/, ""); printf "%sn", \$0;}' <<your .pem file>> allowOutOfDateCert Allow out of date certificates (required) false allowSHA1Certificates Allow SHA1 based certificates (required) false trustForIseAuth Trust for authentication within ISE false trustForClientAuth Trust for client authentication and Syslog false trustForCertificateBasedAdminAuth Trust for Certificate based Admin authentication false trustForCiscoServicesAuth Trust for authentication of Cisco Services false validateCertificateExtensions Validate extensions for trust certificate false NOTE: If name is not set, a default name of the following format will be generated: common-name#issuer#nnnnn where "nnnnn" is a unique number. You can always change the friendly name later by editing the certificate. You must choose how this certificate will be trusted in ISE. The objective here is to distinguish between certificates that are used for trust within an ISE deployment and public certificates that are used to trust Cisco services. Typically, you will not want to use a given certificate for both purposes. Trusted For Usage Authentication within ISE Use "trustForIseAuth":true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Client authentication and Syslog Use "trustForClientAuth":true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: "" can be set true only if the "trustForIseAuth" has been set true. Certificate based admin authentication Use "trustForCertificateBasedAdminAuth":true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes Note: "trustForCertificateBasedAdminAuth" can be set true only if "trustForIseAuth" and "trustForClientAuth" are true. Authentication of Cisco Services Use "trustForCiscoServicesAuth":true if the certificate is to be used for trusting external Cisco services, such as Feed Service. .

Args:

allow_basic_constraint_cafalse(boolean): Allow Certificates with Basic Constraints CA Field as False (required), property of the request body.

allow_out_of_date_cert(boolean): Allow out of date certificates (required), property of the request body.

allow_sha1_certificates(boolean): Allow SHA1 based certificates (required), property of the request body.

data(string): Certificate content (required), property of the request body.

description(string): Description of the certificate, property of the request body.

name(string): Name of the certificate, property of the request body.

trust_for_certificate_based_admin_auth(boolean): Trust for Certificate based Admin authentication, property of the request body.

trust_for_cisco_services_auth(boolean): Trust for authentication of Cisco Services, property of the request body.

trust_for_client_auth(boolean): Trust for client authentication and Syslog, property of the request body.

trust_for_ise_auth(boolean): Trust for authentication within ISE, property of the request body.

validate_certificate_extensions(boolean): Validate trust certificate extension, property of the request body.

headers(dict): Dictionary of HTTP Headers to send with the Request .

payload(dict): A JSON serializable Python object to send in the body of the Request.

active_validation(bool): Enable/Disable payload validation. Defaults to True.

****query_parameters:** Additional query parameters (provides support for parameters that may be added in the future).

Returns:

RestResponse: REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Raises: **TypeError:** If the parameter types are incorrect. **MalformedRequest:** If the request body created is invalid. **ApiError:** If the Identity Services Engine cloud returns an error.

get_trusted_certificate_by_id(id, headers=None, **query_parameters)

This API can displays details of a Trust Certificate based on a given ID.

Parameters

- **id (basestring)** – id path parameter. The id of the trust certificate.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict):** response headers.
- **response(MyDict):** response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes):** representation of the request's response
- **text(str):** representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_trusted_certificate(id, authenticate_before_crl_received=None, automatic_crl_update=None,
                           automatic_crl_update_period=None, automatic_crl_update_units=None,
                           crl_distribution_url=None, crl_download_failure_retries=None,
                           crl_download_failure_retries_units=None, description=None,
                           download_crl=None, enable_ocsp_validation=None,
                           enable_server_identity_check=None, ignore_crl_expiration=None,
                           name=None, non_automatic_crl_update_period=None,
                           non_automatic_crl_update_units=None,
                           reject_if_no_status_from_ocs_p=None,
                           reject_if_unreachable_from_ocs_p=None, selected_ocsp_service=None,
                           status=None, trust_for_certificate_based_admin_auth=None,
                           trust_for_cisco_services_auth=None, trust_for_client_auth=None,
                           trust_for_ise_auth=None, headers=None, payload=None,
                           active_validation=True, **query_parameters)
```

Update a trusted certificate present in ISE trust store. Following Parameters are used in PUT request body

| PARAMETER | DESCRIPTION | EXAMPLE | name | Friendly name of the certificate(required) | Trust Certificate status | Status of the certificate | Enabled | description | Description of the certificate | Certificate for secure connection to cisco.com | trustForIseAuth | Trust for authentication within ISE | false | trustForClientAuth | Trust for client authentication and Syslog | false | trustForCertificateBasedAdminAuth | Trust for Certificate based Admin authentication | false | trustForCiscoServicesAuth | Trust for authentication of Cisco Services | false | enableOCSPValidation | Switch to enable/disable OCSP Validation | false | selectedOCSPService | Name of selected OCSP Service | INTERNAL_OCSP_SERVICE | rejectIfNoStatusFromOCSP | Switch to reject certificate if there is no status from OCSP | false | rejectIfUnreachableFromOCSP | Switch to reject certificate if unreachable from OCSP | false | downloadCRL | Switch to enable/disable download of CRL | false | crlDistributionUrl | Certificate Revocation List Distribution URL | automaticCRLUpdate | Switch to enable/disable automatic CRL update | false | automaticCRLUpdatePeriod | Automatic CRL update period | 5 | automaticCRLUpdateUnits | Unit of time for automatic CRL update | Minutes | nonAutomaticCRLUpdatePeriod | Non automatic CRL update period | 1 | nonAutomaticCRLUpdateUnits | Unit of time of non automatic CRL update | Hours | crlDownloadFailureRetries | If CRL download fails, wait time before retry | 10 | crlDownloadFailureRetriesUnits | Unit of time before retry if CRL download fails | Minutes | enableServerIdentityCheck | Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL | false | authenticateBeforeCRLReceived | Switch to enable/disable CRL Verification if CRL is not Received | false | ignoreCRLExpiration | Switch to enable/disable ignore CRL Expiration | false | Trusted For Usage Authentication within ISE | Use “trustForIseAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes | Client authentication and Syslog | Use “trustForClientAuth”:true if the certificate is to be used for authentication of endpoints that contact ISE over the EAP protocol. Also check this box if certificate is used to trust a Syslog server. Make sure to have keyCertSign bit asserted under KeyUsage extension for this certificate. Note: “trustForClientAuth” can be set true only if the “trustForIseAuth” has been set true. Certificate based admin authentication | Use “trustForCertificateBasedAdminAuth”:true if the certificate is used for trust within ISE, such as for secure communication between ISE nodes | Note: “trustForCertificateBasedAdminAuth” can be set true only if “trustForIseAuth” and “trustForClientAuth” are true. Authentication of Cisco Services | Use “trustForCiscoServicesAuth”:true if the certificate is to be used for trusting external Cisco services, such as Feed Service. OCSP Configuration Usage Validation against OCSP service | Use “enableOCSPValidation”:true to validate the certificate against OCSP service mentioned in the field selectedOCSPService | OCSP Service name | Use “selectedOCSPService”:“Name of OCSP Service” | Name of the OCSP service against which the certificate should be validated | Note: “selectedOCSPService” value will on be used if “enableOCSPValidation” has been set true. Reject the request if OCSP returns UNKNOWN status | Use “rejectIfNoStatusFromOCSP”:true to reject the certificate if the OCSP service returns UNKNOWN status | Note: “rejectIfNoStatusFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Reject the request if OCSP Responder is unreachable | Use “rejectIfUnreachableFromOCSP”:true to reject the certificate if the OCSP service is unreachable. |
|-----------|-------------|---------|------|--|--------------------------|---------------------------|---------|-------------|--------------------------------|--|-----------------|-------------------------------------|-------|--------------------|--|-------|-----------------------------------|--|-------|---------------------------|--|-------|----------------------|--|-------|---------------------|-------------------------------|-----------------------|--------------------------|--|-------|-----------------------------|---|-------|-------------|--|-------|--------------------|--|--------------------|---|-------|--------------------------|-----------------------------|---|-------------------------|---------------------------------------|---------|-----------------------------|---------------------------------|---|----------------------------|--|-------|---------------------------|---|----|--------------------------------|---|---------|---------------------------|---|-------|-------------------------------|--|-------|---------------------|--|-------|---|--|----------------------------------|--|--|---|--|---|-------------------|--|--|--|--|---|--|
|-----------|-------------|---------|------|--|--------------------------|---------------------------|---------|-------------|--------------------------------|--|-----------------|-------------------------------------|-------|--------------------|--|-------|-----------------------------------|--|-------|---------------------------|--|-------|----------------------|--|-------|---------------------|-------------------------------|-----------------------|--------------------------|--|-------|-----------------------------|---|-------|-------------|--|-------|--------------------|--|--------------------|---|-------|--------------------------|-----------------------------|---|-------------------------|---------------------------------------|---------|-----------------------------|---------------------------------|---|----------------------------|--|-------|---------------------------|---|----|--------------------------------|---|---------|---------------------------|---|-------|-------------------------------|--|-------|---------------------|--|-------|---|--|----------------------------------|--|--|---|--|---|-------------------|--|--|--|--|---|--|

Note: “rejectIfUnreachableFromOCSP:true” can be used only if “enableOCSPValidation” has been set true. Certificate Revocation List Configuration Usage Validation against CRL Use “downloadCRL”:true to validate the certificate against CRL downloaded from URL mentioned in the field `crlDistributionUrl` CRL distribution url Use “`crlDistributionUrl`” to specify the URL from where the CRL should be downloaded Note: “`crlDistributionUrl`” value will only be used if “downloadCRL” has been set true. Retrieve CRL time Use “automaticCRLUpdate”:true and `automaticCRLUpdatePeriod`, `automaticCRLUpdatePeriod` to set the time before which CRL is automatically retrieved prior to expiration Use “nonAutomaticCRLUpdatePeriod”, `nonAutomaticCRLUpdateUnits` to set the time period for CRL retrieval in loop. Note: All the above fields can be used only if “downloadCRL” has been set true. If download fails Use “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” to set retry time period if CRL download fails Note: “`crlDownloadFailureRetries`” and “`crlDownloadFailureRetriesUnits`” can be used only if “downloadCRL” has been set true. Enable Server Identity Check Use “enableServerIdentityCheck”:true to verify that HTTPS or LDAPS server certificate name fits the configured server URL Note: “enableServerIdentityCheck:true” can be used only if “downloadCRL” has been set true. Bypass CRL Verification if CRL is not Received Use “authenticateBeforeCRLReceived”:true to bypass CRL Verification if CRL is not Received Note: “authenticateBeforeCRLReceived:true” can be used only if “downloadCRL” has been set true. Ignore that CRL is not yet valid or has expired Use “ignoreCRLExpiration”:true to ignore if CRL is not yet valid or expired Note: “ignoreCRLExpiration:true” can be used only if “downloadCRL” has been set true. Note: boolean properties accept integers values as well, with 0 considered as false and other values being considered as true .

Parameters

- **authenticate_before_crl_received** (*boolean*) – Switch to enable/disable CRL Verification if CRL is not Received, property of the request body.
- **automatic_crl_update** (*boolean*) – Switch to enable/disable automatic CRL update, property of the request body.
- **automatic_crl_update_period** (*integer*) – Automatic CRL update period, property of the request body.
- **automatic_crl_update_units** (*string*) – Unit of time for automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **crl_distribution_url** (*string*) – CRL Distribution URL, property of the request body.
- **crl_download_failure_retries** (*integer*) – If CRL download fails, wait time before retry, property of the request body.
- **crl_download_failure_retries_units** (*string*) – Unit of time before retry if CRL download fails, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **description** (*string*) – Description for trust certificate, property of the request body.
- **download_crl** (*boolean*) – Switch to enable/disable download of CRL, property of the request body.
- **enable_ocsp_validation** (*boolean*) – Switch to enable/disable OCSP Validation, property of the request body.
- **enable_server_identity_check** (*boolean*) – Switch to enable/disable verification if HTTPS or LDAP server certificate name fits the configured server URL, property of the request body.
- **ignore_crl_expiration** (*boolean*) – Switch to enable/disable ignore CRL Expiration, property of the request body.
- **name** (*string*) – Friendly name of the certificate, property of the request body.

- **non_automatic_crl_update_period** (*integer*) – Non automatic CRL update period, property of the request body.
- **non_automatic_crl_update_units** (*string*) – Unit of time of non automatic CRL update, property of the request body. Available values are ‘Days’, ‘Hours’, ‘Minutes’ and ‘Weeks’.
- **reject_if_no_status_from_ocs_p** (*boolean*) – Switch to reject certificate if there is no status from OCSP, property of the request body.
- **reject_if_unreachable_from_ocs_p** (*boolean*) – Switch to reject certificate if unreachable from OCSP, property of the request body.
- **selected_ocs_service** (*string*) – Name of selected OCSP Service, property of the request body.
- **status** (*string*) – status, property of the request body. Available values are ‘Disabled’ and ‘Enabled’.
- **trust_for_certificate_based_admin_auth** (*boolean*) – Trust for Certificate based Admin authentication, property of the request body.
- **trust_for_cisco_services_auth** (*boolean*) – Trust for authentication of Cisco Services, property of the request body.
- **trust_for_client_auth** (*boolean*) – Trust for client authentication and Syslog, property of the request body.
- **trust_for_ise_auth** (*boolean*) – Trust for authentication within ISE, property of the request body.
- **id** (*basestring*) – id path parameter. The id of the trust certificate.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_trusted_certificate_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a Trust Certificate from Trusted Certificate Store based on a given ID.

Parameters

- **id** (*basestring*) – id path parameter. The ID of the Trusted Certificate to be deleted.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear_threats_and_vulnerabilities**class ClearThreatsAndVulnerabilities**

Identity Services Engine ClearThreatsAndVulnerabilities API (version: 3.1.0).

Wraps the Identity Services Engine ClearThreatsAndVulnerabilities API and exposes the API as native Python methods that return native Python objects.

clear_threats_and_vulnerabilities(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to delete the ThreatContext and Threat events that are associated with the given MAC Address.

Parameters

- **mac_addresses** (*string*) – macAddresses, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`clear`(*mac_addresses=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *clear_threats_and_vulnerabilities*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the clear threats and vulnerabilities.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

consumer

class Consumer

Identity Services Engine Consumer API (version: 3.1.0).

Wraps the Identity Services Engine Consumer API and exposes the API as native Python methods that return native Python objects.

`create_account`(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccountCreate.

Parameters

- **`node_name`** (*string*) – nodeName, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_account*

activate_account(*description=None, headers=None, payload=None, active_validation=True, **query_parameters*)
AccountActivate.

Parameters

- **description** (*string*) – description, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

lookup_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceLookup.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

access_secret(*peer_node_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

AccessSecret.

Parameters

- **peer_node_name** (*string*) – peerNodeName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

device_administration_authentication_rules

class DeviceAdministrationAuthenticationRules

Identity Services Engine Device Administration - Authentication Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_authentication_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authentication rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authentication_rules`*

```
create_device_admin_authentication_rule(policy_id, identity_source_name=None,
                                         if_auth_fail=None, if_process_fail=None,
                                         if_user_not_found=None, link=None, rule=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

Device Admin Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*,
if_user_not_found=None, *link=None*, *rule=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)
Alias for *create_device_admin_authentication_rule*

reset_hit_counts_device_admin_authentication_rules(*policy_id*, *headers=None*,
***query_parameters*)

Device Admin Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)
Alias for *reset_hit_counts_device_admin_authentication_rules*

get_device_admin_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)
Device Admin Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *get_device_admin_authentication_rule_by_id*

update_device_admin_authentication_rule_by_id(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update rule.

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_authentication_rule_by_id*

delete_device_admin_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_authentication_rule_by_id*

device_administration_authorization_exception_rules

class DeviceAdministrationAuthorizationExceptionRules

Identity Services Engine Device Administration - Authorization Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)
Device Admin Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)
Alias for *get_device_admin_local_exception_rules*

create_device_admin_local_exception_rule(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.

- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_device_admin_local_exception_rule*

reset_hit_counts_device_admin_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Device Admin Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_local_exceptions*

get_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_device_admin_local_exception_rule_by_id*

update_device_admin_local_exception_rule_by_id(*id*, *policy_id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Update local exception rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_device_admin_local_exception_rule_by_id*

delete_device_admin_local_exception_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Device Admin Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_local_exception_rule_by_id*

device_administration_authorization_global_exception_rules**class DeviceAdministrationAuthorizationGlobalExceptionRules**

Identity Services Engine Device Administration - Authorization Global Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_set_global_exception_rules(*headers=None*, ***query_parameters*)

Device Admin Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_device_admin_policy_set_global_exception_rules*

create_device_admin_policy_set_global_exception(*commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Device Admin Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set_global_exception*

reset_hit_counts_device_admin_global_exceptions(*headers=None, **query_parameters*)

Device Admin Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts`(*headers=None, **query_parameters*)

Alias for *`reset_hit_counts_device_admin_global_exceptions`*

`get_device_admin_policy_set_global_exception_by_rule_id`(*id, headers=None, **query_parameters*)

Device Admin Get global exception rule attribute.

Parameters

- **`id`** (*basestring*) – id path parameter. Rule id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id`(*id, headers=None, **query_parameters*)

Alias for *`get_device_admin_policy_set_global_exception_by_rule_id`*

`update_device_admin_policy_set_global_exception_by_rule_id`(*id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update global exception authorization rule.

Parameters

- **`commands`** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).

- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *link=None*, *profile=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_global_exception_by_rule_id*

delete_device_admin_policy_set_global_exception_by_rule_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_device_admin_policy_set_global_exception_by_rule_id`*

device_administration_authorization_rules

class DeviceAdministrationAuthorizationRules

Identity Services Engine Device Administration - Authorization Rules API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_authorization_rules(policy_id, headers=None, **query_parameters)`

Device Admin Get authorization rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_device_admin_authorization_rules`*

```
create_device_admin_authorization_rule(policy_id, commands=None, link=None, profile=None,  
                                         rule=None, headers=None, payload=None,  
                                         active_validation=True, **query_parameters)
```

Device Admin Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(policy_id, commands=None, link=None, profile=None, rule=None, headers=None, payload=None,  
        active_validation=True, **query_parameters)
```

Alias for *create_device_admin_authorization_rule*

```
reset_hit_counts_device_admin_authorization_rules(policy_id, headers=None,  
                                                    **query_parameters)
```

Device Admin Reset HitCount for Authorization Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_device_admin_authorization_rules*

get_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Device Admin Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers*=None, ***query_parameters*)

Alias for *get_device_admin_authorization_rule_by_id*

update_device_admin_authorization_rule_by_id(*id*, *policy_id*, *commands*=None, *link*=None, *profile*=None, *rule*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Device Admin Update authorization rule.

Parameters

- **commands** (*list*) – Command sets enforce the specified list of commands that can be executed by a device administrator, property of the request body (list of strings).
- **link** (*object*) – link, property of the request body.
- **profile** (*string*) – Device admin profiles control the initial login session of the device administrator, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *commands*=None, *link*=None, *profile*=None, *rule*=None, *headers*=None, *payload*=None, *active_validation*=True, ***query_parameters*)

Alias for *update_device_admin_authorization_rule_by_id*

delete_device_admin_authorization_rule_by_id(*id*, *policy_id*, *headers*=None, ***query_parameters*)

Device Admin Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)
Alias for *delete_device_admin_authorization_rule_by_id*

device_administration_command_set

class DeviceAdministrationCommandSet

Identity Services Engine Device Administration - Command Set API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Command Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_command_sets(*headers=None*, ***query_parameters*)
Device Admin Return list of command sets. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_command_sets*

device_administration_conditions

class DeviceAdministrationConditions

Identity Services Engine Device Administration - Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_conditions(*headers=None, **query_parameters*)
Device Admin Returns list of library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_conditions*

```
create_device_admin_condition(attribute_name=None, attribute_value=None, children=None,
                               condition_type=None, dates_range=None,
                               dates_range_exception=None, description=None,
                               dictionary_name=None, dictionary_value=None, hours_range=None,
                               hours_range_exception=None, id=None, is_negate=None, link=None,
                               name=None, operator=None, week_days=None,
                               week_days_exception=None, headers=None, payload=None,
                               active_validation=True, **query_parameters)
```

Device Admin Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to existing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.

- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_condition*

get_device_admin_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authentication rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authentication_rules*

get_device_admin_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Device Admin Returns list of library conditions for authorization rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization_rules(*headers=None, **query_parameters*)

Alias for *get_device_admin_conditions_for_authorization_rules*

get_device_admin_condition_by_name(*name, headers=None, **query_parameters*)

Device Admin Returns a library condition.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_device_admin_condition_by_name*

update_device_admin_condition_by_name(*name, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.

- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the re-

quest body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').

- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_condition_by_name*

delete_device_admin_condition_by_name(*name*, *headers=None*, ***query_parameters*)

NDevice Admin Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_condition_by_name*

get_device_admin_conditions_for_policy_sets(*headers=None*, ***query_parameters*)

Device Admin Returns list of library conditions for policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_for_policy_sets(*headers=None*, ***query_parameters*)

Alias for *get_device_admin_conditions_for_policy_sets*

get_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Returns a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_device_admin_condition_by_id`

`update_device_admin_condition_by_id(id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update library condition.

Parameters

- **`attribute_name (string)`** – Dictionary attribute name, property of the request body.
- **`attribute_value (string)`** – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children (list)`** – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type (string)`** – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **`dates_range (object)`** – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **`dates_range_exception (object)`** – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **`description (string)`** – Condition description, property of the request body.
- **`dictionary_name (string)`** – Dictionary name, property of the request body.

- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [`update_device_admin_condition_by_id`](#)

delete_device_admin_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [`delete_device_admin_condition_by_id`](#)

device_administration_dictionary_attributes_list

class DeviceAdministrationDictionaryAttributesList

Identity Services Engine Device Administration - Dictionary Attributes List API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_device_admin_dictionaries_authentication(*headers=None*, ***query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authentication*

get_device_admin_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_authorization*

get_device_admin_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_policy_set(*headers=None, **query_parameters*)

Alias for *get_device_admin_dictionaries_policy_set*

device_administration_identity_stores

class DeviceAdministrationIdentityStores

Identity Services Engine Device Administration - Identity Stores API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Identity Stores API and exposes the API as native Python methods that return native Python objects.

get_device_admin_identity_stores(*headers=None, **query_parameters*)

Device Admin Return list of identity stores for authentication. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_identity_stores*

device_administration_network_conditions

class DeviceAdministrationNetworkConditions

Identity Services Engine Device Administration - Network Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_network_conditions(*headers=None, **query_parameters*)
Device Admin Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_device_admin_network_conditions*

create_device_admin_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device AdminCreates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.

- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_network_condition*

get_device_admin_network_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_device_admin_network_condition_by_id`

`update_device_admin_network_condition_by_id(id, condition_type=None, conditions=None, description=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Device Admin Update network condition.

Parameters

- **`condition_type`** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **`conditions`** (*list*) – conditions, property of the request body (list of objects).
- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Network Condition name, property of the request body.
- **`id`** – id path parameter. Condition id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_network_condition_by_id*

delete_device_admin_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_device_admin_network_condition_by_id*

device_administration_policy_set

class DeviceAdministrationPolicySet

Identity Services Engine Device Administration - Policy Set API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_device_admin_policy_sets(*headers=None*, ***query_parameters*)

Device Admin List of policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_device_admin_policy_sets*

`create_device_admin_policy_set`(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model `ConditionReference` , or, dynamically built conditions which are not stored in the conditions Library, using models `ConditionAttributes`, `ConditionAndBlock`, `ConditionOrBlock` . .

Parameters

- **`condition`** (*object*) – condition, property of the request body.
- **`default`** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **`description`** (*string*) – The description for the policy set, property of the request body.
- **`hit_counts`** (*integer*) – The amount of times the policy was matched, property of the request body.
- **`id`** (*string*) – Identifier for the policy set, property of the request body.
- **`is_proxy`** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **`link`** (*object*) – link, property of the request body.
- **`name`** (*string*) – Given name for the policy set, [Valid characters are alphanumeric, underscore, hyphen, space, period, parentheses], property of the request body.
- **`rank`** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **`service_name`** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **`state`** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are 'disabled', 'enabled' and 'monitor'.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_policy_set*

reset_hit_counts_device_admin_policy_sets(*headers=None, **query_parameters*)

Device Admin Reset HitCount for PolicySets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for [*reset_hit_counts_device_admin_policy_sets*](#)

get_device_admin_policy_set_by_id(*id, headers=None, **query_parameters*)

Device Admin Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for [*get_device_admin_policy_set_by_id*](#)

update_device_admin_policy_set_by_id(*id, condition=None, default=None, description=None, hit_counts=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **link** (*object*) – link, property of the request body.

- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_policy_set_by_id*

delete_device_admin_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_device_admin_policy_set_by_id`*

device_administration_profiles

class DeviceAdministrationProfiles

Identity Services Engine Device Administration - Profiles API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Profiles API and exposes the API as native Python methods that return native Python objects.

`get_device_admin_profiles(headers=None, **query_parameters)`

Device Admin Returns list of shell profiles. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of `MyDict` objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for *`get_device_admin_profiles`*

device_administration_service_names

class DeviceAdministrationServiceNames

Identity Services Engine Device Administration - Service Names API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Service Names API and exposes the API as native Python methods that return native Python objects.

get_device_admin_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Device Admin Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_device_admin_service_names*

device_administration_time_date_conditions

class DeviceAdministrationTimeDateConditions

Identity Services Engine Device Administration - Time/Date Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Device Administration - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_device_admin_time_conditions(*headers=None, **query_parameters*)

Device Admin Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*headers=None, **query_parameters*)

Alias for *get_device_admin_time_conditions*

`create_device_admin_time_condition`(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Creates time/date condition.

Parameters

- **`attribute_name`** (*string*) – Dictionary attribute name, property of the request body.
- **`attribute_value`** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children`** (*list*) – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type`** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type `enum(reference,single)` indicates than “`conditionId`” OR “`ConditionAttrs`” fields should contain condition data but not both Logical aggregation(`and,or`) `enum` indicates that additional conditions are present under the `children` field, property of the request body. Available values are ‘`ConditionAndBlock`’, ‘`ConditionAttributes`’, ‘`ConditionOrBlock`’, ‘`ConditionReference`’, ‘`LibraryConditionAndBlock`’, ‘`LibraryConditionAttributes`’, ‘`LibraryConditionOrBlock`’ and ‘`TimeAndDateCondition`’.
- **`dates_range`** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format `yyyy- mm-dd` (MM = month, dd = day, yyyy = year), property of the request body.
- **`dates_range_exception`** (*object*) – Defines for which date/s `TimeAndDate` condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates

Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_device_admin_time_condition*

get_device_admin_time_condition_by_id(*id, headers=None, **query_parameters*)

Device Admin Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_device_admin_time_condition_by_id*

update_device_admin_time_condition_by_id(*id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Device Admin Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_device_admin_time_condition_by_id*

delete_device_admin_time_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Device Admin Delete Time/Date condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`
Alias for `delete_device_admin_time_condition_by_id`

downloadable_acl

class DownloadableAcl

Identity Services Engine DownloadableACL API (version: 3.1.0).

Wraps the Identity Services Engine DownloadableACL API and exposes the API as native Python methods that return native Python objects.

`get_downloadable_acl_by_id(id, headers=None, **query_parameters)`
This API allows the client to get a downloadable ACL by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`
Alias for `get_downloadable_acl_by_id`

```
update_downloadable_acl_by_id(id, dacl=None, dacl_type=None, description=None, name=None,
                               headers=None, payload=None, active_validation=True,
                               **query_parameters)
```

This API allows the client to update a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string `\n` for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: `IPV4`, `IPV6`, `IP_AGNOSTIC`, property of the request body.
- **description** (*string*) – Use the string `\n` for a newline, property of the request body.
- **id** (*basestring*) – `id`, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters `[_.-]`, property of the request body.
- **id** – `id` path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to `True`.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, dacl=None, dacl_type=None, description=None, name=None, headers=None,
              payload=None, active_validation=True, **query_parameters)
```

Alias for *update_downloadable_acl_by_id*

```
delete_downloadable_acl_by_id(id, headers=None, **query_parameters)
```

This API deletes a downloadable ACL.

Parameters

- **id** (*basestring*) – `id` path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_downloadable_acl_by_id*

get_downloadable_acl(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_downloadable_acl*

get_downloadable_acl_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all downloadable ACLs.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_downloadable_acl_generator*

create_downloadable_acl(*dacl=None, dacl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a downloadable ACL.

Parameters

- **dacl** (*string*) – The DACL Content. Use the string n for a newline, property of the request body.
- **dacl_type** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **description** (*string*) – Use the string n for a newline, property of the request body.
- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*acl=None, acl_type=None, description=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_downloadable_acl*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the downloadable ACL.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

egress_matrix_cell

class EgressMatrixCell

Identity Services Engine EgressMatrixCell API (version: 3.1.0).

Wraps the Identity Services Engine EgressMatrixCell API and exposes the API as native Python methods that return native Python objects.

clear_all_matrix_cells(*headers=None, **query_parameters*)

This API allows the client to clear all the egress matrix cells.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clear(*headers=None, **query_parameters*)

Alias for *clear_all_matrix_cells*

set_all_cells_status(*status, headers=None, **query_parameters*)

This API allows the client to set status of all the egress matrix cells.

Parameters

- **status** (*basestring*) – status path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

set_status(*status*, *headers=None*, ***query_parameters*)

Alias for *set_all_cells_status*

clone_matrix_cell(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

This API allows the client to clone an egress matrix cell.

Parameters

- **id** (*basestring*) – id path parameter.
- **src_sgt_id** (*basestring*) – srcSgtId path parameter.
- **dst_sgt_id** (*basestring*) – dstSgtId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

clone(*dst_sgt_id*, *id*, *src_sgt_id*, *headers=None*, ***query_parameters*)

Alias for *clone_matrix_cell*

get_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an egress matrix cell by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_egress_matrix_cell_by_id`

`update_egress_matrix_cell_by_id(id, default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an egress matrix cell.

Parameters

- **`default_rule (string)`** – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`destination_sgt_id (string)`** – destinationSgtId, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`matrix_cell_status (string)`** – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`sgacIs (list)`** – sgacIs, property of the request body (list of strings).
- **`source_sgt_id (string)`** – sourceSgtId, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_rule=None*, *description=None*, *destination_sgt_id=None*,
matrix_cell_status=None, *name=None*, *sgacls=None*, *source_sgt_id=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_egress_matrix_cell_by_id*

delete_egress_matrix_cell_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an egress matrix cell.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_egress_matrix_cell_by_id*

get_egress_matrix_cell(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrc-Value, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET

/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDstName, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell*

get_egress_matrix_cell_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the egress matrix cell. Filter: [sgtSrcValue, matrixStatus, description, sgtSrcName, sgtDstName, sgtDstValue] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13

Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [description, sgtSrcName, sgtDst-
Name, sgtDstValue].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_egress_matrix_cell_generator*

```
create_egress_matrix_cell(default_rule=None, description=None, destination_sgt_id=None,
                           matrix_cell_status=None, name=None, sgacIs=None, source_sgt_id=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API creates an egress matrix cell.

Parameters

- **default_rule** (*string*) – Allowed values: NONE, DENY_IP, PERMIT_IP, property of the request body.
- **description** (*string*) – description, property of the request body.
- **destination_sgt_id** (*string*) – destinationSgtId, property of the request body.
- **matrix_cell_status** (*string*) – Allowed values: DISABLED, ENABLED, MONITOR, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgacIs** (*list*) – sgacIs, property of the request body (list of strings).
- **source_sgt_id** (*string*) – sourceSgtId, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(default_rule=None, description=None, destination_sgt_id=None, matrix_cell_status=None,
        name=None, sgacIs=None, source_sgt_id=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
```

Alias for *create_egress_matrix_cell*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the egress matrix cell.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_egress_matrix_cell(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_egress_matrix_cell*

monitor_bulk_status_egress_matrix_cell(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_egress_matrix_cell*

endpoint_certificate

class EndpointCertificate

Identity Services Engine EndpointCertificate API (version: 3.1.0).

Wraps the Identity Services Engine EndpointCertificate API and exposes the API as native Python methods that return native Python objects.

create_endpoint_certificate(*cert_template_name=None, certificate_request=None, format=None, password=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create an endpoint certificate.

Parameters

- **cert_template_name** (*string*) – Name of an Internal CA template, property of the request body.
- **certificate_request** (*object*) – Key value map. Must have CN and SAN entries, property of the request body.

- **format** (*string*) – Allowed values: PKCS12, PKCS12_CHAIN, PKCS8, PKCS8_CHAIN, property of the request body.
- **password** (*string*) – Protects the private key. Must have more than 8 characters, less than 15 characters, at least one upper case letter, at least one lower case letter, at least one digit, and can only contain [A-Z][a-z][0-9]_#, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type `urllib3.response.HTTPResponse`

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

create(*cert_template_name=None, certificate_request=None, format=None, password=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [create_endpoint_certificate](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint_identity_group**class EndpointIdentityGroup**

Identity Services Engine EndpointIdentityGroup API (version: 3.1.0).

Wraps the Identity Services Engine EndpointIdentityGroup API and exposes the API as native Python methods that return native Python objects.

get_endpoint_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_group_by_name*

get_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_endpoint_group_by_id`

`update_endpoint_group_by_id(id, description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update an endpoint identity group.

Parameters

- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`system_defined (boolean)`** – `systemDefined`, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *system_defined=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_group_by_id*

delete_endpoint_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint identity group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_group_by_id*

get_endpoint_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_groups*

get_endpoint_groups_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the endpoint identity groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoint_groups_generator*

create_endpoint_group(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **system_defined** (*boolean*) – systemDefined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, system_defined=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint identity group.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

external_radius_server

class ExternalRadiusServer

Identity Services Engine ExternalRADIUSServer API (version: 3.1.0).

Wraps the Identity Services Engine ExternalRADIUSServer API and exposes the API as native Python methods that return native Python objects.

get_external_radius_server_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_name*

get_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an external RADIUS server by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server_by_id*

update_external_radius_server_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.
- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore), property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.

- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *accounting_port=None*, *authentication_port=None*, *authenticator_key=None*, *description=None*, *enable_key_wrap=None*, *encryption_key=None*, *host_ip=None*, *key_input_format=None*, *name=None*, *proxy_timeout=None*, *retries=None*, *shared_secret=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_external_radius_server_by_id*

delete_external_radius_server_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an external RADIUS server.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_external_radius_server_by_id*

get_external_radius_server(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_external_radius_server*

get_external_radius_server_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the external RADIUS servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_external_radius_server_generator*

create_external_radius_server(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an external RADIUS server.

Parameters

- **accounting_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authentication_port** (*integer*) – Valid Range 1 to 65535, property of the request body.
- **authenticator_key** (*string*) – The authenticatorKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 20 ASCII characters or 40 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **description** (*string*) – description, property of the request body.
- **enable_key_wrap** (*boolean*) – KeyWrap may only be enabled if it is supported on the device. When running in FIPS mode this option should be enabled for such devices, property of the request body.
- **encryption_key** (*string*) – The encryptionKey is required only if enableKeyWrap is true, otherwise it must be ignored or empty. The maximum length is 16 ASCII characters or 32 HEXADECIMAL characters (depend on selection in field 'keyInputFormat'), property of the request body.
- **host_ip** (*string*) – The IP of the host must be a valid IPV4 address, property of the request body.
- **key_input_format** (*string*) – Specifies the format of the input for fields 'encryption-Key' and 'authenticatorKey'. Allowed Values: ASCII HEXADECIMAL, property of the request body.

- **name** (*string*) – Resource Name. Allowed characters are alphanumeric and _ (underscore), property of the request body.
- **proxy_timeout** (*integer*) – Valid Range 1 to 600, property of the request body.
- **retries** (*integer*) – Valid Range 1 to 9, property of the request body.
- **shared_secret** (*string*) – Shared secret maximum length is 128 characters, property of the request body.
- **timeout** (*integer*) – Valid Range 1 to 120, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*accounting_port=None, authentication_port=None, authenticator_key=None, description=None, enable_key_wrap=None, encryption_key=None, host_ip=None, key_input_format=None, name=None, proxy_timeout=None, retries=None, shared_secret=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_external_radius_server*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the external RADIUS server.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

filter_policy

class FilterPolicy

Identity Services Engine FilterPolicy API (version: 3.1.0).

Wraps the Identity Services Engine FilterPolicy API and exposes the API as native Python methods that return native Python objects.

get_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a filter policy by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_filter_policy_by_id*

update_filter_policy_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *domains=None*, *sgt=None*, *subnet=None*, *vn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_filter_policy_by_id*

delete_filter_policy_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a filter policy.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_filter_policy_by_id`*

`get_filter_policy(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`

Alias for *`get_filter_policy`*

`get_filter_policy_generator(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the filter policies.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_filter_policy_generator*

create_filter_policy(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a filter policy.

Parameters

- **domains** (*string*) – List of SXP Domains, separated with comma, property of the request body.
- **sgt** (*string*) – SGT name or ID. At least one of subnet or sgt or vn should be defined, property of the request body.
- **subnet** (*string*) – Subnet for filter policy (hostname is not supported). At least one of subnet or sgt or vn should be defined, property of the request body.
- **vn** (*string*) – Virtual Network. At least one of subnet or sgt or vn should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*domains=None, sgt=None, subnet=None, vn=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_filter_policy*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the filter policy.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_location

class GuestLocation

Identity Services Engine GuestLocation API (version: 3.1.0).

Wraps the Identity Services Engine GuestLocation API and exposes the API as native Python methods that return native Python objects.

get_guest_location_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a guest location by ID.

Parameters

- **`id (basestring)`** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_location_by_id*

get_guest_location(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_location*

get_guest_location_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest locations. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type (basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_guest_location_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest location.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_smtp_notification_configuration

class GuestSmtpNotificationConfiguration

Identity Services Engine GuestSMTPNotificationConfiguration API (version: 3.1.0).

Wraps the Identity Services Engine GuestSMTPNotificationConfiguration API and exposes the API as native Python methods that return native Python objects.

get_guest_smtp_notification_settings_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest SMTP notification configuration by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_smtp_notification_settings_by_id*

update_guest_smtp_notification_settings_by_id(*id*, *connection_timeout=None*,
default_from_address=None,
notification_enabled=None, *password=None*,
smtp_port=None, *smtp_server=None*,
use_default_from_address=None,
use_password_authentication=None,
use_tlssr_ssl_encryption=None,
user_name=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update a SMTP configuration setting.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlslor_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_timeout=None*, *default_from_address=None*, *notification_enabled=None*, *password=None*, *smtp_port=None*, *smtp_server=None*, *use_default_from_address=None*, *use_password_authentication=None*, *use_tlslor_ssl_encryption=None*, *user_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_smtp_notification_settings_by_id*

```
get_guest_smtp_notification_settings(filter=None, filter_type=None, page=None, size=None,
                                     sortasc=None, sortdsc=None, headers=None,
                                     **query_parameters)
```

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for *get_guest_smtp_notification_settings*

```
get_guest_smtp_notification_settings_generator(filter=None, filter_type=None, page=None,
                                                size=None, sortasc=None, sortdsc=None,
                                                headers=None, **query_parameters)
```

This API allows the client to get all the guest SMTP notification configurations. Filter: [name] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

Alias for `get_guest_smtp_notification_settings_generator`


```
create_guest_smtp_notification_settings(connection_timeout=None, default_from_address=None,
                                         notification_enabled=None, password=None,
                                         smtp_port=None, smtp_server=None,
                                         use_default_from_address=None,
                                         use_password_authentication=None,
                                         use_tlssr_ssl_encryption=None, user_name=None,
                                         headers=None, payload=None, active_validation=True,
                                         **query_parameters)
```

This API creates a guest SMTP notification configuration.

Parameters

- **connection_timeout** (*string*) – Interval in seconds for all the SMTP client connections, property of the request body.
- **default_from_address** (*string*) – The default from email address to be used to send emails from, property of the request body.
- **notification_enabled** (*boolean*) – Indicates if the email notification service is to be enabled, property of the request body.
- **password** (*string*) – Password of Secure SMTP server, property of the request body.
- **smtp_port** (*string*) – Port at which SMTP Secure Server is listening, property of the request body.
- **smtp_server** (*string*) – The SMTP server ip address or fqdn such as out-bound.mycompany.com, property of the request body.
- **use_default_from_address** (*boolean*) – If the default from address should be used rather than using a sponsor user email address, property of the request body.
- **use_password_authentication** (*boolean*) – If configured to true, SMTP server authentication will happen using username/password, property of the request body.
- **use_tlssr_ssl_encryption** (*boolean*) – If configured to true, SMTP server authentication will happen using TLS/SSL, property of the request body.
- **user_name** (*string*) – Username of Secure SMTP server, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_timeout=None, default_from_address=None, notification_enabled=None, password=None, smtp_port=None, smtp_server=None, use_default_from_address=None, use_password_authentication=None, use_tlsor_ssl_encryption=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_guest_smtp_notification_settings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest smtp notification configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_ssid

class GuestSsid

Identity Services Engine GuestSSID API (version: 3.1.0).

Wraps the Identity Services Engine GuestSSID API and exposes the API as native Python methods that return native Python objects.

get_guest_ssid_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_guest_ssid_by_id`

`update_guest_ssid_by_id(id, name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a guest SSID by ID.

Parameters

- **`id (basestring)`** – id, property of the request body.
- **`name (string)`** – Resource Name. Name may contain alphanumeric or any of the following characters `[_.-]`, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_ssid_by_id*

delete_guest_ssid_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest SSID by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_ssid_by_id*

get_guest_ssid(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*,
 headers=None, ***query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and

can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid*

get_guest_ssid_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest SSIDs. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_ssid_generator*

create_guest_ssid(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest SSID.

Parameters

- **name** (*string*) – Resource Name. Name may contain alphanumeric or any of the following characters [_.-], property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_ssid*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the guest SSID.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

guest_type

class `GuestType`

Identity Services Engine GuestType API (version: 3.1.0).

Wraps the Identity Services Engine GuestType API and exposes the API as native Python methods that return native Python objects.

`update_guest_type_email`(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update a guest type email by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_email(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_guest_type_email*

update_guest_type_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*,
 active_validation=True, ***query_parameters*)

This API allows the client to update a guest type sms by ID.

Parameters

- **additional_data** (*list*) – additionalData, property of the request body (list of objects).
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
***query_parameters*)

Alias for *update_guest_type_sms*

get_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest type by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_type_by_id*

update_guest_type_by_id(*id*, *access_time=None*, *description=None*, *expiration_notification=None*,
is_default_type=None, *login_options=None*, *name=None*,
sponsor_groups=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *access_time=None*, *description=None*, *expiration_notification=None*, *is_default_type=None*, *login_options=None*, *name=None*, *sponsor_groups=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_type_by_id*

delete_guest_type_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest type.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_guest_type_by_id`

`get_guest_type(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type*

get_guest_type_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest types. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_type_generator*

create_guest_type(*access_time=None, description=None, expiration_notification=None, is_default_type=None, login_options=None, name=None, sponsor_groups=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest type.

Parameters

- **access_time** (*object*) – accessTime, property of the request body.
- **description** (*string*) – description, property of the request body.
- **expiration_notification** (*object*) – Expiration Notification Settings, property of the request body.
- **is_default_type** (*boolean*) – isDefaultType, property of the request body.
- **login_options** (*object*) – loginOptions, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sponsor_groups** (*list*) – sponsorGroups, property of the request body (list of strings).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(access_time=None, description=None, expiration_notification=None, is_default_type=None,
        login_options=None, name=None, sponsor_groups=None, headers=None, payload=None,
        active_validation=True, **query_parameters)
Alias for create_guest_type
```

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the guest type.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

guest_user

class GuestUser

Identity Services Engine GuestUser API (version: 3.1.0).

Wraps the Identity Services Engine GuestUser API and exposes the API as native Python methods that return native Python objects.

```
approve_guest_user_by_id(id, headers=None, **query_parameters)
```

This API allows the client to approve a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`approve_by_id(id, headers=None, **query_parameters)`

Alias for `approve_guest_user_by_id`

`change_sponsor_password(portal_id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to change the sponsor password.

Parameters

- **`additional_data(list)`** – `additionalData`, property of the request body (list of objects).
- **`portal_id(basestring)`** – `portalId` path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`suspend_guest_user_by_name(name, headers=None, **query_parameters)`

This API allows the client to suspend a guest user by name.

Parameters

- **`name(basestring)`** – `name` path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

suspend_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *suspend_guest_user_by_name*

reinstate_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reinstate_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *reinstate_guest_user_by_name*

get_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_name*

update_guest_user_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by name.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.

- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *id=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_name*

delete_guest_user_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a guest user.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_guest_user_by_name*

reset_guest_user_password_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reset the guest user password.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_password_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *reset_guest_user_password_by_id*

reinstate_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to reinstate a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reinstate_by_id(id, headers=None, **query_parameters)`

Alias for *`reinstate_guest_user_by_id`*

`update_guest_user_email(id, portal_id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a guest user email by ID.

Parameters

- **`additional_data(list)`** – `additionalData`, property of the request body (list of objects).
- **`id(basestring)`** – `id` path parameter.
- **`portal_id(basestring)`** – `portalId` path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to `True`.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_email(id, portal_id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Alias for *`update_guest_user_email`*

update_guest_user_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

This API allows the client to update a guest user sms by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **portal_id** (*basestring*) – portalId path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_sms(*id*, *portal_id*, *headers=None*, ***query_parameters*)

Alias for *update_guest_user_sms*

deny_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deny a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deny_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deny_guest_user_by_id*

get_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_guest_user_by_id*

update_guest_user_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a guest user by ID.

Parameters

- **custom_fields** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_access_info** (*object*) – guestAccessInfo, property of the request body.
- **guest_info** (*object*) – guestInfo, property of the request body.
- **guest_type** (*string*) – guestType, property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **name** (*string*) – name, property of the request body.
- **portal_id** (*string*) – portalId, property of the request body.
- **reason_for_visit** (*string*) – reasonForVisit, property of the request body.
- **sponsor_user_id** (*string*) – sponsorUserId, property of the request body.
- **sponsor_user_name** (*string*) – sponsorUserName, property of the request body.
- **status** (*string*) – status, property of the request body.
- **status_reason** (*string*) – statusReason, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_fields=None*, *description=None*, *guest_access_info=None*, *guest_info=None*, *guest_type=None*, *name=None*, *portal_id=None*, *reason_for_visit=None*, *sponsor_user_id=None*, *sponsor_user_name=None*, *status=None*, *status_reason=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_guest_user_by_id*

delete_guest_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a guest user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_guest_user_by_id`

`get_guest_users(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_guest_users*

`get_guest_users_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the guest users. Filter: [lastName, sponsor, creationTime, personBeingVisited, toDate, userName, firstName, emailAddress, phoneNumber, groupTag, name, company, guestType, status] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [firstName, lastName, emailAddress, name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_guest_users_generator`

`create_guest_user`(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a guest user.

Parameters

- **`custom_fields`** (*object*) – Key value map, property of the request body.
- **`description`** (*string*) – description, property of the request body.
- **`guest_access_info`** (*object*) – `guestAccessInfo`, property of the request body.
- **`guest_info`** (*object*) – `guestInfo`, property of the request body.
- **`guest_type`** (*string*) – `guestType`, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`portal_id`** (*string*) – `portalId`, property of the request body.
- **`reason_for_visit`** (*string*) – `reasonForVisit`, property of the request body.
- **`sponsor_user_id`** (*string*) – `sponsorUserId`, property of the request body.
- **`sponsor_user_name`** (*string*) – `sponsorUserName`, property of the request body.
- **`status`** (*string*) – status, property of the request body.
- **`status_reason`** (*string*) – `statusReason`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*custom_fields=None, description=None, guest_access_info=None, guest_info=None, guest_type=None, name=None, portal_id=None, reason_for_visit=None, sponsor_user_id=None, sponsor_user_name=None, status=None, status_reason=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_guest_user*

suspend_guest_user_by_id(*id, additional_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to suspend a guest user by ID.

Parameters

- **`additional_data (list)`** – `additionalData`, property of the request body (list of objects).
- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

suspend_by_id(*id*, *additional_data=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *suspend_guest_user_by_id*

get_version(*headers=None*, ***query_parameters*)

This API helps to retrieve the version information related to the guest user.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_guest_user(*operation_type=None*, *resource_media_type=None*, *headers=None*,
 payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_guest_user*

monitor_bulk_status_guest_user(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_guest_user*

hotspot_portal

class HotspotPortal

Identity Services Engine HotspotPortal API (version: 3.1.0).

Wraps the Identity Services Engine HotspotPortal API and exposes the API as native Python methods that return native Python objects.

get_hotspot_portal_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a hotspot portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_hotspot_portal_by_id*

update_hotspot_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*,
portal_test_url=None, *portal_type=None*, *settings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a hotspot portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_hotspot_portal_by_id*

delete_hotspot_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a hotspot portal by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_hotspot_portal_by_id*

get_hotspot_portal(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal*

get_hotspot_portal_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the hotspot portals. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_hotspot_portal_generator*

```
create_hotspot_portal(customizations=None, description=None, name=None, portal_test_url=None,  
                      portal_type=None, settings=None, headers=None, payload=None,  
                      active_validation=True, **query_parameters)
```

This API creates a hotspot portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a BYOD, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(customizations=None, description=None, name=None, portal_test_url=None, portal_type=None,  
       settings=None, headers=None, payload=None, active_validation=True, **query_parameters)  
Alias for create_hotspot_portal
```

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the hotspot portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

ip_to_sgt_mapping

class IpToSgtMapping

Identity Services Engine IPToSGTMMapping API (version: 3.1.0).

Wraps the Identity Services Engine IPToSGTMMapping API and exposes the API as native Python methods that return native Python objects.

deploy_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *deploy_ip_to_sgt_mapping_by_id*

deploy_all_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mappings. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all(*headers=None*, ***query_parameters*)

Alias for *deploy_all_ip_to_sgt_mapping*

get_deploy_status_ip_to_sgt_mapping(*headers=None*, ***query_parameters*)

This API allows the client to get the IP to SGT mapping deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status(*headers=None, **query_parameters*)

Alias for *get_deploy_status_ip_to_sgt_mapping*

get_ip_to_sgt_mapping_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_by_id*

update_ip_to_sgt_mapping_by_id(*id, deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to update an IP to SGT mapping by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deployType=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if hostName is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if hostIp is empty, property of the request body.

- **id** (*basestring*) – id, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless sgt and deployTo and deployType are set, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *host_ip=None*, *host_name=None*, *mapping_group=None*, *name=None*, *sgt=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_by_id*

delete_ip_to_sgt_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_ip_to_sgt_mapping_by_id`*

`get_ip_to_sgt_mapping(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping*

`get_ip_to_sgt_mapping_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mappings. Filter: [hostName, groupName, ip, sgtName] To search guest users by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [hostName, groupName, ip, sgtName].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response

- `text(str)`: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_generator*

create_ip_to_sgt_mapping(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping.

Parameters

- **deploy_to** (*string*) – Mandatory unless `mappingGroup` is set or unless `deployType=ALL`, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **host_ip** (*string*) – Mandatory if `hostName` is empty -valid IP, property of the request body.
- **host_name** (*string*) – Mandatory if `hostIp` is empty, property of the request body.
- **mapping_group** (*string*) – Mapping Group Id. Mandatory unless `sgt` and `deployTo` and `deployType` are set, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless `mappingGroup` is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*deploy_to=None, deploy_type=None, host_ip=None, host_name=None, mapping_group=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to IP to SGT mapping.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_ip_to_sgt_mapping(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping*

monitor_bulk_status_ip_to_sgt_mapping(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping*

ip_to_sgt_mapping_group

class IpToSgtMappingGroup

Identity Services Engine IPToSGTMappingGroup API (version: 3.1.0).

Wraps the Identity Services Engine IPToSGTMappingGroup API and exposes the API as native Python methods that return native Python objects.

deploy_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to deploy an IP to SGT mapping group by ID. Only one Deploy process can run at any given time.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

deploy_all_ip_to_sgt_mapping_group(*headers=None*, ***query_parameters*)

This API allows the client to deploy all the IP to SGT mapping groups. Only one Deploy process can run at any given time.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_deploy_status_ip_to_sgt_mapping_group(*headers=None, **query_parameters*)

This API allows the client to get the IP to SGT mapping group deployment status. Deploy Status will show last Deploy command output. The information will be saved until the next Deploy command.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_ip_to_sgt_mapping_group_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get an IP to SGT mapping group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_by_id*

update_ip_to_sgt_mapping_group_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*,
sgt=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

This API allows the client to update an IP to SGT mapping group by ID.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *deploy_to=None*, *deploy_type=None*, *name=None*, *sgt=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_ip_to_sgt_mapping_group_by_id*

delete_ip_to_sgt_mapping_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an IP to SGT mapping group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_ip_to_sgt_mapping_group_by_id*

get_ip_to_sgt_mapping_group(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group*

get_ip_to_sgt_mapping_group_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the IP to SGT mapping groups. Filter: [name, sgt-Name] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, sgtName].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_ip_to_sgt_mapping_group_generator*

create_ip_to_sgt_mapping_group(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an IP to SGT mapping group.

Parameters

- **deploy_to** (*string*) – Mandatory unless mappingGroup is set or unless deploy-Type=ALL, property of the request body.
- **deploy_type** (*string*) – Allowed values: ALL, ND, NDG, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt** (*string*) – Mandatory unless mappingGroup is set, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*deploy_to=None, deploy_type=None, name=None, sgt=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_ip_to_sgt_mapping_group*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the IP to SGT mapping group.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_ip_to_sgt_mapping_group`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_ip_to_sgt_mapping_group*

monitor_bulk_status_ip_to_sgt_mapping_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_ip_to_sgt_mapping_group*

identity_groups

class IdentityGroups

Identity Services Engine IdentityGroups API (version: 3.1.0).

Wraps the Identity Services Engine IdentityGroups API and exposes the API as native Python methods that return native Python objects.

get_identity_group_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_group_by_name*

get_identity_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_group_by_id*

update_identity_group_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_group_by_id*

```
get_identity_groups(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                    sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for *get_identity_groups*

get_identity_groups_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the identity groups. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_identity_groups_generator*

```
create_identity_group(description=None, name=None, parent=None, headers=None, payload=None,  
                      active_validation=True, **query_parameters)
```

This API creates an identity group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, name=None, parent=None, headers=None, payload=None,  
       active_validation=True, **query_parameters)
```

Alias for *create_identity_group*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to identity group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

identity_sequence

class IdentitySequence

Identity Services Engine IdentitySequence API (version: 3.1.0).

Wraps the Identity Services Engine IdentitySequence API and exposes the API as native Python methods that return native Python objects.

get_identity_sequence_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_name*

get_identity_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an identity sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_identity_sequence_by_id*

update_identity_sequence_by_id(*id*, *break_on_store_fail=None*,
certificate_authentication_profile=None, *description=None*,
id_seq_item=None, *name=None*, *parent=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update an identity sequence. Partial update is not supported.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *break_on_store_fail=None*, *certificate_authentication_profile=None*, *description=None*, *id_seq_item=None*, *name=None*, *parent=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_identity_sequence_by_id*

`delete_identity_sequence_by_id`(*id*, *headers=None*, ***query_parameters*)

This API deletes an identity sequence.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_identity_sequence_by_id*

`get_identity_sequence`(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence*

get_identity_sequence_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the identity sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request's response
 - text(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_identity_sequence_generator*

create_identity_sequence(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an identity sequence.

Parameters

- **break_on_store_fail** (*boolean*) – breakOnStoreFail, property of the request body.
- **certificate_authentication_profile** (*string*) – certificateAuthenticationProfile, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id_seq_item** (*list*) – idSeqItem, property of the request body (list of objects).
- **name** (*string*) – name, property of the request body.
- **parent** (*string*) – parent, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*break_on_store_fail=None, certificate_authentication_profile=None, description=None, id_seq_item=None, name=None, parent=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_identity_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the identity sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

internal_user

class InternalUser

Identity Services Engine InternalUser API (version: 3.1.0).

Wraps the Identity Services Engine InternalUser API and exposes the API as native Python methods that return native Python objects.

get_internal_user_by_name(*name*, *headers=None*, ****query_parameters**)

This API allows the client to get an internal user by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for `get_internal_user_by_name`

update_internal_user_by_name(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by name.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_name`(*name*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *id=None*, *identity_groups=None*, *last_name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *`update_internal_user_by_name`*

`delete_internal_user_by_name`(*name*, *headers=None*, ***query_parameters*)

This API deletes an internal user by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`delete_internal_user_by_name`*

`get_internal_user_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an internal user by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_internal_user_by_id*

update_internal_user_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an internal user by ID.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.

- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *change_password=None*, *custom_attributes=None*, *description=None*, *email=None*, *enable_password=None*, *enabled=None*, *expiry_date=None*, *expiry_date_enabled=None*, *first_name=None*, *identity_groups=None*, *last_name=None*, *name=None*, *password=None*, *password_idstore=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_internal_user_by_id*

delete_internal_user_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an internal user by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_by_id(id, headers=None, **query_parameters)
```

Alias for *delete_internal_user_by_id*

```
get_internal_user(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
                  headers=None, **query_parameters)
```

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
get_all(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None,
        headers=None, **query_parameters)
```

Alias for *get_internal_user*

```
get_internal_user_generator(filter=None, filter_type=None, page=None, size=None, sortasc=None,
                             sortdsc=None, headers=None, **query_parameters)
```

This API allows the client to get all the internal users. Filter: [firstName, lastName, identityGroup, name, description, email, enabled] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request's response
 - text(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_internal_user_generator*

create_internal_user(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an internal user.

Parameters

- **change_password** (*boolean*) – changePassword, property of the request body.
- **custom_attributes** (*object*) – Key value map, property of the request body.
- **description** (*string*) – description, property of the request body.
- **email** (*string*) – email, property of the request body.
- **enable_password** (*string*) – enablePassword, property of the request body.
- **enabled** (*boolean*) – Whether the user is enabled/disabled. To use it as filter, the values should be 'Enabled' or 'Disabled'. The values are case sensitive. For example, '[ERSObjectURL]?filter=enabled.EQ.Enabled', property of the request body.
- **expiry_date** (*string*) – To store the internal user's expiry date information. It's format is = 'YYYY-MM-DD', property of the request body.
- **expiry_date_enabled** (*boolean*) – expiryDateEnabled, property of the request body.
- **first_name** (*string*) – firstName, property of the request body.
- **identity_groups** (*string*) – CSV of identity group IDs, property of the request body.
- **last_name** (*string*) – lastName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **password** (*string*) – password, property of the request body.
- **password_idstore** (*string*) – The id store where the internal user's password is kept, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

create(*change_password=None, custom_attributes=None, description=None, email=None, enable_password=None, enabled=None, expiry_date=None, expiry_date_enabled=None, first_name=None, identity_groups=None, last_name=None, name=None, password=None, password_idstore=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_internal_user*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the internal user.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

mdm

class Mdm

Identity Services Engine MDM API (version: 3.1.0).

Wraps the Identity Services Engine MDM API and exposes the API as native Python methods that return native Python objects.

get_endpoints(*headers=None, **query_parameters*)
getEndpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_endpoints*

get_endpoint_by_mac_address(*headers=None, **query_parameters*)
getEndpointByMacAddress.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_type(*headers=None, **query_parameters*)
getEndpointsByType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_endpoints_by_os_type(*headers=None, **query_parameters*)
getEndpointsByOsType.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

misc

class Misc

Identity Services Engine Misc API (version: 3.1.0).

Wraps the Identity Services Engine Misc API and exposes the API as native Python methods that return native Python objects.

get_active_count(*headers=None, **query_parameters*)
ActiveCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_active_list(*headers=None, **query_parameters*)
ActiveList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_session_auth_list(*headers=None, **query_parameters*)

Session/AuthList.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_posture_count(*headers=None, **query_parameters*)

PostureCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_profiler_count(*headers=None, **query_parameters*)
ProfilerCount.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_mac(*mac, headers=None, **query_parameters*)
Sessions by MAC.

Parameters

- **mac** (*basestring*) – mac path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_username(*username*, *headers=None*, ***query_parameters*)

Sessions by Username.

Parameters

- **username** (*basestring*) – username path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_nas_ip(*nas_ipv4*, *headers=None*, ***query_parameters*)

Sessions by NAS IP.

Parameters

- **nas_ipv4** (*basestring*) – nas_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_endpoint_ip(*endpoint_ipv4*, *headers=None*, ***query_parameters*)

Sessions by Endpoint IP.

Parameters

- **endpoint_ipv4** (*basestring*) – endpoint_ipv4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_sessions_by_session_id(*session_id*, *headers=None*, ***query_parameters*)

Sessions by SessionID.

Parameters

- **session_id** (*basestring*) – session_id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_all_sessions(*headers=None, **query_parameters*)

Delete All Sessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_mnt_version(*headers=None, **query_parameters*)

MNT Version.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_failure_reasons(*headers=None, **query_parameters*)
FailureReasons.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_authentication_status_by_mac(*mac, rec_ord_s, sec_ond_s, headers=None, **query_parameters*)
AuthenticationStatus by MAC.

Parameters

- **mac** (*basestring*) – MAC path parameter.
- **sec_ond_s** (*basestring*) – SECONDS path parameter.
- **rec_ord_s** (*basestring*) – RECORDS path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_reauthentication_by_mac(*end_poi_ntm_ac*, *psn_nam_e*, *rea_uth_typ_e*, *headers=None*,
***query_parameters*)

Session Reauthentication by MAC.

Parameters

- **psn_nam_e** (*basestring*) – PSN_NAME path parameter.
- **end_poi_ntm_ac** (*basestring*) – ENDPOINT_MAC path parameter.
- **rea_uth_typ_e** (*basestring*) – REAUTH_TYPE path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_disconnect(*dis_con_nec_tty_pe*, *end_poi_nti_p*, *mac*, *nas_ipv4*, *psn_nam_e*, *headers=None*,
***query_parameters*)

Session Disconnect.

Parameters

- **end_poi_nti_p** (*basestring*) – ENDPOINT_IP path parameter.
- **psn_nam_e** (*basestring*) – PSN_NAME path parameter.
- **mac** (*basestring*) – MAC path parameter.
- **dis_con_nec_tty_pe** (*basestring*) – DISCONNECT_TYPE path parameter.
- **nas_ipv4** (*basestring*) – NAS_IPV4 path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_account_status_by_mac`(*duration, mac, headers=None, **query_parameters*)
AccountStatus by MAC.

Parameters

- **`mac`** (*basestring*) – mac path parameter.
- **`duration`** (*basestring*) – duration path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

my_device_portal

class MyDevicePortal

Identity Services Engine MyDevicePortal API (version: 3.1.0).

Wraps the Identity Services Engine MyDevicePortal API and exposes the API as native Python methods that return native Python objects.

get_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_my_device_portal_by_id*

update_my_device_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a my device portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_my_device_portal_by_id*

delete_my_device_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a my device portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_my_device_portal_by_id*

get_my_device_portal(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal*

get_my_device_portal_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the my device portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_my_device_portal_generator*

create_my_device_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a my device portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a Mydevice portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)
 Alias for [*create_my_device_portal*](#)

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the my device portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

native_suppllicant_profile

class NativeSuppllicantProfile

Identity Services Engine NativeSuppllicantProfile API (version: 3.1.0).

Wraps the Identity Services Engine NativeSuppllicantProfile API and exposes the API as native Python methods that return native Python objects.

get_native_suppllicant_profile_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a native suppllicant profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_native_suppllicant_profile_by_id`*

`update_native_suppllicant_profile_by_id(id, description=None, name=None, wireless_profiles=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a native suppllicant profile.

Parameters

- **`description`** (*string*) – description, property of the request body.
- **`id`** (*basestring*) – id, property of the request body.
- **`name`** (*string*) – name, property of the request body.
- **`wireless_profiles`** (*list*) – wirelessProfiles, property of the request body (list of objects).
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *wireless_profiles=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_native_suppllicant_profile_by_id](#)

delete_native_suppllicant_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a native supplicant profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [delete_native_suppllicant_profile_by_id](#)

get_native_suppllicant_profile(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the native supplicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile*

get_native_suppllicant_profile_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the native suppllicant profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type *Generator*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_native_suppllicant_profile_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the native suppllicant profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

network_access_authentication_rules

class NetworkAccessAuthenticationRules

Identity Services Engine Network Access - Authentication Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authentication Rules API and exposes the API as native Python methods that return native Python objects.

`get_network_access_authentication_rules`(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authentication rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*policy_id*, *headers=None*, ***query_parameters*)

Alias for `get_network_access_authentication_rules`

```
create_network_access_authentication_rule(policy_id, identity_source_name=None,  
                                           if_auth_fail=None, if_process_fail=None,  
                                           if_user_not_found=None, link=None, rule=None,  
                                           headers=None, payload=None,  
                                           active_validation=True, **query_parameters)
```

Network Access Create authentication rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authentication policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **identity_source_name** (*string*) – Identity source name from the identity stores, property of the request body.
- **if_auth_fail** (*string*) – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **if_process_fail** (*string*) – Action to perform when ISE is unable to access the identity database, property of the request body.
- **if_user_not_found** (*string*) – Action to perform when user is not found in any of identity stores, property of the request body.
- **link** (*object*) – link, property of the request body.
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *identity_source_name=None*, *if_auth_fail=None*, *if_process_fail=None*, *if_user_not_found=None*, *link=None*, *rule=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authentication_rule*

reset_hit_counts_network_access_authentication_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authentication Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authentication_rules*

get_network_access_authentication_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, policy_id, headers=None, **query_parameters)`

Alias for `get_network_access_authentication_rule_by_id`

`update_network_access_authentication_rule_by_id(id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update rule.

Parameters

- **`identity_source_name (string)`** – Identity source name from the identity stores, property of the request body.
- **`if_auth_fail (string)`** – Action to perform when authentication fails such as Bad credentials, disabled user and so on, property of the request body.
- **`if_process_fail (string)`** – Action to perform when ISE is unable to access the identity database, property of the request body.
- **`if_user_not_found (string)`** – Action to perform when user is not found in any of identity stores, property of the request body.
- **`link (object)`** – link, property of the request body.
- **`rule (object)`** – Common attributes in rule authentication/authorization, property of the request body.
- **`policy_id (basestring)`** – policyId path parameter. Policy id.
- **`id (basestring)`** – id path parameter. Rule id.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id, policy_id, identity_source_name=None, if_auth_fail=None, if_process_fail=None, if_user_not_found=None, link=None, rule=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *update_network_access_authentication_rule_by_id*

delete_network_access_authentication_rule_by_id(*id, policy_id, headers=None, **query_parameters*)

Network Access Delete rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id, policy_id, headers=None, **query_parameters*)

Alias for *delete_network_access_authentication_rule_by_id*

network_access_authorization_exception_rules

class NetworkAccessAuthorizationExceptionRules

Identity Services Engine Network Access - Authorization Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_local_exception_rules(*policy_id*, *headers=None*, ***query_parameters*)
Network Access Get local exception rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*policy_id*, *headers=None*, ***query_parameters*)
Alias for *get_network_access_local_exception_rules*

create_network_access_local_exception_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*,
security_group=None, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Create local authorization exception rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_local_exception_rule*

reset_hit_counts_network_access_local_exceptions(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for local exceptions.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_local_exceptions*

get_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*,
***query_parameters*)

Network Access Get local exception rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_local_exception_rule_by_id*

update_network_access_local_exception_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*,
rule=None, *security_group=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Update local exception rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_local_exception_rule_by_id*

delete_network_access_local_exception_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Delete local exception rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_local_exception_rule_by_id*

network_access_authorization_global_exception_rules

class NetworkAccessAuthorizationGlobalExceptionRules

Identity Services Engine Network Access - Authorization Global Exception Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Global Exception Rules API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_set_global_exception_rules(*headers=None*, ***query_parameters*)

Network Access Get global exception rules.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rules*

create_network_access_policy_set_global_exception_rule(*link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create global exception authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set_global_exception_rule*

reset_hit_counts_network_access_global_exceptions(*headers=None, **query_parameters*)

Network Access Reset HitCount for Global Exceptions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_global_exceptions*

get_network_access_policy_set_global_exception_rule_by_id(*id, headers=None, **query_parameters*)

Network Access Get global exception rule attributes.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_network_access_policy_set_global_exception_rule_by_id*

update_network_access_policy_set_global_exception_rule_by_id(*id, link=None, profile=None, rule=None, security_group=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update global exception authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.

- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_global_exception_rule_by_id*

delete_network_access_policy_set_global_exception_rule_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete global exception authorization rule.

Parameters

- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_network_access_policy_set_global_exception_rule_by_id`*

network_access_authorization_rules

class `NetworkAccessAuthorizationRules`

Identity Services Engine Network Access - Authorization Rules API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Authorization Rules API and exposes the API as native Python methods that return native Python objects.

`get_network_access_authorization_rules(policy_id, headers=None, **query_parameters)`

Network Access Get authorization rules.

Parameters

- **`policy_id`** (*basestring*) – policyId path parameter. Policy id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(policy_id, headers=None, **query_parameters)`

Alias for *`get_network_access_authorization_rules`*

create_network_access_authorization_rule(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Create authorization rule: Rule must include name and condition. Condition has hierarchical structure which define a set of conditions for which authorization policy rule could be match. Condition can be either reference to a stored Library condition, using model ConditionReference or dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_authorization_rule*

reset_hit_counts_network_access_authorization_rules(*policy_id*, *headers=None*, ***query_parameters*)

Network Access Reset HitCount for Authorization Rules.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reset_hit_counts_by_id(*policy_id*, *headers=None*, ***query_parameters*)

Alias for *reset_hit_counts_network_access_authorization_rules*

get_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Network Access Get authorization rule attributes.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_authorization_rule_by_id*

update_network_access_authorization_rule_by_id(*id*, *policy_id*, *link=None*, *profile=None*,
rule=None, *security_group=None*,
headers=None, *payload=None*,
active_validation=True, ***query_parameters*)

Network Access Update authorization rule.

Parameters

- **link** (*object*) – link, property of the request body.
- **profile** (*list*) – The authorization profile/s, property of the request body (list of strings).
- **rule** (*object*) – Common attributes in rule authentication/authorization, property of the request body.
- **security_group** (*string*) – Security group used in authorization policies, property of the request body.
- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *policy_id*, *link=None*, *profile=None*, *rule=None*, *security_group=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_authorization_rule_by_id*

delete_network_access_authorization_rule_by_id(*id*, *policy_id*, *headers=None*,
***query_parameters*)

Network Access Delete authorization rule.

Parameters

- **policy_id** (*basestring*) – policyId path parameter. Policy id.
- **id** (*basestring*) – id path parameter. Rule id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *policy_id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_authorization_rule_by_id*

network_access_conditions

class NetworkAccessConditions

Identity Services Engine Network Access - Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_conditions(*headers=None*, ***query_parameters*)

Network Access Returns all library conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_conditions*

create_network_access_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates a library condition: Library Condition has hierarchical structure which define a set of condition for which authentication and authorization policy rules could be match. Condition can be compose from single dictionary attribute name and value using model LibraryConditionAttributes , or from combination of dictionary attributes with logical operation of AND/OR between them, using models: LibraryConditionAndBlock or LibraryConditionOrBlock . When using AND/OR blocks, the condition will include inner layers inside these blocks, these layers are built using the inner condition models: ConditionAttributes , ConditionAndBlock , ConditionOrBlock , that represent dynamically built Conditions which are not stored in the conditions Library, or using ConditionReference , which includes an ID to existing stored condition in the library. The LibraryCondition models can only be used in the outer-most layer (root of the condition) and must always include the condition name. When using one of the 3 inner condition models (ConditionAttributes, ConditionAndBlock, ConditionOrBlock), condition name cannot be included in the request, since these will not be stored in the conditions library, and used only as inner members of the root condition. When using ConditionReference model in inner layers, the condition name is not required. ConditionReference objects can also include a reference ID to a condition of type TimeAndDate

..

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_condition*

get_network_access_conditions_for_authentication_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authentication rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_network_access_conditions_for_authorization_rules(*headers=None, **query_parameters*)

Network Access Returns list of library conditions for Authorization rules scope.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_network_access_condition_by_name`(*name*, *headers=None*, ***query_parameters*)

Network Access Returns a library condition.

Parameters

- **`name`** (*basestring*) – name path parameter. Condition name.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for *`get_network_access_condition_by_name`*

`update_network_access_condition_by_name`(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update library condition using condition name.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘notContains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).

- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **name** – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *id=None*, *is_negate=None*, *link=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_condition_by_name*

delete_network_access_condition_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition using condition Name.

Parameters

- **name** (*basestring*) – name path parameter. Condition name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_name(name, headers=None, **query_parameters)`

Alias for *`delete_network_access_condition_by_name`*

`get_network_access_conditions_for_policy_sets(headers=None, **query_parameters)`

Network Access Returns list of library conditions for PolicySet scope.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_for_policy_sets(headers=None, **query_parameters)`

Alias for *`get_network_access_conditions_for_policy_sets`*

`get_network_access_condition_by_id(id, headers=None, **query_parameters)`

Network Access Returns a library condition.

Parameters

- **`id(basestring)`** – id path parameter. Condition id.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_network_access_condition_by_id`*

`update_network_access_condition_by_id(id, attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Network Access Update library condition.

Parameters

- **`attribute_name (string)`** – Dictionary attribute name, property of the request body.
- **`attribute_value (string)`** – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **`children (list)`** – In case type is `andBlock` or `orBlock` additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **`condition_type (string)`** – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates that “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **`dates_range (object)`** – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **`dates_range_exception (object)`** – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.

- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'not-Contains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_network_access_condition_by_id*](#)

delete_network_access_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a library condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_network_access_condition_by_id*](#)

network_access_dictionary

class NetworkAccessDictionary

Identity Services Engine Network Access - Dictionary API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries(*headers=None*, ***query_parameters*)

Get all Dictionaries.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries*

create_network_access_dictionaries(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new Dictionary.

Parameters

- **description** (*string*) – The description of the Dictionary, property of the request body.
- **dictionary_attr_type** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.
- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*description=None, dictionary_attr_type=None, id=None, link=None, name=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_network_access_dictionaries*

`get_network_access_dictionary_by_name`(*name, headers=None, **query_parameters*)
GET a dictionary by name.

Parameters

- **`name`** (*basestring*) – name path parameter. the dictionary name.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name, headers=None, **query_parameters*)
Alias for *get_network_access_dictionary_by_name*

`update_network_access_dictionary_by_name`(*name, description=None, dictionary_attr_type=None, id=None, link=None, version=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Update a Dictionary.

Parameters

- **`description`** (*string*) – The description of the Dictionary, property of the request body.
- **`dictionary_attr_type`** (*string*) – The dictionary attribute type, property of the request body. Available values are 'ENTITY_ATTR', 'MSG_ATTR' and 'PIP_ATTR'.

- **id** (*string*) – Identifier for the dictionary, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*basestring*) – The dictionary name, property of the request body.
- **version** (*string*) – The dictionary version, property of the request body.
- **name** – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *dictionary_attr_type=None*, *id=None*, *link=None*, *version=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_by_name*

delete_network_access_dictionary_by_name(*name*, *headers=None*, ***query_parameters*)

Network Access Delete a Dictionary.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary name.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_dictionary_by_name*

network_access_dictionary_attribute

class NetworkAccessDictionaryAttribute

Identity Services Engine Network Access - Dictionary Attribute API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary Attribute API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionary_attributes_by_dictionary_name(*dictionary_name*,
headers=None,
***query_parameters*)

Returns a list of Dictionary Attributes for an existing Dictionary.

Parameters

- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*dictionary_name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attributes_by_dictionary_name*

```
create_network_access_dictionary_attribute(dictionary_name, allowed_values=None,
                                           data_type=None, description=None,
                                           direction_type=None, id=None, internal_name=None,
                                           name=None, headers=None, payload=None,
                                           active_validation=True, **query_parameters)
```

Create a new Dictionary Attribute for an existing Dictionary.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are ‘BOOLEAN’, ‘DATE’, ‘FLOAT’, ‘INT’, ‘IP’, ‘IPV4’, ‘IPV6’, ‘IPV6INTERFACE’, ‘IPV6PREFIX’, ‘LONG’, ‘OCTET_STRING’, ‘STRING’, ‘UINT64’ and ‘UNIT32’.
- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are ‘BOTH’, ‘IN’, ‘NONE’ and ‘OUT’.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*string*) – The dictionary attribute’s name, property of the request body.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*dictionary_name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *create_network_access_dictionary_attribute*

get_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Get a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_dictionary_attribute_by_name*

update_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update a Dictionary Attribute.

Parameters

- **allowed_values** (*list*) – all of the allowed values for the dictionary attribute, property of the request body (list of objects).
- **data_type** (*string*) – the data type for the dictionary attribute, property of the request body. Available values are 'BOOLEAN', 'DATE', 'FLOAT', 'INT', 'IP', 'IPV4', 'IPV6',

'IPV6INTERFACE', 'IPV6PREFIX', 'LONG', 'OCTET_STRING', 'STRING', 'UINT64' and 'UNIT32'.

- **description** (*string*) – The description of the Dictionary attribute, property of the request body.
- **dictionary_name** (*basestring*) – the name of the dictionary which the dictionary attribute belongs to, property of the request body.
- **direction_type** (*string*) – the direction for the usage of the dictionary attribute, property of the request body. Available values are 'BOTH', 'IN', 'NONE' and 'OUT'.
- **id** (*string*) – Identifier for the dictionary attribute, property of the request body.
- **internal_name** (*string*) – the internal name of the dictionary attribute, property of the request body.
- **name** (*basestring*) – The dictionary attribute's name, property of the request body.
- **name** – name path parameter. the dictionary attribute name.
- **dictionary_name** – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*dictionary_name*, *name*, *allowed_values=None*, *data_type=None*, *description=None*, *direction_type=None*, *id=None*, *internal_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_dictionary_attribute_by_name*

delete_network_access_dictionary_attribute_by_name(*dictionary_name*, *name*, *headers=None*, ***query_parameters*)

Delete a Dictionary Attribute.

Parameters

- **name** (*basestring*) – name path parameter. the dictionary attribute name.
- **dictionary_name** (*basestring*) – dictionaryName path parameter. the name of the dictionary the dictionary attribute belongs to.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*dictionary_name, name, headers=None, **query_parameters*)

Alias for *delete_network_access_dictionary_attribute_by_name*

network_access_dictionary_attributes_list

class NetworkAccessDictionaryAttributesList

Identity Services Engine Network Access - Dictionary Attributes List API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Dictionary Attributes List API and exposes the API as native Python methods that return native Python objects.

get_network_access_dictionaries_authentication(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authentication.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authentication(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authentication*

get_network_access_dictionaries_authorization(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for authorization.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_authorization(*headers=None, **query_parameters*)

Alias for *get_network_access_dictionaries_authorization*

get_network_access_dictionaries_policy_set(*headers=None, **query_parameters*)

Network Access Returns list of dictionary attributes for policyset.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_policy_set(headers=None, **query_parameters)`

Alias for *`get_network_access_dictionaries_policy_set`*

`network_access_identity_stores`

`class NetworkAccessIdentityStores`

Identity Services Engine Network Access - Identity Stores API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Identity Stores API and exposes the API as native Python methods that return native Python objects.

`get_network_access_identity_stores(headers=None, **query_parameters)`

Network Access Return list of identity stores for authentication policy definition. (Other CRUD APIs available through ERS).

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(headers=None, **query_parameters)`

Alias for *`get_network_access_identity_stores`*

network_access_network_conditions

class NetworkAccessNetworkConditions

Identity Services Engine Network Access - Network Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Network Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_network_conditions(*headers=None, **query_parameters*)

Network Access Returns a list of network conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_network_conditions*

create_network_access_network_condition(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are 'DeviceCondition', 'DevicePortCondition' and 'EndstationCondition'.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*condition_type=None, conditions=None, description=None, id=None, link=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_network_condition*

get_network_access_network_condition_by_id(*id, headers=None, **query_parameters*)

Network Access Returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [get_network_access_network_condition_by_id](#)

update_network_access_network_condition_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **condition_type** (*string*) – This field determines the content of the conditions field, property of the request body. Available values are ‘DeviceCondition’, ‘DevicePortCondition’ and ‘EndstationCondition’.
- **conditions** (*list*) – conditions, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Network Condition name, property of the request body.
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition_type=None*, *conditions=None*, *description=None*, *link=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [update_network_access_network_condition_by_id](#)

delete_network_access_network_condition_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)
Alias for *delete_network_access_network_condition_by_id*

network_access_policy_set**class NetworkAccessPolicySet**

Identity Services Engine Network Access - Policy Set API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Policy Set API and exposes the API as native Python methods that return native Python objects.

get_network_access_policy_sets(*headers=None*, ***query_parameters*)
Get all network access policy sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_policy_sets*

create_network_access_policy_set(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Create a new policy set: Policy must include name , service identifier (either server sequence or allowed protocol) and a condition. Condition has hierarchical structure which define a set of condition for which policy could be match. Condition can be either reference to a stored Library condition, using model ConditionReference , or, dynamically built conditions which are not stored in the conditions Library, using models ConditionAttributes, ConditionAndBlock, ConditionOrBlock . .

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*string*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type ‘Proxy Sequence’ or ‘Allowed Protocols’, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.
- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*condition=None, default=None, description=None, hit_counts=None, id=None, is_proxy=None, link=None, name=None, rank=None, service_name=None, state=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_access_policy_set*

`reset_hit_counts_network_access_policy_sets`(*headers=None, **query_parameters*)

Network Access Reset HitCount for PolicySets.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`reset_hit_counts`(*headers=None, **query_parameters*)

Alias for *reset_hit_counts_network_access_policy_sets*

`get_network_access_policy_set_by_id`(*id, headers=None, **query_parameters*)

Network Access Get policy set attributes.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_policy_set_by_id*

update_network_access_policy_set_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update a policy set.

Parameters

- **condition** (*object*) – condition, property of the request body.
- **default** (*boolean*) – Flag which indicates if this policy set is the default one, property of the request body.
- **description** (*string*) – The description for the policy set, property of the request body.
- **hit_counts** (*integer*) – The amount of times the policy was matched, property of the request body.
- **id** (*basestring*) – Identifier for the policy set, property of the request body.
- **is_proxy** (*boolean*) – Flag which indicates if the policy set service is of type 'Proxy Sequence' or 'Allowed Protocols', property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Given name for the policy set, [Valid characters are alphanumerics, underscore, hyphen, space, period, parentheses], property of the request body.
- **rank** (*integer*) – The rank(priority) in relation to other policy set. Lower rank is higher priority., property of the request body.
- **service_name** (*string*) – Policy set service identifier Allowed Protocols,Server Sequence..., property of the request body.

- **state** (*string*) – The state that the policy set is in. A disabled policy set cannot be matched., property of the request body. Available values are ‘disabled’, ‘enabled’ and ‘monitor’.
- **id** – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *condition=None*, *default=None*, *description=None*, *hit_counts=None*, *is_proxy=None*, *link=None*, *name=None*, *rank=None*, *service_name=None*, *state=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_policy_set_by_id*

delete_network_access_policy_set_by_id(*id*, *headers=None*, ***query_parameters*)

Network Access Delete a policy set.

Parameters

- **id** (*basestring*) – id path parameter. Policy id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_policy_set_by_id*

network_access_profiles

class NetworkAccessProfiles

Identity Services Engine Network Access - Profiles API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Profiles API and exposes the API as native Python methods that return native Python objects.

get_network_access_profiles(*headers=None*, ***query_parameters*)

Network Access Returns list of authorization profiles. (Other CRUD APIs available throught ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None*, ***query_parameters*)

Alias for *get_network_access_profiles*

network_access_security_groups

class NetworkAccessSecurityGroups

Identity Services Engine Network Access - Security Groups API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Security Groups API and exposes the API as native Python methods that return native Python objects.

get_network_access_security_groups(*headers=None, **query_parameters*)

Network Access Return list of available security groups for authorization policy definition. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_network_access_security_groups*

network_access_service_names

class NetworkAccessServiceNames

Identity Services Engine Network Access - Service Names API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Service Names API and exposes the API as native Python methods that return native Python objects.

get_network_access_service_names(*headers=None, **query_parameters*)

Returns list of Allowed Protocols and Server Sequences for Network Access Policy Set results. 'isLocalAuthorization' property is available only for Network Access Policy Set results of type Server Sequence. (Other CRUD APIs available through ERS).

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(list)`: A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)
Alias for *get_network_access_service_names*

network_access_time_date_conditions**class NetworkAccessTimeDateConditions**

Identity Services Engine Network Access - Time/Date Conditions API (version: 3.1.0).

Wraps the Identity Services Engine Network Access - Time/Date Conditions API and exposes the API as native Python methods that return native Python objects.

get_network_access_time_conditions(*headers=None, **query_parameters*)
Network Access Returns a list of time and date conditions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for [*get_network_access_time_conditions*](#)

create_network_access_time_condition(*attribute_name=None, attribute_value=None, children=None, condition_type=None, dates_range=None, dates_range_exception=None, description=None, dictionary_name=None, dictionary_value=None, hours_range=None, hours_range_exception=None, id=None, is_negate=None, link=None, name=None, operator=None, week_days=None, week_days_exception=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Network Access Creates time/date condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children field, property of the request body. Available values are ‘ConditionAndBlock’, ‘ConditionAttributes’, ‘ConditionOrBlock’, ‘ConditionReference’, ‘LibraryConditionAndBlock’, ‘LibraryConditionAttributes’, ‘LibraryConditionOrBlock’ and ‘TimeAndDateCondition’.
- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*string*) – id, property of the request body.

- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are ‘contains’, ‘endsWith’, ‘equals’, ‘greaterOrEquals’, ‘greaterThan’, ‘in’, ‘ipEquals’, ‘ipGreaterThan’, ‘ipLessThan’, ‘ipNotEquals’, ‘lessOrEquals’, ‘lessThan’, ‘matches’, ‘not-Contains’, ‘notEndsWith’, ‘notEquals’, ‘notIn’, ‘notStartsWith’ and ‘startsWith’.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are ‘Friday’, ‘Monday’, ‘Saturday’, ‘Sunday’, ‘Thursday’, ‘Tuesday’ and ‘Wednesday’).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(attribute_name=None, attribute_value=None, children=None, condition_type=None,
      dates_range=None, dates_range_exception=None, description=None, dictionary_name=None,
      dictionary_value=None, hours_range=None, hours_range_exception=None, id=None,
      is_negate=None, link=None, name=None, operator=None, week_days=None,
      week_days_exception=None, headers=None, payload=None, active_validation=True,
      **query_parameters)
```

Alias for *create_network_access_time_condition*

```
get_network_access_time_condition_by_id(id, headers=None, **query_parameters)
```

Network Access returns a network condition.

Parameters

- **id** (*basestring*) – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_access_time_condition_by_id*

update_network_access_time_condition_by_id(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Network Access Update network condition.

Parameters

- **attribute_name** (*string*) – Dictionary attribute name, property of the request body.
- **attribute_value** (*string*) – Attribute value for condition Value type is specified in dictionary object if multiple values allowed is specified in dictionary object, property of the request body.
- **children** (*list*) – In case type is andBlock or orBlock additional conditions will be aggregated under this logical (OR/AND) condition, property of the request body (list of objects).
- **condition_type** (*string*) – Indicates whether the record is the condition itself(data) or a logical(or,and) aggregation Data type enum(reference,single) indicates than “conditionId” OR “ConditionAttrs” fields should contain condition data but not both Logical aggregation(and,or) enum indicates that additional conditions are present under the children

field, property of the request body. Available values are 'ConditionAndBlock', 'ConditionAttributes', 'ConditionOrBlock', 'ConditionReference', 'LibraryConditionAndBlock', 'LibraryConditionAttributes', 'LibraryConditionOrBlock' and 'TimeAndDateCondition'.

- **dates_range** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **dates_range_exception** (*object*) – Defines for which date/s TimeAndDate condition will be matched Options are Date range, for specific date, the same date should be used for start/end date Default no specific dates In order to reset the dates to have no specific dates Date format yyyy- mm-dd (MM = month, dd = day, yyyy = year), property of the request body.
- **description** (*string*) – Condition description, property of the request body.
- **dictionary_name** (*string*) – Dictionary name, property of the request body.
- **dictionary_value** (*string*) – Dictionary value, property of the request body.
- **hours_range** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **hours_range_exception** (*object*) – Defines for which hours a TimeAndDate condition will be matched Time format hh:mm (h = hour , mm = minutes) Default All Day , property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_negate** (*boolean*) – Indicates whereas this condition is in negate mode, property of the request body.
- **link** (*object*) – link, property of the request body.
- **name** (*string*) – Condition name, property of the request body.
- **operator** (*string*) – Equality operator, property of the request body. Available values are 'contains', 'endsWith', 'equals', 'greaterOrEquals', 'greaterThan', 'in', 'ipEquals', 'ipGreaterThan', 'ipLessThan', 'ipNotEquals', 'lessOrEquals', 'lessThan', 'matches', 'notContains', 'notEndsWith', 'notEquals', 'notIn', 'notStartsWith' and 'startsWith'.
- **week_days** (*list*) – Defines for which days this condition will be matched Days format Arrays of WeekDay enums Default List of All week days, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **week_days_exception** (*list*) – Defines for which days this condition will NOT be matched Days format Arrays of WeekDay enums Default Not enabled, property of the request body (list of strings. Available values are 'Friday', 'Monday', 'Saturday', 'Sunday', 'Thursday', 'Tuesday' and 'Wednesday').
- **id** – id path parameter. Condition id.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`update_by_id`(*id*, *attribute_name=None*, *attribute_value=None*, *children=None*, *condition_type=None*, *dates_range=None*, *dates_range_exception=None*, *description=None*, *dictionary_name=None*, *dictionary_value=None*, *hours_range=None*, *hours_range_exception=None*, *is_negate=None*, *link=None*, *name=None*, *operator=None*, *week_days=None*, *week_days_exception=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_access_time_condition_by_id*

`delete_network_access_time_condition_by_id`(*id*, *headers=None*, ***query_parameters*)

Network Access Delete Time/Date condition.

Parameters

- **`id`** (*basestring*) – id path parameter. Condition id.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id`(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_access_time_condition_by_id*

network_device

class NetworkDevice

Identity Services Engine NetworkDevice API (version: 3.1.0).

Wraps the Identity Services Engine NetworkDevice API and exposes the API as native Python methods that return native Python objects.

get_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_name*

update_network_device_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by name.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.

- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*string*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *id=None*, *model_name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_name*

delete_network_device_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a network device by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_by_name*

get_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_network_device_by_id*

update_network_device_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*,
dtls_dns_name=None, *model_name=None*, *name=None*,
network_device_group_list=None, *network_device_ip_list=None*,
profile_name=None, *snmpsettings=None*, *software_version=None*,
tacacs_settings=None, *trustsecsettings=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

This API allows the client to update a network device by ID.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).
- **network_device_ip_list** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *authentication_settings=None*, *coa_port=None*, *description=None*, *dtls_dns_name=None*, *model_name=None*, *name=None*, *network_device_group_list=None*, *network_device_ip_list=None*, *profile_name=None*, *snmpsettings=None*, *software_version=None*, *tacacs_settings=None*, *trustsecsettings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_by_id*

delete_network_device_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_network_device_by_id*

get_network_device(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device*

get_network_device_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network devices. Filter: [ipaddress, name, description, location, type] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_generator*

create_network_device(*authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None, model_name=None, name=None, network_device_group_list=None, network_device_ip_list=None, profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None, trustsecsettings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device.

Parameters

- **network_device_group_list** (*list*) – List of Network Device Group names for this node, property of the request body (list of strings).

- **network_device_iplist** (*list*) – List of IP Subnets for this node, property of the request body (list of objects).
- **authentication_settings** (*object*) – authenticationSettings, property of the request body.
- **coa_port** (*integer*) – coaPort, property of the request body.
- **description** (*string*) – description, property of the request body.
- **dtls_dns_name** (*string*) – This value is used to verify the client identity contained in the X.509 RADIUS/DTLS client certificate, property of the request body.
- **model_name** (*string*) – modelName, property of the request body.
- **name** (*string*) – name, property of the request body.
- **profile_name** (*string*) – profileName, property of the request body.
- **snmpsettings** (*object*) – snmpsettings, property of the request body.
- **software_version** (*string*) – softwareVersion, property of the request body.
- **tacacs_settings** (*object*) – tacacsSettings, property of the request body.
- **trustsecsettings** (*object*) – trustsecsettings, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(authentication_settings=None, coa_port=None, description=None, dtls_dns_name=None,  
        model_name=None, name=None, network_device_group_list=None, network_device_iplist=None,  
        profile_name=None, snmpsettings=None, software_version=None, tacacs_settings=None,  
        trustsecsettings=None, headers=None, payload=None, active_validation=True,  
        **query_parameters)
```

Alias for *create_network_device*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the network device.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_network_device(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_network_device*

monitor_bulk_status_network_device(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_network_device*

network_device_group

class NetworkDeviceGroup

Identity Services Engine NetworkDeviceGroup API (version: 3.1.0).

Wraps the Identity Services Engine NetworkDeviceGroup API and exposes the API as native Python methods that return native Python objects.

get_network_device_group_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get a network device group by name.

Parameters

- **name** (*basestring*) – name path parameter. colon is used as a separator instead of (#) in the NDG name. For example, if the name is a#b#c it should appear in the request URL as a:b:c.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name(name, headers=None, **query_parameters)`

Alias for *`get_network_device_group_by_name`*

`get_network_device_group_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a network device group by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_network_device_group_by_id`*

`update_network_device_group_by_id(id, description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse***Raises**

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *othername=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_network_device_group_by_id*

delete_network_device_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a network device group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_network_device_group_by_id`

`get_network_device_group(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group*

get_network_device_group_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the network device groups. Filter: [name, description, type] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- RestResponse: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_network_device_group_generator*

create_network_device_group(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a network device group.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **othername** (*string*) – othername, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, othername=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_network_device_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the network device group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_deployment

class NodeDeployment

Identity Services Engine Node Deployment API (version: 3.1.0).

Wraps the Identity Services Engine Node Deployment API and exposes the API as native Python methods that return native Python objects.

get_nodes(*headers=None, **query_parameters*)

Discovers all deployment nodes in the cluster. It provides basic information about each of deployed nodes in the cluster like Hostname, personas, status, roles and services. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

register_node(*administration=None, fdqn=None, general_settings=None, password=None, profile_configuration=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Register ISE node to form a multi-node deployment .

Parameters

- **administration** (*object*) – administration, property of the request body.
- **fdqn** (*string*) – fdqn, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **general_settings** (*object*) – generalSettings, property of the request body.
- **password** (*string*) – password, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **user_name** (*string*) – userName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

promote_node(*promotion_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Changes the cluster setting by promoting a node to primary when executed on standalone or secondary node. It could also be used to convert a deployment node to standalone node. .

Parameters

- **promotion_type** (*string*) – promotionType, property of the request body. Available values are 'SECONDARY_TO_PRIMARY', 'STANDALONE_TO_PRIMARY' and 'TO_STANDALONE'.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_details(*hostname*, *headers=None*, ***query_parameters*)

It provides detailed information of the deployed node in the cluster. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*hostname*, *headers=None*, ***query_parameters*)

Alias for *get_node_details*

update_node(*hostname*, *general_settings=None*, *profile_configuration=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Updates the deployed ISE node with the information provided .

Parameters

- **general_settings** (*object*) – generalSettings, property of the request body.
- **profile_configuration** (*object*) – profileConfiguration, property of the request body.
- **hostname** (*basestring*) – hostname path parameter. ID of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node(hostname, headers=None, **query_parameters)

The de-register ednode becomes a standalone Cisco ISE node. It retains the last configuration that it received from the PrimaryPAN and assumes the default personas of a standalone node that are Administration, PolicyService, and Monitoring. .

Parameters

- **hostname** (*basestring*) – hostname path parameter. node name of the existing deployed node.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

node_group**class NodeGroup**

Identity Services Engine Node Group API (version: 3.1.0).

Wraps the Identity Services Engine Node Group API and exposes the API as native Python methods that return native Python objects.

get_node_groups(*headers=None, **query_parameters*)

Get details of all the node groups in the cluster. To detect node failure and to reset all URL-redirceted sessions on the failed node, two or more Policy Service nodes can be placed in the same node group. When a node that belongs to a node group fails, another node in the same node group issues a Change of Authorization (CoA) for all URL-redirceted sessions on the failed node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_node_group(*node_group_name, headers=None, **query_parameters*)

Get details of a node group in the cluster.

Parameters

- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create_node_group(*node_group_name, description=None, mar_cache=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Developers need to create node group in the system. Node Group is a group of PSNs, mainly used for terminating posture pending sessions when a PSN in local node group fails. Node group members can communicate over TCP/7800.

Parameters

- **description** (*string*) – description, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **mar_cache** (*object*) – mar-cache, property of the request body.
- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_node_group(*node_group_name*, *description=None*, *mar_cache=None*, *headers=None*,
payload=None, *active_validation=True*, ***query_parameters*)

API updates an existing node group in the system.

Parameters

- **description** (*string*) – description, property of the request body. Constraints: maxLength set to 256 and minLength set to 1.
- **mar_cache** (*object*) – mar-cache, property of the request body.
- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_node_group(*node_group_name*, *headers=None*, ***query_parameters*)

Developers need to delete node group in the system.

Parameters

- **node_group_name** (*basestring*) – node-group-name path parameter. ID of the existing node group.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

node_details

class NodeDetails

Identity Services Engine NodeDetails API (version: 3.1.0).

Wraps the Identity Services Engine NodeDetails API and exposes the API as native Python methods that return native Python objects.

`get_node_detail_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_name`(*name*, *headers=None*, ***query_parameters*)

Alias for `get_node_detail_by_name`

`get_node_detail_by_id`(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_node_detail_by_id*

get_node_details(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_node_details*

get_node_details_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the node details. Filter: [nodeservice-types] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page(int)** – page query parameter. Page number.
- **size(int)** – size query parameter. Number of objects returned per page.
- **filter(basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type(basestring)** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- `TypeError` – If the parameter types are incorrect.
- `MalformedRequest` – If the request body created is invalid.
- `ApiError` – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for `get_node_details_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the node details.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- `TypeError` – If the parameter types are incorrect.
- `MalformedRequest` – If the request body created is invalid.
- `ApiError` – If the Identity Services Engine cloud returns an error.

pan_ha

class PanHa

Identity Services Engine PAN HA API (version: 3.1.0).

Wraps the Identity Services Engine PAN HA API and exposes the API as native Python methods that return native Python objects.

get_pan_ha_status(*headers=None, **query_parameters*)

In a high availability configuration, the Primary Administration Node (PAN) is in the active state. The Secondary PAN (backup PAN) is in the standby state, which means it receives all configuration updates from the Primary PAN, but is not active in the ISE network. You can configure ISE to automatically promote the secondary PAN when the primary PAN becomes unavailable.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

enable_pan_ha(*failed_attempts=None, is_enabled=None, polling_interval=None, primary_health_check_node=None, secondary_health_check_node=None, headers=None, payload=None, active_validation=True, **query_parameters*)

To deploy the auto-failover feature, you must have at least three nodes, where two of the nodes assume the Administration persona, and one node acts as the health check node. A health check node is a non-administration node and can be a Policy Service, Monitoring, or pxGrid node, or a combination of these. If the PANs are in different data centers, you must have a health check node for each PAN.

Parameters

- **failed_attempts** (*integer*) – failedAttempts, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **polling_interval** (*integer*) – pollingInterval, property of the request body.
- **primary_health_check_node** (*string*) – primaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **secondary_health_check_node** (*string*) – secondaryHealthCheckNode, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

disable_pan_ha(*headers=None, **query_parameters*)

Disable the automatic PAN failover.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

portal_global_setting

class PortalGlobalSetting

Identity Services Engine PortalGlobalSetting API (version: 3.1.0).

Wraps the Identity Services Engine PortalGlobalSetting API and exposes the API as native Python methods that return native Python objects.

get_portal_global_setting_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get the portal global settings by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_global_setting_by_id*

update_portal_global_setting_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update the portal global settings by id.

Parameters

- **customization** (*string*) – Allowed values: HTML, HTMLANDJAVASCRIPT, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customization=None*, *headers=None*, *payload=None*, *active_validation=True*,
 ***query_parameters*)

Alias for *update_portal_global_setting_by_id*

get_portal_global_settings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*,
 sortdsc=None, *headers=None*, ***query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_global_settings*

`get_portal_global_settings_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal global settings. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_portal_global_settings_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal global setting .

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

portal_theme

class PortalTheme

Identity Services Engine PortalTheme API (version: 3.1.0).

Wraps the Identity Services Engine PortalTheme API and exposes the API as native Python methods that return native Python objects.

get_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_theme_by_id*

update_portal_theme_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a portal theme by ID.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *theme_data=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_portal_theme_by_id*

delete_portal_theme_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a portal theme by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_portal_theme_by_id*

get_portal_themes(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes*

get_portal_themes_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the portal themes. Filter: [name] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portal_themes_generator*

create_portal_theme(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a portal theme.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **theme_data** (*string*) – Portal Theme for all portals, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, theme_data=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_portal_theme*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the portal theme.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler

class Profiler

Identity Services Engine Profiler API (version: 3.1.0).

Wraps the Identity Services Engine Profiler API and exposes the API as native Python methods that return native Python objects.

`get_profiles(headers=None, **query_parameters)`
getProfiles.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

profiler_profile

class ProfilerProfile

Identity Services Engine ProfilerProfile API (version: 3.1.0).

Wraps the Identity Services Engine ProfilerProfile API and exposes the API as native Python methods that return native Python objects.

get_profiler_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a profiler profile by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profile_by_id*

get_profiler_profiles(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_profiler_profiles*

get_profiler_profiles_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the profiler profiles. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_profiler_profiles_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the profiler profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request’s response
- **text(str)**: representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

provider

class Provider

Identity Services Engine Provider API (version: 3.1.0).

Wraps the Identity Services Engine Provider API and exposes the API as native Python methods that return native Python objects.

register_service(*name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

ServiceRegister.

Parameters

- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

unregister_service(*headers=None, **query_parameters*)

ServiceUnregister.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

reregister_service(*headers=None, **query_parameters*)
ServiceReregister.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

authorization(*headers=None, **query_parameters*)
Authorization.

Parameters

- **headers(dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

psn_node_details_with_radius_service**class PsnNodeDetailsWithRadiusService**

Identity Services Engine PsnNodeDetailsWithRadiusService API (version: 3.1.0).

Wraps the Identity Services Engine PsnNodeDetailsWithRadiusService API and exposes the API as native Python methods that return native Python objects.

`get_session_service_node_by_name`(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_name*

get_session_service_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a PSN node details by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_session_service_node_by_id*

get_session_service_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node*

get_session_service_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the PSN node details.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_session_service_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the PSN node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

pull_deployment_info

class PullDeploymentInfo

Identity Services Engine PullDeploymentInfo API (version: 3.1.0).

Wraps the Identity Services Engine PullDeploymentInfo API and exposes the API as native Python methods that return native Python objects.

get_deployment_info(*timeout=None, headers=None, **query_parameters*)

This API allows the client to pull the deployment information.

Parameters

- **`timeout`** (*float, tuple*) – How long to wait for the server to send data before giving up.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_all(*timeout=None, headers=None, **query_parameters*)

Alias for *get_deployment_info*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pull deployment info.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_settings**class PxGridSettings**

Identity Services Engine PxGridSettings API (version: 3.1.0).

Wraps the Identity Services Engine PxGridSettings API and exposes the API as native Python methods that return native Python objects.

```
autoapprove_px_grid_settings(allow_password_based_accounts=None,  
                               auto_approve_cert_based_accounts=None, headers=None,  
                               payload=None, active_validation=True, **query_parameters)
```

This API allows the client to auto approve the pxGrid settings.

Parameters

- **allow_password_based_accounts** (*boolean*) – Allow password based accounts when true, property of the request body.
- **auto_approve_cert_based_accounts** (*boolean*) – Auto approve certificate based accounts when true, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`autoapprove`(*allow_password_based_accounts=None, auto_approve_cert_based_accounts=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *autoapprove_px_grid_settings*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid settings.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

radius_failure

class RadiusFailure

Identity Services Engine RADIUS Failure API (version: 3.1.0).

Wraps the Identity Services Engine RADIUS Failure API and exposes the API as native Python methods that return native Python objects.

`get_failures`(*headers=None, **query_parameters*)
getFailures.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

radius_server_sequence

class RadiusServerSequence

Identity Services Engine RADIUSServerSequence API (version: 3.1.0).

Wraps the Identity Services Engine RADIUSServerSequence API and exposes the API as native Python methods that return native Python objects.

get_radius_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a RADIUS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence_by_id*

update_radius_server_sequence_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a RADIUS server sequence.

Parameters

- **before_accept_attr_manipulators_list** (*list*) – The beforeAcceptAttrManipulators is required only if useAttrSetBeforeAcc is true, property of the request body (list of objects).
- **on_request_attr_manipulator_list** (*list*) – The onRequestAttrManipulators is required only if useAttrSetOnRequest is true, property of the request body (list of objects).
- **radius_server_list** (*list*) – RadiusServerList, property of the request body (list of strings).
- **continue_authorz_policy** (*boolean*) – continueAuthorzPolicy, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_separator** (*string*) – The prefixSeparator is required only if stripPrefix is true. The maximum length is 1 character, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **strip_prefix** (*boolean*) – stripPrefix, property of the request body.
- **strip_suffix** (*boolean*) – stripSuffix, property of the request body.
- **suffix_separator** (*string*) – The suffixSeparator is required only if stripSuffix is true. The maximum length is 1 character, property of the request body.
- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.

- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *before_accept_attr_manipulators_list=None*, *continue_authorz_policy=None*, *description=None*, *local_accounting=None*, *name=None*, *on_request_attr_manipulator_list=None*, *prefix_separator=None*, *radius_server_list=None*, *remote_accounting=None*, *strip_prefix=None*, *strip_suffix=None*, *suffix_separator=None*, *use_attr_set_before_acc=None*, *use_attr_set_on_request=None*, *headers=None*, *payload=None*, *active_validation=True*, ****query_parameters**)

Alias for *update_radius_server_sequence_by_id*

delete_radius_server_sequence_by_id(*id*, *headers=None*, ****query_parameters**)

This API deletes a RADIUS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_radius_server_sequence_by_id*

get_radius_server_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_radius_server_sequence*

get_radius_server_sequence_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the RADIUS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for `get_radius_server_sequence_generator`

`create_radius_server_sequence`(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a RADIUS server sequence.

Parameters

- **`before_accept_attr_manipulators_list`** (*list*) – The `beforeAcceptAttrManipulators` is required only if `useAttrSetBeforeAcc` is true, property of the request body (list of objects).
- **`on_request_attr_manipulator_list`** (*list*) – The `onRequestAttrManipulators` is required only if `useAttrSetOnRequest` is true, property of the request body (list of objects).
- **`radius_server_list`** (*list*) – `RadiusServerList`, property of the request body (list of strings).
- **`continue_authorz_policy`** (*boolean*) – `continueAuthorzPolicy`, property of the request body.
- **`description`** (*string*) – `description`, property of the request body.
- **`local_accounting`** (*boolean*) – `localAccounting`, property of the request body.
- **`name`** (*string*) – `name`, property of the request body.
- **`prefix_separator`** (*string*) – The `prefixSeparator` is required only if `stripPrefix` is true. The maximum length is 1 character, property of the request body.
- **`remote_accounting`** (*boolean*) – `remoteAccounting`, property of the request body.
- **`strip_prefix`** (*boolean*) – `stripPrefix`, property of the request body.
- **`strip_suffix`** (*boolean*) – `stripSuffix`, property of the request body.
- **`suffix_separator`** (*string*) – The `suffixSeparator` is required only if `stripSuffix` is true. The maximum length is 1 character, property of the request body.

- **use_attr_set_before_acc** (*boolean*) – useAttrSetBeforeAcc, property of the request body.
- **use_attr_set_on_request** (*boolean*) – useAttrSetOnRequest, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*before_accept_attr_manipulators_list=None, continue_authorz_policy=None, description=None, local_accounting=None, name=None, on_request_attr_manipulator_list=None, prefix_separator=None, radius_server_list=None, remote_accounting=None, strip_prefix=None, strip_suffix=None, suffix_separator=None, use_attr_set_before_acc=None, use_attr_set_on_request=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_radius_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the RADIUS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

restid_store

class RestidStore

Identity Services Engine RESTIDStore API (version: 3.1.0).

Wraps the Identity Services Engine RESTIDStore API and exposes the API as native Python methods that return native Python objects.

get_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by name.

Parameters

- **`name`** (*basestring*) – name path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_name*

update_rest_id_store_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store by name.

Parameters

- **`description`** (*string*) – description, property of the request body.

- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*basestring*) – name, property of the request body.
- **name** – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *description=None*, *ers_rest_idstore_attributes=None*, *id=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_name*

delete_rest_id_store_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_name*

get_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a REST ID store by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_rest_id_store_by_id*

update_rest_id_store_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *ers_rest_idstore_attributes=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_rest_id_store_by_id*

delete_rest_id_store_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a REST ID store.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_rest_id_store_by_id*

get_rest_id_store(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
 Alias for *get_rest_id_store*

get_rest_id_store_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the REST ID stores. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_rest_id_store_generator*

create_rest_id_store(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a REST ID store.

Parameters

- **description** (*string*) – description, property of the request body.
- **ers_rest_idstore_attributes** (*object*) – ersRestIDStoreAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, ers_rest_idstore_attributes=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_rest_id_store*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the REST ID store.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

replication_status

class ReplicationStatus

Identity Services Engine Replication Status API (version: 3.1.0).

Wraps the Identity Services Engine Replication Status API and exposes the API as native Python methods that return native Python objects.

`get_node_replication_status`(*node*, *headers=None*, ***query_parameters*)

Retrives replication status of a node.

Parameters

- **`node`** (*basestring*) – node path parameter. ID of the existing node.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

repository

class Repository

Identity Services Engine Repository API (version: 3.1.0).

Wraps the Identity Services Engine Repository API and exposes the API as native Python methods that return native Python objects.

get_repositories(*headers=None, **query_parameters*)

This will get the full list of repository definitions on the system. .

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_repositories*

create_repository(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create a new repository in the system. The name provided for the repository must be unique. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*string*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.

- **user_name** (*string*) – Username may contain alphanumeric and `_./@$` characters., property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*enable_pki=None, name=None, password=None, path=None, protocol=None, server_name=None, user_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_repository*

get_repository(*name, headers=None, **query_parameters*)
Get a specific repository identified by the name passed in the URL. .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_repository*

update_repository(*name*, *enable_pki=None*, *password=None*, *path=None*, *protocol=None*,
server_name=None, *user_name=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Update the definition of a specific repository, providing ALL parameters for the repository. .

Parameters

- **enable_pki** (*boolean*) – enablePki, property of the request body.
- **name** (*basestring*) – Repository name should be less than 80 characters and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **password** (*string*) – Password can contain alphanumeric and/or special characters., property of the request body.
- **path** (*string*) – Path should always start with “/” and can contain alphanumeric, underscore, hyphen and dot characters., property of the request body.
- **protocol** (*string*) – protocol, property of the request body. Available values are ‘CDROM’, ‘DISK’, ‘FTP’, ‘HTTP’, ‘HTTPS’, ‘NFS’, ‘SFTP’ and ‘TFTP’.
- **server_name** (*string*) – serverName, property of the request body.
- **user_name** (*string*) – Username may contain alphanumeric and _./@\$ characters., property of the request body.
- **name** – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_name(*name*, *enable_pki=None*, *password=None*, *path=None*, *protocol=None*,
server_name=None, *user_name=None*, *headers=None*, *payload=None*,
active_validation=True, ***query_parameters*)

Alias for *update_repository*

delete_repository(*name*, *headers=None*, ***query_parameters*)

Long description TBD .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_repository*

get_repository_files(*name*, *headers=None*, ***query_parameters*)

This will get the full list of files present in the named repository. .

Parameters

- **name** (*basestring*) – name path parameter. Unique name for a repository.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_files(*name*, *headers=None*, ***query_parameters*)

Alias for *get_repository_files*

sms_provider

class SmsProvider

Identity Services Engine SMSProvider API (version: 3.1.0).

Wraps the Identity Services Engine SMSProvider API and exposes the API as native Python methods that return native Python objects.

get_sms_provider(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)
Alias for *get_sms_provider*

`get_sms_provider_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SMS providers. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sortasc`** (*basestring*) – sortasc query parameter. sort asc.
- **`sortdsc`** (*basestring*) – sortdsc query parameter. sort desc.
- **`filter`** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `Generator`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for `get_sms_provider_generator`

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SMS provider.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type `RestResponse`

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

sxp_connections

class `SxpConnections`

Identity Services Engine SXPConnections API (version: 3.1.0).

Wraps the Identity Services Engine SXPConnections API and exposes the API as native Python methods that return native Python objects.

`get_sxp_connections_by_id`(*id, headers=None, **query_parameters*)

This API allows the client to get a SXP connection by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_connections_by_id*

update_sxp_connections_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *enabled=None*, *ip_address=None*, *sxp_mode=None*, *sxp_node=None*, *sxp_peer=None*, *sxp_version=None*, *sxp_vpn=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_connections_by_id*

delete_sxp_connections_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP connection.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_connections_by_id*

get_sxp_connections(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections*

get_sxp_connections_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP connections. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_connections_generator*

```
create_sxp_connections(description=None, enabled=None, ip_address=None, sxp_mode=None,
                        sxp_node=None, sxp_peer=None, sxp_version=None, sxp_vpn=None,
                        headers=None, payload=None, active_validation=True, **query_parameters)
```

This API creates a SXP connection.

Parameters

- **description** (*string*) – description, property of the request body.
- **enabled** (*boolean*) – enabled, property of the request body.
- **ip_address** (*string*) – ipAddress, property of the request body.
- **sxp_mode** (*string*) – sxpMode, property of the request body.
- **sxp_node** (*string*) – sxpNode, property of the request body.
- **sxp_peer** (*string*) – sxpPeer, property of the request body.
- **sxp_version** (*string*) – sxpVersion, property of the request body.
- **sxp_vpn** (*string*) – sxpVpn, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, enabled=None, ip_address=None, sxp_mode=None, sxp_node=None,
       sxp_peer=None, sxp_version=None, sxp_vpn=None, headers=None, payload=None,
       active_validation=True, **query_parameters)
```

Alias for *create_sxp_connections*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the SXP connections.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_sxp_connections(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type (string)** – operationType, property of the request body.
- **resource_media_type (string)** – resourceMediaType, property of the request body.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- **payload (dict)** – A JSON serializable Python object to send in the body of the Request.
- **active_validation (bool)** – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_connections*

monitor_bulk_status_sxp_connections(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_connections*

sxp_local_bindings

class SxpLocalBindings

Identity Services Engine SXPLocalBindings API (version: 3.1.0).

Wraps the Identity Services Engine SXPLocalBindings API and exposes the API as native Python methods that return native Python objects.

get_sxp_local_bindings_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a SXP local binding by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for `get_sxp_local_bindings_by_id`

`update_sxp_local_bindings_by_id(id, binding_name=None, description=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a SXP local binding.

Parameters

- **`binding_name (string)`** – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`id (basestring)`** – id, property of the request body.
- **`ip_address_or_host (string)`** – IP address for static mapping (hostname is not supported), property of the request body.
- **`sgt (string)`** – SGT name or ID, property of the request body.
- **`sxp_vpn (string)`** – List of SXP Domains, separated with comma. At least one of: `sxpVpn` or `vns` should be defined, property of the request body.
- **`vns (string)`** – List of Virtual Networks, separated with comma. At least one of: `sxpVpn` or `vns` should be defined, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *binding_name=None*, *description=None*, *ip_address_or_host=None*, *sgt=None*, *sxp_vpn=None*, *vns=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sxp_local_bindings_by_id*

delete_sxp_local_bindings_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP local binding.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_local_bindings_by_id*

get_sxp_local_bindings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings*

get_sxp_local_bindings_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP local bindings. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.

- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_local_bindings_generator*

create_sxp_local_bindings(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP local binding.

Parameters

- **binding_name** (*string*) – This field is deprecated from Cisco ISE 3.0, property of the request body.
- **description** (*string*) – description, property of the request body.

- **id** (*string*) – id, property of the request body.
- **ip_address_or_host** (*string*) – IP address for static mapping (hostname is not supported), property of the request body.
- **sgt** (*string*) – SGT name or ID, property of the request body.
- **sxp_vpn** (*string*) – List of SXP Domains, separated with comma. At least one of: `sxpVpn` or `vns` should be defined, property of the request body.
- **vns** (*string*) – List of Virtual Networks, separated with comma. At least one of: `sxpVpn` or `vns` should be defined, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*binding_name=None, description=None, id=None, ip_address_or_host=None, sgt=None, sxp_vpn=None, vns=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_sxp_local_bindings*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the SXP local bindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_local_bindings`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_sxp_local_bindings`*

`monitor_bulk_status_sxp_local_bindings`(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **`bulkid`** (*basestring*) – `bulkid` path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_sxp_local_bindings*

sxp_vpns

class SxpVpns

Identity Services Engine SXPVPNs API (version: 3.1.0).

Wraps the Identity Services Engine SXPVPNs API and exposes the API as native Python methods that return native Python objects.

get_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a SXP VPN by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sxp_vpn_by_id*

delete_sxp_vpn_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a SXP VPN.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sxp_vpn_by_id*

get_sxp_vpns(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns*

get_sxp_vpns_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the SXP VPNs. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW:

Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sxp_vpns_generator*

create_sxp_vpn(*sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a SXP VPN.

Parameters

- **sxp_vpn_name** (*string*) – sxpVpnName, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create(sxp_vpn_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`
Alias for `create_sxp_vpn`

`get_version(headers=None, **query_parameters)`

This API helps to retrieve the version information related to the SXP VPNs.

Parameters

- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_sxp_vpns(operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to submit the bulk request.

Parameters

- **`operation_type(string)`** – operationType, property of the request body.
- **`resource_media_type(string)`** – resourceMediaType, property of the request body.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_sxp_vpns*

monitor_bulk_status_sxp_vpns(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid, headers=None, **query_parameters*)

Alias for *monitor_bulk_status_sxp_vpns*

security_group_to_virtual_network

class SecurityGroupToVirtualNetwork

Identity Services Engine SecurityGroupToVirtualNetwork API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroupToVirtualNetwork API and exposes the API as native Python methods that return native Python objects.

get_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group to virtual network by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_by_id*

update_security_groups_to_vn_to_vlan_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **id** – id path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *sgt_id=None*, *virtualnetworklist=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_groups_to_vn_to_vlan_by_id*

delete_security_groups_to_vn_to_vlan_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group ACL to virtual network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_to_vn_to_vlan_by_id*

get_security_groups_to_vn_to_vlan(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan*

get_security_groups_to_vn_to_vlan_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACL to virtual networks. Filter: [sgtId] To search guest users by using toDate column, follow the format: DD- MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_security_groups_to_vn_to_vlan_generator*

```
create_security_groups_to_vn_to_vlan(description=None, id=None, name=None, sgt_id=None,  
                                     virtualnetworklist=None, headers=None, payload=None,  
                                     active_validation=True, **query_parameters)
```

This API creates a security group to virtual network.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **sgt_id** (*string*) – sgtId, property of the request body.
- **virtualnetworklist** (*list*) – virtualnetworklist, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(description=None, id=None, name=None, sgt_id=None, virtualnetworklist=None, headers=None,  
       payload=None, active_validation=True, **query_parameters)
```

Alias for *create_security_groups_to_vn_to_vlan*

```
get_version(headers=None, **query_parameters)
```

This API helps to retrieve the version information related to the security group to virtual network.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_groups_to_vn_to_vlan`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type`** (*string*) – `operationType`, property of the request body.
- **`resource_media_type`** (*string*) – `resourceMediaType`, property of the request body.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_request_for_security_groups_to_vn_to_vlan`*

monitor_bulk_status_security_groups_to_vn_to_vlan(*bulkid*, *headers=None*, ***query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_groups_to_vn_to_vlan*

security_groups

class SecurityGroups

Identity Services Engine SecurityGroups API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroups API and exposes the API as native Python methods that return native Python objects.

get_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_group_by_id*

update_security_group_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACLs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propagate_to_apic** (*boolean*) – propagateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 or 65519 or -1 to auto- generate, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *default_sgacIs=None*, *description=None*, *generation_id=None*, *is_read_only=None*, *name=None*, *propagate_to_apic=None*, *value=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_security_group_by_id*

delete_security_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a security group.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_group_by_id*

get_security_groups(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups*

get_security_groups_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security groups. Filter: [propagateToApic, name, description, value] To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description, value].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_generator*

create_security_group(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propogate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group.

Parameters

- **default_sgacIs** (*list*) – defaultSGACLs, property of the request body (list of objects).
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **name** (*string*) – name, property of the request body.
- **propogate_to_apic** (*boolean*) – propogateToApic, property of the request body.
- **value** (*integer*) – Value range: 2 ot 65519 or -1 to auto- generate, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*default_sgacIs=None, description=None, generation_id=None, is_read_only=None, name=None, propagate_to_apic=None, value=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security groups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_security_group(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_group*

monitor_bulk_status_security_group(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_group*

security_groups_acls

class SecurityGroupsAcls

Identity Services Engine SecurityGroupsACLs API (version: 3.1.0).

Wraps the Identity Services Engine SecurityGroupsACLs API and exposes the API as native Python methods that return native Python objects.

get_security_groups_acl_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a security group ACL by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_security_groups_acl_by_id*

```
update_security_groups_acl_by_id(id, aclcontent=None, description=None, generation_id=None,
                                ip_version=None, is_read_only=None, modelled_content=None,
                                name=None, headers=None, payload=None,
                                active_validation=True, **query_parameters)
```

This API allows the client to update a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, aclcontent=None, description=None, generation_id=None, ip_version=None,
             is_read_only=None, modelled_content=None, name=None, headers=None, payload=None,
             active_validation=True, **query_parameters)
```

Alias for *update_security_groups_acl_by_id*

```
delete_security_groups_acl_by_id(id, headers=None, **query_parameters)
```

This API deletes a security group ACL.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_security_groups_acl_by_id*

get_security_groups_acl(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl*

get_security_groups_acl_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the security group ACLs. Filter: [ipVersion, name, description] To search guest users by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [ipVersion, name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request's response
 - **text(str)**: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_security_groups_acl_generator*

create_security_groups_acl(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a security group ACL.

Parameters

- **aclcontent** (*string*) – aclcontent, property of the request body.
- **description** (*string*) – description, property of the request body.
- **generation_id** (*string*) – generationId, property of the request body.
- **ip_version** (*string*) – Allowed values: IPV4, IPV6, IP_AGNOSTIC, property of the request body.
- **is_read_only** (*boolean*) – isReadOnly, property of the request body.
- **modelled_content** (*object*) – Modelled content of contract, property of the request body.
- **name** (*string*) – name, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`create`(*aclcontent=None, description=None, generation_id=None, ip_version=None, is_read_only=None, modelled_content=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_security_groups_acl*

`get_version`(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the security group ACLs.

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_for_security_groups_acl`(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **`operation_type (string)`** – `operationType`, property of the request body.
- **`resource_media_type (string)`** – `resourceMediaType`, property of the request body.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_security_groups_acl*

monitor_bulk_status_security_groups_acl(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

monitor_bulk_status(*bulkid*, *headers=None*, ***query_parameters*)

Alias for *monitor_bulk_status_security_groups_acl*

self_registered_portal

class SelfRegisteredPortal

Identity Services Engine SelfRegisteredPortal API (version: 3.1.0).

Wraps the Identity Services Engine SelfRegisteredPortal API and exposes the API as native Python methods that return native Python objects.

get_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_self_registered_portal_by_id*

update_self_registered_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a self registered portal by ID.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.

- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_self_registered_portal_by_id*

delete_self_registered_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a self registered portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_self_registered_portal_by_id`*

`get_self_registered_portals(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_self_registered_portals*

get_self_registered_portals_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the self registered portals. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type Generator

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *`get_self_registered_portals_generator`*

`create_self_registered_portal`(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a self registered portal.

Parameters

- **`customizations (object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description (string)`** – description, property of the request body.
- **`name (string)`** – name, property of the request body.
- **`portal_test_url (string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type (string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings (object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *`RestResponse`*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_self_registered_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the self registered portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

session_directory

class SessionDirectory

Identity Services Engine Session Directory API (version: 3.1.0).

Wraps the Identity Services Engine Session Directory API and exposes the API as native Python methods that return native Python objects.

get_sessions(*headers=None, **query_parameters*)
getSessions.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_sessions_for_recovery`(*headers=None, **query_parameters*)
`getSessionsForRecovery.`

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_session_by_ip_address`(*headers=None, **query_parameters*)
`getSessionByIpAddress.`

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_session_by_mac_address(headers=None, **query_parameters)`
`getSessionByMacAddress.`

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_user_groups(headers=None, **query_parameters)`
`getUserGroups.`

Parameters

- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_user_group_by_user_name(*headers=None, **query_parameters*)
getUserGroupByUserName.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*headers=None, **query_parameters*)
Alias for *get_user_group_by_user_name*

sponsor_group

class SponsorGroup

Identity Services Engine SponsorGroup API (version: 3.1.0).

Wraps the Identity Services Engine SponsorGroup API and exposes the API as native Python methods that return native Python objects.

get_sponsor_group_by_id(*id, headers=None, **query_parameters*)
This API allows the client to get a sponsor group by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_sponsor_group_by_id`*

`update_sponsor_group_by_id(id, auto_notification=None, create_permissions=None, description=None, guest_types=None, is_default_group=None, is_enabled=None, locations=None, manage_permission=None, member_groups=None, name=None, other_permissions=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsor group by ID.

Parameters

- **`auto_notification`** (*boolean*) – `autoNotification`, property of the request body.
- **`create_permissions`** (*object*) – `createPermissions`, property of the request body.
- **`description`** (*string*) – `description`, property of the request body.
- **`guest_types`** (*list*) – `guestTypes`, property of the request body (list of strings).
- **`id`** (*basestring*) – `id`, property of the request body.
- **`is_default_group`** (*boolean*) – `isDefaultGroup`, property of the request body.
- **`is_enabled`** (*boolean*) – `isEnabled`, property of the request body.
- **`locations`** (*list*) – `locations`, property of the request body (list of strings).
- **`manage_permission`** (*string*) – `managePermission`, property of the request body.
- **`member_groups`** (*list*) – `memberGroups`, property of the request body (list of strings).
- **`name`** (*string*) – `name`, property of the request body.
- **`other_permissions`** (*object*) – `otherPermissions`, property of the request body.
- **`id`** – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *auto_notification=None*, *create_permissions=None*, *description=None*, *guest_types=None*, *is_default_group=None*, *is_enabled=None*, *locations=None*, *manage_permission=None*, *member_groups=None*, *name=None*, *other_permissions=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsor_group_by_id*

delete_sponsor_group_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsor group by ID.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsor_group_by_id*

get_sponsor_group(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
 To search resources by using toDate column, follow the format: DD-MON-YY
 (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
 /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group*

get_sponsor_group_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor groups. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_generator*

```
create_sponsor_group(auto_notification=None, create_permissions=None, description=None,
    guest_types=None, is_default_group=None, is_enabled=None, locations=None,
    manage_permission=None, member_groups=None, name=None,
    other_permissions=None, headers=None, payload=None, active_validation=True,
    **query_parameters)
```

This API creates a sponsor group.

Parameters

- **auto_notification** (*boolean*) – autoNotification, property of the request body.
- **create_permissions** (*object*) – createPermissions, property of the request body.
- **description** (*string*) – description, property of the request body.
- **guest_types** (*list*) – guestTypes, property of the request body (list of strings).
- **is_default_group** (*boolean*) – isDefaultGroup, property of the request body.
- **is_enabled** (*boolean*) – isEnabled, property of the request body.
- **locations** (*list*) – locations, property of the request body (list of strings).
- **manage_permission** (*string*) – managePermission, property of the request body.
- **member_groups** (*list*) – memberGroups, property of the request body (list of strings).
- **name** (*string*) – name, property of the request body.
- **other_permissions** (*object*) – otherPermissions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
create(auto_notification=None, create_permissions=None, description=None, guest_types=None,
    is_default_group=None, is_enabled=None, locations=None, manage_permission=None,
    member_groups=None, name=None, other_permissions=None, headers=None, payload=None,
    active_validation=True, **query_parameters)
```

Alias for *create_sponsor_group*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_group_member

class SponsorGroupMember

Identity Services Engine SponsorGroupMember API (version: 3.1.0).

Wraps the Identity Services Engine SponsorGroupMember API and exposes the API as native Python methods that return native Python objects.

get_sponsor_group_member(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member*

get_sponsor_group_member_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor group members. Filter: [name]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data

model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request's response
 - text(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_group_member_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor group member.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsor_portal

class SponsorPortal

Identity Services Engine SponsorPortal API (version: 3.1.0).

Wraps the Identity Services Engine SponsorPortal API and exposes the API as native Python methods that return native Python objects.

get_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_sponsor_portal_by_id*

update_sponsor_portal_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update a sponsor portal by ID.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.

- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsor_portal_by_id*

delete_sponsor_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsor portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for `delete_sponsor_portal_by_id`

`get_sponsor_portal(filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters)`

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sortasc(basestring)`** – sortasc query parameter. sort asc.
- **`sortdsc(basestring)`** – sortdsc query parameter. sort desc.
- **`filter(basestring, list, set, tuple)`** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal*

get_sponsor_portal_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsor portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsor_portal_generator*

create_sponsor_portal(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a sponsor portal.

Parameters

- **customizations** (*object*) – customizations, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.
- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *create_sponsor_portal*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the sponsor portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sponsored_guest_portal

class SponsoredGuestPortal

Identity Services Engine SponsoredGuestPortal API (version: 3.1.0).

Wraps the Identity Services Engine SponsoredGuestPortal API and exposes the API as native Python methods that return native Python objects.

get_sponsored_guest_portal_by_id(*id, headers=None, **query_parameters*)

This API allows the client to get a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_sponsored_guest_portal_by_id`*

`update_sponsored_guest_portal_by_id(id, customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)`

This API allows the client to update a sponsored guest portal by ID.

Parameters

- **`customizations(object)`** – Defines all of the Portal Customizations available, property of the request body.
- **`description(string)`** – description, property of the request body.
- **`id(basestring)`** – id, property of the request body.
- **`name(string)`** – name, property of the request body.
- **`portal_test_url(string)`** – URL to bring up a test page for this portal, property of the request body.
- **`portal_type(string)`** – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDQUEST, property of the request body.
- **`settings(object)`** – Defines all of the settings groups available for a portal, property of the request body.
- **`id`** – id path parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload(dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation(bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sponsored_guest_portal_by_id*

delete_sponsored_guest_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a sponsored guest portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sponsored_guest_portal_by_id*

get_sponsored_guest_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.

- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_sponsored_guest_portals*

get_sponsored_guest_portals_generator (*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the sponsored guest portals. Filter: [name, description] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_sponsored_guest_portals_generator*

create_sponsored_guest_portal(*customizations=None*, *description=None*, *name=None*, *portal_test_url=None*, *portal_type=None*, *settings=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API creates a sponsored guest portal.

Parameters

- **customizations** (*object*) – Defines all of the Portal Customizations available, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_test_url** (*string*) – URL to bring up a test page for this portal, property of the request body.

- **portal_type** (*string*) – Allowed values: BYOD, HOTSPOTGUEST, MYDEVICE, SELFREGGUEST, SPONSOR, SPONSOREDGUEST, property of the request body.
- **settings** (*object*) – Defines all of the settings groups available for a portal, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(customizations=None, description=None, name=None, portal_test_url=None, portal_type=None, settings=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_sponsored_guest_portal*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the sponsored guest portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_download

class SupportBundleDownload

Identity Services Engine SupportBundleDownload API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleDownload API and exposes the API as native Python methods that return native Python objects.

download_support_bundle(*file_name=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to upload a support bundle.

Parameters

- **file_name** (*string*) – fileName, property of the request body.
- **dirpath** (*basestring*) – Directory absolute path. Defaults to os.getcwd().
- **save_file** (*bool*) – Enable or disable automatic file creation of raw response.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

HTTP Response container. For more information check the [urllib3 documentation](#)

Return type urllib3.response.HTTPResponse

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.
- **DownloadFailure** – If was not able to download the raw
- **response to a file.** –

download(*file_name=None, dirpath=None, save_file=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *download_support_bundle*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle download.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

support_bundle_status**class SupportBundleStatus**

Identity Services Engine SupportBundleStatus API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleStatus API and exposes the API as native Python methods that return native Python objects.

`get_support_bundle_status_by_id(id, headers=None, **query_parameters)`

This API allows the client to get a support bundle status by ID.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status_by_id*

get_support_bundle_status(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_support_bundle_status*

get_support_bundle_status_generator(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the support bundle status.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_support_bundle_status_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the support bundle status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

support_bundle_trigger_configuration

class SupportBundleTriggerConfiguration

Identity Services Engine SupportBundleTriggerConfiguration API (version: 3.1.0).

Wraps the Identity Services Engine SupportBundleTriggerConfiguration API and exposes the API as native Python methods that return native Python objects.

create_support_bundle(*description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a support bundle trigger configuration.

Parameters

- **description** (*string*) – description, property of the request body.

- **host_name** (*string*) – This parameter is hostName only, xxxx of xxxx.yyy.zz, property of the request body.
- **name** (*string*) – Resource Name, property of the request body.
- **support_bundle_include_options** (*object*) – supportBundleIncludeOptions, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(description=None, host_name=None, name=None, support_bundle_include_options=None, headers=None, payload=None, active_validation=True, **query_parameters)

Alias for *create_support_bundle*

get_version(headers=None, **query_parameters)

This API helps to retrieve the version information related to the support bundle trigger configuration.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sync_ise_node**class SyncIseNode**

Identity Services Engine Sync ISE Node API (version: 3.1.0).

Wraps the Identity Services Engine Sync ISE Node API and exposes the API as native Python methods that return native Python objects.

sync_node(hostname=None, headers=None, payload=None, active_validation=True, **query_parameters)

Performing a manual sync will involve a reload of the target node, but not the primary PAN. There might be situations where if the node has been out of sync for a long time, it may not be possible to recover via a manual sync.

Parameters

- **hostname** (*string*) – hostname, property of the request body. Constraints: maxLength set to 64 and minLength set to 1.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_health

class SystemHealth

Identity Services Engine System Health API (version: 3.1.0).

Wraps the Identity Services Engine System Health API and exposes the API as native Python methods that return native Python objects.

get_healths(*headers=None, **query_parameters*)
getHealths.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_performances(*headers=None, **query_parameters*)
getPerformances.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

system_certificate

class SystemCertificate

Identity Services Engine SystemCertificate API (version: 3.1.0).

Wraps the Identity Services Engine SystemCertificate API and exposes the API as native Python methods that return native Python objects.

create_system_certificate(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to create a system certificate.

Parameters

- **ers_local_cert_stub** (*object*) – Inputs for certificate creation, property of the request body.
- **node_id** (*string*) – NodeId of Cisco ISE application, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*ers_local_cert_stub=None, node_id=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_system_certificate*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the system certificate.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_command_sets**class TacacsCommandSets**

Identity Services Engine TACACSCCommandSets API (version: 3.1.0).

Wraps the Identity Services Engine TACACSCCommandSets API and exposes the API as native Python methods that return native Python objects.

get_tacacs_command_sets_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_name*

get_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS command sets by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_command_sets_by_id*

update_tacacs_command_sets_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *commands=None*, *description=None*, *name=None*, *permit_unmatched=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_command_sets_by_id*

delete_tacacs_command_sets_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS command sets.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_command_sets_by_id*

get_tacacs_command_sets(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_command_sets*

get_tacacs_command_sets_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS command sets.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_command_sets_generator*

create_tacacs_command_sets(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS command sets.

Parameters

- **commands** (*object*) – commands, property of the request body.
- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **permit_unmatched** (*boolean*) – permitUnmatched, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*commands=None, description=None, name=None, permit_unmatched=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_command_sets*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS command sets.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_external_servers**class TacacsExternalServers**

Identity Services Engine TACACSExternalServers API (version: 3.1.0).

Wraps the Identity Services Engine TACACSExternalServers API and exposes the API as native Python methods that return native Python objects.

get_tacacs_external_servers_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_name*

get_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get TACACS external servers by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers_by_id*

update_tacacs_external_servers_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.

- **timeout** (*integer*) – The server timeout, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *connection_port=None*, *description=None*, *host_ip=None*, *name=None*, *shared_secret=None*, *single_connect=None*, *timeout=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_tacacs_external_servers_by_id*

delete_tacacs_external_servers_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes TACACS external servers.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_tacacs_external_servers_by_id*

get_tacacs_external_servers(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_external_servers*

get_tacacs_external_servers_generator(*page=None*, *size=None*, *headers=None*,
***query_parameters*)

This API allows the client to get all the TACACS external servers.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_external_servers_generator*

create_tacacs_external_servers(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates TACACS external servers.

Parameters

- **connection_port** (*integer*) – The port to connect the server, property of the request body.
- **description** (*string*) – description, property of the request body.
- **host_ip** (*string*) – The server IPV4 address, property of the request body.
- **name** (*string*) – name, property of the request body.
- **shared_secret** (*string*) – The server shared secret, property of the request body.
- **single_connect** (*boolean*) – Define the use of single connection, property of the request body.
- **timeout** (*integer*) – The server timeout, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*connection_port=None, description=None, host_ip=None, name=None, shared_secret=None, single_connect=None, timeout=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_external_servers*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS external servers.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_profile

class TacacsProfile

Identity Services Engine TACACSProfile API (version: 3.1.0).

Wraps the Identity Services Engine TACACSProfile API and exposes the API as native Python methods that return native Python objects.

get_tacacs_profile_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get a TACACS profile by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_profile_by_name*

get_tacacs_profile_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS profile by ID.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_profile_by_id*

```
update_tacacs_profile_by_id(id, description=None, name=None, session_attributes=None,
                           headers=None, payload=None, active_validation=True,
                           **query_parameters)
```

This API allows the client to update a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
update_by_id(id, description=None, name=None, session_attributes=None, headers=None, payload=None,
             active_validation=True, **query_parameters)
```

Alias for *update_tacacs_profile_by_id*

```
delete_tacacs_profile_by_id(id, headers=None, **query_parameters)
```

This API deletes a TACACS profile.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`delete_by_id(id, headers=None, **query_parameters)`

Alias for *`delete_tacacs_profile_by_id`*

`get_tacacs_profile(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the TACACS profiles.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all(page=None, size=None, headers=None, **query_parameters)`

Alias for *`get_tacacs_profile`*

`get_tacacs_profile_generator(page=None, size=None, headers=None, **query_parameters)`

This API allows the client to get all the TACACS profiles.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_profile_generator*

create_tacacs_profile(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS profile.

Parameters

- **description** (*string*) – description, property of the request body.
- **name** (*string*) – name, property of the request body.
- **session_attributes** (*object*) – Holds list of session attributes. View type for GUI is Shell by default, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, name=None, session_attributes=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_profile*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS profile.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

tacacs_server_sequence

class TacacsServerSequence

Identity Services Engine TacacsServerSequence API (version: 3.1.0).

Wraps the Identity Services Engine TacacsServerSequence API and exposes the API as native Python methods that return native Python objects.

get_tacacs_server_sequence_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get a TACACS server sequence by name.

Parameters

- **name** (*basestring*) – name path parameter.

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_server_sequence_by_name*

get_tacacs_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a TACACS server sequence by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_tacacs_server_sequence_by_id*

```
update_tacacs_server_sequence_by_id(id, description=None, local_accounting=None, name=None,
                                     prefix_delimiter=None, prefix_strip=None,
                                     remote_accounting=None, server_list=None,
                                     suffix_delimiter=None, suffix_strip=None, headers=None,
                                     payload=None, active_validation=True, **query_parameters)
```

This API allows the client to update a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *local_accounting=None*, *name=None*, *prefix_delimiter=None*, *prefix_strip=None*, *remote_accounting=None*, *server_list=None*, *suffix_delimiter=None*, *suffix_strip=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for [*update_tacacs_server_sequence_by_id*](#)

delete_tacacs_server_sequence_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes a TACACS server sequence.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for [*delete_tacacs_server_sequence_by_id*](#)

get_tacacs_server_sequence(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_server_sequence*

`get_tacacs_server_sequence_generator`(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the TACACS server sequences.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:
 - `headers(MyDict)`: response headers.
 - `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - `content(bytes)`: representation of the request's response
 - `text(str)`: representation of the request's response

Return type *Generator*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all_generator`(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_tacacs_server_sequence_generator*

`create_tacacs_server_sequence`(*description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates a TACACS server sequence.

Parameters

- **description** (*string*) – description, property of the request body.
- **local_accounting** (*boolean*) – localAccounting, property of the request body.
- **name** (*string*) – name, property of the request body.
- **prefix_delimiter** (*string*) – The delimiter that will be used for prefix strip, property of the request body.
- **prefix_strip** (*boolean*) – Define if a delimiter will be used for prefix strip, property of the request body.
- **remote_accounting** (*boolean*) – remoteAccounting, property of the request body.
- **server_list** (*string*) – The names of Tacacs external servers separated by commas. The order of the names in the string is the order of servers that will be used during authentication, property of the request body.
- **suffix_delimiter** (*string*) – The delimiter that will be used for suffix strip, property of the request body.
- **suffix_strip** (*boolean*) – Define if a delimiter will be used for suffix strip, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, local_accounting=None, name=None, prefix_delimiter=None, prefix_strip=None, remote_accounting=None, server_list=None, suffix_delimiter=None, suffix_strip=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_tacacs_server_sequence*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the TACACS server sequence.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

telemetry_information

class TelemetryInformation

Identity Services Engine TelemetryInformation API (version: 3.1.0).

Wraps the Identity Services Engine TelemetryInformation API and exposes the API as native Python methods that return native Python objects.

get_telemetry_info_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get telemetry information by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_info_by_id*

get_telemetry_information(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *headers=None*, ***query_parameters*)

Alias for *get_telemetry_information*

get_telemetry_information_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the telemetry information. Filter: [deploymentId] To search resources by using toDate column, follow the format: DD-MON-YY (Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 .

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request’s response
 - **text**(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, headers=None, **query_parameters*)

Alias for *get_telemetry_information_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the telemetry information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

trust_sec_configuration**class TrustSecConfiguration**

Identity Services Engine TrustSec Configuration API (version: 3.1.0).

Wraps the Identity Services Engine TrustSec Configuration API and exposes the API as native Python methods that return native Python objects.

get_security_groups(headers=None, **query_parameters)
getSecurityGroups.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_security_groups*

get_security_group_acls(*headers=None, **query_parameters*)

getSecurityGroupAcls.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_egress_policies(*headers=None, **query_parameters*)

getEgressPolicies.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_egress_matrices(*headers=None, **query_parameters*)
getEgressMatrices.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

trust_sec_sxp

class TrustSecSxp

Identity Services Engine TrustSec SXP API (version: 3.1.0).

Wraps the Identity Services Engine TrustSec SXP API and exposes the API as native Python methods that return native Python objects.

get_bindings(*headers=None, **query_parameters*)
getBindings.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

version_and_patch

class VersionAndPatch

Identity Services Engine VersionAndPatch API (version: 3.1.0).

Wraps the Identity Services Engine VersionAndPatch API and exposes the API as native Python methods that return native Python objects.

get_ise_version_and_patch(*headers=None, **query_parameters*)

This API allows the client to get Cisco ISE version and patch information.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*headers=None, **query_parameters*)

Alias for *get_ise_version_and_patch*

version_info

class VersionInfo

Identity Services Engine VersionInfo API (version: 3.1.0).

Wraps the Identity Services Engine VersionInfo API and exposes the API as native Python methods that return native Python objects.

get_version_info(*resource*, *headers=None*, ***query_parameters*)

Get all VersionInfo.

Parameters

- **resource** (*basestring*) – resource path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

endpoint

class Endpoint

Identity Services Engine endpoint API (version: 3.1.0).

Wraps the Identity Services Engine endpoint API and exposes the API as native Python methods that return native Python objects.

release_rejected_endpoint(*id*, *headers=None*, ***query_parameters*)

This API allows the client to release a rejected endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`release_rejected(id, headers=None, **query_parameters)`

Alias for *`release_rejected_endpoint`*

`deregister_endpoint(id, headers=None, **query_parameters)`

This API allows the client to de-register an endpoint.

Parameters

- **`id (basestring)`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`deregister(id, headers=None, **query_parameters)`

Alias for *`deregister_endpoint`*

`get_rejected_endpoints(headers=None, **query_parameters)`

This API allows the client to get the rejected endpoints.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_rejected(*headers=None, **query_parameters*)

Alias for *get_rejected_endpoints*

get_endpoint_by_name(*name, headers=None, **query_parameters*)

This API allows the client to get an endpoint by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name, headers=None, **query_parameters*)

Alias for *get_endpoint_by_name*

get_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get an endpoint by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_endpoint_by_id*

update_endpoint_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to update an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.

- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *custom_attributes=None*, *description=None*, *group_id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_endpoint_by_id*

delete_endpoint_by_id(*id*, *headers=None*, ***query_parameters*)

This API deletes an endpoint.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_endpoint_by_id*

register_endpoint(*custom_attributes=None*, *description=None*, *group_id=None*, *id=None*, *identity_store=None*, *identity_store_id=None*, *mac=None*, *mdm_attributes=None*, *name=None*, *portal_user=None*, *profile_id=None*, *static_group_assignment=None*, *static_profile_assignment=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

This API allows the client to register an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **id** (*string*) – id, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.
- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

register(*custom_attributes=None, description=None, group_id=None, id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *register_endpoint*

get_endpoints(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: `/ers/config/endpoint?filter={filter name}.{operator}.{logical profile name}` Example: https://{{ise-ip}}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET `/ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18` Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring, list, set, tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints*

get_endpoints_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

This API allows the client to get all the endpoints. Filter: Filters can be used to filter out Endpoints based on a set of attributes. This API currently provides the following filters: [logicalProfileName, portalUser, staticProfileAssignment, profileId, profile, groupId, staticGroupAssignment, mac] Example 1: The logicalProfileName filter can be used to get Endpoints that belong to a specific Logical Profile. The supported operator for logicalProfileNamefilter is EQ (equal to). The syntax to invoke the API with this filter: /ers/config/endpoint?filter={filter name}.{operator}.{logical profile name} Example: [https://{ise-ip}:9060/ers/config/endpoint?filter=logical ProfileName.EQ.LP_Apple](https://{ise-ip}:9060/ers/config/endpoint?filter=logical%20ProfileName.EQ.LP_Apple) Example 2: To search resources by using toDate column, follow the format: DD-MON-YY (Example:13-SEP-18) Day or Year:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13 Month:GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date:GET /ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page (int)** – page query parameter. Page number.
- **size (int)** – size query parameter. Number of objects returned per page.
- **sortasc (basestring)** – sortasc query parameter. sort asc.
- **sortdsc (basestring)** – sortdsc query parameter. sort desc.
- **filter (basestring, list, set, tuple)** – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(MyDict): response headers.
 - **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(bytes): representation of the request's response
 - **text**(str): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_endpoints_generator*

create_endpoint(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API creates an endpoint.

Parameters

- **custom_attributes** (*object*) – customAttributes, property of the request body.
- **description** (*string*) – description, property of the request body.
- **group_id** (*string*) – groupId, property of the request body.
- **identity_store** (*string*) – identityStore, property of the request body.
- **identity_store_id** (*string*) – identityStoreId, property of the request body.
- **mac** (*string*) – mac, property of the request body.
- **mdm_attributes** (*object*) – mdmAttributes, property of the request body.
- **name** (*string*) – name, property of the request body.
- **portal_user** (*string*) – portalUser, property of the request body.
- **profile_id** (*string*) – profileId, property of the request body.
- **static_group_assignment** (*boolean*) – staticGroupAssignment, property of the request body.

- **static_profile_assignment** (*boolean*) – staticProfileAssignment, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*custom_attributes=None, description=None, group_id=None, identity_store=None, identity_store_id=None, mac=None, mdm_attributes=None, name=None, portal_user=None, profile_id=None, static_group_assignment=None, static_profile_assignment=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_endpoint*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the endpoint.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_for_endpoint(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

This API allows the client to submit the bulk request.

Parameters

- **operation_type** (*string*) – operationType, property of the request body.
- **resource_media_type** (*string*) – resourceMediaType, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request(*operation_type=None, resource_media_type=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_request_for_endpoint*

monitor_bulk_status_endpoint(*bulkid, headers=None, **query_parameters*)

This API allows the client to monitor the bulk request.

Parameters

- **bulkid** (*basestring*) – bulkid path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.

- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`monitor_bulk_status(bulkid, headers=None, **query_parameters)`

Alias for *monitor_bulk_status_endpoint*

nbar_app

class NbarApp

Identity Services Engine nbarApp API (version: 3.1.0).

Wraps the Identity Services Engine nbarApp API and exposes the API as native Python methods that return native Python objects.

`get_nbar_apps(filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters)`

Get all NBAR Applications.

Parameters

- **`page(int)`** – page query parameter. Page number.
- **`size(int)`** – size query parameter. Number of objects returned per page.
- **`sort(basestring)`** – sort query parameter. sort type asc or desc.
- **`sort_by(basestring)`** – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter(basestring)`** – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type(basestring)`** – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers(dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_all`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_nbar_apps*

`get_nbar_apps_generator`(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all NBAR Applications.

Parameters

- **`page`** (*int*) – page query parameter. Page number.
- **`size`** (*int*) – size query parameter. Number of objects returned per page.
- **`sort`** (*basestring*) – sort query parameter. sort type asc or desc.
- **`sort_by`** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **`filter`** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **`filter_type`** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- `RestResponse`: REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_nbar_apps_generator*

create_nbar_app(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create NBAR application.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*string*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **network_identities** (*list*) – Array of NIs, property of the request body (list of objects).
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*description=None, id=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for [create_nbar_app](#)

get_nbar_app_by_id(*id, headers=None, **query_parameters*)

Get NBAR Application by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [RestResponse](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for [get_nbar_app_by_id](#)

update_nbar_app_by_id(*id, description=None, name=None, network_identities=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Update NBAR Application.

Parameters

- **description** (*string*) – description, property of the request body.
- **id** (*basestring*) – id, property of the request body.
- **name** (*string*) – name, property of the request body.
- **network_identities** (*list*) – Array of NIs, property of the request body (list of objects).
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *description=None*, *name=None*, *network_identities=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_nbar_app_by_id*

delete_nbar_app_by_id(*id*, *headers=None*, ***query_parameters*)

Delete NBAR Application.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_nbar_app_by_id*

portal

class Portal

Identity Services Engine portal API (version: 3.1.0).

Wraps the Identity Services Engine portal API and exposes the API as native Python methods that return native Python objects.

get_portal_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a portal by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_portal_by_id*

get_portals(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.

- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

Alias for *get_portals*

get_portals_generator (*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sortasc=None*, *sortdsc=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the portals. Filter: [name, description]
To search resources by using toDate column, follow the format: DD-MON-YY
(Example: 13-SEP-18) Day or Year: GET /ers/config/guestuser/?filter=toDate.CONTAINS.13
Month: GET /ers/config/guestuser/?filter=toDate.CONTAINS.SEP Date: GET
/ers/config/guestuser/?filter=toDate.CONTAINS.13-SEP-18 Sorting: [name, description].

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sortasc** (*basestring*) – sortasc query parameter. sort asc.
- **sortdsc** (*basestring*) – sortdsc query parameter. sort desc.
- **filter** (*basestring*, *list*, *set*, *tuple*) – filter query parameter. **Simple filtering** should be available through the filter query string parameter. The structure of a filter

is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. (Operator: Description), (EQ: Equals), (NEQ: Not Equals), (GT: Greater Than), (LT: Less Than), (STARTSW: Starts With), (NSTARTSW: Not Starts With), (ENDSW: Ends With), (NENDSW: Not Ends With), (CONTAINS: Contains), (NCONTAINS: Not Contains), .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - headers(MyDict): response headers.
 - response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - content(bytes): representation of the request’s response
 - text(str): representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sortasc=None, sortdsc=None, headers=None, **query_parameters*)

Alias for *get_portals_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information realted to the portal.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request’s response
- text(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

px_grid_node

class PxGridNode

Identity Services Engine pxGridNode API (version: 3.1.0).

Wraps the Identity Services Engine pxGridNode API and exposes the API as native Python methods that return native Python objects.

approve_px_grid_node(*name*, *headers=None*, ***query_parameters*)

This API allows the client to approve a pxGrid node. Only pending pxGrid nodes can be approved.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

approve(*name*, *headers=None*, ***query_parameters*)

Alias for *approve_px_grid_node*

get_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_name*

delete_px_grid_node_by_name(*name*, *headers=None*, ***query_parameters*)

This API deletes a pxGrid node by name.

Parameters

- **name** (*basestring*) – name path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_name(*name*, *headers=None*, ***query_parameters*)

Alias for *delete_px_grid_node_by_name*

get_px_grid_node_by_id(*id*, *headers=None*, ***query_parameters*)

This API allows the client to get a pxGrid node by ID.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_px_grid_node_by_id*

get_px_grid_node(*page=None*, *size=None*, *headers=None*, ***query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node*

get_px_grid_node_generator(*page=None, size=None, headers=None, **query_parameters*)

This API allows the client to get all the npxGrid nodes.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers**(*MyDict*): response headers.
 - **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
 - **content**(*bytes*): representation of the request's response
 - **text**(*str*): representation of the request's response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*page=None, size=None, headers=None, **query_parameters*)

Alias for *get_px_grid_node_generator*

get_version(*headers=None, **query_parameters*)

This API helps to retrieve the version information related to the pxGrid node.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(*MyDict*): response headers.
- **response**(*MyDict*): response body as a *MyDict* object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(*bytes*): representation of the request's response
- **text**(*str*): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

sg_vn_mapping

class SgVnMapping

Identity Services Engine sgVnMapping API (version: 3.1.0).

Wraps the Identity Services Engine sgVnMapping API and exposes the API as native Python methods that return native Python objects.

get_sg_vn_mappings(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings*

get_sg_vn_mappings_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Security Group and Virtual Network mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type *Generator*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_sg_vn_mappings_generator*

create_sg_vn_mapping(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Security Group and Virtual Network mapping.

Parameters

- **id** (*string*) – Identifier of the SG-VN mapping, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **sg_name** (*string*) – Name of the associated Security Group to be used for identity if id is not provided, property of the request body.
- **sgt_id** (*string*) – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for [*create_sg_vn_mapping*](#)

bulk_create_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type [*RestResponse*](#)

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for [*bulk_create_sg_vn_mappings*](#)

bulk_delete_sg_vn_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete SG-VN Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.

- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_delete`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_delete_sg_vn_mappings`*

`bulk_update_sg_vn_mappings`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update SG-VN Mappings in bulk.

Parameters

- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`payload`** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **`active_validation`** (*bool*) – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`bulk_request_update`(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *`bulk_update_sg_vn_mappings`*

`get_sg_vn_mapping_by_id`(*id, headers=None, **query_parameters*)

Get Security Group and Virtual Network mapping by id.

Parameters

- **`id`** (*basestring*) – id path parameter.
- **`headers`** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a `MyDict` object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **`TypeError`** – If the parameter types are incorrect.
- **`MalformedRequest`** – If the request body created is invalid.
- **`ApiError`** – If the Identity Services Engine cloud returns an error.

`get_by_id(id, headers=None, **query_parameters)`

Alias for *`get_sg_vn_mapping_by_id`*

`update_sg_vn_mapping_by_id(id, last_update=None, sg_name=None, sgt_id=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters)`

Update Security Group and Virtual Network mapping.

Parameters

- **`id (basestring)`** – Identifier of the SG-VN mapping, property of the request body.
- **`last_update (string)`** – Timestamp for the last update of the SG-VN mapping, property of the request body.
- **`sg_name (string)`** – Name of the associated Security Group to be used for identity if `id` is not provided, property of the request body.
- **`sgt_id (string)`** – Identifier of the associated Security Group which is required unless its name is provided, property of the request body.
- **`vn_id (string)`** – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **`vn_name (string)`** – Name of the associated Virtual Network to be used for identity if `id` is not provided, property of the request body.
- **`id`** – id path parameter.
- **`headers (dict)`** – Dictionary of HTTP Headers to send with the Request .
- **`payload (dict)`** – A JSON serializable Python object to send in the body of the Request.
- **`active_validation (bool)`** – Enable/Disable payload validation. Defaults to True.
- **`**query_parameters`** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.

- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *last_update=None*, *sg_name=None*, *sgt_id=None*, *vn_id=None*, *vn_name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_sg_vn_mapping_by_id*

delete_sg_vn_mapping_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Security Group and Virtual Network mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_sg_vn_mapping_by_id*

tasks

class Tasks

Identity Services Engine tasks API (version: 3.1.0).

Wraps the Identity Services Engine tasks API and exposes the API as native Python methods that return native Python objects.

get_task_status(*headers=None, **query_parameters*)
get all task status.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(list): A list of MyDict objects. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_task_status_by_id(*task_id, headers=None, **query_parameters*)
Monitor task status.

Parameters

- **task_id** (*basestring*) – taskId path parameter. The id of the task executed before.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

virtual_network**class VirtualNetwork**

Identity Services Engine virtualNetwork API (version: 3.1.0).

Wraps the Identity Services Engine virtualNetwork API and exposes the API as native Python methods that return native Python objects.

get_virtual_networks(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks*

get_virtual_networks_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all Virtual Networks.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.

- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_virtual_networks_generator*

create_virtual_network(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*string*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*additional_attributes=None, id=None, last_update=None, name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_virtual_network*

bulk_create_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .

- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_create_virtual_networks*

bulk_delete_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.

- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *bulk_delete_virtual_networks*

bulk_update_virtual_networks(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update Virtual Network in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *bulk_update_virtual_networks*

get_virtual_network_by_id(*id, headers=None, **query_parameters*)
Get Virtual Network by id.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *get_virtual_network_by_id*

update_virtual_network_by_id(*id*, *additional_attributes=None*, *last_update=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Update Virtual Network.

Parameters

- **additional_attributes** (*string*) – JSON String of additional attributes for the Virtual Network, property of the request body.
- **id** (*basestring*) – Identifier of the Virtual Network, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the Virtual Network, property of the request body.
- **name** (*string*) – Name of the Virtual Network, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

update_by_id(*id*, *additional_attributes=None*, *last_update=None*, *name=None*, *headers=None*, *payload=None*, *active_validation=True*, ***query_parameters*)

Alias for *update_virtual_network_by_id*

delete_virtual_network_by_id(*id*, *headers=None*, ***query_parameters*)

Delete Virtual Network.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

delete_by_id(*id*, *headers=None*, ***query_parameters*)

Alias for *delete_virtual_network_by_id*

vn_vlan_mapping

class VnVlanMapping

Identity Services Engine vnVlanMapping API (version: 3.1.0).

Wraps the Identity Services Engine vnVlanMapping API and exposes the API as native Python methods that return native Python objects.

get_vn_vlan_mappings(*filter=None*, *filter_type=None*, *page=None*, *size=None*, *sort=None*, *sort_by=None*, *headers=None*, ***query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.

- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the “filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .
- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mappings*

get_vn_vlan_mappings_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Get all VN-Vlan Mappings.

Parameters

- **page** (*int*) – page query parameter. Page number.
- **size** (*int*) – size query parameter. Number of objects returned per page.
- **sort** (*basestring*) – sort query parameter. sort type asc or desc.
- **sort_by** (*basestring*) – sortBy query parameter. sort column by which objects needs to be sorted.
- **filter** (*basestring*) – filter query parameter. Simple filtering should be available through the filter query string parameter. The structure of a filter is a triplet of field operator and value separated with dots. More than one filter can be sent. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the

“filterType=or” query string parameter. Each resource Data model description should specify if an attribute is a filtered field. OPERATOR DESCRIPTION EQ Equals NEQ Not Equals GT Greater Than LT Less Than STARTSW Starts With NSTARTSW Not Starts With ENDSW Ends With NENDSW Not Ends With CONTAINS Contains NCONTAINS Not Contains .

- **filter_type** (*basestring*) – filterType query parameter. The logical operator common to ALL filter criteria will be by default AND, and can be changed by using the parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

A generator object containing the following object.

- **RestResponse**: REST response with following properties:
 - **headers(MyDict)**: response headers.
 - **response(MyDict)**: response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
 - **content(bytes)**: representation of the request’s response
 - **text(str)**: representation of the request’s response

Return type Generator

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_all_generator(*filter=None, filter_type=None, page=None, size=None, sort=None, sort_by=None, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mappings_generator*

create_vn_vlan_mapping(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mapping.

Parameters

- **id** (*string*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **is_data** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **max_value** (*integer*) – Max value, property of the request body.
- **name** (*string*) – Name of the Vlan, property of the request body.

- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response
- text(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

create(*id=None, is_data=None, is_default_vlan=None, last_update=None, max_value=None, name=None, vn_id=None, vn_name=None, headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *create_vn_vlan_mapping*

bulk_create_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Create VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- headers(MyDict): response headers.
- response(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- content(bytes): representation of the request's response

- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_create(*headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *bulk_create_vn_vlan_mappings*

bulk_delete_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Delete VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- `headers(MyDict)`: response headers.
- `response(MyDict)`: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- `content(bytes)`: representation of the request's response
- `text(str)`: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_delete(*headers=None, payload=None, active_validation=True, **query_parameters*)
Alias for *bulk_delete_vn_vlan_mappings*

bulk_update_vn_vlan_mappings(*headers=None, payload=None, active_validation=True, **query_parameters*)

Update VN-Vlan Mappings in bulk.

Parameters

- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*list*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.

- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

bulk_request_update(*headers=None, payload=None, active_validation=True, **query_parameters*)

Alias for *bulk_update_vn_vlan_mappings*

get_vn_vlan_mapping_by_id(*id, headers=None, **query_parameters*)

Get VN-Vlan Mapping by id.

Parameters

- **id (basestring)** – id path parameter.
- **headers (dict)** – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers(MyDict)**: response headers.
- **response(MyDict)**: response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content(bytes)**: representation of the request's response
- **text(str)**: representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

get_by_id(*id, headers=None, **query_parameters*)

Alias for *get_vn_vlan_mapping_by_id*


```
update_vn_vlan_mapping_by_id(id, is_data=None, is_default_vlan=None, last_update=None,
                             max_value=None, name=None, vn_id=None, vn_name=None,
                             headers=None, payload=None, active_validation=True,
                             **query_parameters)
```

Update VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – Identifier of the VN-Vlan Mapping, property of the request body.
- **is_data** (*boolean*) – Flag which indicates whether the Vlan is data or voice type, property of the request body.
- **is_default_vlan** (*boolean*) – Flag which indicates if the Vlan is default, property of the request body.
- **last_update** (*string*) – Timestamp for the last update of the VN-Vlan Mapping, property of the request body.
- **max_value** (*integer*) – Max value, property of the request body.
- **name** (*string*) – Name of the Vlan, property of the request body.
- **vn_id** (*string*) – Identifier for the associated Virtual Network which is required unless its name is provided, property of the request body.
- **vn_name** (*string*) – Name of the associated Virtual Network to be used for identity if id is not provided, property of the request body.
- **id** – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- **payload** (*dict*) – A JSON serializable Python object to send in the body of the Request.
- **active_validation** (*bool*) – Enable/Disable payload validation. Defaults to True.
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object's properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request's response
- **text**(str): representation of the request's response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

```
delete_vn_vlan_mapping_by_id(id, headers=None, **query_parameters)
```

Delete VN-Vlan Mapping.

Parameters

- **id** (*basestring*) – id path parameter.
- **headers** (*dict*) – Dictionary of HTTP Headers to send with the Request .
- ****query_parameters** – Additional query parameters (provides support for parameters that may be added in the future).

Returns

REST response with following properties:

- **headers**(MyDict): response headers.
- **response**(MyDict): response body as a MyDict object. Access the object’s properties by using the dot notation or the bracket notation.
- **content**(bytes): representation of the request’s response
- **text**(str): representation of the request’s response

Return type *RestResponse*

Raises

- **TypeError** – If the parameter types are incorrect.
- **MalformedRequest** – If the request body created is invalid.
- **ApiError** – If the Identity Services Engine cloud returns an error.

Identity Services Engine Data Object

MyDict

class MyDict

A **Python** `_dict_` subclass which tries to act like **JavaScript** objects, so you can use the **dot notation** (`.`) to access members of the object. If the member doesn’t exist yet then it’s created when you assign something to it. Brackets notation (`d['foo']`) is also possible.

has_path(*key*)

Check existence of “path” in the tree.

```
d = MyDict({'foo': {'bar': 'baz'}})
d.has_path('foo.bar') == True
```

It only supports “dot-notation” (`d.foo.bar`)

get(*key*, *default=None*)

Return the value for key if key is in the dictionary, else default.

to_json()

Returns a JSON-like string representing this instance

RestResponse

class RestResponse

RestResponse to represent the response of the calls to the Identity Services Engine APIs.

property content

The content (bytes) of the RestResponse.

property text

The text (str) of the RestResponse.

property response

The response (MyDict) of the RestResponse.

property headers

The headers (MyDict) of the RestResponse.

Exceptions

exception ciscoisesdkException

Bases: [Exception](#)

Base class for all ciscoisesdk package exceptions.

exception AccessTokenError

Bases: [ciscoisesdk.exceptions.ciscoisesdkException](#)

Raised when an incorrect Identity Services Engine Access Token has been provided.

exception VersionError

Bases: [ciscoisesdk.exceptions.ciscoisesdkException](#)

Raised when an incorrect Identity Services Engine version has been provided.

exception ApiError

Bases: [ciscoisesdk.exceptions.ciscoisesdkException](#)

Errors returned in response to requests sent to the Identity Services Engine APIs.

Several data attributes are available for inspection.

response

The `requests.Response` object returned from the API call.

request

The `requests.PreparedRequest` of the API call.

status_code

The HTTP status code from the API response.

status

The HTTP status from the API response.

details_str

The text from the API response.

details

The parsed JSON details from the API response.

message

The error message from the parsed API response.

description

A description of the HTTP Response Code from the API docs.

exception RateLimitError

Bases: [ciscoisesdk.exceptions.ApiError](#)

Identity Services Engine Rate-Limit exceeded Error.

Raised when a rate-limit exceeded message is received and the request **will not** be retried.

retry_after

The *Retry-After* time period (in seconds) provided by Identity Services Engine.

Defaults to 15 seconds if the response *Retry-After* header isn't present in the response headers, and defaults to a minimum wait time of 1 second if Identity Services Engine returns a *Retry-After* header of 0 seconds.

exception RateLimitWarning

Bases: [UserWarning](#)

Identity Services Engine rate-limit exceeded warning.

Raised when a rate-limit exceeded message is received and the request will be retried.

retry_after

The *Retry-After* time period (in seconds) provided by Identity Services Engine.

Defaults to 15 seconds if the response *Retry-After* header isn't present in the response headers, and defaults to a minimum wait time of 1 second if Identity Services Engine returns a *Retry-After* header of 0 seconds.

exception MalformedRequest

Bases: [ciscoisesdk.exceptions.ciscoisesdkException](#)

Raised when a malformed request is received from Identity Services Engine user.

exception DownloadFailure

Bases: [ciscoisesdk.exceptions.ciscoisesdkException](#)

Errors returned in response to requests sent to the Identity Services Engine APIs with stream=True.

Several data attributes are available for inspection.

response

The `requests.Response` object returned from the API call.

request

The `requests.PreparedRequest` of the API call.

status_code

The HTTP status code from the API response.

status

The HTTP status from the API response.

original_error

The original exception

raw

The raw value of the API response

Copyright (c) 2021 Cisco and/or its affiliates.

THE DEVELOPMENT COMMUNITY

Interested in contributing to the project? Please review our community's Code of Conduct and then check out the Contributing page for info to help you get started.

2.1 Contributor Covenant Code of Conduct

2.1.1 Our Pledge

In the interest of fostering an open and welcoming environment, we as contributors and maintainers pledge to making participation in our project and our community a harassment-free experience for everyone, regardless of age, body size, disability, ethnicity, gender identity and expression, level of experience, nationality, personal appearance, race, religion, or sexual identity and orientation.

2.1.2 Our Standards

Examples of behavior that contributes to creating a positive environment include:

- Using welcoming and inclusive language
- Being respectful of differing viewpoints and experiences
- Gracefully accepting constructive criticism
- Focusing on what is best for the community
- Showing empathy towards other community members

Examples of unacceptable behavior by participants include:

- The use of sexualized language or imagery and unwelcome sexual attention or advances
- Trolling, insulting/derogatory comments, and personal or political attacks
- Public or private harassment
- Publishing others' private information, such as a physical or electronic address, without explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

2.1.3 Our Responsibilities

Project maintainers are responsible for clarifying the standards of acceptable behavior and are expected to take appropriate and fair corrective action in response to any instances of unacceptable behavior.

Project maintainers have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, or to ban temporarily or permanently any contributor for other behaviors that they deem inappropriate, threatening, offensive, or harmful.

2.1.4 Scope

This Code of Conduct applies both within project spaces and in public spaces when an individual is representing the project or its community. Examples of representing a project or community include using an official project e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event. Representation of a project may be further defined and clarified by project maintainers.

2.1.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported by contacting the project team. The project team will review and investigate all complaints, and will respond in a way that it deems appropriate to the circumstances. The project team is obligated to maintain confidentiality with regard to the reporter of an incident. Further details of specific enforcement policies may be posted separately.

Project maintainers who do not follow or enforce the Code of Conduct in good faith may face temporary or permanent repercussions as determined by other members of the project's leadership.

2.1.6 Attribution

This Code of Conduct is adapted from the [Contributor Covenant](#), version 1.4.

2.2 Contributing

ciscoisesdk is a community development project. Feedback, thoughts, ideas, and code contributions are most welcome!

2.2.1 How to contribute Feedback, Issues, Thoughts and Ideas

Please use the [issues](#) page to report issues or post ideas for enhancement.

2.2.2 Interested in Contributing Code?

Developer Scripts

We have created some scripts to automate everyday actions needed when working on the project. Please see the [script](#) directory, and it's README for more information.

Notes on the Test Suite

The test suite is grouped by Identity Services Engine versions supported in the Cisco Identity Services Engine SDK.

The test suite uses a mockup server, instead of calling to a Identity Services Engine server directly.

The mockup server is not perfect, that is why it is sometimes necessary to rerun a failed test, we do this by using *pytest-rerunfailures*. On the *script/test* file, you can find the *pytest-rerunfailures* settings, adjust them locally if strictly necessary.

Contributing Code - Using the CI Automated Testing

1. Check for open [issues](#) or create a new *issue* for the item you want to work on and make sure to comment and let us know that you are working on it.
2. Fork a copy of the [repository](#) and clone your forked repository to your development environment.
3. Run `script/setup` to install the development dependencies and setup your environment.
4. Configure the following environment variables in your development environment:
 - `TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - Your test account's Identity Services Engine encoded_auth (username:password encoded in base 64). This variable has priority over username and password.
 - `TEST_IDENTITY_SERVICES_ENGINE_USERNAME` - Your test account's Identity Services Engine username.
 - `TEST_IDENTITY_SERVICES_ENGINE_PASSWORD` - Your test account's Identity Services Engine password.
 - `DEBUG_ENVIRONMENT_VARIABLE` - Your test's debug variable, which controls whether to log information about Identity Services Engine APIs' request and response process.
 - `VERSION_ENVIRONMENT_VARIABLE` - The Identity Services Engine API's version used to test the SDK.
5. Add your code to your forked repository.

If you are creating some new feature or functionality (excellent!), please also write a [test](#) to verify that your code works as expected.

6. We follow [PEP8](#) reasonably strictly for this project. Please make sure your code passes the linter.
Run `script/test lint` or simply run `flake8` from the project root.
7. Commit your changes.
8. Submit a [pull request](#). The GitHub/Travis CI system runs the test suite against your pull request code. If any tests fail, please review your changes. If everything looks good, we will gladly merge your request!

Contributing Code - Running the Test Suite Locally

1. Check for open [issues](#) or create a new 'issue' for the item you want to work on and make sure to comment and let us know that you are working on it.
2. Fork a copy of the [repository](#) and clone your forked repository to your development environment.
Run `script/setup` to install the development dependencies and setup your environment.
3. Configure the following environment variables in your development environment:
 - `TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH` - Your test account's Identity Services Engine encoded_auth (username:password encoded in base 64). This variable has priority over username and password.

- `TEST_IDENTITY_SERVICES_ENGINE_USERNAME` - Your test account's Identity Services Engine username.
- `TEST_IDENTITY_SERVICES_ENGINE_PASSWORD` - Your test account's Identity Services Engine password.
- `DEBUG_ENVIRONMENT_VARIABLE` - Your test's debug variable, which controls whether to log information about Identity Services Engine APIs' request and response process.
- `VERSION_ENVIRONMENT_VARIABLE` - The Identity Services Engine API's version used to test the SDK.

Example:

```
#!/usr/bin/env bash
export TEST_IDENTITY_SERVICES_ENGINE_ENCODED_AUTH="<test account's_
↪username:password encoded in base 64>"
```

4. Add your code to your forked repository.

If you are creating some new feature or functionality (excellent!), please also write a `test` to verify that your code works as expected.

5. We follow [PEP8](#) reasonably strictly for this project. Please make sure your code passes the linter.

Run `script/test lint` from the project root.

6. Commit your changes.

7. Ensure your code passes all of the default tests for all the involved Identity Services Engine versions.

Run `script/test` and ensure all tests execute successfully.

8. Submit a [pull request](#). If everything looks good, we will gladly merge your request!

GENERAL INFORMATION ABOUT THE IDENTITY SERVICES ENGINE SERVICE

3.1 What is Identity Services Engine?

“A better way to control your network. Cisco Identity Services Engine is the network management and command center for Cisco Identity Services Engine, your intent-based network for the enterprise.”

Visit the official [Identity Services Engine](#) website for more information and to create a [free account](#)!

3.2 Identity Services Engine for Developers

Leveraging the Identity Services Engine APIs and developing on top of the Identity Services Engine cloud is easy. Signup for a [free account](#) and then head over to the [Identity Services Engine for Developers](#) website to learn more.

Copyright (c) 2021 Cisco and/or its affiliates.

PYTHON MODULE INDEX

C

`ciscoisesdk.config`, [12](#)

Symbols

`__init__()` (*IdentityServicesEngineAPI* method), 26

A

`access_secret()` (*Consumer* method), 123, 639

`access_token` (*IdentityServicesEngineAPI* property), 28

`AccessTokenError`, 1087

`AciBindings` (class in *ciscois-esdk.api.v3_0_0.aci_bindings*), 30

`AciBindings` (class in *ciscois-esdk.api.v3_1_0.aci_bindings*), 546

`AciSettings` (class in *ciscois-esdk.api.v3_0_0.aci_settings*), 32

`AciSettings` (class in *ciscois-esdk.api.v3_1_0.aci_settings*), 548

`activate_account()` (*Consumer* method), 122, 638

`ActiveDirectory` (class in *ciscois-esdk.api.v3_0_0.active_directory*), 41

`ActiveDirectory` (class in *ciscois-esdk.api.v3_1_0.active_directory*), 557

`add_api()` (*CustomCaller* method), 29

`AdminUser` (class in *ciscois-esdk.api.v3_0_0.admin_user*), 52

`AdminUser` (class in *ciscois-esdk.api.v3_1_0.admin_user*), 567

`AllowedProtocols` (class in *ciscois-esdk.api.v3_0_0.allowed_protocols*), 55

`AllowedProtocols` (class in *ciscois-esdk.api.v3_1_0.allowed_protocols*), 570

`AncEndpoint` (class in *ciscois-esdk.api.v3_0_0.anc_endpoint*), 36

`AncEndpoint` (class in *ciscois-esdk.api.v3_1_0.anc_endpoint*), 551

`AncPolicy` (class in *ciscoisesdk.api.v3_0_0.anc_policy*), 62

`AncPolicy` (class in *ciscoisesdk.api.v3_1_0.anc_policy*), 578

`ApiError`, 1087

`apply()` (*AncEndpoint* method), 39, 555

`apply_anc_endpoint()` (*AncEndpoint* method), 39, 554

`approve()` (*PxGridNode* method), 541, 1061

`approve_by_id()` (*GuestUser* method), 222, 739

`approve_guest_user_by_id()` (*GuestUser* method), 222, 738

`approve_px_grid_node()` (*PxGridNode* method), 541, 1061

`Authentication` (class in *ciscois-esdk.api.authentication*), 28

`authentication_api()` (*Authentication* method), 28

`authorization()` (*Provider* method), 395, 911

`AuthorizationProfile` (class in *ciscois-esdk.api.v3_0_0.authorization_profile*), 69

`AuthorizationProfile` (class in *ciscois-esdk.api.v3_1_0.authorization_profile*), 585

`autoapprove()` (*PxGridSettings* method), 401, 917

`autoapprove_px_grid_settings()` (*PxGridSettings* method), 400, 916

B

`BackupAndRestore` (class in *ciscois-esdk.api.v3_0_0.backup_and_restore*), 82

`BackupAndRestore` (class in *ciscois-esdk.api.v3_1_0.backup_and_restore*), 598

`base_url` (*Authentication* property), 28

`base_url` (*IdentityServicesEngineAPI* property), 28

`bind_csr()` (*Certificates* method), 102, 618

`bulk_create_sg_vn_mappings()` (*SgVnMapping* method), 1068

`bulk_create_virtual_networks()` (*VirtualNetwork* method), 1075

`bulk_create_vn_vlan_mappings()` (*VnVlanMapping* method), 1082

`bulk_delete_sg_vn_mappings()` (*SgVnMapping* method), 1068

`bulk_delete_virtual_networks()` (*VirtualNetwork* method), 1076

`bulk_delete_vn_vlan_mappings()` (*VnVlanMapping* method), 1083

`bulk_request()` (*AncEndpoint* method), 41, 556

`bulk_request()` (*AncPolicy* method), 68, 584

`bulk_request()` (*EgressMatrixCell* method), 182, 698

`bulk_request()` (*Endpoint* method), 537, 1052

`bulk_request()` (*GuestUser* method), 236, 753

- `bulk_request()` (*IpToSgtMapping* method), 250, 767
 - `bulk_request()` (*IpToSgtMappingGroup* method), 258, 775
 - `bulk_request()` (*NetworkDevice* method), 362, 878
 - `bulk_request()` (*SecurityGroups* method), 454, 970
 - `bulk_request()` (*SecurityGroupsAcls* method), 461, 977
 - `bulk_request()` (*SecurityGroupToVirtualNetwork* method), 448, 963
 - `bulk_request()` (*SxpConnections* method), 429, 944
 - `bulk_request()` (*SxpLocalBindings* method), 436, 951
 - `bulk_request()` (*SxpVpns* method), 441, 957
 - `bulk_request_create()` (*SgVnMapping* method), 1068
 - `bulk_request_create()` (*VirtualNetwork* method), 1076
 - `bulk_request_create()` (*VnVlanMapping* method), 1083
 - `bulk_request_delete()` (*SgVnMapping* method), 1069
 - `bulk_request_delete()` (*VirtualNetwork* method), 1077
 - `bulk_request_delete()` (*VnVlanMapping* method), 1083
 - `bulk_request_for_anc_endpoint()` (*AncEndpoint* method), 40, 556
 - `bulk_request_for_anc_policy()` (*AncPolicy* method), 68, 583
 - `bulk_request_for_egress_matrix_cell()` (*EgressMatrixCell* method), 181, 698
 - `bulk_request_for_endpoint()` (*Endpoint* method), 536, 1052
 - `bulk_request_for_guest_user()` (*GuestUser* method), 236, 752
 - `bulk_request_for_ip_to_sgt_mapping()` (*IpToSgtMapping* method), 250, 766
 - `bulk_request_for_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup* method), 258, 774
 - `bulk_request_for_network_device()` (*NetworkDevice* method), 361, 877
 - `bulk_request_for_security_group()` (*SecurityGroups* method), 454, 969
 - `bulk_request_for_security_groups_acl()` (*SecurityGroupsAcls* method), 461, 976
 - `bulk_request_for_security_groups_to_vn_to_vlan()` (*SecurityGroupToVirtualNetwork* method), 447, 963
 - `bulk_request_for_sxp_connections()` (*SxpConnections* method), 428, 944
 - `bulk_request_for_sxp_local_bindings()` (*SxpLocalBindings* method), 435, 951
 - `bulk_request_for_sxp_vpns()` (*SxpVpns* method), 440, 956
 - `bulk_request_update()` (*SgVnMapping* method), 1069
 - `bulk_request_update()` (*VirtualNetwork* method), 1077
 - `bulk_request_update()` (*VnVlanMapping* method), 1084
 - `bulk_update_sg_vn_mappings()` (*SgVnMapping* method), 1069
 - `bulk_update_virtual_networks()` (*VirtualNetwork* method), 1077
 - `bulk_update_vn_vlan_mappings()` (*VnVlanMapping* method), 1083
 - `ByodPortal` (class in *ciscoisesdk.api.v3_0_0.byod_portal*), 76
 - `ByodPortal` (class in *ciscoisesdk.api.v3_1_0.byod_portal*), 592
- ## C
- `call_api()` (*CustomCaller* method), 29
 - `cancel()` (*BackupAndRestore* method), 83, 599
 - `cancel_backup()` (*BackupAndRestore* method), 83, 598
 - `CertificateProfile` (class in *ciscoisesdk.api.v3_0_0.certificate_profile*), 88
 - `CertificateProfile` (class in *ciscoisesdk.api.v3_1_0.certificate_profile*), 603
 - `Certificates` (class in *ciscoisesdk.api.v3_0_0.certificates*), 96
 - `Certificates` (class in *ciscoisesdk.api.v3_1_0.certificates*), 612
 - `CertificateTemplate` (class in *ciscoisesdk.api.v3_0_0.certificate_template*), 93
 - `CertificateTemplate` (class in *ciscoisesdk.api.v3_1_0.certificate_template*), 609
 - `change_sponsor_password()` (*GuestUser* method), 223, 739
 - `ciscoisesdk.config` module, 12
 - `ciscoisesdkException`, 1087
 - `clear()` (*AncEndpoint* method), 37, 552
 - `clear()` (*ClearThreatsAndVulnerabilities* method), 120, 637
 - `clear()` (*EgressMatrixCell* method), 175, 691
 - `clear_all_matrix_cells()` (*EgressMatrixCell* method), 174, 691
 - `clear_anc_endpoint()` (*AncEndpoint* method), 36, 552
 - `clear_threats_and_vulnerabilities()` (*ClearThreatsAndVulnerabilities* method), 120, 636
 - `ClearThreatsAndVulnerabilities` (class in *ciscoisesdk.api.v3_0_0.clear_threats_and_vulnerabilities*), 120
 - `ClearThreatsAndVulnerabilities` (class in *ciscoisesdk.api.v3_1_0.clear_threats_and_vulnerabilities*), 636

`clone()` (*EgressMatrixCell* method), 176, 692
`clone_matrix_cell()` (*EgressMatrixCell* method), 175, 692
`config()` (*BackupAndRestore* method), 83, 598
`config_backup()` (*BackupAndRestore* method), 82, 598
`Consumer` (class in *ciscoisesdk.api.v3_0_0.consumer*), 121
`Consumer` (class in *ciscoisesdk.api.v3_1_0.consumer*), 637
`content` (*RestResponse* property), 1087
`create()` (*ActiveDirectory* method), 51, 566
`create()` (*AllowedProtocols* method), 61, 577
`create()` (*AncPolicy* method), 67, 583
`create()` (*AuthorizationProfile* method), 75, 591
`create()` (*BackupAndRestore* method), 87, 603
`create()` (*ByodPortal* method), 81, 597
`create()` (*CertificateProfile* method), 92, 608
`create()` (*Consumer* method), 122, 638
`create()` (*DeviceAdministrationAuthenticationRules* method), 125, 641
`create()` (*DeviceAdministrationAuthorizationExceptionRules* method), 129, 646
`create()` (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 134, 650
`create()` (*DeviceAdministrationAuthorizationRules* method), 138, 654
`create()` (*DeviceAdministrationConditions* method), 144, 660
`create()` (*DeviceAdministrationNetworkConditions* method), 156, 672
`create()` (*DeviceAdministrationPolicySet* method), 159, 676
`create()` (*DeviceAdministrationTimeDateConditions* method), 166, 683
`create()` (*DownloadableAcl* method), 174, 690
`create()` (*EgressMatrixCell* method), 181, 697
`create()` (*Endpoint* method), 535, 1051
`create()` (*EndpointCertificate* method), 184, 700
`create()` (*EndpointIdentityGroup* method), 189, 706
`create()` (*ExternalRadiusServer* method), 196, 712
`create()` (*FilterPolicy* method), 200, 717
`create()` (*GuestSntpNotificationConfiguration* method), 209, 726
`create()` (*GuestSsid* method), 214, 731
`create()` (*GuestType* method), 221, 737
`create()` (*GuestUser* method), 235, 751
`create()` (*HotspotPortal* method), 242, 758
`create()` (*IdentityGroups* method), 264, 780
`create()` (*IdentitySequence* method), 269, 785
`create()` (*InternalUser* method), 277, 794
`create()` (*IpToSgtMapping* method), 249, 766
`create()` (*IpToSgtMappingGroup* method), 257, 774
`create()` (*MyDevicePortal* method), 294, 810
`create()` (*NbarApp* method), 1055
`create()` (*NetworkAccessAuthenticationRules* method), 300, 816
`create()` (*NetworkAccessAuthorizationExceptionRules* method), 304, 821
`create()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 309, 825
`create()` (*NetworkAccessAuthorizationRules* method), 313, 829
`create()` (*NetworkAccessConditions* method), 318, 835
`create()` (*NetworkAccessDictionary* method), 327, 844
`create()` (*NetworkAccessDictionaryAttribute* method), 331, 848
`create()` (*NetworkAccessNetworkConditions* method), 338, 854
`create()` (*NetworkAccessPolicySet* method), 342, 858
`create()` (*NetworkAccessTimeDateConditions* method), 349, 865
`create()` (*NetworkDevice* method), 360, 876
`create()` (*NetworkDeviceGroup* method), 367, 883
`create()` (*PortalTheme* method), 389, 905
`create()` (*RadiusServerSequence* method), 407, 923
`create()` (*Repository* method), 417, 933
`create()` (*RestidStore* method), 414, 930
`create()` (*SecurityGroups* method), 453, 969
`create()` (*SecurityGroupsAcls* method), 460, 976
`create()` (*SecurityGroupToVirtualNetwork* method), 446, 962
`create()` (*SelfRegisteredPortal* method), 467, 983
`create()` (*SgVnMapping* method), 1067
`create()` (*SponsoredGuestPortal* method), 490, 1005
`create()` (*SponsorGroup* method), 476, 991
`create()` (*SponsorPortal* method), 484, 999
`create()` (*SupportBundleTriggerConfiguration* method), 495, 1010
`create()` (*SxpConnections* method), 427, 943
`create()` (*SxpLocalBindings* method), 434, 950
`create()` (*SxpVpns* method), 440, 956
`create()` (*SystemCertificate* method), 498, 1013
`create()` (*TacacsCommandSets* method), 503, 1018
`create()` (*TacacsExternalServers* method), 508, 1024
`create()` (*TacacsProfile* method), 513, 1029
`create()` (*TacacsServerSequence* method), 519, 1034
`create()` (*VirtualNetwork* method), 1075
`create()` (*VnVlanMapping* method), 1082
`create_account()` (*Consumer* method), 121, 637
`create_active_directory()` (*ActiveDirectory* method), 50, 565
`create_allowed_protocol()` (*AllowedProtocols* method), 60, 575
`create_anc_policy()` (*AncPolicy* method), 66, 582
`create_authorization_profile()` (*AuthorizationProfile* method), 74, 589
`create_byod_portal()` (*ByodPortal* method), 80, 596

`create_certificate_profile()` (*CertificateProfile method*), 91, 607
`create_device_admin_authentication_rule()` (*DeviceAdministrationAuthenticationRules method*), 124, 640
`create_device_admin_authorization_rule()` (*DeviceAdministrationAuthorizationRules method*), 137, 653
`create_device_admin_condition()` (*DeviceAdministrationConditions method*), 142, 658
`create_device_admin_local_exception_rule()` (*DeviceAdministrationAuthorizationExceptionRules method*), 129, 645
`create_device_admin_network_condition()` (*DeviceAdministrationNetworkConditions method*), 155, 671
`create_device_admin_policy_set()` (*DeviceAdministrationPolicySet method*), 158, 675
`create_device_admin_policy_set_global_exception()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 133, 649
`create_device_admin_time_condition()` (*DeviceAdministrationTimeDateConditions method*), 164, 681
`create_downloadable_acl()` (*DownloadableAcl method*), 173, 689
`create_egress_matrix_cell()` (*EgressMatrixCell method*), 180, 696
`create_endpoint()` (*Endpoint method*), 534, 1050
`create_endpoint_certificate()` (*EndpointCertificate method*), 183, 699
`create_endpoint_group()` (*EndpointIdentityGroup method*), 189, 705
`create_external_radius_server()` (*ExternalRadiusServer method*), 194, 711
`create_filter_policy()` (*FilterPolicy method*), 200, 716
`create_guest_smtp_notification_settings()` (*GuestSmtpNotificationConfiguration method*), 208, 724
`create_guest_ssid()` (*GuestSsid method*), 214, 730
`create_guest_type()` (*GuestType method*), 220, 737
`create_guest_user()` (*GuestUser method*), 234, 750
`create_hotspot_portal()` (*HotspotPortal method*), 241, 757
`create_identity_group()` (*IdentityGroups method*), 263, 779
`create_identity_sequence()` (*IdentitySequence method*), 268, 785
`create_internal_user()` (*InternalUser method*), 276, 793
`create_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 248, 765
`create_ip_to_sgt_mapping_group()` (*IpToSgtMap- pingGroup method*), 256, 773
`create_my_device_portal()` (*MyDevicePortal method*), 293, 810
`create_nbar_app()` (*NbarApp method*), 1055
`create_network_access_authentication_rule()` (*NetworkAccessAuthenticationRules method*), 299, 815
`create_network_access_authorization_rule()` (*NetworkAccessAuthorizationRules method*), 312, 828
`create_network_access_condition()` (*NetworkAccessConditions method*), 316, 833
`create_network_access_dictionaries()` (*NetworkAccessDictionary method*), 327, 843
`create_network_access_dictionary_attribute()` (*NetworkAccessDictionaryAttribute method*), 330, 846
`create_network_access_local_exception_rule()` (*NetworkAccessAuthorizationExceptionRules method*), 304, 820
`create_network_access_network_condition()` (*NetworkAccessNetworkConditions method*), 337, 853
`create_network_access_policy_set()` (*NetworkAccessPolicySet method*), 340, 857
`create_network_access_policy_set_global_exception_rule()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 308, 824
`create_network_access_time_condition()` (*NetworkAccessTimeDateConditions method*), 347, 864
`create_network_device()` (*NetworkDevice method*), 359, 875
`create_network_device_group()` (*NetworkDeviceGroup method*), 367, 883
`create_node_group()` (*NodeGroup method*), 373, 889
`create_portal_theme()` (*PortalTheme method*), 388, 904
`create_radius_server_sequence()` (*RadiusServerSequence method*), 406, 922
`create_repository()` (*Repository method*), 416, 932
`create_rest_id_store()` (*RestidStore method*), 414, 930
`create_scheduled_config_backup()` (*BackupAndRestore method*), 86, 602
`create_security_group()` (*SecurityGroups method*), 452, 968
`create_security_groups_acl()` (*SecurityGroupsAcls method*), 459, 975
`create_security_groups_to_vn_to_vlan()` (*SecurityGroupToVirtualNetwork method*), 446, 961
`create_self_registered_portal()` (*SelfRegisteredPortal method*), 466, 982
`create_sg_vn_mapping()` (*SgVnMapping method*),

1067
 create_sponsor_group() (*SponsorGroup method*), 475, 990
 create_sponsor_portal() (*SponsorPortal method*), 483, 999
 create_sponsored_guest_portal() (*SponsoredGuestPortal method*), 489, 1004
 create_support_bundle() (*SupportBundleTriggerConfiguration method*), 494, 1009
 create_sxp_connections() (*SxpConnections method*), 427, 942
 create_sxp_local_bindings() (*SxpLocalBindings method*), 433, 949
 create_sxp_vpn() (*SxpVpns method*), 439, 955
 create_system_certificate() (*SystemCertificate method*), 497, 1013
 create_tacacs_command_sets() (*TacacsCommandSets method*), 502, 1018
 create_tacacs_external_servers() (*TacacsExternalServers method*), 507, 1023
 create_tacacs_profile() (*TacacsProfile method*), 513, 1028
 create_tacacs_server_sequence() (*TacacsServerSequence method*), 518, 1033
 create_virtual_network() (*VirtualNetwork method*), 1075
 create_vn_vlan_mapping() (*VnVlanMapping method*), 1081
 CustomCaller (*class in ciscoisesdk.api.custom_caller*), 29

D

DEFAULT_BASE_URL (*in module ciscoisesdk.config*), 12
 DEFAULT_DEBUG (*in module ciscoisesdk.config*), 12
 DEFAULT_SINGLE_REQUEST_TIMEOUT (*in module ciscoisesdk.config*), 12
 DEFAULT_USES_API_GATEWAY (*in module ciscoisesdk.config*), 12
 DEFAULT_VERIFY (*in module ciscoisesdk.config*), 12
 DEFAULT_VERSION (*in module ciscoisesdk.config*), 12
 DEFAULT_WAIT_ON_RATE_LIMIT (*in module ciscoisesdk.config*), 12
 delete_active_directory_by_id() (*ActiveDirectory method*), 48, 563
 delete_all_sessions() (*Misc method*), 285, 802
 delete_allowed_protocol_by_id() (*AllowedProtocols method*), 58, 573
 delete_anc_policy_by_id() (*AncPolicy method*), 64, 580
 delete_authorization_profile_by_id() (*AuthorizationProfile method*), 72, 588
 delete_by_id() (*ActiveDirectory method*), 48, 564
 delete_by_id() (*AllowedProtocols method*), 58, 574
 delete_by_id() (*AncPolicy method*), 64, 580
 delete_by_id() (*AuthorizationProfile method*), 73, 588
 delete_by_id() (*ByodPortal method*), 78, 594
 delete_by_id() (*DeviceAdministrationAuthenticationRules method*), 128, 644
 delete_by_id() (*DeviceAdministrationAuthorizationExceptionRules method*), 132, 649
 delete_by_id() (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 136, 653
 delete_by_id() (*DeviceAdministrationAuthorizationRules method*), 140, 657
 delete_by_id() (*DeviceAdministrationConditions method*), 152, 668
 delete_by_id() (*DeviceAdministrationNetworkConditions method*), 158, 674
 delete_by_id() (*DeviceAdministrationPolicySet method*), 162, 679
 delete_by_id() (*DeviceAdministrationTimeDateConditions method*), 170, 686
 delete_by_id() (*DownloadableAcl method*), 172, 688
 delete_by_id() (*EgressMatrixCell method*), 178, 694
 delete_by_id() (*Endpoint method*), 531, 1047
 delete_by_id() (*EndpointIdentityGroup method*), 187, 703
 delete_by_id() (*ExternalRadiusServer method*), 193, 710
 delete_by_id() (*FilterPolicy method*), 198, 715
 delete_by_id() (*GuestSsid method*), 212, 728
 delete_by_id() (*GuestType method*), 218, 735
 delete_by_id() (*GuestUser method*), 231, 748
 delete_by_id() (*HotspotPortal method*), 239, 755
 delete_by_id() (*IdentitySequence method*), 267, 783
 delete_by_id() (*InternalUser method*), 274, 791
 delete_by_id() (*IpToSgtMapping method*), 246, 763
 delete_by_id() (*IpToSgtMappingGroup method*), 254, 771
 delete_by_id() (*MyDevicePortal method*), 291, 808
 delete_by_id() (*NativeSupplicantProfile method*), 296, 813
 delete_by_id() (*NbarApp method*), 1057
 delete_by_id() (*NetworkAccessAuthenticationRules method*), 303, 819
 delete_by_id() (*NetworkAccessAuthorizationExceptionRules method*), 307, 824
 delete_by_id() (*NetworkAccessAuthorizationGlobalExceptionRules method*), 311, 828
 delete_by_id() (*NetworkAccessAuthorizationRules method*), 315, 832
 delete_by_id() (*NetworkAccessConditions method*), 326, 842
 delete_by_id() (*NetworkAccessNetworkConditions method*), 340, 856
 delete_by_id() (*NetworkAccessPolicySet method*), 344, 861
 delete_by_id() (*NetworkAccessTimeDateConditions*

`method`), 352, 868
`delete_by_id()` (*NetworkDevice* method), 357, 873
`delete_by_id()` (*NetworkDeviceGroup* method), 365, 881
`delete_by_id()` (*PortalTheme* method), 386, 902
`delete_by_id()` (*RadiusServerSequence* method), 405, 921
`delete_by_id()` (*RestidStore* method), 412, 928
`delete_by_id()` (*SecurityGroups* method), 450, 966
`delete_by_id()` (*SecurityGroupsAcls* method), 457, 973
`delete_by_id()` (*SecurityGroupToVirtualNetwork* method), 444, 960
`delete_by_id()` (*SelfRegisteredPortal* method), 464, 980
`delete_by_id()` (*SgVnMapping* method), 1071
`delete_by_id()` (*SponsoredGuestPortal* method), 487, 1002
`delete_by_id()` (*SponsorGroup* method), 473, 988
`delete_by_id()` (*SponsorPortal* method), 481, 997
`delete_by_id()` (*SxpConnections* method), 425, 940
`delete_by_id()` (*SxpLocalBindings* method), 431, 947
`delete_by_id()` (*SxpVpns* method), 437, 953
`delete_by_id()` (*TacacsCommandSets* method), 501, 1016
`delete_by_id()` (*TacacsExternalServers* method), 506, 1022
`delete_by_id()` (*TacacsProfile* method), 511, 1027
`delete_by_id()` (*TacacsServerSequence* method), 517, 1032
`delete_by_id()` (*VirtualNetwork* method), 1079
`delete_by_name()` (*DeviceAdministrationConditions* method), 148, 665
`delete_by_name()` (*GuestUser* method), 226, 743
`delete_by_name()` (*InternalUser* method), 272, 788
`delete_by_name()` (*NetworkAccessConditions* method), 322, 839
`delete_by_name()` (*NetworkAccessDictionary* method), 329, 846
`delete_by_name()` (*NetworkAccessDictionaryAttribute* method), 334, 850
`delete_by_name()` (*NetworkDevice* method), 355, 871
`delete_by_name()` (*PxGridNode* method), 542, 1062
`delete_by_name()` (*Repository* method), 419, 935
`delete_by_name()` (*RestidStore* method), 410, 926
`delete_byod_portal_by_id()` (*ByodPortal* method), 78, 593
`delete_csr_by_id()` (*Certificates* method), 101, 617
`delete_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules* method), 127, 644
`delete_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules* method), 140, 656
`delete_device_admin_condition_by_id()` (*DeviceAdministrationConditions* method), 151, 668
`delete_device_admin_condition_by_name()` (*DeviceAdministrationConditions* method), 147, 664
`delete_device_admin_local_exception_rule_by_id()` (*DeviceAdministrationAuthorizationExceptionRules* method), 132, 648
`delete_device_admin_network_condition_by_id()` (*DeviceAdministrationNetworkConditions* method), 157, 674
`delete_device_admin_policy_set_by_id()` (*DeviceAdministrationPolicySet* method), 162, 678
`delete_device_admin_policy_set_global_exception_by_rule_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 136, 652
`delete_device_admin_time_condition_by_id()` (*DeviceAdministrationTimeDateConditions* method), 169, 685
`delete_downloadable_acl_by_id()` (*DownloadableAcl* method), 171, 687
`delete_egress_matrix_cell_by_id()` (*EgressMatrixCell* method), 177, 694
`delete_endpoint_by_id()` (*Endpoint* method), 531, 1046
`delete_endpoint_group_by_id()` (*EndpointIdentityGroup* method), 186, 703
`delete_external_radius_server_by_id()` (*ExternalRadiusServer* method), 193, 709
`delete_filter_policy_by_id()` (*FilterPolicy* method), 198, 714
`delete_guest_ssid_by_id()` (*GuestSsid* method), 211, 728
`delete_guest_type_by_id()` (*GuestType* method), 218, 734
`delete_guest_user_by_id()` (*GuestUser* method), 231, 747
`delete_guest_user_by_name()` (*GuestUser* method), 226, 742
`delete_hotspot_portal_by_id()` (*HotspotPortal* method), 239, 755
`delete_identity_sequence_by_id()` (*IdentitySequence* method), 266, 783
`delete_internal_user_by_id()` (*InternalUser* method), 274, 790
`delete_internal_user_by_name()` (*InternalUser* method), 271, 788
`delete_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping* method), 246, 762
`delete_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup* method), 254, 770
`delete_my_device_portal_by_id()` (*MyDevicePor-*

`tal method)`, 291, 807
`delete_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile method*), 296, 813
`delete_nbar_app_by_id()` (*NbarApp method*), 1057
`delete_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules method*), 302, 819
`delete_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules method*), 315, 831
`delete_network_access_condition_by_id()` (*NetworkAccessConditions method*), 325, 842
`delete_network_access_condition_by_name()` (*NetworkAccessConditions method*), 322, 838
`delete_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute method*), 333, 849
`delete_network_access_dictionary_by_name()` (*NetworkAccessDictionary method*), 329, 845
`delete_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 306, 823
`delete_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions method*), 339, 855
`delete_network_access_policy_set_by_id()` (*NetworkAccessPolicySet method*), 344, 860
`delete_network_access_policy_set_global_exception_rule_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 311, 827
`delete_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions method*), 352, 868
`delete_network_device_by_id()` (*NetworkDevice method*), 357, 873
`delete_network_device_by_name()` (*NetworkDevice method*), 354, 870
`delete_network_device_group_by_id()` (*NetworkDeviceGroup method*), 364, 880
`delete_node()` (*NodeDeployment method*), 371, 887
`delete_node_group()` (*NodeGroup method*), 374, 890
`delete_portal_theme_by_id()` (*PortalTheme method*), 386, 902
`delete_px_grid_node_by_name()` (*PxGridNode method*), 542, 1062
`delete_radius_server_sequence_by_id()` (*RadiusServerSequence method*), 404, 920
`delete_repository()` (*Repository method*), 419, 935
`delete_rest_id_store_by_id()` (*RestidStore method*), 411, 927
`delete_rest_id_store_by_name()` (*RestidStore method*), 409, 925
`delete_security_group_by_id()` (*SecurityGroups method*), 450, 966
`delete_security_groups_acl_by_id()` (*SecurityGroupsAcls method*), 457, 972
`delete_security_groups_to_vn_to_vlan_by_id()` (*SecurityGroupToVirtualNetwork method*), 443, 959
`delete_self_registered_portal_by_id()` (*SelfRegisteredPortal method*), 463, 979
`delete_sg_vn_mapping_by_id()` (*SgVnMapping method*), 1071
`delete_sponsor_group_by_id()` (*SponsorGroup method*), 472, 988
`delete_sponsor_portal_by_id()` (*SponsorPortal method*), 481, 996
`delete_sponsored_guest_portal_by_id()` (*SponsoredGuestPortal method*), 486, 1002
`delete_sxp_connections_by_id()` (*SxpConnections method*), 424, 940
`delete_sxp_local_bindings_by_id()` (*SxpLocalBindings method*), 431, 947
`delete_sxp_vpn_by_id()` (*SxpVpns method*), 437, 953
`delete_system_certificate_by_id()` (*Certificates method*), 111, 627
`delete_tacacs_command_sets_by_id()` (*TacacsCommandSets method*), 500, 1016
`delete_tacacs_external_servers_by_id()` (*TacacsExternalServers method*), 506, 1021
`delete_tacacs_profile_by_id()` (*TacacsProfile method*), 511, 1026
`delete_tacacs_server_sequence_by_id()` (*TacacsServerSequence method*), 516, 1032
`delete_trusted_certificate_by_id()` (*Certificates method*), 119, 635
`delete_virtual_network_by_id()` (*VirtualNetwork method*), 1079
`delete_vn_vlan_mapping_by_id()` (*VnVlanMapping method*), 1085
`deny_by_id()` (*GuestUser method*), 229, 746
`deny_guest_user_by_id()` (*GuestUser method*), 229, 745
`deploy_all()` (*IpToSgtMapping method*), 244, 760
`deploy_all_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 243, 760
`deploy_all_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup method*), 252, 768
`deploy_by_id()` (*IpToSgtMapping method*), 243, 760
`deploy_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping method*), 243, 759
`deploy_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup method*), 251, 768
`deregister()` (*Endpoint method*), 528, 1043
`deregister_endpoint()` (*Endpoint method*), 527, 1043
`description` (*ApiError attribute*), 1087
`details` (*ApiError attribute*), 1087

[details_str \(ApiError attribute\), 1087](#)
[DeviceAdministrationAuthenticationRules](#) (class in [ciscoesdk.api.v3_0_0.device_administration_identity_stores](#)), 154
[DeviceAdministrationAuthenticationRules](#) (class in [ciscoesdk.api.v3_1_0.device_administration_identity_stores](#)), 670
[DeviceAdministrationAuthenticationRules](#) (class in [ciscoesdk.api.v3_0_0.device_administration_network_conditions](#)), 154
[DeviceAdministrationAuthenticationRules](#) (class in [ciscoesdk.api.v3_1_0.device_administration_network_conditions](#)), 671
[DeviceAdministrationAuthorizationExceptionRules](#) (class in [ciscoesdk.api.v3_0_0.device_administration_policy_set](#)), 132
[DeviceAdministrationAuthorizationExceptionRules](#) (class in [ciscoesdk.api.v3_1_0.device_administration_policy_set](#)), 674
[DeviceAdministrationAuthorizationGlobalExceptionRules](#) (class in [ciscoesdk.api.v3_0_0.device_administration_profiles](#)), 132
[DeviceAdministrationAuthorizationGlobalExceptionRules](#) (class in [ciscoesdk.api.v3_1_0.device_administration_profiles](#)), 679
[DeviceAdministrationAuthorizationRules](#) (class in [ciscoesdk.api.v3_0_0.device_administration_service_names](#)), 136
[DeviceAdministrationAuthorizationRules](#) (class in [ciscoesdk.api.v3_1_0.device_administration_service_names](#)), 653
[DeviceAdministrationCommandSet](#) (class in [ciscoesdk.api.v3_0_0.device_administration_service_names](#)), 141
[DeviceAdministrationCommandSet](#) (class in [ciscoesdk.api.v3_1_0.device_administration_service_names](#)), 657
[DeviceAdministrationConditions](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 141
[DeviceAdministrationConditions](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 658
[DeviceAdministrationDictionaryAttributesList](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 152
[DeviceAdministrationDictionaryAttributesList](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 668
[DeviceAdministrationIdentityStores](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 152
[DeviceAdministrationIdentityStores](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 668
[DeviceAdministrationNetworkConditions](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 154
[DeviceAdministrationNetworkConditions](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 671
[DeviceAdministrationPolicySet](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 132
[DeviceAdministrationPolicySet](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 674
[DeviceAdministrationProfiles](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 132
[DeviceAdministrationProfiles](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 679
[DeviceAdministrationServiceNames](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 136
[DeviceAdministrationServiceNames](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 653
[DeviceAdministrationTimeDateConditions](#) (class in [ciscoesdk.api.v3_0_0.device_administration_time_date_conditions](#)), 141
[DeviceAdministrationTimeDateConditions](#) (class in [ciscoesdk.api.v3_1_0.device_administration_time_date_conditions](#)), 658
[Disable_pan_ha\(\) \(PanHa method\), 380, 896](#)
[download\(\) \(SupportBundleDownload method\), 491, 1006](#)
[download_support_bundle\(\) \(SupportBundleDownload method\), 490, 1006](#)
[DownloadableAcl](#) (class in [ciscoesdk.api.v3_0_0.downloadable_acl](#)), 170
[DownloadableAcl](#) (class in [ciscoesdk.api.v3_1_0.downloadable_acl](#)), 686
[DownloadFailure, 1088](#)

E

EgressMatrixCell (class in *ciscoisesdk.api.v3_0_0.egress_matrix_cell*), 174

EgressMatrixCell (class in *ciscoisesdk.api.v3_1_0.egress_matrix_cell*), 691

enable_pan_ha() (*PanHa* method), 379, 895

Endpoint (class in *ciscoisesdk.api.v3_0_0.endpoint*), 527

Endpoint (class in *ciscoisesdk.api.v3_1_0.endpoint*), 1042

EndpointCertificate (class in *ciscoisesdk.api.v3_0_0.endpoint_certificate*), 183

EndpointCertificate (class in *ciscoisesdk.api.v3_1_0.endpoint_certificate*), 699

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_0_0.endpoint_identity_group*), 184

EndpointIdentityGroup (class in *ciscoisesdk.api.v3_1_0.endpoint_identity_group*), 701

ers_base_url (*IdentityServicesEngineAPI* property), 28

ERS_BASE_URL_ENVIRONMENT_VARIABLE (in module *ciscoisesdk.config*), 12

export_csr() (*Certificates* method), 99, 615

export_system_certificate() (*Certificates* method), 104, 620

export_trusted_certificate() (*Certificates* method), 114, 630

ExternalRadiusServer (class in *ciscoisesdk.api.v3_0_0.external_radius_server*), 190

ExternalRadiusServer (class in *ciscoisesdk.api.v3_1_0.external_radius_server*), 707

F

FilterPolicy (class in *ciscoisesdk.api.v3_0_0.filter_policy*), 197

FilterPolicy (class in *ciscoisesdk.api.v3_1_0.filter_policy*), 713

G

generate_csr() (*Certificates* method), 98, 613

generate_intermediate_ca_csr() (*Certificates* method), 100, 616

get() (*MyDict* method), 1086

get_account_status_by_mac() (*Misc* method), 288, 805

get_aci_bindings() (*AciBindings* method), 30, 546

get_aci_bindings_generator() (*AciBindings* method), 31, 547

get_aci_settings() (*AciSettings* method), 32, 548

get_active_count() (*Misc* method), 280, 797

get_active_directory() (*ActiveDirectory* method), 49, 564

get_active_directory_by_id() (*ActiveDirectory* method), 47, 563

get_active_directory_by_name() (*ActiveDirectory* method), 41, 557

get_active_directory_generator() (*ActiveDirectory* method), 49, 565

get_active_list() (*Misc* method), 281, 797

get_admin_user_by_id() (*AdminUser* method), 52, 567

get_admin_users() (*AdminUser* method), 52, 568

get_admin_users_generator() (*AdminUser* method), 53, 569

get_all() (*AciBindings* method), 31, 547

get_all() (*AciSettings* method), 33, 549

get_all() (*ActiveDirectory* method), 49, 565

get_all() (*AdminUser* method), 53, 569

get_all() (*AllowedProtocols* method), 59, 574

get_all() (*AncEndpoint* method), 38, 553

get_all() (*AncPolicy* method), 65, 581

get_all() (*AuthorizationProfile* method), 73, 589

get_all() (*ByodPortal* method), 79, 595

get_all() (*CertificateProfile* method), 90, 606

get_all() (*CertificateTemplate* method), 95, 610

get_all() (*DeviceAdministrationAuthenticationRules* method), 124, 640

get_all() (*DeviceAdministrationAuthorizationExceptionRules* method), 129, 645

get_all() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 133, 649

get_all() (*DeviceAdministrationAuthorizationRules* method), 137, 653

get_all() (*DeviceAdministrationCommandSet* method), 141, 658

get_all() (*DeviceAdministrationConditions* method), 142, 658

get_all() (*DeviceAdministrationIdentityStores* method), 154, 671

get_all() (*DeviceAdministrationNetworkConditions* method), 155, 671

get_all() (*DeviceAdministrationPolicySet* method), 158, 675

get_all() (*DeviceAdministrationProfiles* method), 163, 679

get_all() (*DeviceAdministrationServiceNames* method), 164, 680

get_all() (*DeviceAdministrationTimeDateConditions* method), 164, 681

get_all() (*DownloadableAcl* method), 172, 688

get_all() (*EgressMatrixCell* method), 179, 695

get_all() (*Endpoint* method), 533, 1049

get_all() (*EndpointIdentityGroup* method), 188, 704

get_all() (*ExternalRadiusServer* method), 194, 710

- `get_all()` (*FilterPolicy* method), 199, 715
- `get_all()` (*GuestLocation* method), 203, 719
- `get_all()` (*GuestSntpNotificationConfiguration* method), 207, 723
- `get_all()` (*GuestSsid* method), 213, 729
- `get_all()` (*GuestType* method), 219, 736
- `get_all()` (*GuestUser* method), 232, 749
- `get_all()` (*HotspotPortal* method), 240, 756
- `get_all()` (*IdentityGroups* method), 262, 778
- `get_all()` (*IdentitySequence* method), 267, 784
- `get_all()` (*InternalUser* method), 275, 792
- `get_all()` (*IpToSgtMapping* method), 247, 764
- `get_all()` (*IpToSgtMappingGroup* method), 255, 772
- `get_all()` (*Mdm* method), 279, 795
- `get_all()` (*MyDevicePortal* method), 292, 809
- `get_all()` (*NativeSupplicantProfile* method), 297, 814
- `get_all()` (*NbarApp* method), 1054
- `get_all()` (*NetworkAccessAuthenticationRules* method), 299, 815
- `get_all()` (*NetworkAccessAuthorizationExceptionRules* method), 303, 820
- `get_all()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 308, 824
- `get_all()` (*NetworkAccessAuthorizationRules* method), 312, 828
- `get_all()` (*NetworkAccessConditions* method), 316, 833
- `get_all()` (*NetworkAccessDictionary* method), 327, 843
- `get_all()` (*NetworkAccessDictionaryAttribute* method), 330, 846
- `get_all()` (*NetworkAccessIdentityStores* method), 336, 852
- `get_all()` (*NetworkAccessNetworkConditions* method), 337, 853
- `get_all()` (*NetworkAccessPolicySet* method), 340, 857
- `get_all()` (*NetworkAccessProfiles* method), 345, 861
- `get_all()` (*NetworkAccessSecurityGroups* method), 346, 862
- `get_all()` (*NetworkAccessServiceNames* method), 347, 863
- `get_all()` (*NetworkAccessTimeDateConditions* method), 347, 863
- `get_all()` (*NetworkDevice* method), 358, 874
- `get_all()` (*NetworkDeviceGroup* method), 366, 882
- `get_all()` (*NodeDeployment* method), 370, 886
- `get_all()` (*NodeDetails* method), 377, 893
- `get_all()` (*Portal* method), 539, 1059
- `get_all()` (*PortalGlobalSetting* method), 383, 899
- `get_all()` (*PortalTheme* method), 387, 903
- `get_all()` (*ProfilerProfile* method), 392, 908
- `get_all()` (*PsnNodeDetailsWithRadiusService* method), 398, 914
- `get_all()` (*PullDeploymentInfo* method), 399, 915
- `get_all()` (*PxGridNode* method), 543, 1064
- `get_all()` (*RadiusServerSequence* method), 405, 921
- `get_all()` (*Repository* method), 416, 932
- `get_all()` (*RestidStore* method), 412, 928
- `get_all()` (*SecurityGroups* method), 451, 967
- `get_all()` (*SecurityGroupsAcls* method), 458, 974
- `get_all()` (*SecurityGroupToVirtualNetwork* method), 445, 960
- `get_all()` (*SelfRegisteredPortal* method), 465, 981
- `get_all()` (*SgVnMapping* method), 1066
- `get_all()` (*SmsProvider* method), 421, 937
- `get_all()` (*SponsoredGuestPortal* method), 488, 1003
- `get_all()` (*SponsorGroup* method), 474, 989
- `get_all()` (*SponsorGroupMember* method), 478, 993
- `get_all()` (*SponsorPortal* method), 482, 998
- `get_all()` (*SupportBundleStatus* method), 493, 1008
- `get_all()` (*SxpConnections* method), 426, 941
- `get_all()` (*SxpLocalBindings* method), 432, 948
- `get_all()` (*SxpVpns* method), 438, 954
- `get_all()` (*TacacsCommandSets* method), 502, 1017
- `get_all()` (*TacacsExternalServers* method), 507, 1022
- `get_all()` (*TacacsProfile* method), 512, 1027
- `get_all()` (*TacacsServerSequence* method), 517, 1033
- `get_all()` (*TelemetryInformation* method), 521, 1036
- `get_all()` (*TrustSecConfiguration* method), 523, 1039
- `get_all()` (*VersionAndPatch* method), 526, 1041
- `get_all()` (*VirtualNetwork* method), 1074
- `get_all()` (*VnVlanMapping* method), 1080
- `get_all_authentication()` (*DeviceAdministrationDictionaryAttributesList* method), 152, 669
- `get_all_authentication()` (*NetworkAccessDictionaryAttributesList* method), 334, 851
- `get_all_authentication_rules()` (*DeviceAdministrationConditions* method), 144, 661
- `get_all_authorization()` (*DeviceAdministrationDictionaryAttributesList* method), 153, 669
- `get_all_authorization()` (*NetworkAccessDictionaryAttributesList* method), 335, 851
- `get_all_authorization_rules()` (*DeviceAdministrationConditions* method), 145, 662
- `get_all_for_policy_sets()` (*DeviceAdministrationConditions* method), 149, 665
- `get_all_for_policy_sets()` (*NetworkAccessConditions* method), 323, 839
- `get_all_generator()` (*AciBindings* method), 32, 547
- `get_all_generator()` (*ActiveDirectory* method), 50, 565
- `get_all_generator()` (*AdminUser* method), 54, 570
- `get_all_generator()` (*AllowedProtocols* method), 59, 575
- `get_all_generator()` (*AncEndpoint* method), 39, 554
- `get_all_generator()` (*AncPolicy* method), 66, 582
- `get_all_generator()` (*AuthorizationProfile* method), 74, 589

`get_all_generator()` (*ByodPortal method*), 80, 596
`get_all_generator()` (*CertificateProfile method*), 91, 607
`get_all_generator()` (*CertificateTemplate method*), 95, 611
`get_all_generator()` (*DownloadableAcl method*), 173, 689
`get_all_generator()` (*EgressMatrixCell method*), 180, 696
`get_all_generator()` (*Endpoint method*), 534, 1050
`get_all_generator()` (*EndpointIdentityGroup method*), 189, 705
`get_all_generator()` (*ExternalRadiusServer method*), 194, 711
`get_all_generator()` (*FilterPolicy method*), 200, 716
`get_all_generator()` (*GuestLocation method*), 204, 720
`get_all_generator()` (*GuestSmtNotificationConfiguration method*), 208, 724
`get_all_generator()` (*GuestSsid method*), 214, 730
`get_all_generator()` (*GuestType method*), 220, 737
`get_all_generator()` (*GuestUser method*), 234, 750
`get_all_generator()` (*HotspotPortal method*), 241, 757
`get_all_generator()` (*IdentityGroups method*), 263, 779
`get_all_generator()` (*IdentitySequence method*), 268, 784
`get_all_generator()` (*InternalUser method*), 276, 793
`get_all_generator()` (*IpToSgtMapping method*), 248, 765
`get_all_generator()` (*IpToSgtMappingGroup method*), 256, 773
`get_all_generator()` (*MyDevicePortal method*), 293, 810
`get_all_generator()` (*NativeSupplicantProfile method*), 298, 814
`get_all_generator()` (*NbarApp method*), 1055
`get_all_generator()` (*NetworkDevice method*), 359, 875
`get_all_generator()` (*NetworkDeviceGroup method*), 367, 883
`get_all_generator()` (*NodeDetails method*), 378, 894
`get_all_generator()` (*Portal method*), 540, 1060
`get_all_generator()` (*PortalGlobalSetting method*), 384, 900
`get_all_generator()` (*PortalTheme method*), 388, 904
`get_all_generator()` (*ProfilerProfile method*), 393, 909
`get_all_generator()` (*PsnNodeDetailsWithRadiusService method*), 398, 914
`get_all_generator()` (*PxGridNode method*), 544, 1064
`get_all_generator()` (*RadiusServerSequence method*), 406, 922
`get_all_generator()` (*RestidStore method*), 413, 929
`get_all_generator()` (*SecurityGroups method*), 452, 968
`get_all_generator()` (*SecurityGroupsAcls method*), 459, 975
`get_all_generator()` (*SecurityGroupToVirtualNetwork method*), 446, 961
`get_all_generator()` (*SelfRegisteredPortal method*), 466, 982
`get_all_generator()` (*SgVnMapping method*), 1067
`get_all_generator()` (*SmsProvider method*), 422, 938
`get_all_generator()` (*SponsoredGuestPortal method*), 489, 1004
`get_all_generator()` (*SponsorGroup method*), 475, 990
`get_all_generator()` (*SponsorGroupMember method*), 479, 994
`get_all_generator()` (*SponsorPortal method*), 483, 999
`get_all_generator()` (*SupportBundleStatus method*), 493, 1009
`get_all_generator()` (*SxpConnections method*), 427, 942
`get_all_generator()` (*SxpLocalBindings method*), 433, 949
`get_all_generator()` (*SxpVpns method*), 439, 955
`get_all_generator()` (*TacacsCommandSets method*), 502, 1018
`get_all_generator()` (*TacacsExternalServers method*), 507, 1023
`get_all_generator()` (*TacacsProfile method*), 512, 1028
`get_all_generator()` (*TacacsServerSequence method*), 518, 1033
`get_all_generator()` (*TelemetryInformation method*), 522, 1037
`get_all_generator()` (*VirtualNetwork method*), 1075
`get_all_generator()` (*VnVlanMapping method*), 1081
`get_all_policy_set()` (*DeviceAdministrationDictionaryAttributesList method*), 153, 670
`get_all_policy_set()` (*NetworkAccessDictionaryAttributesList method*), 335, 852
`get_allowed_protocol_by_id()` (*AllowedProtocols method*), 55, 571
`get_allowed_protocol_by_name()` (*AllowedProtocols method*), 55, 570
`get_allowed_protocols()` (*AllowedProtocols method*), 58, 574
`get_allowed_protocols_generator()` (*AllowedProtocols method*), 59, 574
`get_anc_endpoint()` (*AncEndpoint method*), 37, 553
`get_anc_endpoint_by_id()` (*AncEndpoint method*),

36, 551

`get_anc_endpoint_generator()` (*AncEndpoint method*), 38, 553

`get_anc_policy()` (*AncPolicy method*), 64, 580

`get_anc_policy_by_id()` (*AncPolicy method*), 63, 578

`get_anc_policy_by_name()` (*AncPolicy method*), 62, 578

`get_anc_policy_generator()` (*AncPolicy method*), 65, 581

`get_authentication_status_by_mac()` (*Misc method*), 287, 803

`get_authorization_profile_by_id()` (*AuthorizationProfile method*), 70, 585

`get_authorization_profile_by_name()` (*AuthorizationProfile method*), 69, 585

`get_authorization_profiles()` (*AuthorizationProfile method*), 73, 588

`get_authorization_profiles_generator()` (*AuthorizationProfile method*), 73, 589

`get_bindings()` (*TrustSecSxp method*), 525, 1040

`get_by_id()` (*ActiveDirectory method*), 48, 563

`get_by_id()` (*AdminUser method*), 52, 568

`get_by_id()` (*AllowedProtocols method*), 56, 571

`get_by_id()` (*AncEndpoint method*), 36, 552

`get_by_id()` (*AncPolicy method*), 63, 579

`get_by_id()` (*AuthorizationProfile method*), 70, 586

`get_by_id()` (*ByodPortal method*), 77, 592

`get_by_id()` (*CertificateProfile method*), 89, 604

`get_by_id()` (*CertificateTemplate method*), 94, 610

`get_by_id()` (*DeviceAdministrationAuthenticationRules method*), 126, 643

`get_by_id()` (*DeviceAdministrationAuthorizationExceptionRules method*), 131, 647

`get_by_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 135, 651

`get_by_id()` (*DeviceAdministrationAuthorizationRules method*), 139, 655

`get_by_id()` (*DeviceAdministrationConditions method*), 149, 666

`get_by_id()` (*DeviceAdministrationNetworkConditions method*), 156, 673

`get_by_id()` (*DeviceAdministrationPolicySet method*), 160, 677

`get_by_id()` (*DeviceAdministrationTimeDateConditions method*), 167, 683

`get_by_id()` (*DownloadableAcl method*), 170, 686

`get_by_id()` (*EgressMatrixCell method*), 176, 693

`get_by_id()` (*Endpoint method*), 529, 1045

`get_by_id()` (*EndpointIdentityGroup method*), 185, 702

`get_by_id()` (*ExternalRadiusServer method*), 191, 708

`get_by_id()` (*FilterPolicy method*), 197, 713

`get_by_id()` (*GuestLocation method*), 202, 718

`get_by_id()` (*GuestSmtipNotificationConfiguration method*), 205, 721

`get_by_id()` (*GuestSsid method*), 210, 727

`get_by_id()` (*GuestType method*), 217, 733

`get_by_id()` (*GuestUser method*), 230, 746

`get_by_id()` (*HotspotPortal method*), 238, 754

`get_by_id()` (*IdentityGroups method*), 260, 777

`get_by_id()` (*IdentitySequence method*), 265, 782

`get_by_id()` (*InternalUser method*), 272, 789

`get_by_id()` (*IpToSgtMapping method*), 245, 761

`get_by_id()` (*IpToSgtMappingGroup method*), 253, 770

`get_by_id()` (*MyDevicePortal method*), 290, 806

`get_by_id()` (*NativeSupplicantProfile method*), 295, 812

`get_by_id()` (*NbarApp method*), 1056

`get_by_id()` (*NetworkAccessAuthenticationRules method*), 301, 818

`get_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 306, 822

`get_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 310, 826

`get_by_id()` (*NetworkAccessAuthorizationRules method*), 314, 830

`get_by_id()` (*NetworkAccessConditions method*), 323, 840

`get_by_id()` (*NetworkAccessNetworkConditions method*), 338, 854

`get_by_id()` (*NetworkAccessPolicySet method*), 343, 859

`get_by_id()` (*NetworkAccessTimeDateConditions method*), 350, 866

`get_by_id()` (*NetworkDevice method*), 355, 871

`get_by_id()` (*NetworkDeviceGroup method*), 363, 879

`get_by_id()` (*NodeDetails method*), 376, 892

`get_by_id()` (*Portal method*), 538, 1058

`get_by_id()` (*PortalGlobalSetting method*), 381, 897

`get_by_id()` (*PortalTheme method*), 385, 901

`get_by_id()` (*ProfilerProfile method*), 391, 907

`get_by_id()` (*PsnNodeDetailsWithRadiusService method*), 397, 913

`get_by_id()` (*PxGridNode method*), 543, 1063

`get_by_id()` (*RadiusServerSequence method*), 403, 919

`get_by_id()` (*RestidStore method*), 410, 926

`get_by_id()` (*SecurityGroups method*), 449, 965

`get_by_id()` (*SecurityGroupsAcls method*), 456, 971

`get_by_id()` (*SecurityGroupToVirtualNetwork method*), 442, 958

`get_by_id()` (*SelfRegisteredPortal method*), 462, 978

`get_by_id()` (*SgVnMapping method*), 1070

`get_by_id()` (*SponsoredGuestPortal method*), 485, 1001

`get_by_id()` (*SponsorGroup method*), 471, 987

`get_by_id()` (*SponsorPortal method*), 480, 995

`get_by_id()` (*SupportBundleStatus method*), 492, 1007

`get_by_id()` (*SxpConnections method*), 423, 939

`get_by_id()` (*SxpLocalBindings method*), 430, 946

`get_by_id()` (*SxpVpns method*), 437, 953
`get_by_id()` (*TacacsCommandSets method*), 500, 1015
`get_by_id()` (*TacacsExternalServers method*), 505, 1020
`get_by_id()` (*TacacsProfile method*), 510, 1025
`get_by_id()` (*TacacsServerSequence method*), 515, 1030
`get_by_id()` (*TelemetryInformation method*), 520, 1036
`get_by_id()` (*VirtualNetwork method*), 1078
`get_by_id()` (*VnVlanMapping method*), 1084
`get_by_name()` (*ActiveDirectory method*), 42, 557
`get_by_name()` (*AllowedProtocols method*), 55, 571
`get_by_name()` (*AncPolicy method*), 62, 578
`get_by_name()` (*AuthorizationProfile method*), 70, 585
`get_by_name()` (*CertificateProfile method*), 88, 604
`get_by_name()` (*CertificateTemplate method*), 93, 609
`get_by_name()` (*DeviceAdministrationConditions method*), 145, 662
`get_by_name()` (*Endpoint method*), 529, 1044
`get_by_name()` (*EndpointIdentityGroup method*), 185, 701
`get_by_name()` (*ExternalRadiusServer method*), 191, 707
`get_by_name()` (*GuestUser method*), 225, 741
`get_by_name()` (*IdentityGroups method*), 260, 776
`get_by_name()` (*IdentitySequence method*), 265, 781
`get_by_name()` (*InternalUser method*), 270, 787
`get_by_name()` (*NetworkAccessConditions method*), 320, 836
`get_by_name()` (*NetworkAccessDictionary method*), 328, 844
`get_by_name()` (*NetworkAccessDictionaryAttribute method*), 332, 848
`get_by_name()` (*NetworkDevice method*), 353, 869
`get_by_name()` (*NetworkDeviceGroup method*), 363, 879
`get_by_name()` (*NodeDetails method*), 375, 891
`get_by_name()` (*PsnNodeDetailsWithRadiusService method*), 396, 912
`get_by_name()` (*PxGridNode method*), 542, 1062
`get_by_name()` (*Repository method*), 418, 934
`get_by_name()` (*RestidStore method*), 408, 924
`get_by_name()` (*SessionDirectory method*), 470, 986
`get_by_name()` (*TacacsCommandSets method*), 499, 1015
`get_by_name()` (*TacacsExternalServers method*), 504, 1020
`get_by_name()` (*TacacsProfile method*), 509, 1025
`get_by_name()` (*TacacsServerSequence method*), 514, 1030
`get_byod_portal()` (*ByodPortal method*), 78, 594
`get_byod_portal_by_id()` (*ByodPortal method*), 76, 592
`get_byod_portal_generator()` (*ByodPortal method*), 79, 595
`get_certificate_profile()` (*CertificateProfile method*), 90, 606
`get_certificate_profile_by_id()` (*CertificateProfile method*), 88, 604
`get_certificate_profile_by_name()` (*CertificateProfile method*), 88, 603
`get_certificate_profile_generator()` (*CertificateProfile method*), 90, 606
`get_certificate_template()` (*CertificateTemplate method*), 94, 610
`get_certificate_template_by_id()` (*CertificateTemplate method*), 93, 609
`get_certificate_template_by_name()` (*CertificateTemplate method*), 93, 609
`get_certificate_template_generator()` (*CertificateTemplate method*), 95, 610
`get_csr_by_id()` (*Certificates method*), 100, 616
`get_csrs()` (*Certificates method*), 96, 612
`get_csrs_generator()` (*Certificates method*), 97, 613
`get_deploy_status()` (*IpToSgtMapping method*), 244, 761
`get_deploy_status_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 244, 760
`get_deploy_status_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup method*), 252, 769
`get_deployment_info()` (*PullDeploymentInfo method*), 399, 915
`get_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules method*), 126, 642
`get_device_admin_authentication_rules()` (*DeviceAdministrationAuthenticationRules method*), 124, 640
`get_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules method*), 138, 655
`get_device_admin_authorization_rules()` (*DeviceAdministrationAuthorizationRules method*), 136, 653
`get_device_admin_command_sets()` (*DeviceAdministrationCommandSet method*), 141, 657
`get_device_admin_condition_by_id()` (*DeviceAdministrationConditions method*), 149, 665
`get_device_admin_condition_by_name()` (*DeviceAdministrationConditions method*), 145, 662
`get_device_admin_conditions()` (*DeviceAdministrationConditions method*), 141, 658
`get_device_admin_conditions_for_authentication_rules()` (*DeviceAdministrationConditions method*), 144, 661
`get_device_admin_conditions_for_authorization_rules()`

(*DeviceAdministrationConditions method*), 144, 661
 get_device_admin_conditions_for_policy_sets() (*DeviceAdministrationConditions method*), 148, 665
 get_device_admin_dictionaries_authentication() (*DeviceAdministrationDictionaryAttributesList method*), 152, 668
 get_device_admin_dictionaries_authorization() (*DeviceAdministrationDictionaryAttributesList method*), 152, 669
 get_device_admin_dictionaries_policy_set() (*DeviceAdministrationDictionaryAttributesList method*), 153, 669
 get_device_admin_identity_stores() (*DeviceAdministrationIdentityStores method*), 154, 670
 get_device_admin_local_exception_rule_by_id() (*DeviceAdministrationAuthorizationExceptionRules method*), 130, 647
 get_device_admin_local_exception_rules() (*DeviceAdministrationAuthorizationExceptionRules method*), 128, 645
 get_device_admin_network_condition_by_id() (*DeviceAdministrationNetworkConditions method*), 156, 672
 get_device_admin_network_conditions() (*DeviceAdministrationNetworkConditions method*), 154, 671
 get_device_admin_policy_set_by_id() (*DeviceAdministrationPolicySet method*), 160, 677
 get_device_admin_policy_set_global_exception_by_rule_id() (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 134, 651
 get_device_admin_policy_set_global_exception_rules() (*DeviceAdministrationAuthorizationGlobalExceptionRules method*), 132, 649
 get_device_admin_policy_sets() (*DeviceAdministrationPolicySet method*), 158, 674
 get_device_admin_profiles() (*DeviceAdministrationProfiles method*), 162, 679
 get_device_admin_service_names() (*DeviceAdministrationServiceNames method*), 163, 680
 get_device_admin_time_condition_by_id() (*DeviceAdministrationTimeDateConditions method*), 166, 683
 get_device_admin_time_conditions() (*DeviceAdministrationTimeDateConditions method*), 164, 680
 get_downloadable_acl() (*DownloadableAcl method*), 172, 688
 get_downloadable_acl_by_id() (*DownloadableAcl method*), 170, 686
 get_downloadable_acl_generator() (*DownloadableAcl method*), 172, 688
 get_egress_matrices() (*TrustSecConfiguration method*), 524, 1040
 get_egress_matrix_cell() (*EgressMatrixCell method*), 178, 694
 get_egress_matrix_cell_by_id() (*EgressMatrixCell method*), 176, 692
 get_egress_matrix_cell_generator() (*EgressMatrixCell method*), 179, 695
 get_egress_policies() (*TrustSecConfiguration method*), 524, 1039
 get_endpoint_by_id() (*Endpoint method*), 529, 1044
 get_endpoint_by_mac_address() (*Mdm method*), 279, 795
 get_endpoint_by_name() (*Endpoint method*), 528, 1044
 get_endpoint_group_by_id() (*EndpointIdentityGroup method*), 185, 701
 get_endpoint_group_by_name() (*EndpointIdentityGroup method*), 184, 701
 get_endpoint_groups() (*EndpointIdentityGroup method*), 187, 703
 get_endpoint_groups_generator() (*EndpointIdentityGroup method*), 188, 704
 get_endpoints() (*Endpoint method*), 532, 1048
 get_endpoints() (*Mdm method*), 278, 795
 get_endpoints_by_os_type() (*Mdm method*), 280, 796
 get_endpoints_by_type() (*Mdm method*), 279, 796
 get_endpoints_generator() (*Endpoint method*), 533, 1049
 get_external_radius_server() (*ExternalRadiusServer method*), 193, 710
 get_external_radius_server_by_id() (*ExternalRadiusServer method*), 191, 707
 get_external_radius_server_by_name() (*ExternalRadiusServer method*), 190, 707
 get_external_radius_server_generator() (*ExternalRadiusServer method*), 194, 710
 get_failure_reasons() (*Misc method*), 286, 803
 get_failures() (*RadiusFailure method*), 401, 917
 get_files() (*Repository method*), 420, 936
 get_filter_policy() (*FilterPolicy method*), 199, 715
 get_filter_policy_by_id() (*FilterPolicy method*), 197, 713
 get_filter_policy_generator() (*FilterPolicy method*), 199, 715
 get_groups_by_domain() (*ActiveDirectory method*), 46, 562
 get_guest_location() (*GuestLocation method*), 202, 718
 get_guest_location_by_id() (*GuestLocation method*), 201, 717

`get_guest_location_generator()` (*GuestLocation method*), 203, 719
`get_guest_smtp_notification_settings()` (*GuestSmtpNotificationConfiguration method*), 206, 722
`get_guest_smtp_notification_settings_by_id()` (*GuestSmtpNotificationConfiguration method*), 204, 721
`get_guest_smtp_notification_settings_generator()` (*GuestSmtpNotificationConfiguration method*), 207, 723
`get_guest_ssid()` (*GuestSsid method*), 212, 728
`get_guest_ssid_by_id()` (*GuestSsid method*), 210, 726
`get_guest_ssid_generator()` (*GuestSsid method*), 213, 729
`get_guest_type()` (*GuestType method*), 218, 735
`get_guest_type_by_id()` (*GuestType method*), 216, 733
`get_guest_type_generator()` (*GuestType method*), 219, 736
`get_guest_user_by_id()` (*GuestUser method*), 229, 746
`get_guest_user_by_name()` (*GuestUser method*), 224, 740
`get_guest_users()` (*GuestUser method*), 232, 748
`get_guest_users_generator()` (*GuestUser method*), 233, 749
`get_healths()` (*SystemHealth method*), 496, 1012
`get_hotspot_portal()` (*HotspotPortal method*), 239, 755
`get_hotspot_portal_by_id()` (*HotspotPortal method*), 237, 753
`get_hotspot_portal_generator()` (*HotspotPortal method*), 240, 756
`get_identity_group_by_id()` (*IdentityGroups method*), 260, 776
`get_identity_group_by_name()` (*IdentityGroups method*), 259, 776
`get_identity_groups()` (*IdentityGroups method*), 261, 777
`get_identity_groups_generator()` (*IdentityGroups method*), 262, 778
`get_identity_sequence()` (*IdentitySequence method*), 267, 783
`get_identity_sequence_by_id()` (*IdentitySequence method*), 265, 781
`get_identity_sequence_by_name()` (*IdentitySequence method*), 264, 781
`get_identity_sequence_generator()` (*IdentitySequence method*), 267, 784
`get_internal_user()` (*InternalUser method*), 274, 791
`get_internal_user_by_id()` (*InternalUser method*), 272, 788
`get_internal_user_by_name()` (*InternalUser method*), 270, 786
`get_internal_user_generator()` (*InternalUser method*), 275, 792
`get_ip_to_sgt_mapping()` (*IpToSgtMapping method*), 246, 763
`get_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping method*), 244, 761
`get_ip_to_sgt_mapping_generator()` (*IpToSgtMapping method*), 247, 764
`get_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup method*), 254, 771
`get_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup method*), 253, 769
`get_ip_to_sgt_mapping_group_generator()` (*IpToSgtMappingGroup method*), 255, 772
`get_ise_version_and_patch()` (*VersionAndPatch method*), 525, 1041
`get_last_config_backup_status()` (*BackupAndRestore method*), 83, 599
`get_last_status()` (*BackupAndRestore method*), 84, 599
`get_mnt_version()` (*Misc method*), 286, 802
`get_my_device_portal()` (*MyDevicePortal method*), 291, 808
`get_my_device_portal_by_id()` (*MyDevicePortal method*), 289, 806
`get_my_device_portal_generator()` (*MyDevicePortal method*), 292, 809
`get_native_suppllicant_profile()` (*NativeSuppllicantProfile method*), 296, 813
`get_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile method*), 295, 811
`get_native_suppllicant_profile_generator()` (*NativeSuppllicantProfile method*), 297, 814
`get_nbar_app_by_id()` (*NbarApp method*), 1056
`get_nbar_apps()` (*NbarApp method*), 1053
`get_nbar_apps_generator()` (*NbarApp method*), 1054
`get_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules method*), 301, 817
`get_network_access_authentication_rules()` (*NetworkAccessAuthenticationRules method*), 298, 815
`get_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules method*), 313, 830
`get_network_access_authorization_rules()` (*NetworkAccessAuthorizationRules method*), 311, 828
`get_network_access_condition_by_id()` (*NetworkAccessConditions method*), 323, 839
`get_network_access_condition_by_name()` (*Net-*

`workAccessConditions method`), 319, 836
`get_network_access_conditions()` (*NetworkAccessConditions method*), 316, 832
`get_network_access_conditions_for_authentication_rules()` (*NetworkAccessConditions method*), 318, 835
`get_network_access_conditions_for_authorization_rules()` (*NetworkAccessConditions method*), 319, 835
`get_network_access_conditions_for_policy_sets()` (*NetworkAccessConditions method*), 322, 839
`get_network_access_dictionaries()` (*NetworkAccessDictionary method*), 326, 842
`get_network_access_dictionaries_authentication_attributes()` (*NetworkAccessDictionaryAttributesList method*), 334, 850
`get_network_access_dictionaries_authorization_attributes()` (*NetworkAccessDictionaryAttributesList method*), 334, 851
`get_network_access_dictionaries_policy_set()` (*NetworkAccessDictionaryAttributesList method*), 335, 851
`get_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute method*), 331, 848
`get_network_access_dictionary_attributes_by_name()` (*NetworkAccessDictionaryAttribute method*), 330, 846
`get_network_access_dictionary_by_name()` (*NetworkAccessDictionary method*), 328, 844
`get_network_access_identity_stores()` (*NetworkAccessIdentityStores method*), 336, 852
`get_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 305, 822
`get_network_access_local_exception_rules()` (*NetworkAccessAuthorizationExceptionRules method*), 303, 820
`get_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions method*), 338, 854
`get_network_access_network_conditions()` (*NetworkAccessNetworkConditions method*), 336, 853
`get_network_access_policy_set_by_id()` (*NetworkAccessPolicySet method*), 342, 858
`get_network_access_policy_set_global_exception_rules()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 309, 826
`get_network_access_policy_set_global_exception_rules()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 307, 824
`get_network_access_policy_sets()` (*NetworkAccessPolicySet method*), 340, 856
`get_network_access_profiles()` (*NetworkAccessProfiles method*), 345, 861
`get_network_access_security_groups()` (*NetworkAccessSecurityGroups method*), 345, 862
`get_network_access_service_names()` (*NetworkAccessServiceNames method*), 346, 862
`get_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions method*), 349, 865
`get_network_access_time_conditions()` (*NetworkAccessTimeDateConditions method*), 347, 863
`get_network_device()` (*NetworkDevice method*), 357, 873
`get_network_device_by_id()` (*NetworkDevice method*), 355, 871
`get_network_device_by_name()` (*NetworkDevice method*), 353, 869
`get_network_device_generator()` (*NetworkDevice method*), 358, 874
`get_network_device_group()` (*NetworkDeviceGroup method*), 365, 881
`get_network_device_group_by_id()` (*NetworkDeviceGroup method*), 363, 879
`get_network_device_group_by_name()` (*NetworkDeviceGroup method*), 362, 878
`get_network_device_group_generator()` (*NetworkDeviceGroup method*), 366, 882
`get_node_detail_by_id()` (*NodeDetails method*), 375, 891
`get_node_detail_by_name()` (*NodeDetails method*), 375, 891
`get_node_details()` (*NodeDeployment method*), 370, 886
`get_node_details()` (*NodeDetails method*), 376, 892
`get_node_details_generator()` (*NodeDetails method*), 377, 893
`get_node_group()` (*NodeGroup method*), 372, 888
`get_node_groups()` (*NodeGroup method*), 372, 888
`get_node_replication_status()` (*ReplicationStatus method*), 415, 931
`get_nodes()` (*NodeDeployment method*), 368, 884
`get_pan_ha_status()` (*PanHa method*), 379, 895
`get_performances()` (*SystemHealth method*), 497, 1012
`get_portal_global_setting_by_id()` (*PortalGlobalSetting method*), 381, 897
`get_portal_global_settings()` (*PortalGlobalSetting method*), 382, 898
`get_portal_global_settings_generator()` (*PortalGlobalSetting method*), 383, 899
`get_portal_theme_by_id()` (*PortalTheme method*), 385, 901
`get_portal_themes()` (*PortalTheme method*), 386, 902

[get_portal_themes_generator\(\)](#) (*PortalTheme method*), 387, 903
[get_portals\(\)](#) (*Portal method*), 538, 1058
[get_portals_generator\(\)](#) (*Portal method*), 539, 1059
[get_posture_count\(\)](#) (*Misc method*), 282, 798
[get_profiler_count\(\)](#) (*Misc method*), 282, 799
[get_profiler_profile_by_id\(\)](#) (*ProfilerProfile method*), 391, 907
[get_profiler_profiles\(\)](#) (*ProfilerProfile method*), 391, 907
[get_profiler_profiles_generator\(\)](#) (*ProfilerProfile method*), 392, 908
[get_profiles\(\)](#) (*Profiler method*), 390, 906
[get_px_grid_node\(\)](#) (*PxGridNode method*), 543, 1063
[get_px_grid_node_by_id\(\)](#) (*PxGridNode method*), 542, 1062
[get_px_grid_node_by_name\(\)](#) (*PxGridNode method*), 541, 1061
[get_px_grid_node_generator\(\)](#) (*PxGridNode method*), 543, 1064
[get_radius_server_sequence\(\)](#) (*RadiusServerSequence method*), 405, 921
[get_radius_server_sequence_by_id\(\)](#) (*RadiusServerSequence method*), 402, 918
[get_radius_server_sequence_generator\(\)](#) (*RadiusServerSequence method*), 405, 921
[get_rejected\(\)](#) (*Endpoint method*), 528, 1044
[get_rejected_endpoints\(\)](#) (*Endpoint method*), 528, 1043
[get_repositories\(\)](#) (*Repository method*), 416, 932
[get_repository\(\)](#) (*Repository method*), 417, 933
[get_repository_files\(\)](#) (*Repository method*), 419, 935
[get_rest_id_store\(\)](#) (*RestidStore method*), 412, 928
[get_rest_id_store_by_id\(\)](#) (*RestidStore method*), 410, 926
[get_rest_id_store_by_name\(\)](#) (*RestidStore method*), 408, 924
[get_rest_id_store_generator\(\)](#) (*RestidStore method*), 413, 929
[get_security_group_acls\(\)](#) (*TrustSecConfiguration method*), 523, 1039
[get_security_group_by_id\(\)](#) (*SecurityGroups method*), 448, 964
[get_security_groups\(\)](#) (*SecurityGroups method*), 450, 966
[get_security_groups\(\)](#) (*TrustSecConfiguration method*), 523, 1038
[get_security_groups_acl\(\)](#) (*SecurityGroupsAcls method*), 457, 973
[get_security_groups_acl_by_id\(\)](#) (*SecurityGroupsAcls method*), 455, 971
[get_security_groups_acl_generator\(\)](#) (*SecurityGroupsAcls method*), 458, 974
[get_security_groups_generator\(\)](#) (*SecurityGroups method*), 451, 967
[get_security_groups_to_vn_to_vlan\(\)](#) (*SecurityGroupToVirtualNetwork method*), 444, 960
[get_security_groups_to_vn_to_vlan_by_id\(\)](#) (*SecurityGroupToVirtualNetwork method*), 442, 958
[get_security_groups_to_vn_to_vlan_generator\(\)](#) (*SecurityGroupToVirtualNetwork method*), 445, 960
[get_self_registered_portal_by_id\(\)](#) (*SelfRegisteredPortal method*), 462, 978
[get_self_registered_portals\(\)](#) (*SelfRegisteredPortal method*), 464, 980
[get_self_registered_portals_generator\(\)](#) (*SelfRegisteredPortal method*), 465, 981
[get_session_auth_list\(\)](#) (*Misc method*), 281, 798
[get_session_by_ip_address\(\)](#) (*SessionDirectory method*), 469, 984
[get_session_by_mac_address\(\)](#) (*SessionDirectory method*), 469, 985
[get_session_service_node\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 397, 913
[get_session_service_node_by_id\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 397, 913
[get_session_service_node_by_name\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 396, 912
[get_session_service_node_generator\(\)](#) (*PsnNodeDetailsWithRadiusService method*), 398, 914
[get_sessions\(\)](#) (*SessionDirectory method*), 468, 983
[get_sessions_by_endpoint_ip\(\)](#) (*Misc method*), 284, 801
[get_sessions_by_mac\(\)](#) (*Misc method*), 283, 799
[get_sessions_by_nas_ip\(\)](#) (*Misc method*), 284, 800
[get_sessions_by_session_id\(\)](#) (*Misc method*), 285, 801
[get_sessions_by_username\(\)](#) (*Misc method*), 283, 800
[get_sessions_for_recovery\(\)](#) (*SessionDirectory method*), 468, 984
[get_sg_vn_mapping_by_id\(\)](#) (*SgVnMapping method*), 1069
[get_sg_vn_mappings\(\)](#) (*SgVnMapping method*), 1065
[get_sg_vn_mappings_generator\(\)](#) (*SgVnMapping method*), 1066
[get_sms_provider\(\)](#) (*SmsProvider method*), 420, 936
[get_sms_provider_generator\(\)](#) (*SmsProvider method*), 421, 937
[get_sponsor_group\(\)](#) (*SponsorGroup method*), 473, 988
[get_sponsor_group_by_id\(\)](#) (*SponsorGroup method*), 471, 986
[get_sponsor_group_generator\(\)](#) (*SponsorGroup method*), 471, 986

method), 474, 989

get_sponsor_group_member() (*SponsorGroupMember method*), 477, 992

get_sponsor_group_member_generator() (*SponsorGroupMember method*), 478, 993

get_sponsor_portal() (*SponsorPortal method*), 481, 997

get_sponsor_portal_by_id() (*SponsorPortal method*), 479, 995

get_sponsor_portal_generator() (*SponsorPortal method*), 482, 998

get_sponsored_guest_portal_by_id() (*SponsoredGuestPortal method*), 485, 1000

get_sponsored_guest_portals() (*SponsoredGuestPortal method*), 487, 1002

get_sponsored_guest_portals_generator() (*SponsoredGuestPortal method*), 488, 1003

get_support_bundle_status() (*SupportBundleStatus method*), 492, 1008

get_support_bundle_status_by_id() (*SupportBundleStatus method*), 492, 1007

get_support_bundle_status_generator() (*SupportBundleStatus method*), 493, 1008

get_sxp_connections() (*SxpConnections method*), 425, 940

get_sxp_connections_by_id() (*SxpConnections method*), 423, 938

get_sxp_connections_generator() (*SxpConnections method*), 426, 941

get_sxp_local_bindings() (*SxpLocalBindings method*), 431, 947

get_sxp_local_bindings_by_id() (*SxpLocalBindings method*), 429, 945

get_sxp_local_bindings_generator() (*SxpLocalBindings method*), 432, 948

get_sxp_vpn_by_id() (*SxpVpns method*), 436, 952

get_sxp_vpns() (*SxpVpns method*), 437, 953

get_sxp_vpns_generator() (*SxpVpns method*), 438, 954

get_system_certificate_by_id() (*Certificates method*), 109, 625

get_system_certificates() (*Certificates method*), 107, 623

get_system_certificates_generator() (*Certificates method*), 108, 624

get_tacacs_command_sets() (*TacacsCommandSets method*), 501, 1016

get_tacacs_command_sets_by_id() (*TacacsCommandSets method*), 499, 1015

get_tacacs_command_sets_by_name() (*TacacsCommandSets method*), 499, 1014

get_tacacs_command_sets_generator() (*TacacsCommandSets method*), 502, 1017

get_tacacs_external_servers() (*TacacsExternalServers method*), 506, 1022

get_tacacs_external_servers_by_id() (*TacacsExternalServers method*), 504, 1020

get_tacacs_external_servers_by_name() (*TacacsExternalServers method*), 504, 1019

get_tacacs_external_servers_generator() (*TacacsExternalServers method*), 507, 1022

get_tacacs_profile() (*TacacsProfile method*), 511, 1027

get_tacacs_profile_by_id() (*TacacsProfile method*), 509, 1025

get_tacacs_profile_by_name() (*TacacsProfile method*), 509, 1024

get_tacacs_profile_generator() (*TacacsProfile method*), 512, 1027

get_tacacs_server_sequence() (*TacacsServerSequence method*), 517, 1032

get_tacacs_server_sequence_by_id() (*TacacsServerSequence method*), 514, 1030

get_tacacs_server_sequence_by_name() (*TacacsServerSequence method*), 514, 1029

get_tacacs_server_sequence_generator() (*TacacsServerSequence method*), 517, 1033

get_task_status() (*Tasks method*), 545, 1072

get_task_status_by_id() (*Tasks method*), 545, 1072

get_telemetry_info_by_id() (*TelemetryInformation method*), 520, 1035

get_telemetry_information() (*TelemetryInformation method*), 520, 1036

get_telemetry_information_generator() (*TelemetryInformation method*), 521, 1036

get_trusted_certificate_by_id() (*Certificates method*), 116, 632

get_trusted_certificates() (*Certificates method*), 112, 628

get_trusted_certificates_generator() (*Certificates method*), 113, 629

get_trusted_domains() (*ActiveDirectory method*), 45, 560

get_user_group_by_user_name() (*SessionDirectory method*), 470, 986

get_user_groups() (*ActiveDirectory method*), 42, 557

get_user_groups() (*SessionDirectory method*), 470, 985

get_version() (*AciBindings method*), 32, 547

get_version() (*AciSettings method*), 35, 551

get_version() (*ActiveDirectory method*), 51, 566

get_version() (*AdminUser method*), 54, 570

get_version() (*AllowedProtocols method*), 61, 577

get_version() (*AncEndpoint method*), 40, 555

get_version() (*AncPolicy method*), 67, 583

get_version() (*AuthorizationProfile method*), 76, 591

get_version() (*ByodPortal method*), 81, 597

get_version() (*CertificateProfile method*), 92, 608

- `get_version()` (*CertificateTemplate method*), 95, 611
`get_version()` (*ClearThreatsAndVulnerabilities method*), 120, 637
`get_version()` (*DownloadableAcl method*), 174, 690
`get_version()` (*EgressMatrixCell method*), 181, 697
`get_version()` (*Endpoint method*), 536, 1051
`get_version()` (*EndpointCertificate method*), 184, 700
`get_version()` (*EndpointIdentityGroup method*), 189, 706
`get_version()` (*ExternalRadiusServer method*), 196, 712
`get_version()` (*FilterPolicy method*), 200, 717
`get_version()` (*GuestLocation method*), 204, 720
`get_version()` (*GuestSntpNotificationConfiguration method*), 209, 726
`get_version()` (*GuestSsid method*), 214, 731
`get_version()` (*GuestType method*), 221, 738
`get_version()` (*GuestUser method*), 235, 752
`get_version()` (*HotspotPortal method*), 242, 758
`get_version()` (*IdentityGroups method*), 264, 780
`get_version()` (*IdentitySequence method*), 269, 785
`get_version()` (*InternalUser method*), 277, 794
`get_version()` (*IpToSgtMapping method*), 249, 766
`get_version()` (*IpToSgtMappingGroup method*), 257, 774
`get_version()` (*MyDevicePortal method*), 294, 811
`get_version()` (*NativeSupplicantProfile method*), 298, 814
`get_version()` (*NetworkDevice method*), 360, 876
`get_version()` (*NetworkDeviceGroup method*), 367, 883
`get_version()` (*NodeDetails method*), 378, 894
`get_version()` (*Portal method*), 540, 1060
`get_version()` (*PortalGlobalSetting method*), 384, 900
`get_version()` (*PortalTheme method*), 389, 905
`get_version()` (*ProfilerProfile method*), 393, 909
`get_version()` (*PsnNodeDetailsWithRadiusService method*), 398, 914
`get_version()` (*PullDeploymentInfo method*), 399, 915
`get_version()` (*PxGridNode method*), 544, 1064
`get_version()` (*PxGridSettings method*), 401, 917
`get_version()` (*RadiusServerSequence method*), 407, 923
`get_version()` (*RestidStore method*), 414, 930
`get_version()` (*SecurityGroups method*), 453, 969
`get_version()` (*SecurityGroupsAcls method*), 460, 976
`get_version()` (*SecurityGroupToVirtualNetwork method*), 447, 962
`get_version()` (*SelfRegisteredPortal method*), 467, 983
`get_version()` (*SmsProvider method*), 422, 938
`get_version()` (*SponsoredGuestPortal method*), 490, 1005
`get_version()` (*SponsorGroup method*), 476, 991
`get_version()` (*SponsorGroupMember method*), 479, 994
`get_version()` (*SponsorPortal method*), 484, 1000
`get_version()` (*SupportBundleDownload method*), 491, 1006
`get_version()` (*SupportBundleStatus method*), 493, 1009
`get_version()` (*SupportBundleTriggerConfiguration method*), 495, 1010
`get_version()` (*SxpConnections method*), 427, 943
`get_version()` (*SxpLocalBindings method*), 434, 950
`get_version()` (*SxpVpns method*), 440, 956
`get_version()` (*SystemCertificate method*), 498, 1013
`get_version()` (*TacacsCommandSets method*), 503, 1018
`get_version()` (*TacacsExternalServers method*), 508, 1024
`get_version()` (*TacacsProfile method*), 513, 1029
`get_version()` (*TacacsServerSequence method*), 519, 1034
`get_version()` (*TelemetryInformation method*), 522, 1037
`get_version_info()` (*VersionInfo method*), 526, 1042
`get_virtual_network_by_id()` (*VirtualNetwork method*), 1077
`get_virtual_networks()` (*VirtualNetwork method*), 1073
`get_virtual_networks_generator()` (*VirtualNetwork method*), 1074
`get_vn_vlan_mapping_by_id()` (*VnVlanMapping method*), 1084
`get_vn_vlan_mappings()` (*VnVlanMapping method*), 1079
`get_vn_vlan_mappings_generator()` (*VnVlanMapping method*), 1080
GuestLocation (class in *ciscoisesdk.api.v3_0_0.guest_location*), 201
GuestLocation (class in *ciscoisesdk.api.v3_1_0.guest_location*), 717
GuestSntpNotificationConfiguration (class in *ciscoisesdk.api.v3_0_0.guest_sntp_notification_configuration*), 204
GuestSntpNotificationConfiguration (class in *ciscoisesdk.api.v3_1_0.guest_sntp_notification_configuration*), 721
GuestSsid (class in *ciscoisesdk.api.v3_0_0.guest_ssid*), 210
GuestSsid (class in *ciscoisesdk.api.v3_1_0.guest_ssid*), 726
GuestType (class in *ciscoisesdk.api.v3_0_0.guest_type*), 215
GuestType (class in *ciscoisesdk.api.v3_1_0.guest_type*),

731
 GuestUser (class in *ciscoisesdk.api.v3_0_0.guest_user*),
 222
 GuestUser (class in *ciscoisesdk.api.v3_1_0.guest_user*),
 738

H

has_path() (*MyDict* method), 1086
 headers (*RestResponse* property), 1087
 HotspotPortal (class in *ciscoisesdk.api.v3_0_0.hotspot_portal*), 237
 HotspotPortal (class in *ciscoisesdk.api.v3_1_0.hotspot_portal*), 753

I

IdentityGroups (class in *ciscoisesdk.api.v3_0_0.identity_groups*), 259
 IdentityGroups (class in *ciscoisesdk.api.v3_1_0.identity_groups*), 776
 IdentitySequence (class in *ciscoisesdk.api.v3_0_0.identity_sequence*), 264
 IdentitySequence (class in *ciscoisesdk.api.v3_1_0.identity_sequence*), 781
 IdentityServicesEngineAPI (class in *ciscoisesdk*), 26
 import_system_certificate() (*Certificates* method), 105, 621
 import_trust_certificate() (*Certificates* method), 114, 630
 InternalUser (class in *ciscoisesdk.api.v3_0_0.internal_user*), 270
 InternalUser (class in *ciscoisesdk.api.v3_1_0.internal_user*), 786
 IpToSgtMapping (class in *ciscoisesdk.api.v3_0_0.ip_to_sgt_mapping*), 243
 IpToSgtMapping (class in *ciscoisesdk.api.v3_1_0.ip_to_sgt_mapping*), 759
 IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_0_0.ip_to_sgt_mapping_group*), 251
 IpToSgtMappingGroup (class in *ciscoisesdk.api.v3_1_0.ip_to_sgt_mapping_group*), 768
 is_user_member_of_groups() (*ActiveDirectory* method), 44, 560

J

join_domain() (*ActiveDirectory* method), 48, 564
 join_domain_with_all_nodes() (*ActiveDirectory* method), 45, 561

L

leave_domain() (*ActiveDirectory* method), 43, 559

leave_domain_with_all_nodes() (*ActiveDirectory* method), 46, 561
 load_groups_from_domain() (*ActiveDirectory* method), 43, 558
 lookup_service() (*Consumer* method), 122, 639

M

MalformedRequest, 1088
 Mdm (class in *ciscoisesdk.api.v3_0_0.mdm*), 278
 Mdm (class in *ciscoisesdk.api.v3_1_0.mdm*), 795
 message (*ApiError* attribute), 1087
 Misc (class in *ciscoisesdk.api.v3_0_0.misc*), 280
 Misc (class in *ciscoisesdk.api.v3_1_0.misc*), 797
 mnt_base_url (*IdentityServicesEngineAPI* property), 28
 MNT_BASE_URL_ENVIRONMENT_VARIABLE (in module *ciscoisesdk.config*), 12
 module
 ciscoisesdk.config, 12
 monitor_bulk_status() (*AncEndpoint* method), 41, 557
 monitor_bulk_status() (*AncPolicy* method), 69, 585
 monitor_bulk_status() (*EgressMatrixCell* method), 183, 699
 monitor_bulk_status() (*Endpoint* method), 537, 1053
 monitor_bulk_status() (*GuestUser* method), 237, 753
 monitor_bulk_status() (*IpToSgtMapping* method), 251, 767
 monitor_bulk_status() (*IpToSgtMappingGroup* method), 259, 775
 monitor_bulk_status() (*NetworkDevice* method), 362, 878
 monitor_bulk_status() (*SecurityGroups* method), 455, 971
 monitor_bulk_status() (*SecurityGroupsAcls* method), 462, 978
 monitor_bulk_status() (*SecurityGroupToVirtualNetwork* method), 448, 964
 monitor_bulk_status() (*SxpConnections* method), 429, 945
 monitor_bulk_status() (*SxpLocalBindings* method), 436, 952
 monitor_bulk_status() (*SxpVpns* method), 442, 957
 monitor_bulk_status_anc_endpoint() (*AncEndpoint* method), 41, 556
 monitor_bulk_status_anc_policy() (*AncPolicy* method), 68, 584
 monitor_bulk_status_egress_matrix_cell() (*EgressMatrixCell* method), 182, 699
 monitor_bulk_status_endpoint() (*Endpoint* method), 537, 1052
 monitor_bulk_status_guest_user() (*GuestUser* method), 236, 753

`monitor_bulk_status_ip_to_sgt_mapping()` (*IpToSgtMapping* method), 250, 767
`monitor_bulk_status_ip_to_sgt_mapping_group()` (*IpToSgtMappingGroup* method), 258, 775
`monitor_bulk_status_network_device()` (*NetworkDevice* method), 362, 878
`monitor_bulk_status_security_group()` (*SecurityGroups* method), 454, 970
`monitor_bulk_status_security_groups_acl()` (*SecurityGroupsAcls* method), 461, 977
`monitor_bulk_status_security_groups_to_vn_to_vlans()` (*SecurityGroupToVirtualNetwork* method), 448, 963
`monitor_bulk_status_sxp_connections()` (*SxpConnections* method), 429, 945
`monitor_bulk_status_sxp_local_bindings()` (*SxpLocalBindings* method), 436, 951
`monitor_bulk_status_sxp_vpns()` (*SxpVpns* method), 441, 957
`MyDevicePortal` (class in *ciscoisesdk.api.v3_0_0.my_device_portal*), 289
`MyDevicePortal` (class in *ciscoisesdk.api.v3_1_0.my_device_portal*), 806
`MyDict` (class in *ciscoisesdk.models.mydict*), 1086

N

`NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_0_0.native_supplicant_profile*), 295
`NativeSupplicantProfile` (class in *ciscoisesdk.api.v3_1_0.native_supplicant_profile*), 811
`NbarApp` (class in *ciscoisesdk.api.v3_1_0.nbar_app*), 1053
`NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_0_0.network_access_authentication_rules*), 298
`NetworkAccessAuthenticationRules` (class in *ciscoisesdk.api.v3_1_0.network_access_authentication_rules*), 815
`NetworkAccessAuthorizationExceptionRules` (class in *ciscoisesdk.api.v3_0_0.network_access_authorization_exception_rules*), 303
`NetworkAccessAuthorizationExceptionRules` (class in *ciscoisesdk.api.v3_1_0.network_access_authorization_exception_rules*), 820
`NetworkAccessAuthorizationGlobalExceptionRules` (class in *ciscoisesdk.api.v3_0_0.network_access_authorization_global_exception_rules*), 307
`NetworkAccessAuthorizationGlobalExceptionRules` (class in *ciscoisesdk.api.v3_1_0.network_access_authorization_global_exception_rules*), 824
`NetworkAccessAuthorizationRules` (class in *ciscoisesdk.api.v3_0_0.network_access_authorization_rules*), 311
`NetworkAccessAuthorizationRules` (class in *ciscoisesdk.api.v3_1_0.network_access_authorization_rules*), 828
`NetworkAccessConditions` (class in *ciscoisesdk.api.v3_0_0.network_access_conditions*), 316
`NetworkAccessConditions` (class in *ciscoisesdk.api.v3_1_0.network_access_conditions*), 832
`NetworkAccessDictionary` (class in *ciscoisesdk.api.v3_0_0.network_access_dictionary*), 326
`NetworkAccessDictionary` (class in *ciscoisesdk.api.v3_1_0.network_access_dictionary*), 842
`NetworkAccessDictionaryAttribute` (class in *ciscoisesdk.api.v3_0_0.network_access_dictionary_attribute*), 330
`NetworkAccessDictionaryAttribute` (class in *ciscoisesdk.api.v3_1_0.network_access_dictionary_attribute*), 846
`NetworkAccessDictionaryAttributesList` (class in *ciscoisesdk.api.v3_0_0.network_access_dictionary_attributes_list*), 334
`NetworkAccessDictionaryAttributesList` (class in *ciscoisesdk.api.v3_1_0.network_access_dictionary_attributes_list*), 850
`NetworkAccessIdentityStores` (class in *ciscoisesdk.api.v3_0_0.network_access_identity_stores*), 336
`NetworkAccessIdentityStores` (class in *ciscoisesdk.api.v3_1_0.network_access_identity_stores*), 852
`NetworkAccessNetworkConditions` (class in *ciscoisesdk.api.v3_0_0.network_access_network_conditions*), 336
`NetworkAccessNetworkConditions` (class in *ciscoisesdk.api.v3_1_0.network_access_network_conditions*), 853
`NetworkAccessPolicySet` (class in *ciscoisesdk.api.v3_0_0.network_access_policy_set*), 340
`NetworkAccessPolicySet` (class in *ciscoisesdk.api.v3_1_0.network_access_policy_set*), 853

`esdk.api.v3_1_0.network_access_policy_set`), 856

`NetworkAccessProfiles` (class in `ciscoisesdk.api.v3_0_0.network_access_profiles`), 345

`NetworkAccessProfiles` (class in `ciscoisesdk.api.v3_1_0.network_access_profiles`), 861

`NetworkAccessSecurityGroups` (class in `ciscoisesdk.api.v3_0_0.network_access_security_groups`), 345

`NetworkAccessSecurityGroups` (class in `ciscoisesdk.api.v3_1_0.network_access_security_groups`), 862

`NetworkAccessServiceNames` (class in `ciscoisesdk.api.v3_0_0.network_access_service_names`), 346

`NetworkAccessServiceNames` (class in `ciscoisesdk.api.v3_1_0.network_access_service_names`), 862

`NetworkAccessTimeDateConditions` (class in `ciscoisesdk.api.v3_0_0.network_access_time_date_conditions`), 347

`NetworkAccessTimeDateConditions` (class in `ciscoisesdk.api.v3_1_0.network_access_time_date_conditions`), 863

`NetworkDevice` (class in `ciscoisesdk.api.v3_0_0.network_device`), 353

`NetworkDevice` (class in `ciscoisesdk.api.v3_1_0.network_device`), 869

`NetworkDeviceGroup` (class in `ciscoisesdk.api.v3_0_0.network_device_group`), 362

`NetworkDeviceGroup` (class in `ciscoisesdk.api.v3_1_0.network_device_group`), 878

`NodeDeployment` (class in `ciscoisesdk.api.v3_0_0.node_deployment`), 368

`NodeDeployment` (class in `ciscoisesdk.api.v3_1_0.node_deployment`), 884

`NodeDetails` (class in `ciscoisesdk.api.v3_0_0.node_details`), 375

`NodeDetails` (class in `ciscoisesdk.api.v3_1_0.node_details`), 891

`NodeGroup` (class in `ciscoisesdk.api.v3_0_0.node_group`), 372

`NodeGroup` (class in `ciscoisesdk.api.v3_1_0.node_group`), 888

`PanHa` (class in `ciscoisesdk.api.v3_1_0.pan_ha`), 895

`Portal` (class in `ciscoisesdk.api.v3_0_0.portal`), 537

`Portal` (class in `ciscoisesdk.api.v3_1_0.portal`), 1058

`PortalGlobalSetting` (class in `ciscoisesdk.api.v3_0_0.portal_global_setting`), 381

`PortalGlobalSetting` (class in `ciscoisesdk.api.v3_1_0.portal_global_setting`), 897

`PortalTheme` (class in `ciscoisesdk.api.v3_0_0.portal_theme`), 385

`PortalTheme` (class in `ciscoisesdk.api.v3_1_0.portal_theme`), 901

`Profiler` (class in `ciscoisesdk.api.v3_0_0.profiler`), 390

`Profiler` (class in `ciscoisesdk.api.v3_1_0.profiler`), 906

`ProfilerProfile` (class in `ciscoisesdk.api.v3_0_0.profiler_profile`), 391

`ProfilerProfile` (class in `ciscoisesdk.api.v3_1_0.profiler_profile`), 907

`promote_node()` (`NodeDeployment` method), 369, 885

`Provider` (class in `ciscoisesdk.api.v3_0_0.provider`), 394

`Provider` (class in `ciscoisesdk.api.v3_1_0.provider`), 910

`PsnNodeDetailsWithRadiusService` (class in `ciscoisesdk.api.v3_0_0.psn_node_details_with_radius_service`), 396

`PsnNodeDetailsWithRadiusService` (class in `ciscoisesdk.api.v3_1_0.psn_node_details_with_radius_service`), 912

`PullDeploymentInfo` (class in `ciscoisesdk.api.v3_0_0.pull_deployment_info`), 399

`PullDeploymentInfo` (class in `ciscoisesdk.api.v3_1_0.pull_deployment_info`), 915

`px_grid_base_url` (`IdentityServicesEngineAPI` property), 28

`PX_GRID_BASE_URL_ENVIRONMENT_VARIABLE` (in module `ciscoisesdk.config`), 12

`PxGridNode` (class in `ciscoisesdk.api.v3_0_0.px_grid_node`), 541

`PxGridNode` (class in `ciscoisesdk.api.v3_1_0.px_grid_node`), 1061

`PxGridSettings` (class in `ciscoisesdk.api.v3_0_0.px_grid_settings`), 400

`PxGridSettings` (class in `ciscoisesdk.api.v3_1_0.px_grid_settings`), 916

R

`RadiusFailure` (class in `ciscoisesdk.api.v3_0_0.radius_failure`), 401

`RadiusFailure` (class in `ciscoisesdk.api.v3_1_0.radius_failure`), 917

`RadiusServerSequence` (class in `ciscoisesdk.api.v3_0_0.radius_server_sequence`),

O

`original_error` (`DownloadFailure` attribute), 1088

P

`PanHa` (class in `ciscoisesdk.api.v3_0_0.pan_ha`), 379

- 402
- RadiusServerSequence (class in *ciscoisesdk.api.v3_1_0.radius_server_sequence*), 918
- RateLimitError, 1088
- RateLimitWarning, 1088
- raw (*DownloadFailure* attribute), 1088
- regenerate_ise_root_ca() (*Certificates* method), 101, 617
- register() (*Endpoint* method), 532, 1048
- register_endpoint() (*Endpoint* method), 531, 1047
- register_node() (*NodeDeployment* method), 369, 885
- register_service() (*Provider* method), 394, 910
- reinstate_by_id() (*GuestUser* method), 227, 744
- reinstate_by_name() (*GuestUser* method), 224, 740
- reinstate_guest_user_by_id() (*GuestUser* method), 227, 743
- reinstate_guest_user_by_name() (*GuestUser* method), 224, 740
- release_rejected() (*Endpoint* method), 527, 1043
- release_rejected_endpoint() (*Endpoint* method), 527, 1042
- renew_certificates() (*Certificates* method), 102, 618
- ReplicationStatus (class in *ciscoisesdk.api.v3_0_0.replication_status*), 415
- ReplicationStatus (class in *ciscoisesdk.api.v3_1_0.replication_status*), 931
- Repository (class in *ciscoisesdk.api.v3_0_0.repository*), 416
- Repository (class in *ciscoisesdk.api.v3_1_0.repository*), 932
- request (*ApiError* attribute), 1087
- request (*DownloadFailure* attribute), 1088
- reregister_service() (*Provider* method), 395, 911
- reset_guest_user_password_by_id() (*GuestUser* method), 226, 743
- reset_hit_counts() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 134, 651
- reset_hit_counts() (*DeviceAdministrationPolicySet* method), 160, 676
- reset_hit_counts() (*NetworkAccessAuthorizationGlobalExceptionRules* method), 309, 826
- reset_hit_counts() (*NetworkAccessPolicySet* method), 342, 858
- reset_hit_counts_by_id() (*DeviceAdministrationAuthenticationRules* method), 126, 642
- reset_hit_counts_by_id() (*DeviceAdministrationAuthorizationExceptionRules* method), 130, 647
- reset_hit_counts_by_id() (*DeviceAdministrationAuthorizationRules* method), 138, 655
- reset_hit_counts_by_id() (*NetworkAccessAuthenticationRules* method), 300, 817
- reset_hit_counts_by_id() (*NetworkAccessAutho-*
rizationExceptionRules method), 305, 822
- reset_hit_counts_by_id() (*NetworkAccessAutho-*
rizationRules method), 313, 830
- reset_hit_counts_device_admin_authentication_rules() (*DeviceAdministrationAuthenticationRules* method), 125, 642
- reset_hit_counts_device_admin_authorization_rules() (*DeviceAdministrationAuthorizationRules* method), 138, 654
- reset_hit_counts_device_admin_global_exceptions() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 134, 650
- reset_hit_counts_device_admin_local_exceptions() (*DeviceAdministrationAuthorizationExceptionRules* method), 130, 646
- reset_hit_counts_device_admin_policy_sets() (*DeviceAdministrationPolicySet* method), 159, 676
- reset_hit_counts_network_access_authentication_rules() (*NetworkAccessAuthenticationRules* method), 300, 817
- reset_hit_counts_network_access_authorization_rules() (*NetworkAccessAuthorizationRules* method), 313, 829
- reset_hit_counts_network_access_global_exceptions() (*NetworkAccessAuthorizationGlobalExceptionRules* method), 309, 825
- reset_hit_counts_network_access_local_exceptions() (*NetworkAccessAuthorizationExceptionRules* method), 304, 821
- reset_hit_counts_network_access_policy_sets() (*NetworkAccessPolicySet* method), 342, 858
- reset_password_by_id() (*GuestUser* method), 227, 743
- response (*ApiError* attribute), 1087
- response (*DownloadFailure* attribute), 1088
- response (*RestResponse* property), 1087
- RestidStore (class in *ciscoisesdk.api.v3_0_0.restid_store*), 408
- RestidStore (class in *ciscoisesdk.api.v3_1_0.restid_store*), 924
- restore() (*BackupAndRestore* method), 84, 600
- restore_config_backup() (*BackupAndRestore* method), 84, 599
- RestResponse (class in *ciscoisesdk.restresponse*), 1087
- retry_after (*RateLimitError* attribute), 1088
- retry_after (*RateLimitWarning* attribute), 1088
- ## S
- SecurityGroups (class in *ciscoisesdk.api.v3_0_0.security_groups*), 448
- SecurityGroups (class in *ciscoisesdk.api.v3_1_0.security_groups*), 964

- SecurityGroupsAcls (class in *ciscoisesdk.api.v3_0_0.security_groups_acls*), 455
- SecurityGroupsAcls (class in *ciscoisesdk.api.v3_1_0.security_groups_acls*), 971
- SecurityGroupToVirtualNetwork (class in *ciscoisesdk.api.v3_0_0.security_group_to_virtual_network*), 442
- SecurityGroupToVirtualNetwork (class in *ciscoisesdk.api.v3_1_0.security_group_to_virtual_network*), 958
- SelfRegisteredPortal (class in *ciscoisesdk.api.v3_0_0.self_registered_portal*), 462
- SelfRegisteredPortal (class in *ciscoisesdk.api.v3_1_0.self_registered_portal*), 978
- session (*IdentityServicesEngineAPI* property), 27
- session_disconnect() (*Misc* method), 288, 804
- session_ers (*IdentityServicesEngineAPI* property), 28
- session_mnt (*IdentityServicesEngineAPI* property), 28
- session_px_grid (*IdentityServicesEngineAPI* property), 28
- session_reauthentication_by_mac() (*Misc* method), 287, 804
- session_ui (*IdentityServicesEngineAPI* property), 27
- SessionDirectory (class in *ciscoisesdk.api.v3_0_0.session_directory*), 468
- SessionDirectory (class in *ciscoisesdk.api.v3_1_0.session_directory*), 983
- set_all_cells_status() (*EgressMatrixCell* method), 175, 691
- set_status() (*EgressMatrixCell* method), 175, 692
- SgVnMapping (class in *ciscoisesdk.api.v3_1_0.sg_vn_mapping*), 1065
- single_request_timeout (*Authentication* property), 28
- single_request_timeout (*IdentityServicesEngineAPI* property), 28
- SmsProvider (class in *ciscoisesdk.api.v3_0_0.sms_provider*), 420
- SmsProvider (class in *ciscoisesdk.api.v3_1_0.sms_provider*), 936
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_0_0.sponsored_guest_portal*), 485
- SponsoredGuestPortal (class in *ciscoisesdk.api.v3_1_0.sponsored_guest_portal*), 1000
- SponsorGroup (class in *ciscoisesdk.api.v3_0_0.sponsor_group*), 471
- SponsorGroup (class in *ciscoisesdk.api.v3_1_0.sponsor_group*), 986
- SponsorGroupMember (class in *ciscoisesdk.api.v3_0_0.sponsor_group_member*), 477
- SponsorGroupMember (class in *ciscoisesdk.api.v3_1_0.sponsor_group_member*), 992
- SponsorPortal (class in *ciscoisesdk.api.v3_0_0.sponsor_portal*), 479
- SponsorPortal (class in *ciscoisesdk.api.v3_1_0.sponsor_portal*), 995
- status (*ApiError* attribute), 1087
- status (*DownloadFailure* attribute), 1088
- status_code (*ApiError* attribute), 1087
- status_code (*DownloadFailure* attribute), 1088
- SupportBundleDownload (class in *ciscoisesdk.api.v3_0_0.support_bundle_download*), 490
- SupportBundleDownload (class in *ciscoisesdk.api.v3_1_0.support_bundle_download*), 1006
- SupportBundleStatus (class in *ciscoisesdk.api.v3_0_0.support_bundle_status*), 492
- SupportBundleStatus (class in *ciscoisesdk.api.v3_1_0.support_bundle_status*), 1007
- SupportBundleTriggerConfiguration (class in *ciscoisesdk.api.v3_0_0.support_bundle_trigger_configuration*), 494
- SupportBundleTriggerConfiguration (class in *ciscoisesdk.api.v3_1_0.support_bundle_trigger_configuration*), 1009
- suspend_by_id() (*GuestUser* method), 235, 751
- suspend_by_name() (*GuestUser* method), 224, 740
- suspend_guest_user_by_id() (*GuestUser* method), 235, 751
- suspend_guest_user_by_name() (*GuestUser* method), 223, 739
- SxpConnections (class in *ciscoisesdk.api.v3_0_0.sxp_connections*), 423
- SxpConnections (class in *ciscoisesdk.api.v3_1_0.sxp_connections*), 938
- SxpLocalBindings (class in *ciscoisesdk.api.v3_0_0.sxp_local_bindings*), 429
- SxpLocalBindings (class in *ciscoisesdk.api.v3_1_0.sxp_local_bindings*), 945
- SxpVpns (class in *ciscoisesdk.api.v3_0_0.sxp_vpns*), 436
- SxpVpns (class in *ciscoisesdk.api.v3_1_0.sxp_vpns*), 952
- sync_node() (*SyncIseNode* method), 495, 1011
- SyncIseNode (class in *ciscoisesdk.api.v3_0_0.sync_ise_node*), 495
- SyncIseNode (class in *ciscoisesdk.api.v3_1_0.sync_ise_node*), 1011
- SystemCertificate (class in *ciscoisesdk*), 1011

esdk.api.v3_0_0.system_certificate), 497
 SystemCertificate (class in *ciscoisesdk.api.v3_1_0.system_certificate*), 1013
 SystemHealth (class in *ciscoisesdk.api.v3_0_0.system_health*), 496
 SystemHealth (class in *ciscoisesdk.api.v3_1_0.system_health*), 1012

T

TacacsCommandSets (class in *ciscoisesdk.api.v3_0_0.tacacs_command_sets*), 499
 TacacsCommandSets (class in *ciscoisesdk.api.v3_1_0.tacacs_command_sets*), 1014
 TacacsExternalServers (class in *ciscoisesdk.api.v3_0_0.tacacs_external_servers*), 504
 TacacsExternalServers (class in *ciscoisesdk.api.v3_1_0.tacacs_external_servers*), 1019
 TacacsProfile (class in *ciscoisesdk.api.v3_0_0.tacacs_profile*), 509
 TacacsProfile (class in *ciscoisesdk.api.v3_1_0.tacacs_profile*), 1024
 TacacsServerSequence (class in *ciscoisesdk.api.v3_0_0.tacacs_server_sequence*), 514
 TacacsServerSequence (class in *ciscoisesdk.api.v3_1_0.tacacs_server_sequence*), 1029
 Tasks (class in *ciscoisesdk.api.v3_0_0.tasks*), 545
 Tasks (class in *ciscoisesdk.api.v3_1_0.tasks*), 1072
 TelemetryInformation (class in *ciscoisesdk.api.v3_0_0.telemetry_information*), 520
 TelemetryInformation (class in *ciscoisesdk.api.v3_1_0.telemetry_information*), 1035
 test_aci_connectivity() (*AciSettings* method), 33, 549
 text (*RestResponse* property), 1087
 to_json() (*MyDict* method), 1086
 TrustSecConfiguration (class in *ciscoisesdk.api.v3_0_0.trust_sec_configuration*), 523
 TrustSecConfiguration (class in *ciscoisesdk.api.v3_1_0.trust_sec_configuration*), 1038
 TrustSecSxp (class in *ciscoisesdk.api.v3_0_0.trust_sec_sxp*), 525
 TrustSecSxp (class in *ciscoisesdk.api.v3_1_0.trust_sec_sxp*), 1040

U

ui_base_url (*IdentityServicesEngineAPI* property), 28
 UI_BASE_URL_ENVIRONMENT_VARIABLE (in module *ciscoisesdk.config*), 12
 unregister_service() (*Provider* method), 394, 910
 update() (*BackupAndRestore* method), 86, 602
 update_aci_settings_by_id() (*AciSettings* method), 33, 549
 update_allowed_protocol_by_id() (*AllowedProtocols* method), 56, 571
 update_anc_policy_by_id() (*AncPolicy* method), 63, 579
 update_authorization_profile_by_id() (*AuthorizationProfile* method), 70, 586
 update_by_id() (*AciSettings* method), 35, 551
 update_by_id() (*AllowedProtocols* method), 58, 573
 update_by_id() (*AncPolicy* method), 64, 579
 update_by_id() (*AuthorizationProfile* method), 72, 587
 update_by_id() (*ByodPortal* method), 78, 593
 update_by_id() (*CertificateProfile* method), 90, 605
 update_by_id() (*DeviceAdministrationAuthenticationRules* method), 127, 644
 update_by_id() (*DeviceAdministrationAuthorizationExceptionRules* method), 131, 648
 update_by_id() (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 136, 652
 update_by_id() (*DeviceAdministrationAuthorizationRules* method), 140, 656
 update_by_id() (*DeviceAdministrationConditions* method), 151, 668
 update_by_id() (*DeviceAdministrationNetworkConditions* method), 157, 674
 update_by_id() (*DeviceAdministrationPolicySet* method), 162, 678
 update_by_id() (*DeviceAdministrationTimeDateConditions* method), 169, 685
 update_by_id() (*DownloadableAcl* method), 171, 687
 update_by_id() (*EgressMatrixCell* method), 177, 694
 update_by_id() (*Endpoint* method), 531, 1046
 update_by_id() (*EndpointIdentityGroup* method), 186, 703
 update_by_id() (*ExternalRadiusServer* method), 193, 709
 update_by_id() (*FilterPolicy* method), 198, 714
 update_by_id() (*GuestSmtNotificationConfiguration* method), 206, 722
 update_by_id() (*GuestSsid* method), 211, 728
 update_by_id() (*GuestType* method), 218, 734
 update_by_id() (*GuestUser* method), 231, 747
 update_by_id() (*HotspotPortal* method), 239, 755
 update_by_id() (*IdentityGroups* method), 261, 777
 update_by_id() (*IdentitySequence* method), 266, 783
 update_by_id() (*InternalUser* method), 274, 790
 update_by_id() (*IpToSgtMapping* method), 246, 762

`update_by_id()` (*IpToSgtMappingGroup* method), 254, 770

`update_by_id()` (*MyDevicePortal* method), 290, 807

`update_by_id()` (*NativeSupplicantProfile* method), 296, 812

`update_by_id()` (*NbarApp* method), 1057

`update_by_id()` (*NetworkAccessAuthenticationRules* method), 302, 819

`update_by_id()` (*NetworkAccessAuthorizationExceptionRules* method), 306, 823

`update_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules* method), 311, 827

`update_by_id()` (*NetworkAccessAuthorizationRules* method), 315, 831

`update_by_id()` (*NetworkAccessConditions* method), 325, 842

`update_by_id()` (*NetworkAccessNetworkConditions* method), 339, 855

`update_by_id()` (*NetworkAccessPolicySet* method), 344, 860

`update_by_id()` (*NetworkAccessTimeDateConditions* method), 352, 868

`update_by_id()` (*NetworkDevice* method), 357, 873

`update_by_id()` (*NetworkDeviceGroup* method), 364, 880

`update_by_id()` (*PortalGlobalSetting* method), 382, 898

`update_by_id()` (*PortalTheme* method), 386, 902

`update_by_id()` (*RadiusServerSequence* method), 404, 920

`update_by_id()` (*RestidStore* method), 411, 927

`update_by_id()` (*SecurityGroups* method), 450, 966

`update_by_id()` (*SecurityGroupsAcls* method), 457, 972

`update_by_id()` (*SecurityGroupToVirtualNetwork* method), 443, 959

`update_by_id()` (*SelfRegisteredPortal* method), 463, 979

`update_by_id()` (*SgVnMapping* method), 1071

`update_by_id()` (*SponsoredGuestPortal* method), 486, 1002

`update_by_id()` (*SponsorGroup* method), 472, 988

`update_by_id()` (*SponsorPortal* method), 481, 996

`update_by_id()` (*SxpConnections* method), 424, 940

`update_by_id()` (*SxpLocalBindings* method), 431, 947

`update_by_id()` (*TacacsCommandSets* method), 500, 1016

`update_by_id()` (*TacacsExternalServers* method), 506, 1021

`update_by_id()` (*TacacsProfile* method), 511, 1026

`update_by_id()` (*TacacsServerSequence* method), 516, 1032

`update_by_id()` (*VirtualNetwork* method), 1078

`update_by_name()` (*DeviceAdministrationConditions* method), 147, 664

`update_by_name()` (*GuestUser* method), 226, 742

`update_by_name()` (*InternalUser* method), 271, 788

`update_by_name()` (*NetworkAccessConditions* method), 322, 838

`update_by_name()` (*NetworkAccessDictionary* method), 329, 845

`update_by_name()` (*NetworkAccessDictionaryAttribute* method), 333, 849

`update_by_name()` (*NetworkDevice* method), 354, 870

`update_by_name()` (*Repository* method), 419, 934

`update_by_name()` (*RestidStore* method), 409, 925

`update_byod_portal_by_id()` (*ByodPortal* method), 77, 592

`update_certificate_profile_by_id()` (*CertificateProfile* method), 89, 604

`update_device_admin_authentication_rule_by_id()` (*DeviceAdministrationAuthenticationRules* method), 126, 643

`update_device_admin_authorization_rule_by_id()` (*DeviceAdministrationAuthorizationRules* method), 139, 656

`update_device_admin_condition_by_id()` (*DeviceAdministrationConditions* method), 149, 666

`update_device_admin_condition_by_name()` (*DeviceAdministrationConditions* method), 145, 662

`update_device_admin_local_exception_rule_by_id()` (*DeviceAdministrationAuthorizationExceptionRules* method), 131, 647

`update_device_admin_network_condition_by_id()` (*DeviceAdministrationNetworkConditions* method), 156, 673

`update_device_admin_policy_set_by_id()` (*DeviceAdministrationPolicySet* method), 161, 677

`update_device_admin_policy_set_global_exception_by_rule_id()` (*DeviceAdministrationAuthorizationGlobalExceptionRules* method), 135, 651

`update_device_admin_time_condition_by_id()` (*DeviceAdministrationTimeDateConditions* method), 167, 683

`update_downloadable_acl_by_id()` (*DownloadableAcl* method), 170, 686

`update_egress_matrix_cell_by_id()` (*EgressMatrixCell* method), 177, 693

`update_email()` (*GuestType* method), 216, 732

`update_email()` (*GuestUser* method), 228, 744

`update_endpoint_by_id()` (*Endpoint* method), 529, 1045

`update_endpoint_group_by_id()` (*EndpointIdentityGroup* method), 185, 702

`update_external_radius_server_by_id()` (*Exter-*

`nalRadiusServer method`), 191, 708
`update_filter_policy_by_id()` (*FilterPolicy method*), 197, 713
`update_guest_smtp_notification_settings_by_id()` (*GuestSmtpNotificationConfiguration method*), 205, 721
`update_guest_ssid_by_id()` (*GuestSsid method*), 211, 727
`update_guest_type_by_id()` (*GuestType method*), 217, 733
`update_guest_type_email()` (*GuestType method*), 215, 731
`update_guest_type_sms()` (*GuestType method*), 216, 732
`update_guest_user_by_id()` (*GuestUser method*), 230, 746
`update_guest_user_by_name()` (*GuestUser method*), 225, 741
`update_guest_user_email()` (*GuestUser method*), 228, 744
`update_guest_user_sms()` (*GuestUser method*), 228, 744
`update_hotspot_portal_by_id()` (*HotspotPortal method*), 238, 754
`update_identity_group_by_id()` (*IdentityGroups method*), 260, 777
`update_identity_sequence_by_id()` (*IdentitySequence method*), 265, 782
`update_internal_user_by_id()` (*InternalUser method*), 273, 789
`update_internal_user_by_name()` (*InternalUser method*), 270, 787
`update_ip_to_sgt_mapping_by_id()` (*IpToSgtMapping method*), 245, 761
`update_ip_to_sgt_mapping_group_by_id()` (*IpToSgtMappingGroup method*), 253, 770
`update_my_device_portal_by_id()` (*MyDevicePortal method*), 290, 806
`update_native_suppllicant_profile_by_id()` (*NativeSuppllicantProfile method*), 295, 812
`update_nbar_app_by_id()` (*NbarApp method*), 1056
`update_network_access_authentication_rule_by_id()` (*NetworkAccessAuthenticationRules method*), 301, 818
`update_network_access_authorization_rule_by_id()` (*NetworkAccessAuthorizationRules method*), 314, 831
`update_network_access_condition_by_id()` (*NetworkAccessConditions method*), 323, 840
`update_network_access_condition_by_name()` (*NetworkAccessConditions method*), 320, 836
`update_network_access_dictionary_attribute_by_name()` (*NetworkAccessDictionaryAttribute method*), 332, 848
`update_network_access_dictionary_by_name()` (*NetworkAccessDictionary method*), 328, 844
`update_network_access_local_exception_rule_by_id()` (*NetworkAccessAuthorizationExceptionRules method*), 306, 822
`update_network_access_network_condition_by_id()` (*NetworkAccessNetworkConditions method*), 338, 855
`update_network_access_policy_set_by_id()` (*NetworkAccessPolicySet method*), 343, 859
`update_network_access_policy_set_global_exception_rule_by_id()` (*NetworkAccessAuthorizationGlobalExceptionRules method*), 310, 826
`update_network_access_time_condition_by_id()` (*NetworkAccessTimeDateConditions method*), 350, 866
`update_network_device_by_id()` (*NetworkDevice method*), 356, 872
`update_network_device_by_name()` (*NetworkDevice method*), 353, 869
`update_network_device_group_by_id()` (*NetworkDeviceGroup method*), 363, 879
`update_node()` (*NodeDeployment method*), 370, 886
`update_node_group()` (*NodeGroup method*), 374, 890
`update_portal_global_setting_by_id()` (*PortalGlobalSetting method*), 381, 897
`update_portal_theme_by_id()` (*PortalTheme method*), 385, 901
`update_radius_server_sequence_by_id()` (*RadiusServerSequence method*), 403, 919
`update_repository()` (*Repository method*), 418, 934
`update_rest_id_store_by_id()` (*RestidStore method*), 410, 926
`update_rest_id_store_by_name()` (*RestidStore method*), 408, 924
`update_scheduled_config_backup()` (*BackupAndRestore method*), 85, 600
`update_security_group_by_id()` (*SecurityGroups method*), 449, 965
`update_security_groups_acl_by_id()` (*SecurityGroupsAcls method*), 456, 971
`update_security_groups_to_vn_to_vlan_by_id()` (*SecurityGroupToVirtualNetwork method*), 442, 958
`update_self_registered_portal_by_id()` (*SelfRegisteredPortal method*), 463, 978
`update_sg_vn_mapping_by_id()` (*SgVnMapping method*), 1070
`update_sms()` (*GuestType method*), 216, 733
`update_sms()` (*GuestUser method*), 229, 745
`update_sponsor_group_by_id()` (*SponsorGroup method*), 471, 987
`update_sponsor_portal_by_id()` (*SponsorPortal method*), 480, 995

`update_sponsored_guest_portal_by_id()` (*SponsoredGuestPortal method*), 485, 1001

`update_sxp_connections_by_id()` (*SxpConnections method*), 423, 939

`update_sxp_local_bindings_by_id()` (*SxpLocalBindings method*), 430, 946

`update_system_certificate()` (*Certificates method*), 109, 626

`update_tacacs_command_sets_by_id()` (*TacacsCommandSets method*), 500, 1015

`update_tacacs_external_servers_by_id()` (*TacacsExternalServers method*), 505, 1020

`update_tacacs_profile_by_id()` (*TacacsProfile method*), 510, 1025

`update_tacacs_server_sequence_by_id()` (*TacacsServerSequence method*), 515, 1030

`update_trusted_certificate()` (*Certificates method*), 116, 633

`update_virtual_network_by_id()` (*VirtualNetwork method*), 1078

`update_vn_vlan_mapping_by_id()` (*VnVlanMapping method*), 1084

`uses_api_gateway` (*IdentityServicesEngineAPI property*), 27

`USES_API_GATEWAY_ENVIRONMENT_VARIABLE` (*in module ciscoisesdk.config*), 12

V

`verify` (*Authentication property*), 28

`verify` (*IdentityServicesEngineAPI property*), 28

`version` (*IdentityServicesEngineAPI property*), 28

`VersionAndPatch` (*class in ciscoisesdk.api.v3_0_0.version_and_patch*), 525

`VersionAndPatch` (*class in ciscoisesdk.api.v3_1_0.version_and_patch*), 1041

`VersionError`, 1087

`VersionInfo` (*class in ciscoisesdk.api.v3_0_0.version_info*), 526

`VersionInfo` (*class in ciscoisesdk.api.v3_1_0.version_info*), 1042

`VirtualNetwork` (*class in ciscoisesdk.api.v3_1_0.virtual_network*), 1073

`VnVlanMapping` (*class in ciscoisesdk.api.v3_1_0.vn_vlan_mapping*), 1079

W

`wait_on_rate_limit` (*IdentityServicesEngineAPI property*), 28